

Cihan's Work

Cihan Sari¹, Albert Ali Salah², and Alkim Almila Akdag Salah³

¹System and Control Engineering,

² Department of Computer Engineering,

{cihan.sari, salah}@boun.edu.tr

³Royal Netherlands Academy of Arts and Sciences

a.a.akdag@uva.nl

Abstract. ?????????????????? ??? ???? ??? ????? ???? ??? ???? ??? ??
? ? ???? ????? ??? ?????????????????????? ??? ???? ??? ????? ???? ??? ????
??? ?? ? ? ???? ?????? ??? ?????????????????????? ??? ???? ??? ????? ????
??? ????? ??? ?? ? ? ???? ?????? ??? ...

Keywords: ?????????????????????? ??? ???? ??? ????? ???? ??? ???? ???
?? ? ? ???? ?????? ???

1 Introduction

Face detection has been a very interesting task for the society, culture, art, history, computer vision and machine learning.

2 Related Work

I **really** should categorize related works in these three: art-related, methodology related and face recognition related.

[1][2][3][4][5][6][7][8][9][10][11][12][13][14][15][16]

3 Methodology

3.1 Data Supervisor

In today's modern world, thanks to the computation power and the availability of Internet, there are thousands of databases available for a research scientist. However, vast majority of the databases have been gathered for a single purpose and marked as such. For example, Iris Flower Database[17]. It is a multivariate data set that contains sepal and petal dimensions (width and height) from Iris flowers of three related species. Another example, MNIST[18] is an image database of handwritten digits. It is gathered and tailored together to distinguish between different handwritten digits. These databases are currently used as benchmarking studies for machine learning algorithms. MNIST, along with ImageNet[8], is one of the most popular benchmark for C-NN implementations from different libraries and tool sets. At the end of the day, most of the databases have been gathered for specific purposes and does not (cannot) contain all the information regarding objects they contain.

Supervisor is developed to address this main issue. Data supervisor, as the name might suggest, attempts to annotate the database into categories given to the system via strings. In summary, the algorithm uses Google image search[6] to retrieve first hundred query results for the string, to understand the category. These supervised categorical data are then converted to information via C-NN[19] feature extraction. Therefore, system gains access to the supervised categorical information in C-NN feature space. Linear SVM model is trained to distinguish between the categorical information, using C-NN feature responses. Resulting svm model is then used over the unknown C-NN feature responses from the database to compute probability of each image belonging to each given string and sorted accordingly.

Supervisor is a software framework with roots in Matlab[20], MatConvNet[21], pre-trained C-NN model[19] (imagenet-vgg-f) on ImageNet[8] and Qt. Its purpose is to sort any given raw database of images into categories specified by the user inspired largely by In Search of Art by Zisserman[5].

An example of the data supervisor from Rijksmuseum[25] is given in 1. One of the main differences from Zisserman’s[5] implementation is that data supervisor does not have a predefined negative set. However, user can still add broad category names into the list for the sole purpose of concentrating the other categories (e.g. stuff, things, etc).




Fig. 1. Supervisor results on RijksMuseum

3.2 Face crop with FisherFaces in OpenCV

3.3 Face landmarks with Intraface

3.4 Face alignment and LBP features

3.5 Style Transfer

4 Rijksmuseum Art Database

4.1 Meta data and dates on Rijksmuseum

4.2 Face Crop on Rijksmuseum

5 Face image databases annotated with gender info

First step on preparing a gender recognition algorithm is to prepare annotated training data. In most cases, variety in the training set is directly proportional to the algorithm's success.

General info regarding crop, cleaning and if applicable, annotating will be here.

Each subsection should mention the value of databases and their unique characteristics for our study.

Importance of the annotation[10] should be remarked.

5.1 IMDB and Google Image results

To this end, 250 actor and 250 actress names from IMDB (Internet Movie DataBase) are used to collect male and female photos from Google Image results using part of the Database Sorter3.1. This method is inspired largely by Jia's work: Learning to classify gender from four million images [22].

For data preparation, Zhu framework[2] is used to locate the faces, find the landmarks and crop to face bounding box. Algorithm results are cleaned by hand for false positives (or reorganized in the case of wrong gender).

5.2 Labeled faces in the wild

LFW[23] face database is used to form another set of gender images. Similar to section 5.1, Viola-Jones algorithm is used for face crop.

LFW dataset, as provided, are not categorized by the gender but only the names of the celebrities. Therefore, genderize.io framework is used on the first names of the celebrities to determine their gender. Unfortunately, genderize predictions were not very satisfactory (a little above fifty per cent observed) and face crops are, again, reorganized by hand for wrong gender (and false positives).

5.3 10k US Adult Faces Database

10k adult faces[24] database contains more than ten thousand images, aligned and landmarked. This database contains neither gender information nor first names like LFW. Hence, first Viola-Jones, then hand organization is performed for labeling.

5.4 Rijkmuseum Art Database

Painting[25] image pieces hand-annotated into four sub-categories:

- Female (499)
- Male (1.006)
- Bad Face (11.030)
- Trash

Trash contains false positive face regions which are not actually face or are of very poor quality. Bad Face category consists of correct face regions that are poor quality, are not paintings - pieces from masks / statues etc., cartoons or any non-oil painting piece in general.

6 Whole Packages

6.1 Painting Recognizer on Google Images

Google image result collection similar to section 3.1 for portrait images over centuries. An example query in Figure 2.




Fig. 2. Google Image search results

Viola-Jones[26] face detection is used on the downloaded images for face detection. From the face bounding box, a vector is generated pointing downwards with a distance around one face height to pointing the clothing in the portrait.



Fig. 3. Painting Recognizer process

A small rectangle around the clothing is used for color analysis. Example image given in Figure 3.

RGB intensity values are then used to compute five dominant colors per 3 years window per gender using k-means (with $k = 5$). The representation of the data over time can be seen in Figure 4.

7 Conclusions




Fig. 4. Painting Recognizer results

References

1. van Noord, N., Hendriks, E., Postma, E.: Toward discovery of the artist's style: Learning to recognize artists by their artworks. *Signal Processing Magazine, IEEE* **32**(4) (2015) 46–54
2. Zhu, X., Ramanan, D.: Face detection, pose estimation, and landmark localization in the wild. In: *Computer Vision and Pattern Recognition (CVPR)*, 2012 IEEE Conference on, IEEE (2012) 2879–2886
3. Xiong, X., De la Torre, F.: Supervised descent method and its applications to face alignment. In: *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*. (2013)
4. Srinivasan, R., Rudolph, C., Roy-Chowdhury, A.K.: Computerized face recognition in renaissance portrait art: A quantitative measure for identifying uncertain subjects in ancient portraits. *Signal Processing Magazine, IEEE* **32**(4) (2015) 85–94
5. Crowley, E.J., Zisserman, A.: In search of art. In: *Workshop on Computer Vision for Art Analysis, ECCV*. (2014)
6. image search, G.: <http://www.google.com/images>
7. Everingham, M., Van Gool, L., Williams, C.K.I., Winn, J., Zisserman, A.: The PASCAL Visual Object Classes Challenge 2012 (VOC2012) Results. <http://www.pascal-network.org/challenges/VOC/voc2012/workshop/index.html>
8. Russakovsky, O., Deng, J., Su, H., Krause, J., Satheesh, S., Ma, S., Huang, Z., Karpathy, A., Khosla, A., Bernstein, M., Berg, A.C., Fei-Fei, L.: ImageNet Large Scale Visual Recognition Challenge. *International Journal of Computer Vision (IJCV)* **115**(3) (2015) 211–252
9. Agrawal, P., Girshick, R., Malik, J.: Analyzing the performance of multilayer neural networks for object recognition. In: *Computer Vision–ECCV 2014*. Springer (2014) 329–344
10. Mathias, M., Benenson, R., Pedersoli, M., Van Gool, L.: Face detection without bells and whistles. In: *Computer Vision–ECCV 2014*. Springer (2014) 720–735
11. Cheng, D.S., Setti, F., Zeni, N., Ferrario, R., Cristani, M.: Semantically-driven automatic creation of training sets for object recognition. *Computer Vision and Image Understanding* **131** (2015) 56–71
12. Lempitsky, V., Zisserman, A.: Learning to count objects in images. In: *Advances in Neural Information Processing Systems*. (2010) 1324–1332
13. Grosso, E., Lagorio, A., Pulina, L., Tistarelli, M.: Understanding critical factors in appearance-based gender categorization. In: *Computer Vision–ECCV 2012. Workshops and Demonstrations*, Springer (2012) 280–289
14. Ng, C.B., Tay, Y.H., Goi, B.M.: Recognizing human gender in computer vision: a survey. In: *PRICAI 2012: Trends in Artificial Intelligence*. Springer (2012) 335–346
15. Castrillón-Santana, M., Lorenzo-Navarro, J., Ramón-Balmaseda, E.: Improving gender classification accuracy in the wild. In: *Progress in Pattern Recognition, Image Analysis, Computer Vision, and Applications*. Springer (2013) 270–277
16. Zhao, M., Zhu, S.C.: Portrait painting using active templates. In: *NPAC '11: Proceedings of the ACM SIGGRAPH/Eurographics Symposium on Non-Photorealistic Animation and Rendering*, New York, NY, USA, ACM (2011) 117–124
17. Fisher, R.A.: The use of multiple measurements in taxonomic problems. *Annals of eugenics* **7**(2) (1936) 179–188
18. LeCun, Y., Cortes, C., Burges, C.J.: The mnist database of handwritten digits (1998)

19. Chatfield, K., Simonyan, K., Vedaldi, A., Zisserman, A.: Return of the devil in the details: Delving deep into convolutional nets. In: British Machine Vision Conference. (2014)
20. MATLAB: version 8.3.0 (R2014a). The MathWorks Inc., Natick, Massachusetts (2014)
21. Vedaldi, A., Lenc, K.: Matconvnet – convolutional neural networks for matlab
22. Jia, S., Cristianini, N.: Learning to classify gender from four million images. Pattern Recognition Letters **58** (2015) 35–41
23. Huang, G.B., Ramesh, M., Berg, T., Learned-Miller, E.: Labeled faces in the wild: A database for studying face recognition in unconstrained environments. Technical Report 07-49, University of Massachusetts, Amherst (October 2007)
24. Bainbridge, W.A., Isola, P., Oliva, A.: The intrinsic memorability of face photographs. Journal of Experimental Psychology: General **142**(4) (2013) 1323
25. (Netherlands), R.: Tot lering en vermaak: betekenissen van Hollandse genrevoorstellingen uit de zeventiende eeuw. Rijksmuseum (1976)
26. Viola, P., Jones, M.J.: Robust real-time face detection. Int. J. Comput. Vision **57**(2) (May 2004) 137–154