## DIT gentle introduction to Python

v 2.3 (PhD) January-February 2024

#### Alberto Barrón-Cedeño

Alma Mater Studiorum-Università di Bologna a.barron@unibo.it @\_albarron\_

29/01/2024



### Table of Contents

- 1 Basics
- 2 Algorithms
- 3 Programming languages
- Baby steps into coding

#### **Basics**

A programming language is just a language. . .

A programming language is just a language. . .

A formal language comprising a set of instructions that produce various kinds of output [given an input]

https://en.wikipedia.org/wiki/Programming\_language (from an old version of the article; I don't like the current definition)

A programming language is just a language. . .

A formal language comprising a set of instructions that produce various kinds of output [given an input]

https://en.wikipedia.org/wiki/Programming\_language (from an old version of the article; I don't like the current definition)



Diagram borrowed from L. Moroney's Introduction to TensorFlow for Artificial Intelligence, Machine Learning, and Deep Learning

Programming languages are used in computer programming to implement an algorithm\*

 $\verb|https://en.wikipedia.org/wiki/Programming_language|\\$ 

Programming languages are used in computer programming to implement an algorithm\*

https://en.wikipedia.org/wiki/Programming\_language



\* derived from the 9th century Persian Mathematician Muhammad ibn Mūsā al-Khwārizmī

1983 USSR stamp commemorating al-Khwārizmī's (approximate) 1200th birthday

## The first programmer



A. Lovelace by 1840

**Ada Lovelace**<sup>a</sup> (Mathematician) published the first algorithm for Charles Babbage's analytical engine



<sup>a</sup>Lord Byron's daughter

### **Algorithms**

## Algorithm

A finite sequence of <u>well-defined computer-implementable</u> instructions, typically to solve a class of problems or to perform a computation

https://en.wikipedia.org/wiki/Algorithm

Algorithm Example: Find out if a number is odd or even\*

https://www.c-programming-simple-steps.com/algorithm-examples.html Alberto Barrón-Cedeño (DIT-UniBO)

<sup>\*</sup>Adapted from

# Algorithm Example: Find out if a number is odd or even\* Definitions

- A number is even if it can be divided by 2 without remainder
- A number is odd if it leaves a remainder when divided by 2

<sup>\*</sup>Adapted from

# Algorithm Example: Find out if a number is odd or even\* Definitions

- A number is even if it can be divided by 2 without remainder
- A number is odd if it leaves a remainder when divided by 2

#### **Examples**

Even numbers: 2, 4, 6, 8, etc.

Odd numbers: 1, 3, 5, 7, etc.

<sup>\*</sup>Adapted from

# Algorithm Example: Find out if a number is odd or even\* Definitions

- A number is even if it can be divided by 2 without remainder
- A number is odd if it leaves a remainder when divided by 2

#### **Examples**

Even numbers: 2, 4, 6, 8, etc.

Odd numbers: 1, 3, 5, 7, etc.

### Silly (useless) solution:

- Produce all possible even numbers and store them in box EVEN.
   Produce all possible odd numbers and store them box ODD.
- Given an input number, look for it in both boxes return the label of the one in which you found it

<sup>\*</sup>Adapted from

# Algorithm Example: Find out if a number is odd or even

### Input/Output

- $\rightarrow$  an integer (data)
- ← even or odd (more data)

# Algorithm Example: Find out if a number is odd or even

### Input/Output

- $\rightarrow$  an integer (data)
- $\leftarrow$  even or odd (more data)

#### **Process**

A series of instructions and routines





Diagram borrowed from

https://www.c-programming-simple-steps.com/algorithm-examples.html

## Algorithm Example: Find out if a number is odd or even

From the algorithm to the implementation



```
if n%2 == 0:
  print('even')
else:
  print('odd')
```

**Programming languages** 

## History of (some) flagship languages (1/2)

| year | language | highlights  |
|------|----------|---|
| 1957 | Fortran  | Compiled, imperative                                |
| 1959 | Lisp*    | Object-oriented, popular in AI, recursive functions |
| 1964 | Basic*   | Procedural, object-oriented ("goto")                |
| 1970 | Pascal*  | Imperative, procedural, lists, trees                |
| 1972 | C*       | Procedural, recursion, static type system           |
| 1983 | C++*     | Object-oriented, compiled, functional               |

<sup>\*</sup> language I "speak" (or "spoke" at some point in time)

## History of (some) flagship languages (2/2)

| year | language     | highlights                                     |
|------|--------------|--|
| 1989 | Python*      | Interpreted, object-oriented, code readability |
| 1995 | Java*        | Compiled, object-oriented                      |
| 1995 | Javascript   | Just-in-time-compiled, object-oriented, WWW    |
| 1995 | PHP*         | Scripting, Web-oriented                        |
| 2001 | V. Basic.NET | Object-oriented, .NET framework                |
| 2009 | Go           | Compiled, C-like (safer)                       |

<sup>\*</sup> language I "speak" (or "spoke" at some point in time)

(Among other things), python is...

### **General-purpose**

Applicable across application domains

(Among other things), python is...

#### **General-purpose**

Applicable across application domains

#### High-level

Strong abstraction from the computer (hardware)

(Among other things), python is...

#### **General-purpose**

Applicable across application domains

#### **High-level**

Strong abstraction from the computer (hardware)

#### Interpreted

No previous compilation into machine-level instructions necessary

(Among other things), python is...

#### **General-purpose**

Applicable across application domains

#### **High-level**

Strong abstraction from the computer (hardware)

#### Interpreted

No previous compilation into machine-level instructions necessary

## (Not-necessarily) object-oriented

An object contains data (attributes) and procedures (methods)

Some notable features

ullet Elegant syntax (indentation-based) ightarrow easy to read

Some notable features

- ullet Elegant syntax (indentation-based) o easy to read
- Simple and ideal for prototyping

Some notable features

- ullet Elegant syntax (indentation-based) o easy to read
- Simple and ideal for prototyping
- It has a large standard library for diverse tasks (e.g., web servers, text search and processing, file reading/modifying)

Some notable features

- ullet Elegant syntax (indentation-based) o easy to read
- Simple and ideal for prototyping
- It has a large standard library for diverse tasks (e.g., web servers, text search and processing, file reading/modifying)
- ullet Interactive mode o continuous snippet testing

Some notable features

- ullet Elegant syntax (indentation-based) o easy to read
- Simple and ideal for prototyping
- It has a large standard library for diverse tasks (e.g., web servers, text search and processing, file reading/modifying)
- ullet Interactive mode o continuous snippet testing
- Extendable with modules in compiled languages (e.g., C++)

Some notable features

- ullet Elegant syntax (indentation-based) o easy to read
- Simple and ideal for prototyping
- It has a large standard library for diverse tasks (e.g., web servers, text search and processing, file reading/modifying)
- ullet Interactive mode o continuous snippet testing
- Extendable with modules in compiled languages (e.g., C++)
- Multi-platform (e.g., Mac OS X, GNU Linux, Unix, MS Windows)

#### Some notable features

- $\bullet \ \, \mathsf{Elegant} \ \mathsf{syntax} \ \mathsf{(indentation\text{-}based)} \to \mathsf{easy} \ \mathsf{to} \ \mathsf{read} \\$
- Simple and ideal for prototyping
- It has a large standard library for diverse tasks (e.g., web servers, text search and processing, file reading/modifying)
- ullet Interactive mode o continuous snippet testing
- Extendable with modules in compiled languages (e.g., C++)
- Multi-platform (e.g., Mac OS X, GNU Linux, Unix, MS Windows)
- Free: zero-cost to download/use; open-source license

#### Some notable features

- ullet Elegant syntax (indentation-based) o easy to read
- Simple and ideal for prototyping
- It has a large standard library for diverse tasks (e.g., web servers, text search and processing, file reading/modifying)
- ullet Interactive mode o continuous snippet testing
- Extendable with modules in compiled languages (e.g., C++)
- Multi-platform (e.g., Mac OS X, GNU Linux, Unix, MS Windows)
- Free: zero-cost to download/use; open-source license
- Large and friendly community

#### Some notable features

- ullet Elegant syntax (indentation-based) o easy to read
- Simple and ideal for prototyping
- It has a large standard library for diverse tasks (e.g., web servers, text search and processing, file reading/modifying)
- ullet Interactive mode o continuous snippet testing
- Extendable with modules in compiled languages (e.g., C++)
- Multi-platform (e.g., Mac OS X, GNU Linux, Unix, MS Windows)
- Free: zero-cost to download/use; open-source license
- Large and friendly community
- Top alternative for deep learning

Some programming-language features

- A variety of basic data types are available:<sup>1</sup>
  - numbers (floating point, complex, integers)
  - strings (both ASCII and Unicode)
  - Lists
  - ► Dictionaries

Some programming-language features

- A variety of basic data types are available:<sup>1</sup>
  - numbers (floating point, complex, integers)
  - strings (both ASCII and Unicode)
  - ▶ Lists
  - Dictionaries
  - It supports object-oriented programming
- Code can be grouped into modules and packages

## Python

Some ways to code/launch a python program


#### [UNIX , GNU Linux , MacOS , Windows] terminal

```
alberto@ssit-ufftec-04:~$ python3
Python 3.9.16 (main, Dec 7 2022, 01:11:58)
[GCC 7.5.0] on linux
Type "help", "copyright", "credits" or "license" for more information.
>>> list1 = []
>>> for i in range(2, 16, 2):
... list1.append(i)
...
>>> list1
[2, 4, 6, 8, 10, 12, 14]
>>> exit()
alberto@ssit-ufftec-04:~$
```

#### Python

Some ways to code/launch a python program


Web browser: local, online, on Google's colab



### Python

Some ways to code/launch a python program

From your web browser on DIT's magamago (remotely online)<sup>2</sup>



<sup>&</sup>lt;sup>2</sup>Open to advanced students only

Enough! Let us look at some code!

Baby steps into coding

### Google's colab


a free Jupyter notebook environment that runs in the cloud and stores its notebooks on Google Drive

https://colab.research.google.com

## Google's colab

a free Jupyter notebook environment that runs in the cloud and stores its notebooks on Google Drive


https://colab.research.google.com



Our first jupyter notebook

## Google's colab: baby steps

- 1 Visit https://colab.research.google.com
- Click on Github
- Type (or paste)
  https://github.com/TinfFoil/learning\_dit\_python
- Press search
- Select DIT\_python\_notebook\_1\_static.ipynb



What we know so far

#### input/output

- print() displays stuff to the screen
- input() captures information from the user

What we know so far

#### input/output

- print() displays stuff to the screen
- input() captures information from the user

#### variables

| x = 5 | x is a variable                         |
|-------|---|
|       | we assign values to a variable with $=$ |
|       | (aka store information)                 |

What we know so far

#### input/output

- print() displays stuff to the screen
- input() captures information from the user

#### variables

| x = 5      | x is a variable                         |
|------------|---|
|            | we assign values to a variable with $=$ |
|            | (aka store information)                 |
| x = 5      | x is an integer                         |
| x = 5.5    | x is a float                            |
| x = 'ciao' | x is a string                           |
| x = "ciao" | x is also a string                      |
| x = '5'    | x is what?                              |

What we know so far

#### input/output

- print() displays stuff to the screen
- input() captures information from the user

#### variables

| x = 5      | x is a variable                          |
|------------|--|
| x - 3      | / 10 a Tallable                          |
|            | we assign values to a variable with $=$  |
|            | (aka store information)                  |
| x = 5      | x is an integer                          |
| x = 5.5    | x is a float                             |
| x = 'ciao' | x is a string                            |
| x = "ciao" | x is also a string                       |
| x = '5'    | x is what?                               |
| x = x * 3  | we can apply operators to variables      |
|            | and (re-)assign the output to a variable |

What we know so far

#### **Basic formatting**

```
# my code
x = 0
while x < 50:
   for i in range(x):
      print('x', end="")
   print()
   x += 1</pre>
```

- Comments start with #
- A line break is enough to close an instruction (in Java or C, we need;)
- A colon opens a code snippet
- Indentation is crucial

What we know so far

#### flow control - conditionals

```
if (condition):
    execute something
elif (condition):
    execute something
else:
    execute something
```

Only one of these three snippets is executed

What we know so far

#### flow control - conditionals

```
if (condition):
    execute something
elif (condition):
    execute something
else:
    execute something
```

Only one of these three snippets is executed

```
if (condition):
    execute something
if (condition):
    execute something
else:
    execute something
```

How is this different?

What we know so far

#### flow control - conditionals

```
if (condition):
    execute something
elif (condition):
    execute something
else:
    execute something
```

Only one of these three snippets is executed

```
if (condition):
    execute something
if (condition):
    execute something
else:
    execute something
```

How is this different?

#### flow control – loops

The code snippet will be executed during a number of iterations Danger: a loop could run forever if there is a *bug* 

```
for (iterator):
   execute something
```

```
while (condition):
execute something
```

# You know a lot already!

It is your turn to play with the notebook

