

Data types in SQLite

The following table shows how many common datatype names from more traditional SQL implementations are converted into affinities by the five rules of the previous section. This table shows only a small subset of the datatype names that SQLite will accept. Note that numeric arguments in parentheses that following the type name (ex: "VARCHAR(255)") are ignored by SQLite - SQLite does not impose any length restrictions (other than the large global [SQLITE_MAX_LENGTH](#) limit) on the length of strings, BLOBs or numeric values.

Example Typenames From The CREATE TABLE Statement or CAST Expression	Resulting Affinity	Rule Used To Determine Affinity
INT INTEGER TINYINT SMALLINT MEDIUMINT BIGINT UNSIGNED BIG INT INT2 INT8	INTEGER	1
CHARACTER(20) VARCHAR(255) VARYING CHARACTER(255) NCHAR(55) NATIVE CHARACTER(70) NVARCHAR(100) TEXT CLOB	TEXT	2
BLOB <i>no datatype specified</i>	BLOB	3
REAL DOUBLE DOUBLE PRECISION FLOAT	REAL	4
NUMERIC DECIMAL(10,5) BOOLEAN DATE DATETIME	NUMERIC	5

Note that a declared type of "FLOATING POINT" would give INTEGER affinity, not REAL affinity, due to the "INT" at the end of "POINT". And the declared type of "STRING" has an affinity of NUMERIC, not TEXT.