

Drafting

Helpful functions for content positioning and margin comments/notes

v0.2.2

August 27, 2025

<https://github.com/ntjess/typest-drafting>

Nathan Jessurun

Jens Tinggaard

ABSTRACT

drafting is used when drafting documents, it can show various notes in the margin, or inlined in the document, along with some positioning utilities.

CONTENTS

I hello	2
I.a Drafting	2

I HELLO

I.a Drafting

- [absolute-place\(\)](#)
- [inline-note\(\)](#)
- [margin-note\(\)](#)
- [note-outline\(\)](#)
- [place-margin-rects\(\)](#)
- [rule-grid\(\)](#)
- [set-margin-note-defaults\(\)](#)
- [set-page-properties\(\)](#)
- [text-direction\(\)](#)

Variables

- [margin-note-defaults](#)

I.a.a absolute-place

Place content at a specific location on the page relative to the top left corner of the page, regardless of margins, current container, etc.

I.a.a.a Parameters

```
absolute-place(  
  dx,  
  dy,  
  content  
) -> content
```

I.a.b inline-note

Place a note inline with the text body.

I.a.b.a Parameters

```
inline-note(  
  body: content,  
  par-break: bool,  
  ..kwargs: any  
) -> content
```

I.a.b.a.a body `content`

Margin note contents, usually text

I.a.b.a.b par-break `bool`

Whether to break the paragraph after the note, which places the note on its own line.

Default: `true`

I.a.b.a.c ..kwargs any

Additional properties to apply to the note. Accepted values are keys from `margin-note-defaults`.

I.a.c margin-note

Places a boxed note in the left or right page margin.

I.a.c.a Parameters

```
margin-note(  
  body: content,  
  dy: length,  
  ..kwargs: any  
) -> content
```

I.a.c.a.a body content

Margin note contents, usually text

I.a.c.a.b dy length

Vertical offset from the note's location – negative values move the note up, positive values move the note down

Default: `auto`

I.a.c.a.c ..kwargs any

Additional properties to apply to the note. Accepted values are keys from `margin-note-defaults`.

I.a.d note-outline

Show an outline of all notes

I.a.d.a Parameters

```
note-outline(  
  title: string,  
  level: number,  
  row-gutter: relative  
) -> content
```

I.a.d.a.a title `string`

Title of the outline

Default: `"List of Notes"`

I.a.d.a.b level `number`

Level of the heading

Default: `1`

I.a.d.a.c row-gutter `relative`

Spacing between outline elements

Default: `10pt`

I.a.e place-margin-rects

Place a rectangle in the margin of the page. Useful for debugging spacing.

I.a.e.a Parameters

```
place-margin-rects(  
  padding: length,  
  ..rect-kwargs: any  
) -> content
```

I.a.e.a.a padding `length`

amount of padding to add to the left and right of the rectangles

Default: `1%`

I.a.e.a.b ..rect-kwargs `any`

Additional properties to apply to the rectangles

I.a.f rule-grid

Add a series of evenly spaced x- any y-axis lines to the page.

I.a.f.a Parameters

```
rule-grid(  
  dx: length,  
  dy: length,  
  stroke: paint,  
  width: length,  
  height: length,  
  spacing: length, array,  
  divisions: int, array,  
  square: bool,  
  relative: bool  
) -> content
```

I.a.f.a.a dx length

Horizontal offset from the top left corner of the page

Default: 0pt

I.a.f.a.b dy length

Vertical offset from the top left corner of the page

Default: 0pt

I.a.f.a.c stroke paint

Stroke to use for the grid lines. The paint of this stroke will determine the text color.

Default: black

I.a.f.a.d width length

Total width of the grid

Default: 100cm

I.a.f.a.e height length

Total height of the grid

Default: 100cm

I.a.f.a.f spacing length, array

Spacing between grid lines. If an array is provided, the values are taken in (x, y) order. Cannot be provided alongside divisions.

Default: none

I.a.f.a.g divisions `int, array`

Number of divisions along each axis. If an array is provided, the values are taken in (x, y) order. Cannot be provided alongside `spacing`.

Default: `none`

I.a.f.a.h square `bool`

Whether to make the grid square. If `true`, and either `divisions` or `spacing` is provided, the smaller of the two values will be used for both axes to ensure each grid cell is square.

Default: `false`

I.a.f.a.i relative `bool`

If `true` (default), the grid will be placed relative to the current container. If `false`, the grid will be placed relative to the top left corner of the page.

Default: `true`

I.a.g set-margin-note-defaults

Changes the default properties for margin notes. See documentation on `margin-note-defaults` for available options.

I.a.g.a Parameters

```
set-margin-note-defaults(..defaults) -> any
```

I.a.h set-page-properties

Required for `margin-note` to work, since it informs `drafting` of the page setup.

I.a.h.a Parameters

```
set-page-properties(..kwargs)
```

I.a.i text-direction

get direction of text based on defaults for the language <https://github.com/typst/typst/blob/521ceae889f15f2a93683ab776cd86a423e5dbed/crates/typst-library/src/text/lang.rs#L109>

I.a.i.a Parameters

```
text-direction(  
  dir,  
  lang  
) -> text-direction
```

I.a.j margin-note-defaults dictionary

Default properties for margin notes. These can be overridden per function call, or globally by calling `set-margin-note-defaults`. Available options are:

- `margin-right` (length): Size of the right margin
- `margin-left` (length): Size of the left margin
- `margin-inside` (length): Size of the inside margin
- `margin-outside` (length): Size of the outside margin
- `page-binding` (auto | alignment): Where the page is bound
- `page-width` (length): Width of the page minus the margins. This is automatically inferrable when using `set-page-properties`
- `page-offset-x` (length): Horizontal offset of the page/container. This is generally only useful if margin notes are applied inside a box/rect; at the page level this can remain unspecified
- `stroke` (paint): Stroke to use for the margin note's border and connecting line
- `fill` (paint): Background to use for the note
- `rect` (function): Function to use for drawing the margin note's border. This function must accept positional `content` and keyword `width` arguments.
- `side` (side): Which side of the page to place the margin note on. Must be `left` or `right`
- `hidden` (bool): Whether to hide the margin note. This is useful for temporarily disabling margin notes without removing them from the code
- `caret-height` (length): Size of the caret from the text baseline
- `link` ("line" | "index"): Whether to link the origin of the note to the note margin itself with a link or with an index.
- `inline-numbering` (numbering | auto): The numbering shown in the text inlined. Doesn't do anything unless `link` is set to `"index"`
- `note-numbering` (numbering | auto): The numbering shown in the margin note.