

The Performance Parameters & Configuration Table of Skateboard Chassis HOOKE 2.0					
No	System Category		Description	Basic Parameter	
				4 -Wheel Drive & 4 -Wheel	2 -Wheel Drive & 2 -Wheel
1	Steering System	Motor Performance	Rated Power (KW)	0.5	0.5
2			Rated Torque (N.M)	4.5	4.5
3			Rated Rotating Speed (r/min)	1050	1050
4			Operating Voltage (V)	10.8~14	10.8~14
5			Steering Range (°)	±450	±450
6			Steering Structure	Drive-by-wire Electric Steering	Drive-by-wire Electric Steering
7			Steering Type	Ackerman Steering	Ackerman Steering
8			Steering Mode	Four-wheel/Wedge Steering	Two-wheel/Wedge Steering
9			Operating Temperature (°C)	-40~105	-40~105
10			Communication Speed (kps)	500	500
11		Control Performance	Steering Accuracy (°)	1	1
12			Response Time (ms)	≤150	≤150
13			Max Output Force of Steering Rod	10000	10000
14			Communication Protocol	CAN2.0B	CAN2.0B
15			Steady-state error (°)	±1	±1
16			Overshoot (°)	≤15	≤15
17			Control Method	Target Steering Wheel Angle &	Target Steering Wheel Angle &
18			Toe-in (mm)	5	5
1	Braking System	Braking Type	Braking Type for Driving	Drive-by-wire Hydraulic Braking	Drive-by-wire Hydraulic Braking
2			Braking Type for Parking	Electronic Parking System	Electronic Parking System
3			Overshoot (Mpa)	0.5	0.5
4			Brake Type	Disc	Disc
5		Braking Performance	Motor Type	Permanent Magnet Brushless	Permanent Magnet Brushless
6			Rated Power (KW)	0.45	0.45
7			Rated Torque (N.M)	2.3	2.3
8			Rated Rotating Speed (r/min)	1700	1700
9			Operating Voltage (V)	9~14	9~14
10			Response Time (ms)	≤200	≤200
11			Communication Protocol	CAN2.0B	CAN2.0B
12			Max Braking Pressure (Mpa)	7	7
13			Max Pressure Build-up Time (ms)	≤300ms	≤300ms
14			Control Method	Target pressure closed loop	Target pressure closed loop
15			Control precision (Mpa)	0.1	0.1
16			Steady-state Error (Mpa)	0.3	0.3
17			Operating Temperature (°C)	-40 ~ 85	-40 ~ 85
18			Max Braking Distance (m)	≤6	≤6
1	Power System	In-wheel Motor	Rated Power (KW)	4×3	2×3
2			Rated Torque (N.M)	4×126	2×126
3			Rated Rotating Speed (r/min)	230	230
4			Peak Power (KW)	4×3.8	2×3.8
5			Peak Torque (N.M)	4×180	4×180
6			Peak Rotating Speed (r/min)	550	550
7			Rated Voltage (V)	72V	72V
8			Cooling Method	Air Cooling	Air Cooling
9			Speed Control Accuracy (km/h)	0.1	0.1
10			Motor Size (mm)	ø280	ø280
11		Control Performance	Responding Speed (ms)	≤200ms	≤200ms
12			Steady-state Error (km/h)	0.2	0.2
13			Communication Protocol	CAN2.0B	CAN2.0B
14			Drive motor type	Permanent Magnet Brushless DC	Permanent Magnet Brushless DC
15			Overshoot (km/h)	0.4	0.4
16			Control Method	Accelerator Pedal Opening	Accelerator Pedal Opening
1	Mechanical System	Main Parameters	Dimensions (mm)	2510×1700×630	2510×1700×620
2			Wheelbase (mm)	1900	1900
3			Front/Rear Wheel Track (mm)	1465/1465	1465/1465
4			Front/Rear Overhang (mm)	237/237	237/237
5			Min Ground Clearance (mm)	175	170
6			Approach Angle /Departure Angle (°)	/	/
7			Height of the Interior Floor above the	380	375
8			Min Turning Radius (m)	3	6
9			Curb Weight (kg)	450	420
10			Max Allowable Load Mass (kg)	500	400
11			Full Load Mass (kg)	950	820
12			Normal Speed (Km/h)	≤40	≤40
13			Max Speed (Km/h) No Load (A Disclaimer Agreement Needs to be Signed)	60	55
14			Max Gradability (%) No Load	30	20
15			Acceleration Time (s)	4.5	9
16			Inner/Outer Wheel Steering Angle	30/27	30/27
17			Suspension Type	Front & Rear Double Wishbone	Front & Rear Double Wishbone
18			Tire Specifications	215/45R17	205/45R17
19			IP Level	IP56	IP56
20			Suspension Spring Stroke (mm)	30±3	30±3
21			Frame Material	High Strength Steel	High Strength Steel
22			Drive Style	Four-Wheel Drive	Two-Wheel Drive
23			Cruising Range (Km) No Load	70	90
25		Load 800KG		□ Optional	
1	Power Supply System	Energy Storage System	Power Battery Type	Ternary Lithium Battery	Ternary Lithium Battery
2			Rated Voltage of Battery System (V)	72	72
3			Rated Capacity of Battery System	100	100
4			Battery System Energy (kW.h)	7.2	7.2
5			Max Output Power of Battery System(KW)(less than or equal to 60S)	25	25
6			Over-discharge Protection Method for	BMS	BMS
7			Overcharge Protection Method for	BMS	BMS
8			Charging Method	AC Slow Charge	AC Slow Charge
9			Charging Time (h)	6	6
10			Cooling Method	Natural Cooling	Natural Cooling
11		Low Voltage Power Supply	Low Voltage Starting Power	Lead-acid Battery	Lead-acid Battery
12			Operating Voltage(V)	12~14	12~14
1	Accessories	Signal and Lighting	Front Light	Standard	Standard
2			Rear Position Light	Standard	Standard
3			Front Steering Light	Standard	Standard
4			Rear Steering Light	Standard	Standard
5			Rear Braking Light	Standard	Standard
6		Assisting Equipments	OBD Diagnostic Interface	Standard	Standard
7			DB9 Test Interface	Standard	Standard
8			Chassis Communication Type	CAN2.0B	CAN2.0B
9			Autonomous Driving System	Reserved Interface	Reserved Interface
	Chassis Appearance	Colour			Silver Grey
		Surface Sealing	Standard		