CIRCUS CHARLIE

™

SERVICE MANUAL
901-2169

OPTIONAL DIP SWITCH SETTINGS

A. Dip Switch No.1 (8P Dip Switch)

Credits

Coin	Plays	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8
1	1	Off	Off	Off	Off	Off	Off	Off	Off
1	2	On	Off	Off	Off	On	Off	Off	Off
1	3	Off	On	Off	Off	Off	On	Off	Off
1	4	On	On	Off	Off	On	On	Off	Off
1	5	Off	Off	On	Off	Off	Off	On	Off
1	6	On	Off	On	Off	On	Off	On	Off
1	7	Off	On	On	Off	Off	On	On	Off
2	1	On	On	On	Off	On	On	On	Off
2	3	Off	Off	Off	On	Off	Off	Off	On
2	5	On	Off	Off	On	On	Off	Off	On
3	1	Off	On	Off	On	Off	On	Off	On
3	2	On	On	Off	On	On	On	Off	On
3	4	Off	Off	On	On	Off	Off	On	On
4	1	On	Off	On	On	On	Off	On	On
4	3	Off	On	On	On	Off	On	On	On
Free Play		On	On	On	On	On	On	On	On

B: Dip Switch No.2 (8P Dip Switch)

1. Number Of Clowns

Number	SW1	SW2
○ 3	Off	Off
4	On	Off
5	Off	On
7	On	On

2. Game Type

Style	SW3	Players
Table	Off	1 or 2 Players
Upright	On	Only 1 Player

3. Bonus Points Setting

First	And Every	SW4	SW5
○ 20,000	70,000	Off	Off
30,000	80,000	On	Off

B. Dip Switch No.2 (continues)

   4. Play Difficulty

Option	SW6	SW7
Easy	Off	Off
◯ Normal	On	Off
Hard	Off	On
Difficult	On	On

   5. Audio Attraction

Sound Mode	SW8
No Sound In Attract Mode	Off
◯ Sound In Attract Mode	On

◯ Denotes Normal Settings

FIGURE 13

			TOLERANCES Unless Otherwise Specified			NAME CPU HARNESS-CIRCUS CHARLIE, C/T		
			FRACTIONS	±	1/32			
			DECIMALS 2 PL	±	.015			
			DECIMALS 3 PL	±	.005	MATL'S.	HEAT TREAT.	FINISH
A	4041-01	CHGED GRAY WIRE TO BRN, CHGED BRN WIRE QTY FRM 24" TO 143", GRAY FRM 20"4 TO 155"	MJ	HOLES	+	.003			
				-	.001	DWN MJ	APP'D	DATE 12-28-83	SCALE X	PART NO. 008-4930	REV A
REV. LET.	ECN NO.	REVISION	BY	ANGLES SHT. MET BENDS	± ±	1/2° 2°			

33

NOTE

$\uparrow$: VCC +5V $\square$: 5V CONNECTOR 2P
$\perp$: GND 0V $\bigcirc$: CERAMIC CONDENSER
$\bigcirc$: FLAT CABLE CONNECTOR 40P
$\oplus$: ELECTROLYTIC CONDENSER
$\odot$: TANTALUM ELECTROLYTOR CONDENSER

TOLERANCES
FRACTIONS
DECIMALS 2 PL.
DECIMALS 3 PL.
HOLES
ANGLES

SOUND BOARD P.C.B. CIRCUS CHARLIE

HIALEAH, FLORIDA 33014

THE MATERIAL CONTAINED HEREIN IS CONFIDENTIAL AND NO PART OF IT CAN BE REPRODUCED WITHOUT THE EXPRESSED PERMISSION OF CENTURI, INC.

PART No. 405-1916