



SPECIFICATION	仕様
CONTACT RESISTANCE 接触抵抗	50mΩ or less at 10mA (INITIAL)
DIELECTRIC WITHSTANDING VOLTAGE 絶縁耐電圧	500 V.A.C for 1 minute
INSULATION RESISTANCE 絶縁抵抗	1000MΩ or more at 500V.D.C
OPERATING TEMPERATURE 作動温度	-65°~+150°
RETENTION FORCE 固定力の強さ	0.5kg for 1 minute
INSERTION	10000 c/v.c.(MECHANICAL)

★	18	COTS	55-113-131-01	HEX. THIN NUT M2	SUS	2	SUP. WITH SOCKETS
★	17	COTS	55-113-111-01	SPRING LOCK WASHER 2.0	SUS	2	SUP. WITH SOCKETS
★	16	COTS	55-113-009-01	PAN HEAD SCREW M2X10	SUS	2	SHIP WITH SOCKETS
★	15	QON-64-0.5-01-10	55-111-952-01	RIVET	SUS	1	
	14	COTS	55-113-002-01	E-RING(Ø1.2)	SUS	2	
	13	QFN-68-0.5-01-12	55-111-835-01	GROUND P IN	BRASS	1	Au PLATING
	12	FP-28-1, 27-09-003	55-112-035-01	COIL SPRING	SUS	1	FOR COVER
	11	FPQ-64-1, 0-01-004	55-112-007-01	COIL SPRING	SUS	1	FOR STOPPER
	10	QFN-68-0.5-01-11	55-112-808-01	COIL SPRING	SUS	1	FOR PUSHER
	9	QFN-68-0.5-01-10	55-111-834-01	SHAFT	SUS	1	FOR COVER
	8	QFN-68-0.5-01-09	55-111-833-01	SHAFT	SUS	1	FOR STOPPER
	7	FPQ-64-1, 0-01-003	55-299-043-01	STOPPER	PPS	1	
	6	QFN-68-0.5-01-06	56-290-836-01	PUSHER	PES	1	
	5	QFN-68-0.5-01-03	56-110-723-01	FWTO CONTACT	BeCu	32	
	4	QFN-68-0.5-01-02	56-110-722-01	FWSO CONTACT	BeCu	32	
	3	QFN-64-0.5-01-01	56-290-890-01	GUIDE	PES	1	
	2	QFN-68-0.5-01-05	56-290-835-01	COVER	PES	1	
	1	QFN-64-0.5-01-01	56-290-850-01	BODY	PES	1	

**ESP CONFIDENTIAL**

[illegible]