

Izzy Escobar

FOH CHANNEL EQ SETUP — DiGiCo Quantum 225

Show	Izzy Escobar
Show Date	2026-06-26
Venue	Fountain Square (outdoor)
Console	DiGiCo Quantum 225
Channels	19
FOH Engineer	Brian Lloyd
Monitor Engineer	Sam Carpenter
Show Time	9:00pm
Rev	Rev 1.0 Deep Build (gear-informed)

DOCUMENT CONTENTS

- 1. Cover Page — show, venue, and personnel
- 2. Input List — color-coded full channel patch sheet
- 3. Patching — AES and Local inputs sorted by port
- 4. EQ Setup — 19 channels for DiGiCo Quantum 225
- 5. Reference — EQ structure, pan guide, bus grouping, soundcheck order

SHOW STYLE: Restraint-forward pop-soul — the voice is the mix; band sits under it. Outdoor, intimate, minimal verb.

Izzy Escobar

VENUE: Fountain Square (outdoor)

DATE: 2026-06-26

REV: Rev 1.0 Deep Build
(gear-informed)

FOH: Brian Lloyd

MON: Sam Carpenter

SHOW TIME: 9:00pm

Ch	Instrument	Mic / DI	Patch	48V	Stand	Notes
■ DRUMS						
1	Kick In	Shure Beta 91A	Local 1	✓	Boom	Beta 91A inside + 52A at the port — treat as one blend: same VCA, pan together, polarity-check (flip one if thinner).
2	Kick Out	Shure Beta 52A	Local 2		Boom	Body/punch half of the kick blend — see Kick In.
3	Snare Top	Audix i5	Local 3		Boom	
5	Hat	Shure SM81	Local 5	✓	Boom	
6	Rack 1	Audix D2	Local 6		Boom	
7	Rack 2	Audix D2	Local 7		Boom	
8	Floor	Audix D4	Local 8		Boom	
9	OH HL	Shure SM81	Local 9	✓	Boom	
10	OH HR	Shure SM81	Local 10	✓	Boom	
■ RHYTHM						
11	Bass DI	XLR (DI)	Local 11		DI	Bass DI + SM57 cab blend: DI = weight + low-mid warmth, 57 = punch/grind. One VCA, polarity-check against the 57.
12	Bass Mic	Shure SM57	Local 12		DI	Blend with the DI — see Bass DI. Ampeg SVT-CL + 810 'fridge'.
13	Guitar 57	Shure SM57	Local 13		DI	SM57 on a Fender Deluxe Reverb '65, edge-of-breakup. 57 + Beta 27 blend (off-axis pair) — same VCA, polarity-check.
14	Guitar 27	Shure Beta 27	Local 14	✓	DI	57/27 blend pair on the Deluxe — 27 carries clean low body + a sliver of air. Polarity-check against the 57.
15	Acoustic Guitar	BSS AR-133	Local 15		DI	
17	Keys	Whirlwind IMP (DI)	Local 17		DI	Yamaha Motif XF8.
18	Click	Whirlwind IMP (DI)	Local 18		DI	Monitors / IEM only — never assigned to FOH.
19	Guide	Whirlwind IMP (DI)	Local 19		DI	Cue track — monitors only.

Ch	Instrument	Mic / DI	Patch	48V	Stand	Notes
20	Tracks	Whirlwind IMP (DI)	Local 20		DI	Mastered, full-range stem (her strings/synths/BGV bed).
■ VOCALS						
25	Izzy	Neumann KMS 105	Local 25	✓	Tall	Wired handheld on a stand (not the wireless system).

■ DRUMS ■

Ch 1 | Kick In

Mic: Shure Beta 91A

Mic Notes: Boundary mic inside a 22in maple kick with a Powerstroke 3 batter — the head is already muffled/focused, and the 91A is the attack/click layer.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	40 Hz	LC	—	—	High-pass
4	3.5 kHz	Bell	+4 dB	1.2	
3	600 Hz	Bell	-2 dB	2	
2	300 Hz	Bell	-3 dB	1.8	
1	80 Hz	Bell	+3 dB	1.2	
HC	—	HC	—	—	No LPF

Engineer Notes: The 91A owns the click — +4@3.5k beater definition that travels outdoors. Lows modest so they tuck under the 52A; box cut eased to -3 because the Powerstroke 3 + maple shell are already controlled, no need to gut 250.

Ch 2 | Kick Out

Mic: Shure Beta 52A

Mic Notes: 52A at the port = the body/weight engine of the maple kick.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	40 Hz	LC	—	—	High-pass
4	3 kHz	Bell	+2 dB	1.2	
3	600 Hz	Bell	-2 dB	2	
2	300 Hz	Bell	-3 dB	1.8	
1	70 Hz	Bell	+5 dB	1.2	
HC	—	HC	—	—	No LPF

Engineer Notes: +5@70 supports the weight open air swallows; only a small 3k snap since the 91A carries the real click. Mud cut eased for outdoors.

Ch 3 | Snare Top

Mic: Audix i5

Mic Notes: i5 has a built-in ~3.5-4k presence peak and slightly scooped low-mids — fuller, less boxy than a 57. The drum is a brass Ludwig Black Beauty: dark, with a strong metallic ring and big mid projection.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	120 Hz	LC	—	—	High-pass
4	7 kHz	Bell	+2 dB	0.8	
3	1 kHz	Bell	+3 dB	1	
2	500 Hz	Bell	-3 dB	2	
1	300 Hz	Bell	-4 dB	2	
HC	—	HC	—	—	No LPF

Engineer Notes: On a Black Beauty the ring is the thing to manage — -3@500 tames the metallic ring/projection without gutting the drum (a Supraphonic wouldn't need this). -4@300 box, eased because the brass carries wanted body. +3@1k restores the crack the i5 scoops; +2@7k snap for the outdoor throw — coated Emperor + i5 presence mean it doesn't need more.

Ch 5 | Hat

Mic: Shure SM81

Mic Notes: SM81 — smooth, un-hyped highs. The hats are 14in Zildjian K Custom Session: dark and warm, not bright.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	500 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	—	OFF	—	—	Flat
2	2 kHz	Bell	-4 dB	1.2	
1	800 Hz	Bell	-6 dB	1.5	
HC	16 kHz	HC	—	—	Low-pass

Engineer Notes: No HF boost — dark K hats through a smooth 81 already sit nicely, and lifting the top over a long outdoor throw just adds hiss. Clear the low bleed (800) and the 2k clang; LPF 16k trims any edge.

Ch 6 | Rack 1

Mic: Audix D2

Mic Notes: D2 is tuned to control tom resonance — articulate with little EQ. This is the 10in rack (highest tom), Clear Emperor.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	100 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	3 kHz	Bell	+4 dB	1	
2	450 Hz	Bell	-3 dB	1.8	
1	150 Hz	Bell	+3 dB	1.2	
HC	12 kHz	HC	—	—	Low-pass

Engineer Notes: Voiced highest in the kit series. Gentle body @150, modest mud cut @450, +4@3k stick attack — trust the D2's voicing.

Ch 7 | Rack 2

Mic: Audix D2

Mic Notes: As Rack 1, shifted down for the larger 12in drum.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	85 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	2.6 kHz	Bell	+4 dB	1	
2	400 Hz	Bell	-3 dB	1.8	
1	130 Hz	Bell	+3 dB	1.2	
HC	12 kHz	HC	—	—	Low-pass

Engineer Notes: Same treatment as Rack 1, voiced a touch lower for the bigger shell — let the D2 do the work.

Ch 8 | Floor

Mic: Audix D4

Mic Notes: D4 reaches an octave lower than the D2 natively — the 16in floor's weight is there without much help.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	55 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	1.8 kHz	Bell	+4 dB	1	
2	400 Hz	Bell	-3 dB	1.8	
1	70 Hz	Shelf	+4 dB	0.71	
HC	10 kHz	HC	—	—	Low-pass

Engineer Notes: Body shelf stays modest (+4) — support, not a big lift; ride the sub outdoors. -3@400 mud; +4@1.8k stick definition.

Ch 9 | OH HL

Mic: Shure SM81

Mic Notes: Cymbal sheen + kit glue. The cymbals are dark Zildjian K Customs; the SM81 is already detailed.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	180 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	—	OFF	—	—	Flat
2	6 kHz	Bell	+2 dB	0.8	
1	300 Hz	Bell	-5 dB	1.5	
HC	—	HC	—	—	No LPF

Engineer Notes: +2@6k only (not +5) — dark K cymbals plus a long outdoor throw mean a big HF lift turns brittle and washy. -5@300 clears the low wash so the OHs stay cymbals, not a second kit mic.

Ch 10 | OH HR

Mic: Shure SM81

Mic Notes: Matched to OH HL — keep the stereo pair identical.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	180 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	—	OFF	—	—	Flat
2	6 kHz	Bell	+2 dB	0.8	
1	300 Hz	Bell	-5 dB	1.5	
HC	—	HC	—	—	No LPF

Engineer Notes: Same as OH HL.

■ RHYTHM ■

Ch 11 | Bass DI

Mic: XLR (DI)

Mic Notes: DI carries the lows the sealed 810 rolls off. Flatwounds + fingerstyle = dark, round, low-mid forward, very little string clank.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	40 Hz	LC	—	—	High-pass
4	1.5 kHz	Bell	-5 dB	1.5	
3	600 Hz	Bell	+4 dB	1	
2	250 Hz	Bell	-6 dB	2	
1	80 Hz	Shelf	+5 dB	0.71	
HC	—	HC	—	—	No LPF

Engineer Notes: Soul/Motown bass — dark, round, low-mid forward, top rolled. +4@600 is the Motown 'wool'; -5@1.5k tames what little clank there is (flats are already dark); -6@250 keeps it off the kick AND the cab's strong low-mids; +5@80 foundation for the open air.

Ch 12 | Bass Mic

Mic: Shure SM57

Mic Notes: 57 on the 810 cab — it's the punch/grind mid layer over the DI (the 57 rolls off below ~200). The sealed 810 is already strong in the low-mids and has no top sizzle.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	60 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	800 Hz	Bell	+5 dB	1	
2	400 Hz	Bell	-7 dB	2	
1	100 Hz	Shelf	+5 dB	0.71	
HC	5 kHz	HC	—	—	Low-pass

Engineer Notes: +5@800 is the SVT growl; -7@400 carves a deep pocket so it doesn't stack the DI AND the 810's baked low-mid into mud. LPF 5k keeps the dark flatwound character — the fridge has no top anyway. Blend constant with the DI, same VCA.

Ch 13 | Guitar 57

Mic: Shure SM57

Mic Notes: 57 brings honky mids; the amp is a Fender Deluxe Reverb '65 — bright-cap chime, scooped mids, a snappy/glassy top that turns ice-picky past ~5 on the dial. The treble is the thing to tame, not boost.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	100 Hz	LC	—	—	High-pass
4	3.5 kHz	Bell	-4 dB	1.4	
3	800 Hz	Bell	+2 dB	1.2	
2	400 Hz	Bell	-3 dB	2	
1	150 Hz	Bell	-3 dB	1.2	
HC	—	HC	—	—	No LPF

Engineer Notes: Re-voiced for the actual amp (Deluxe Reverb '65 from the backline quote — overrides the 'Vox AC30' note in the brief). A Deluxe is bright and scooped, so instead of a rock-style 2.5k push this TAMES the chime at 3.5k, trims the flubby low end at 150, and adds just a touch of body at 800 so the clean tone sits under the vocal. The mid scoop is left alone — that's the Fender voice.

Ch 14 | Guitar 27

Mic: Shure Beta 27

Mic Notes: Bright detailed condenser — on a bright Deluxe its value is clean low body + a hint of air, NOT more upper-mid, which would just stack the amp's chime.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	100 Hz	LC	—	—	High-pass
4	10 kHz	Bell	+2 dB	0.8	
3	3.5 kHz	Bell	-3 dB	1.4	
2	400 Hz	Bell	-2 dB	2	
1	120 Hz	Shelf	+2 dB	0.71	
HC	—	HC	—	—	No LPF

Engineer Notes: Re-thought from the KB condenser default: 57 owns mids, 27 owns clean body + a sliver of air. Because the Deluxe is already bright, the 27's presence region (3.5k) is trimmed, not boosted, and the air sits up at 10k above the ice-pick zone. -2@400 to match a little box; same VCA as the 57.

Ch 15 | Acoustic Guitar

Mic: BSS AR-133

Mic Notes: AR-133 is a clean/transparent DI; the source is a piezo — quack at 1.5-2k, brassy at ~5k.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	100 Hz	LC	—	—	High-pass
4	8 kHz	Shelf	+3 dB	0.71	
3	2 kHz	Bell	-6 dB	1.8	DYNAMIC: thr=-12dB atk=5ms rel=80ms — bites only on peaks
2	400 Hz	Bell	-5 dB	2	
1	200 Hz	Shelf	+4 dB	0.71	
HC	—	HC	—	—	No LPF

Engineer Notes: Air at 8k, NOT 5k — 5k is the brassy piezo zone you cut. The -6@2k quack cut is DYNAMIC so it only bites on loud strums without gutting sustain; -5@400 box; +4@200 body the piezo can't make on its own.

Ch 17 | Keys

Mic: Whirlwind IMP (DI)

Mic Notes: Motif XF8 is a full-range workstation — real piano lows and it can be bright; clean DI. Piano is central to her writing.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	50 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	8 kHz	Shelf	+2 dB	0.71	
2	2.5 kHz	Bell	+3 dB	0.8	
1	200 Hz	Bell	-4 dB	1.5	
HC	—	HC	—	—	No LPF

Engineer Notes: HPF only 50 to keep the piano's real low end. Carve -4@200 so it doesn't crowd the bass + vocal low-mids; +3@2.5k for definition in a dense mix; a gentle 8k shelf for sparkle. Musical, not hyped — the Motif is already full and produced.

Ch 18 | Click

Mic: Whirlwind IMP (DI)

Mic Notes: Utility / cue.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	80 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	—	OFF	—	—	Flat
2	315 Hz	Bell	-4 dB	2	
1	200 Hz	Shelf	-2 dB	0.71	
HC	—	HC	—	—	No LPF

Engineer Notes: Mud trimmed so it's clean in the players' ears. CONFIRM: monitors / IEM only — never to FOH.

Ch 19 | Guide

Mic: Whirlwind IMP (DI)

Mic Notes: Guide vocal / cue track.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	80 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	—	OFF	—	—	Flat
2	315 Hz	Bell	-4 dB	2	
1	200 Hz	Shelf	-2 dB	0.71	
HC	—	HC	—	—	No LPF

Engineer Notes: Same utility treatment. *CONFIRM: monitors / IEM only — not in FOH.*

Ch 20 | Tracks

Mic: Whirlwind IMP (DI)

Mic Notes: Already a balanced, mastered master — not a mic'd source.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	30 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	—	OFF	—	—	Flat
2	—	OFF	—	—	Flat
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: Left near-flat (HPF 30 only) — EQ'ing a finished master like a mic'd source just thins the production. Add a small 315 trim live *ONLY* if it clouds the band.

■ VOCALS ■

Ch 25 | Izzy

Mic: Neumann KMS 105

Mic Notes: KMS 105 — transparent, smooth 7-12k presence, NOT a sibilant mic. Wired handheld on a stand.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	110 Hz	LC	—	—	High-pass
4	7.5 kHz	Bell	-3 dB	3	DYNAMIC: thr=-18dB atk=3ms rel=120ms — bites only on peaks
3	1.6 kHz	Bell	-3 dB	1.4	
2	300 Hz	Bell	-4 dB	2	
1	—	OFF	—	—	Flat
HC	15 kHz	HC	—	—	Low-pass

Engineer Notes: The show lives here. A DYNAMIC de-ess at 7.5k instead of a static -5@8k — keep the air a soul voice wants and only act on sibilant peaks. HPF pulled to 110 (the mic compensates proximity, won't boom) to protect the throaty Winehouse chest body. -3@1.6k gentle nasal; -4@300 box for outdoor intelligibility. Protective + subtractive, not aggressive. NOTE: this overrides the FSQ template's wireless-vocal baseline (removes its feedback notch) — watch for feedback at soundcheck and reach for the Mustard comp + a touch of plate before any more EQ.