

The Hot Magnolias

FOH CHANNEL EQ SETUP — DiGiCo Quantum 225

Show	The Hot Magnolias
Show Date	2026-07-11
Venue	Fountain Square (outdoor)
Console	DiGiCo Quantum 225
Channels	17
FOH Engineer	Brian Lloyd
Monitor Engineer	TBD
Show Time	TBD
Rev	Rev 1.0 Deep Think

DOCUMENT CONTENTS

1. Cover Page — show, venue, and personnel
2. Input List — color-coded full channel patch sheet
3. Patching — AES and Local inputs sorted by port
4. EQ Setup — 17 channels for DiGiCo Quantum 225
5. Reference — EQ structure, pan guide, bus grouping, soundcheck order

SHOW STYLE: Horn-forward New Orleans party band — warm and danceable, three-horn front line carries the show.

The Hot Magnolias

VENUE: Fountain Square (outdoor)	DATE: 2026-07-11	REV: Rev 1.0 Deep Think
FOH: Brian Lloyd	MON: TBD	SHOW TIME: TBD

REV: Rev 1.0 Deep Think

SHOW TIME: TBD

Ch	Instrument	Mic / DI	Patch	48V	Stand	Notes
■ DRUMS						
1	Kick In	Shure Beta 91A	Local 1	✓	Bar	Beta 91A/D6 two-mic kick — 91A is the attack/click layer inside on the batter head. Treat the pair as ONE: same VCA, pan together, blend constant. Polarity: sum in mono, flip one mic if thinner. Bus: notch -2/-3 @300-500 if it builds.
2	Kick Out	Audix D6	Local 2		Boom	Beta 91A/D6 two-mic kick — D6 is the body/thump core at the port. Treat the pair as one; pan together, same VCA.
3	Snare Top	Audix i5	Local 3		Clip	Gate to reject hat/kick bleed without chopping ghost notes; release to tempo.
5	Hi-Hat	Sennheiser e609	Local 5		Clip	e609 on hat is unusual (it's a cab dynamic) — placement/rejection driven on a loud stage. Light ducker over a hard gate. FLAG mic choice.
6	Rack 1	Audix D2	Local 6		Clip	Gate release matched to the kit's decay.
8	Floor	Audix D4	Local 8		Clip	Gate release long enough to keep the floor's natural decay.
9	OH L	Shure SM57	Local 9		Tall	SM57 overheads — dark, bleed-rejecting for a loud open stage. Polarity check OH L vs OH R in mono; flip if the sum thins.
10	OH R	Shure SM57	Local 10		Tall	Matched to OH L. Polarity check vs Ch 9 — sum in mono, flip if thinner.
■ BASS						
11	Bass DI	Whirlwind IMP (passive DI)	Local 11		DI	Passive DI. Gentle comp to even note-to-note level.
■ GUITAR						

Ch	Instrument	Mic / DI	Patch	48V	Stand	Notes
13	Guitar	Shure SM57	Local 13		Boom	Bennett doubles banjo (Ch 15) and guitar — only one is live at a time. Single 57 (no ribbon blend outdoors).
15	Banjo	Whirlwind IMP (passive DI)	Local 15		DI	Same player as Ch 13 — one live at a time. DI off the banjo pickup.
■ KEYS						
17	Keys	DI (XLR)	Local 17		DI	Direct out via XLR. FLAG: confirm mono vs stereo (single fader assumed).
■ HORNS						
18	Sax	Audio-Technica Pro 35	Local 18	✓	Clip	Clip-on; player moves (2nd-line). Fast-attack comp — brass transients jump.
19	Trombone	Audio-Technica Pro 35	Local 19	✓	Clip	Clip on the bell; player moves. Fast-attack comp.
20	Trumpet	Audio-Technica Pro 35	Local 20	✓	Clip	Clip on the bell; player moves. Fast-attack comp.
■ VOCALS						
25	Vocal 1	Shure Beta 58A	Local 25		Tall	Jason Burkett — lead. Cuts-only (feedback rule). Comp to even; expander opens on breath. OVERRIDES the FSQ template vocal curve on fader 25 — confirm on console.
26	Vocal 2	Shure Beta 58A	Local 26		Tall	Backing / shared (horn players sing gang vocals). Matched to Vocal 1. Mark SPARE if unused. Overrides template baseline on fader 26.

■ DRUMS ■

Ch 1 | Kick In

Mic: Shure Beta 91A

Mic Notes: Boundary on the batter head — the attack/click engine. Keep its lows tucked under the D6.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	40 Hz	LC	—	—	High-pass
4	3.5 kHz	Bell	+4 dB	1.2	
3	500 Hz	Bell	-3 dB	2	
2	250 Hz	Bell	-3 dB	1.8	
1	70 Hz	Bell	+3 dB	1.2	
HC	—	HC	—	—	No LPF

Engineer Notes: +4 @ 3.5k gives beater definition that carries in open air; box (500) and mud (250) cuts eased because outdoor has far less low-mid buildup than a room; modest +3 @ 70 so it doesn't stack on the D6's voiced lows.

Ch 2 | Kick Out

Mic: Audix D6

Mic Notes: D6 is pre-scooped with a voiced ~4k click and big lows — it barely needs EQ; let it own the body.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	30 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	400 Hz	Bell	-2 dB	2	
2	—	OFF	—	—	Flat
1	60 Hz	Bell	+3 dB	1.2	
HC	—	HC	—	—	No LPF

Engineer Notes: Almost flat by design — +3 @ 60 restores the weight open air eats, a small 400 nudge only if it builds. Top left alone: the D6's click is already voiced in and the 91A carries the real attack.

Ch 3 | Snare Top

Mic: Audix i5

Mic Notes: i5 is punchy and mid-forward with its own 4-5k presence — ease the crack boost so it doesn't get spiky.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	100 Hz	LC	—	—	High-pass
4	5 kHz	Bell	+2 dB	1.4	
3	500 Hz	Bell	-3 dB	1.8	
2	220 Hz	Bell	-2 dB	1.6	
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: Small +2 @ 5k for cut in open air (the i5 is already forward); 500 box cut for clarity; only a light 220 trim so the backbeat keeps its body — party-band snare wants pop and thump, not a thin rock crack.

Ch 5 | Hi-Hat

Mic: Sennheiser e609

Mic Notes: e609 is a flat-face cab dynamic — a hard ~4-5k presence, edgy 2.5-4k, and no airy top extension. It's here for rejection on a loud stage, not sheen.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	500 Hz	LC	—	—	High-pass
4	3.5 kHz	Bell	-3 dB	1.6	
3	800 Hz	Bell	-3 dB	2	
2	—	OFF	—	—	Flat
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: HPF hard at 500 to dump snare/kick bleed; tame the e609 edge at 3.5k and the 800 clank. No top boost — the mic doesn't reach there, and the overheads carry cymbal air. FLAG: confirm e609 vs. SM81/SM57 on the hat.

Ch 6 | Rack 1

Mic: Audix D2

Mic Notes: D2 is voiced for mid toms — punchy with its own low-mid weight; mostly needs mud control.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	80 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	450 Hz	Bell	-3 dB	1.8	
2	—	OFF	—	—	Flat
1	110 Hz	Bell	+2 dB	1.2	
HC	—	HC	—	—	No LPF

Engineer Notes: -3 @ 450 clears low-mid mud; +2 @ 110 restores body outdoors. Attack left alone — the D2 has its own punch and open air doesn't need extra stick.

Ch 8 | Floor

Mic: Audix D4

Mic Notes: D4 extends lower than the D2 — the floor's low-end owner.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	45 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	400 Hz	Bell	-3 dB	1.8	
2	—	OFF	—	—	Flat
1	80 Hz	Bell	+3 dB	1.2	
HC	—	HC	—	—	No LPF

Engineer Notes: +3 @ 80 supports the boom open air swallows; -3 @ 400 keeps it from getting woofy. Top left natural.

Ch 9 | OH L

Mic: Shure SM57

Mic Notes: SM57 as OH = deliberately dark and bleed-rejecting; it won't give natural cymbal sheen, hence the small air lift.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	200 Hz	LC	—	—	High-pass
4	10 kHz	Bell	+2 dB	1	
3	3 kHz	Bell	-3 dB	1.6	
2	400 Hz	Bell	-3 dB	1.8	
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: +2 @ 10k gently restores the sizzle the 57 can't reach (like lifting a closed piano lid — a physical loss, not a mix choice); 3k honk and 400 box cut clean the cymbal wash. Polarity-check the pair in mono.

Ch 10 | OH R

Mic: Shure SM57

Mic Notes: Matched pair with OH L.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	200 Hz	LC	—	—	High-pass
4	10 kHz	Bell	+2 dB	1	
3	3 kHz	Bell	-3 dB	1.6	
2	400 Hz	Bell	-3 dB	1.8	
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: Matched to OH L — same dark-dynamic recovery curve. Polarity-check the pair in mono and flip one if the sum thins.

Ch 11 | Bass DI

Mic: Whirlwind IMP (passive DI)

Mic Notes: Whirlwind IMP passive DI — honest and flat, no active sparkle, so definition is an EQ job.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	35 Hz	LC	—	—	High-pass
4	800 Hz	Bell	+2 dB	1.2	
3	300 Hz	Bell	-3 dB	1.8	
2	—	OFF	—	—	Flat
1	80 Hz	Bell	+3 dB	1.2	
HC	—	HC	—	—	No LPF

Engineer Notes: +3 @ 80 anchors the low end open air eats; +2 @ 800 adds finger/growl definition that travels past the subs' throw for the dancers up front; 300 mud cut keeps it tight.

Ch 13 | Guitar

Mic: Shure SM57

Mic Notes: Mid-forward and proximity-prone — the cab box at 400 and the honk at 3k are the usual 57 suspects.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	100 Hz	LC	—	—	High-pass
4	3 kHz	Bell	-2 dB	1.6	
3	400 Hz	Bell	-4 dB	1.8	
2	—	OFF	—	—	Flat
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: -4 @ 400 kills the cab box; -2 @ 3k tames the 57 honk while leaving the upper presence so rhythm chank cuts. Sits under the horns — carve, don't feature.

Ch 15 | Banjo

Mic: Whirlwind IMP (passive DI)

Mic Notes: DI off a banjo pickup — very bright and plunky, much more HF than a guitar pickup and thin on body.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	120 Hz	LC	—	—	High-pass
4	4 kHz	Bell	-4 dB	1.6	
3	800 Hz	Bell	-3 dB	2	
2	200 Hz	Bell	+2 dB	1.2	
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: -4 @ 4k pulls the piezo/pickup zing that gets strident through a big PA; +2 @ 200 restores body the pickup can't; 800 plunk cut cleans the attack.

■ KEYS ■

Ch 17 | Keys

Mic: DI (XLR)

Mic Notes: Clean direct source — EQ is about carving space around bass/guitar/horns, not correcting a mic.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	40 Hz	LC	—	—	High-pass
4	3 kHz	Bell	-2 dB	1.4	
3	300 Hz	Bell	-3 dB	1.6	
2	—	OFF	—	—	Flat
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: -3 @ 300 opens room for the bass and low brass; -2 @ 3k softens any hard upper-mid from a digital piano/organ patch. Confirm mono vs stereo at patch.

■ HORNS ■

Ch 18 | Sax

Mic: Audio-Technica Pro 35

Mic Notes: Pro 35 is warmer than most clip-ons but slightly treble-forward and thin down low; takes screaming SPL without complaint.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	80 Hz	LC	—	—	High-pass
4	6 kHz	Bell	-2 dB	1.4	
3	1 kHz	Bell	-3 dB	1.6	
2	400 Hz	Bell	+2 dB	1.2	
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: Sax needs its upper harmonics to cut in a horn stack, so the top trim is gentle (-2 @ 6k, just the plastic edge); +2 @ 400 fills the body the clip loses; -3 @ 1k keeps the reed from barking.

Ch 19 | Trombone

Mic: Audio-Technica Pro 35

Mic Notes: Low brass — its own weight at 200-300; the blat lives at 700-900. Pro 35 clip takes the bell SPL fine.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	60 Hz	LC	—	—	High-pass
4	5 kHz	Bell	-2 dB	1.4	
3	800 Hz	Bell	-3 dB	1.8	
2	250 Hz	Bell	+2 dB	1.2	
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: +2 @ 250 keeps the bone warm and full; -3 @ 800 tames the blat; light -2 @ 5k off the clip's top. Kept musical — this is the fat middle of the horn line.

Ch 20 | Trumpet

Mic: Audio-Technica Pro 35

Mic Notes: Brightest of the three horns; the blare zone is 2-4k when it's wailing. Pro 35 handles a lead trumpet at 4 inches without folding.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	120 Hz	LC	—	—	High-pass
4	6 kHz	Bell	-2 dB	1.4	
3	2.5 kHz	Bell	-3 dB	1.6	
2	—	OFF	—	—	Flat
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: -3 @ 2.5k tames the blare so the lead lines don't ice the ears through the A15s; light top trim off the clip. Left mostly open — the trumpet is the horn line's cutting edge and shouldn't be dulled.

■ VOCALS ■

Ch 25 | Vocal 1

Mic: Shure Beta 58A

Mic Notes: Beta 58A — brighter than an SM58 with TWO presence peaks (~4k and ~10k) and a tighter pattern for more gain before feedback on the open stage; those peaks can get strident.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	110 Hz	LC	—	—	High-pass
4	4 kHz	Bell	-3 dB	2	DYNAMIC: thr=-18dB atk=3ms rel=120ms — bites only on peaks
3	600 Hz	Bell	-3 dB	1.8	
2	250 Hz	Bell	-2 dB	1.6	
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: Cuts only. DEQ the 4k peak so it ducks only when he leans in; 600 box is the main feedback breeder outdoors; 250 proximity trim. Let the mic's own 10k air carry the top — no boosts.

Ch 26 | Vocal 2

Mic: Shure Beta 58A

Mic Notes: Backing/shared vocal — matched to Vocal 1.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	110 Hz	LC	—	—	High-pass
4	4 kHz	Bell	-3 dB	2	DYNAMIC: thr=-18dB atk=3ms rel=120ms — bites only on peaks
3	600 Hz	Bell	-3 dB	1.8	
2	250 Hz	Bell	-2 dB	1.6	
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: Same cuts-only curve as Vocal 1. If it goes unused, pull it to SPARE; if a horn player is on it for shout choruses, it's ready.