

Izzy Escobar

FOH CHANNEL EQ SETUP — DiGiCo Quantum 225

Show	Izzy Escobar
Show Date	2026-06-26
Venue	Fountain Square (outdoor)
Console	DiGiCo Quantum 225
Channels	19
FOH Engineer	Brian Lloyd
Monitor Engineer	Sam Carpenter
Show Time	9:00pm
Rev	Rev 2.0 Deep Think

DOCUMENT CONTENTS

- 1. Cover Page — show, venue, and personnel
- 2. Input List — color-coded full channel patch sheet
- 3. Patching — AES and Local inputs sorted by port
- 4. EQ Setup — 19 channels for DiGiCo Quantum 225
- 5. Reference — EQ structure, pan guide, bus grouping, soundcheck order

SHOW STYLE: Pop-soul / indie-R&B.; Restraint over aggression — subtractive, musical, protect the vocal's warmth. Open-air FSQ: support lows + presence to carry, no room to hide in. Deep-research pass.

Izzy Escobar

VENUE: Fountain Square (outdoor)

DATE: 2026-06-26

REV: Rev 2.0 Deep Think

FOH: Brian Lloyd

MON: Sam Carpenter

SHOW TIME: 9:00pm

Ch	Instrument	Mic / DI	Patch	48V	Stand	Notes
■ DRUMS						
1	Kick In	Shure Beta 91A	Local 1	✓	Boom	Beta 91A/52A kick blend — 91A is the attack/click layer. Treat the pair as ONE: same VCA, pan together, blend constant. Polarity: sum in mono, flip on one mic if thinner. Bus: notch -2/-3 dB @300-500 if it builds.
2	Kick Out	Shure Beta 52A	Local 2		Boom	Beta 91A/52A kick blend — 52A is the body/punch core. Treat the pair as one; pan together, same VCA.
3	Snare Top	Audix i5	Local 3		Boom	
5	Hat	Shure SM81	Local 5	✓	Boom	
6	Rack 1	Audix D2	Local 6		Boom	
7	Rack 2	Audix D2	Local 7		Boom	
8	Floor	Audix D4	Local 8		Boom	
9	OH HL	Shure SM81	Local 9	✓	Boom	
10	OH HR	Shure SM81	Local 10	✓	Boom	
■ RHYTHM						
11	Bass DI	XLR (DI)	Local 11		DI	Bass DI + SM57 cab blend: DI = weight + low-mid warmth, 57 = punch + air. Group to one VCA, polarity-check against the 57.
12	Bass Mic	Shure SM57	Local 12		DI	Blend with the DI — see Bass DI note.
13	Guitar 57	Shure SM57	Local 13		DI	SM57/Beta 27 blend — 57 owns mids, 27 owns air + body. Don't double the 2.5k. Same VCA, polarity-check.
14	Guitar 27	Shure Beta 27	Local 14	✓	DI	SM57/Beta 27 blend — 27 carries the air + clean body the 57 lacks.
15	Acoustic Guitar	BSS AR-133	Local 15		DI	
17	Keys	Whirlwind IMP (DI)	Local 17		DI	
18	Click	Whirlwind IMP (DI)	Local 18		DI	
19	Guide	Whirlwind IMP (DI)	Local 19		DI	

Ch	Instrument	Mic / DI	Patch	48V	Stand	Notes
20	Tracks	Whirlwind IMP (DI)	Local 20		DI	
■ VOCALS						
25	Izzy	Neumann KMS 105	Local 25	✓	Tall	

■ DRUMS ■

Ch 1 | Kick In

Mic: Shure Beta 91A

Mic Notes: Boundary mic inside the kick — the attack engine; let it own the click, keep its lows tucked under the 52A.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	40 Hz	LC	—	18 dB/oct	High-pass
4	3 kHz	Bell	+4 dB	1.2	
3	600 Hz	Bell	-2 dB	2	
2	250 Hz	Bell	-3 dB	1.8	
1	80 Hz	Bell	+3 dB	1.2	
HC	—	HC	—	—	No LPF

Engineer Notes: +4@3k beater definition that travels outdoors (eased from +5 — pop-soul punch, not a metal click). Lows modest so they don't stack with the 52A. 250 box cut eased to -3: open air has far less low-mid buildup than a room.

Ch 2 | Kick Out

Mic: Shure Beta 52A

Mic Notes: Body/punch engine at the port.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	40 Hz	LC	—	18 dB/oct	High-pass
4	3 kHz	Bell	+3 dB	1.2	
3	600 Hz	Bell	-2 dB	2	
2	250 Hz	Bell	-3 dB	1.8	
1	80 Hz	Bell	+5 dB	1.2	
HC	—	HC	—	—	No LPF

Engineer Notes: +5@80 supports the weight open air swallows; small 3k snap (the 91A carries the real click). Mud cut eased for outdoors.

Ch 3 | Snare Top

Mic: Audix i5

Mic Notes: i5 has a built-in ~3.5k presence peak + scooped mids; more body, less boxy than an SM57.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	120 Hz	LC	—	18 dB/oct	High-pass
4	7 kHz	Bell	+2 dB	0.8	
3	5.5 kHz	Bell	-2 dB	2	
2	1 kHz	Bell	+3 dB	1	
1	300 Hz	Bell	-5 dB	2	
HC	—	HC	—	—	No LPF

Engineer Notes: Crack boost small (+3@1k) and box cut -5 not -7 — the capsule isn't boxy, don't gut it. +2@7k snap to cut outdoors; -2@5.5k tames ring.

Ch 5 | Hat

Mic: Shure SM81

Mic Notes: SM81 — smooth, un-hyped highs.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	500 Hz	LC	—	18 dB/oct	High-pass
4	—	OFF	—	—	Flat
3	—	OFF	—	—	Flat
2	2 kHz	Bell	-5 dB	1.2	
1	800 Hz	Bell	-6 dB	1.5	
HC	16 kHz	HC	—	—	Low-pass

Engineer Notes: No HF boost needed; just clear the low bleed (800) and the 2k clang so it sparkles without harshness.

Ch 6 | Rack 1

Mic: Audix D2

Mic Notes: D2 is tuned to control tom resonance; articulate with little EQ.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	90 Hz	LC	—	18 dB/oct	High-pass
4	—	OFF	—	—	Flat
3	2.8 kHz	Bell	+4 dB	1	
2	450 Hz	Bell	-3 dB	1.8	
1	135 Hz	Bell	+3 dB	1.2	
HC	12 kHz	HC	—	—	Low-pass

Engineer Notes: Attack lift eased to +4 — trust the capsule; gentle body, modest mud cut.

Ch 7 | Rack 2

Mic: Audix D2

Mic Notes: As Rack 1, shifted down for the larger drum.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	80 Hz	LC	—	18 dB/oct	High-pass
4	—	OFF	—	—	Flat
3	2.525 kHz	Bell	+4 dB	1	
2	405 Hz	Bell	-3 dB	1.8	
1	120 Hz	Bell	+3 dB	1.2	
HC	12 kHz	HC	—	—	Low-pass

Engineer Notes: Let the D2 do the work.

Ch 8 | Floor

Mic: Audix D4

Mic Notes: D4 reaches an octave lower than the D2 natively.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	55 Hz	LC	—	18 dB/oct	High-pass
4	—	OFF	—	—	Flat
3	1.8 kHz	Bell	+4 dB	1	
2	405 Hz	Bell	-3 dB	1.8	
1	70 Hz	Shelf	+4 dB	0.71	
HC	10 kHz	HC	—	—	Low-pass

Engineer Notes: Body shelf stays modest (+4) — support, not a big lift; ride the sub outdoors. Attack at 1.8k for stick definition.

Ch 9 | OH HL

Mic: Shure SM81

Mic Notes: Cymbal sheen + kit glue.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	180 Hz	LC	—	18 dB/oct	High-pass
4	—	OFF	—	—	Flat
3	—	OFF	—	—	Flat
2	5 kHz	Bell	+3 dB	0.8	
1	300 Hz	Bell	-5 dB	1.5	
HC	—	HC	—	—	No LPF

Engineer Notes: +3@5k eased from +5 — SM81 is already detailed; a big lift gets brittle over a long outdoor throw. 300 clears low wash.

Ch 10 | OH HR

Mic: Shure SM81

Mic Notes: Matched to OH HL — keep the stereo pair identical.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	180 Hz	LC	—	18 dB/oct	High-pass
4	—	OFF	—	—	Flat
3	—	OFF	—	—	Flat
2	5 kHz	Bell	+3 dB	0.8	
1	300 Hz	Bell	-5 dB	1.5	
HC	—	HC	—	—	No LPF

Engineer Notes: Same as OH HL.

Ch 11 | Bass DI

Mic: XLR (DI)

Mic Notes: DI carries the lows the cab mic can't.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	40 Hz	LC	—	18 dB/oct	High-pass
4	1.5 kHz	Bell	-5 dB	1.5	
3	600 Hz	Bell	+5 dB	1	
2	250 Hz	Bell	-6 dB	2	
1	80 Hz	Shelf	+5 dB	0.71	
HC	—	HC	—	—	No LPF

Engineer Notes: Soul/Motown bass = dark, round, low-mid forward, top rolled. +5@600 is the Motown 'wool'; -5@1.5k tames string clank; -6@250 keeps it off the kick/cab; +5@80 foundation.

Ch 12 | Bass Mic

Mic: Shure SM57

Mic Notes: 57 rolls off below ~200 — not a low source; it's the punch/air mid layer over the DI.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	60 Hz	LC	—	18 dB/oct	High-pass
4	—	OFF	—	—	Flat
3	900 Hz	Bell	+5 dB	1	
2	400 Hz	Bell	-7 dB	2	
1	100 Hz	Shelf	+5 dB	0.71	
HC	5 kHz	HC	—	—	Low-pass

Engineer Notes: +5@900 grind; -7@400 carves a pocket so it doesn't double the DI mud. LPF 5k keeps the dark soul character.

Ch 13 | Guitar 57

Mic: Shure SM57

Mic Notes: 57 owns the mid grit + presence core.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	100 Hz	LC	—	18 dB/oct	High-pass
4	2.5 kHz	Bell	+4 dB	1	
3	800 Hz	Bell	+3 dB	1.2	
2	450 Hz	Bell	-5 dB	2	
1	200 Hz	Bell	-4 dB	2	
HC	—	HC	—	—	No LPF

Engineer Notes: Dreamy/supportive guitar (not a rock wall): mid boosts eased so it sits under the vocal. Box at 450; 200 cleared so it doesn't stack with the 27's body.

Ch 14 | Guitar 27

Mic: Shure Beta 27

Mic Notes: Bright detailed condenser — value is the air + clean low body the 57 lacks.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	100 Hz	LC	—	18 dB/oct	High-pass
4	9 kHz	Bell	+4 dB	0.8	
3	800 Hz	Bell	+1 dB	1.2	
2	450 Hz	Bell	-2 dB	2	
1	120 Hz	Shelf	+2 dB	0.71	
HC	—	HC	—	—	No LPF

Engineer Notes: Re-thought from a KB default: instead of doubling the 57 at 2.5k, give it air at 9k + clean body at 120 and stay out of the mids. 57 owns mids, 27 owns air+body — no doubling.

Ch 15 | Acoustic Guitar

Mic: BSS AR-133

Mic Notes: AR-133 is clean/transparent; the source is a piezo — quack at 1-3k, brassy at ~5k.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	100 Hz	LC	—	18 dB/oct	High-pass
4	8 kHz	Shelf	+3 dB	0.71	
3	2 kHz	Bell	-6 dB	1.8	DYNAMIC: thr=-12dB atk=5ms rel=80ms — bites only on peaks
2	400 Hz	Bell	-5 dB	2	
1	200 Hz	Shelf	+4 dB	0.71	
HC	—	HC	—	—	No LPF

Engineer Notes: Biggest fix vs the KB default: air moved OFF 5k (that's the brassy piezo zone you cut) up to 8k. The -6@2k quack cut made DYNAMIC so it only bites on loud strums without gutting sustain; -5@400 box; +4@200 body the piezo lacks.

Ch 17 | Keys

Mic: Whirlwind IMP (DI)

Mic Notes: Piano is central to her writing.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	60 Hz	LC	—	18 dB/oct	High-pass
4	—	OFF	—	—	Flat
3	2.5 kHz	Bell	+4 dB	0.8	
2	300 Hz	Bell	+3 dB	0.8	
1	200 Hz	Bell	-5 dB	1.5	
HC	—	HC	—	—	No LPF

Engineer Notes: Warmth (+3@300) + a little clarity (+4@2.5k, eased) without hype; -5@200 clears mud so it doesn't crowd the bass + vocal low-mids.

Ch 18 | Click

Mic: Whirlwind IMP (DI)

Mic Notes: Utility / cue.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	80 Hz	LC	—	18 dB/oct	High-pass
4	—	OFF	—	—	Flat
3	—	OFF	—	—	Flat
2	315 Hz	Bell	-4 dB	2	
1	200 Hz	Shelf	-2 dB	0.71	
HC	—	HC	—	—	No LPF

Engineer Notes: Mud trimmed so it's clean in the players' ears. CONFIRM: monitors / IEM only — never assigned to FOH.

Ch 19 | Guide

Mic: Whirlwind IMP (DI)

Mic Notes: Guide vocal / cue track.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	80 Hz	LC	—	18 dB/oct	High-pass
4	—	OFF	—	—	Flat
3	—	OFF	—	—	Flat
2	315 Hz	Bell	-4 dB	2	
1	200 Hz	Shelf	-2 dB	0.71	
HC	—	HC	—	—	No LPF

Engineer Notes: Same utility treatment. *CONFIRM:* monitors / IEM only — not in FOH.

Ch 20 | Tracks

Mic: Whirlwind IMP (DI)

Mic Notes: Mastered, full-range stem (her lush strings/synths/BGV bed).

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	30 Hz	LC	—	18 dB/oct	High-pass
4	—	OFF	—	—	Flat
3	—	OFF	—	—	Flat
2	—	OFF	—	—	Flat
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: Re-thought: it's already balanced — EQ'ing it like a mic'd source thins the production. Left near-flat (HPF 30 only). Add a small 315 trim live ONLY if it clouds the band.

■ VOCALS ■

Ch 25 | Izzy

Mic: Neumann KMS 105

Mic Notes: KMS 105 — transparent, smooth 7-12k presence, NOT a sibilant mic. Wired handheld on a stand (not the wireless system).

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	110 Hz	LC	—	18 dB/oct	High-pass
4	7.5 kHz	Bell	-3 dB	3	DYNAMIC: thr=-18dB atk=3ms rel=120ms — bites only on peaks
3	1.6 kHz	Bell	-3 dB	1.4	
2	300 Hz	Bell	-4 dB	2	
1	—	OFF	—	—	Flat
HC	15 kHz	HC	—	—	Low-pass

Engineer Notes: The show lives here. Killed the static -5@8k for a DYNAMIC de-ess that only acts on sibilant peaks — keep the air a soul voice wants. HPF pulled to 110 (mic compensates proximity, won't boom) to protect the throaty Winehouse chest body. -3@1.6k gentle nasal; -4@300 box for outdoor intelligibility. Protective + subtractive, not aggressive. NOTE: this overrides the template's wireless vocal baseline (removes its -18@5k feedback notch) — watch for feedback at soundcheck; reach for the Mustard comp + a touch of plate before any more EQ.