

The Hot Magnolias

FOH CHANNEL EQ SETUP — DiGiCo Quantum 225

Show	The Hot Magnolias
Show Date	2026-07-11
Venue	Fountain Square (outdoor)
Console	DiGiCo Quantum 225
Channels	17
FOH Engineer	Brian Lloyd
Monitor Engineer	TBD
Show Time	TBD
Rev	Rev 2.0 Deep Think (hot-mag 2)

DOCUMENT CONTENTS

1. Cover Page — show, venue, and personnel
2. Input List — color-coded full channel patch sheet
3. Patching — AES and Local inputs sorted by port
4. EQ Setup — 17 channels for DiGiCo Quantum 225
5. Reference — EQ structure, pan guide, bus grouping, soundcheck order

SHOW STYLE: Horn-forward New Orleans party band — warm and danceable, three-horn front line carries the show.

The Hot Magnolias		
VENUE: Fountain Square (outdoor)	DATE: 2026-07-11	REV: Rev 2.0 Deep Think (hot-mag 2)
FOH: Brian Lloyd	MON: TBD	SHOW TIME: TBD

REV: Rev 2.0 Deep Think
(hot-mag 2)

SHOW TIME: TBD

Ch	Instrument	Mic / DI	Patch	48V	Stand	Notes
■ DRUMS						
1	Kick In	Shure Beta 91A	Local 1	✓	Bar	Beta 91A/D6 two-mic kick — 91A is the attack/click layer inside on the batter head. Treat the pair as ONE: same VCA, pan together. Polarity: sum in mono, flip one mic if thinner. Bus: notch @300-500 if it builds.
2	Kick Out	Audix D6	Local 2		Boom	Beta 91A/D6 two-mic kick — D6 is the body/thump core at the port. Same VCA, pan together.
3	Snare Top	Audix i5	Local 3		Clip	Gate to reject hat/kick bleed without chopping ghost notes; release to tempo.
5	Hi-Hat	Sennheiser e609	Local 5		Clip	e609 on hat is unusual (a cab dynamic) — placement/rejection driven on a loud stage. Light ducker over a hard gate. FLAG mic choice.
6	Rack 1	Audix D2	Local 6		Clip	Gate release matched to the kit's decay.
8	Floor	Audix D4	Local 8		Clip	Gate release long enough to keep the natural decay.
9	Overheads	Shure SM57 (pair)	Local 9		Tall	STEREO pair on fader 9 (NOT split 9/10 — fader 10 is the SNARE PL8 return). Dark dynamics for a loud open stage. Polarity check L vs R within the pair — sum in mono, flip if it thins.
■ BASS						
11	Bass DI	Whirlwind IMP (passive DI)	Local 11		DI	Passive DI. Gentle comp to even note-to-note.
■ GUITAR						

Ch	Instrument	Mic / DI	Patch	48V	Stand	Notes
13	Guitar Dyn	Shure SM57	Local 13		Boom	57/27 blend on ONE amp — SM57 = body/grind primary. Same VCA as CH14; pan together; polarity check vs CH14 CRITICAL (sum in mono, flip if thinner); notch @300-500 on the bus if it builds. Bennett doubles Banjo (CH15).
14	Guitar CON	Shure Beta 27	Local 14	✓	Boom	57/27 blend on the SAME amp — Beta 27 = bright condenser complement. Same VCA as CH13; polarity check vs CH13 CRITICAL. 48V (Beta 27 is a condenser).
15	Banjo	Whirlwind IMP (passive DI)	Local 15		DI	Same player as CH13/14 guitar — one live at a time. DI off the banjo pickup.
■ KEYS						
17	Keys	DI (XLR)	Local 17		DI	Direct out via XLR. FLAG: confirm mono vs stereo (single fader assumed).
■ HORNS						
18	Sax	Audio-Technica Pro 35	Local 18	✓	Clip	Clip-on; player moves (2nd-line). Fast-attack comp.
19	Trombone	Audio-Technica Pro 35	Local 19	✓	Clip	Clip on the bell; player moves. Fast-attack comp.
20	Trumpet	Audio-Technica Pro 35	Local 20	✓	Clip	Clip on the bell; player moves. Fast-attack comp.
■ VOCALS						
25	Vocal 1	Shure Beta 58A	Local 25		Tall	Jason Burkett — lead. Cuts-only (feedback rule). Comp to even; expander opens on breath. OVERRIDES the FSQ template vocal curve on fader 25 — confirm on console.
26	Vocal 2	Shure Beta 58A	Local 26		Tall	Backing / shared (horn players sing gang vocals). Matched to Vocal 1. Mark SPARE if unused. Overrides template baseline on fader 26.

■ DRUMS ■

Ch 1 | Kick In

Mic: Shure Beta 91A

Mic Notes: Boundary on the batter head — the attack/click engine. Keep its lows tucked under the D6.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	40 Hz	LC	—	—	High-pass
4	3.5 kHz	Bell	+4 dB	1.2	
3	500 Hz	Bell	-8 dB	2	
2	250 Hz	Bell	-6 dB	1.8	
1	70 Hz	Bell	+3 dB	1.2	
HC	—	HC	—	—	No LPF

Engineer Notes: +4 @ 3.5k for beater definition that carries in open air; box (-8 @ 500) and mud (-6 @ 250) cut DEEP for outdoor clarity; +3 @ 70 support so the weight survives the throw without stacking on the D6.

Ch 2 | Kick Out

Mic: Audix D6

Mic Notes: D6 is pre-scooped with a voiced ~4k click and big lows — let it own the body.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	30 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	400 Hz	Bell	-6 dB	2	
2	—	OFF	—	—	Flat
1	60 Hz	Bell	+3 dB	1.2	
HC	—	HC	—	—	No LPF

Engineer Notes: Near-flat by design — +3 @ 60 restores the weight open air eats; -6 @ 400 cleans the boxy port honk (deeper than a room would need). Top left alone — the 91A carries the attack.

Ch 3 | Snare Top

Mic: Audix i5

Mic Notes: i5 is punchy and mid-forward with its own 4-5k presence — small crack boost only.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	100 Hz	LC	—	—	High-pass
4	5 kHz	Bell	+2 dB	1.4	
3	500 Hz	Bell	-7 dB	1.8	
2	220 Hz	Bell	-4 dB	1.6	
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: +2 @ 5k for cut in open air; box cut DEEP (-7 @ 500) for outdoor clarity; only -4 @ 220 so the backbeat keeps body (220 is the drum's body, not mud — the deep cut goes on the box).

Ch 5 | Hi-Hat

Mic: Sennheiser e609

Mic Notes: e609 = flat-face cab dynamic — a hard ~4-5k presence, edgy 2.5-4k, no airy top. Here for rejection, not sheen.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	500 Hz	LC	—	—	High-pass
4	3.5 kHz	Bell	-7 dB	1.6	
3	800 Hz	Bell	-6 dB	2	
2	—	OFF	—	—	Flat
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: HPF hard at 500 to dump bleed; the e609 edge (–7 @ 3.5k) and clank (–6 @ 800) cut deep for open-air clarity. No top boost — the OHs carry cymbal air. FLAG: confirm e609 vs SM81/SM57.

Ch 6 | Rack 1

Mic: Audix D2

Mic Notes: D2 is voiced for mid toms — punchy with its own weight; mostly mud control.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	80 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	450 Hz	Bell	-7 dB	1.8	
2	—	OFF	—	—	Flat
1	110 Hz	Bell	+2 dB	1.2	
HC	—	HC	—	—	No LPF

Engineer Notes: -7 @ 450 clears low-mid mud (deep for outdoor clarity); +2 @ 110 restores body. Attack left alone.

Ch 8 | Floor

Mic: Audix D4

Mic Notes: D4 extends lower than the D2 — the floor's low-end owner.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	45 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	400 Hz	Bell	-7 dB	1.8	
2	—	OFF	—	—	Flat
1	80 Hz	Bell	+3 dB	1.2	
HC	—	HC	—	—	No LPF

Engineer Notes: +3 @ 80 supports the boom open air swallows; -7 @ 400 keeps it from getting woofy (deep for clarity). Top natural.

Ch 9 | Overheads

Mic: Shure SM57 (pair)

Mic Notes: SM57 pair as OH = deliberately dark and bleed-rejecting; won't give natural sheen, hence the small air lift.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	200 Hz	LC	—	—	High-pass
4	10 kHz	Bell	+2 dB	1	
3	3 kHz	Bell	-6 dB	1.6	
2	400 Hz	Bell	-7 dB	1.8	
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: +2 @ 10k gently restores the sizzle the 57 can't reach (a physical loss, not tone-shaping); 57 honk (-6 @ 3k) and box/bleed (-7 @ 400) cut deep for open-air clarity. Internal L/R polarity check in mono.

Ch 11 | Bass DI

Mic: Whirlwind IMP (passive DI)

Mic Notes: Whirlwind IMP passive DI — honest and flat, no active sparkle, so definition is an EQ job.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	35 Hz	LC	—	—	High-pass
4	800 Hz	Bell	+2 dB	1.2	
3	300 Hz	Bell	-7 dB	1.8	
2	—	OFF	—	—	Flat
1	80 Hz	Bell	+3 dB	1.2	
HC	—	HC	—	—	No LPF

Engineer Notes: +3 @ 80 anchors the low end open air eats; +2 @ 800 adds finger/growl definition that travels past the subs; -7 @ 300 clears the mud deep so it stays tight outdoors.

Ch 13 | Guitar Dyn

Mic: Shure SM57

Mic Notes: SM57 is the body/grind primary in the blend — owns the mids; the Beta 27 adds the top.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	100 Hz	LC	—	—	High-pass
4	3 kHz	Bell	-4 dB	1.6	
3	400 Hz	Bell	-8 dB	1.8	
2	—	OFF	—	—	Flat
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: -8 @ 400 kills the cab box deep for outdoor clarity; -4 @ 3k tames the 57 honk while leaving upper presence so rhythm chank cuts. Primary of the pair — the 27 sits on top of this.

Ch 14 | Guitar CON

Mic: Shure Beta 27

Mic Notes: Beta 27 (LDC) = the bright/air complement on the same cab; low-mids backed off hard so it doesn't stack on the 57.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	150 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	800 Hz	Bell	-6 dB	1.8	
2	400 Hz	Bell	-8 dB	1.8	
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: HPF up at 150 and deep 400/800 cuts keep it out of the 57's body — it's here for top-end detail only. Polarity vs CH13 is CRITICAL; flip if the mono sum thins. Its natural top is left to carry — no boost.

Ch 15 | Banjo

Mic: Whirlwind IMP (passive DI)

Mic Notes: DI off a banjo pickup — very bright, plunky, much more HF than a guitar pickup and thin on body.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	120 Hz	LC	—	—	High-pass
4	4 kHz	Bell	-8 dB	1.6	
3	800 Hz	Bell	-6 dB	2	
2	200 Hz	Bell	+2 dB	1.2	
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: -8 @ 4k pulls the piezo zing that gets strident through a big PA (deep for open air); -6 @ 800 cleans the plunk; +2 @ 200 restores body the pickup can't.

■ KEYS ■

Ch 17 | Keys

Mic: DI (XLR)

Mic Notes: Clean direct source — EQ carves space around bass/guitar/horns, not correcting a mic.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	40 Hz	LC	—	—	High-pass
4	3 kHz	Bell	-4 dB	1.4	
3	300 Hz	Bell	-7 dB	1.6	
2	—	OFF	—	—	Flat
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: -7 @ 300 opens deep room for the bass and low brass (outdoor clarity); -4 @ 3k softens any hard upper-mid from a digital piano/organ patch. Confirm mono vs stereo at patch.

■ HORNS ■

Ch 18 | Sax

Mic: Audio-Technica Pro 35

Mic Notes: Pro 35 is warmer than most clip-ons but slightly treble-forward and thin down low; takes screaming SPL.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	80 Hz	LC	—	—	High-pass
4	6 kHz	Bell	-3 dB	1.4	
3	1 kHz	Bell	-6 dB	1.6	
2	400 Hz	Bell	+2 dB	1.2	
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: Reed honk cut deep (-6 @ 1k) for clarity in the horn stack; +2 @ 400 fills the body the clip loses; top trim stays GENTLE (-3 @ 6k) — the sax needs its overtones to cut, so the deep-cut rule spares the presence.

Ch 19 | Trombone

Mic: Audio-Technica Pro 35

Mic Notes: Low brass — weight at 200-300; blat at 700-900. Pro 35 clip takes the bell SPL fine.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	60 Hz	LC	—	—	High-pass
4	5 kHz	Bell	-3 dB	1.4	
3	800 Hz	Bell	-6 dB	1.8	
2	250 Hz	Bell	+2 dB	1.2	
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: +2 @ 250 keeps the bone warm and full; blat cut deep (-6 @ 800); top trim gentle (-3 @ 5k). Musical — this is the fat middle of the horn line.

Ch 20 | Trumpet

Mic: Audio-Technica Pro 35

Mic Notes: Brightest of the three horns; blare zone 2-4k when it wails. Pro 35 handles a lead trumpet at 4 inches.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	120 Hz	LC	—	—	High-pass
4	6 kHz	Bell	-3 dB	1.4	
3	2.5 kHz	Bell	-6 dB	1.6	
2	—	OFF	—	—	Flat
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: Blare cut deep (–6 @ 2.5k) so the lead lines don't ice the ears through the A15s; top trim gentle (–3 @ 6k). Left otherwise open — the trumpet is the horn line's cutting edge.

■ VOCALS ■

Ch 25 | Vocal 1

Mic: Shure Beta 58A

Mic Notes: Beta 58A — brighter than an SM58 with TWO presence peaks (~4k and ~10k), tighter pattern for more gain before feedback outdoors; those peaks can get strident.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	110 Hz	LC	—	—	High-pass
4	4 kHz	Bell	-4 dB	2	DYNAMIC: thr=-18dB atk=3ms rel=120ms — bites only on peaks
3	600 Hz	Bell	-8 dB	1.8	
2	250 Hz	Bell	-5 dB	1.6	
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: Cuts only, deeper for open air. DEQ the 4k peak so it ducks only when he leans in; 600 box cut DEEP (-8) — the main feedback breeder outdoors; -5 @ 250 proximity. Mic's own 10k air carries the top — no boosts.

Ch 26 | Vocal 2

Mic: Shure Beta 58A

Mic Notes: Backing/shared vocal — matched to Vocal 1.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	110 Hz	LC	—	—	High-pass
4	4 kHz	Bell	-4 dB	2	DYNAMIC: thr=-18dB atk=3ms rel=120ms — bites only on peaks
3	600 Hz	Bell	-8 dB	1.8	
2	250 Hz	Bell	-5 dB	1.6	
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: Same cuts-only deeper curve as Vocal 1. If unused, pull to SPARE; ready if a horn player takes it for shout choruses.

The Hot Magnolias — FOH EQ Rationale

Fountain Square (outdoor) · DiGiCo Quantum 225 · 2026-07-11 · Rev 2.0 Deep Think (hot-mag 2)

Artist. The Hot Magnolias — Cincinnati 8-piece New Orleans party band (formed 2013; CCM players and scene vets). Repertoire runs 1920s trad-jazz standards through Mardi Gras 2nd-line to 70s NOLA funk. Live lineup: Jason Burkett (lead vocals), David Sharkey (sax), Chapman Sowash (trombone), Michael Cruse (trumpet), Kevin McClellan (bass), Jamarco Thomas (keys/piano), Bennett Kottler (banjo/guitar — one player doubling), Ryan Mitchell (drums/perc). The three-horn front line and the party energy ARE the show: mix horn-forward, warm and danceable — not a scooped rock sound.

Room. Fountain Square open-air: no room gain, lows and HF dissipate over the throw, downtown noise floor + wind tighten gain-before-feedback. FSQ runs cuts DEEPER than indoor (−6 to −9 dB typical, up to −10 on mud/box) — clarity is the whole game outdoors — while supporting lows and presence the open air swallows. Cuts-first on everything, vocals cuts-only. Mid-July show window: warm/dry air = extra HF loss over distance, so horn/vocal presence is protected, not over-cut; watch wind wash on the open mics.

Research. Band/lineup: Bandcamp, CincyMusic, NKYTribune. Per-source: A-T Pro 35 (warm-for-a-clip-on, slightly treble-forward, thin lows, 145 dB, 80 Hz LC); NOLA brass mixing (frequency-slot the three horns, keep overtones so they cut); banjo pickup DI (far more HF than a guitar pickup, needs top roll-off + body). KB eq-starting-points + mic-library for the kit, bass DI, SM57 overheads, Beta 58A; reverb-reference (Seventh Heaven Pro, FSQ section).

Monitors. MIX 1 Lead Vocal — Jason (wedge) · MIX 2 Horns — Sax/Tbn/Tpt front line (wedge) · MIX 3 Drums — Ryan (wedge) · MIX 4 Bass + Keys (wedge) · MIX 5 Guitar/Banjo — Bennett (wedge) · Counts/splits confirm at soundcheck — 8× L-Acoustics X12 on the M32.

What changed from the KB default / prior rev — and why

- REV 2 vs Rev 1 (run-1 console pass, 2026-07-08): FSQ cuts re-cut DEEPER — box/mud now −6 to −9 (up to −10). Rev 1 eased them for outdoor; the console pass reversed that: open air needs clarity, not a room's forgiveness.
- Overheads are now a STEREO pair on fader 9 (SM57 pair) — Rev 1 wrongly split OH L/R across 9/10; fader 10 is the reserved SNARE PL8 return and is left alone.
- Guitar is now a 57/27 blend on ONE amp: CH13 Guitar Dyn (SM57, body/grind primary) + CH14 Guitar CON (Beta 27, bright complement). Complement's low-mids backed off hard so it doesn't stack; polarity check vs CH13 is CRITICAL.
- Kick In (Beta 91A) carries the attack; Kick Out (D6) left near-flat (pre-voiced) — no stacked HF boost.
- Horns (Pro 35): low-mid honk/box cut deeper, but top trims stay gentle (−3) — NOLA brass needs its overtones to cut through the A15s; the deeper-cut rule targets mud/box, not horn presence.
- Banjo DI zing pulled −8 @ 4k; body added at 200.
- Vocal 1/2 cuts-only, deeper 600 box cut + DEQ on the Beta 58A 4k peak — OVERRIDES the FSQ template vocal curve + feedback notch on faders 25/26. Confirm on the console.
- Reverb section now shipped (Seventh Heaven Pro) per the 2026-07-08 FSQ rule — sends stay judicious outdoors; whether they come up is Brian's call at the desk.

Question round — what was asked, what Brian decided

- Run-1 console pass → FSQ cuts run DEEPER (−6 to −9, up to −10 mud/box). This rev re-cut accordingly.
- Run-1 console pass → OH is a STEREO pair on fader 9; fader 10 is SNARE PL8 return. OH R removed; overheads are one stereo channel on ch 9.
- Input list rev → CH13/14 are a 57/27 blend on one guitar amp (Guitar Dyn / Guitar CON), treated as a two-mic source.

- Reverb → full Seventh Heaven Pro section shipped on every FSQ show (2026-07-08 rule).
- Open flags carried from run 1 (Brian to rule at load-in): Hi-Hat on e609 (vs SM81/57); Keys mono vs stereo; vocal mics were blank — Jason on Beta 58A lead, CH26 shared/backing, rest SPARE.
- Bennett doubles Guitar (CH13/14 blend) + Banjo (CH15) — one live at a time; all patched.

Reverb — Seventh Heaven Pro (100% wet returns)

- **VOCAL — Plates 1 / #06 Vocal Plate** | Settings: Decay 1.4s · PreDelay 24ms · VLF -16 · E/L Max Early · Late -4 · Late Rolloff 9k · 100% wet | In-plugin EQ: LC 180 Hz on the return; leave the top bright (outdoors loses HF over distance); Late Rolloff up to 9k | Why: The default lead verb — dense, forward plate that gives Jason placement without wash on the up-tempo 2nd-line tunes.
- **VOCAL — Chambers 1 / #10 Vocal Chamber** | Settings: Decay 1.3s · PreDelay 20ms · VLF -12 · E/L Max Early · Late -6 · Late Rolloff 8k · 100% wet | In-plugin EQ: LC 160 Hz; Ducker in Reverb mode, Thr -22 dB, Release 250 ms so it clears between phrases | Why: Warmer place for the slow/torch numbers; the ducker keeps it out of the way when he's driving the up-tempo material.
- **VOCAL — Plates 1 / #01 Bright Plate** | Settings: Decay 1.4s · PreDelay 0 · VLF -15 · E/L Max Early · Late Equal · Late Rolloff 10k · 100% wet | In-plugin EQ: LC 200 Hz; keep it bright (Late Rolloff 10k) for cut | Why: Reach for it only on the loudest shouters where the lead needs extra sheen to slice over the full horn line.
- **INSTRUMENT — Halls 1 / #15 Brass Hall** | Settings: Decay 1.7s · PreDelay 20ms · VLF -11 · E/L Max Early · Late -6 · Late Rolloff 8k · 100% wet | In-plugin EQ: Master Filter HS -2 @ 8k to take the edge off three close clip mics; LC 120 Hz | Why: The horn-section verb — one shared hall so sax/bone/trumpet read as a single front line, kept shorter/darker than the vocal plates so it places the horns without stacking tail on the groove.
- **INSTRUMENT — Rooms 1 / #10 Large Wooden** | Settings: Decay 0.75s · PreDelay 0 · VLF -12 · E/L Max Early · Late Equal · Late Rolloff 9k · 100% wet | In-plugin EQ: LC 150 Hz; leave bright | Why: A hair of natural wood air for banjo/guitar if they feel dry against the horns — barely up, placement only.
- **GENERAL — Rooms 1 / #01 Studio A** | Settings: Decay 0.6s · PreDelay 4ms · VLF -6 · E/L Max Early · Late Equal · Late Rolloff 9k · 100% wet | In-plugin EQ: LC 120 Hz; very small send | Why: Transparent glue over the whole band if the mix feels disconnected outdoors — depth, not effect.
- **USING THEM TOGETHER** — Vocal Plate is the default lead verb for the up-tempo 2nd-line material; hand off to Vocal Chamber (ducked) for the slow/torch numbers, and reach for Bright Plate only on the loudest shouters where the lead needs extra sheen to cut the horns. Brass Hall sits under the three horns as their shared room — shorter and a touch darker than the vocal plates so it places the front line without stacking tail. Large Wooden and Studio A stay near-off; bring them up only if the banjo/guitar feel dry or the band needs glue. Outdoors gives nothing back and wash competes with building slap, so every send stays judicious — placement, not effect.

DRUMS

Ch 1 | Kick In · Shure Beta 91A

HPF 40 | LPF off || B4 +4@3.5 kHz Q1.2 BELL B3 -8@500 Hz Q2 BELL B2 -6@250 Hz Q1.8 BELL B1 +3@70 Hz Q1.2 BELL

Boundary on the batter head — the attack/click engine. Keep its lows tucked under the D6.

+4 @ 3.5k for beater definition that carries in open air; box (-8 @ 500) and mud (-6 @ 250) cut DEEP for outdoor clarity; +3 @ 70 support so the weight survives the throw without stacking on the D6.

Ch 2 | Kick Out · Audix D6

HPF 30 | LPF off || B4 flat B3 -6@400 Hz Q2 BELL B2 flat B1 +3@60 Hz Q1.2 BELL

D6 is pre-scooped with a voiced ~4k click and big lows — let it own the body.

Near-flat by design — +3 @ 60 restores the weight open air eats; -6 @ 400 cleans the boxy port honk (deeper than a room would need). Top left alone — the 91A carries the attack.

Ch 3 | Snare Top · Audix i5

HPF 100 | LPF off || B4 +2@5 kHz Q1.4 BELL B3 -7@500 Hz Q1.8 BELL B2 -4@220 Hz Q1.6 BELL B1 flat

i5 is punchy and mid-forward with its own 4-5k presence — small crack boost only.

+2 @ 5k for cut in open air; box cut DEEP (–7 @ 500) for outdoor clarity; only –4 @ 220 so the backbeat keeps body (220 is the drum's body, not mud — the deep cut goes on the box).

Ch 5 | Hi-Hat · Sennheiser e609

HPF 500 | LPF off || B4 -7@3.5 kHz Q1.6 BELL B3 -6@800 Hz Q2 BELL B2 flat B1 flat

e609 = flat-face cab dynamic — a hard ~4-5k presence, edgy 2.5-4k, no airy top. Here for rejection, not sheen.

HPF hard at 500 to dump bleed; the e609 edge (–7 @ 3.5k) and clank (–6 @ 800) cut deep for open-air clarity. No top boost — the OHs carry cymbal air. FLAG: confirm e609 vs SM81/SM57.

Ch 6 | Rack 1 · Audix D2

HPF 80 | LPF off || B4 flat B3 -7@450 Hz Q1.8 BELL B2 flat B1 +2@110 Hz Q1.2 BELL

D2 is voiced for mid toms — punchy with its own weight; mostly mud control.

–7 @ 450 clears low-mid mud (deep for outdoor clarity); +2 @ 110 restores body. Attack left alone.

Ch 8 | Floor · Audix D4

HPF 45 | LPF off || B4 flat B3 -7@400 Hz Q1.8 BELL B2 flat B1 +3@80 Hz Q1.2 BELL

D4 extends lower than the D2 — the floor's low-end owner.

+3 @ 80 supports the boom open air swallows; –7 @ 400 keeps it from getting woofy (deep for clarity). Top natural.

Ch 9 | Overheads · Shure SM57 (pair)

HPF 200 | LPF off || B4 +2@10 kHz Q1 BELL B3 -6@3 kHz Q1.6 BELL B2 -7@400 Hz Q1.8 BELL B1 flat

SM57 pair as OH = deliberately dark and bleed-rejecting; won't give natural sheen, hence the small air lift.

+2 @ 10k gently restores the sizzle the 57 can't reach (a physical loss, not tone-shaping); 57 honk (–6 @ 3k) and box/bleed (–7 @ 400) cut deep for open-air clarity. Internal L/R polarity check in mono.

BASS

Ch 11 | Bass DI · Whirlwind IMP (passive DI)

HPF 35 | LPF off || B4 +2@800 Hz Q1.2 BELL B3 -7@300 Hz Q1.8 BELL B2 flat B1 +3@80 Hz Q1.2 BELL

Whirlwind IMP passive DI — honest and flat, no active sparkle, so definition is an EQ job.

+3 @ 80 anchors the low end open air eats; +2 @ 800 adds finger/growl definition that travels past the subs; –7 @ 300 clears the mud deep so it stays tight outdoors.

GUITAR

Ch 13 | Guitar Dyn · Shure SM57

HPF 100 | LPF off || B4 -4@3 kHz Q1.6 BELL B3 -8@400 Hz Q1.8 BELL B2 flat B1 flat

SM57 is the body/grind primary in the blend — owns the mids; the Beta 27 adds the top.

−8 @ 400 kills the cab box deep for outdoor clarity; −4 @ 3k tames the 57 honk while leaving upper presence so rhythm chank cuts. Primary of the pair — the 27 sits on top of this.

Ch 14 | Guitar CON · Shure Beta 27

HPF 150 | LPF off || B4 flat B3 -6@800 Hz Q1.8 BELL B2 -8@400 Hz Q1.8 BELL B1 flat

Beta 27 (LDC) = the bright/air complement on the same cab; low-mids backed off hard so it doesn't stack on the 57.

HPF up at 150 and deep 400/800 cuts keep it out of the 57's body — it's here for top-end detail only. Polarity vs CH13 is CRITICAL; flip if the mono sum thins. Its natural top is left to carry — no boost.

Ch 15 | Banjo · Whirlwind IMP (passive DI)

HPF 120 | LPF off || B4 -8@4 kHz Q1.6 BELL B3 -6@800 Hz Q2 BELL B2 +2@200 Hz Q1.2 BELL B1 flat

DI off a banjo pickup — very bright, plunky, much more HF than a guitar pickup and thin on body.

−8 @ 4k pulls the piezo zing that gets strident through a big PA (deep for open air); −6 @ 800 cleans the plunk; +2 @ 200 restores body the pickup can't.

KEYS

Ch 17 | Keys · DI (XLR)

HPF 40 | LPF off || B4 -4@3 kHz Q1.4 BELL B3 -7@300 Hz Q1.6 BELL B2 flat B1 flat

Clean direct source — EQ carves space around bass/guitar/horns, not correcting a mic.

−7 @ 300 opens deep room for the bass and low brass (outdoor clarity); −4 @ 3k softens any hard upper-mid from a digital piano/organ patch. Confirm mono vs stereo at patch.

HORNS

Ch 18 | Sax · Audio-Technica Pro 35

HPF 80 | LPF off || B4 -3@6 kHz Q1.4 BELL B3 -6@1 kHz Q1.6 BELL B2 +2@400 Hz Q1.2 BELL B1 flat

Pro 35 is warmer than most clip-ons but slightly treble-forward and thin down low; takes screaming SPL.

Reed honk cut deep (−6 @ 1k) for clarity in the horn stack; +2 @ 400 fills the body the clip loses; top trim stays GENTLE (−3 @ 6k) — the sax needs its overtones to cut, so the deep-cut rule spares the presence.

Ch 19 | Trombone · Audio-Technica Pro 35

HPF 60 | LPF off || B4 -3@5 kHz Q1.4 BELL B3 -6@800 Hz Q1.8 BELL B2 +2@250 Hz Q1.2 BELL B1 flat

Low brass — weight at 200-300; blat at 700-900. Pro 35 clip takes the bell SPL fine.

+2 @ 250 keeps the bone warm and full; blat cut deep (−6 @ 800); top trim gentle (−3 @ 5k). Musical — this is the fat middle of the horn line.

Ch 20 | Trumpet · Audio-Technica Pro 35

HPF 120 | LPF off || B4 -3@6 kHz Q1.4 BELL B3 -6@2.5 kHz Q1.6 BELL B2 flat B1 flat

Brightest of the three horns; blare zone 2-4k when it wails. Pro 35 handles a lead trumpet at 4 inches.

Blare cut deep (–6 @ 2.5k) so the lead lines don't ice the ears through the A15s; top trim gentle (–3 @ 6k). Left otherwise open — the trumpet is the horn line's cutting edge.

VOCALS

Ch 25 | Vocal 1 · Shure Beta 58A

HPF 110 | LPF off || B4 -4@4 kHz Q2 BELL +DEQ B3 -8@600 Hz Q1.8 BELL B2 -5@250 Hz Q1.6 BELL B1 flat

Beta 58A — brighter than an SM58 with TWO presence peaks (~4k and ~10k), tighter pattern for more gain before feedback outdoors; those peaks can get strident.

Cuts only, deeper for open air. DEQ the 4k peak so it ducks only when he leans in; 600 box cut DEEP (–8) — the main feedback breeder outdoors; –5 @ 250 proximity. Mic's own 10k air carries the top — no boosts.

Ch 26 | Vocal 2 · Shure Beta 58A

HPF 110 | LPF off || B4 -4@4 kHz Q2 BELL +DEQ B3 -8@600 Hz Q1.8 BELL B2 -5@250 Hz Q1.6 BELL B1 flat

Backing/shared vocal — matched to Vocal 1.

Same cuts-only deeper curve as Vocal 1. If unused, pull to SPARE; ready if a horn player takes it for shout choruses.

Deep-research pass — values reasoned from mic behavior, instrument, genre, the artist's references, and the room. Informed starting points, not gospel; trust your ears at soundcheck.