

The Hot Magnolias

FOH CHANNEL EQ SETUP — DiGiCo Quantum 225

Show	The Hot Magnolias
Show Date	2026-07-11
Venue	Fountain Square (outdoor)
Console	DiGiCo Quantum 225
Channels	17
FOH Engineer	Brian Lloyd
Monitor Engineer	TBD
Show Time	TBD
Rev	Rev 3.0 Deep Think (hot-mag 3 — blind rebuild)

DOCUMENT CONTENTS

1. Cover Page — show, venue, and personnel
2. Input List — color-coded full channel patch sheet
3. Patching — AES and Local inputs sorted by port
4. EQ Setup — 17 channels for DiGiCo Quantum 225
5. Reference — EQ structure, pan guide, bus grouping, soundcheck order

SHOW STYLE: Horn-forward New Orleans party band — warm, danceable, three-horn front line carries the show.

The Hot Magnolias

VENUE: Fountain Square (outdoor)

DATE: 2026-07-11

REV: Rev 3.0 Deep Think
(hot-mag 3 — blind rebuild)

FOH: Brian Lloyd

MON: TBD

SHOW TIME: TBD

Ch	Instrument	Mic / DI	Patch	48V	Stand	Notes
■ DRUMS						
1	Kick In	Shure Beta 91A	Local 1	✓	Bar	91A/D6 two-mic kick — 91A inside on the batter, the attack/click layer. Treat the pair as ONE: same VCA, pan together, sum in mono and flip one if thinner. Contour switch FLAT (box cut is on the desk).
2	Kick Out	Audix D6	Local 2		Short	91A/D6 two-mic kick — D6 at the port, the body/thump core. Same VCA as CH1, pan together, polarity-check the pair in mono.
3	Snare Top	Audix i5	Local 3		Clip	Second-line snare is the motor of this band — gate light or not at all; ghost notes and press rolls must live. Release to tempo.
5	Hi-Hat	Sennheiser e609	Local 5		Boom	e609 on a hat is a cab mic doing hat duty — spec'd deliberately. Supercardioid rejection is the win; aim the null at the snare.
6	Rack 1	Audix D2	Local 6		Clip	Gate release matched to the kit's decay.
8	Floor Tom	Audix D4	Local 8		Clip	Gate release long enough to keep the natural decay.
9	OH	Shure SM57 (pair)	Local 9		Tall	STEREO pair on fader 9 — fader 10 is the reserved SNARE PL8 return, leave it alone (Brian ruled). Cymbals + kit glue, not the primary kit sound.
■ BASS						
11	Bass DI	Whirlwind IMP (passive DI)	Local 11		DI	Passive DI — neutral but slightly soft on top. Gentle comp to even note-to-note; the pocket with keys LH is the dance floor.

Ch	Instrument	Mic / DI	Patch	48V	Stand	Notes
■ GUITAR						
13	Guitar Dyn	Shure SM57	Local 13		Short	57/27 blended on the SAME amp — 57 is the primary (grit/presence). Same VCA as CH14, pan together, keep the blend constant. Polarity-check the pair in mono.
14	Guitar CON	Shure Beta 27	Local 14	✓	Short	57/27 blend, SAME amp — Beta 27 is the bright complement. Same VCA as CH13, pan together. POLARITY CHECK vs CH13 is critical: sum in mono, flip if thinner. Notch 300–500 on the bus if it builds.
15	Banjo	Whirlwind IMP (passive DI)	Local 15		DI	Same player as CH13/14 guitar — one live at a time. DI off the banjo pickup, piezo-type character.
■ KEYS						
17	Keys	DI (XLR)	Local 17		DI	Direct out via XLR. FLAG: confirm mono vs stereo at load-in (single fader assumed).
■ HORNS						
18	Sax	Audio-Technica Pro 35	Local 18	✓	Clip	Clip-on; player roams (2nd-line). Fast-attack comp (10–20 ms, 3:1) — brass transients jump.
19	Trombone	Audio-Technica Pro 35	Local 19	✓	Clip	Clip on the bell; player roams. Fast-attack comp same as sax.
20	Trumpet	Audio-Technica Pro 35	Local 20	✓	Clip	Clip on the bell; player roams. Fast-attack comp; trumpet is the loudest thing on stage.
■ VOCALS						
25	Vocal 1	Shure Beta 58A	Local 25		Tall	Jason Burkett — lead. CUTS ONLY (feedback rule). Comp to even the shout-to-croon range; expander opens on breath. OVERRIDES the FSQ template wireless curve/notch on this fader — confirm on console.

Ch	Instrument	Mic / DI	Patch	48V	Stand	Notes
26	Vocal 2	Shure Beta 58A	Local 26		Tall	Backing / shared — horn players sing gang vocals. Matched to Vocal 1 so it's a working SPARE for the lead. Same template-override flag as CH25.

■ DRUMS ■

Ch 1 | Kick In

Mic: Shure Beta 91A

Mic Notes: Boundary on the head — beater snap plus known shell boxiness at 300–500 (KB + PSW). Contour switch would cut 400 by 7 dB; assumed flat.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	50 Hz	LC	—	—	High-pass
4	5 kHz	Bell	+4 dB	1.4	
3	400 Hz	Bell	-7 dB	1.8	
2	200 Hz	Bell	-5 dB	1.8	
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: +4 @ 5k gives the beater the definition that survives open air; -7 @ 400 kills the shell box deep per the FSQ rule; -5 @ 200 keeps its lows tucked so the D6 owns the body. HPF 50 for the same reason — this channel is the click engine, not the weight.

Ch 2 | Kick Out

Mic: Audix D6

Mic Notes: Pre-scooped smiley voicing — peaks ~60 Hz and ~5k, -15 dB mid scoop at 600 baked in (Gearspace/RecordingHacks + KB agree: needs almost no EQ).

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	30 Hz	LC	—	—	High-pass
4	5 kHz	Bell	-4 dB	1.6	
3	350 Hz	Bell	-4 dB	2	
2	—	OFF	—	—	Flat
1	60 Hz	Bell	+3 dB	1.2	
HC	—	HC	—	—	No LPF

Engineer Notes: -4 @ 5k trims the D6's baked click so it doesn't stack on the 91A's +4 — the layers stay split. -4 @ 350 is a light touch on what the capsule didn't already scoop. +3 @ 60 feeds the KS21s: outdoors there's no room gain, the subs carry all the weight.

Ch 3 | Snare Top

Mic: Audix i5

Mic Notes: i5 bakes in +9 dB @ 5.5k presence and a +5 dB body lift ~150 (SOS/Gearspace + KB). The crack is already in the capsule.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	100 Hz	LC	—	—	High-pass
4	5.5 kHz	Bell	-3 dB	2.5	
3	500 Hz	Bell	-7 dB	1.8	
2	—	OFF	—	—	Flat
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: The baked 5.5k peak IS the cut-through — just -3 @ 5.5k to take its harsh edge off the A15s. -7 @ 500 dumps the box deep per FSQ. The 150 body lift stays untouched: second-line snare wants that fatness. Ring gets handled live if the head speaks.

Ch 5 | Hi-Hat

Mic: Sennheiser e609

Mic Notes: Bright 4–5k presence voiced for guitar cabs, edgy 2.5–4k on bright sources, thin lows (helpful here). Rolled top vs a condenser — don't chase air that isn't in the capsule.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	500 Hz	LC	—	—	High-pass
4	3.5 kHz	Bell	-6 dB	1.8	
3	900 Hz	Bell	-6 dB	2	
2	—	OFF	—	—	Flat
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: HPF 500 per the hat rule — everything below is bleed. -6 @ 3.5k tames the capsule's cab-voiced edge before it turns cymbal wash spitty; -6 @ 900 clears snare-bleed clank. In a trad-jazz set the hat rides the time — it needs to be clean, not loud.

Ch 6 | Rack 1

Mic: Audix D2

Mic Notes: Scooped mids and voiced attack baked in; leaner deep lows than the D4 (DFO/Gearspace + KB).

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	80 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	500 Hz	Bell	-6 dB	1.8	
2	—	OFF	—	—	Flat
1	120 Hz	Bell	+2 dB	1.2	
HC	—	HC	—	—	No LPF

Engineer Notes: -6 @ 500 finishes the cardboard the capsule's scoop started — deep per FSQ. +2 @ 120 puts back the body the D2 runs lean on. Attack is already voiced in; no top boost.

Ch 8 | Floor Tom

Mic: Audix D4

Mic Notes: Reaches 35 Hz, smooth unscooped mids, less upper-mid attack than the D2 (KB flags it may need a touch of click).

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	40 Hz	LC	—	—	High-pass
4	4 kHz	Bell	+2 dB	1.4	
3	450 Hz	Bell	-7 dB	1.8	
2	—	OFF	—	—	Flat
1	80 Hz	Bell	+3 dB	1.2	
HC	—	HC	—	—	No LPF

Engineer Notes: The D4 doesn't scoop its own mids, so the -7 @ 450 mud cut does the work here. +3 @ 80 for weight into the subs, +2 @ 4k adds the click the capsule undersells — a funk floor tom outdoors disappears without it.

Ch 9 | OH

Mic: Shure SM57 (pair)

Mic Notes: 57s as overheads = deliberately dark, mid-forward cymbals (TapeOp/PSW consensus); box 300–500 and presence clang 3–5k are the known problems, top end rolls off early.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	250 Hz	LC	—	—	High-pass
4	10 kHz	Bell	+3 dB	1	
3	3 kHz	Bell	-5 dB	1.8	
2	400 Hz	Bell	-6 dB	1.6	
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: +3 @ 10k as a wide bell (not a shelf) opens the top the 57 doesn't have — outdoors the air dies over the throw and these are the only cymbal mics. -5 @ 3k pulls the clang the 57's presence bump makes of crash wash; -6 @ 400 dumps the kit box. HPF 250: everything below lives in the close mics.

■ BASS ■

Ch 11 | Bass DI

Mic: Whirlwind IMP (passive DI)

Mic Notes: IMP is honest with a slight passive HF/level loss (KB) — no active sparkle to lean on.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	35 Hz	LC	—	—	High-pass
4	800 Hz	Bell	+2 dB	1.4	
3	350 Hz	Bell	-7 dB	1.8	
2	—	OFF	—	—	Flat
1	80 Hz	Bell	+3 dB	1.2	
HC	—	HC	—	—	No LPF

Engineer Notes: +3 @ 80 is the funk punch into the KS21s; -7 @ 350 clears the mud lane deep per FSQ so keys and guitar can live there; +2 @ 800 is the definition/growl (research: 700 Hz–2k is where bass reads past the subs on a plaza).
Fundamental-plus-harmonics, not just weight.

Ch 13 | Guitar Dyn

Mic: Shure SM57

Mic Notes: Mid-forward workhorse: presence 3–5k, box/honk builds 300–500 on cabs (KB + every forum thread ever).

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	100 Hz	LC	—	—	High-pass
4	3.2 kHz	Bell	-4 dB	2	
3	400 Hz	Bell	-8 dB	1.8	
2	—	OFF	—	—	Flat
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: NOLA funk guitar is clean chunk, not high-gain wall — the 57's presence is the scratch, so only -4 @ 3.2k to keep the A15s from getting scratchy. -8 @ 400 dumps the cab box hard (FSQ deep rule); the Beta 27 fills the body cleanly instead.

Ch 14 | Guitar CON

Mic: Shure Beta 27

Mic Notes: Flat 60–3k with small peaks at 5.5k and 9k — the clean open top the 57 lacks; slight 9k fizz on bright amps (KB).

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	150 Hz	LC	—	—	High-pass
4	9 kHz	Bell	-3 dB	2.5	
3	500 Hz	Bell	-7 dB	1.2	
2	—	OFF	—	—	Flat
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: Complement rule: its low-mids come down so it can't stack on the 57's midrange — -7 @ 500 at a wide Q1.2 covers the 150–800 dump. -3 @ 9k takes the fizz off before the open air exposes it. Its job is body and top; the 57 owns the middle.

Ch 15 | Banjo

Mic: Whirlwind IMP (passive DI)

Mic Notes: Banjo pickups carry far more HF zing than a guitar pickup plus the piezo quack; the IMP passes it all through honestly (KB: treat at the desk).

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	120 Hz	LC	—	—	High-pass
4	5 kHz	Bell	-7 dB	1.6	
3	1.2 kHz	Bell	-6 dB	1.8	
2	220 Hz	Bell	+2 dB	1.4	
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: -6 @ 1.2k centers the nasal quack (Banjo Hangout consensus: 0.8–1.6k); -7 @ 5k kills the brittle zing before it ice-picks the plaza. +2 @ 220 puts back the wood/head body the pickup misses — trad-jazz banjo is a rhythm chunk, it should sound like an instrument, not a transducer.

■ KEYS ■

Ch 17 | Keys

Mic: DI (XLR)

Mic Notes: Clean line source — EQ is mix carving, not correction (KB).

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	40 Hz	LC	—	—	High-pass
4	3 kHz	Bell	-3 dB	2	
3	300 Hz	Bell	-6 dB	1.6	
2	—	OFF	—	—	Flat
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: NOLA piano (the Longhair/Booker rolls) lives in the mids, so the work is making room around it: -6 @ 300 clears DI low-mid warmth against the PA, -3 @ 3k bows to the horns in their lane. HPF 40 keeps the left hand — the piano bass matters when the band drops to keys and snare.

■ HORNS ■

Ch 18 | Sax

Mic: Audio-Technica Pro 35

Mic Notes: Pro 35: voiced presence lift, subtly rounded treble, thin lows, plasticky upper-mid when close (maker + KB agree). 145 dB — level is never the problem.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	80 Hz	LC	—	—	High-pass
4	6 kHz	Bell	-4 dB	1.8	
3	1 kHz	Bell	-6 dB	1.6	
2	400 Hz	Bell	+2 dB	1.2	
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: Sax owns the ~2k slot in the three-horn line, so its cut sits at 1k (–6, clears the bone's lane and its own honk). –4 @ 6k takes the clip-mic plastic glare; +2 @ 400 warms the thin capsule so the sax reads full, not reedy. Overtones stay — NOLA horns cut with harmonics, not volume.

Ch 19 | Trombone

Mic: Audio-Technica Pro 35

Mic Notes: Same Pro 35 character — rounded treble, voiced presence, thin lows.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	60 Hz	LC	—	—	High-pass
4	5 kHz	Bell	-4 dB	1.8	
3	600 Hz	Bell	-6 dB	1.8	
2	250 Hz	Bell	+2 dB	1.2	
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: Bone owns the ~1k slot (research: it differentiates there), so nothing is cut at 1k — the blat/box comes out below it at -6 @ 600. -4 @ 5k for the clip glare, +2 @ 250 for the low warmth that makes a trombone sound like brass plumbing instead of a kazoo. HPF 60 keeps the pedal-range weight.

Ch 20 | Trumpet

Mic: Audio-Technica Pro 35

Mic Notes: Pro 35 on a trumpet bell: the voiced presence plus trumpet's natural 1–4k aggression is the thing to manage, not encourage.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	150 Hz	LC	—	—	High-pass
4	3.5 kHz	Bell	-3 dB	2	
3	1.1 kHz	Bell	-5 dB	1.8	
2	—	OFF	—	—	Flat
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: Trumpet owns 3k-and-up in the slotting, so only a -3 trim at 3.5k keeps it from dominating the A15s while the brilliance above stays intact. -5 @ 1.1k clears its honk out of the bone's lane. HPF 150 per the research consensus — nothing useful below. It'll still lead the section; that's the job.

■ VOCALS ■

Ch 25 | Vocal 1

Mic: Shure Beta 58A

Mic Notes: Beta 58A: two baked presence peaks (4k and 10k), sub-500 attenuated for proximity control, supercardioid = the gain-before-feedback pick outdoors (Shure spec + KB).

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	120 Hz	LC	—	—	High-pass
4	4 kHz	Bell	-4 dB	2	DYNAMIC: thr=-18dB atk=3ms rel=120ms — bites only on peaks
3	600 Hz	Bell	-8 dB	1.8	
2	250 Hz	Bell	-5 dB	1.6	
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: Cuts only. -8 @ 600 is the box cut where feedback builds first — deep per FSQ. -5 @ 250 handles the proximity mud when he eats the mic on the shouters. The 4k peak gets a DYNAMIC -4 (thr -18, 3 ms/120 ms): it only clamps when he leans in hot, so intelligibility stays the rest of the time. The 10k peak is left alone — that's the only air a cuts-only channel gets.

Ch 26 | Vocal 2

Mic: Shure Beta 58A

Mic Notes: Matched to CH25.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	120 Hz	LC	—	—	High-pass
4	4 kHz	Bell	-4 dB	2	DYNAMIC: thr=-18dB atk=3ms rel=120ms — bites only on peaks
3	600 Hz	Bell	-8 dB	1.8	
2	250 Hz	Bell	-5 dB	1.6	
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: Identical to Vocal 1 — gang vocals hit it loose and off-axis, and matching means it doubles as the lead spare without a rebuild mid-show.