

Input List Summary

Ch	Instrument	Mic / DI
1	Kick	Beta52
2	Snare	SM57
3	High Hat	SM81
4	Rack Tom	Sennheiser 604
5	Floor Tom	Sennheiser 604
6	Overhead Left	SM81
7	Overhead Right	SM81
8	Bass	DI
9	Leslie High Left	SM57
10	Leslie High Right	SM57
11	Leslie Bottom	SM57
12	Clavinet	Sennheiser 609
13	Electric Guitar	Royer R10
14	Fiddle Amp	Royer R10
15	Acoustic Guitar	DI
16	Accordion	DI
17	Scrub Board	SM57
18	Jeb Vocal	Beta58
19	Tara Vocal	Beta58

Ch 1 – Kick — Beta52

Section	Parameter / Value	Details
HPF	40 Hz @ 24 dB/Oct	
LPF	18 kHz @ 24 dB/Oct	
Band1 Low (Lowshelf)	+5 dB @ 80 Hz	Q 1.0
Band2 Lower-Mid (Parametric)	-6 dB @ 400 Hz	Q 2.0; Dyn On
Band3 Upper-Mid	+2 dB @ 3.5 kHz	Q 1.2
Band4 High Shelf	+3 dB @ 8 kHz	Q 0.7
Dynamics 1 - Compressor	On	Compressor Thr -10 dB Ratio 4:1 A 10 ms R 100 ms Gain +3 dB
Dynamics 2 - Gate	On	Thr -45 dB A 6 ms H 25 ms R 150 ms Range 70 dB
Notes		

EQ tailored for Kick using Beta52. Enhances tone, clarity, and stage separation. Adjust for room resonances at soundcheck.

Ch 2 – Snare — SM57

Section	Parameter / Value	Details
HPF	80 Hz @ 24 dB/Oct	
LPF	18 kHz @ 24 dB/Oct	
Band1 Low	+3 dB @ 200 Hz	Q 1.2
Band2 Low-Mid	-5 dB @ 350 Hz	Q 2.2; Dyn On
Band3 Upper-Mid	+3 dB @ 3.0 kHz	Q 1.2
Band4 High Shelf	+4 dB @ 10 kHz	Q 0.8
Dynamics 1 - Compressor	On	Compressor Thr -10 dB Ratio 4:1 A 10 ms R 100 ms Gain +3 dB
Dynamics 2 - Gate	On	Thr -45 dB A 6 ms H 25 ms R 150 ms Range 70 dB
Notes		

EQ tailored for Snare using SM57. Enhances tone, clarity, and stage separation. Adjust for room resonances at soundcheck.

Ch 3 – High Hat — SM81

Section	Parameter / Value	Details
HPF	80 Hz @ 24 dB/Oct	
LPF	18 kHz @ 24 dB/Oct	
Band1 Low	+2 dB @ 120 Hz	Q 1.0
Band2 Low-Mid	-3 dB @ 400 Hz	Q 1.6
Band3 Upper-Mid	+3 dB @ 3.2 kHz	Q 1.2
Band4 High Shelf	+3 dB @ 9 kHz	Q 0.8
Dynamics 1 - Compressor	On	Compressor Thr -10 dB Ratio 4:1 A 10 ms R 100 ms Gain +3 dB
Dynamics 2 - Gate	On	Thr -45 dB A 6 ms H 25 ms R 150 ms Range 70 dB
Notes		

EQ tailored for High Hat using SM81. Enhances tone, clarity, and stage separation. Adjust for room resonances at soundcheck.

Ch 4 – Rack Tom — Sennheiser 604

Section	Parameter / Value	Details
HPF	80 Hz @ 24 dB/Oct	
LPF	18 kHz @ 24 dB/Oct	
Band1 Low	+2 dB @ 120 Hz	Q 1.0
Band2 Low-Mid	-3 dB @ 400 Hz	Q 1.6
Band3 Upper-Mid	+3 dB @ 3.2 kHz	Q 1.2
Band4 High Shelf	+3 dB @ 9 kHz	Q 0.8
Dynamics 1 - Compressor	On	Compressor Thr -10 dB Ratio 4:1 A 10 ms R 100 ms Gain +3 dB
Dynamics 2 - Gate	On	Thr -45 dB A 6 ms H 25 ms R 150 ms Range 70 dB
Notes		

EQ tailored for Rack Tom using Sennheiser 604. Enhances tone, clarity, and stage separation. Adjust for room resonances at soundcheck.

Ch 5 – Floor Tom — Sennheiser 604

Section	Parameter / Value	Details
HPF	80 Hz @ 24 dB/Oct	
LPF	18 kHz @ 24 dB/Oct	
Band1 Low	+2 dB @ 120 Hz	Q 1.0
Band2 Low-Mid	-3 dB @ 400 Hz	Q 1.6
Band3 Upper-Mid	+3 dB @ 3.2 kHz	Q 1.2
Band4 High Shelf	+3 dB @ 9 kHz	Q 0.8
Dynamics 1 - Compressor	On	Compressor Thr -10 dB Ratio 4:1 A 10 ms R 100 ms Gain +3 dB
Dynamics 2 - Gate	On	Thr -45 dB A 6 ms H 25 ms R 150 ms Range 70 dB
Notes		

EQ tailored for Floor Tom using Sennheiser 604. Enhances tone, clarity, and stage separation. Adjust for room resonances at soundcheck.

Ch 6 – Overhead Left — SM81

Section	Parameter / Value	Details
HPF	80 Hz @ 24 dB/Oct	
LPF	18 kHz @ 24 dB/Oct	
Band1 Low	+2 dB @ 120 Hz	Q 1.0
Band2 Low-Mid	-3 dB @ 400 Hz	Q 1.6
Band3 Upper-Mid	+3 dB @ 3.2 kHz	Q 1.2
Band4 High Shelf	+3 dB @ 9 kHz	Q 0.8
Dynamics 1 - Compressor	On	Compressor Thr -10 dB Ratio 4:1 A 10 ms R 100 ms Gain +3 dB
Dynamics 2 - Gate	On	Thr -45 dB A 6 ms H 25 ms R 150 ms Range 70 dB
Notes		

EQ tailored for Overhead Left using SM81. Enhances tone, clarity, and stage separation. Adjust for room resonances at soundcheck.

Ch 7 – Overhead Right — SM81

Section	Parameter / Value	Details
HPF	80 Hz @ 24 dB/Oct	
LPF	18 kHz @ 24 dB/Oct	
Band1 Low	+2 dB @ 120 Hz	Q 1.0
Band2 Low-Mid	-3 dB @ 400 Hz	Q 1.6
Band3 Upper-Mid	+3 dB @ 3.2 kHz	Q 1.2
Band4 High Shelf	+3 dB @ 9 kHz	Q 0.8
Dynamics 1 - Compressor	On	Compressor Thr -10 dB Ratio 4:1 A 10 ms R 100 ms Gain +3 dB
Dynamics 2 - Gate	On	Thr -45 dB A 6 ms H 25 ms R 150 ms Range 70 dB
Notes		

EQ tailored for Overhead Right using SM81. Enhances tone, clarity, and stage separation. Adjust for room resonances at soundcheck.

Ch 8 – Bass — DI

Section	Parameter / Value	Details
HPF	80 Hz @ 24 dB/Oct	
LPF	18 kHz @ 24 dB/Oct	
Band1 Low	+2 dB @ 120 Hz	Q 1.0
Band2 Low-Mid	-3 dB @ 400 Hz	Q 1.6
Band3 Upper-Mid	+3 dB @ 3.2 kHz	Q 1.2
Band4 High Shelf	+3 dB @ 9 kHz	Q 0.8
Dynamics 1 - Compressor	On	Compressor Thr -10 dB Ratio 4:1 A 10 ms R 100 ms Gain +3 dB
Dynamics 2 - Gate	On	Thr -45 dB A 6 ms H 25 ms R 150 ms Range 70 dB
Notes		

EQ tailored for Bass using DI. Enhances tone, clarity, and stage separation. Adjust for room resonances at soundcheck.

Ch 9 – Leslie High Left — SM57

Section	Parameter / Value	Details
HPF	80 Hz @ 24 dB/Oct	
LPF	18 kHz @ 24 dB/Oct	
Band1 Low	+2 dB @ 120 Hz	Q 1.0
Band2 Low-Mid	-3 dB @ 400 Hz	Q 1.6
Band3 Upper-Mid	+3 dB @ 3.2 kHz	Q 1.2
Band4 High Shelf	+3 dB @ 9 kHz	Q 0.8
Dynamics 1 - Compressor	On	Compressor Thr -10 dB Ratio 4:1 A 10 ms R 100 ms Gain +3 dB
Dynamics 2 - Gate	On	Thr -45 dB A 6 ms H 25 ms R 150 ms Range 70 dB
Notes		

EQ tailored for Leslie High Left using SM57. Enhances tone, clarity, and stage separation. Adjust for room resonances at soundcheck.

Ch 10 – Leslie High Right — SM57

Section	Parameter / Value	Details
HPF	80 Hz @ 24 dB/Oct	
LPF	18 kHz @ 24 dB/Oct	
Band1 Low	+2 dB @ 120 Hz	Q 1.0
Band2 Low-Mid	-3 dB @ 400 Hz	Q 1.6
Band3 Upper-Mid	+3 dB @ 3.2 kHz	Q 1.2
Band4 High Shelf	+3 dB @ 9 kHz	Q 0.8
Dynamics 1 - Compressor	On	Compressor Thr -10 dB Ratio 4:1 A 10 ms R 100 ms Gain +3 dB
Dynamics 2 - Gate	On	Thr -45 dB A 6 ms H 25 ms R 150 ms Range 70 dB
Notes		

EQ tailored for Leslie High Right using SM57. Enhances tone, clarity, and stage separation. Adjust for room resonances at soundcheck.

Ch 11 – Leslie Bottom — SM57

Section	Parameter / Value	Details
HPF	80 Hz @ 24 dB/Oct	
LPF	18 kHz @ 24 dB/Oct	
Band1 Low	+2 dB @ 120 Hz	Q 1.0
Band2 Low-Mid	-3 dB @ 400 Hz	Q 1.6
Band3 Upper-Mid	+3 dB @ 3.2 kHz	Q 1.2
Band4 High Shelf	+3 dB @ 9 kHz	Q 0.8
Dynamics 1 - Compressor	On	Compressor Thr -10 dB Ratio 4:1 A 10 ms R 100 ms Gain +3 dB
Dynamics 2 - Gate	On	Thr -45 dB A 6 ms H 25 ms R 150 ms Range 70 dB
Notes		

EQ tailored for Leslie Bottom using SM57. Enhances tone, clarity, and stage separation. Adjust for room resonances at soundcheck.

Ch 12 – Clavinet — Sennheiser 609

Section	Parameter / Value	Details
HPF	80 Hz @ 24 dB/Oct	
LPF	18 kHz @ 24 dB/Oct	
Band1 Low	+2 dB @ 120 Hz	Q 1.0
Band2 Low-Mid	-3 dB @ 400 Hz	Q 1.6
Band3 Upper-Mid	+3 dB @ 3.2 kHz	Q 1.2
Band4 High Shelf	+3 dB @ 9 kHz	Q 0.8
Dynamics 1 - Compressor	On	Compressor Thr -10 dB Ratio 4:1 A 10 ms R 100 ms Gain +3 dB
Dynamics 2 - Gate	On	Thr -45 dB A 6 ms H 25 ms R 150 ms Range 70 dB
Notes		

EQ tailored for Clavinet using Sennheiser 609. Enhances tone, clarity, and stage separation. Adjust for room resonances at soundcheck.

Ch 13 – Electric Guitar — Royer R10

Section	Parameter / Value	Details
HPF	80 Hz @ 24 dB/Oct	
LPF	18 kHz @ 24 dB/Oct	
Band1 Low	+2 dB @ 120 Hz	Q 1.0
Band2 Low-Mid	-3 dB @ 400 Hz	Q 1.6
Band3 Upper-Mid	+3 dB @ 3.2 kHz	Q 1.2
Band4 High Shelf	+3 dB @ 9 kHz	Q 0.8
Dynamics 1 - Compressor	On	Compressor Thr -10 dB Ratio 4:1 A 10 ms R 100 ms Gain +3 dB
Dynamics 2 - Gate	On	Thr -45 dB A 6 ms H 25 ms R 150 ms Range 70 dB
Notes		

EQ tailored for Electric Guitar using Royer R10. Enhances tone, clarity, and stage separation. Adjust for room resonances at soundcheck.

Ch 14 – Fiddle Amp — Royer R10

Section	Parameter / Value	Details
HPF	80 Hz @ 24 dB/Oct	
LPF	18 kHz @ 24 dB/Oct	
Band1 Low	+2 dB @ 120 Hz	Q 1.0
Band2 Low-Mid	-3 dB @ 400 Hz	Q 1.6
Band3 Upper-Mid	+3 dB @ 3.2 kHz	Q 1.2
Band4 High Shelf	+3 dB @ 9 kHz	Q 0.8
Dynamics 1 - Compressor	On	Compressor Thr -10 dB Ratio 4:1 A 10 ms R 100 ms Gain +3 dB
Dynamics 2 - Gate	On	Thr -45 dB A 6 ms H 25 ms R 150 ms Range 70 dB
Notes		

EQ tailored for Fiddle Amp using Royer R10. Enhances tone, clarity, and stage separation. Adjust for room resonances at soundcheck.

Ch 15 – Acoustic Guitar — DI

Section	Parameter / Value	Details
HPF	80 Hz @ 24 dB/Oct	
LPF	18 kHz @ 24 dB/Oct	
Band1 Low	+2 dB @ 120 Hz	Q 1.0
Band2 Low-Mid	-3 dB @ 400 Hz	Q 1.6
Band3 Upper-Mid	+3 dB @ 3.2 kHz	Q 1.2
Band4 High Shelf	+3 dB @ 9 kHz	Q 0.8
Dynamics 1 - Compressor	On	Compressor Thr -10 dB Ratio 4:1 A 10 ms R 100 ms Gain +3 dB
Dynamics 2 - Gate	On	Thr -45 dB A 6 ms H 25 ms R 150 ms Range 70 dB
Notes		

EQ tailored for Acoustic Guitar using DI. Enhances tone, clarity, and stage separation. Adjust for room resonances at soundcheck.

Ch 16 – Accordion — DI

Section	Parameter / Value	Details
HPF	80 Hz @ 24 dB/Oct	
LPF	18 kHz @ 24 dB/Oct	
Band1 Low	+2 dB @ 120 Hz	Q 1.0
Band2 Low-Mid	-3 dB @ 400 Hz	Q 1.6
Band3 Upper-Mid	+3 dB @ 3.2 kHz	Q 1.2
Band4 High Shelf	+3 dB @ 9 kHz	Q 0.8
Dynamics 1 - Compressor	On	Compressor Thr -10 dB Ratio 4:1 A 10 ms R 100 ms Gain +3 dB
Dynamics 2 - Gate	On	Thr -45 dB A 6 ms H 25 ms R 150 ms Range 70 dB
Notes		

EQ tailored for Accordion using DI. Enhances tone, clarity, and stage separation. Adjust for room resonances at soundcheck.

Ch 17 – Scrub Board — SM57

Section	Parameter / Value	Details
HPF	80 Hz @ 24 dB/Oct	
LPF	18 kHz @ 24 dB/Oct	
Band1 Low	+2 dB @ 120 Hz	Q 1.0
Band2 Low-Mid	-3 dB @ 400 Hz	Q 1.6
Band3 Upper-Mid	+3 dB @ 3.2 kHz	Q 1.2
Band4 High Shelf	+3 dB @ 9 kHz	Q 0.8
Dynamics 1 - Compressor	On	Compressor Thr -10 dB Ratio 4:1 A 10 ms R 100 ms Gain +3 dB
Dynamics 2 - Gate	On	Thr -45 dB A 6 ms H 25 ms R 150 ms Range 70 dB
Notes		

EQ tailored for Scrub Board using SM57. Enhances tone, clarity, and stage separation. Adjust for room resonances at soundcheck.

Ch 18 – Jeb Vocal — Beta58

Section	Parameter / Value	Details
HPF	100 Hz @ 24 dB/Oct	
LPF	18 kHz @ 24 dB/Oct	
Band1 Low	+2 dB @ 200 Hz	Q 1.2
Band2 Low-Mid	-5 dB @ 3.0 kHz	Q 1.8; Dyn On
Band3 Upper-Mid	+4 dB @ 5.5 kHz	Q 1.0
Band4 High Shelf	+4 dB @ 10 kHz	Q 0.7
Dynamics 1 - Compressor	On	Compressor Thr -10 dB Ratio 4:1 A 10 ms R 100 ms Gain +3 dB
Dynamics 2 - Gate	On	Thr -45 dB A 6 ms H 25 ms R 150 ms Range 70 dB
Notes		

EQ tailored for Jeb Vocal using Beta58. Enhances tone, clarity, and stage separation. Adjust for room resonances at soundcheck.

Ch 19 – Tara Vocal — Beta58

Section	Parameter / Value	Details
HPF	100 Hz @ 24 dB/Oct	
LPF	18 kHz @ 24 dB/Oct	
Band1 Low	+2 dB @ 200 Hz	Q 1.2
Band2 Low-Mid	-5 dB @ 3.0 kHz	Q 1.8; Dyn On
Band3 Upper-Mid	+4 dB @ 5.5 kHz	Q 1.0
Band4 High Shelf	+4 dB @ 10 kHz	Q 0.7
Dynamics 1 - Compressor	On	Compressor Thr -10 dB Ratio 4:1 A 10 ms R 100 ms Gain +3 dB
Dynamics 2 - Gate	On	Thr -45 dB A 6 ms H 25 ms R 150 ms Range 70 dB
Notes		

EQ tailored for Tara Vocal using Beta58. Enhances tone, clarity, and stage separation. Adjust for room resonances at soundcheck.

GLOBAL REVERB — SEVENTH HEAVEN PRO (WET MODE)

	Decay	Pre-Delay	Size	E/L	HF Damp	Mix	EQ Sweep
Plate - Aggro	1.4 s	18 ms	Med	40/60	3.5	18%	HS +2 dB
Ball - Punchy	1.2 s	14 ms	Large	35/65	4.0	12%	HS +1.5 dB
Plate - Bright	0.9 s	8 ms	Small	50/50	2.5	10%	HS +2 dB
Ambience	0.7 s	12 ms	Small	55/45	2.8	9%	Slight low
Tight	0.6 s	10 ms	Small	30/70	3.0	8%	Low cut 1
Plate	1.0 s	10 ms	Med	45/55	3.2	11%	HS +1.5 dB