

Pop Goes Emo – Rock/Emo Aggressive EQ & Compression Settings

Ch 1: Kick In – Shure Beta 91

EQ (Cuts Only)	HPF @ 40Hz -5dB @ 250Hz (mud) -6dB @ 600Hz (box) -3dB @ 3kHz (click harshness)
Compression	Ratio 5:1 Fast attack Medium release 4–6dB GR
Mustard	Drive + Saturation for weight

Ch 2: Kick Out – Audix D6

EQ (Cuts Only)	HPF @ 35Hz -6dB @ 400Hz (box) -4dB @ 800Hz (honk)
Compression	Ratio 4:1 Medium attack/release 3–5dB GR
Mustard	Low boost saturation

Ch 3: Snare Top – Audix i5

EQ (Cuts Only)	HPF @ 100Hz -5dB @ 250Hz (mud) -6dB @ 500Hz (box) -3dB @ 7kHz (harshness)
Compression	Ratio 6:1 Fast attack Medium release 5–7dB GR
Mustard	Drive for crack

Ch 4: Snare Bottom – Shure SM57

EQ (Cuts Only)	HPF @ 120Hz -6dB @ 500Hz (box) -4dB @ 8kHz (harshness)
Compression	Ratio 5:1 Fast attack Medium release 4–6dB GR
Mustard	Saturation for sizzle

Ch 5: Hi-Hat – EV N/D408

EQ (Cuts Only)	HPF @ 200Hz -5dB @ 1kHz (harsh) -4dB @ 8kHz (sharpness)
Compression	Ratio 3:1 Fast attack/release 2–3dB GR
Mustard	Light saturation

Ch 6: Rack Tom 1 – Audix D2

EQ (Cuts Only)	HPF @ 60Hz -6dB @ 400Hz (box) -3dB @ 800Hz (honk)
Compression	Ratio 5:1 Medium attack Medium release 4–6dB GR
Mustard	Drive for punch

Ch 7: Rack Tom 2 – Audix D2

EQ (Cuts Only)	HPF @ 60Hz -6dB @ 400Hz (box) -3dB @ 800Hz (honk)
Compression	Ratio 5:1 Medium attack Medium release 4–6dB GR
Mustard	Drive for punch

Ch 8: Floor Tom – Audix D4

EQ (Cuts Only)	HPF @ 50Hz -6dB @ 300Hz (mud) -4dB @ 600Hz (box)
Compression	Ratio 5:1 Medium attack Medium release 4–6dB GR
Mustard	Drive for depth

Ch 9: Overhead L – Shure SM81

EQ (Cuts Only)	HPF @ 150Hz -5dB @ 2kHz (harsh) -3dB @ 6kHz (sharpness)
Compression	Ratio 3:1 Fast attack/release 2–4dB GR
Mustard	Light air saturation

Ch 10: Overhead R – Shure SM81

EQ (Cuts Only)	HPF @ 150Hz -5dB @ 2kHz (harsh) -3dB @ 6kHz (sharpness)
Compression	Ratio 3:1 Fast attack/release 2–4dB GR
Mustard	Light air saturation

Ch 11: Bass DI – BSS DI

EQ (Cuts Only)	HPF @ 50Hz -6dB @ 250Hz (mud) -4dB @ 500Hz (box)
Compression	Ratio 6:1 Fast attack Medium release 6–8dB GR
Mustard	Saturation for grit

Ch 12: Bass Mic – Shure SM57

EQ (Cuts Only)	HPF @ 60Hz -5dB @ 250Hz (mud) -6dB @ 400Hz (box) -3dB @ 3kHz (harsh)
Compression	Ratio 6:1 Fast attack Medium release 6–8dB GR
Mustard	Drive for growl

Ch 13: Guitar 1 – Sennheiser e609

EQ (Cuts Only)	HPF @ 90Hz -6dB @ 250Hz (mud) -4dB @ 2kHz (harsh) -3dB @ 6kHz (ice pick)
Compression	Ratio 4:1 Medium attack/release 3–5dB GR
Mustard	Saturation for edge