

Ch 1 – Piano Low

Mic – Helpinstill Pickup

Standard Compressor	Value
Threshold	-12 dB
Ratio	4:1
Attack	12 ms
Release	90 ms
Makeup	+3 dB

Standard Gate/Expander	Value
Threshold	-45 dB
Attack	5 ms
Hold	80 ms
Release	150 ms

Mustard Tube	Value
Drive (0-1)	0.55
Type	Even Harmonics
Output (dB)	-6 dB

Mustard EQ	Band / Setting
Not used	-

Mustard Dynamics — Row 1	Flavor: Blue Threshold/Input: -10 dB Ratio: 4:1 Attack: 12 ms Release: 100 ms
Mustard Dynamics — Row 2	Output Trim: +2 dB Notes: Flavor-specific behavior — use for color or smooth control.

Standard EQ Band (High → Low)	Setting
HPF	60 Hz
Body	+5 dB @ 100 Hz (Q 1.2)
Resonance	-4 dB @ 2-4 kHz (Q 2.0)
Presence	+3 dB @ 9 kHz (Q 1.2)
Note	Aggressive surgical cuts to remove pickup resonances

- HPF 60 Hz — Remove subsonic rumble and stage floor vibration that build up in a reverberant room.
- +5 dB @ 100 Hz (Q 1.2) — Reinforce the instrument's fundamental to read on the PA and retain perceived weight in a live venue.
- -4 dB @ 2-4 kHz (Q 2.0) — Reduce boxy/muddy resonances that smear in a ringy room and obscure clarity.
- +3 dB @ 9 kHz (Q 1.2) — Shape the upper harmonics for clarity and air; dynamic EQ used where boost/cut should only occur when problematic.
- Aggressive surgical cuts to remove pickup resonances — Practical note: use surgical cuts and dynamic bands to address room-excited peaks.
- Signal chain: compressor then gate reduces triggering from EQ boosts; Mustard tube used sparingly to add body without exciting room resonances.

Ch 2 – Piano Mid

Mic – Helpinstill Pickup

Standard Compressor	Value
Threshold	-12 dB
Ratio	4:1
Attack	12 ms
Release	90 ms
Makeup	+3 dB

Standard Gate/Expander	Value
Threshold	-45 dB
Attack	5 ms
Hold	80 ms
Release	150 ms

Mustard Tube	Value
Drive (0-1)	0.55
Type	Even Harmonics
Output (dB)	-6 dB

Mustard EQ	Band / Setting
Not used	-

Mustard Dynamics — Row 1	Flavor: Blue Threshold/Input: -10 dB Ratio: 4:1 Attack: 12 ms Release: 100 ms
Mustard Dynamics — Row 2	Output Trim: +2 dB Notes: Flavor-specific behavior — use for color or smooth control.

Standard EQ Band (High → Low)	Setting
HPF	60 Hz
Body	+5 dB @ 100 Hz (Q 1.2)
Resonance	-4 dB @ 2-4 kHz (Q 2.0)
Presence	+3 dB @ 9 kHz (Q 1.2)
Note	Aggressive surgical cuts to remove pickup resonances

- HPF 60 Hz — Remove subsonic rumble and stage floor vibration that build up in a reverberant room.
- +5 dB @ 100 Hz (Q 1.2) — Reinforce the instrument's fundamental to read on the PA and retain perceived weight in a live venue.
- -4 dB @ 2-4 kHz (Q 2.0) — Reduce boxy/muddy resonances that smear in a ringy room and obscure clarity.
- +3 dB @ 9 kHz (Q 1.2) — Shape the upper harmonics for clarity and air; dynamic EQ used where boost/cut should only occur when problematic.
- Aggressive surgical cuts to remove pickup resonances — Practical note: use surgical cuts and dynamic bands to address room-excited peaks.
- Signal chain: compressor then gate reduces triggering from EQ boosts; Mustard tube used sparingly to add body without exciting room resonances.

Ch 3 – Piano High

Mic – Helpinstill Pickup

Standard Compressor	Value
Threshold	-12 dB
Ratio	4:1
Attack	12 ms
Release	90 ms
Makeup	+3 dB

Standard Gate/Expander	Value
Threshold	-45 dB
Attack	5 ms
Hold	80 ms
Release	150 ms

Mustard Tube	Value
Drive (0-1)	0.55
Type	Even Harmonics
Output (dB)	-6 dB

Mustard EQ	Band / Setting
Not used	-

Mustard Dynamics — Row 1	Flavor: Blue Threshold/Input: -10 dB Ratio: 4:1 Attack: 12 ms Release: 100 ms
Mustard Dynamics — Row 2	Output Trim: +2 dB Notes: Flavor-specific behavior — use for color or smooth control.

Standard EQ Band (High → Low)	Setting
HPF	60 Hz
Body	+5 dB @ 100 Hz (Q 1.2)
Resonance	-4 dB @ 2-4 kHz (Q 2.0)
Presence	+3 dB @ 9 kHz (Q 1.2)
Note	Aggressive surgical cuts to remove pickup resonances

- HPF 60 Hz — Remove subsonic rumble and stage floor vibration that build up in a reverberant room.
- +5 dB @ 100 Hz (Q 1.2) — Reinforce the instrument's fundamental to read on the PA and retain perceived weight in a live venue.
- -4 dB @ 2-4 kHz (Q 2.0) — Reduce boxy/muddy resonances that smear in a ringy room and obscure clarity.
- +3 dB @ 9 kHz (Q 1.2) — Shape the upper harmonics for clarity and air; dynamic EQ used where boost/cut should only occur when problematic.
- Aggressive surgical cuts to remove pickup resonances — Practical note: use surgical cuts and dynamic bands to address room-excited peaks.
- Signal chain: compressor then gate reduces triggering from EQ boosts; Mustard tube used sparingly to add body without exciting room resonances.

Ch 4 – Piano DPA Low

Mic – DPA 4099

Standard Compressor	Value
Threshold	-12 dB
Ratio	4:1
Attack	12 ms
Release	90 ms
Makeup	+3 dB

Standard Gate/Expander	Value
Threshold	-45 dB
Attack	5 ms
Hold	80 ms
Release	150 ms

Mustard Tube	Value
Drive (0-1)	0.55
Type	Even Harmonics
Output (dB)	-6 dB

Mustard EQ	Band / Setting
Not used	-

Mustard Dynamics — Row 1	Flavor: Purple Threshold/Input: -10 dB Ratio: 4:1 Attack: 12 ms Release: 100 ms
Mustard Dynamics — Row 2	Output Trim: +2 dB Notes: Flavor-specific behavior — use for color or smooth control.

Standard EQ Band (High → Low)	Setting
HPF	40 Hz
Body	+3 dB @ 80-120 Hz (Q 1.2)
Clarity	+2 dB @ 3-5 kHz
Air	+2 dB @ 10 kHz
Note	Blend DPA for realism with Helpinstill for presence

- HPF 40 Hz — Remove subsonic rumble and stage floor vibration that build up in a reverberant room.
- +3 dB @ 80-120 Hz (Q 1.2) — Reinforce the instrument's fundamental to read on the PA and retain perceived weight in a live venue.
- +2 dB @ 3-5 kHz — Practical note: use surgical cuts and dynamic bands to address room-excited peaks.
- +2 dB @ 10 kHz — Shape the upper harmonics for clarity and air; dynamic EQ used where boost/cut should only occur when problematic.
- Blend DPA for realism with Helpinstill for presence — Practical note: use surgical cuts and dynamic bands to address room-excited peaks.
- Signal chain: compressor then gate reduces triggering from EQ boosts; Mustard tube used sparingly to add body without exciting room resonances.

Ch 5 – Piano DPA High

Mic – DPA 4099

Standard Compressor	Value
Threshold	-12 dB
Ratio	4:1
Attack	12 ms
Release	90 ms
Makeup	+3 dB

Standard Gate/Expander	Value
Threshold	-45 dB
Attack	5 ms
Hold	80 ms
Release	150 ms

Mustard Tube	Value
Drive (0-1)	0.55
Type	Even Harmonics
Output (dB)	-6 dB

Mustard EQ	Band / Setting
Not used	-

Mustard Dynamics — Row 1	Flavor: Purple Threshold/Input: -10 dB Ratio: 4:1 Attack: 12 ms Release: 100 ms
Mustard Dynamics — Row 2	Output Trim: +2 dB Notes: Flavor-specific behavior — use for color or smooth control.

Standard EQ Band (High → Low)	Setting
HPF	40 Hz
Body	+3 dB @ 80-120 Hz (Q 1.2)
Clarity	+2 dB @ 3-5 kHz
Air	+2 dB @ 10 kHz
Note	Blend DPA for realism with Helpinstill for presence

- HPF 40 Hz — Remove subsonic rumble and stage floor vibration that build up in a reverberant room.
- +3 dB @ 80-120 Hz (Q 1.2) — Reinforce the instrument's fundamental to read on the PA and retain perceived weight in a live venue.
- +2 dB @ 3-5 kHz — Practical note: use surgical cuts and dynamic bands to address room-excited peaks.
- +2 dB @ 10 kHz — Shape the upper harmonics for clarity and air; dynamic EQ used where boost/cut should only occur when problematic.
- Blend DPA for realism with Helpinstill for presence — Practical note: use surgical cuts and dynamic bands to address room-excited peaks.
- Signal chain: compressor then gate reduces triggering from EQ boosts; Mustard tube used sparingly to add body without exciting room resonances.

Ch 6 – DJ Left

Mic – Radial J48

Standard Compressor	Value
Threshold	-12 dB
Ratio	4:1
Attack	12 ms
Release	90 ms
Makeup	+3 dB

Standard Gate/Expander	Value
Threshold	-45 dB
Attack	5 ms
Hold	80 ms
Release	150 ms

Mustard Tube	Value
Drive (0-1)	0.55
Type	Even Harmonics
Output (dB)	-6 dB

Mustard EQ	Band / Setting
Not used	-

Mustard Dynamics — Row 1	Flavor: Red Threshold/Input: -10 dB Ratio: 4:1 Attack: 12 ms Release: 100 ms
Mustard Dynamics — Row 2	Output Trim: +2 dB Notes: Flavor-specific behavior — use for color or smooth control.

Standard EQ Band (High → Low)	Setting
HPF	100 Hz
Shelf	+3 dB @ 8-10 kHz
Cut	-3 dB @ 600-800 Hz
Body	+2 dB @ 150-200 Hz
Note	Adjust to taste

- HPF 100 Hz — Remove subsonic rumble and stage floor vibration that build up in a reverberant room.
- +3 dB @ 8-10 kHz — Gentle shelf/roll to control extreme highs that exaggerate in reflective rooms.
- -3 dB @ 600-800 Hz — Applied to balance frequency energy for live PA translation.
- +2 dB @ 150-200 Hz — Reinforce the instrument's fundamental to read on the PA and retain perceived weight in a live venue.
- Adjust to taste — Practical note: use surgical cuts and dynamic bands to address room-excited peaks.
- Conservative processing; verify on stage and adjust band gains to taste.

Ch 7 – DJ Right

Mic – Radial J48

Standard Compressor	Value
Threshold	-12 dB
Ratio	4:1
Attack	12 ms
Release	90 ms
Makeup	+3 dB

Standard Gate/Expander	Value
Threshold	-45 dB
Attack	5 ms
Hold	80 ms
Release	150 ms

Mustard Tube	Value
Drive (0-1)	0.55
Type	Even Harmonics
Output (dB)	-6 dB

Mustard EQ	Band / Setting
Not used	-

Mustard Dynamics — Row 1	Flavor: Red Threshold/Input: -10 dB Ratio: 4:1 Attack: 12 ms Release: 100 ms
Mustard Dynamics — Row 2	Output Trim: +2 dB Notes: Flavor-specific behavior — use for color or smooth control.

Standard EQ Band (High → Low)	Setting
HPF	100 Hz
Shelf	+3 dB @ 8-10 kHz
Cut	-3 dB @ 600-800 Hz
Body	+2 dB @ 150-200 Hz
Note	Adjust to taste

- HPF 100 Hz — Remove subsonic rumble and stage floor vibration that build up in a reverberant room.
- +3 dB @ 8-10 kHz — Gentle shelf/roll to control extreme highs that exaggerate in reflective rooms.
- -3 dB @ 600-800 Hz — Applied to balance frequency energy for live PA translation.
- +2 dB @ 150-200 Hz — Reinforce the instrument's fundamental to read on the PA and retain perceived weight in a live venue.
- Adjust to taste — Practical note: use surgical cuts and dynamic bands to address room-excited peaks.
- Conservative processing; verify on stage and adjust band gains to taste.

Ch 8 – Clipping Vocal 1

Mic – XLR (unspecified)

Standard Compressor	Value
Threshold	-12 dB

Ratio	4:1
Attack	12 ms
Release	90 ms
Makeup	+3 dB

Standard Gate/Expander	Value
Threshold	-45 dB
Attack	5 ms
Hold	80 ms
Release	150 ms

Mustard Tube	Value
Drive (0-1)	0.55
Type	Even Harmonics
Output (dB)	-6 dB

Mustard EQ	Band / Setting
Not used	-

Mustard Dynamics — Row 1	Flavor: Purple Threshold/Input: -10 dB Ratio: 4:1 Attack: 12 ms Release: 100 ms
Mustard Dynamics — Row 2	Output Trim: +2 dB Notes: Flavor-specific behavior — use for color or smooth control.

Standard EQ Band (High → Low)	Setting
HPF	100 Hz
Shelf	+3 dB @ 8-10 kHz
Cut	-3 dB @ 600-800 Hz
Body	+2 dB @ 150-200 Hz
Note	Adjust to taste

- HPF 100 Hz — Remove subsonic rumble and stage floor vibration that build up in a reverberant room.
- +3 dB @ 8-10 kHz — Gentle shelf/roll to control extreme highs that exaggerate in reflective rooms.
- -3 dB @ 600-800 Hz — Applied to balance frequency energy for live PA translation.
- +2 dB @ 150-200 Hz — Reinforce the instrument's fundamental to read on the PA and retain perceived weight in a live venue.
- Adjust to taste — Practical note: use surgical cuts and dynamic bands to address room-excited peaks.
- Conservative processing; verify on stage and adjust band gains to taste.

Ch 9 – Clipping Vocal 2

Mic – XLR (unspecified)

Standard Compressor	Value
Threshold	-12 dB
Ratio	4:1
Attack	12 ms

Release	90 ms
Makeup	+3 dB

Standard Gate/Expander	Value
Threshold	-45 dB
Attack	5 ms
Hold	80 ms
Release	150 ms

Mustard Tube	Value
Drive (0-1)	0.55
Type	Even Harmonics
Output (dB)	-6 dB

Mustard EQ	Band / Setting
Not used	-

Mustard Dynamics — Row 1	Flavor: Purple Threshold/Input: -10 dB Ratio: 4:1 Attack: 12 ms Release: 100 ms
Mustard Dynamics — Row 2	Output Trim: +2 dB Notes: Flavor-specific behavior — use for color or smooth control.

Standard EQ Band (High → Low)	Setting
HPF	100 Hz
Shelf	+3 dB @ 8-10 kHz
Cut	-3 dB @ 600-800 Hz
Body	+2 dB @ 150-200 Hz
Note	Adjust to taste

- HPF 100 Hz — Remove subsonic rumble and stage floor vibration that build up in a reverberant room.
- +3 dB @ 8-10 kHz — Gentle shelf/roll to control extreme highs that exaggerate in reflective rooms.
- -3 dB @ 600-800 Hz — Applied to balance frequency energy for live PA translation.
- +2 dB @ 150-200 Hz — Reinforce the instrument's fundamental to read on the PA and retain perceived weight in a live venue.
- Adjust to taste — Practical note: use surgical cuts and dynamic bands to address room-excited peaks.
- Conservative processing; verify on stage and adjust band gains to taste.

Ch 10 – Flute (Primary)

Mic – DPA 4099

Standard Compressor	Value
Threshold	-12 dB
Ratio	4:1
Attack	12 ms
Release	90 ms
Makeup	+3 dB

Standard Gate/Expander	Value
Threshold	-45 dB
Attack	5 ms
Hold	80 ms
Release	150 ms

Mustard Tube	Value
Drive (0-1)	0.55
Type	Even Harmonics
Output (dB)	-6 dB

Mustard EQ	Band / Setting
Not used	-

Mustard Dynamics — Row 1	Flavor: Purple Threshold/Input: -10 dB Ratio: 4:1 Attack: 12 ms Release: 100 ms
Mustard Dynamics — Row 2	Output Trim: +2 dB Notes: Flavor-specific behavior — use for color or smooth control.

Standard EQ Band (High → Low)	Setting
HPF	250 Hz
Warmth	+2 dB @ 500 Hz (Q 1.5)
Harsh	-3 dB @ 3.5 kHz (dynamic)
Air	+2 dB @ 7 kHz
Note	Avoid boosting above 10 kHz

- HPF 250 Hz — Remove subsonic rumble and stage floor vibration that build up in a reverberant room.
- +2 dB @ 500 Hz (Q 1.5) — Applied to balance frequency energy for live PA translation.
- -3 dB @ 3.5 kHz (dynamic) — Shape the upper harmonics for clarity and air; dynamic EQ used where boost/cut should only occur when problematic.
- +2 dB @ 7 kHz — Shape the upper harmonics for clarity and air; dynamic EQ used where boost/cut should only occur when problematic.
- Avoid boosting above 10 kHz — Practical note: use surgical cuts and dynamic bands to address room-excited peaks.
- Optical compression for natural dynamics; dynamic EQ on harsh upper mids to avoid brittle air.

Ch 10 – Flute (Alternate)

Mic – Schoeps MK4

Standard Compressor	Value
Threshold	-12 dB
Ratio	4:1
Attack	12 ms
Release	90 ms
Makeup	+3 dB

Standard Gate/Expander	Value
------------------------	-------

Threshold	-45 dB
Attack	5 ms
Hold	80 ms
Release	150 ms

Mustard Tube	Value
Drive (0-1)	0.55
Type	Even Harmonics
Output (dB)	-6 dB

Mustard EQ	Band / Setting
Not used	-

Mustard Dynamics — Row 1	Flavor: Purple Threshold/Input: -10 dB Ratio: 4:1 Attack: 12 ms Release: 100 ms
Mustard Dynamics — Row 2	Output Trim: +2 dB Notes: Flavor-specific behavior — use for color or smooth control.

Standard EQ Band (High → Low)	Setting
HPF	220 Hz
Warmth	+3 dB @ 600 Hz (Q 1.5)
Harsh	-4 dB @ 4 kHz (dynamic)
Air	+3 dB shelf @ 9 kHz
Note	Manage room bleed with cuts 200-400 Hz

- HPF 220 Hz — Remove subsonic rumble and stage floor vibration that build up in a reverberant room.
- +3 dB @ 600 Hz (Q 1.5) — Applied to balance frequency energy for live PA translation.
- -4 dB @ 4 kHz (dynamic) — Shape the upper harmonics for clarity and air; dynamic EQ used where boost/cut should only occur when problematic.
- +3 dB shelf @ 9 kHz — Shape the upper harmonics for clarity and air; dynamic EQ used where boost/cut should only occur when problematic.
- Manage room bleed with cuts 200-400 Hz — Practical note: use surgical cuts and dynamic bands to address room- excited peaks.
- Optical compression for natural dynamics; dynamic EQ on harsh upper mids to avoid brittle air.

Ch 11 – English / Clarinet

Mic – Royer 121 (Cloudlifter)

Standard Compressor	Value
Threshold	-12 dB
Ratio	4:1
Attack	12 ms
Release	90 ms
Makeup	+3 dB

Standard Gate/Expander	Value
Threshold	-45 dB

Attack	5 ms
Hold	80 ms
Release	150 ms

Mustard Tube	Value
Drive (0-1)	0.55
Type	Even Harmonics
Output (dB)	-6 dB

Mustard EQ	Band / Setting
Not used	-

Mustard Dynamics — Row 1	Flavor: Blue Threshold/Input: -10 dB Ratio: 4:1 Attack: 12 ms Release: 100 ms
Mustard Dynamics — Row 2	Output Trim: +2 dB Notes: Flavor-specific behavior — use for color or smooth control.

Standard EQ Band (High → Low)	Setting
HPF	100 Hz
Shelf	+3 dB @ 8-10 kHz
Cut	-3 dB @ 600-800 Hz
Body	+2 dB @ 150-200 Hz
Note	Adjust to taste

- HPF 100 Hz — Remove subsonic rumble and stage floor vibration that build up in a reverberant room.
- +3 dB @ 8-10 kHz — Gentle shelf/roll to control extreme highs that exaggerate in reflective rooms.
- -3 dB @ 600-800 Hz — Applied to balance frequency energy for live PA translation.
- +2 dB @ 150-200 Hz — Reinforce the instrument's fundamental to read on the PA and retain perceived weight in a live venue.
- Adjust to taste — Practical note: use surgical cuts and dynamic bands to address room-excited peaks.
- Conservative processing; verify on stage and adjust band gains to taste.

Ch 12 – French Horn

Mic – Royer R10 (Cloudlifter)

Standard Compressor	Value
Threshold	-12 dB
Ratio	4:1
Attack	12 ms
Release	90 ms
Makeup	+3 dB

Standard Gate/Expander	Value
Threshold	-45 dB
Attack	5 ms
Hold	80 ms

Release	150 ms
---------	--------

Mustard Tube	Value
Drive (0-1)	0.55
Type	Even Harmonics
Output (dB)	-6 dB

Mustard EQ	Band / Setting
Not used	-

Mustard Dynamics — Row 1	Flavor: Blue Threshold/Input: -10 dB Ratio: 4:1 Attack: 12 ms Release: 100 ms
Mustard Dynamics — Row 2	Output Trim: +2 dB Notes: Flavor-specific behavior — use for color or smooth control.

Standard EQ Band (High → Low)	Setting
HPF	100 Hz
Body	+3 dB @ 200-300 Hz
Honky Cut	-3 to -6 dB @ 1-2 kHz
Presence	+2-3 dB @ 3-6 kHz
Note	Tame harshness, keep presence

- HPF 100 Hz — Remove subsonic rumble and stage floor vibration that build up in a reverberant room.
- +3 dB @ 200-300 Hz — Reinforce the instrument's fundamental to read on the PA and retain perceived weight in a live venue.
- -3 to -6 dB @ 1-2 kHz — Applied to balance frequency energy for live PA translation.
- +2-3 dB @ 3-6 kHz — Shape the upper harmonics for clarity and air; dynamic EQ used where boost/cut should only occur when problematic.
- Tame harshness, keep presence — Practical note: use surgical cuts and dynamic bands to address room-excited peaks.
- Conservative processing; verify on stage and adjust band gains to taste.

Ch 13 – Kick

Mic – Earthworks DM6

Standard Compressor	Value
Threshold	-12 dB
Ratio	4:1
Attack	12 ms
Release	90 ms
Makeup	+3 dB

Standard Gate/Expander	Value
Threshold	-45 dB
Attack	5 ms
Hold	80 ms
Release	150 ms

Mustard Tube	Value
Drive (0-1)	0.55
Type	Even Harmonics
Output (dB)	-6 dB

Mustard EQ	Band / Setting
Not used	-

Mustard Dynamics — Row 1	Flavor: Green (FET / 1176) Input Drive: +6 dB Ratio: 8 Attack: 800 μ s Release: 100 ms
Mustard Dynamics — Row 2	Output Trim: +3 dB Notes: Drive for 3–6 dB GR — fast attack to catch transients; adjust ratio to taste.

Standard EQ Band (High → Low)	Setting
HPF	35 Hz, 12 dB/oct
Fundamental	+5 dB @ 70 Hz (Q 0.8)
Boxiness	-4 dB @ 300 Hz (Q 1.5)
Attack	+3 dB @ 3.5 kHz (Q 1.2)
Air	LPF/roll-off above 12 kHz

- HPF 35 Hz, 12 dB/oct — Remove subsonic rumble and stage floor vibration that build up in a reverberant room.
- +5 dB @ 70 Hz (Q 0.8) — Reinforce the instrument's fundamental to read on the PA and retain perceived weight in a live venue.
- -4 dB @ 300 Hz (Q 1.5) — Reduce boxy/muddy resonances that smear in a ringy room and obscure clarity.
- +3 dB @ 3.5 kHz (Q 1.2) — Add presence/attack so transients cut through reverberant decay and maintain definition.
- LPF/roll-off above 12 kHz — Shape the upper harmonics for clarity and air; dynamic EQ used where boost/cut should only occur when problematic.
- Use tight gate and fast FET to preserve attack; emphasize click to cut through reverb-heavy room.

Ch 14 – Snare

Mic – Lauten Audio Snare Mic

Standard Compressor	Value
Threshold	-12 dB
Ratio	4:1
Attack	12 ms
Release	90 ms
Makeup	+3 dB

Standard Gate/Expander	Value
Threshold	-45 dB
Attack	5 ms
Hold	80 ms
Release	150 ms

Mustard Tube	Value
--------------	-------

Drive (0-1)	0.55
Type	Even Harmonics
Output (dB)	-6 dB

Mustard EQ	Band / Setting
Not used	-

Mustard Dynamics — Row 1	Flavor: Green (FET / 1176) Input Drive: +6 dB Ratio: 8 Attack: 800 μ s Release: 100 ms
Mustard Dynamics — Row 2	Output Trim: +3 dB Notes: Drive for 3–6 dB GR — fast attack to catch transients; adjust ratio to taste.

Standard EQ Band (High → Low)	Setting
HPF	50 Hz
Body	+4 dB @ 180 Hz (Q 2.0)
Boxiness	-6 dB @ 500 Hz (Q 1.5)
Crack	+3 dB @ 4 kHz (Q 2.0)
Air	+2 dB shelf @ 8 kHz

- HPF 50 Hz — Remove subsonic rumble and stage floor vibration that build up in a reverberant room.
- +4 dB @ 180 Hz (Q 2.0) — Reinforce the instrument's fundamental to read on the PA and retain perceived weight in a live venue.
- -6 dB @ 500 Hz (Q 1.5) — Reduce boxy/muddy resonances that smear in a ringy room and obscure clarity.
- +3 dB @ 4 kHz (Q 2.0) — Add presence/attack so transients cut through reverberant decay and maintain definition.
- +2 dB shelf @ 8 kHz — Shape the upper harmonics for clarity and air; dynamic EQ used where boost/cut should only occur when problematic.
- FET compression for transient control; tube for presence. Scoop boxy mids which build up in the room.

Ch 15 – OH Left

Mic – Earthworks SR20sp

Standard Compressor	Value
Threshold	-12 dB
Ratio	4:1
Attack	12 ms
Release	90 ms
Makeup	+3 dB

Standard Gate/Expander	Value
Threshold	-45 dB
Attack	5 ms
Hold	80 ms
Release	150 ms

Mustard Tube	Value
Drive (0-1)	0.55

Type	Even Harmonics
Output (dB)	-6 dB
Mustard EQ	Band / Setting
Not used	-
Mustard Dynamics — Row 1	Flavor: Red Threshold/Input: -10 dB Ratio: 4:1 Attack: 12 ms Release: 100 ms
Mustard Dynamics — Row 2	Output Trim: +2 dB Notes: Flavor-specific behavior — use for color or smooth control.
Standard EQ Band (High → Low)	Setting
HPF	100 Hz
Mud	-3 dB @ 300-600 Hz (Q 1.5)
Sheen	+5 dB shelf @ 10-12 kHz
Harsh	Dynamic cut 4-6 kHz if needed
Shelf	+2 dB @ 12 kHz

- HPF 100 Hz — Remove subsonic rumble and stage floor vibration that build up in a reverberant room.
- -3 dB @ 300-600 Hz (Q 1.5) — Reduce boxy/muddy resonances that smear in a ringy room and obscure clarity.
- +5 dB shelf @ 10-12 kHz — Shape the upper harmonics for clarity and air; dynamic EQ used where boost/cut should only occur when problematic.
- Dynamic cut 4-6 kHz if needed — Shape the upper harmonics for clarity and air; dynamic EQ used where boost/cut should only occur when problematic.
- +2 dB @ 12 kHz — Gentle shelf/roll to control extreme highs that exaggerate in reflective rooms.
- Preserve cymbal air but remove low-mid wash that smears in the hall.

Ch 16 – OH Right

Mic – Earthworks SR20sp

Standard Compressor	Value
Threshold	-12 dB
Ratio	4:1
Attack	12 ms
Release	90 ms
Makeup	+3 dB
Standard Gate/Expander	Value
Threshold	-45 dB
Attack	5 ms
Hold	80 ms
Release	150 ms
Mustard Tube	Value
Drive (0-1)	0.55
Type	Even Harmonics

Output (dB)	-6 dB
Mustard EQ	Band / Setting
Not used	-

Mustard Dynamics — Row 1	Flavor: Red Threshold/Input: -10 dB Ratio: 4:1 Attack: 12 ms Release: 100 ms
Mustard Dynamics — Row 2	Output Trim: +2 dB Notes: Flavor-specific behavior — use for color or smooth control.

Standard EQ Band (High → Low)	Setting
HPF	100 Hz
Mud	-3 dB @ 300-600 Hz (Q 1.5)
Sheen	+5 dB shelf @ 10-12 kHz
Harsh	Dynamic cut 4-6 kHz if needed
Shelf	+2 dB @ 12 kHz

- HPF 100 Hz — Remove subsonic rumble and stage floor vibration that build up in a reverberant room.
- -3 dB @ 300-600 Hz (Q 1.5) — Reduce boxy/muddy resonances that smear in a ringy room and obscure clarity.
- +5 dB shelf @ 10-12 kHz — Shape the upper harmonics for clarity and air; dynamic EQ used where boost/cut should only occur when problematic.
- Dynamic cut 4-6 kHz if needed — Shape the upper harmonics for clarity and air; dynamic EQ used where boost/cut should only occur when problematic.
- +2 dB @ 12 kHz — Gentle shelf/roll to control extreme highs that exaggerate in reflective rooms.
- Preserve cymbal air but remove low-mid wash that smears in the hall.

Ch 17 – Violin / Viola

Mic – Line Audio CM4

Standard Compressor	Value
Threshold	-12 dB
Ratio	4:1
Attack	12 ms
Release	90 ms
Makeup	+3 dB

Standard Gate/Expander	Value
Threshold	-45 dB
Attack	5 ms
Hold	80 ms
Release	150 ms

Mustard Tube	Value
Drive (0-1)	0.55
Type	Even Harmonics
Output (dB)	-6 dB

Mustard EQ	Band / Setting
Not used	-

Mustard Dynamics — Row 1	Flavor: Purple Threshold/Input: -10 dB Ratio: 4:1 Attack: 12 ms Release: 100 ms
Mustard Dynamics — Row 2	Output Trim: +2 dB Notes: Flavor-specific behavior — use for color or smooth control.

Standard EQ Band (High → Low)	Setting
HPF	70 Hz
Mud	-3 dB @ 250 Hz
Presence	+3 dB @ 4 kHz
Air	+2 dB @ 10 kHz
Note	Use dynamic EQ in 3-5 kHz if harsh

- HPF 70 Hz — Remove subsonic rumble and stage floor vibration that build up in a reverberant room.
- -3 dB @ 250 Hz — Reduce boxy/muddy resonances that smear in a ringy room and obscure clarity.
- +3 dB @ 4 kHz — Shape the upper harmonics for clarity and air; dynamic EQ used where boost/cut should only occur when problematic.
- +2 dB @ 10 kHz — Shape the upper harmonics for clarity and air; dynamic EQ used where boost/cut should only occur when problematic.
- Use dynamic EQ in 3-5 kHz if harsh — Practical note: use surgical cuts and dynamic bands to address room- excited peaks.
- Conservative processing; verify on stage and adjust band gains to taste.

Ch 18 – Bass

Mic – Schoeps MK4

Standard Compressor	Value
Threshold	-12 dB
Ratio	4:1
Attack	12 ms
Release	90 ms
Makeup	+3 dB

Standard Gate/Expander	Value
Threshold	-45 dB
Attack	5 ms
Hold	80 ms
Release	150 ms

Mustard Tube	Value
Drive (0-1)	0.55
Type	Even Harmonics
Output (dB)	-6 dB

Mustard EQ	Band / Setting
Not used	-

Mustard Dynamics — Row 1	Flavor: Green (FET / 1176) Input Drive: +6 dB Ratio: 8 Attack: 800 μ s Release: 100 ms
Mustard Dynamics — Row 2	Output Trim: +3 dB Notes: Drive for 3–6 dB GR — fast attack to catch transients; adjust ratio to taste.

Standard EQ Band (High → Low)	Setting
HPF	40 Hz
Sub	+5 dB @ 70 Hz (Q 0.9)
Mud	-4 dB @ 300-400 Hz
Clarity	+3 dB @ 1.2 kHz
Roll-off	10 kHz

- HPF 40 Hz — Remove subsonic rumble and stage floor vibration that build up in a reverberant room.
- +5 dB @ 70 Hz (Q 0.9) — Reinforce the instrument's fundamental to read on the PA and retain perceived weight in a live venue.
- -4 dB @ 300-400 Hz — Reduce boxy/muddy resonances that smear in a ringy room and obscure clarity.
- +3 dB @ 1.2 kHz — Practical note: use surgical cuts and dynamic bands to address room-excited peaks.
- 10 kHz — Gentle shelf/roll to control extreme highs that exaggerate in reflective rooms.
- Reinforce fundamental and tame 300-400 Hz to avoid masking vocals/instruments.

Ch 19 – Cello

Mic – Royer R10

Standard Compressor	Value
Threshold	-12 dB
Ratio	4:1
Attack	12 ms
Release	90 ms
Makeup	+3 dB

Standard Gate/Expander	Value
Threshold	-45 dB
Attack	5 ms
Hold	80 ms
Release	150 ms

Mustard Tube	Value
Drive (0-1)	0.55
Type	Even Harmonics
Output (dB)	-6 dB

Mustard EQ	Band / Setting
Not used	-

Mustard Dynamics — Row 1	Flavor: Purple Threshold/Input: -10 dB Ratio: 4:1 Attack: 12 ms Release: 100 ms
Mustard Dynamics — Row 2	Output Trim: +2 dB Notes: Flavor-specific behavior — use for color or smooth control.

Standard EQ Band (High → Low)	Setting
HPF	60 Hz
Body	+4 dB @ 200 Hz
Mid Cut	-3 dB @ 500 Hz
Presence	+2 dB @ 3 kHz
Note	Optical comp helps sustain

- HPF 60 Hz — Remove subsonic rumble and stage floor vibration that build up in a reverberant room.
- +4 dB @ 200 Hz — Reinforce the instrument's fundamental to read on the PA and retain perceived weight in a live venue.
- -3 dB @ 500 Hz — Reduce boxy/muddy resonances that smear in a ringy room and obscure clarity.
- +2 dB @ 3 kHz — Shape the upper harmonics for clarity and air; dynamic EQ used where boost/cut should only occur when problematic.
- Optical comp helps sustain — Practical note: use surgical cuts and dynamic bands to address room-excited peaks.
- Conservative processing; verify on stage and adjust band gains to taste.

Ch 20 – Acoustic Guitar

Mic – Neve RNDI

Standard Compressor	Value
Threshold	-12 dB
Ratio	4:1
Attack	12 ms
Release	90 ms
Makeup	+3 dB

Standard Gate/Expander	Value
Threshold	-45 dB
Attack	5 ms
Hold	80 ms
Release	150 ms

Mustard Tube	Value
Drive (0-1)	0.55
Type	Even Harmonics
Output (dB)	-6 dB

Mustard EQ	Band / Setting
Not used	-

Mustard Dynamics — Row 1	Flavor: Blue Threshold/Input: -10 dB Ratio: 4:1 Attack: 12 ms Release: 100 ms
Mustard Dynamics — Row 2	Output Trim: +2 dB Notes: Flavor-specific behavior — use for color or smooth control.

Standard EQ Band (High → Low)	Setting
HPF	60 Hz
Body	+2 dB @ 120 Hz
Mud	-3 dB @ 250 Hz
Presence	+4 dB @ 8 kHz
Note	Consider DI blend for low end

- HPF 60 Hz — Remove subsonic rumble and stage floor vibration that build up in a reverberant room.
- +2 dB @ 120 Hz — Reinforce the instrument's fundamental to read on the PA and retain perceived weight in a live venue.
- -3 dB @ 250 Hz — Reduce boxy/muddy resonances that smear in a ringy room and obscure clarity.
- +4 dB @ 8 kHz — Shape the upper harmonics for clarity and air; dynamic EQ used where boost/cut should only occur when problematic.
- Consider DI blend for low end — Practical note: use surgical cuts and dynamic bands to address room-excited peaks.
- Conservative processing; verify on stage and adjust band gains to taste.

Ch 21 – Air Organ

Mic – XLR (unspecified)

Standard Compressor	Value
Threshold	-12 dB
Ratio	4:1
Attack	12 ms
Release	90 ms
Makeup	+3 dB

Standard Gate/Expander	Value
Threshold	-45 dB
Attack	5 ms
Hold	80 ms
Release	150 ms

Mustard Tube	Value
Drive (0-1)	0.55
Type	Even Harmonics
Output (dB)	-6 dB

Mustard EQ	Band / Setting
Not used	-

Mustard Dynamics — Row 1	Flavor: Purple Threshold/Input: -10 dB Ratio: 4:1 Attack: 12 ms Release: 100 ms
Mustard Dynamics — Row 2	Output Trim: +2 dB Notes: Flavor-specific behavior — use for color or smooth control.

Standard EQ Band (High → Low)	Setting
HPF	100 Hz
Shelf	+3 dB @ 8-10 kHz
Cut	-3 dB @ 600-800 Hz
Body	+2 dB @ 150-200 Hz
Note	Adjust to taste

- HPF 100 Hz — Remove subsonic rumble and stage floor vibration that build up in a reverberant room.
- +3 dB @ 8-10 kHz — Gentle shelf/roll to control extreme highs that exaggerate in reflective rooms.
- -3 dB @ 600-800 Hz — Applied to balance frequency energy for live PA translation.
- +2 dB @ 150-200 Hz — Reinforce the instrument's fundamental to read on the PA and retain perceived weight in a live venue.
- Adjust to taste — Practical note: use surgical cuts and dynamic bands to address room-excited peaks.
- Conservative processing; verify on stage and adjust band gains to taste.

Ch 22 – Kelly Interface Left

Mic – XLR (unspecified)

Standard Compressor	Value
Threshold	-12 dB
Ratio	4:1
Attack	12 ms
Release	90 ms
Makeup	+3 dB

Standard Gate/Expander	Value
Threshold	-45 dB
Attack	5 ms
Hold	80 ms
Release	150 ms

Mustard Tube	Value
Drive (0-1)	0.55
Type	Even Harmonics
Output (dB)	-6 dB

Mustard EQ	Band / Setting
Not used	-

Mustard Dynamics — Row 1	Flavor: Purple Threshold/Input: -10 dB Ratio: 4:1 Attack: 12 ms Release: 100 ms
Mustard Dynamics — Row 2	Output Trim: +2 dB Notes: Flavor-specific behavior — use for color or smooth control.

Standard EQ Band (High → Low)	Setting
HPF	100 Hz
Shelf	+3 dB @ 8-10 kHz
Cut	-3 dB @ 600-800 Hz
Body	+2 dB @ 150-200 Hz
Note	Adjust to taste

- HPF 100 Hz — Remove subsonic rumble and stage floor vibration that build up in a reverberant room.
- +3 dB @ 8-10 kHz — Gentle shelf/roll to control extreme highs that exaggerate in reflective rooms.
- -3 dB @ 600-800 Hz — Applied to balance frequency energy for live PA translation.
- +2 dB @ 150-200 Hz — Reinforce the instrument's fundamental to read on the PA and retain perceived weight in a live venue.
- Adjust to taste — Practical note: use surgical cuts and dynamic bands to address room-excited peaks.
- Conservative processing; verify on stage and adjust band gains to taste.

Ch 23 – Kelly Interface Right

Mic – XLR (unspecified)

Standard Compressor	Value
Threshold	-12 dB
Ratio	4:1
Attack	12 ms
Release	90 ms
Makeup	+3 dB

Standard Gate/Expander	Value
Threshold	-45 dB
Attack	5 ms
Hold	80 ms
Release	150 ms

Mustard Tube	Value
Drive (0-1)	0.55
Type	Even Harmonics
Output (dB)	-6 dB

Mustard EQ	Band / Setting
Not used	-

Mustard Dynamics — Row 1	Flavor: Purple Threshold/Input: -10 dB Ratio: 4:1 Attack: 12 ms Release: 100 ms
Mustard Dynamics — Row 2	Output Trim: +2 dB Notes: Flavor-specific behavior — use for color or smooth control.

Standard EQ Band (High → Low)	Setting
HPF	100 Hz
Shelf	+3 dB @ 8-10 kHz
Cut	-3 dB @ 600-800 Hz
Body	+2 dB @ 150-200 Hz
Note	Adjust to taste

- HPF 100 Hz — Remove subsonic rumble and stage floor vibration that build up in a reverberant room.
- +3 dB @ 8-10 kHz — Gentle shelf/roll to control extreme highs that exaggerate in reflective rooms.
- -3 dB @ 600-800 Hz — Applied to balance frequency energy for live PA translation.
- +2 dB @ 150-200 Hz — Reinforce the instrument's fundamental to read on the PA and retain perceived weight in a live venue.
- Adjust to taste — Practical note: use surgical cuts and dynamic bands to address room-excited peaks.
- Conservative processing; verify on stage and adjust band gains to taste.

Seventh Heaven Pro — Wet Presets (Live FOH)

Page	Preset	Decay	Pre-Delay	Size	HF Damping	Mix
ums	Studio B	1.2 s	20 ms	Medium	6 kHz	100%
are	Rich Plate 1	1.4 s	12 ms	Medium	Flat	100%
itar/Bass	Plate 2	1.5 s	15 ms	Medium	8 kHz	100%
ano/Keys	Chamber	1.8 s	25 ms	Large	7 kHz	100%
rns	Small Hall	1.4 s	20 ms	Medium	6.5 kHz	100%
nd	Studio A	1.6 s	10 ms	Medium	7.5 kHz	100%
cals Hall	Vocal Hall	2.2 s	25 ms	Large	8 kHz	100%
cals Plate	Vocal Plate	1.8 s	15 ms	Medium	8.5 kHz	100%
cals Chamber	Vocal Chamber	1.5 s	20 ms	Medium	7 kHz	100%