

Mic & DI Library

Brian Lloyd · Jazz at the Memo · Memorial Hall, Cincinnati

DYNAMICS

Model	Pattern	Primary Applications	Notes / Phantom
Shure SM57	Cardioid	Snare, guitar cab, brass, perc, utility	Standalone · No phantom
Shure SM58	Cardioid	Handheld vocals	Standalone · No phantom
Shure Beta 52	Supercardioid	Kick drum — body/thump layer (inside)	Standalone · No phantom
Shure Beta 58	Supercardioid	Handheld vocals — higher off-axis rejection than SM58	Standalone · No phantom
Sennheiser MD421	Cardioid	Toms, guitar cabs, brass, woodwinds	Standalone · 5-pos bass rolloff · No phantom
Sennheiser e609	Supercardioid	Guitar cab (side-address — hang over cab face)	Standalone · No phantom
Sennheiser e604	Cardioid	Toms, snare (clip-on mount)	Standalone · No phantom
Audix D6	Cardioid	Kick drum — attack/click layer (inside)	Standalone + DP8 · No phantom
Audix i5	Cardioid	Snare — tight, punchy	DP8 · No phantom
Audix D2	Cardioid	Small/mid toms	DP8 · No phantom
Audix D4	Cardioid	Floor tom — more low-end extension than D2	DP8 · No phantom
sE V-Kick	Dynamic	Kick drum — compact alternative	V Pack Arena · No phantom
sE V-Beat	Dynamic	Toms — V-Clamp rim mount	V Pack Arena · No phantom
sE V7 X	Supercardioid	Snare — dynamic instrument mic	V Pack Arena · No phantom

SMALL DIAPHRAGM CONDENSERS

Model	Pattern	Primary Applications	Notes / Phantom
Shure SM81	Cardioid	Overheads, hi-hat, acoustic instruments	Standalone · Requires 48V
Shure Beta 91	Boundary (half-card.)	Kick drum — attack layer (inside, on head)	Standalone · Requires 48V; pair with Beta 52
AKG C422	Stereo coincident	Stereo overheads, acoustic piano	Standalone · Requires 48V; XY pair in one body
DPA 4099	Supercardioid	Instrument clip — strings, brass, woodwinds, piano, guitar; spot mic on kit	Standalone · Requires 48V; 144 dB SPL; instrument-specific mounts
Audix M1280BHC	Cardioid	Hi-hat — ultra-compact condenser clip mic	DP8 · Requires 48V
Audix M1280B (pr)	Cardioid	Overheads / cymbals — compact matched pair	DP8 · Requires 48V
Earthworks DM6	Supercardioid	Kick drum — condenser; wide freq response; solo or layer with dynamic	DK-6 · Requires 48V; Triad-Orbit M2-R mount included
Earthworks DM17	Cardioid	Snare, toms — rim-mount (RM3); condenser clarity on kit	DK-6 · Requires 48V; RM3 rim mount included
Earthworks SR20sp G2	Cardioid	Drum overheads — matched stereo pair	DK-6 · Requires 48V
Earthworks SR25	Cardioid	Overheads (×2) or kick (×1) — 3 mics in DK-25	DK-25 · Requires 48V
sE sE8	Cardioid	Drum overheads — matched stereo pair	V Pack Arena · Requires 48V
Schoeps CMC6 + MK4	Cardioid	Classical overheads, acoustic soloists, spot mics	Standalone · Requires 48V; interchangeable cap body
Schoeps CMC6 + MK5	Omni / Cardioid	Classical room, Decca tree, wide ambient	Standalone · Requires 48V; switchable
Sennheiser MKH 40 (pr)	Cardioid	Classical main pair — ORTF, NOS, spaced omni	Standalone · Requires 48V; extremely low self-noise
Line Audio OM1 (pr)	Omni pressure	Crowd / ambient — flown 18' above stage at The Memo	Standalone · Requires 48V; EQ in venue notes
Line Audio CM4 (pr)	Cardioid (ORTF pr)	Crowd, balcony rear-facing at The Memo	Standalone · Requires 48V; EQ in venue notes

LARGE DIAPHRAGM CONDENSERS

Model	Pattern(s)	Primary Applications	Notes / Phantom
Neumann KMS 105	Supercardioid	Lead vocals (stage condenser) — detail and presence over dynamics	Requires 48V; designed for live handheld use
Neumann TLM 102	Cardioid	Studio/recording vocals, acoustic instruments, overheads	Requires 48V; transformerless; low self-noise
Shure Beta 27	Cardioid	Vocals, overheads, acoustic instruments	Requires 48V; low-cut & -15dB pad switches
AKG C414	Omni / Cardioid / Fig-8 / Supercard	Versatile — room, overheads, vocals, brass, strings	Requires 48V; multiple pattern/pad/HPF switches

RIBBONS

Model	Pattern	Primary Applications	Notes / Phantom
Royer R-121	Figure-8	Guitar cab blend mic (pair with SM57)	NO 48V — phantom will destroy ribbon. Sit 6–10 dB below SM57. Polarity-check in mono. VCA-group with 57.
Royer R-10	Figure-8	Guitar cab, room, acoustic instruments — compact ribbon alternative to R-121	NO 48V — phantom will destroy ribbon.
AEA R88	Stereo Fig-8 (Blumlein)	Room, overhead, acoustic ensemble	NO 48V — phantom will destroy ribbon. Handle with care. High output — watch gain.

■ RIBBON WARNING: Never apply 48V phantom power to the R-121 or R88. Always verify phantom is OFF on these channels before patching.

SHOTGUN / SPECIALTY

Model	Pattern	Primary Applications	Notes / Phantom
Deity S2 (pr)	Short shotgun	Crowd — under main-floor PA, aimed into audience at The Memo	Requires 48V; EQ starting points in venue notes

DRUM KIT PACKAGES — INVENTORY SUMMARY

Package	Confirmed Contents	Notes
Audix DP8	D6 (kick) · i5 (snare) · D2 ×2 (rack toms) · D4 ×1 (floor tom) · M1280BHC (hi-hat) · M1280B ×2 (overheads)	8 mics total; D6 also owned standalone
Audix D6 (standalone)	Single kick mic — cardioid dynamic	Attack/click layer inside kick
sE Electronics V Pack Arena	V-Kick (kick) · V-Beat ×3 w/ V-Clamps (toms) · V7 X dynamic (snare) · sE8 matched pair (overheads) · Pelican-style case	All-dynamic except sE8 OHs; 7 mics total
Earthworks DK-6	DM6 supercardioid condenser w/ Triad-Orbit mount (kick) · DM17 ×4 w/ RM3 rim mounts (snare/toms) · SR20sp Gen 2 stereo pair (overheads) · SKB hard case	7 mics total; all require 48V
Earthworks DK-25	SR25 ×3 (2× overhead, 1× kick) · KickPad (kick drum pad/mount)	3 mics total; all require 48V

Individual mics from each kit are listed in their respective category sections above (Dynamics / SDC) for quick reference during patching.

DIS — DIRECT BOXES

Model	Type	Primary Applications	Notes / Phantom
Radial J48	Active (phantom)	General-purpose DI — keys, bass, acoustic guitar, playback	Requires 48V; best-in-class active; Jensen-style transformer output
Neve RNDI	Active (phantom)	Hi-Z instrument DI — electric bass, guitar direct, synth	Requires 48V; transformer-balanced; excellent for bass clarity and harmonic character

DOCUMENTED MIC PAIRINGS

SM57 + R-121 on SR Guitar (Memorial Hall CH 13 / 15): Set SM57 level first — it is the primary. Bring R-121 up from zero until brittleness reduces. Typical blend: R-121 sits 6–10 dB below SM57. Polarity-check in mono — combined should be fuller than either alone; flip R-121 if thinner. Group both to same VCA for level riding. Post-blend: watch 300–500 Hz buildup on bus EQ; notch –2 to –3 dB if needed.