

Seventh Heaven Pro

Reference Guide — Memorial Hall / Live Sound

Brian Lloyd | Liquidsonics Seventh Heaven Professional | Sources: Manual v1.5.7 & Presets List v1.100

All factory specs verified against official Liquidsonics documentation. Control descriptions accurate to plugin implementation.

Plugin Overview

Seventh Heaven Pro is a Bricasti M7 emulation using Liquidsonics' Fusion-IR technique — multiple impulse responses at different decay-time points are convolved and mixed for a living, non-static reverb field. The result is the closest available software emulation of M7 behavior, including authentic modulation character per algorithm and accurate early reflection patterns.

236 presets across 12 banks. Three algorithm types. 32 discrete early reflection patterns, each individually captured from hardware M7 units.

V1 — Static / Realistic

Low modulation. Stable, accurate M7 character. Preserves source identity. Use for classical, jazz, acoustic folk, Celtic, chamber, any context where you want the instrument to stay itself. The default choice.

Nonlinear

Non-decaying initial region (~50–300ms depending on size setting) followed by a short ~200ms exponential tail. Gated-style effect. Use for snare/drum effects. Not a primary tool at Memorial Hall.

V2 — Modulated / Lush

Brighter, more shimmer and bloom. Sustained wash. Use for gospel, contemporary, dense choir, synth pads, pop/rock. When you want the reverb to be a texture rather than a room.

Rule of thumb

Acoustic shows: V1. Contemporary: V2 for plates and vocals, V1 for halls. When uncertain: V1.

Controls Reference

All descriptions are accurate to Seventh Heaven Pro as implemented in plugin versions referenced above. Several control names differ from common reverb conventions — read carefully before writing channel cards.

Decay Time

RT60 in seconds. Right-click "Decay Time" to jump to exact sampled M7 values — interpolation between those points is good but landing on a sampled value gives you the actual M7 capture. At Memorial Hall (RT60 ~1.6s working), pull factory decay 30–40% as a starting point. The room adds the late field; you're adding placement and character.

Exception: Close-mic'd dry sources (DI bass, kick inside, lip-close vocal) can run longer — the mic isn't capturing natural room so reverb has to provide context.

Pre-delay

Delays the onset of the late reverb and VLF only. **Does not move the early reflections** — that's an M7 design behavior, and the plugin replicates it accurately. Range 0–500ms, tempo-sync available. Minimum 10ms on most sends; 20–30ms on vocals.

VLF — Very Low Frequency Reverb

VLF is a single level slider. It controls the level of the M7's dedicated sub-200Hz reverb component, which provides body and fullness to the reverb tail. It is NOT an EQ band, and it is NOT a binary cut. Factory values range from 0dB (Studio B Close) to –20dB (Sunset Chamber) relative to the late tail level. VLF has its own metering lane separate from early reflections and late tail.

At Memorial Hall, the room is already reinforcing 60–315Hz through standing waves. Cut VLF significantly from factory:

- Classical / acoustic: –18 to –20dB, or off entirely
- Jazz / folk: –15 to –18dB
- Contemporary / gospel: –12 to –15dB (can use more VLF for sub density on vocals/drums)

Watch: Studio B Close (0dB factory) and Boston Hall A (–2dB factory) — always cut these hard at Memo before anything else.

Early / Late (Balance Slider)

Early/Late is a single balance slider — not two separate level controls. It adjusts the ratio of early reflections to late reverb field relative to the preset's captured M7 balance. The Liquidsonics presets PDF shows Early and Late as separate dB values — those are the M7 hardware's original capture levels, shown for reference. You control them with one slider in the plugin.

Push Early↑ for room placement without long tail. Push Late↑ for bloom and wash. At Memo, most sends benefit from slightly Early↑ — the room handles the late field.

Early Reflections Set (0–31)

32 discrete early reflection patterns individually sampled from M7 hardware. Lower numbers = smaller, closer spaces. Higher numbers = larger, more distant or reflective environments. Within each group: 0–9 closest, 10–19 moderate, 20–25 further, 26–31 most distant. Factory Early Select value is listed in the spec tables below.

Early Rolloff / Late Rolloff

These controls are not called "HF Damp." That term does not exist in Seventh Heaven Pro. There are two separate filter cutpoint controls: Early Rolloff (affects HF content of early reflections) and Late Rolloff (where the late tail starts losing HF). Both are modeled on the M7's actual filter curves.

- **Late Rolloff** — the primary tweak at Memo. 4–6kHz for classical/acoustic (matches room HF absorption with audience). 6–9kHz for jazz/folk. 8–10kHz for contemporary.
- **Early Rolloff** — controls HF content of the early reflection pattern. Usually leave at factory unless the early reflections feel too harsh.

Frequency Dependent Decay Time

HF and LF multipliers relative to the main RT60, with adjustable crossover frequencies. A LF multiplier below 1.0 can tighten bass reverb time without touching the main decay — useful at Memo with low-end buildup. **This is a separate system from the Master Filter EQ.**

Master Filter (Return EQ)

Master Filter has 3 bands — not 5. Low band (switchable shelf/bell), mid band (fixed bell), high band (switchable shelf/bell). The high-cut uses a Massberg 12dB/oct low-pass filter. The system runs at twice the project sample rate. Master Filter EQ and Frequency Dependent Decay Time are separate, independent systems.

Use the high shelf for taming air on room reverbs, low shelf for reducing muddiness on longer decays. At Memo, a high shelf cut (–2 to –4dB above 8kHz) is sometimes useful on hall presets to compensate for the room's natural HF brightness.

Ducker

Correct mode names: "Reverb" and "Wet mix." Previous documentation referred to these as "Late" and "Full" — those are not the correct names.

- **Reverb mode** — ducks the late tail AND VLF. Early reflections remain at full level during ducking. Best for vocals: early reflections provide placement between phrases while the tail ducks.
- **Wet mix mode** — ducks everything: early reflections, late tail, and VLF.

Controls: Threshold, Ratio, Release, Trim. For vocal sends at Memo: Reverb mode, Threshold around –20 to –25dB, Release 200–400ms.

Reverb Line Format (Locked)

Use this format in all show paperwork channel card Quick Summaries and reverb notes.

Preset: [Bank / Name] | Decay Xs • PreDelay Xms • VLF [dB or off] • E/L [Early↑ / Balanced / Late↑] • Late Rolloff [kHz] • Mix X% — [rationale]

Example: Preset: Halls 1 / Boston Hall A | Decay 1.3s • PreDelay 20ms • VLF -18dB • E/L Early↑ • Late Rolloff 5kHz • Mix 18% — classical vocal; room handles late field, early gives placement

Include return EQ (high shelf / low cut) where applied. Note ducker settings (mode + threshold) for vocal sends. VLF is listed as dB value or "off" — never abbreviated as "cut" without a value.

Memorial Hall Context

RT60: ~1.6s working (2.2s was the pre-renovation/empty estimate — use 1.6s for all processing decisions).

Problem zones: 63Hz, 125Hz, 200Hz, 250–315Hz standing waves. The room is already doing reverb work — treat this as the third layer in any reverb stack.

Starting rule: pull factory decay 30–40%. Then trim VLF hard. Push Early/Late slightly Early↑.

Tweak Priority Order (Memo)

1. **Decay** — pull 30–40% from factory (see Factory Specs tables for starting numbers).
2. **VLF** — cut from factory. Room reinforces 60–315Hz. Studio B Close and Boston Hall A especially: factory VLF is 0dB and -2dB respectively — always the first thing to cut.
3. **Pre-delay** — 10ms minimum on most sends; 20–30ms on vocals. Remember: pre-delay moves late reverb and VLF only, not early reflections.
4. **Late Rolloff** — 4–6kHz classical/acoustic; 6–9kHz jazz/folk; 8–10kHz contemporary.
5. **Early/Late balance** — push slightly Early↑ on most sends. Room handles late field.
6. **Ducker** — Reverb mode on vocal sends. Keeps early reflections up between phrases.

Layering

Classic two-reverb approach: short chamber/plate (close perspective) + long hall pre-delayed 40–80ms (tail). At Memo, the room is the third layer — most useful on close-mic'd sources not picking up much natural room.

Example vocal chain: Chambers 1 / Vocal Chamber (1.0s, 10ms pre-delay) + Halls 1 / Boston Hall A (1.3s, 50ms pre-delay). Both VLF at -18dB+. Vocal Chamber gives place; Boston Hall adds size between phrases.

Factory Specs — Halls

All values from Liquidsonics Seventh Heaven Professional Presets List v1.100. Early Bal / Late Bal = the M7 hardware's original capture levels (reference). Late Rolloff = factory frequency cutpoint. Early Set = factory early reflection index (0–31).

Preset	Decay	PreDly	VLF	Early Bal	Late Bal	Late Rolloff	Early Set	Algo	Memo Notes
Halls 1 / Concert Hall	2.20s	18ms	-10dB	0dB	0dB	5200Hz	19	V1	Full ensemble. Pull to 1.3–1.4s. VLF off or -20dB.
Halls 1 / Boston Hall A	2.10s	0ms	-2dB	-2dB	0dB	6000Hz	12	V1	Solo/chamber. Pull to 1.2–1.3s. <i>VLF only -2dB factory — cut hard.</i>
Halls 1 / Boston Hall B	1.80s	0ms	-9dB	-2dB	0dB	4800Hz	9	V1	Smaller/darker alt. Pull to 1.1–1.3s.
Halls 1 / Piano Hall	2.00s	24ms	-8dB	-4dB	0dB	6400Hz	16	V1	Piano solo. Pull to 1.2s. VLF to -18dB+. Stereo send.
Halls 1 / Sandors Hall	2.60s	20ms	-14dB	-1dB	0dB	5600Hz	19	V1	Dense. Pull to 1.6–1.8s. Gospel: can bring VLF up to -10dB.
Halls 1 / Small Hall	1.40s	0ms	-10dB	-4dB	0dB	5600Hz	6	V1	Flute, woodwinds. Pull to 0.9–1.0s.
Halls 1 / Brass Hall	2.00s	20ms	-11dB	0dB	-2dB	8400Hz	19	V1	Brass section. Factory Rolloff 8400Hz bright — pull to 6kHz at Memo.
Halls 2 / Large Hall	2.35s	24ms	-13dB	-12dB	0dB	3600Hz	21	V2	Keys/synth. Pull to 1.5–1.7s. Early Bal -12dB = inherently early-heavy.

Halls 2 / Jazz Church	1.35s	0ms	−10dB	−12dB	0dB	8800Hz	20	V2	V2 modulation. Pull to 0.9s.
-----------------------	-------	-----	-------	-------	-----	--------	----	----	------------------------------

Factory Specs — Chambers

Preset	Decay	PreDly	VLF	Early Bal	Late Bal	Late Rolloff	Early Set	Algo	Memo Notes
Chambers 1 / Vocal Chamber	1.60s	0ms	−10dB	0dB	0dB	8000Hz	9	V1	Jazz/ classical vocal. Pull to 1.0s. Pre-delay 20–40ms. Ducker on.
Chambers 1 / Sunset Chamber	2.15s	20ms	−20dB	−2dB	0dB	7200Hz	7	V1	Classical vocal. Pull to 1.3–1.5s. Factory VLF already −20dB — good.
Chambers 1 / A&M Chamber	2.20s	20ms	−14dB	−5dB	0dB	6400Hz	7	V1	Strings/ fiddle. Pull to 1.4s. Pre-delay at factory.
Chambers 1 / Small Chamber	1.00s	0ms	−12dB	0dB	0dB	6400Hz	5	V1	Flute, Celtic. Pull to 0.65s.
Chambers 1 / Medium Chamber	1.25s	4ms	−12dB	0dB	0dB	6400Hz	5	V1	Uilleann pipes. Pull to 0.8s.
Chambers 1 / Kick Chamber	0.70s	0ms	−6dB	0dB	0dB	5600Hz	3	V1	Short by design. Cut VLF further at Memo.

Factory Specs — Plates

Preset	Decay	PreDly	VLF	Early Bal	Late Bal	Late Rolloff	Early Set	Algo	Memo Notes
Plates 1 / Snare Plate A	1.20s	0ms	−9dB	0dB	0dB	6800Hz	5	V1	Standard snare. Pull to 0.8s.
Plates 1 / Snare Plate B	1.00s	20ms	−10dB	−1dB	0dB	7200Hz	3	V1	Dense mixes — factory 20ms pre-delay good for snare.
Plates 1 / Vocal Plate	1.50s	24ms	−19dB	0dB	0dB	6400Hz	15	V1	Sits further back. Pull to 1.0s. VLF nearly off at factory.
Plates 1 / Rich Plate	1.90s	0ms	−9dB	−2dB	0dB	9200Hz	4	V1	Gospel BG/ choir. Pull to 1.2–1.3s.
Plates 1 / Dark Plate	1.50s	0ms	−15dB	0dB	0dB	4800Hz	8	V1	Rock/blues vintage snare. Factory 4800Hz already dark.
Plates 2 / Vocal Shimmer	1.80s	20ms	−14dB	−2dB	0dB	8000Hz	8	V2	Contemporary vocal. Pull to 1.1–1.3s. Factory includes baked delay at 236ms/ −10dB — part of the shimmer.

Factory Specs — Rooms

Preset	Decay	PreDly	VLF	Early Bal	Late Bal	Late Rolloff	Early Set	Algo	Memo Notes
Rooms 1 / Studio B Close	0.75s	0ms	0dB	0dB	−7dB	8000Hz	7	V1	Drum bus/ jazz. Pull to 0.5–0.6s. <i>VLF 0dB factory — always cut first at Memo.</i>
Rooms 1 / Studio B Far	0.65s	0ms	−3dB	0dB	−1dB	9200Hz	12	V1	Bodhran alt. Cut VLF.
Rooms 1 / Large Wooden	1.20s	0ms	−9dB	0dB	−1dB	8000Hz	9	V1	Acoustic guitar, Celtic, upright bass. Pull to 0.75s. VLF to −15dB.
Rooms 1 / Small Wooden	0.60s	0ms	−7dB	0dB	0dB	9600Hz	9	V1	Upright bass alt.
Rooms 1 / Djangos Room	0.80s	4ms	−10dB	0dB	−2dB	5200Hz	6	V1	Jazz-club feel. Pull to 0.55s. VLF to −15dB.
Rooms 1 / Small Room	0.60s	0ms	−12dB	0dB	−10dB	6800Hz	6	V1	Very short. Late Bal −10dB = almost no tail at factory.
Rooms 2 / Guitar Room	1.20s	0ms	−11dB	0dB	0dB	5200Hz	25	V2	Electric guitar. Pull to 0.8s. <i>Baked-in delay at 300ms/ −14dB with modulation — leave it.</i>

Factory Specs — Ambiences & Spaces

Preset	Decay	PreDly	VLF	Early Bal	Late Bal	Late Rolloff	Early Set	Algo	Memo Notes
Ambiences 1 / Large Ambience	0.80s	10ms	-10dB	0dB	-10dB	6000Hz	12	V1	Air/glue on full ensemble. Pull to 0.5–0.6s. Late Bal -10dB = early-heavy inherently.
Ambiences 1 / Percussion Air	0.50s	0ms	-6dB	0dB	-11dB	8000Hz	6	V1	Drum bus alt. Very short, very early-heavy.
Spaces 1 / North Church	3.20s	0ms	-6dB	-3dB	0dB	5600Hz	15	V1	Choir/large ensemble alt. Pull hard to 1.8–2.0s. VLF cut from -6dB.

By Genre — Classical / Chamber / Orchestral

V1 throughout. Minimal processing philosophy — spots blend into the room. Nothing aggressive. VLF off or near off across the board.

Use	Preset	Factory	Memo Target	Notes
Full ensemble	Halls 1 / Concert Hall	2.20s	1.3–1.4s	Low modulation, stable. VLF off or –20dB. E/L Early↑. Late Rolloff 4–5kHz.
Solo instrument / small chamber	Halls 1 / Boston Hall A	2.10s	1.2–1.3s	Brighter, empty-hall character. Factory VLF only –2dB — cut aggressively at Memo.
Piano solo	Halls 1 / Piano Hall	2.00s	1.2s	Factory 24ms pre-delay built in. VLF to –18dB+. Stereo send.
Classical vocal	Chambers 1 / Sunset Chamber	2.15s	1.3–1.5s	Factory VLF already –20dB. Low diffusion — keeps source character. Min 20ms pre-delay.
Amplified strings	Chambers 1 / A&M Chamber	2.20s	1.4s	Smooth, mid-forward. Pre-delay 20ms at factory.
Ensemble air / glue	Ambiences 1 / Large Ambience	0.80s	0.5–0.6s	Very short — adds space without obvious tail. VLF down from –10dB factory.

By Genre — Jazz

V1. Rooms and chambers over halls. Keep it tight and natural — Memo's room is warm enough, especially for straight-ahead acoustic jazz.

Use	Preset	Factory	Memo Target	Notes
Drum bus / overheads	Rooms 1 / Studio B Close	0.75s	0.5–0.6s	Factory Late Bal –7dB = inherently early-heavy. VLF 0dB factory — cut to –12dB at Memo.
Acoustic instruments	Rooms 1 / Djangos Room	0.80s	0.55s	Small jazz-club feel. VLF to –15dB.
Upright bass / acoustic guitar	Rooms 1 / Large Wooden	1.20s	0.75s	Natural air. VLF to –15dB.
Lead vocal	Chambers 1 / Vocal Chamber	1.60s	1.0s	Classic chamber. Pre-delay 20–40ms. Ducker on (Reverb mode).
Snare	Plates 1 / Snare Plate A	1.20s	0.8s	Bright and dense.

By Genre — Celtic / Acoustic Folk

Use	Preset	Factory	Memo Target	Notes
Acoustic instruments	Rooms 1 / Large Wooden	1.20s	0.75s	Natural, airy. VLF to –15dB.
Flute / whistles	Chambers 1 / Small Chamber	1.00s	0.65s	Compact, warm.
Uilleann pipes	Chambers 1 / Medium Chamber	1.25s	0.80s	Tight enough to stay clean.
Bodhran	Rooms 1 / Studio B Close	0.75s	0.5s	Short and dense. Cut VLF from 0dB factory.
Vocals	Chambers 1 / Sunset Chamber	2.15s	1.3–1.5s	Warm, characterful. Factory VLF already –20dB.
Fiddle / strings	Chambers 1 / A&M Chamber	2.20s	1.4s	Smooth, mid-forward.

By Genre — Gospel / Contemporary

V1 for halls. V2 for plates and vocal shimmer effects. Can run slightly more VLF than classical — gospel needs the sub density, but still cut from factory at Memo.

Use	Preset	Factory	Memo Target	Notes
Hall / choir wash	Halls 1 / Sandors Hall	2.60s	1.6–1.8s	Dense. Factory VLF –14dB — can bring to –10dB for gospel weight.
Lead vocal (traditional)	Chambers 1 / Vocal Chamber	1.60s	1.0–1.1s	V1 warmth. Ducker on (Reverb mode).
Lead vocal (contemporary)	Plates 2 / Vocal Shimmer	1.80s	1.1–1.3s	V2 bloom. Factory baked delay 236ms/–10dB — part of the shimmer, leave it.
BG / choir vocals	Plates 1 / Rich Plate	1.90s	1.2–1.3s	Warmth and density.
Snare	Plates 1 / Snare Plate A	1.20s	0.8s	Standard.
Drum bus	Rooms 1 / Studio B Close	0.75s	0.5s	Keep drums tight. Cut VLF from 0dB factory.
Keys / synth pads	Halls 2 / Large Hall	2.35s	1.5–1.7s	V2 bloom. VLF –13dB, Early Bal –12dB at factory — inherently early-heavy.

By Genre — Rock / Blues / Americana

Use	Preset	Factory	Memo Target	Notes
Snare (crack)	Plates 1 / Snare Plate A	1.20s	0.8s	Bright and aggressive.
Snare (vintage warmth)	Plates 1 / Dark Plate	1.50s	1.0s	Factory Late Rolloff 4800Hz already dark.
Drum bus	Rooms 1 / Studio B Close	0.75s	0.5s	Dense, dry-ish.
Electric guitar	Rooms 2 / Guitar Room	1.20s	0.8s	V2. Baked-in 300ms delay — pre-built slap, leave it.
Vocal	Chambers 1 / Vocal Chamber	1.60s	1.0–1.1s	Warm. Or Plates 1 / Vocal Plate (1.50s factory, 1.0s Memo) to sit further back.

Quick Picks by Source — Memo

Source	First Choice	Alt	Key Watch-Out
Lead vocal (classical/ acoustic)	Chambers 1 / Sunset Chamber	Chambers 1 / Vocal Chamber	Factory VLF already -20dB on Sunset — good. Cut Vocal Chamber from -10dB.
Lead vocal (contemporary)	Plates 1 / Vocal Plate	Plates 2 / Vocal Shimmer	Vocal Plate VLF -19dB factory. Shimmer has baked delay — keep it.
Choir / group vocals	Halls 1 / Sandors Hall	Spaces 1 / North Church	North Church is 3.2s factory — pull hard to 1.8–2.0s. VLF cut from -6dB.
Snare	Plates 1 / Snare Plate A	Plates 1 / Snare Plate B	Plate B has 20ms factory pre-delay — good for snare in dense mixes.
Kick (layer)	Chambers 1 / Kick Chamber	—	0.70s factory, short by design. VLF -6dB factory — cut further at Memo.
Drum bus / overheads	Rooms 1 / Studio B Close	Ambiences 1 / Percussion Air	Studio B Close VLF 0dB factory — always cut first.
Acoustic guitar	Rooms 1 / Large Wooden	Chambers 1 / Small Chamber	Large Wooden: airy, natural. Small Chamber: tighter, drier.
Piano (solo)	Halls 1 / Piano Hall	Halls 1 / Boston Hall A	Piano Hall factory VLF only -8dB — cut to -18dB+. Boston Hall A factory VLF -2dB — cut hard.
Upright bass	Rooms 1 / Djangos Room	Rooms 1 / Small Wooden	Djangos: 0.80s factory, jazz-club character.
Orchestral strings	Halls 1 / Concert Hall	Halls 1 / Sandors Hall	Concert Hall: stable, low modulation. Sandors: denser, more tail.
Amplified strings (clip-on)	Chambers 1 / A&M Chamber	Rooms 1 / Studio B Far	A&M: smooth '70s. Pre-delay 20ms factory already there.
Brass section	Halls 1 / Brass Hall	Halls 1 / Small Hall	Brass Hall: 8400Hz Late Rolloff factory — bright. Pull to 6kHz at Memo.
Flute / woodwinds	Chambers 1 / Small Chamber	Halls 1 / Small Hall	—
Uilleann pipes	Chambers 1 / Medium Chamber	Rooms 1 / Large Wooden	—
Bodhran	Rooms 1 / Studio B Close	Rooms 1 / Studio B Far	VLF 0dB and -3dB factory on both — always cut.
Underhat / underhead cymbals	Any per show	—	Add +2 to +3dB to reverb send to compensate for reduced natural air pickup.

Sources & Accuracy Notes

All preset names, factory decay times, VLF levels, Early/Late balance values, Late Rolloff frequencies, Early Select indices, and algorithm assignments in this document are verified against:

- **Liquidsonics Seventh Heaven Professional Manual v1.5.7**
- **Liquidsonics Seventh Heaven Professional Presets List v1.100**

Control descriptions are accurate to plugin implementation as documented in Manual v1.5.7.

Corrections vs. Prior Documentation

Was Written	Correct	Source
"HF Damp X.X" control	Does not exist in the plugin. Correct names: Early Rolloff and Late Rolloff (two separate controls)	Manual v1.5.7, Ch. 3
"Early/Late XX/XX" — implying two level values	Single balance slider. The presets PDF shows original M7 capture levels for reference only	Manual v1.5.7; Presets List v1.100
"VLF cut" — implying binary or EQ-style operation	VLF is a continuous level slider (sub-200Hz reverb body), not an EQ band	Manual v1.5.7
Ducker mode "Full" / "Late"	Correct names: "Wet mix" (ducks everything) / "Reverb" (ducks late tail + VLF only — early reflections stay up)	Manual v1.5.7
"Five EQ bands" inconsistency	Master Filter = 3 bands (low, mid, high). Frequency Dependent Decay Time = 2 separate multiplier controls. Different systems entirely.	Manual v1.5.7
Pre-delay described as moving early reflections	Pre-delay affects late reverb and VLF only. Early reflections are unaffected — M7 hardware design behavior	Manual v1.5.7

Operational context: Memorial Hall (Jazz At The Memo), Cincinnati OH. 556 seats, RT60 ~1.6s working, standing wave issues at 63/125/200/250–315Hz. Console: DiGiCo Quantum 225.

Compiled by: Brian Lloyd | Last updated: May 2026