

# Yolo Band

## FOH CHANNEL EQ SETUP — DiGiCo Quantum 225

|                  |                           |
|------------------|---------------------------|
| Show             | Yolo Band                 |
| Show Date        | 2026-07-24                |
| Venue            | Fountain Square (outdoor) |
| Console          | DiGiCo Quantum 225        |
| Channels         | 31                        |
| FOH Engineer     | Brian Lloyd               |
| Monitor Engineer |                           |
| Show Time        |                           |
| Rev              | Rev 1.0 Deep Think        |

DOCUMENT CONTENTS

- 1. Cover Page — show, venue, and personnel
- 2. Input List — color-coded full channel patch sheet
- 3. Patching — AES and Local inputs sorted by port
- 4. EQ Setup — 31 channels for DiGiCo Quantum 225
- 5. Reference — EQ structure, pan guide, bus grouping, soundcheck order

**SHOW STYLE:** Open-air Fountain Square — no room gain, low end + HF dissipate over the throw, façade slap but no reverb tail. Cuts run deeper than indoor (−6 to −9 typ), HPF decisive, clarity first. L-Acoustics A15/KS21 house PA, M32 monitors.

|                                  |                  |                         |
|----------------------------------|------------------|-------------------------|
| <h1>Yolo Band</h1>               |                  |                         |
| VENUE: Fountain Square (outdoor) | DATE: 2026-07-24 | REV: Rev 1.0 Deep Think |
| FOH: Brian Lloyd                 | MON:             | SHOW TIME:              |

**REV: Rev 1.0 Deep Think**

## SHOW TIME:

| Ch       | Instrument | Mic / DI        | Patch    | 48V | Stand | Notes                                                                                                                                                                                                      |
|----------|------------|-----------------|----------|-----|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ■ DRUMS  |            |                 |          |     |       |                                                                                                                                                                                                            |
| 1        | Kick In    | Shure Beta 91A  | Local 1  | ✓   | —     | Beta 91A/D6 kick blend — 91A is the attack/click layer. Treat the pair as ONE: same VCA, pan together, blend constant. Polarity: sum in mono, flip one if thinner. Bus: notch -2/-3 @300-500 if it builds. |
| 2        | Kick Out   | Audix D6        | Local 2  |     | Short | Beta 91A/D6 kick blend — D6 is the sub/body core. Pan together, same VCA.                                                                                                                                  |
| 3        | Snare Top  | Audix i5        | Local 3  |     | Claw  | Snare top/bottom pair — treat with the e604 as one snare; polarity-check the pair.                                                                                                                         |
| 4        | Snare Bot  | Sennheiser e604 | Local 4  |     | Claw  | Bottom head — wire capture only. Polarity-check against the snare top; flip if the pair thins.                                                                                                             |
| 5        | Hat        | Shure SM81      | Local 5  | ✓   | Tall  |                                                                                                                                                                                                            |
| 6        | Rack 1     | Audix D2        | Local 6  |     | Claw  |                                                                                                                                                                                                            |
| 7        | Rack 2     | Audix D2        | Local 7  |     | Claw  |                                                                                                                                                                                                            |
| 8        | Floor      | Audix D4        | Local 8  |     | Claw  |                                                                                                                                                                                                            |
| 9        | OH (st)    | Shure Beta 27   | Local 9  | ✓   | Tall  | STEREO pair on fader 9 (both OH mics on this one fader). FSQ ch 10 is the SNARE PL8 return — not an input.                                                                                                 |
| ■ BASS   |            |                 |          |     |       |                                                                                                                                                                                                            |
| 11       | Bass DI    | XLR (DI)        | Local 11 |     | DI    | Bass DI + PG52 cab blend — INVERTED lanes: DI = definition/mids/top, PG52 = sub/thump. Group to one VCA, polarity-check against the PG52.                                                                  |
| 12       | Bass Mic   | Shure PG52      | Local 12 |     | Short | Blend with the DI — see Bass DI note. PG52 carries the lows.                                                                                                                                               |
| ■ GUITAR |            |                 |          |     |       |                                                                                                                                                                                                            |

| Ch        | Instrument | Mic / DI        | Patch    | 48V | Stand | Notes                                                                                                       |
|-----------|------------|-----------------|----------|-----|-------|-------------------------------------------------------------------------------------------------------------|
| 13        | Gtr 1      | Sennheiser e609 | Local 13 |     | Hang  | Four guitars (1/2 = e609, 3/4 = SM57) — pan-spread, freq-staggered so the mids don't pile.                  |
| 14        | Gtr 2      | Sennheiser e609 | Local 14 |     | Hang  | See Gtr 1 — shifted for separation from Gtr 1.                                                              |
| 15        | Gtr 3      | Shure SM57      | Local 15 |     | Short | SM57 guitars (3/4) voiced with presence UP where the e609 guitars are cut — that's the 4-guitar separation. |
| 16        | Gtr 4      | Shure SM57      | Local 16 |     | Short | See Gtr 3 — shifted for separation.                                                                         |
| ■ KEYS    |            |                 |          |     |       |                                                                                                             |
| 17        | Keys 1     | XLR (DI)        | Local 17 |     | DI    | Stereo keys — keep the pair identical.                                                                      |
| 18        | Keys 2     | XLR (DI)        | Local 18 |     | DI    | See Keys 1.                                                                                                 |
| ■ DRUMS   |            |                 |          |     |       |                                                                                                             |
| 19        | Perc 1     | Shure SM57      | Local 19 |     | Tall  | Generic aux percussion (per FOH) — specific instrument unconfirmed; neutral voicing, dial at soundcheck.    |
| 20        | Perc 2     | Shure SM57      | Local 20 |     | Tall  | Generic aux percussion (per FOH) — specific instrument unconfirmed; neutral voicing, dial at soundcheck.    |
| ■ SPARE   |            |                 |          |     |       |                                                                                                             |
| 21        | Spare 5    | —               | Local 21 |     | —     |                                                                                                             |
| 22        | Spare 6    | —               | Local 22 |     | —     |                                                                                                             |
| 23        | Spare 7    | —               | Local 23 |     | —     |                                                                                                             |
| ■ AMBIENT |            |                 |          |     |       |                                                                                                             |
| 24        | BT Aux     | Line / BT       | Local 24 |     | —     |                                                                                                             |
| ■ VOCALS  |            |                 |          |     |       |                                                                                                             |
| 25        | Wls 1      | Shure Beta 58A  | Local 25 |     | Round |                                                                                                             |
| 26        | Wls 2      | Shure Beta 58A  | Local 26 |     | Round |                                                                                                             |
| 27        | Wls 3      | Shure Beta 58A  | Local 27 |     | Round |                                                                                                             |
| 28        | Wls 4      | Shure Beta 58A  | Local 28 |     | Round |                                                                                                             |
| 29        | Vox 5      | Shure SM58      | Local 29 |     | Tall  |                                                                                                             |
| 30        | Vox 6      | Shure SM58      | Local 30 |     | Tall  |                                                                                                             |
| ■ AMBIENT |            |                 |          |     |       |                                                                                                             |
| 31        | DJ L       | XLR (DI)        | Local 31 |     | DI    | Stereo DJ playback — keep 31/32 identical.                                                                  |

| Ch | Instrument | Mic / DI | Patch    | 48V | Stand | Notes     |
|----|------------|----------|----------|-----|-------|-----------|
| 32 | DJ R       | XLR (DI) | Local 32 |     | DI    | See DJ L. |

## ■ DRUMS ■

### Ch 1 | Kick In

Mic: Shure Beta 91A

**Mic Notes:** Beta 91A boundary inside the kick — the click/attack engine. Contour assumed FLAT (the 400 cut lives on the desk; if the switch is engaged, halve it). Owns click + upper; lows tucked under the D6.

| Band | Freq   | Type | Gain  | Q   | Notes / Rationale |
|------|--------|------|-------|-----|-------------------|
| LC   | 40 Hz  | LC   | —     | —   | High-pass         |
| 4    | 3 kHz  | Bell | +4 dB | 1.2 |                   |
| 3    | 400 Hz | Bell | -3 dB | 2   |                   |
| 2    | 250 Hz | Bell | -3 dB | 1.8 |                   |
| 1    | 80 Hz  | Bell | +2 dB | 1.2 |                   |
| HC   | —      | HC   | —     | —   | No LPF            |

**Engineer Notes:** +4@3k beater definition that travels outdoors (R&B; punch, not a metal click). 400/250 clear the shell boom the boundary picks up — eased for open air. Lows modest (+2@80) so they don't stack with the D6's baked 63Hz. TRACE: base(91A boundary, +4@3k click) · equip(22" Mapex Saturn kick — no change) · genre(R&B; — punch over click) · artist(no dig) · venue(FSQ — box cuts eased, no room mud). COMP (doc only, not patched): Green FET ~4:1, 15ms atk, 3–4 dB GR.

## Ch 2 | Kick Out

*Mic: Audix D6*

**Mic Notes:** Audix D6 pre-scooped 'smiley' — peaks ~63Hz & ~5kHz, deep scoop -15dB @600. Thump+click baked in; needs almost no EQ. Owns the sub/body under the 91A's click.

| Band | Freq   | Type | Gain  | Q   | Notes / Rationale |
|------|--------|------|-------|-----|-------------------|
| LC   | 40 Hz  | LC   | —     | —   | High-pass         |
| 4    | —      | OFF  | —     | —   | Flat              |
| 3    | —      | OFF  | —     | —   | Flat              |
| 2    | 250 Hz | Bell | -2 dB | 1.8 |                   |
| 1    | 60 Hz  | Bell | +3 dB | 1.2 |                   |
| HC   | —      | HC   | —     | —   | No LPF            |

**Engineer Notes:** Barely touched — the capsule IS the kick voicing. +3@60 supports the low open air swallows; light 250 trim. Capsule-voicing gate: NO 3–5k boost (D6 already bakes +5k — a boost stacks harsh) and NO 600 cut (already -15 scooped). TRACE: base(D6 smiley — near-flat) · equip(22" kick — no change) · genre(R&B; thump) · artist(—) · venue(FSQ — +60 for lost low). Two-mic: D6 owns sub, 91A owns click.

## Ch 3 | Snare Top

Mic: Audix i5

**Mic Notes:** i5 bakes +5dB@150 body + a strong +9dB@5.5k presence, mids slightly scooped — more open/body than a 57. Owns the snare body + crack; the e604 owns the wire snap.

| Band | Freq    | Type | Gain  | Q   | Notes / Rationale |
|------|---------|------|-------|-----|-------------------|
| LC   | 120 Hz  | LC   | —     | —   | High-pass         |
| 4    | 7 kHz   | Bell | +2 dB | 0.8 |                   |
| 3    | 5.5 kHz | Bell | -2 dB | 2   |                   |
| 2    | 1 kHz   | Bell | +3 dB | 1   |                   |
| 1    | 300 Hz  | Bell | -5 dB | 2   |                   |
| HC   | —       | HC   | —     | —   | No LPF            |

**Engineer Notes:** Capsule-voicing gate: the +9@5.5k is baked, so I TRIM it -2 (not boost) and put the snap up at 7k where the capsule rolls off. +3@1k crack, -5@300 box (eased — the i5 isn't boxy, don't gut it). TRACE: base(i5 +9@5.5k baked → trim) · equip(14" Black Panther — no change) · genre(R&B; backbeat — body over crack) · artist(—) · venue(FSQ — 7k snap to cut outdoors). GATE (doc): fast ~1ms atk but ghost notes/press rolls must live — 15–20ms rel. Two-mic: i5 body+crack, e604 snap.

## Ch 4 | Snare Bot

*Mic: Sennheiser e604*

**Mic Notes:** e604 clip on the bottom head — scooped low-mids, voiced attack, thin lows (ideal for wires). Owns the snare-wire snap/sizzle only.

| Band | Freq   | Type | Gain  | Q   | Notes / Rationale |
|------|--------|------|-------|-----|-------------------|
| LC   | 180 Hz | LC   | —     | —   | High-pass         |
| 4    | 8 kHz  | Bell | +3 dB | 0.8 |                   |
| 3    | 1 kHz  | Bell | -3 dB | 1.5 |                   |
| 2    | —      | OFF  | —     | —   | Flat              |
| 1    | —      | OFF  | —     | —   | Flat              |
| HC   | —      | HC   | —     | —   | No LPF            |

**Engineer Notes:** HPF way up at 180 so it's wires, not shell or kick bleed. +3@8k snap; -3@1k clears the e604's box. Lane: owns the top-end wire sizzle, the i5 owns body — no overlap. TRACE: base(e604 thin/voiced-attack) · equip(snare wires) · genre(R&B; — crisp backbeat) · artist(—) · venue(FSQ — 8k to cut). GATE (doc): key off the snare top so wires don't chatter.



# Ch 5 | Hat

Mic: Shure SM81

**Mic Notes:** SM81 — ruler-flat, un-hyped highs. Takes EQ straight; no built-in flattery to fight.

| Band | Freq   | Type | Gain  | Q   | Notes / Rationale |
|------|--------|------|-------|-----|-------------------|
| LC   | 500 Hz | LC   | —     | —   | High-pass         |
| 4    | —      | OFF  | —     | —   | Flat              |
| 3    | —      | OFF  | —     | —   | Flat              |
| 2    | 2 kHz  | Bell | -5 dB | 1.2 |                   |
| 1    | 800 Hz | Bell | -6 dB | 1.5 |                   |
| HC   | 16 kHz | HC   | —     | —   | Low-pass          |

**Engineer Notes:** No HF boost (81 is already detailed and dry 7/24 air thins the top over the throw anyway — don't make it brittle). Clear the low bleed (800) + the 2k clang so it sparkles clean. TRACE: base(SM81 flat) · equip(14" HHX hats) · genre(R&B; — tight hat) · artist(—) · venue(FSQ+dry — resist top boost).

## Ch 6 | Rack 1

Mic: Audix D2

**Mic Notes:** D2 tuned to control tom resonance — articulate with little EQ; leaner deep lows than the D4.

| Band | Freq    | Type | Gain  | Q   | Notes / Rationale |
|------|---------|------|-------|-----|-------------------|
| LC   | 90 Hz   | LC   | —     | —   | High-pass         |
| 4    | —       | OFF  | —     | —   | Flat              |
| 3    | 2.8 kHz | Bell | +4 dB | 1   |                   |
| 2    | 450 Hz  | Bell | -3 dB | 1.8 |                   |
| 1    | 135 Hz  | Bell | +3 dB | 1.2 |                   |
| HC   | 12 kHz  | HC   | —     | —   | Low-pass          |

**Engineer Notes:** Attack lift +4@2.8k (trust the capsule), gentle 135 body, modest 450 mud cut. TRACE: base(D2 — articulate) · equip(10" Saturn rack) · genre(R&B; fills) · artist(—) · venue(FSQ). GATE (doc): snappy release for funk; don't choke the decay.

# Ch 7 | Rack 2

Mic: Audix D2

**Mic Notes:** As Rack 1, shifted down for the larger 12" drum.

| Band | Freq    | Type | Gain  | Q   | Notes / Rationale |
|------|---------|------|-------|-----|-------------------|
| LC   | 80 Hz   | LC   | —     | —   | High-pass         |
| 4    | —       | OFF  | —     | —   | Flat              |
| 3    | 2.5 kHz | Bell | +4 dB | 1   |                   |
| 2    | 405 Hz  | Bell | -3 dB | 1.8 |                   |
| 1    | 120 Hz  | Bell | +3 dB | 1.2 |                   |
| HC   | 12 kHz  | HC   | —     | —   | Low-pass          |

**Engineer Notes:** Let the D2 do the work; body at 120 for the bigger shell. TRACE: base(D2) · equip(12" Saturn rack) · genre · artist(—) · venue(FSQ).

## Ch 8 | Floor

Mic: Audix D4

**Mic Notes:** D4 reaches ~an octave lower than the D2 natively; smooth 800–1k (not scooped) — may want a touch of click.

| Band | Freq    | Type  | Gain  | Q    | Notes / Rationale |
|------|---------|-------|-------|------|-------------------|
| LC   | 55 Hz   | LC    | —     | —    | High-pass         |
| 4    | —       | OFF   | —     | —    | Flat              |
| 3    | 1.8 kHz | Bell  | +4 dB | 1    |                   |
| 2    | 405 Hz  | Bell  | -3 dB | 1.8  |                   |
| 1    | 70 Hz   | Shelf | +4 dB | 0.71 |                   |
| HC   | 10 kHz  | HC    | —     | —    | Low-pass          |

**Engineer Notes:** Body shelf modest +4@70 (support, not a lift; ride the sub outdoors). +4@1.8k stick definition the D4 lacks. TRACE: base(D4 — deep, smooth mids) · equip(16" Saturn floor) · genre(R&B;) · artist(—) · venue(FSQ — modest sub). GATE (doc): slower release than the racks so the floor decay lives.

## Ch 9 | OH (st)

Mic: Shure Beta 27

**Mic Notes:** Beta 27 LDC pair as overheads — flat 60Hz–3k with baked +2dB bumps at 5.5k & 9k, supercardioid (tight, less room — good outdoors), –15 pad available.

| Band | Freq   | Type | Gain  | Q   | Notes / Rationale |
|------|--------|------|-------|-----|-------------------|
| LC   | 200 Hz | LC   | —     | —   | High-pass         |
| 4    | —      | OFF  | —     | —   | Flat              |
| 3    | —      | OFF  | —     | —   | Flat              |
| 2    | 9 kHz  | Bell | -2 dB | 2   |                   |
| 1    | 300 Hz | Bell | -5 dB | 1.5 |                   |
| HC   | —      | HC   | —     | —   | No LPF            |

**Engineer Notes:** Capsule-voicing gate: the top is already lifted (5.5k+9k baked) → NO HF boost; a light –2@9k tames fizz instead. –5@300 clears low wash + kit bleed so it's cymbals/sheen, not a room mic. Supercardioid keeps the outdoor stage tight. HPF 200. TRACE: base(Beta 27 — baked top) · equip(HHX cymbals) · genre(R&B; — cymbal sheen) · artist(—) · venue(FSQ — supercard tight, clear wash).

## Ch 19 | Perc 1

Mic: Shure SM57

**Mic Notes:** SM57 on aux/hand percussion — kept conservative per the brief (instrument not confirmed).

| Band | Freq   | Type | Gain  | Q   | Notes / Rationale |
|------|--------|------|-------|-----|-------------------|
| LC   | 120 Hz | LC   | —     | —   | High-pass         |
| 4    | —      | OFF  | —     | —   | Flat              |
| 3    | 4 kHz  | Bell | +2 dB | 1   |                   |
| 2    | 400 Hz | Bell | -3 dB | 1.8 |                   |
| 1    | —      | OFF  | —     | —   | Flat              |
| HC   | —      | HC   | —     | —   | No LPF            |

**Engineer Notes:** Conservative per the brief: light +2@4k attack, -3@400 box, HPF 120. Voicing left neutral — dial to the actual instrument at soundcheck. TRACE: base(SM57) · equip(aux perc) · genre(R&B;) · artist(—) · venue(FSQ).

# Ch 20 | Perc 2

Mic: Shure SM57

**Mic Notes:** SM57 on aux/hand percussion — kept conservative per the brief (instrument not confirmed).

| Band | Freq   | Type | Gain  | Q   | Notes / Rationale |
|------|--------|------|-------|-----|-------------------|
| LC   | 120 Hz | LC   | —     | —   | High-pass         |
| 4    | —      | OFF  | —     | —   | Flat              |
| 3    | 4 kHz  | Bell | +2 dB | 1   |                   |
| 2    | 400 Hz | Bell | -3 dB | 1.8 |                   |
| 1    | —      | OFF  | —     | —   | Flat              |
| HC   | —      | HC   | —     | —   | No LPF            |

**Engineer Notes:** Conservative per the brief: light +2@4k attack, -3@400 box, HPF 120. Voicing left neutral — dial to the actual instrument at soundcheck. TRACE: base(SM57) · equip(aux perc) · genre(R&B;) · artist(—) · venue(FSQ).

## Ch 11 | Bass DI

Mic: XLR (DI)

**Mic Notes:** Bass DI — clean, full-range. The PG52 (a kick mic) is on the cab. LANE: the DI owns note definition + mids + upper harmonics; the PG52 owns the sub/thump — so the DI's lows are pulled back to de-stack.

| Band | Freq    | Type  | Gain  | Q    | Notes / Rationale |
|------|---------|-------|-------|------|-------------------|
| LC   | 40 Hz   | LC    | —     | —    | High-pass         |
| 4    | 1.5 kHz | Bell  | -4 dB | 1.5  |                   |
| 3    | 700 Hz  | Bell  | +4 dB | 1    |                   |
| 2    | 250 Hz  | Bell  | -5 dB | 2    |                   |
| 1    | 80 Hz   | Shelf | +3 dB | 0.71 |                   |
| HC   | —       | HC    | —     | —    | No LPF            |

**Engineer Notes:** R&B;/soul bass = round, low-mid forward, top rolled. +4@700 note/growl (DI's lane), -4@1.5k tames string clank, -5@250 de-stacks off the PG52's low body, +3@80 modest (PG52 carries the real sub). TRACE: base(DI clean — definition lane) · equip(bass rig, DI+cab) · genre(R&B; — round, low-mid forward) · artist(—) · venue(FSQ — support 80). COMP (doc): opto ~3:1, 20–30ms atk, even the pocket.



## Ch 12 | Bass Mic

Mic: Shure PG52

**Mic Notes:** PG52 is a kick mic on the bass cab — 30Hz–13k, tuned low-end thump + a slight upper-mid click bump, rolls off above 13k (no air). It's the SUB/BODY layer under the DI.

| Band | Freq    | Type  | Gain  | Q    | Notes / Rationale |
|------|---------|-------|-------|------|-------------------|
| LC   | 30 Hz   | LC    | —     | —    | High-pass         |
| 4    | —       | OFF   | —     | —    | Flat              |
| 3    | 2.5 kHz | Bell  | +2 dB | 1    |                   |
| 2    | 400 Hz  | Bell  | -5 dB | 2    |                   |
| 1    | 90 Hz   | Shelf | +4 dB | 0.71 |                   |
| HC   | 8 kHz   | HC    | —     | —    | Low-pass          |

**Engineer Notes:** Owns the low thump: +4@90 shelf. -5@400 carves a pocket so it doesn't double the DI's mud. Small +2@2.5k for finger attack (the PG52's click bump). LPF 8k — no useful top, keep it dark body. TRACE: base(PG52 kick-mic-on-cab — sub lane) · equip(bass cab) · genre(R&B; thump) · artist(—) · venue(FSQ). Two-mic: PG52 lows, DI definition — no low boost on both.

## ■ GUITAR ■

### Ch 13 | Gtr 1

Mic: Sennheiser e609

**Mic Notes:** e609 flat-face over the cab — bright upper-mid/presence 4–5k, supercardioid, can get edgy 2.5–4k on bright amps. Owns cab presence.

| Band | Freq    | Type | Gain  | Q   | Notes / Rationale |
|------|---------|------|-------|-----|-------------------|
| LC   | 100 Hz  | LC   | —     | —   | High-pass         |
| 4    | 3 kHz   | Bell | -3 dB | 2   |                   |
| 3    | 1.2 kHz | Bell | +2 dB | 1.2 |                   |
| 2    | 400 Hz  | Bell | -4 dB | 2   |                   |
| 1    | 150 Hz  | Bell | -3 dB | 1.5 |                   |
| HC   | —       | HC   | —     | —   | No LPF            |

**Engineer Notes:** Rhythm R&B; guitar sits under the vocal + horns. -3@3k tames the e609 edge; +2@1.2k so the comp speaks; -4@400 box; HPF 100 + -3@150 keeps it out of the bass. TRACE: base(e609 — bright/edgy) · equip(gtr cab) · genre(R&B; comp — supportive, not a wall) · artist(—) · venue(FSQ — deeper box cut). Staggered vs the 57 guitars.

## Ch 14 | Gtr 2

*Mic: Sennheiser e609*

**Mic Notes:** e609 as Gtr 1; voiced a hair different (edge 2.8k, presence 1.4k) so two e609 guitars don't overlay.

| Band | Freq    | Type | Gain  | Q   | Notes / Rationale |
|------|---------|------|-------|-----|-------------------|
| LC   | 100 Hz  | LC   | —     | —   | High-pass         |
| 4    | 2.8 kHz | Bell | -3 dB | 2   |                   |
| 3    | 1.4 kHz | Bell | +2 dB | 1.2 |                   |
| 2    | 450 Hz  | Bell | -4 dB | 2   |                   |
| 1    | 150 Hz  | Bell | -3 dB | 1.5 |                   |
| HC   | —       | HC   | —     | —   | No LPF            |

**Engineer Notes:** As Gtr 1 with the edge/presence shifted so the two e609 guitars separate. *TRACE: base(e609) · equip(gtr cab) · genre(R&B; comp) · artist(—) · venue(FSQ).*

## Ch 15 | Gtr 3

Mic: Shure SM57

**Mic Notes:** SM57 on the cab — mid-forward, presence 3–5k, builds box/honk 300–500. Owns mid grit.

| Band | Freq    | Type | Gain  | Q   | Notes / Rationale |
|------|---------|------|-------|-----|-------------------|
| LC   | 100 Hz  | LC   | —     | —   | High-pass         |
| 4    | 3.5 kHz | Bell | +3 dB | 1   |                   |
| 3    | 800 Hz  | Bell | -2 dB | 1.2 |                   |
| 2    | 400 Hz  | Bell | -5 dB | 2   |                   |
| 1    | 180 Hz  | Bell | -3 dB | 1.5 |                   |
| HC   | —       | HC   | —     | —   | No LPF            |

**Engineer Notes:** +3@3.5k presence (57's lane — differs from the e609 guitars' voicing so 4 gtrs separate), -5@400 box, -2@800 honk, HPF 100 + 180 trim off the bass. TRACE: base(SM57 — mid grit) · equip(gtr cab) · genre(R&B; — present, under the vocals) · artist(—) · venue(FSQ — deeper box).

# Ch 16 | Gtr 4

Mic: Shure SM57

Mic Notes: SM57 as Gtr 3; presence at 3k, box 450 so the two 57 guitars separate.

| Band | Freq   | Type | Gain  | Q   | Notes / Rationale |
|------|--------|------|-------|-----|-------------------|
| LC   | 100 Hz | LC   | —     | —   | High-pass         |
| 4    | 3 kHz  | Bell | +3 dB | 1   |                   |
| 3    | 850 Hz | Bell | -2 dB | 1.2 |                   |
| 2    | 450 Hz | Bell | -5 dB | 2   |                   |
| 1    | 180 Hz | Bell | -3 dB | 1.5 |                   |
| HC   | —      | HC   | —     | —   | No LPF            |

Engineer Notes: As Gtr 3, shifted. TRACE: base(SM57) · equip(gtr cab) · genre(R&B;) · artist(—) · venue(FSQ).

# Ch 17 | Keys 1

Mic: XLR (DI)

Mic Notes: Yamaha CP33 stage piano via DI, stereo pair (EP/organ/piano patches).

| Band | Freq    | Type | Gain  | Q   | Notes / Rationale |
|------|---------|------|-------|-----|-------------------|
| LC   | 50 Hz   | LC   | —     | —   | High-pass         |
| 4    | —       | OFF  | —     | —   | Flat              |
| 3    | 2.5 kHz | Bell | +3 dB | 0.8 |                   |
| 2    | 300 Hz  | Bell | +2 dB | 0.8 |                   |
| 1    | 200 Hz  | Bell | -5 dB | 1.5 |                   |
| HC   | —       | HC   | —     | —   | No LPF            |

Engineer Notes: Warmth +2@300 + clarity +3@2.5k without hype; -5@200 clears mud off the bass/vocal low-mids. Stereo — keep the pair identical. TRACE: base(CP33 DI) · equip(CP33 88-key) · genre(R&B; keys) · artist(—) · venue(FSQ).

# Ch 18 | Keys 2

Mic: XLR (DI)

Mic Notes: Yamaha CP33 stage piano via DI, stereo pair (EP/organ/piano patches).

| Band | Freq    | Type | Gain  | Q   | Notes / Rationale |
|------|---------|------|-------|-----|-------------------|
| LC   | 50 Hz   | LC   | —     | —   | High-pass         |
| 4    | —       | OFF  | —     | —   | Flat              |
| 3    | 2.5 kHz | Bell | +3 dB | 0.8 |                   |
| 2    | 300 Hz  | Bell | +2 dB | 0.8 |                   |
| 1    | 200 Hz  | Bell | -5 dB | 1.5 |                   |
| HC   | —       | HC   | —     | —   | No LPF            |

Engineer Notes: Warmth +2@300 + clarity +3@2.5k without hype; -5@200 clears mud off the bass/vocal low-mids. Stereo — keep the pair identical. TRACE: base(CP33 DI) · equip(CP33 88-key) · genre(R&B; keys) · artist(—) · venue(FSQ).

Ch 21 | Spare 5

Mic: —

Mic Notes: Open fader — no input patched.

| Band | Freq  | Type | Gain | Q | Notes / Rationale |
|------|-------|------|------|---|-------------------|
| LC   | 20 Hz | LC   | —    | — | High-pass         |
| 4    | —     | OFF  | —    | — | Flat              |
| 3    | —     | OFF  | —    | — | Flat              |
| 2    | —     | OFF  | —    | — | Flat              |
| 1    | —     | OFF  | —    | — | Flat              |
| HC   | —     | HC   | —    | — | No LPF            |

Engineer Notes: Spare / available.



# Ch 22 | Spare 6

Mic: —

Mic Notes: Open fader — no input patched.

| Band | Freq  | Type | Gain | Q | Notes / Rationale |
|------|-------|------|------|---|-------------------|
| LC   | 20 Hz | LC   | —    | — | High-pass         |
| 4    | —     | OFF  | —    | — | Flat              |
| 3    | —     | OFF  | —    | — | Flat              |
| 2    | —     | OFF  | —    | — | Flat              |
| 1    | —     | OFF  | —    | — | Flat              |
| HC   | —     | HC   | —    | — | No LPF            |

Engineer Notes: Spare / available.

# Ch 23 | Spare 7

Mic: —

**Mic Notes:** Open fader — no input patched.

| Band | Freq  | Type | Gain | Q | Notes / Rationale |
|------|-------|------|------|---|-------------------|
| LC   | 20 Hz | LC   | —    | — | High-pass         |
| 4    | —     | OFF  | —    | — | Flat              |
| 3    | —     | OFF  | —    | — | Flat              |
| 2    | —     | OFF  | —    | — | Flat              |
| 1    | —     | OFF  | —    | — | Flat              |
| HC   | —     | HC   | —    | — | No LPF            |

**Engineer Notes:** Spare / available.

# ■ AMBIENT ■

## Ch 24 | BT Aux

Mic: Line / BT

**Mic Notes:** Bluetooth aux — walk-in / between-set music, not a performance input.

| Band | Freq  | Type | Gain | Q | Notes / Rationale |
|------|-------|------|------|---|-------------------|
| LC   | 40 Hz | LC   | —    | — | High-pass         |
| 4    | —     | OFF  | —    | — | Flat              |
| 3    | —     | OFF  | —    | — | Flat              |
| 2    | —     | OFF  | —    | — | Flat              |
| 1    | —     | OFF  | —    | — | Flat              |
| HC   | —     | HC   | —    | — | No LPF            |

**Engineer Notes:** Near-flat playback. HPF 40 only. TRACE: base(mastered playback) · venue(FSQ).

## Ch 31 | DJ L

*Mic: XLR (DI)*

**Mic Notes:** DJ playback (turntables/controller), stereo — mastered full-range.

| Band | Freq  | Type | Gain | Q | Notes / Rationale |
|------|-------|------|------|---|-------------------|
| LC   | 30 Hz | LC   | —    | — | High-pass         |
| 4    | —     | OFF  | —    | — | Flat              |
| 3    | —     | OFF  | —    | — | Flat              |
| 2    | —     | OFF  | —    | — | Flat              |
| 1    | —     | OFF  | —    | — | Flat              |
| HC   | —     | HC   | —    | — | No LPF            |

**Engineer Notes:** Left near-flat — EQ'ing mastered playback like a mic thins it. HPF 30 only; add a small 315 trim live only if it clouds the band. TRACE: base(mastered stereo) · venue(FSQ).

## Ch 32 | DJ R

*Mic: XLR (DI)*

**Mic Notes:** DJ playback (turntables/controller), stereo — mastered full-range.

| Band | Freq  | Type | Gain | Q | Notes / Rationale |
|------|-------|------|------|---|-------------------|
| LC   | 30 Hz | LC   | —    | — | High-pass         |
| 4    | —     | OFF  | —    | — | Flat              |
| 3    | —     | OFF  | —    | — | Flat              |
| 2    | —     | OFF  | —    | — | Flat              |
| 1    | —     | OFF  | —    | — | Flat              |
| HC   | —     | HC   | —    | — | No LPF            |

**Engineer Notes:** Left near-flat — EQ'ing mastered playback like a mic thins it. HPF 30 only; add a small 315 trim live only if it clouds the band. TRACE: base(mastered stereo) · venue(FSQ).

## ■ VOCALS ■

### Ch 25 | Wls 1

Mic: Shure Beta 58A

**Mic Notes:** Beta 58A supercardioid handheld — TWO baked presence peaks (~4k & ~10k), boxy ~600, <500 attenuated, tight pattern/high GBF (brighter than an SM58). LEAD voicing.

| Band | Freq   | Type | Gain  | Q   | Notes / Rationale                                          |
|------|--------|------|-------|-----|------------------------------------------------------------|
| LC   | 100 Hz | LC   | —     | —   | High-pass                                                  |
| 4    | 10 kHz | Bell | -3 dB | 2   | DYNAMIC: thr=-18dB atk=3ms rel=120ms — bites only on peaks |
| 3    | 4 kHz  | Bell | -2 dB | 2.5 |                                                            |
| 2    | 600 Hz | Bell | -4 dB | 1.5 |                                                            |
| 1    | —      | OFF  | —     | —   | Flat                                                       |
| HC   | 16 kHz | HC   | —     | —   | Low-pass                                                   |

**Engineer Notes:** Cut-only (feedback + taste). Dynamic de-ess -3@10k on the baked top peak so the air stays between sibilants; light -2@4k tames stridency without killing the bite the capsule bakes; -4@600 box for outdoor intelligibility. HPF 100. Overrides the FSQ template wireless curve/notch — ring out at soundcheck; reach for comp + a touch of plate before more EQ. TRACE: base(Beta 58A twin peaks) · genre(R&B; lead) · venue(FSQ intelligibility).

## Ch 26 | Wls 2

Mic: Shure Beta 58A

**Mic Notes:** Beta 58A handheld — backing voicing: sits a touch behind the lead (–2@3k) so the harmony supports.

| Band | Freq   | Type | Gain  | Q   | Notes / Rationale                                          |
|------|--------|------|-------|-----|------------------------------------------------------------|
| LC   | 120 Hz | LC   | —     | —   | High-pass                                                  |
| 4    | 10 kHz | Bell | -2 dB | 2   | DYNAMIC: thr=-18dB atk=3ms rel=120ms — bites only on peaks |
| 3    | 3 kHz  | Bell | -2 dB | 2.5 |                                                            |
| 2    | 600 Hz | Bell | -4 dB | 1.5 |                                                            |
| 1    | —      | OFF  | —     | —   | Flat                                                       |
| HC   | 16 kHz | HC   | —     | —   | Low-pass                                                   |

**Engineer Notes:** Cut-only. –4@600 box, –2@10k de-ess, –2@3k to seat it behind the lead. HPF 120. Overrides the template wireless notch — ring out. TRACE: base(Beta 58A) · genre(R&B; BGV) · venue(FSQ).

## Ch 27 | Wls 3

Mic: Shure Beta 58A

**Mic Notes:** Beta 58A handheld — backing voicing: sits a touch behind the lead (–2@3k) so the harmony supports.

| Band | Freq   | Type | Gain  | Q   | Notes / Rationale                                          |
|------|--------|------|-------|-----|------------------------------------------------------------|
| LC   | 120 Hz | LC   | —     | —   | High-pass                                                  |
| 4    | 10 kHz | Bell | -2 dB | 2   | DYNAMIC: thr=-18dB atk=3ms rel=120ms — bites only on peaks |
| 3    | 3 kHz  | Bell | -2 dB | 2.5 |                                                            |
| 2    | 600 Hz | Bell | -4 dB | 1.5 |                                                            |
| 1    | —      | OFF  | —     | —   | Flat                                                       |
| HC   | 16 kHz | HC   | —     | —   | Low-pass                                                   |

**Engineer Notes:** Cut-only. –4@600 box, –2@10k de-ess, –2@3k to seat it behind the lead. HPF 120. Overrides the template wireless notch — ring out. TRACE: base(Beta 58A) · genre(R&B; BGV) · venue(FSQ).



## Ch 28 | Wls 4

Mic: Shure Beta 58A

**Mic Notes:** Beta 58A handheld — backing voicing: sits a touch behind the lead (–2@3k) so the harmony supports.

| Band | Freq   | Type | Gain  | Q   | Notes / Rationale                                          |
|------|--------|------|-------|-----|------------------------------------------------------------|
| LC   | 120 Hz | LC   | —     | —   | High-pass                                                  |
| 4    | 10 kHz | Bell | -2 dB | 2   | DYNAMIC: thr=-18dB atk=3ms rel=120ms — bites only on peaks |
| 3    | 3 kHz  | Bell | -2 dB | 2.5 |                                                            |
| 2    | 600 Hz | Bell | -4 dB | 1.5 |                                                            |
| 1    | —      | OFF  | —     | —   | Flat                                                       |
| HC   | 16 kHz | HC   | —     | —   | Low-pass                                                   |

**Engineer Notes:** Cut-only. –4@600 box, –2@10k de-ess, –2@3k to seat it behind the lead. HPF 120. Overrides the template wireless notch — ring out. TRACE: base(Beta 58A) · genre(R&B; BGV) · venue(FSQ).

## Ch 29 | Vox 5

Mic: Shure SM58

**Mic Notes:** SM58 on a stand — presence 4–6k, boxy ~500, gentle low rolloff. Backing/utility vocal.

| Band | Freq   | Type | Gain  | Q   | Notes / Rationale |
|------|--------|------|-------|-----|-------------------|
| LC   | 110 Hz | LC   | —     | —   | High-pass         |
| 4    | —      | OFF  | —     | —   | Flat              |
| 3    | 5 kHz  | Bell | -2 dB | 2.5 |                   |
| 2    | 500 Hz | Bell | -4 dB | 1.5 |                   |
| 1    | —      | OFF  | —     | —   | Flat              |
| HC   | 16 kHz | HC   | —     | —   | Low-pass          |

**Engineer Notes:** Cut-only. -4@500 box, light -2@5k if spitty, HPF 110. Supportive — a touch behind the leads. TRACE: base(SM58) · genre(R&B; BGV) · venue(FSQ).

## Ch 30 | Vox 6

Mic: Shure SM58

**Mic Notes:** SM58 on a stand — presence 4–6k, boxy ~500, gentle low rolloff. Backing/utility vocal.

| Band | Freq   | Type | Gain  | Q   | Notes / Rationale |
|------|--------|------|-------|-----|-------------------|
| LC   | 110 Hz | LC   | —     | —   | High-pass         |
| 4    | —      | OFF  | —     | —   | Flat              |
| 3    | 5 kHz  | Bell | -2 dB | 2.5 |                   |
| 2    | 500 Hz | Bell | -4 dB | 1.5 |                   |
| 1    | —      | OFF  | —     | —   | Flat              |
| HC   | 16 kHz | HC   | —     | —   | Low-pass          |

**Engineer Notes:** Cut-only. -4@500 box, light -2@5k if spitty, HPF 110. Supportive — a touch behind the leads. TRACE: base(SM58) · genre(R&B; BGV) · venue(FSQ).