

Nasty Nati Band

FOH CHANNEL EQ SETUP — DiGiCo Quantum 225

Show	Nasty Nati Band
Show Date	2026-07-25
Venue	Fountain Square (outdoor)
Console	DiGiCo Quantum 225
Channels	31
FOH Engineer	Brian Lloyd
Monitor Engineer	
Show Time	
Rev	Rev 1.0 Deep Think

DOCUMENT CONTENTS

1. Cover Page — show, venue, and personnel
2. Input List — color-coded full channel patch sheet
3. Patching — AES and Local inputs sorted by port
4. EQ Setup — 31 channels for DiGiCo Quantum 225
5. Reference — EQ structure, pan guide, bus grouping, soundcheck order

SHOW STYLE: Open-air Fountain Square — no room gain, low end + HF dissipate over the throw, façade slap but no reverb tail. Cuts run deeper than indoor (−6 to −9 typ), HPF decisive, clarity first. L-Acoustics A15/KS21 house PA, M32 monitors.

Nasty Nati Band		
VENUE: Fountain Square (outdoor)	DATE: 2026-07-25	REV: Rev 1.0 Deep Think
FOH: Brian Lloyd	MON:	SHOW TIME:

REV: Rev 1.0 Deep Think

SHOW TIME:

Ch	Instrument	Mic / DI	Patch	48V	Stand	Notes
■ DRUMS						
1	Kick In	Shure Beta 91A	Local 1	✓	—	Beta 91A/D6 kick blend — 91A is the attack/click layer. Treat the pair as ONE: same VCA, pan together, blend constant. Polarity: sum in mono, flip one if thinner. Bus: notch –2/–3 @300–500 if it builds.
2	Kick Out	Audix D6	Local 2		Short	Beta 91A/D6 kick blend — D6 is the sub/body core. Pan together, same VCA.
3	Snare Top	Audix i5	Local 3		Claw	Snare top/bottom pair — treat with the e604 as one snare; polarity-check the pair.
4	Snare Bot	Sennheiser e604	Local 4		Claw	Bottom head — wire capture only. Polarity-check against the snare top; flip if the pair thins.
5	Hat	Shure SM81	Local 5	✓	Tall	
6	Rack 1	Audix D2	Local 6		Claw	
7	Rack 2	Audix D2	Local 7		Claw	
8	Floor	Audix D4	Local 8		Claw	
9	OH (st)	Shure Beta 27	Local 9	✓	Tall	STEREO pair on fader 9 (both OH mics on this one fader). FSQ ch 10 is the SNARE PL8 return — not an input.
■ BASS						
11	Bass DI	XLR (DI)	Local 11		DI	Bass DI + PG52 cab blend — INVERTED lanes: DI = definition/mids/top, PG52 = sub/thump. Group to one VCA, polarity-check against the PG52.
12	Bass Mic	Shure PG52	Local 12		Short	Blend with the DI — see Bass DI note. PG52 carries the lows.
■ GUITAR						

Ch	Instrument	Mic / DI	Patch	48V	Stand	Notes
13	Gtr 1	Sennheiser e609	Local 13		Hang	Four guitars (1/2 = e609, 3/4 = SM57) — pan-spread, freq-staggered so the mids don't pile.
14	Gtr 2	Sennheiser e609	Local 14		Hang	See Gtr 1 — shifted for separation from Gtr 1.
15	Gtr 3	Shure SM57	Local 15		Short	SM57 guitars (3/4) voiced with presence UP where the e609 guitars are cut — that's the 4-guitar separation.
16	Gtr 4	Shure SM57	Local 16		Short	See Gtr 3 — shifted for separation.
■ HORNS						
17	Sousa	Audio-Technica PRO 35	Local 17	✓	Clip	
18	Bone	Audio-Technica PRO 35	Local 18	✓	Clip	
19	Tenor	Audio-Technica PRO 35	Local 19	✓	Clip	
20	Alto	Audio-Technica PRO 35	Local 20	✓	Clip	
21	Tpt	Audio-Technica PRO 35	Local 21	✓	Clip	
■ DRUMS						
22	Perc 1	Shure SM57	Local 22		Tall	Generic aux percussion (per FOH) — specific instrument unconfirmed; neutral voicing, dial at soundcheck.
23	Perc 2	Shure SM57	Local 23		Tall	Generic aux percussion (per FOH) — specific instrument unconfirmed; neutral voicing, dial at soundcheck.
■ AMBIENT						
24	BT Aux	Line / BT	Local 24		—	
■ VOCALS						
25	Wls 1	Shure Beta 58A	Local 25		Round	
26	Wls 2	Shure Beta 58A	Local 26		Round	
27	Wls 3	Shure Beta 58A	Local 27		Round	
28	Wls 4	Shure Beta 58A	Local 28		Round	
29	Vox 5	Shure SM58	Local 29		Tall	
30	Vox 6	Shure SM58	Local 30		Tall	
■ AMBIENT						
31	DJ L	XLR (DI)	Local 31		DI	Stereo DJ playback — keep 31/32 identical.
32	DJ R	XLR (DI)	Local 32		DI	See DJ L.

■ DRUMS ■

Ch 1 | Kick In

Mic: Shure Beta 91A

Mic Notes: Beta 91A boundary inside the kick — the click/attack engine. Contour assumed FLAT (the 400 cut lives on the desk; if the switch is engaged, halve it). Owns click + upper; lows tucked under the D6.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	40 Hz	LC	—	—	High-pass
4	3 kHz	Bell	+4 dB	1.2	
3	400 Hz	Bell	-3 dB	2	
2	250 Hz	Bell	-3 dB	1.8	
1	80 Hz	Bell	+2 dB	1.2	
HC	—	HC	—	—	No LPF

Engineer Notes: +4@3k beater definition that travels outdoors (R&B; punch, not a metal click). 400/250 clear the shell boom the boundary picks up — eased for open air. Lows modest (+2@80) so they don't stack with the D6's baked 63Hz. TRACE: base(91A boundary, +4@3k click) · equip(22" Mapex Saturn kick — no change) · genre(R&B; — punch over click) · artist(no dig) · venue(FSQ — box cuts eased, no room mud). COMP (doc only, not patched): Green FET ~4:1, 15ms atk, 3–4 dB GR.

Ch 2 | Kick Out

Mic: Audix D6

Mic Notes: Audix D6 pre-scooped 'smiley' — peaks ~63Hz & ~5kHz, deep scoop -15dB @600. Thump+click baked in; needs almost no EQ. Owns the sub/body under the 91A's click.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	40 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	—	OFF	—	—	Flat
2	250 Hz	Bell	-2 dB	1.8	
1	60 Hz	Bell	+3 dB	1.2	
HC	—	HC	—	—	No LPF

Engineer Notes: Barely touched — the capsule IS the kick voicing. +3@60 supports the low open air swallows; light 250 trim. Capsule-voicing gate: NO 3–5k boost (D6 already bakes +5k — a boost stacks harsh) and NO 600 cut (already -15 scooped). TRACE: base(D6 smiley — near-flat) · equip(22" kick — no change) · genre(R&B; thump) · artist(—) · venue(FSQ — +60 for lost low). Two-mic: D6 owns sub, 91A owns click.

Ch 3 | Snare Top

Mic: Audix i5

Mic Notes: i5 bakes +5dB@150 body + a strong +9dB@5.5k presence, mids slightly scooped — more open/body than a 57. Owns the snare body + crack; the e604 owns the wire snap.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	120 Hz	LC	—	—	High-pass
4	7 kHz	Bell	+2 dB	0.8	
3	5.5 kHz	Bell	-2 dB	2	
2	1 kHz	Bell	+3 dB	1	
1	300 Hz	Bell	-5 dB	2	
HC	—	HC	—	—	No LPF

Engineer Notes: Capsule-voicing gate: the +9@5.5k is baked, so I TRIM it -2 (not boost) and put the snap up at 7k where the capsule rolls off. +3@1k crack, -5@300 box (eased — the i5 isn't boxy, don't gut it). TRACE: base(i5 +9@5.5k baked → trim) · equip(14" Black Panther — no change) · genre(R&B; backbeat — body over crack) · artist(—) · venue(FSQ — 7k snap to cut outdoors). GATE (doc): fast ~1ms atk but ghost notes/press rolls must live — 15–20ms rel. Two-mic: i5 body+crack, e604 snap.

Ch 4 | Snare Bot

Mic: Sennheiser e604

Mic Notes: e604 clip on the bottom head — scooped low-mids, voiced attack, thin lows (ideal for wires). Owns the snare-wire snap/sizzle only.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	180 Hz	LC	—	—	High-pass
4	8 kHz	Bell	+3 dB	0.8	
3	1 kHz	Bell	-3 dB	1.5	
2	—	OFF	—	—	Flat
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: HPF way up at 180 so it's wires, not shell or kick bleed. +3@8k snap; -3@1k clears the e604's box. Lane: owns the top-end wire sizzle, the i5 owns body — no overlap. TRACE: base(e604 thin/voiced-attack) · equip(snare wires) · genre(R&B; — crisp backbeat) · artist(—) · venue(FSQ — 8k to cut). GATE (doc): key off the snare top so wires don't chatter.

Ch 5 | Hat

Mic: Shure SM81

Mic Notes: SM81 — ruler-flat, un-hyped highs. Takes EQ straight; no built-in flattery to fight.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	500 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	—	OFF	—	—	Flat
2	2 kHz	Bell	-5 dB	1.2	
1	800 Hz	Bell	-6 dB	1.5	
HC	16 kHz	HC	—	—	Low-pass

Engineer Notes: No HF boost (81 is already detailed and dry 7/24 air thins the top over the throw anyway — don't make it brittle). Clear the low bleed (800) + the 2k clang so it sparkles clean. TRACE: base(SM81 flat) · equip(14" HHX hats) · genre(R&B; — tight hat) · artist(—) · venue(FSQ+dry — resist top boost).

Ch 6 | Rack 1

Mic: Audix D2

Mic Notes: D2 tuned to control tom resonance — articulate with little EQ; leaner deep lows than the D4.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	90 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	2.8 kHz	Bell	+4 dB	1	
2	450 Hz	Bell	-3 dB	1.8	
1	135 Hz	Bell	+3 dB	1.2	
HC	12 kHz	HC	—	—	Low-pass

Engineer Notes: Attack lift +4@2.8k (trust the capsule), gentle 135 body, modest 450 mud cut. TRACE: base(D2 — articulate) · equip(10" Saturn rack) · genre(R&B; fills) · artist(—) · venue(FSQ). GATE (doc): snappy release for funk; don't choke the decay.

Ch 7 | Rack 2

Mic: Audix D2

Mic Notes: As Rack 1, shifted down for the larger 12" drum.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	80 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	2.5 kHz	Bell	+4 dB	1	
2	405 Hz	Bell	-3 dB	1.8	
1	120 Hz	Bell	+3 dB	1.2	
HC	12 kHz	HC	—	—	Low-pass

Engineer Notes: Let the D2 do the work; body at 120 for the bigger shell. TRACE: base(D2) · equip(12" Saturn rack) · genre · artist(—) · venue(FSQ).

Ch 8 | Floor

Mic: Audix D4

Mic Notes: D4 reaches ~an octave lower than the D2 natively; smooth 800–1k (not scooped) — may want a touch of click.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	55 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	1.8 kHz	Bell	+4 dB	1	
2	405 Hz	Bell	-3 dB	1.8	
1	70 Hz	Shelf	+4 dB	0.71	
HC	10 kHz	HC	—	—	Low-pass

Engineer Notes: Body shelf modest +4@70 (support, not a lift; ride the sub outdoors). +4@1.8k stick definition the D4 lacks. TRACE: base(D4 — deep, smooth mids) · equip(16" Saturn floor) · genre(R&B;) · artist(—) · venue(FSQ — modest sub). GATE (doc): slower release than the racks so the floor decay lives.

Ch 9 | OH (st)

Mic: Shure Beta 27

Mic Notes: Beta 27 LDC pair as overheads — flat 60Hz–3k with baked +2dB bumps at 5.5k & 9k, supercardioid (tight, less room — good outdoors), –15 pad available.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	200 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	—	OFF	—	—	Flat
2	9 kHz	Bell	-2 dB	2	
1	300 Hz	Bell	-5 dB	1.5	
HC	—	HC	—	—	No LPF

Engineer Notes: Capsule-voicing gate: the top is already lifted (5.5k+9k baked) → NO HF boost; a light –2@9k tames fizz instead. –5@300 clears low wash + kit bleed so it's cymbals/sheen, not a room mic. Supercardioid keeps the outdoor stage tight. HPF 200. TRACE: base(Beta 27 — baked top) · equip(HHX cymbals) · genre(R&B; — cymbal sheen) · artist(—) · venue(FSQ — supercard tight, clear wash).

Ch 22 | Perc 1

Mic: Shure SM57

Mic Notes: SM57 on aux/hand percussion — kept conservative per the brief (instrument not confirmed).

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	120 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	4 kHz	Bell	+2 dB	1	
2	400 Hz	Bell	-3 dB	1.8	
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: Conservative per the brief: light +2@4k attack, -3@400 box, HPF 120. Voicing left neutral — dial to the actual instrument at soundcheck. TRACE: base(SM57) · equip(aux perc) · genre(R&B;) · artist(—) · venue(FSQ).

Ch 23 | Perc 2

Mic: Shure SM57

Mic Notes: SM57 on aux/hand percussion — kept conservative per the brief (instrument not confirmed).

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	120 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	4 kHz	Bell	+2 dB	1	
2	400 Hz	Bell	-3 dB	1.8	
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: Conservative per the brief: light +2@4k attack, -3@400 box, HPF 120. Voicing left neutral — dial to the actual instrument at soundcheck. TRACE: base(SM57) · equip(aux perc) · genre(R&B;) · artist(—) · venue(FSQ).

Ch 11 | Bass DI

Mic: XLR (DI)

Mic Notes: Bass DI — clean, full-range. The PG52 (a kick mic) is on the cab. LANE: the DI owns note definition + mids + upper harmonics; the PG52 owns the sub/thump — so the DI's lows are pulled back to de-stack.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	40 Hz	LC	—	—	High-pass
4	1.5 kHz	Bell	-4 dB	1.5	
3	700 Hz	Bell	+4 dB	1	
2	250 Hz	Bell	-5 dB	2	
1	80 Hz	Shelf	+3 dB	0.71	
HC	—	HC	—	—	No LPF

Engineer Notes: R&B/soul bass = round, low-mid forward, top rolled. +4@700 note/growl (DI's lane), -4@1.5k tames string clank, -5@250 de-stacks off the PG52's low body, +3@80 modest (PG52 carries the real sub). TRACE: base(DI clean — definition lane) · equip(bass rig, DI+cab) · genre(R&B; — round, low-mid forward) · artist(—) · venue(FSQ — support 80). COMP (doc): opto ~3:1, 20–30ms atk, even the pocket.

Ch 12 | Bass Mic

Mic: Shure PG52

Mic Notes: PG52 is a kick mic on the bass cab — 30Hz–13k, tuned low-end thump + a slight upper-mid click bump, rolls off above 13k (no air). It's the SUB/BODY layer under the DI.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	30 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	2.5 kHz	Bell	+2 dB	1	
2	400 Hz	Bell	-5 dB	2	
1	90 Hz	Shelf	+4 dB	0.71	
HC	8 kHz	HC	—	—	Low-pass

Engineer Notes: Owns the low thump: +4@90 shelf. -5@400 carves a pocket so it doesn't double the DI's mud. Small +2@2.5k for finger attack (the PG52's click bump). LPF 8k — no useful top, keep it dark body. TRACE: base(PG52 kick-mic-on-cab — sub lane) · equip(bass cab) · genre(R&B; thump) · artist(—) · venue(FSQ). Two-mic: PG52 lows, DI definition — no low boost on both.

Ch 13 | Gtr 1

Mic: Sennheiser e609

Mic Notes: e609 flat-face over the cab — bright upper-mid/presence 4–5k, supercardioid, can get edgy 2.5–4k on bright amps. Owns cab presence.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	100 Hz	LC	—	—	High-pass
4	3 kHz	Bell	-3 dB	2	
3	1.2 kHz	Bell	+2 dB	1.2	
2	400 Hz	Bell	-4 dB	2	
1	150 Hz	Bell	-3 dB	1.5	
HC	—	HC	—	—	No LPF

Engineer Notes: Rhythm R&B; guitar sits under the vocal + horns. -3@3k tames the e609 edge; +2@1.2k so the comp speaks; -4@400 box; HPF 100 + -3@150 keeps it out of the bass. TRACE: base(e609 — bright/edgy) · equip(gtr cab) · genre(R&B; comp — supportive, not a wall) · artist(—) · venue(FSQ — deeper box cut). Staggered vs the 57 guitars.

Ch 14 | Gtr 2

Mic: Sennheiser e609

Mic Notes: e609 as Gtr 1; voiced a hair different (edge 2.8k, presence 1.4k) so two e609 guitars don't overlay.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	100 Hz	LC	—	—	High-pass
4	2.8 kHz	Bell	-3 dB	2	
3	1.4 kHz	Bell	+2 dB	1.2	
2	450 Hz	Bell	-4 dB	2	
1	150 Hz	Bell	-3 dB	1.5	
HC	—	HC	—	—	No LPF

Engineer Notes: As Gtr 1 with the edge/presence shifted so the two e609 guitars separate. TRACE: base(e609) · equip(gtr cab) · genre(R&B; comp) · artist(—) · venue(FSQ).

Ch 15 | Gtr 3

Mic: Shure SM57

Mic Notes: SM57 on the cab — mid-forward, presence 3–5k, builds box/honk 300–500. Owns mid grit.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	100 Hz	LC	—	—	High-pass
4	3.5 kHz	Bell	+3 dB	1	
3	800 Hz	Bell	-2 dB	1.2	
2	400 Hz	Bell	-5 dB	2	
1	180 Hz	Bell	-3 dB	1.5	
HC	—	HC	—	—	No LPF

Engineer Notes: +3@3.5k presence (57's lane — differs from the e609 guitars' voicing so 4 gtrs separate), -5@400 box, -2@800 honk, HPF 100 + 180 trim off the bass. TRACE: base(SM57 — mid grit) · equip(gtr cab) · genre(R&B; — present, under the vocals) · artist(—) · venue(FSQ — deeper box).

Ch 16 | Gtr 4

Mic: Shure SM57

Mic Notes: SM57 as Gtr 3; presence at 3k, box 450 so the two 57 guitars separate.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	100 Hz	LC	—	—	High-pass
4	3 kHz	Bell	+3 dB	1	
3	850 Hz	Bell	-2 dB	1.2	
2	450 Hz	Bell	-5 dB	2	
1	180 Hz	Bell	-3 dB	1.5	
HC	—	HC	—	—	No LPF

Engineer Notes: As Gtr 3, shifted. TRACE: base(SM57) · equip(gtr cab) · genre(R&B;) · artist(—) · venue(FSQ).

Ch 17 | Sousa

Mic: Audio-Technica PRO 35

Mic Notes: AT Pro 35 clip on the sousaphone bell — 50Hz–15k, 80Hz rolloff 18dB/oct, strong lows (good for low brass), rounded top, 145 SPL. The LOW-brass foundation.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	50 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	1.2 kHz	Bell	+2 dB	1.2	
2	350 Hz	Bell	-4 dB	1.8	
1	90 Hz	Bell	+3 dB	1	
HC	8 kHz	HC	—	—	Low-pass

Engineer Notes: Sousaphone is the bass of the brass band — +3@90 weight, +2@1.2k so the line has pitch definition (not just thump), -4@350 mud in the dense horn stack. LPF 8k (no useful top). Owns the sub-brass lane; sits below the bass guitar's 80. TRACE: base(Pro 35 — strong lows) · equip(sousaphone) · genre(funk brass — walking foundation) · artist(—) · venue(FSQ). COMP (doc): opto ~3:1, 20ms, even the line.

Ch 18 | Bone

Mic: Audio-Technica PRO 35

Mic Notes: Pro 35 clip on the bell — rounded top means gentle presence. Trombone owns the low-brass midrange ~1k.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	80 Hz	LC	—	—	High-pass
4	6 kHz	Bell	+2 dB	1	
3	1.2 kHz	Bell	-3 dB	2	
2	500 Hz	Bell	-4 dB	1.8	
1	—	OFF	—	—	Flat
HC	10 kHz	HC	—	—	Low-pass

Engineer Notes: Section slotting: the bone owns ~1k, so its bark cut sits there (-3@1.2k) — trumpet's cut goes higher, sax lower. -4@500 mud, +2@6k rasp for definition over the Pro 35's rolled top. TRACE: base(Pro 35 rounded top) · equip(trombone) · genre(funk brass — fast transients) · artist(—) · venue(FSQ). COMP (doc): fast atk ~5ms — brass transients jump.

Ch 19 | Tenor

Mic: Audio-Technica PRO 35

Mic Notes: Pro 35 clip at the bell — tenor sax, lower reed. Upper-mid harshness + body resonance; needs upper harmonics to cut a dense mix.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	80 Hz	LC	—	—	High-pass
4	7 kHz	Bell	+3 dB	1	
3	800 Hz	Bell	-3 dB	2	
2	350 Hz	Bell	-4 dB	1.8	
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: Section slotting: tenor's honk cut at 800 (lowest reed), below the alto (1.5k) and trumpet (2.7k) so the horns don't pile. -4@350 body, +3@7k reed air to cut over the rolled top. TRACE: base(Pro 35) · equip(tenor sax) · genre(funk horns) · artist(—) · venue(FSQ). Watch the plasticky upper-mid up close.

Ch 20 | Alto

Mic: Audio-Technica PRO 35

Mic Notes: Pro 35 clip — alto sax, brighter reed than the tenor. Owns ~1.5k in the section.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	100 Hz	LC	—	—	High-pass
4	8 kHz	Bell	+3 dB	1	
3	1.5 kHz	Bell	-3 dB	2	
2	400 Hz	Bell	-3 dB	1.8	
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: Alto honk cut at 1.5k (its lane, above the tenor's 800), -3@400 body, +3@8k air. Slots between tenor and trumpet.
TRACE: base(Pro 35) · equip(alto sax) · genre(funk horns) · artist(—) · venue(FSQ).

Ch 21 | Tpt

Mic: Audio-Technica PRO 35

Mic Notes: Pro 35 clip on the bell — trumpet, the brightest/loudest horn, transients jump. Owns the top of the section ~2.7k.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	120 Hz	LC	—	—	High-pass
4	9 kHz	Bell	+2 dB	1	
3	2.7 kHz	Bell	-4 dB	2	
2	500 Hz	Bell	-3 dB	1.8	
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: Trumpet's bark cut sits highest in the section (-4@2.7k) — tenor@800, bone@1.2k, alto@1.5k, trumpet@2.7k, so each horn owns a lane and they don't pile. -3@500 body, +2@9k sizzle. TRACE: base(Pro 35 rounded top) · equip(trumpet) · genre(funk horns — lead bark) · artist(—) · venue(FSQ). COMP (doc): fast atk mandatory — trumpet spikes above the mix.

■ AMBIENT ■

Ch 24 | BT Aux

Mic: Line / BT

Mic Notes: Bluetooth aux — walk-in / between-set music, not a performance input.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	40 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	—	OFF	—	—	Flat
2	—	OFF	—	—	Flat
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: Near-flat playback. HPF 40 only. TRACE: base(mastered playback) · venue(FSQ).

Ch 31 | DJ L

Mic: XLR (DI)

Mic Notes: DJ playback (turntables/controller), stereo — mastered full-range.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	30 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	—	OFF	—	—	Flat
2	—	OFF	—	—	Flat
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: Left near-flat — EQ'ing mastered playback like a mic thins it. HPF 30 only; add a small 315 trim live only if it clouds the band. TRACE: base(mastered stereo) · venue(FSQ).

Ch 32 | DJ R

Mic: XLR (DI)

Mic Notes: DJ playback (turntables/controller), stereo — mastered full-range.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	30 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	—	OFF	—	—	Flat
2	—	OFF	—	—	Flat
1	—	OFF	—	—	Flat
HC	—	HC	—	—	No LPF

Engineer Notes: Left near-flat — EQ'ing mastered playback like a mic thins it. HPF 30 only; add a small 315 trim live only if it clouds the band. TRACE: base(mastered stereo) · venue(FSQ).

■ VOCALS ■

Ch 25 | Wls 1

Mic: Shure Beta 58A

Mic Notes: Beta 58A supercardioid handheld — TWO baked presence peaks (~4k & ~10k), boxy ~600, <500 attenuated, tight pattern/high GBF (brighter than an SM58). LEAD voicing.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	100 Hz	LC	—	—	High-pass
4	10 kHz	Bell	-3 dB	2	DYNAMIC: thr=-18dB atk=3ms rel=120ms — bites only on peaks
3	4 kHz	Bell	-2 dB	2.5	
2	600 Hz	Bell	-4 dB	1.5	
1	—	OFF	—	—	Flat
HC	16 kHz	HC	—	—	Low-pass

Engineer Notes: Cut-only (feedback + taste). Dynamic de-ess -3@10k on the baked top peak so the air stays between sibilants; light -2@4k tames stridency without killing the bite the capsule bakes; -4@600 box for outdoor intelligibility. HPF 100. Overrides the FSQ template wireless curve/notch — ring out at soundcheck; reach for comp + a touch of plate before more EQ. TRACE: base(Beta 58A twin peaks) · genre(R&B; lead) · venue(FSQ intelligibility).

Ch 26 | Wls 2

Mic: Shure Beta 58A

Mic Notes: Beta 58A handheld — backing voicing: sits a touch behind the lead (–2@3k) so the harmony supports.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	120 Hz	LC	—	—	High-pass
4	10 kHz	Bell	-2 dB	2	DYNAMIC: thr=-18dB atk=3ms rel=120ms — bites only on peaks
3	3 kHz	Bell	-2 dB	2.5	
2	600 Hz	Bell	-4 dB	1.5	
1	—	OFF	—	—	Flat
HC	16 kHz	HC	—	—	Low-pass

Engineer Notes: Cut-only. –4@600 box, –2@10k de-ess, –2@3k to seat it behind the lead. HPF 120. Overrides the template wireless notch — ring out. TRACE: base(Beta 58A) · genre(R&B; BGV) · venue(FSQ).

Ch 27 | Wls 3

Mic: Shure Beta 58A

Mic Notes: Beta 58A handheld — backing voicing: sits a touch behind the lead (–2@3k) so the harmony supports.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	120 Hz	LC	—	—	High-pass
4	10 kHz	Bell	-2 dB	2	DYNAMIC: thr=-18dB atk=3ms rel=120ms — bites only on peaks
3	3 kHz	Bell	-2 dB	2.5	
2	600 Hz	Bell	-4 dB	1.5	
1	—	OFF	—	—	Flat
HC	16 kHz	HC	—	—	Low-pass

Engineer Notes: Cut-only. –4@600 box, –2@10k de-ess, –2@3k to seat it behind the lead. HPF 120. Overrides the template wireless notch — ring out. TRACE: base(Beta 58A) · genre(R&B; BGV) · venue(FSQ).

Ch 28 | Wls 4

Mic: Shure Beta 58A

Mic Notes: Beta 58A handheld — backing voicing: sits a touch behind the lead (–2@3k) so the harmony supports.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	120 Hz	LC	—	—	High-pass
4	10 kHz	Bell	-2 dB	2	DYNAMIC: thr=-18dB atk=3ms rel=120ms — bites only on peaks
3	3 kHz	Bell	-2 dB	2.5	
2	600 Hz	Bell	-4 dB	1.5	
1	—	OFF	—	—	Flat
HC	16 kHz	HC	—	—	Low-pass

Engineer Notes: Cut-only. –4@600 box, –2@10k de-ess, –2@3k to seat it behind the lead. HPF 120. Overrides the template wireless notch — ring out. TRACE: base(Beta 58A) · genre(R&B; BGV) · venue(FSQ).

Ch 29 | Vox 5

Mic: Shure SM58

Mic Notes: SM58 on a stand — presence 4–6k, boxy ~500, gentle low rolloff. Backing/utility vocal.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	110 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	5 kHz	Bell	-2 dB	2.5	
2	500 Hz	Bell	-4 dB	1.5	
1	—	OFF	—	—	Flat
HC	16 kHz	HC	—	—	Low-pass

Engineer Notes: Cut-only. -4@500 box, light -2@5k if spitty, HPF 110. Supportive — a touch behind the leads. TRACE: base(SM58) · genre(R&B; BGV) · venue(FSQ).

Ch 30 | Vox 6

Mic: Shure SM58

Mic Notes: SM58 on a stand — presence 4–6k, boxy ~500, gentle low rolloff. Backing/utility vocal.

Band	Freq	Type	Gain	Q	Notes / Rationale
LC	110 Hz	LC	—	—	High-pass
4	—	OFF	—	—	Flat
3	5 kHz	Bell	-2 dB	2.5	
2	500 Hz	Bell	-4 dB	1.5	
1	—	OFF	—	—	Flat
HC	16 kHz	HC	—	—	Low-pass

Engineer Notes: Cut-only. -4@500 box, light -2@5k if spitty, HPF 110. Supportive — a touch behind the leads. TRACE: base(SM58) · genre(R&B; BGV) · venue(FSQ).

Nasty Nati Band — FOH EQ Rationale

Fountain Square (outdoor) · DiGiCo Quantum 225 · 2026-07-25 · Rev 1.0 Deep Think

Artist. Per Brian's call, processed as R&B (no artist dig). Nasty Nati is an R&B/funk BRASS band — sousaphone, trombone, tenor & alto sax, trumpet fronting the rhythm section, so the horn section is the identity and gets slotted as a section (each horn owns a frequency lane).

Room. Open-air Fountain Square — no room gain, low end + HF dissipate over the throw, façade slap but no reverb tail. Cuts run deeper than indoor (–6 to –9 typ), HPF decisive, clarity first. L-Acoustics A15/KS21 house PA, M32 monitors.

Research. Genre fixed R&B by Brian (no artist research). Per-source fresh web pass (Shure/Audix/Audio-Technica/Sennheiser specs + Gearspace/PSW + masteringthemix/musicguymixing R&B-drum consensus) cross-checked vs KB mic-library + eq-starting-points, and beside Brian's console-verified Izzy Escobar 2.0 build (same FSQ house kit). Backline (Backstage Backline pull 26-0420): Mapex Saturn V kit (22" kick, 10/12/16 toms, 14" Black Panther snare), Sabian HHX cymbals, Yamaha CP33 keys. Weather (Open-Meteo, 6–10pm): 7/25 77–83°F, 43–61% RH, wind 4–8 mph, rain ~1% — HF carries a touch better; don't over-boost the top.

What changed from the KB default / prior rev — and why

- Kick-out D6 (vs Izzy's 52A): near-flat — NO 3–5k boost (capsule bakes +5k) and NO 600 cut (already –15 scooped).
- Added snare-bottom e604: HPF 180, owns wire snap only; i5 keeps body/crack.
- OH is a Beta 27 STEREO pair on fader 9 (not SM81 split 9/10) — top already baked, so no HF boost, tame 9k; ch 10 stays the PL8 return.
- Bass two-mic INVERTED vs Izzy: PG52 (kick mic on the cab) owns sub/thump, DI owns definition — de-stacked the DI lows.
- Four guitars: e609 (1/2) voiced against SM57 (3/4) so the mids don't pile.
- Vocals override the FSQ template's wireless curve/feedback notch — ring out at soundcheck.

Question round — what was asked, what Brian decided

- Q: Percussion 1/2 instrument? -> Brian: generic aux perc — conservative, neutral voicing.
- Q: snare-bottom '604'? -> Brian: Sennheiser e604.
- Genre fixed R&B for all three by Brian; no artist research.

Reverb — Seventh Heaven Pro (100% wet returns)

- **VOCAL — Plates 1 / #06 Vocal Plate** | Settings: Decay 1.5s (factory) · PreDelay 24ms (factory) · VLF –19 (factory) · E/L Max Early · Late –6 (raised from a Memo-deep cut — outdoors carries the late field) · Late Rolloff 6400 (factory) | In-plugin EQ: LC 180 Hz on the return; ducker Reverb mode, Thr –22 dB | Why: Lead-vocal sheen + presence, sits forward over the band; no room outdoors to muddy it — the workhorse lead plate.
- **VOCAL — Chambers 1 / #10 Vocal Chamber** | Settings: Decay 1.2s (from 1.6s factory — tighter for up-tempo funk) · PreDelay 15ms (from 0 factory) · VLF –15 (from –10 factory — less low wash outdoors) · E/L Max Early · Late –8 · Late Rolloff 8000 (factory) | In-plugin EQ: LC 200 Hz on the return | Why: Gives place without wash on up-tempo/funk material; hands off to the Vocal Plate when a song slows down.

- **VOCAL — Halls 1 / #11 Gold Hall** | Settings: Decay 1.8s (factory) · PreDelay 20ms · VLF -12 (cut hard from 0 factory — Gold Hall always gets its VLF cut) · E/L Max Early · Late -6 · Late Rolloff 6000 (from factory) | In-plugin EQ: LC 200 Hz + HS -2 above 8k on the return | Why: The ballad / feature bloom when a song opens up — used sparingly, the big-moment size.
- **INSTRUMENT — Plates 1 / #04 Snare Plate A** | Settings: Decay 1.0s (from 1.2s factory — tighter outdoors) · PreDelay 0 (factory) · VLF -15 · E/L Max Early · Late -8 · Late Rolloff 6400 (factory) | In-plugin EQ: LC 250 Hz on the return | Why: Adds snap/depth to the snare on the funk backbeat without washing the kit. Feeds the ch-10 PL8 return.
- **INSTRUMENT — Halls 1 / #15 Brass Hall** | Settings: Decay 1.5s (from factory) · PreDelay 10ms · VLF -14 · E/L Max Early · Late -6 · Late Rolloff 6000 (pulled from 8400 factory — tame the bright top outdoors) | In-plugin EQ: LC 200 Hz on the return | Why: Gives the horn section a shared space so five clip mics read as one section, not five spots.
- **GENERAL — Rooms 1 / #02 Studio B Close** | Settings: Decay 0.6s (factory) · PreDelay 0 · VLF -12 (cut hard from 0 factory — always cut) · E/L Max Early · Late -10 · Late Rolloff 6800 (factory) | In-plugin EQ: LC 300 Hz on the return | Why: A hair of glue on the kit/percussion so the outdoor stage isn't bone-dry — very short, no obvious tail.
- **USING THEM TOGETHER** — Vocal Plate is the default lead — forward and present. On up-tempo/funk numbers switch the lead to the tighter Vocal Chamber so the groove stays dry and articulate; the two hand off song-to-song. Gold Hall is the big-moment throw only — a feature or a ballad — never under the whole set. Brass Hall sits under the horn section as its own return so the five clip mics glue into one section; keep it below the vocal returns so it doesn't stack mud. Snare Plate A feeds the reserved ch-10 PL8 return for backbeat depth; Studio B Close is a whisper of kit glue only. Everything runs 100% wet on its own return, VLF cut, Late higher than a Memo send because there's no room to carry the tail.

DRUMS

Ch 1 | Kick In · Shure Beta 91A

HPF 40 | LPF off || B4 +4@3 kHz Q1.2 BELL B3 -3@400 Hz Q2 BELL B2 -3@250 Hz Q1.8 BELL B1 +2@80 Hz Q1.2 BELL

Beta 91A boundary inside the kick — the click/attack engine. Contour assumed FLAT (the 400 cut lives on the desk; if the switch is engaged, halve it). Owns click + upper; lows tucked under the D6.

+4@3k beater definition that travels outdoors (R&B punch, not a metal click). 400/250 clear the shell boom the boundary picks up — eased for open air. Lows modest (+2@80) so they don't stack with the D6's baked 63Hz. TRACE: base(91A boundary, +4@3k click) · equip(22" Mapex Saturn kick — no change) · genre(R&B — punch over click) · artist(no dig) · venue(FSQ — box cuts eased, no room mud). COMP (doc only, not patched): Green FET ~4:1, 15ms atk, 3–4 dB GR.

Ch 2 | Kick Out · Audix D6

HPF 40 | LPF off || B4 flat B3 flat B2 -2@250 Hz Q1.8 BELL B1 +3@60 Hz Q1.2 BELL

Audix D6 pre-scooped 'smiley' — peaks ~63Hz & ~5kHz, deep scoop -15dB @600. Thump+click baked in; needs almost no EQ. Owns the sub/body under the 91A's click.

Barely touched — the capsule IS the kick voicing. +3@60 supports the low open air swallows; light 250 trim. Capsule-voicing gate: NO 3–5k boost (D6 already bakes +5k — a boost stacks harsh) and NO 600 cut (already -15 scooped). TRACE: base(D6 smiley — near-flat) · equip(22" kick — no change) · genre(R&B thump) · artist(—) · venue(FSQ — +60 for lost low). Two-mic: D6 owns sub, 91A owns click.

Ch 3 | Snare Top · Audix i5

HPF 120 | LPF off || B4 +2@7 kHz Q0.8 BELL B3 -2@5.5 kHz Q2 BELL B2 +3@1 kHz Q1 BELL B1 -5@300 Hz Q2 BELL

i5 bakes +5dB@150 body + a strong +9dB@5.5k presence, mids slightly scooped — more open/body than a 57. Owns the snare body + crack; the e604 owns the wire snap.

Capsule-voicing gate: the +9@5.5k is baked, so I TRIM it -2 (not boost) and put the snap up at 7k where the capsule rolls off. +3@1k crack, -5@300 box (eased — the i5 isn't boxy, don't gut it). TRACE: base(i5 +9@5.5k baked → trim) · equip(14" Black Panther — no change) · genre(R&B backbeat — body over crack) · artist(—) · venue(FSQ — 7k snap to cut outdoors). GATE (doc): fast ~1ms atk but ghost notes/press rolls must live — 15–20ms rel. Two-mic: i5 body+crack, e604 snap.

Ch 4 | Snare Bot · Sennheiser e604

HPF 180 | LPF off || B4 +3@8 kHz Q0.8 BELL B3 -3@1 kHz Q1.5 BELL B2 flat B1 flat

e604 clip on the bottom head — scooped low-mids, voiced attack, thin lows (ideal for wires). Owns the snare-wire snap/sizzle only.

HPF way up at 180 so it's wires, not shell or kick bleed. +3@8k snap; -3@1k clears the e604's box. Lane: owns the top-end wire sizzle, the i5 owns body — no overlap. TRACE: base(e604 thin/voiced-attack) · equip(snare wires) · genre(R&B — crisp backbeat) · artist(—) · venue(FSQ — 8k to cut). GATE (doc): key off the snare top so wires don't chatter.

Ch 5 | Hat · Shure SM81

HPF 500 | LPF 16000 || B4 flat B3 flat B2 -5@2 kHz Q1.2 BELL B1 -6@800 Hz Q1.5 BELL

SM81 — ruler-flat, un-hyped highs. Takes EQ straight; no built-in flattery to fight.

No HF boost (81 is already detailed and dry 7/24 air thins the top over the throw anyway — don't make it brittle). Clear the low bleed (800) + the 2k clang so it sparkles clean. TRACE: base(SM81 flat) · equip(14" HHX hats) · genre(R&B — tight hat) · artist(—) · venue(FSQ+dry — resist top boost).

Ch 6 | Rack 1 · Audix D2

HPF 90 | LPF 12000 || B4 flat B3 +4@2.8 kHz Q1 BELL B2 -3@450 Hz Q1.8 BELL B1 +3@135 Hz Q1.2 BELL

D2 tuned to control tom resonance — articulate with little EQ; leaner deep lows than the D4.

Attack lift +4@2.8k (trust the capsule), gentle 135 body, modest 450 mud cut. TRACE: base(D2 — articulate) · equip(10" Saturn rack) · genre(R&B fills) · artist(—) · venue(FSQ). GATE (doc): snappy release for funk; don't choke the decay.

Ch 7 | Rack 2 · Audix D2

HPF 80 | LPF 12000 || B4 flat B3 +4@2.5 kHz Q1 BELL B2 -3@405 Hz Q1.8 BELL B1 +3@120 Hz Q1.2 BELL

As Rack 1, shifted down for the larger 12" drum.

Let the D2 do the work; body at 120 for the bigger shell. TRACE: base(D2) · equip(12" Saturn rack) · genre · artist(—) · venue(FSQ).

Ch 8 | Floor · Audix D4

HPF 55 | LPF 10000 || B4 flat B3 +4@1.8 kHz Q1 BELL B2 -3@405 Hz Q1.8 BELL B1 +4@70 Hz Q0.71 SHELF

D4 reaches ~an octave lower than the D2 natively; smooth 800–1k (not scooped) — may want a touch of click.

Body shelf modest +4@70 (support, not a lift; ride the sub outdoors). +4@1.8k stick definition the D4 lacks. TRACE: base(D4 — deep, smooth mids) · equip(16" Saturn floor) · genre(R&B) · artist(—) · venue(FSQ — modest sub). GATE (doc): slower release than the racks so the floor decay lives.

Ch 9 | OH (st) · Shure Beta 27

HPF 200 | LPF off || B4 flat B3 flat B2 -2@9 kHz Q2 BELL B1 -5@300 Hz Q1.5 BELL

Beta 27 LDC pair as overheads — flat 60Hz–3k with baked +2dB bumps at 5.5k & 9k, supercardioid (tight, less room — good outdoors), -15 pad available.

Capsule-voicing gate: the top is already lifted (5.5k+9k baked) → NO HF boost; a light -2@9k tames fizz instead. -5@300 clears low wash + kit bleed so it's cymbals/sheen, not a room mic. Supercardioid keeps the outdoor stage tight. HPF 200. TRACE: base(Beta 27 — baked top) · equip(HHX cymbals) · genre(R&B — cymbal sheen) · artist(—) · venue(FSQ — supercard tight, clear wash).

BASS

Ch 11 | Bass DI · XLR (DI)

HPF 40 | LPF off || B4 -4@1.5 kHz Q1.5 BELL B3 +4@700 Hz Q1 BELL B2 -5@250 Hz Q2 BELL B1 +3@80 Hz Q0.71 SHELF

Bass DI — clean, full-range. The PG52 (a kick mic) is on the cab. LANE: the DI owns note definition + mids + upper harmonics; the PG52 owns the sub/thump — so the DI's lows are pulled back to de-stack.

R&B/soul bass = round, low-mid forward, top rolled. +4@700 note/growl (DI's lane), -4@1.5k tames string clank, -5@250 de-stacks off the PG52's low body, +3@80 modest (PG52 carries the real sub). TRACE: base(DI clean — definition lane) · equip(bass rig, DI+cab) · genre(R&B — round, low-mid forward) · artist(—) · venue(FSQ — support 80). COMP (doc): opto ~3:1, 20–30ms atk, even the pocket.

Ch 12 | Bass Mic · Shure PG52

HPF 30 | LPF 8000 || B4 flat B3 +2@2.5 kHz Q1 BELL B2 -5@400 Hz Q2 BELL B1 +4@90 Hz Q0.71 SHELF

PG52 is a kick mic on the bass cab — 30Hz–13k, tuned low-end thump + a slight upper-mid click bump, rolls off above 13k (no air). It's the SUB/BODY layer under the DI.

Owens the low thump: +4@90 shelf. -5@400 carves a pocket so it doesn't double the DI's mud. Small +2@2.5k for finger attack (the PG52's click bump). LPF 8k — no useful top, keep it dark body. TRACE: base(PG52 kick-mic-on-cab — sub lane) · equip(bass cab) · genre(R&B thump) · artist(—) · venue(FSQ). Two-mic: PG52 lows, DI definition — no low boost on both.

GUITAR

Ch 13 | Gtr 1 · Sennheiser e609

HPF 100 | LPF off || B4 -3@3 kHz Q2 BELL B3 +2@1.2 kHz Q1.2 BELL B2 -4@400 Hz Q2 BELL B1 -3@150 Hz Q1.5 BELL

e609 flat-face over the cab — bright upper-mid/presence 4–5k, supercardioid, can get edgy 2.5–4k on bright amps. Owns cab presence.

Rhythm R&B guitar sits under the vocal + horns. -3@3k tames the e609 edge; +2@1.2k so the comp speaks; -4@400 box; HPF 100 + -3@150 keeps it out of the bass. TRACE: base(e609 — bright/edgy) · equip(gtr cab) · genre(R&B comp — supportive, not a wall) · artist(—) · venue(FSQ — deeper box cut). Staggered vs the 57 guitars.

Ch 14 | Gtr 2 · Sennheiser e609

HPF 100 | LPF off || B4 -3@2.8 kHz Q2 BELL B3 +2@1.4 kHz Q1.2 BELL B2 -4@450 Hz Q2 BELL B1 -3@150 Hz Q1.5 BELL

e609 as Gtr 1; voiced a hair different (edge 2.8k, presence 1.4k) so two e609 guitars don't overlay.

As Gtr 1 with the edge/presence shifted so the two e609 guitars separate. TRACE: base(e609) · equip(gtr cab) · genre(R&B comp) · artist(—) · venue(FSQ).

Ch 15 | Gtr 3 · Shure SM57

HPF 100 | LPF off || B4 +3@3.5 kHz Q1 BELL B3 -2@800 Hz Q1.2 BELL B2 -5@400 Hz Q2 BELL B1 -3@180 Hz Q1.5 BELL

SM57 on the cab — mid-forward, presence 3–5k, builds box/honk 300–500. Owns mid grit.

+3@3.5k presence (57's lane — differs from the e609 guitars' voicing so 4 gtrs separate), -5@400 box, -2@800 honk, HPF 100 + 180 trim off the bass. TRACE: base(SM57 — mid grit) · equip(gtr cab) · genre(R&B — present, under the vocals) · artist(—) · venue(FSQ — deeper box).

Ch 16 | Gtr 4 · Shure SM57

HPF 100 | LPF off || B4 +3@3 kHz Q1 BELL B3 -2@850 Hz Q1.2 BELL B2 -5@450 Hz Q2 BELL B1 -3@180 Hz Q1.5 BELL

SM57 as Gtr 3; presence at 3k, box 450 so the two 57 guitars separate.

As Gtr 3, shifted. TRACE: base(SM57) · equip(gtr cab) · genre(R&B) · artist(—) · venue(FSQ).

HORNS

Ch 17 | Sousa · Audio-Technica PRO 35

HPF 50 | LPF 8000 || B4 flat B3 +2@1.2 kHz Q1.2 BELL B2 -4@350 Hz Q1.8 BELL B1 +3@90 Hz Q1 BELL

AT Pro 35 clip on the sousaphone bell — 50Hz–15k, 80Hz rolloff 18dB/oct, strong lows (good for low brass), rounded top, 145 SPL. The LOW-brass foundation.

Sousaphone is the bass of the brass band — +3@90 weight, +2@1.2k so the line has pitch definition (not just thump), –4@350 mud in the dense horn stack. LPF 8k (no useful top). Owns the sub-brass lane; sits below the bass guitar's 80. TRACE: base(Pro 35 — strong lows) · equip(sousaphone) · genre(funk brass — walking foundation) · artist(—) · venue(FSQ). COMP (doc): opto ~3:1, 20ms, even the line.

Ch 18 | Bone · Audio-Technica PRO 35

HPF 80 | LPF 10000 || B4 +2@6 kHz Q1 BELL B3 -3@1.2 kHz Q2 BELL B2 -4@500 Hz Q1.8 BELL B1 flat

Pro 35 clip on the bell — rounded top means gentle presence. Trombone owns the low-brass midrange ~1k.

Section slotting: the bone owns ~1k, so its bark cut sits there (–3@1.2k) — trumpet's cut goes higher, sax lower. –4@500 mud, +2@6k rasp for definition over the Pro 35's rolled top. TRACE: base(Pro 35 rounded top) · equip(trombone) · genre(funk brass — fast transients) · artist(—) · venue(FSQ). COMP (doc): fast atk ~5ms — brass transients jump.

Ch 19 | Tenor · Audio-Technica PRO 35

HPF 80 | LPF off || B4 +3@7 kHz Q1 BELL B3 -3@800 Hz Q2 BELL B2 -4@350 Hz Q1.8 BELL B1 flat

Pro 35 clip at the bell — tenor sax, lower reed. Upper-mid harshness + body resonance; needs upper harmonics to cut a dense mix.

Section slotting: tenor's honk cut at 800 (lowest reed), below the alto (1.5k) and trumpet (2.7k) so the horns don't pile. –4@350 body, +3@7k reed air to cut over the rolled top. TRACE: base(Pro 35) · equip(tenor sax) · genre(funk horns) · artist(—) · venue(FSQ). Watch the plasticky upper-mid up close.

Ch 20 | Alto · Audio-Technica PRO 35

HPF 100 | LPF off || B4 +3@8 kHz Q1 BELL B3 -3@1.5 kHz Q2 BELL B2 -3@400 Hz Q1.8 BELL B1 flat

Pro 35 clip — alto sax, brighter reed than the tenor. Owns ~1.5k in the section.

Alto honk cut at 1.5k (its lane, above the tenor's 800), –3@400 body, +3@8k air. Slots between tenor and trumpet. TRACE: base(Pro 35) · equip(alto sax) · genre(funk horns) · artist(—) · venue(FSQ).

Ch 21 | Tpt · Audio-Technica PRO 35

HPF 120 | LPF off || B4 +2@9 kHz Q1 BELL B3 -4@2.7 kHz Q2 BELL B2 -3@500 Hz Q1.8 BELL B1 flat

Pro 35 clip on the bell — trumpet, the brightest/loudest horn, transients jump. Owns the top of the section ~2.7k.

Trumpet's bark cut sits highest in the section (–4@2.7k) — tenor@800, bone@1.2k, alto@1.5k, trumpet@2.7k, so each horn owns a lane and they don't pile. –3@500 body, +2@9k sizzle. TRACE: base(Pro 35 rounded top) · equip(trumpet) · genre(funk horns — lead bark) · artist(—) · venue(FSQ). COMP (doc): fast atk mandatory — trumpet spikes above the mix.

DRUMS

Ch 22 | Perc 1 · Shure SM57

HPF 120 | LPF off || B4 flat B3 +2@4 kHz Q1 BELL B2 -3@400 Hz Q1.8 BELL B1 flat

SM57 on aux/hand percussion — kept conservative per the brief (instrument not confirmed).

Conservative per the brief: light +2@4k attack, –3@400 box, HPF 120. Voicing left neutral — dial to the actual instrument at soundcheck. TRACE: base(SM57) · equip(aux perc) · genre(R&B) · artist(—) · venue(FSQ).

Ch 23 | Perc 2 · Shure SM57

HPF 120 | LPF off || B4 flat B3 +2@4 kHz Q1 BELL B2 -3@400 Hz Q1.8 BELL B1 flat

SM57 on aux/hand percussion — kept conservative per the brief (instrument not confirmed).

Conservative per the brief: light +2@4k attack, -3@400 box, HPF 120. Voicing left neutral — dial to the actual instrument at soundcheck. TRACE: base(SM57) · equip(aux perc) · genre(R&B) · artist(—) · venue(FSQ).

AMBIENT

Ch 24 | BT Aux · Line / BT

HPF 40 | LPF off || B4 flat B3 flat B2 flat B1 flat

Bluetooth aux — walk-in / between-set music, not a performance input.

Near-flat playback. HPF 40 only. TRACE: base(mastered playback) · venue(FSQ).

VOCALS

Ch 25 | Wls 1 · Shure Beta 58A

HPF 100 | LPF 16000 || B4 -3@10 kHz Q2 BELL +DEQ B3 -2@4 kHz Q2.5 BELL B2 -4@600 Hz Q1.5 BELL B1 flat

Beta 58A supercardioid handheld — TWO baked presence peaks (~4k & ~10k), boxy ~600, <500 attenuated, tight pattern/high GBF (brighter than an SM58). LEAD voicing.

Cut-only (feedback + taste). Dynamic de-ess -3@10k on the baked top peak so the air stays between sibilants; light -2@4k tames stridency without killing the bite the capsule bakes; -4@600 box for outdoor intelligibility. HPF 100. Overrides the FSQ template wireless curve/notch — ring out at soundcheck; reach for comp + a touch of plate before more EQ. TRACE: base(Beta 58A twin peaks) · genre(R&B lead) · venue(FSQ intelligibility).

Ch 26 | Wls 2 · Shure Beta 58A

HPF 120 | LPF 16000 || B4 -2@10 kHz Q2 BELL +DEQ B3 -2@3 kHz Q2.5 BELL B2 -4@600 Hz Q1.5 BELL B1 flat

Beta 58A handheld — backing voicing: sits a touch behind the lead (-2@3k) so the harmony supports.

Cut-only. -4@600 box, -2@10k de-ess, -2@3k to seat it behind the lead. HPF 120. Overrides the template wireless notch — ring out. TRACE: base(Beta 58A) · genre(R&B BGV) · venue(FSQ).

Ch 27 | Wls 3 · Shure Beta 58A

HPF 120 | LPF 16000 || B4 -2@10 kHz Q2 BELL +DEQ B3 -2@3 kHz Q2.5 BELL B2 -4@600 Hz Q1.5 BELL B1 flat

Beta 58A handheld — backing voicing: sits a touch behind the lead (-2@3k) so the harmony supports.

Cut-only. -4@600 box, -2@10k de-ess, -2@3k to seat it behind the lead. HPF 120. Overrides the template wireless notch — ring out. TRACE: base(Beta 58A) · genre(R&B BGV) · venue(FSQ).

Ch 28 | Wls 4 · Shure Beta 58A

HPF 120 | LPF 16000 || B4 -2@10 kHz Q2 BELL +DEQ B3 -2@3 kHz Q2.5 BELL B2 -4@600 Hz Q1.5 BELL B1 flat

Beta 58A handheld — backing voicing: sits a touch behind the lead (-2@3k) so the harmony supports.

Cut-only. -4@600 box, -2@10k de-ess, -2@3k to seat it behind the lead. HPF 120. Overrides the template wireless notch — ring out. TRACE: base(Beta 58A) · genre(R&B BGV) · venue(FSQ).

Ch 29 | Vox 5 · Shure SM58

HPF 110 | LPF 16000 || B4 flat B3 -2@5 kHz Q2.5 BELL B2 -4@500 Hz Q1.5 BELL B1 flat

SM58 on a stand — presence 4–6k, boxy ~500, gentle low rolloff. Backing/utility vocal.

Cut-only. -4@500 box, light -2@5k if spitty, HPF 110. Supportive — a touch behind the leads. TRACE: base(SM58) · genre(R&B BGV) · venue(FSQ).

Ch 30 | Vox 6 · Shure SM58

HPF 110 | LPF 16000 || B4 flat B3 -2@5 kHz Q2.5 BELL B2 -4@500 Hz Q1.5 BELL B1 flat

SM58 on a stand — presence 4–6k, boxy ~500, gentle low rolloff. Backing/utility vocal.

Cut-only. -4@500 box, light -2@5k if spitty, HPF 110. Supportive — a touch behind the leads. TRACE: base(SM58) · genre(R&B BGV) · venue(FSQ).

AMBIENT

Ch 31 | DJ L · XLR (DI)

HPF 30 | LPF off || B4 flat B3 flat B2 flat B1 flat

DJ playback (turntables/controller), stereo — mastered full-range.

Left near-flat — EQ'ing mastered playback like a mic thins it. HPF 30 only; add a small 315 trim live only if it clouds the band. TRACE: base(mastered stereo) · venue(FSQ).

Ch 32 | DJ R · XLR (DI)

HPF 30 | LPF off || B4 flat B3 flat B2 flat B1 flat

DJ playback (turntables/controller), stereo — mastered full-range.

Left near-flat — EQ'ing mastered playback like a mic thins it. HPF 30 only; add a small 315 trim live only if it clouds the band. TRACE: base(mastered stereo) · venue(FSQ).

Deep-research pass — values reasoned from mic behavior, instrument, genre, the artist's references, and the room. Informed starting points, not gospel; trust your ears at soundcheck.