

DDL Final

-- Create the schema if not exists

```
CREATE SCHEMA IF NOT EXISTS TaxiManagement;
```

-- Create tables within the TaxiManagement schema

```
CREATE TABLE IF NOT EXISTS TaxiManagement.Signin (
```

```
    LoginID INT PRIMARY KEY,
```

```
    Username VARCHAR(20) NOT NULL,
```

```
    Password VARCHAR(20) NOT NULL,
```

```
    Role VARCHAR(10) NOT NULL CHECK (Role IN ('driver', 'customer', 'drivertaxicoordinator'))
```

```
);
```

```
CREATE TABLE IF NOT EXISTS TaxiManagement.Driver (
```

```
    DriverId INT PRIMARY KEY,
```

```
    Name VARCHAR(20) NOT NULL,
```

```
    PhoneNo VARCHAR(15) NOT NULL,
```

```
    Email VARCHAR(50) NOT NULL,
```

```
    AvlStatus BOOLEAN
```

```
);
```

```
CREATE TABLE IF NOT EXISTS TaxiManagement.Customer (
```

```
    CustomerID INT PRIMARY KEY,
```

```
    Name VARCHAR(20) NOT NULL,
```

```
    PhoneNo VARCHAR(15) NOT NULL,
```

```
    Email VARCHAR(50) NOT NULL
```

```
);
```

```
CREATE TABLE IF NOT EXISTS TaxiManagement.Shift (  
    DriverId INT NOT NULL,          -- Foreign key to Driver table  
    Shiftstart Timestamp NOT NULL,  
    Shiftend Timestamp NOT NULL,  
    Hours INT NOT NULL,  
    FOREIGN KEY (DriverId) REFERENCES TaxiManagement.Driver (DriverId)  
);
```

```
CREATE TABLE TaxiManagement.RideBooking (  
    RideID SERIAL PRIMARY KEY,      -- Unique identifier for each ride  
    RideDate DATE NOT NULL,  
    Fare DECIMAL(10, 2) NOT NULL,   -- Fare amount, with two decimal places  
    DriverID INT NOT NULL,          -- Foreign key to the Driver table  
    CustomerID INT NOT NULL,        -- Foreign key to the Customer table  
    Status VARCHAR(20) NOT NULL,    -- Status of the ride (e.g., booked, completed, canceled)  
    CurrentLocation VARCHAR(100) NOT NULL, -- Current location of the ride (could be a coordinate  
    or address)  
    Destination VARCHAR(100) NOT NULL, -- Destination of the ride (could be a coordinate or  
    address)  
    FOREIGN KEY (DriverID) REFERENCES TaxiManagement.Driver (DriverId),  
    FOREIGN KEY (CustomerID) REFERENCES TaxiManagement.Customer (CustomerID)  
);
```

```
CREATE TABLE IF NOT EXISTS TaxiManagement.Payment (  
    PaymentID SERIAL PRIMARY KEY,  
    Fare DECIMAL(10, 2) NOT NULL,  
    RideID INT NOT NULL,  
    FOREIGN KEY (RideID) REFERENCES TaxiManagement.RideBooking (RideID)  
);
```

```
CREATE TABLE IF NOT EXISTS TaxiManagement.Feedback (  
    FeedbackID SERIAL PRIMARY KEY,
```

```

Rating INT NOT NULL, -- Assuming rating is an integer value, adjust as needed
CustomerID INT NOT NULL,
Comment VARCHAR(200), -- Allows up to 200 characters for comments
FOREIGN KEY (CustomerID) REFERENCES TaxiManagement.Customer (CustomerID)
);

CREATE TABLE IF NOT EXISTS TaxiManagement.DriverTaxiCoordinator (
    AdID SERIAL PRIMARY KEY,
    Name VARCHAR(50) NOT NULL,
    PhoneNo VARCHAR(15) NOT NULL,
    Email VARCHAR(50) NOT NULL
);

CREATE TABLE IF NOT EXISTS TaxiManagement.Taxi (
    PlateNumber VARCHAR(10) PRIMARY KEY,
    Model VARCHAR(50) NOT NULL,
    AdID INT NOT NULL,
    FOREIGN KEY (AdID) REFERENCES TaxiManagement.DriverTaxiCoordinator (AdID)
);

CREATE TABLE IF NOT EXISTS TaxiManagement.Gets (
    DriverID INT NOT NULL,
    AdID INT NOT NULL,
    PlateNumber VARCHAR(10) NOT NULL,
    PRIMARY KEY (DriverID, AdID, PlateNumber),
    FOREIGN KEY (DriverID) REFERENCES TaxiManagement.Driver (DriverId),
    FOREIGN KEY (AdID) REFERENCES TaxiManagement.DriverTaxiCoordinator (AdID),
    FOREIGN KEY (PlateNumber) REFERENCES TaxiManagement.Taxi (PlateNumber)
);

```