Heart Disease Risk Prediction - End-to-End MLOps Pipeline

Machine Learning Operations (AIMLCZG523) - Assignment 1

Contents

- 1. Introduction
- 2. Setup and installation
- 3. Data acquisition and preprocessing
- 4. Exploratory data analysis
- 5. Feature engineering and model development
- 6. Experiment tracking (MLflow)
- 7. Model packaging and reproducibility
- 8. CI/CD pipeline and automated testing
- 9. Containerisation and deployment
- 10. Monitoring and logging
- 11. Architecture
- 12. Challenges and lessons learned
- 13. Conclusion and future work
- References

Student name	
BITS ID	
Code repository	https://github.com/Tirumala-devi-damarla/heart-disease-mlops
Demo video	
API access	Local Kubernetes (minikube) - see Section 9.3

1. Introduction

The goal of this assignment is to build a machine learning classifier that predicts whether a patient has heart disease from routine clinical measurements, and to take it all the way to a monitored API running on Kubernetes using MLOps practices: reproducible data processing, experiment tracking, automated testing, CI/CD, containerisation, deployment and monitoring.

The dataset is the **UCI Heart Disease (Cleveland)** dataset with 303 patients and 13 input features (age, sex, chest pain type, resting blood pressure, cholesterol, fasting blood sugar, resting ECG, maximum heart rate,

exercise-induced angina, ST depression, ST slope, number of major vessels and thalassemia). The original target `num` (0-4) is converted into a binary label: 0 = no disease, 1 = disease present.

Tools used: Python 3.12, pandas, scikit-learn 1.5, MLflow 2.17, FastAPI, pytest, flake8, GitHub Actions, Docker, minikube (Kubernetes v1.37), NGINX Ingress, Prometheus and Grafana.

2. Setup and installation

```
git clone https://github.com/Tirumala-devi-damarla/heart-disease-mlops.git && cd heart-
        disease-mlops
python3.12 -m venv .venv && source .venv/bin/activate
pip install -r requirements.txt
bash scripts/download_data.sh            # data
PYTHONPATH=src python -m heart.eda       # EDA figures
PYTHONPATH=src python -m heart.train     # training + MLflow
pytest -v                                # unit tests
docker build -t heart-api:1.0.0 .        # serving image
```

Two requirement files are used: `requirements.txt` (everything for development, training and tests, all versions pinned) and `requirements-serve.txt` (only what the API needs), which keeps the Docker image smaller. The full command list for Docker, Kubernetes and monitoring is in `README.md`.

3. Data acquisition and preprocessing


`scripts/download_data.sh` calls `src/heart/data.py`, which:


1. downloads `processed.cleveland.data` from the UCI repository (skipped if already present),
2. reads it with the documented column names and treats `?` as missing,
3. removes duplicate rows (none in this file, but the check is there for future data),
4. fills missing values - only **`ca` (4 rows)** and **`thal` (2 rows)** are missing, so they are filled with the column mode instead of dropping 2% of an already small dataset,
5. converts `num` to the binary `target` and casts the code-like columns to integers,
6. validates the result (all columns present, no NaN, binary target, positive age/cholesterol) and saves `data/processed/heart_clean.csv`.

Validation raises an error instead of silently continuing, so bad data stops the CI pipeline. The model pipeline also contains its own imputers, so the API accepts requests where `ca` / `thal` are unknown.


4. Exploratory data analysis

All plots are produced by `src/heart/eda.py` (and shown in `notebooks/01_eda.ipynb`) using a consistent colour scheme: teal = no disease, coral = disease.






The classes are **reasonably balanced (164 / 139, i.e. 54% / 46%)**, so no resampling was needed; a stratified train/test split and stratified cross-validation keep the ratio in every fold.




Numeric features by target

Patients with disease reach a **lower maximum heart rate (`thalach`)** and have a **higher ST depression (`oldpeak`)**; they are also slightly older. Cholesterol and resting blood pressure look very similar for both groups.



Categorical features vs target



Key findings

- `cp = 4` (asymptomatic chest pain), `exang = 1`, `thal = 7` (reversible defect) and `ca > 0` are the strongest indicators of disease.
- `chol` and `fbs` are almost uncorrelated with the target.
- No pair of features is so strongly correlated ($|r| > 0.6$) that one has to be removed.
- Some outliers exist (e.g. cholesterol 564), but they are clinically possible, so they were kept.

5. Feature engineering and model development

5.1 Preprocessing pipeline

Everything that transforms the input is inside one scikit-learn `Pipeline` (`src/heart/features.py`), which is saved together with the model. This means the training code, the tests, the notebook and the API container all run exactly the same transformations, so there is no train/serve skew.

Step	Columns	Transformation
Feature engineering	`age`, `thalach`	new feature **`hr_pct_max = thalach / (220 − age)`**
Numeric	age, trestbps, chol, thalach, oldpeak, ca, hr_pct_max	median imputation + StandardScaler
Binary	sex, fbs, exang	most-frequent imputation
Categorical	cp, restecg, slope, thal	most-frequent imputation + One-Hot (unknown categories ignored)

The engineered feature `hr_pct_max` is the share of the age-predicted maximum heart rate that the patient reached in the exercise test. EDA showed that both age and `thalach` matter, and this ratio combines them into one clinically meaningful value. `ca` is kept as numeric because it is an ordered count (0-3).

5.2 Models and hyper-parameter tuning

Data is split 80/20 (stratified, `random_state=42`): 242 rows for training and 61 for a final hold-out test. Three model families were tuned with `GridSearchCV` using **5-fold stratified cross-validation** and **ROC-AUC** as the selection metric. ROC-AUC was used because it measures how well the model ranks patients by risk independently of a single threshold.


Model	Grid searched	Best parameters
Logistic Regression	C in {0.01, 0.1, 0.5, 1, 5}, penalty in {l1, l2} (10 candidates)	C = 0.5, l2
Random Forest	n_estimators {100, 300}, max_depth {3, 5, None}, min_samples_leaf {1, 4} (12)	100 trees, depth 5, leaf 4
Gradient Boosting	n_estimators {100, 200}, learning_rate {0.05, 0.1}, max_depth {2, 3} (8)	100, 0.05, depth 2


The grids are deliberately small: with only 242 training rows, a large search would mostly fit the noise of the CV folds.

5.3 Results


The best estimator from each search was re-evaluated with 5-fold CV on the training set (accuracy, precision, recall, F1, ROC-AUC) and once on the hold-out test set.


Metric	Logistic Regression	Random Forest	Gradient Boosting
CV accuracy	**0.851**	0.818	0.818
CV precision	**0.887**	0.844	0.827
CV recall	**0.783**	0.755	0.774
CV F1	**0.828**	0.789	0.796
CV ROC-AUC	**0.907 ± 0.020**	0.897 ± 0.028	0.874 ± 0.025
Test accuracy	0.869	0.869	**0.902**
Test recall	0.929	0.929	0.929
Test ROC-AUC	**0.960**	0.958	0.959





Model selection. The model is chosen on **mean CV ROC-AUC**, not on the test score, so the test set stays an unbiased final check. **Logistic Regression** wins on every CV metric and also has the lowest variance across folds. Gradient Boosting has a slightly higher test accuracy, but the test set has only 61 patients (one patient = 1.6%), so this difference is not meaningful compared to the CV results. Logistic Regression also gives well-behaved probabilities and coefficients that a clinician can interpret, which matters for a medical use case. On the test set it finds 26 of 28 disease cases (recall 0.93), which is the most important error type to minimise in screening.






Both models agree with the EDA: `ca`, `thal`, `cp` and `oldpeak` are the most important inputs, and the engineered `hr_pct_max` ranks among the top features for the Random Forest.


6. Experiment tracking (MLflow)

`src/heart/train.py` logs everything to a local MLflow tracking store (`./mlruns`):


- **one parent run per model family** with the best parameters, dataset sizes, all CV metrics (mean and std), all test metrics and the tuning time,
- **one nested child run for every grid candidate** (30 in total) with its parameters and CV ROC-AUC, so the whole tuning process can be compared in the UI,
- **artifacts:** confusion matrix, ROC curve, precision-recall curve, feature importance plot and the full CV results table (CSV),
- **the model** in MLflow format with an input example and signature,
- **tags** `model_family`, `stage`, and `selected_for_serving=true` on the winning run.



MLflow experiment with the parent runs (expandable to nested candidates)



MLflow comparison of the three model families



Selected run: parameters, metrics and tags

Summary: 2 complete training sessions were run (66 runs including nested ones). The results were identical in both, which confirms that the pipeline is reproducible (fixed random seeds, pinned library versions).

7. Model packaging and reproducibility

- **Model formats:** the winning pipeline is saved as `models/model.joblib` (used by the API) and as an MLflow model in `models/mlflow_model/` (contains `MLmodel`, `conda.yaml`, `requirements.txt`, input example and signature). `models/metadata.json` stores the model name, MLflow run id, best parameters, metrics and the feature list.
- **Preprocessing is part of the model**, so a client only sends raw patient values.
- **Pinned dependencies** in `requirements.txt` / `requirements-serve.txt`.
- **Fixed seeds** (`RANDOM_STATE = 42`) for the split, CV folds and models.
- **Single source of configuration** (`src/heart/config.py`) for paths and column lists.
- `scripts/predict.py` and `notebooks/03_inference.ipynb` show inference from the saved file.

8. CI/CD pipeline and automated testing

8.1 Unit tests

The `tests/` folder has **30 pytest tests**:

File	What is tested
`test_data.py` (9)	duplicate removal, missing value filling, binary target, dtypes, validation errors, ? parsing
`test_features.py` (5)	`hr_pct_max` values, no NaN after preprocessing, output width, unseen categories, feature names
`test_model.py` (5)	both model types train and predict valid probabilities, metrics, joblib round-trip, the full `train.main()` with MLflow in a temp folder
`test_api.py` (11)	`/health`, `/predict` (incl. optional fields), invalid inputs return 422, batch endpoint, `/metrics`, 503 when no model is loaded

The tests use a small synthetic dataset, so they run in about 15 seconds and do not touch the real model files.



flake8 and pytest results


8.2 GitHub Actions workflow

`.github/workflows/ci.yml` runs on every push and pull request with four dependent jobs:


1. **Lint** - `flake8` over `src`, `api`, `tests`, `scripts`; report uploaded as an artifact.
2. **Unit tests** - `pytest -v --junitxml`; JUnit XML and log uploaded.
3. **Data + training** - downloads the dataset, trains all models, applies a **quality gate** (job fails if CV ROC-AUC < 0.80) and uploads the model, plots, training log and `mlruns/`.
4. **Docker** - builds the image with the freshly trained model, starts the container, waits for `/health`, calls `/predict` and checks the response; container logs are uploaded.

Because every job `needs` the previous one, a lint error, a failing test or a bad model stops the pipeline with a red build and clear logs (`tee` + `exit ${PIPESTATUS[0]}` keeps the real exit code while still saving the log).

The first run on GitHub (run #1, triggered by the initial push) passed all four jobs in about 3 minutes and produced 5 artifacts. On the fresh Ubuntu runner the selected model reached exactly the same CV ROC-AUC (0.9075) as locally, which is another check that the pipeline is reproducible.



GitHub Actions run #1 - all four jobs passed



Steps of the training job



CI logs (training, quality gate, Docker smoke test) and the uploaded artifacts

9. Containerisation and deployment

9.1 Docker

The `Dockerfile` uses `python:3.12-slim`, installs only `requirements-serve.txt`, copies `src/`, `api/` and the model, runs as a **non-root user (UID 1000)**, has a `HEALTHCHECK` on `/health` and starts `uvicorn` on port 8000.

The FastAPI service (`api/main.py`) exposes:

Endpoint	Purpose
`POST /predict`	JSON patient record -> `prediction`, `label`, `confidence`, `probability_disease`, `risk_level`, `model_version`
`POST /predict/batch`	up to 100 patients
`GET /health`	liveness/readiness probe (503 if the model is not loaded)
`GET /model-info`	contents of `metadata.json`
`GET /metrics`	Prometheus metrics
`GET /docs`	Swagger UI

Input validation is done with Pydantic (value ranges and allowed category codes from the UCI documentation), so invalid requests get a clear HTTP 422 error. `confidence` is the probability of the predicted class.

```
docker build

$ docker build -t heart-api:1.0.0 .
#1 [internal] load build definition from Dockerfile
#2 [internal] load metadata for docker.io/library/python:3.12-slim
#3 [auth] library/python:pull token for registry-1.docker.io
#2 [internal] load metadata for docker.io/library/python:3.12-slim
#2 DONE 1.5s
#4 [internal] load .dockerignore
#5 [1/8] FROM docker.io/library/python:3.12-slim@sha256:a6e34c598f2467ed0e9a8d349809fcd8b5c603269512df273a0bb1784edc11b1
#6 [2/8] WORKDIR /app
#7 [internal] load build context
#8 [3/8] COPY requirements-serve.txt .
#9 [4/8] RUN pip install -r requirements-serve.txt
#9 DONE 36.0s
#10 [5/8] COPY src/ src/
#10 DONE 0.1s
#11 [6/8] COPY api/ api/
#12 [7/8] COPY models/model.joblib models/metadata.json models/
#13 [8/8] RUN useradd --create-home --uid 1000 appuser && chown -R appuser /app
#13 DONE 0.2s
#14 exporting to image
#14 exporting layers
#14 exporting layers 10.6s done
#14 exporting manifest sha256:caae87ad76fd6e6873e1850f286e78033b9dbf3758a3a11a6cd7c37660ad3231 done
#14 exporting config sha256:7ccaf16566a053a70670edfa6d0a1e3e934e3bd4d3023777c790075015fa1c84 done
#14 exporting attestation manifest sha256:23cbf4c57b8a04cda3823c0bc8ea83fb644eaf8c0ec19addd3a969789cff9fba done
#14 exporting manifest list sha256:8b6dfbc929fe50b17fe689ba65e72472f3f135ea9a70c15ee3dbfc59d598b25d done
#14 naming to docker.io/library/heart-api:1.0.0 done
#14 DONE 13.6s

$ docker images heart-api
IMAGE             ID             DISK USAGE   CONTENT SIZE   EXTRA
heart-api:1.0.0   8b6dfbc929fe        704MB          151MB
```

Docker image build

```
docker run + curl /predict

$ docker build -t heart-api:1.0.0 .   (build OK)
$ docker run -d --name heart-api -p 8080:8000 heart-api:1.0.0

$ docker ps --filter name=heart-api
NAMES       IMAGE             STATUS                    PORTS
heart-api   heart-api:1.0.0   Up 6 seconds (healthy)   0.0.0.0:8080->8000/tcp, [::]:8080->8000/tcp


$ curl localhost:8080/health
{"status":"ok","model_version":"logistic_regression-c800af5b"}

$ curl -X POST localhost:8080/predict -H "Content-Type: application/json" -d @sample_request.json
{"prediction":1,"label":"heart
disease","confidence":0.9934,"probability_disease":0.9934,"risk_level":"high","model_version":"logistic_regression-c800af5b"}

$ docker logs heart-api
/usr/local/lib/python3.12/site-packages/pydantic/_internal/_fields.py:132: UserWarning: Field "model_version" in PredictionResponse has conflict with
protected namespace "model_".

You may be able to resolve this warning by setting `model_config['protected_namespaces'] = ()`.
  warnings.warn(
INFO:     Started server process [1]
INFO:     Waiting for application startup.
{"ts": "2026-10-19T18:24:05", "level": "INFO", "logger": "heart_api", "msg": "Model loaded from /app/models/model.joblib (logistic_regression)"}
INFO:     Application startup complete.
INFO:     Uvicorn running on http://0.0.0.0:8000 (Press CTRL+C to quit)
{"ts": "2026-10-19T18:24:08", "level": "INFO", "logger": "heart_api", "msg": "request", "request_id": "411413170055", "method": "GET", "path":
"/health", "status": 200, "latency_ms": 10.26, "client": "127.0.0.1"}
{"ts": "2026-10-19T18:24:09", "level": "INFO", "logger": "heart_api", "msg": "request", "request_id": "b75493ce8dfd", "method": "GET", "path":
"/health", "status": 200, "latency_ms": 0.64, "client": "192.168.65.1"}
{"ts": "2026-10-19T18:24:09", "level": "INFO", "logger": "heart_api", "msg": "prediction", "input": {"age": 58.0, "sex": 1, "cp": 4, "trestbps":
140.0, "chol": 260.0, "fbs": 0, "restecg": 2, "thalach": 130.0, "exang": 1, "oldpeak": 2.4, "slope": 2, "ca": 2, "thal": 7}, "output": {"prediction":
1, "label": "heart disease", "confidence": 0.9934, "probability_disease": 0.9934, "risk_level": "high", "model_version":
"logistic_regression-c800af5b"}}
{"ts": "2026-10-19T18:24:09", "level": "INFO", "logger": "heart_api", "msg": "request", "request_id": "d0877ee5f34b", "method": "POST", "path":
"/predict", "status": 200, "latency_ms": 38.41, "client": "192.168.65.1"}
```

Container running locally and answering /predict




Swagger UI of the API

9.2 Kubernetes manifests (`k8s/`)


File	Resource
`00-namespace.yaml`	namespace `heart-mlops`
`01-configmap.yaml`	`LOG_LEVEL`, `MODEL_PATH`
`02-deployment.yaml`	2 replicas, rolling update (maxUnavailable 0), readiness + liveness probes on `/health`, CPU/memory requests and limits, `runAsNonRoot`, Prometheus scrape annotations
`03-service.yaml`	`LoadBalancer` service on port 80
`04-ingress.yaml`	NGINX Ingress, host `heart-api.local`
`05-hpa.yaml`	HorizontalPodAutoscaler, 2-4 replicas at 70% CPU

9.3 Deployment on minikube and verification

The image is loaded into the cluster with `minikube image load` and deployed with `kubectl apply -f k8s/`. The endpoints were verified through **both** the LoadBalancer service (`minikube service ... --url`) and the NGINX Ingress (port-forward of the ingress controller with `Host: heart-api.local`):



Deployment and endpoint verification



Running resources, HPA reading CPU, pod resource usage

Access instructions (local): run `minikube -p heart-mlops tunnel` in a separate terminal; the LoadBalancer then gets `127.0.0.1` as external IP and the API is reachable at `http://127.0.0.1/predict`. Without the tunnel, use `minikube -p heart-mlops service heart-api -n heart-mlops --url`.


10. Monitoring and logging

Logging. A FastAPI middleware writes one JSON line per request (request id, method, path, status, latency in ms, client IP) and the `/predict` handler logs the input and output of every prediction. A request id is returned in the `x-request-id` header, so a client error can be matched to the log line. Logs are written to stdout and read with `kubectl logs`.

Metrics. `prometheus-client` exposes:

- `api_requests_total{method, endpoint, status}` - request counter,
- `api_request_latency_seconds` - latency histogram per endpoint,
- `model_predictions_total{label}` - predictions per class,
- `model_probability_disease` - histogram of predicted probabilities (useful to spot drift),
- `model_loaded` - 1 when the model is loaded.

Prometheus runs inside the cluster and discovers the API pods automatically through the Kubernetes API (role-based access limited to the namespace) using the `prometheus.io/*` pod annotations, so new replicas created by the HPA are scraped without changing the config. **Grafana** is provisioned from code with the Prometheus datasource and a dashboard JSON (`monitoring/grafana/dashboards/heart-api.json`). Traffic was generated with `scripts/generate_traffic.py` (≈5% deliberately invalid requests to show errors).




Prometheus discovered both API pods



Grafana dashboard: totals, request rate, latency p50/p95, predictions by class, status codes and probability distribution

11. Architecture



End-to-end architecture

The system has three parts: (1) data processing, EDA and training with MLflow tracking, (2) a GitHub Actions pipeline that lints, tests, retrains with a quality gate and builds/tests the Docker image, and (3) serving on Kubernetes: Ingress -> Service -> 2-4 API pods, scraped by Prometheus and visualised in Grafana.

12. Challenges and lessons learned

- **SSL error when downloading the data** - the python.org build of Python on macOS has no CA certificates. Fixed by using the `certifi` bundle in the download code instead of changing system settings.
- **Pods stuck in `CreateContainerConfigError`** - the deployment requires `runAsNonRoot`, but the image used a *named* user (`appuser`), which Kubernetes cannot verify. Fixed by giving the user a fixed UID (1000) in the Dockerfile and setting `runAsUser: 1000`.
- **Existing minikube cluster would not start** (API server never came up) and ports 8000/9090 were already in use - a separate minikube profile (`heart-mlops`) and different host ports were used instead.
- **Re-running training from a notebook** re-exported the model with a new run id, which no longer matched the deployed image. The training notebook now reads results from MLflow, and training only runs through the script / CI. Lesson: there should be exactly one place that produces the served model.
- **HPA showed `<unknown>` CPU** until the `metrics-server` addon was enabled.

13. Conclusion and future work

A complete, reproducible pipeline was built: the selected Logistic Regression model reaches **0.907 CV ROC-AUC (0.960 on the hold-out set)** and is served by a validated, monitored FastAPI service on Kubernetes,

with every change checked by a four-stage CI pipeline.

Possible improvements: use the MLflow Model Registry with a database backend for model stage transitions; push images to a container registry and add a CD job that deploys to a cloud cluster (GKE/EKS); add data-drift detection on the logged inputs (e.g. Evidently); calibrate the decision threshold for higher recall; and train on the other UCI sites (Hungary, Switzerland, VA) to test generalisation.

References

1. Janosi, A., Steinbrunn, W., Pfisterer, M., Detrano, R. (1989). *Heart Disease* [Dataset]. UCI Machine Learning Repository. https://doi.org/10.24432/C52P4X
2. scikit-learn documentation - https://scikit-learn.org
3. MLflow documentation - https://mlflow.org/docs/latest
4. FastAPI documentation - https://fastapi.tiangolo.com
5. Kubernetes documentation - https://kubernetes.io/docs
6. Prometheus and Grafana documentation - https://prometheus.io/docs, https://grafana.com/docs