

Design

1. Proposed Data Model

```
{

  "tasks": [

    {

      "id": "bg-20260313-001",

      "title": "Projects page refactor",

      "ownerSession": "agent:main:telegram:direct:...",

      "taskType": "delegated-process",

      "startedAt": "2026-03-13T21:00:00Z",

      "checkinEveryMinutes": 3,

      "lastCheckinAt": null,

      "lastObservedStatus": "running",

      "notifyTarget": {

        "chat": "telegram:8625301893"
```

```
    },  
  
    "process": {  
  
        "kind": "exec",  
  
        "sessionId": "oceanic-sage"  
  
    },  
  
    "resolution": null  
  
}  
  
]  
  
}
```

2. Watchdog Decision Logic

1. Load active tasks.
2. For each task, inspect current state from the best available source:
 - exec/process status
 - OpenClaw session/subagent status
 - known completion markers
3. If completed or failed, send a final update and mark resolved.
4. If still running and overdue for check-in, send a progress update and refresh `lastCheckinAt`.
5. If observation is inconclusive, send a degraded-status update only if overdue.

3. Notification Rules

- Completion: immediate

- Failure/blocker: immediate
- Running/overdue: every configured interval, default 2–3 minutes
- No duplicate updates if status is unchanged and interval has not elapsed

4. Proof Strategy by Design

- Registry file proves tracked tasks exist.
- Scheduler logs prove checks actually executed.
- Message/update logs prove follow-up notifications were sent.
- State transitions prove completion/failure handling.