

1. Functional Requirements

I D	Requirement
F R - 1	The system shall provide a local Node.js CLI called agent-follow-up as the Phase 1 registration interface.
F R - 2	The system shall store task state in SQLite under a dedicated operational state path, independent of OpenClaw memory artifacts.
F R - 3	The system shall use OpenClaw native cron as the Phase 1 scheduler.
F R - 4	The system shall support these Phase 1 task classes only: process-backed tasks with owned marker files, and manual/marker-backed tasks.
F R - 5	The system shall use a deterministic watchdog and shall not require an LLM for routine reminder decisions.
F R - 6	The system shall emit notifications using a concrete OpenClaw-native message command.
F R -	The system shall suppress duplicate notifications using explicit notification metadata.

7

F

R

The system shall use a configurable check-in interval, with a target default of 2–3 minutes when feasible.

-

8

F

R

The system shall classify tasks using explicit state definitions: running, completed, failed, stale, unknown.

-

9

F

R

The system shall transition a task to unknown after the configured unknown threshold; the default Phase 1 threshold shall be 2 watchdog cycles.

-

1

0

2. Non-Functional Requirements

I

Requirement

D

N

F

R

The system shall not depend on a human manually asking for updates.

-

1

N

F

R

The system shall distinguish observed, inferred, and unverified states.

-

2

N

The system shall emit honest degraded-state updates rather than false

F

R

- success.

3

N

F

R

The system shall operate within the existing Ubuntu/OpenClaw environment.

-

4

N

F

R

The system shall minimize token/compute overhead by keeping Phase 1 evaluation deterministic and non-LLM.

-

5

3. Registration Contract

Phase 1 contract direction:

```
agent-follow-up register --id <id> --title <title> --interval 3
--target telegram:8625301893 --observable-type marker --
observable-id /path/to/marker.json
```