

```
[janikowc@delmar cs4280]$ cat P0_test3.fs25s1
adam 123 adam 35 susan daniel adam 123 35 35 35 susan susan
adam adam 12 23 x x x x x x y y y y y y
```

```
[janikowc@delmar cs4280]$ P0 P0_test3
```

```
[janikowc@delmar cs4280]$ cat P0_test3.preorder
```

```
5: adam 35
  2: 123
    1: daniel 12 23
      3: susan
        7: x
          6: y
```

Note that preorder traversal maps to this tree. Deeper indentations are deeper levels. Same indentations are siblings, the higher printed the more left in the tree. Each node prints its data frequency followed by data of this frequency.

```
[janikowc@delmar cs4280]$ cat P0_test3.inorder
```

```
1: daniel 12 23
2: 123
3: susan
5: adam 35
6: y
7: x
```

```
[janikowc@delmar cs4280]$ cat P0_test3.postorder
```

```
1: daniel 12 23
3: susan
2: 123
6: y
7: x
5: adam 35
```

Note that another testing invocation would be

```
[janikowc@delmar cs4280] P0 <P0_test3.fs25s1
```

resulting in the same outputs except basename would be "out"

Pass 1: create a container of data from the input file along with frequencies, preserving the order of appearance

adam	5
123	2
35	5
susan	3
daniel	1
12	1
23	1
x	7
y	6

Pass 2: over the original file, looking up frequencies, or over the container, creating BST

