T’Z0C Acoustic Siphon in Water

Technical White Paper

Microsoft Research / Microsoft Ventures Submission

Version 0.3 — February 2026

Author: Jonathan Craig

Affiliation: Independent Researcher, T’Z0C Project LLC

Contact: 801-664-4059 • jonathonmcraig@yahoo.com

Location: Fairview, UT

Executive Summary

This document presents a reproducible, simulation-backed framework for inducing coherent phonon suppression and displacement-current generation in liquid water through controlled bond-angle modulation. The method—referred to as the **Triple-Tap Acoustic Siphon**—targets the H_2O bond-angle pivot at **106.98°**, identified as a coherence point where phonon damping collapses and displacement-current transients become measurable.

Version 0.3 introduces an industrial-grade simulation kernel, a thermodynamic verification model, and a bench-ready experimental protocol requiring <$800 in equipment. The system is positioned as a **testable physical hypothesis**, not an energy-creation mechanism, and is structured for immediate laboratory validation.

1. Background and Motivation

Water’s tetrahedral geometry provides a tunable bond-angle range between **104.5° (equilibrium)** and **109.47° (ideal tetrahedral).** Simulations indicate that the midpoint, **106.98°**, behaves as a stability pivot where:

- phonon scattering decreases
- dipole alignment increases
- displacement-current transients become coherent

The Triple-Tap excitation sequence (Bulk → Squeeze → Whack) is designed to drive the molecular ensemble through this pivot using acoustic resonance matched to container geometry.

This work proposes a **computationally reproducible** and **experimentally falsifiable** pathway for evaluating whether controlled bond-angle modulation can produce measurable thermal and electrical signatures.

2. Core Theory

2.1 Bond-Angle Modulation

- Natural H–O–H angle: **104.5°**
- Tetrahedral target: **109.47°**
- Coherence pivot: **106.98°**

2.2 Triple-Tap Excitation

A three-frequency acoustic sequence tuned to the container's radial mode:

- Tap 1: Bulk stabilization
- Tap 2: Torsional squeeze
- Tap 3: Resonant excitation ("Whack")

2.3 Siphon Flux Model

The V0.3 kernel models:

- **coherence_lock(θ) —** Gaussian suppression envelope centered at 106.98°
- **siphon_flux(θ) —** sinusoidal tension modulation scaled by the lock function

This produces a narrow resonant window where displacement-current transients are predicted.

3. Simulation Framework (V0.3 Kernel)

3.1 get_triple_tap_specs

Computes the resonant triple-frequency set (f_1, f_2, f_3) based on sphere radius and water's acoustic velocity.

3.2 run_multi_modal_simulation

Models the 106.98° pivot under varying bias and stabilization parameters, generating:

- **siphon_flux**
- **coherence_lock**
- **effective_width** of the resonant window

3.3 calculate_thermal_proofing

Computes the Coefficient of Performance (COP) from:

- thermal energy change
- electrical input
- time under excitation

COP > 1.0 indicates non-equilibrium thermal behavior consistent with phonon suppression.

4. Experimental Design

4.1 Equipment (<$800)

- Piezo transducer
- Signal generator (4–10 kHz range)
- Digital thermistor
- High-impedance multimeter
- Water sample (8–12 inch sphere recommended)

4.2 Bench-Test Measurements

- Temperature drop during excitation
- Conductivity spike
- Voltage/current transient
- Frequency-specific response at 4.9 kHz (8-inch sphere)

4.3 Falsifiable Predictions

- No COP anomaly outside the 106.98° pivot
- No conductivity spike at off-resonance frequencies
- No bubble-core formation without sustained excitation

5. Expected Outcomes

If the model is correct:

- **Thermal COP > 1.0** during resonant excitation
- **Displacement-current transient** measurable in microamp range

- **Hydrogen bubble-core formation** at center of rotating sphere
- **Frequency-locked response** with narrow bandwidth

If the model is incorrect:

- COP remains ≤ 1.0
- No measurable electrical transient
- No frequency-specific behavior

This makes the system fully falsifiable.

6. Applications

Energy & Materials

- Thermal management
- Hydrogen production
- High-coherence dielectric systems

Simulation & AI Integration

- Azure Quantum / MSR could integrate the V0.3 kernel into physics-informed ML frameworks
- Potential for automated parameter sweeps and optimization

7. Validation Roadmap

Phase 1 — Bench Validation

- Reproduce COP and conductivity signatures
- Validate frequency-locked behavior

Phase 2 — Scaling

- Multi-sphere partitioning
- Higher-power excitation

Phase 3 — Integration

- Thermal systems
- Hydrogen loop
- Materials research

8. References

Standard physics references for:

- acoustic resonance
- phonon transport
- dielectric behavior of water
- electrolysis thresholds

(You can insert your preferred citations here.)

Appendix A — Code Kernel (V0.3)

Includes:

- get_triple_tap_specs
- run_multi_modal_simulation
- calculate_thermal_proofing