

Quality Assurance

Security Testing & Software Quality Assurance

smoltcp v0.12.0 — Open-Source Embedded Network Stack

Agenda

- 1 Introduction & Scope
- 2 Mutation Adequacy Testing
- 3 Input Space Partitioning
- 4 Security Fuzzing
- 5 Conformance Testing

- 6 Performance Testing
- 7 White-Box Coverage
- 8 Software Safety
- 9 Quality Dashboard
- 10 Conclusions

Introduction

What is smoltcp?

A standalone, event-driven TCP/IP stack written in **Rust**, targeting embedded, bare-metal, and resource-constrained systems.

- Rust's memory-safety eliminates buffer overflows, use-after-free, and double-free vulnerabilities
- Logic errors, spec deviations, and performance regressions remain possible
- Our assessment spans **8 quality dimensions**

Platforms: Windows 10 (MSVC) | Ubuntu 24.04.2 LTS (GNU/LLVM)

| Scope & Target Modules

Four highest-complexity modules:

- `storage/assembler.rs`
TCP segment reassembly
- `wire/ipv4.rs`
IPv4 header parsing
- `wire/udp.rs`
UDP datagram handling
- `wire/tcp.rs`
TCP segment parsing & emission

Eight quality dimensions:

1. Mutation adequacy
2. Test suite improvement
3. Input space partitioning
4. Security fuzzing
5. RFC conformance
6. Performance benchmarking
7. White-box coverage
8. Software safety


Custom Python-based mutation engine with 333 first-order mutants

Mutation Testing — Operator Distribution

7 mutation operator classes:

- Constant replacement (98)
- Arithmetic operator (52)
- Relational operator (48)
- Boolean connector (36)
- Bitwise operator (44)
- Assignment operator (28)
- Shift operator (27)

333 total first-order mutants



figures/fig3_operator_distribution.

Mutation Testing — Kill Ratios

figures/fig1_mutation_kill_ratio.png

figures/fig2_mutation_pie.png

Module	Total	Killed	Survived	Kill %
assembler.rs	85	76	9	89.41%
ipv4.rs	88	54	34	61.36%
udp.rs	40	23	17	57.50%
tcp.rs	120	76	44	63.33%
Overall	333	229	104	68.77%

Equivalent Mutant Analysis

- Manual review of **top 5 surviving mutants** (lowest-index survivors)
- 2 classified as **equivalent** (no observable behavior change):
 - **M0004**: Debug-only assertion in `remove_front()`
 - **M0024**: Formatting-only display branch in `Contig`
- 3 classified as **killable** — reveal genuine test gaps:
 - Missing boundary-condition tests for hole sizing
 - Exact-boundary segment assembly not exercised

Adjusted Mutation Adequacy

$$\text{Adequacy} = \frac{229}{333 - 2} = \frac{229}{331} = \mathbf{69.18\%}$$

| Input Space Partitioning

Target: UDP parsing (wire/udp.rs)


6 input dimensions:

1. Buffer length: {0, 7, 8, 12}
2. Length field: {0, 4, 8, 12, 20}
3. Destination port: {0, 53}
4. Checksum mode: {Valid, Zero, Invalid}
5. IP family: {IPv4, IPv6}
6. RX checking: {true, false}

$4 \times 5 \times 2 \times 3 \times 2 \times 2 = \mathbf{480}$ test frames

100% pass rate on both platforms

+216 IPv4 combinatorial test cases (all passing)



figures/fig7_partition_heatmap.png

Input Space Partitioning — Key Findings

Successful parsing requires **all** of:

- Buffer length ≥ 8 bytes
- Length field ≥ 8 and $\leq$ buffer length
- Non-zero destination port
- Valid or zero checksum (when checking enabled)

Notable finding

smoltcp accepts checksum=0 for UDP over IPv6 — a documented deviation from strict RFC 2460 expectations.

Security Fuzzing

Tool: cargo-fuzz + LLVM libFuzzer

5 fuzz targets:

- packet_parser
- tcp_headers
- dhcp_header
- ieee802154_header
- sixlowpan_packet

Campaign: 180s per target

Executions: ~380K

Edges discovered: 759

✓ **Zero crash artifacts**



figures/fig9_fuzzing_coverage.png

Fuzzing — Platform Portability Issue

Windows Fuzzing Blocked

All fuzzing attempts failed on Windows due to missing ASAN runtime DLLs and unresolved sanitizer-coverage symbols (MSVC/libFuzzer incompatibility).

Why zero crashes?

- Rust's bounds checking prevents buffer overflows
- No null pointer dereferences possible
- Safe integer arithmetic by default
- These are the exact vulnerability classes fuzzing typically finds in C/C++ stacks

RFC Conformance Testing

Case	RFC	Expected	Observed
IPv4 bad version	791	Reject	Reject
IPv4 IHL < 20B	791	Reject	Accept
IPv4 total < header	791	Reject	Reject
IPv4 bad checksum	791	Reject	Reject
IPv4 cksum disabled	config	Accept	Accept
UDP len < 8	768	Reject	Reject
UDP dst port = 0	smoltcp	Reject	Reject
UDP/IPv4 cksum = 0	768	Accept	Accept
UDP/IPv6 cksum = 0	2460	Reject	Accept

△ **Two specification deviations** identified (highlighted in orange)

RFC Deviations — Details

1. IPv4 header length < 20 bytes accepted

When IHL encodes a header < 20 bytes (RFC minimum), smoltcp accepts if the buffer is long enough.

- Deliberate design choice for performance
- Risk: crafted packets could bypass validation

2. UDP over IPv6 accepts checksum $= 0$

RFC 2460 mandates non-zero checksums for UDP/IPv6, but smoltcp accepts zero-checksum packets.

- Risk: corrupted datagrams may go undetected on IPv6 networks

Performance Testing

Loopback throughput benchmark

- 128 MB data through internal stack
- Custom in-memory loopback harness
- 5 trial runs per platform

Results

- Ubuntu: **52.15 Gbps** avg
- Windows: **17.11 Gbps** avg
- **~3× difference**

figures/fig4_performance_throughput

White-Box Test Data Adequacy

Tool: cargo-llvm-cov v0.8.5

Key metrics:

- assembler.rs: **98.28%** regions
- Protocol wire modules: 90+% parsing
- tcp.rs: 72.58% (lowest)


Enhanced suites achieved:

- IPv4 combinatorial: **98.53%**
- Microbenchmark: **98.76%**



figures/fig5_whitebox_coverage.png

Enhanced Coverage with LCOV Artifacts



figures/fig11_enhanced_coverage.png

- Only **4 and 2 missed regions** respectively
- Remaining gaps are small but made **explicit and actionable**
- Provides concrete roadmap for future test additions


Software Safety

Panic Safety Testing

- Zero-length buffers
- Truncated headers
- Maximum-value fields
- All tests passed on both platforms


Unsafe Code Inventory

- **18 unsafe occurrences** across 4 files
- All confined to FFI / PHY layer code
- Zero unsafe in core protocol parsing



figures/fig8_unsafe_inventory.png

Quality Assessment Dashboard



figures/fig12_test_dashboard.png

- Mutation adequacy (69.18%) — primary area for improvement
- All other dimensions achieved **80%+ pass rates**
- Core parsing and protocol handling is **robust**

Cross-Platform Portability

Dual-platform execution

8 of 9 test suites executed successfully on both Windows and Ubuntu.

- **Sole exception:** Fuzzing blocked on Windows (MSVC/libFuzzer issue)
- Performance harness used custom in-memory loopback for fair comparison
- Results underscore importance of multi-toolchain testing



