

Week 5

Exercise 35

../35/flexcpp/lexer

```
1 %%
2 [a-zA-Z]+  return matched()[0];
3 [ \t\n]    // Ignored;
```

../35/flexcpp/Scanner.h

```
1 // Generated by Flexc++ V2.06.02 on Fri, 08 Mar 2019 01:22:12 +0100
2
3 #ifndef Scanner_H_INCLUDED_
4 #define Scanner_H_INCLUDED_
5
6 // $insert baseclass_h
7 #include "Scannerbase.h"
8
9
10 // $insert classHead
11 class Scanner: public ScannerBase
12 {
13     public:
14         explicit Scanner(std::istream &in = std::cin,
15                         std::ostream &out = std::cout);
16
17         Scanner(std::string const &infile, std::string const &outfile);
18
19         // $insert lexFunctionDecl
20         int lex();
21
22     private:
23         int lex__();
24         int executeAction__(size_t ruleNr);
25
26         void print();
27         void preCode();           // re-implement this function for code that must
28                                   // be exec'ed before the patternmatching starts
29
30         void postCode(PostEnum__ type);
31                                   // re-implement this function for code that must
32                                   // be exec'ed after the rules's actions.
33 };
34
35 // $insert scannerConstructors
36 inline Scanner::Scanner(std::istream &in, std::ostream &out)
37 :
38     ScannerBase(in, out)
39 {}
40
41 inline Scanner::Scanner(std::string const &infile, std::string const &outfile)
42 :
43     ScannerBase(infile, outfile)
44 {}
45
46 // $insert inlineLexFunction
47 inline int Scanner::lex()
48 {
49     return lex__();
50 }
51
52 inline void Scanner::preCode()
53 {
```

```
54     // optionally replace by your own code
55 }
56
57 inline void Scanner::postCode(PostEnum__ type)
58 {
59     // optionally replace by your own code
60 }
61
62 inline void Scanner::print()
63 {
64     print__();
65 }
66
67
68 #endif // Scanner_H_INCLUDED_
```

../35/main.cc

```
1 #include "main.ih"
2
3 int main(int argc, char **argv)
4 try
5 {
6     multiset<string> words = (argc != 1) ? processfiles(argc, argv) : processcin();
7     // Multiset to order input
8
9     for (auto el: words) // Print output
10         cout << el << '\n';
11 }
12 catch (string &message)
13 {
14     cout << message;
15 }
```

../35/fileexists.cc

```
1 #include "main.ih"
2
3 bool file_exists(const char *fileName)
4 {
5     ifstream infile(fileName);
6     return infile.good();
7 }
```

../35/processcin.cc

```
1 #include "main.ih"
2
3 multiset<string> processcin()
4 {
5     multiset<string> words;
6
7     Scanner flatbed; // Default constructor (cin, cout)
8
9     while (flatbed.lex())
10         words.insert(flatbed.matched());
11
12     return words;
13 }
```

../35/processfiles.cc

```
1 #include "main.ih"
2
```

```
3 multiset<string> processfiles(int argc, char **argv)
4 {
5     multiset<string> words;
6
7     for (int idx = 1; idx != argc; ++idx) // Loop through files
8     {
9         if (!file_exists(argv[idx]))      // Check if input file(s) exist
10        {
11            string message = argv[idx];
12            message += " is not a valid file.";
13            throw message;
14        }
15
16        Scanner flatbed(argv[idx], "/dev/null"); // Scanner from filename
17        // While not elegant, writing the output to /dev/null is the simplest
18        // method I could think of, considering the fact that it should,
19        // indeed, not be stored. Another option is to create a custom constructor,
20        // or associating a filebuf with an istream and passing that to a Scanner
21        // constructor (using cout as the other argument, since it will not output
22        // anything). However, this seemed both the cleanest and clearest option.
23
24        while (flatbed.lex())                // While input
25        {
26            words.insert(flatbed.matched()); // Insert next match into multiset
27        }
28    }
29    return words;
30 }
```

Exercise 36

../36/flexcpp/lexer

```
1 operators      [\/\+\-\*\%\=\!\&\|\~\^\<\>]
2 %%
3
4 [ \t\n]        // Ignored
5 ([a-zA-Z]{2,}) return WORD;
6 [a-zA-Z]       return matched()[0];
7 [0-9]+\.[0-9]+ return FLOAT;
8 [0-9]+         return INT;
9 \".*          return STRING;
10 {operators}+   return OP;
```

../36/flexcpp/Scanner.h

```
1 // Generated by Flexc++ V2.06.02 on Sat, 09 Mar 2019 02:25:30 +0100
2
3 #ifndef Scanner_H_INCLUDED_
4 #define Scanner_H_INCLUDED_
5
6 enum Tokens
7 {
8     INT = 256,
9     FLOAT,
10    STRING,
11    WORD,
12    OP
13 };
14
15 // $insert baseclass_h
16 #include "Scannerbase.h"
17
18
19 // $insert classHead
20 class Scanner: public ScannerBase
21 {
22     public:
23         explicit Scanner(std::istream &in = std::cin,
24                         std::ostream &out = std::cout);
25
26         Scanner(std::string const &infile, std::string const &outfile);
27
28         // $insert lexFunctionDecl
29         int lex();
30
31     private:
32         int lex__();
33         int executeAction__(size_t ruleNr);
34
35         void print();
36         void preCode();           // re-implement this function for code that must
37                                   // be exec'ed before the patternmatching starts
38
39         void postCode(PostEnum__ type);
40                                   // re-implement this function for code that must
41                                   // be exec'ed after the rules's actions.
42 };
43
44 // $insert scannerConstructors
45 inline Scanner::Scanner(std::istream &in, std::ostream &out)
46 :
47     ScannerBase(in, out)
48 {}
```

```
49
50 inline Scanner::Scanner(std::string const &infile, std::string const &outfile)
51 :
52     ScannerBase(infile, outfile)
53 {}
54
55 // $insert inlineLexFunction
56 inline int Scanner::lex()
57 {
58     return lex__();
59 }
60
61 inline void Scanner::preCode()
62 {
63     // optionally replace by your own code
64 }
65
66 inline void Scanner::postCode(PostEnum__ type)
67 {
68     // optionally replace by your own code
69 }
70
71 inline void Scanner::print()
72 {
73     print__();
74 }
75
76
77 #endif // Scanner_H_INCLUDED_
```

../36/main.cc

```
1 #include "main.ih"
2
3 int main(int argc, char const **argv)
4 {
5     if (!file_exists(argv[1]))
6     {
7         cout << "Invalid file.";
8         return 1;
9     }
10
11     return processfile(argv[1]);
12 }
```

The same as in exercise 35:

../36/fileexists.cc

```
1 #include "main.ih"
2
3 bool file_exists(const char *fileName)
4 {
5     ifstream infile(fileName);
6     return infile.good();
7 }
```

../36/processfile.cc

```
1 #include "main.ih"
2
3 int processfile(const char *file)
4 {
5     size_t curLine = 0;
6     Scanner flatbed(file, "/dev/null");
7     while (true)
```

```
8  {
9      if (curLine != flatbed.lineNr())
10     {
11         curLine = flatbed.lineNr();
12         cout << "\nLine " << curLine << ": ";
13     }
14     switch (flatbed.lex())
15     {
16     case 0:
17         return 0;
18     case INT:
19         cout << "INT: " << flatbed.matched() << ' ';
20         break;
21     case WORD:
22         cout << "WORD: " << flatbed.matched() << ' ';
23         break;
24     case FLOAT:
25         cout << "FLOAT: " << flatbed.matched() << ' ';
26         break;
27     case STRING:
28         cout << "STRING: " << flatbed.matched() << ' ';
29         break;
30     case OP:
31         cout << "OPERATOR: " << flatbed.matched() << ' ';
32         break;
33     default:
34         cout << "CHAR: " << flatbed.matched() << ' ';
35         break;
36     }
37 }
38 }
```

Exercise 37

../37/lexer

```
1
2 %x multiline
3 %x hash
4 %x ccomment
5 %x string
6
7 %%
8
9 "\"" begin(StartCondition_::string);
10 <string>["][ ]* begin(StartCondition_::INITIAL);
11 <string>.\|\\n echo();
12
13 "/*" begin(StartCondition_::multiline);
14 <multiline>"*/"[ ]* begin(StartCondition_::INITIAL);
15 <multiline>.\|\\n
16
17 "#" begin(StartCondition_::hash);
18 <hash>"\\n" begin(StartCondition_::INITIAL);
19 <hash>.\|\\n
20
21 //ccomment miniscanner beter leesbaar dan normale lexer code
22 "//" begin(StartCondition_::ccomment);
23 <ccomment>"\\n" begin(StartCondition_::INITIAL);
24 <ccomment>.\|\\n
25
26
27 ^\\n
28 ^(\ | )+
29 ^(\ | \t )+
```

../37/Scanner.h

```
1 // Generated by Flexc++ V2.06.02 on Fri, 15 Mar 2019 16:14:20 +0100
2
3 #ifndef Scanner_H_INCLUDED_
4 #define Scanner_H_INCLUDED_
5
6 enum Token
7 {
8     MULTILINE = 257,
9     HASH,
10 };
11 // $insert baseclass_h
12 #include "Scannerbase.h"
13
14
15 // $insert classHead
16 class Scanner: public ScannerBase
17 {
18     public:
19         explicit Scanner(std::istream &in = std::cin,
20                         std::ostream &out = std::cout);
21
22         Scanner(std::string const &infile, std::string const &outfile);
23
24         // $insert lexFunctionDecl
25         int lex();
26
27     private:
28         int lex_();
29         int executeAction_(size_t ruleNr);
```

```
30
31     void print();
32     void preCode();           // re-implement this function for code that must
33                               // be exec'ed before the patternmatching starts
34
35     void postCode(PostEnum__ type);
36                               // re-implement this function for code that must
37                               // be exec'ed after the rules's actions.
38 };
39
40 // $insert scannerConstructors
41 inline Scanner::Scanner(std::istream &in, std::ostream &out)
42 :
43     ScannerBase(in, out)
44 {}
45
46 inline Scanner::Scanner(std::string const &infile, std::string const &outfile)
47 :
48     ScannerBase(infile, outfile)
49 {}
50
51 // $insert inlineLexFunction
52 inline int Scanner::lex()
53 {
54     return lex__();
55 }
56
57 inline void Scanner::preCode()
58 {
59     // optionally replace by your own code
60 }
61
62 inline void Scanner::postCode(PostEnum__ type)
63 {
64     // optionally replace by your own code
65 }
66
67 inline void Scanner::print()
68 {
69     print__();
70 }
71
72
73 #endif // Scanner_H_INCLUDED_
```

../37/main.cc

```
1 #include "main.ih"
2 #include "Scanner.h"
3
4 int main(int argc, char const **argv)
5 {
6     Scanner hp("input", "output");
7     hp.lex();
8 }
```


Exercise 38

../38/lexer

```
1 %x string
2
3
4 %%
5
6 "\"" {
7     begin(StartCondition_::string);
8     setMatched("grabbed(" + counter() + ", " + \
9     filename() + ".gsl");");
10    echo();
11    }
12 <string>[""][] {
13     begin(StartCondition_::INITIAL);
14 }
15 <string>.\n
```

../38/Scanner.h

```
1 // Generated by Flexc++ V2.06.02 on Fri, 15 Mar 2019 17:38:07 +0100
2
3 #ifndef Scanner_H_INCLUDED_
4 #define Scanner_H_INCLUDED_
5
6 // $insert baseclass_h
7 #include "Scannerbase.h"
8 #include <string>
9
10
11 // $insert classHead
12 class Scanner: public ScannerBase
13 {
14     size_t d_counter = 0;
15
16 public:
17     explicit Scanner(std::istream &in = std::cin,
18                     std::ostream &out = std::cout);
19
20     Scanner(std::string const &infile);
21     Scanner(std::string const &infile, std::string const &outfile);
22
23     // $insert lexFunctionDecl
24     int lex();
25
26     std::string counter();
27
28 private:
29     int lex_();
30     int executeAction_(size_t ruleNr);
31
32     void print();
33     void preCode(); // re-implement this function for code that must
34                     // be exec'ed before the patternmatching starts
35
36     void postCode(PostEnum_ type);
37                     // re-implement this function for code that must
38                     // be exec'ed after the rules's actions.
39 };
40
41 // $insert scannerConstructors
42 inline Scanner::Scanner(std::istream &in, std::ostream &out)
43 :
```

```
44     ScannerBase(in, out)
45 {}
46
47 inline Scanner::Scanner(std::string const &infile)
48 :     ScannerBase(infile, infile + ".tmp")
49 {}
50
51
52 inline Scanner::Scanner(std::string const &infile, std::string const &outfile)
53 :
54     ScannerBase(infile, outfile)
55 {}
56
57 inline std::string Scanner::counter()
58 {
59     return std::to_string(++d_counter);
60 }
61
62 // $insert inlineLexFunction
63 inline int Scanner::lex()
64 {
65     return lex__();
66 }
67
68 inline void Scanner::preCode()
69 {
70     // optionally replace by your own code
71 }
72
73 inline void Scanner::postCode(PostEnum__ type)
74 {
75     // optionally replace by your own code
76 }
77
78 inline void Scanner::print()
79 {
80     print__();
81 }
82
83
84 #endif // Scanner_H_INCLUDED_
```

../38/main.cc

```
1 #include "main.ih"
2
3 int main(int argc, char const **argv)
4 {
5     if (argc == 2)
6     {
7         Scanner scanner(argv[1]);
8         scanner.lex();
9     }
10    else
11    {
12        cout << "Please provide input filename.\n";
13    }
14 }
```