Artificial Intelligence & IoT

Markov Decision Process II




Instructor: Kaikai Pan
Zhejiang University

[These slides were adapted from the slides by Dan Klein and Pieter Abbeel for CS188 Intro to AI at UC Berkeley. http://ai.berkeley.edu.]

Recap: Defining MDPs

- Markov decision processes:
  - Set of states S
  - Start state s_0
  - Set of actions A
  - Transitions P(s'|s,a) (or T(s,a,s'))
  - Rewards R(s,a,s') (and discount γ)



- MDP quantities so far:
  - Policy = Choice of action for each state
  - Utility = sum of (discounted) rewards

浙大《人工智能与物联网》2026夏

Optimal Quantities

- The value (utility) of a state s:


  $V^*(s)$ = expected utility starting in s and acting optimally

- The value (utility) of a q-state (s,a):

  $Q^*(s,a)$ = expected utility starting out having taken action a from state s and (thereafter) acting optimally

- The optimal policy:

  $\pi^*(s)$ = optimal action from state s




s is a *state*


(s, a) is a *q-state*

(s,a,s') is a *transition*


Gridworld Values V*



Gridworld: Q*


Gridworld Display
0.59
0.57
0.64
0.53
0.67
0.60
0.74
0.67
0.77
0.66
0.85
0.57
1.00
0.57
0.51
0.51
0.46
0.57
0.53
-0.60
0.30
-1.00
0.49
0.45
0.41
0.44
0.40
0.43
0.42
0.40
0.48
0.40
0.29
0.41
-0.65
0.28
0.13
0.27
Q-VALUES AFTER 100 ITERATIONS

The Bellman Equations (贝尔曼方程)




The Bellman Equations

- Definition of “optimal utility” via expectimax recurrence gives a simple one-step look-ahead relationship amongst optimal utility values

$$V^*(s) = \max_a Q^*(s,a)$$

$$Q^*(s,a) = \sum_{s'} T(s,a,s') \left[R(s,a,s') + \gamma V^*(s') \right]$$

$$V^*(s) = \max_a \sum_{s'} T(s,a,s') \left[R(s,a,s') + \gamma V^*(s') \right]$$




- These are the Bellman equations, and they characterize optimal values in a way we’ll use over and over

浙大《人工智能与物联网》2026夏

Value Iteration


- Bellman equations characterize the optimal values:

$$V^*(s) = \max_a \sum_{s'} T(s,a,s') \left[R(s,a,s') + \gamma V^*(s') \right]$$



- Value iteration computes them:

$$V_{k+1}(s) \leftarrow \max_a \sum_{s'} T(s,a,s') \left[R(s,a,s') + \gamma V_k(s') \right]$$




- Value iteration is just a fixed point solution method

浙大《人工智能与物联网》2026夏

Problems with Value Iteration

- Value iteration repeats the Bellman updates:


$$V_{k+1}(s) \leftarrow \max_a \sum_{s'} T(s,a,s') \left[R(s,a,s') + \gamma V_k(s') \right]$$



- Problem 1: It's slow – $O(S^2A)$ per iteration
- Problem 2: The "max" at each state rarely changes
- Problem 3: The policy often converges long before the values

浙大《人工智能与物联网》2026夏

k=0




Noise = 0.2
Discount = 0.9
Living reward = 0

k=1



Noise = 0.2
Discount = 0.9
Living reward = 0

k=2




Noise = 0.2
Discount = 0.9
Living reward = 0

k=3




Noise = 0.2
Discount = 0.9
Living reward = 0

k=4



Noise = 0.2
Discount = 0.9
Living reward = 0

k=5



Noise = 0.2
Discount = 0.9
Living reward = 0

k=6




Noise = 0.2
Discount = 0.9
Living reward = 0

k=7



Noise = 0.2
Discount = 0.9
Living reward = 0

k=8




Noise = 0.2
Discount = 0.9
Living reward = 0

k=9




Noise = 0.2
Discount = 0.9
Living reward = 0

k=10



Noise = 0.2
Discount = 0.9
Living reward = 0

k=11



Noise = 0.2
Discount = 0.9
Living reward = 0

k=12




Noise = 0.2
Discount = 0.9
Living reward = 0

k=100




Noise = 0.2
Discount = 0.9
Living reward = 0

Policy Methods




Policy Evaluation (策略评估)




Fixed Policies

Do the optimal action



Do what π says to do




- Expectimax trees max over all actions to compute the optimal values
- If we fixed some policy π(s), then the tree would be simpler – only one action per state
  - … though the tree's value would depend on which policy we fixed

Utilities for a Fixed Policy

- Another basic operation: compute the utility of a state s under a fixed (generally non-optimal) policy

- Define the utility of a state s, under a fixed policy π:

  $V^{\pi}(s)$ = expected total discounted rewards starting in s and following π




- Recursive relation (one-step look-ahead / Bellman equation):

$$V^{\pi}(s) = \sum_{s'} T(s, \pi(s), s')[R(s, \pi(s), s') + \gamma V^{\pi}(s')]$$


浙大《人工智能与物联网》2026夏

Example: Policy Evaluation

Always Go Right



Always Go Forward



Example: Policy Evaluation

Always Go Right



Always Go Forward




Policy Evaluation

- How do we calculate the V's for a fixed policy π?
- Idea 1: Turn recursive Bellman equations into updates (like value iteration)

$$V_0^\pi(s) = 0$$


$$V_{k+1}^\pi(s) \leftarrow \sum_{s'} T(s, \pi(s), s')[R(s, \pi(s), s') + \gamma V_k^\pi(s')]$$



- Efficiency: $O(S^2)$ per iteration
- Idea 2: Without the maxes, the Bellman equations are just a linear system

浙大《人工智能与物联网》2026夏


Policy Extraction (策略提取)



浙大《人工智能与物联网》2026夏

Computing Actions from Values

- Let's imagine we have the optimal values V*(s)
- How should we act?
  - It's not obvious!
- We need to do a mini-expectimax (one step)




$$\pi^*(s) = \arg\max_a \sum_{s'} T(s,a,s')[R(s,a,s') + \gamma V^*(s')]$$

- This is called policy extraction, since it gets the policy implied by the values

Computing Actions from Q-Values

- Let's imagine we have the optimal q-values:




- How should we act?
  - Completely trivial to decide!

$$\pi^*(s) = \arg\max_a Q^*(s,a)$$

- Important lesson: actions are easier to select from q-values than values!

浙大《人工智能与物联

Policy Iteration (策略迭代)



Policy Iteration (策略迭代)

- Alternative approach for optimal values:
  - Step 1: Policy evaluation (策略评估): calculate utilities for some fixed policy (not optimal utilities!) until convergence
  - Step 2: Policy improvement (策略改进): update policy using one-step look-ahead with resulting converged (but not optimal!) utilities as future values
  - Repeat steps until policy converges

- This is policy iteration
  - It's still optimal!
  - Can converge (much) faster under some conditions

浙大《人工智能与物联网》2026夏

Policy Iteration (策略迭代)

- Evaluation: For fixed current policy π, find values with policy evaluation:
  - Iterate until values converge:

$$V_{k+1}^{\pi_i}(s) \leftarrow \sum_{s'} T(s, \pi_i(s), s') \left[R(s, \pi_i(s), s') + \gamma V_k^{\pi_i}(s') \right]$$

- Improvement: For fixed values, get a better policy using policy extraction
  - One-step look-ahead:

$$\pi_{i+1}(s) = \arg\max_a \sum_{s'} T(s, a, s') \left[R(s, a, s') + \gamma V^{\pi_i}(s') \right]$$

浙大《人工智能与物联网》2026夏

Comparison

- Both value iteration and policy iteration compute the same thing (all optimal values)
- In value iteration:
  - Every iteration updates both the values and (implicitly) the policy
  - We don’t track the policy, but taking the max over actions implicitly recomputes it
- In policy iteration:
  - We do several passes that update utilities with fixed policy (each pass is fast because we consider only one action, not all of them)
  - After the policy is evaluated, a new policy is chosen (slow like a value iteration pass)
  - The new policy will be better (or we’re done)
- Both are dynamic programs for solving MDPs

浙大人工智能与物联网》2026夏

Summary: MDP Algorithms


- So you want to….
  - Compute optimal values: use value iteration or policy iteration
  - Compute values for a particular policy: use policy evaluation
  - Turn your values into a policy: use policy extraction (one-step look-ahead)

- These all look the same!
  - They basically are – they are all variations of Bellman updates
  - They all use one-step look-ahead expectimax fragments
  - They differ only in whether we use a fixed policy or max over actions

浙大人工智能与物联网 2026夏

Double Bandits








浙大《人工智能与物联网》2020夏

Double-Bandit MDP

- Actions: *Blue, Red*
- States: Win, Lose



No discount

100 time steps

Both states have the same value

浙大《人工智能与物联网》2026春

Offline Planning (离线规划)


- Solving MDPs is offline planning
  - You determine all quantities through computation
  - You need to know the details of the MDP
  - You do not actually play the game!

No discount

100 time steps

Both states have the same value

	Value
Play Red	150
Play Blue	100



浙大《人工智能与物联网》2026春

Let's Play!






$2 $2 $0 $2 $2

$2 $2 $0 $0 $0

浙大《人工智能与物联网》2020夏

Online Planning (在线规划)

- Rules changed! Red's win chance is different.



浙大人工智能与物联网》2026夏

Let's Play!





$0 $0 $0 $2 $0

$2 $0 $0 $0 $0

浙大《人工智能与物联网》2020夏

What Just Happened?

- That wasn't planning, it was learning!
  - Specifically, reinforcement learning (强化学习)
  - There was an MDP, but you couldn't solve it with just computation
  - You needed to actually act to figure it out



- Important ideas in reinforcement learning that came up
  - Exploration (探索): you have to try unknown actions to get information
  - Exploitation (利用): finally, you have to use what you know
  - Sampling: because of chance, you have to try things repeatedly
  - Difficulty: learning can be much harder than solving a known MDP

浙大《人工智能与物联网》 2026夏