



Provisioning Documentation

Part 2

Integrated Provisioning Services
Airbus Services Solutions

TABLE OF CONTENTS

1.	INTRODUCTION	2
2.	PROVISIONING FILES	2
2.1.	RECOMMENDED SPARE PARTS LIST	2
2.2.	OTHER PROVISIONING LISTS	3
2.3.	SUPPLEMENTARY FILES	4
3.	PROVISIONING DOCUMENTATION	4
3.1.	FORECASTING MODEL PARAMETERS	4
3.1.1.	<i>DESCRIPTION OF PARAMETERS.....</i>	<i>6</i>
3.2.	MATHEMATICAL MODEL FOR PROVISIONING RECOMMENDATIONS.....	8
3.3.	EXCHANGE RATES USED IN THE RECOMMENDATION.....	8
3.4.	AIRCRAFT APPLICATION TABLE	8
4.	CAGE Code List.....	8
5.	RECOMMENDED SPARE PARTS LIST (RSPL)	9
6.	W FILE	16
7.	ABBREVIATION LIST	18
8.	APPENDIX	20

1. INTRODUCTION

The Integrated Provisioning Services Manual provides an overview and may accompany you as a quick reference guide. Furthermore, each of the documents, which you receive, will have an own introduction. Please read these carefully because they explain the individual manuals in more detail.

Note: All provisioning documents are based on spare parts technical data. The prices contained in this recommendation are based on supplier price lists. Any commercial data, especially prices, are listed for **budgetary** purposes and do not represent or imply a firm quote from Airbus or the suppliers.



Tamas Stefka
Senior Director Integrated Provisioning Services

2. PROVISIONING FILES

2.1. RECOMMENDED SPARE PARTS LIST

The Recommended Spare Parts List (RSPL) is the working document presented and discussed during the Material Readiness Conference. It contains recommendations for various spares categories (except of the Proprietary Parts). It will be available as MS-Excel file on CD ROM.

The Initial Provisioning (IP) package includes the following kinds of material:

- LRU** - *Line Replaceable Unit*
A unit which may be replaced on the aircraft during line maintenance.
- LMP** - *Line Maintenance Breakdown Part of LRU*
An item, which might be replaced from an LRU during aircraft maintenance without removing the LRU from the aircraft.
- AIB** - *Airbus Proprietary Part*
A part made and marketed by a company with legal rights or exclusive title to manufacture and sale.
- CPB** - *Cockpit Push Button*
- STD** - *Standard Hardware Material*
Expendable hardware items having relatively high usage, numerous applications and normally available from industrial supply outlets.

2.2. OTHER PROVISIONING LISTS

- AMMF** - *Airbus Material Maintenance Forecast*
Material forecast service for scheduled C-check maintenance.
- FLS** - *Field Loadable Software*
List of loadable software and the related transport media that are not considered as relevant in a spares context and as such are not listed in the RSPLs.
- FCA** - *Fleet Commonality Analysis (only in combination with an LRU RSPL)*
A list of combined LRUs in which part number (PNR) commonality between the different requested A/C types is flagged.
- ACRD** - *Airbus Component Replacement Data*
The ACRD is an Excel based document which reflects all necessary items you will need for replacing all recommended LRUs in your RSPL including tools, expendables, consumables and ground support equipment.

MSD - *Material Storage Data*

The MSD provides shelf life, hazard and storage information for spare parts installed on all Airbus aircraft. The MSD is not customized and is issued quarterly on a chargeable basis. It is available as an individual revision or a subscription package.

Mixed Operators RSPL

It is an RSPL shaped for MROs as it includes and combines information of aircraft from different Airbus operators. Data Release Agreements from the respective operators are required in advance.

Consumable Material Recommendation

Will be presented and distributed upon request only.

Engine Spares Recommendation

The engine manufacturers will give further engine product support.

Nacelle Spares Recommendation

Depending on the A/C model, spares recommendations will be given by either Airbus or the nacelle manufacturers.

Note: Specific outputs of LRU, LMP, AIB, STD, CPB sequenced by PNR, ATA chapter and MFR are available. See appendix for samples.

2.3. SUPPLEMENTARY FILES

GSE & Tools Recommendation (W-FILE)

The W file contains provisioning data for Airbus specific line maintenance tools and Ground Support Equipment (GSE). It is a customized document.

3. PROVISIONING DOCUMENTATION

3.1. FORECASTING MODEL PARAMETERS

These parameters drive the calculation process that determines recommended quantities. They are discussed and agreed upon with the customer – typically within the Material Readiness Set-up Meeting.

The customer can decide whether the calculation shall be based on the Spare Parts Class Code (SPC) of each part or on a defined price range.

Parameters for calculation based on SPC
(sample values only)

		REC1	REC2	REC3
Sub fleet	SF_0001			
A/C type	A320			
Fleet size		12	13	14
Annual Flight hours		2500	2500	2500
Block Time Average		2.0	2.0	2.0
Prot.-Level Tolerance				
Customised Redundancy Factor				
Administration Time		15	15	15
APU consideration factor				

PTL				
SPC1	ESS=1	92	92	92
	ESS=2	88	88	88
	ESS=3	86	86	86
	SPC2			
	ESS=1	92	92	92
	ESS=2	88	88	88
	ESS=3	86	86	86
SPC6	ESS=1	92	92	92
	ESS=2	88	88	88
	ESS=3	86	86	86
MAD				
SPC1	ESS=1	0.5	0.5	0.5
	ESS=2	0.6	0.6	0.6
	ESS=3	1.0	1.0	1.0
	SPC2			
	ESS=1	0.5	0.5	0.5
	ESS=2	0.6	0.6	0.6
	ESS=3	1.0	1.0	1.0
SPC6	ESS=1	0.5	0.5	0.5
	ESS=2	0.6	0.6	0.6
	ESS=3	1.0	1.0	1.0
Transit Time				
Turn Around Time	Rotables	12	12	12
	Repairables	12	12	12
Turn Around Time	Rotables			
	Repairables			
	ATE			

Parameters for calculation based on Price Range
(sample values only)

		REC1	REC2	REC3
Sub fleet	SF_0001			
A/C type	A330			
Fleetsize		8	8	8
Annual Flighthours		5300	5300	5300
Block Time Average		9.4	9.4	9.4
Sub fleet	SF_0002			
A/C type	A340			
Fleetsize		7	7	7
Annual Flighthours		5300	5300	5300
Block Time Average		9.4	9.4	9.4
Prot.-Level Tolerance		1.0	1.0	1.0
Customised Redundancy Factor				
Administration Time		14	14	14
APU consideration factor		100	100	100
Price-ranges in USD instead of SPC:	Y			
Medium Price:		25000	to	200000
PTL				
Lower Price Range	ESS=1	98	98	98
	ESS=2	94	94	94
	ESS=3	90	90	90
Medium Price Range	ESS=1	96	96	96
	ESS=2	92	92	92
	ESS=3	88	88	88
Upper Price Range	ESS=1	90	90	90
	ESS=2	86	86	86
	ESS=3	82	82	82
MAD				
Lower Price Range	ESS=1			0.3
	ESS=2			0.5
	ESS=3			0.8
Medium Price Range	ESS=1			0.3
	ESS=2			0.5
	ESS=3			0.8
Upper Price Range	ESS=1			0.3
	ESS=2			0.5
	ESS=3			0.8
Transit Time	Rotables			
Turn Around Time	Rotables	30	3	30
	Repairables	30	3	30
	ATE			

3.1.1. DESCRIPTION OF PARAMETERS**NUMBER OF A/C IN THE IP PERIOD**

The quantity of aircraft is based on the decision of the customer and counts the number of aircraft for which the Initial Provisioning exercise shall be run. This number may be lower than the number of purchased airplanes to properly consider the start-up requirements at Entry-Into-Service (EIS).

FLIGHT HOURS PER A/C PER YEAR

The total flight hours per year of all aircraft divided by the number of aircraft

PROTECTION LEVEL

The protection level describes the probability of having the part in stock, expressed as a percentage. Reasonable protection levels range from 80-96% and can be allocated individually to parts according to their essentiality code and price level profile.

MINIMUM ANNUAL DEMAND

It is a decision maker, which above the threshold, triggers the first spare to be protected against the risk of first stock-out. Below the threshold, it discards spares in order to be protected against overstocking due to a long re-supply time.

PROTECTION LEVEL TOLERANCE

This value determines how much tolerance may be applied to the protection level in cases where 1 spare less would satisfy the tolerant protection level requirement.

CUSTOMISED REDUNDANCY FACTOR

The CRF controls how much of the redundancy built into Go-If components/systems shall be considered for spares planning when computing a part's demand.

ADMINISTRATION TIME

It is the total time taken in calendar days from removal of an unrepairable part, placing a purchase order, shipping and customs, until the new part is ready for use on the operator's shelf. This value is added to the lead time to determine the replenishment period.

APU CONSIDERATION FACTOR

The APU consideration factor is the ratio between APU operating hours to flight hours.

Turnaround Time and Transit Time

TURN AROUND TIME								
TRANSIT TIME – PART 1					TRANSIT TIME – PART 2			
⇒								⇒
FAULT IDENTIFIED	Customer administration	Customs	Shipping Time	MST	Shipping Time	Customs	Customer administration	UNIT RESTOCKED

TAT

Turnaround Time is the sum of Transit Time (TT) and the Mean/Max Shop Processing Time (MST) expressed in calendar days ($TAT = TT + MST$). Choosing the TAT as an entry parameter the calculation of the recommendations disregards the TT and the individual part's MST and sets the TAT as a global value for all rotatable or repairable spares.

TT

It is the total time taken in calendar days for an unserviceable part to be removed from the aircraft, packaged, shipped to and back from the repair shop including the time spent at customs, until the serviceable part is ready for use on the operator's shelf.

FLIGHT CYCLE

The average duration in hours of a representative flight-leg between engine-on and engine-off (complete take-off and landing sequence).

3.2. MATHEMATICAL MODEL FOR PROVISIONING RECOMMENDATIONS

A mathematical calculation will be used to generate the customised recommended quantities in the various provisioning files or documents taking into account the airline's operational parameters that are usually defined during the Material Readiness Set-up Meeting.

CALCULATION OF RECOMMENDED QUANTITY

For details refer to the brochure "*INTEGRATED PROVISIONING SERVICES- The Mathematical Model*". In the first step a part is analysed for its risk of failure within the first year of operation via testing the annual demand versus the minimum annual demand selected by the customer as *spares qualifier*.

In case the part qualifies as spare, the first spare is allocated to the stock. Further risks out of re-supply chain delays are mitigated by adding further spares to obtain sufficient protection in line with the expected demand during re-supply time.

3.3. EXCHANGE RATES USED IN THE RECOMMENDATION

To convert the price indicated in original source currency into US Dollar, the exchange rates given on the "Parameter" page in the RSPL are used. The individual conversion rates vary depending on the world wide economical development. The exchange rates will be updated monthly.

The exchange rates contained in the documents are for budgetary and planning purposes only and do not represent guaranteed values.

3.4. AIRCRAFT APPLICATION TABLE

The aircraft application table indicates the aircraft or block of aircraft for which the initial provisioning is conducted (sample values only):

Owner	Operator	MSN	Registration	Engine Type	A/C Model	Version	PNR SOURCE	Sub. Fleet	REC1	REC2	REC3
CUST	CUST	2255	XY-A344	V2533-A5	A321-231	CUST01	IPC	SF_0001	1	1	1
CUST	CUST	2261	XY-A345	V2533-A5	A321-231	CUST01	IPC	SF_0001	1	1	1
...	...	...	...	...	...	...	...	...	...	...	...

4. CAGE Code List

All suppliers who appear in the Recommended Spare Parts List are listed in MFR Sort.

The lists show the postal address of the suppliers in order to identify the MFR Code.

Telephone, fax and other details of the address are found in the Vendor Information Manual (VIM) and in the Cataloguing Handbook H4/H8: Section A and B, Commercial and Government Entity (CAGE).

5. RECOMMENDED SPARE PARTS LIST (RSPL)

The Recommended Spare Parts List (RSPL) is available in two different layouts, printable/projector file and plain spreadsheet. Both contain, next to the recommendations, various information given by the following terms and abbreviations (in alphabetical order):

Note: Samples of the RSPL in both layouts are given in the appendix of this manual.

ADT

Additional Descriptive Text

Gives the full description of the item or additional notes when special conditions apply.

ALTPNR / ALT

Alternate Part Number

Identifies a part which fully meets required functional and structural specifications, but differs either in overall dimensions, connections, installations and/or mounting provisions and requires additional parts, rework or modification to install it in a specific location as an alternative to the subject part number.

ALT_MFR

Alternate Manufacturer Code

Indicates the manufacturer of an alternate part.

ATA

Air Transport Association chapter classification of the item.

BFE

Buyer Furnished Equipment

It is indicated when the related Part Number is classified as BFE. The supply of parts tech data is the buyer's responsibility.

CHG

Revision Indicator

Changes to a line since the RSPL was last issued are indicated by the letter "R", deletion by "D" and newly introduced item by "N".

When the "R" revision indicator is shown on the right hand side of the printable/projector file, the data change(s) is (are) underlined in the major data columns: **SPC, ESS, MTBUR, MST, LT, CUR, PRICE, QPA and REC QTY.**

CONTAINS LMP (projector file only)

Contains Component Line Maintenance Breakdown Parts (LMP)

It indicates that Line Maintenance Breakdown Parts of LRU are documented in the RSPL-LMP.

CONTAINS LRU (projector file only)

Contains Line Replaceable Unit

A Line Replaceable Unit (LRU) is documented as a subcomponent to the indicated part number in the RSPL-LRU.

CSN

Catalogue Sequence Number

Identifies a specific location of the subject part number in the Illustrated Parts Catalogue (IPC) for LRUs, the S File or the Illustrated Parts List (IPL) for LMPs.

CUR*Currency Code***Coding:**

1*)	US Dollar	*) Standard currency
2	Canadian Dollar	
3	UK Pound	
8	Swiss Franc	
D	Danish Crown	
G	Japan Yen	
Q	Euro	

Note: If currency of the supplier price list is identical to the currency selected for the conversion there is no second line.

ESS*Essentiality Code*

Indicates whether the part is essential for dispatch of the aircraft.

Coding:

1	'NO GO' item	The aircraft cannot operate for commercial service with the part missing or inoperative.
2	'GO IF' item	The aircraft may operate for commercial services with the part missing or inoperative, dependent upon permissible conditions detailed in the Master Minimum Equipment List (MMEL)

3**'GO' item**

The aircraft can always operate for commercial services with the part missing or inoperative.

EXTENDED PRICE (*projector file only*)

The Extended Price is computed as the product of Unit Price amount times Recommended Quantity.

Calculation: EXTENDED PRICE = UNIT PRICE x REC QTY

ICD*Interchangeability Conditions Document*

Describes the conditions affecting the interchangeability of part numbers.

INC*Interchangeability Code*

The Interchangeability Code (INC) indicates the interchangeability of part numbers to the subject part number.

INC 01 one-way-interchangeability

The old part number may be used as a replacement only where the old part number was installed. The new part number is an acceptable replacement for either the old or new part number.

INC 02 two-way-interchangeability

The old and the new part numbers are each either acceptable replacements for the old or new part number.

INC 03 not interchangeable

When the old part number is removed, it must be replaced with the same part number. When the new part is removed, it must be replaced with the new part number.

INC 04 as a set

The old and new part numbers can replace each other provided that the complete shipset of part numbers are replaced.

INC 05 conditionally interchangeable

The two parts are conditionally interchangeable. The conditions affecting the interchangeability are listed in the Interchangeability Conditions Document (ICD).

INC 06 part reidentification

Indicates that the part number link was established to correct the identification of the referenced part.

INC_CODE

Interchangeability Code of Interchangeable Part Number

It indicates the interchangeability of the Interchangeable Part Number.

INC_MFR

Manufacturer Code of Interchangeable Part Number

Indicates the Manufacturer of an Interchangeable Part.

INC_PNR

Interchangeable Part Number

It is the superseding part number to the subject part number, caused by part number evolution.

The Interchangeable Part Number always comes along with a defined interchangeability code (**INC**).

LTM

Lead Time

The maximum number of calendar days required by the supplier after receipt of a purchase order to make shipment of the quantity ordered.

MFR

Manufacturer Code

The MFR Code identifies the manufacturer, government agency or other organisation controlling the design and the part number assignment of the subject part.

For those items for which **Airbus** has the exclusive sales rights the **letter "P" precedes the MFR Code**.

MMI

Math Model Indicator

It indicates if a calculated recommendation was changed caused by the usage of MAD (Minimum Annual Demand), CRF (Customised Redundancy Factor) or PLT (Protection Level Tolerance).

Indicator:

- () no calculation
- (0) normal calculation, without of any parameter
- (M) indicates that value of REC QTY results from MAD parameter
- (C) indicates that value of REC QTY results from CRF parameter
- (P) indicates that value of REC QTY results from PLT parameter
- (CP) indicates that value of REC QTY results from CRF and PLT parameter

(MC) indicates that value of REC QTY results from MAD and CRF parameter

For details refer to the brochure "INTEGRATED PROVISIONING SERVICES- The Mathematical Model."

MST

Mean/Max Shop Processing Time (depending on GCP)

It indicates the total number of calendar days from receipt of the part at repair base until dispatch. This includes administration, handling, repair test and other functions at the repair shop. It is applicable to items with Spare Part Class Code **SPC 2** or **SPC 6**.

MTBUR

Mean Time Between Unscheduled Removals

The statistical average in operating hours of the item between unscheduled removals. Scheduled removals are not taken into account.

Format: **TCC** **XXXXXX** **RRI**

TCC

Time Cycle Code

It indicates that the MTBUR is in hours (**H**) or cycles (**C**)

RRI

Removal Rate Indicator

RRI indicates the exponential factor to the power of 10. It applies to the Mean Time/Cycles Between Unscheduled Removals. MTBUR/MCBUR figures sometimes require more than the available 6-digit field.

Formula: $MTBUR \times 10^{\wedge} RRI$

Example: $125,000 \times 10^{\wedge} 2 = 12,500,000$

NHA / NHAPNR

Next Higher Assembly Part Number

The Next Higher Assembly Part Number is indicated for each breakdown part. It is shown with part number and ATA chapter.

PTQ

Provisioning Total Quantity

Specifies for the subject part number the total extended number of units (in implied units of each) used in the assembly of the component End Item.

OPL / OPLPNR

Optional Part Number

It identifies a fully interchangeable part in form, fit and function with the subject part number, thus providing a choice of parts for procurement and support purposes.

OPL_MFR

Manufacturer Code of Optional Part Number

Indicates the Manufacturer of an Optional Part.

OPNPNR (projector file only)

Overlength Part Number

Overlength Part Number identifies the complete part number when the part number exceeds fifteen digits in length.

OSC (projector file only)

Optional Supply Code

Indicates the Manufacturer Code(s) of optional supply sources.

PNR*Part Number*

Airbus indicates the Part Number being the manufacturer's, supplier's or industry standard identity as per SPEC 2000.

PPI*Power Plant Indicator*

It indicates if the subject part number is part of the Power Plant (P), the Quick Engine Change Unit (Q) or if the part number is common to a part number on the Power Plant (C).

PPR / PPRPNR*Preferred Part Number*

It identifies for the subject part number the preferred spare whether or not installed on the purchased equipment.

PPR_MFR*Manufacturer Code of Preferred Part Number*

Indicates the Manufacturer of a Preferred Part.

PTC*Price Type*

It indicates the type of Unit Price, its availability by quotation or its applicability to an optional part number according to the following table:

Coding:

0	Price not required per specification
1	Firm price
2	Budget or estimated price
3	Price applies to the manufacturer's assigned Optional Part Number (noted in Explanation Code 39-Optional Part Number-) and only when the part is procured from the End Item Manufacturer
4	Price available on quotation only

PTQ*Provisioning Total Quantity*

See NHA / NHAPNR

QPA*Quantity per aircraft*

It indicates the **average** quantity of the unit installed per aircraft across the fleet.

REC*Recommended Quantity*

It indicates the recommended quantity to meet the demands for the number of customer's aircraft to which the part applies through application of the **Airbus** math model and the use of the customer's provisioning parameters (as defined in paragraph 3.1.).

Note: The recommendation covers one main base only.

RESTR (split effectivity indication) (projector file only)*Restricted Usage*

The restriction of applicability within an aircraft fleet is printed after the word "**RESTR**" in-groups of 8 characters.

e.g.: **RESTR 0010 0020** means part number is applicable for aircraft MSN 10 to 20 in line with the aircraft application table (3.3)

At the old part number level the new part number is mentioned with "**REPBY**" (Replaced by).

At the new part number level the old part number is mentioned with "**REPLS**" (Replaces)

If the interchangeability code is **01** between two parts installed on different aircraft at production line level, both old and new part numbers have a restricted usage information and a replacement part number will be printed additionally.

Only the new part number is subject to the recommendation calculation.

e.g.: **RESTR** xxxx yyyy
REPBY (new part number) **INC = 01**
REPLS (old part number) **INC = 01**

If the interchangeability code is **02** between two parts installed on different aircraft at production line level, the old and new parts have part number reference information.

Only the new part number is subject to the recommendation calculation.

e.g.: **RESTR**
REPBY (new part number) **INC = 02**
REPLS (old part number) **INC = 02**

If the interchangeability code is **03** between two parts installed on different aircraft at production level, the old and new parts have a restricted usage information with part number cross-reference information.

Both part numbers are subject to the recommendation based on the size of the respective subfleet.

e.g.: **RESTR**
REPBY (new part number) **INC = 03**
RESTR
REPLS (old part number) **INC = 03**

RFS*Reason for Selection*

Specifies the primary reason for selecting the subject part as a potential spare part.

RPN*Replacing Part Number*

It is the part number that replaces the subject part number. The RPN always comes along with a defined Interchangeability Code (**INC**).

RRI*Removal Rate Indicator*

See MTBUR

SICSN (*projector file only*)*S-File Catalogue Sequence Number*

Identifies a specific location of the subject part number in the Illustrated Parts Catalogue (IPC) for LRUs, the S File or the Illustrated Parts List (IPL) for LMPs.

SPC*Spare Part Class Code*

It indicates the classification of the spare part as follows:

Coding:

1	Expendable Spare
2	Rotable Spare
	- Repairable Spare that has a supporting Component Maintenance Manual (CMM)
6	Repairable Spare
	- Repairable Spare that does not have an own Component Maintenance Manual (CMM)

SCR*Scrap Rate*

It identifies the percentage (to one decimal) of units which when removed from service are found to be beyond economic repair or unrepairable and therefore scrapped.

For print space reasons the decimal point is not printed.

example: 999 reads 99.9 %

TCC*Time Cycle Indicator*

See MTBUR

TOTAL

Total = REC x Unit Price

TPC*Technical Publication Code*

The TPC abbreviations are as follows:

ACMM = Abbreviated Component Maintenance Manual
 ATCE = Airline Test Cell Equipment Manual
 ATP = Atlas Program
 BM = Build-Up Manual
 CMM = Component Maintenance Manual
 CSM = Computer Software Manual
 EFM = Eprom Fixture Manual
 EM = Engine Manual
 HMM = Heavy Maintenance Manual
 IM = Installation Manual
 INSM = Instruction Manual
 IPC = Illustrated Parts Catalog
 MFP = Maintenance Facility Planning Manual
 MM = Maintenance Manual
 NTM = Non-destructive Testing Manual
 OASI = Operation and Service Instruction Manual
 OM = Overhaul Manual
 OP = Operating Manual
 SDD = Software Detailed Description
 SHM = Shop Manual
 SM = Standards Manual
 SOIM = Specific Operation Instruction Manual
 SPM = Standard Practices Manual
 SRM = Structure Repair Manual
 TDS = Technical Data Sheet
 TEM = Tool and Equipment Manual
 TSM = Trouble Shooting Manual

TPC_REF*Technical Publication Reference*

The technical publication code (TPC) and corresponding ATA reference are shown.

UNP*Unit Price*

Shows the price per unit with two decimals.

Line 1: Unit price in original supplier list currency (as per CUR).

Line 2: Unit price in USD unless otherwise specified by the operator.

Note: The prices in this recommendation are based on supplier price lists. They are for budgetary purposes only and do not represent or imply a firm quote from **Airbus** or the respective supplier even though they might be indicated as firm.

UNT*Unit Of Measure*

This code specifies the type of count, measurement, container or form of the subject part and correlates to the unit price.

6. W FILE

The recommendation is based on the required maintenance level, which is provided by the airline.

The W File has specific outputs in PNR, ATA chapter and CAGE sequence and includes the following details:

DWG*Drawing available*

It indicates the possibility of local manufacturing.

Coding:

Y	drawing available, possibility of local manufacturing provided
P	supplier proprietary item

UMT*Selected **Unscheduled Maintenance Tasks***

It indicates the classification of required maintenance actions.

Coding:

A	APU change
B	Brake change
C	Additional recommended items – C-2C level maintenance
D	Additional recommended items - 1D level maintenance
E	Engine change
F	Additional recommended items – first year of operation

G	Additional recommended items – 4C level maintenance
H	Additional recommended items – 2D level maintenance
I	IDG change
L	Additional recommended items – line & servicing
M	MMEL items
U	Various unscheduled maintenance – not recommended for IP.
W	Wheel change

SMC

Selected Maintenance Check as per MPD.

Reference to the lowest MPD scheduled maintenance interval where tool is required.

If tool is to be used in various scheduled check levels, the first occurrence is indicated only.

Coding:

DW	Daily / Weekly checks
XA	A- and multiple A-checks
2C	C- and 2C-checks
4C	4C-checks
1D	Structure check: 4 or 5 YE, depending on aircraft type
2D	Structure check: 8 or 10 YE, depending on aircraft type
HT	Hard Time items

NOTE 1**Coding:**

F	Tool is included in Flight Kit
L	Tool is available for loan/lease
E	Equivalent tool may be used
N	National requirements (NR) (Task known as being subject to national regulatory requirement)
V	Vendor recommendation (VR) (Task/interval is a vendor recommendation)

NOTE 2**Coding:**

N	Nose Landing Gear change
M	Main Landing Gear change
C	Centre Landing Gear change

ATA + TEM

Tool Equipment Manual

Coding:

TEM-documentation	in	accordance	with	ATA:
VV				ATA chapter
XX				ATA subchapter
YY				ATA subchapter
ZZ				Page

AMM

Aircraft Maintenance Manual

It indicates the first use of a tool in accordance with the AMM and job instruction cards.

7. ABBREVIATION LIST

A/C	Aircraft	FLS	Field Loadable Software
ACMM	Abbreviated Component Maintenance Manual	GCP	General Conditions of Purchase
		GSE	Ground Support Equipment
ADT	Additional Descriptive Text	HMM	Heavy Maintenance Manual
AIB	Airbus Proprietary Part	ICD	Interchangeability Conditions Document
ALT_MFR	Alternate Manufacturer Code	IM	Installation Manual
ALTPNR	Alternate Part Number	INC	Interchangeability Code
AMM	Aircraft Maintenance Manual	INSM	Instruction Manual
AMMF	Airbus Material Maintenance Forecast	IP	Initial Provisioning
APU	Auxiliary Power Unit	IPC	Illustrated Parts Catalogue
ATA	Air Transport Association	IPL	Illustrated Parts List
ATCE	Airline Test Cell Equipment Manual	LMP	Line Maintenance Breakdown Part
ATP	Atlas Program	LRU	Line Replaceable Unit
BFE	Buyer Furnished Equipment	LT/LTM	Lead Time
BM	Build-Up Manual	MAD	Minimum Annual Demand
CAGE	Commercial and Government Entity	MFP	Maintenance Facility Planning Manual
CHG	Change / Revision Indicator	MFR	Manufacturer Code
CML	Consumable Material List	MM	Maintenance Manual
CMM	Component Maintenance Manual	MMEL	Master Minimum Equipment List
CPB	Cockpit Push Button	MMI	Math Model Indicator
CRF	Customised Redundancy Factor	MPD	Maintenance Planning Document
CSM	Computer Software Manual	MRO	Maintenance and Repair Organisation
CSN	Catalogue Sequence Number	MSD	Maintenance Storage Data
CUR	Currency Code	MSN	Manufacturer's Serial Number
DWG	Drawing available	MSQ	Minimum Sales Quantity
EFM	Eprom Fixture Manual	MST	Mean/Max Shop Processing Time
EIS	Entry-Into-Service	MTBUR	Mean Time Between Unscheduled Removals
EM	Engine Manual	NHA	Next Higher Assembly Part Number
ESS	Essentiality Code	NHAPNR	Next Higher Assembly Part Number
FCA	Fleet Commonality Analysis	NR	National Requirements
		NTM	Non-destructive Testing Manual

ABBREVIATION LIST (cont.)

OASI	Operation and Service Instruction Manual	SCR	Scrap Rate
OM	Overhaul Manual	SDD	Software Detailed Description
OP	Operating Manual	SHM	Shop Manual
OPL	Optional Part Number	SM	Standards Manual
OPLPNR	Optional Part Number	SMC	Selected Maintenance Check
OPL_MFR	Manufacturer Code of Optional Part Number	SOIM	Specific Operation Instruction Manual
OPN_PNR	Overlength Part Number	SPC	Spare Part Class Code
OSC	Optional Supply Code	SPM	Standard Practices Manual
PICL	Pool Item Candidate List	SRM	Structure Repair Manual
PLT	Protection Level Tolerance	STD	Standard Hardware Material
PNR	Part Number	TAT	Turn Around Time
PPI	Power Plant Indicator	TCC	Time Cycle Code
PPR	Preferred Part Number	TDS	Technical Data Sheet
PPRPNR	Preferred Part Number	TEM	Tool and Equipment Manual
PPR_MFR	Manufacturer Code of Preferred Part Number	TPC	Technical Publication Code
PTC	Price type	TPC_REF	Technical Publication Reference
PTQ	Provisioning Total Quantity	TSM	Trouble Shooting Manual
QPA	Quantity per Aircraft	TT	Transit Time
REC QTY	Recommended Quantity	UMT	Unscheduled Maintenance Task
REPB	Replaced by	UNP	Unit Price
REPLS	Replaces	UNT	Unit of Measure
RESTR	Restricted Usage	VIM	Vendor Information Manual
RFS	Reason for Selection	VR	Vendor Recommendation
RPN	Replacing Part Number		
RRI	Removal Rate Indicator		
RSPL	Recommended Spare Parts List		
S/C SN	S-File Catalogue Sequence Number		

8. APPENDIX

Sample prints of various provisioning documents:

A) RSPL as printable/projector files

1. RSPL - Line Replaceable Units (LRU)
Part Number Sort
2. RSPL - Line Maintenance Breakdown Parts (LMP)
Breakdown Part Number Sort
3. RSPL - Line Maintenance Breakdown Parts (LMP)
End Unit ATA Sort
4. RSPL - Standard Hardware Material (STD)
5. RSPL - Cockpit Push Button (CPB)
6. RSPL - Airbus Proprietary Parts (AIB)
7. W File ATA Sort

B) RSPL as spreadsheet files

8. RSPL - Line Replaceable Units

RSPL – Line Replaceable Units (LRU)*Part Number Sort*

PNR	DESCRIPTION		S P C	E S C	T C C	MTBUR	R I	S C R	M S T	Q P A	L T M	C U R	UNP	REC 1		REC 2		REC 3		ATA	C H G	APTL
														QTY	TOTAL	QTY	TOTAL	QTY	TOTAL			
160494-1	COOLER-OIL SEE CMM 499434 NHAPNR 3800708-1 ATA 49 99193 CSN 49910901 010	70210	2	2	H	36000	0	001	15	1	7	1	19319.23	000 (M)	0.00	000 (M)	0.00	000 (M)	0.00	49		0.0
2704506-2	MOTOR-STARTER SEE CMM 494120 CONTAINS LMP INCPNR 2704506-3 INC 2 V70210 NHAPNR 3800708-1 ATA 49 99193 CSN 49420901 020A	70210	2	2	H	5000	0	001	15	1	15	1	18496.00	001 (M)	18496.00	001 (M)	18496.00	001 (M)	18496.00	49		98.5
3291238-2	VALVE-SURGE CONTROL SEE CMM 495231 NHAPNR 3800708-1 ATA 49 99193 CSN 49510901 070	59364	2	2	H	7200	0	001	15	1	15	1	81996.00	001 (M)	81996.00	001 (M)	81996.00	001 (M)	81996.00	49		99.3
3291432-1	VALVE-LOAD CONTROL SEE CMM 495235 NHAPNR 3800708-1 ATA 49 99193 CSN 49510901 080	59364	2	2	H	8550	0	001	15	1	15	1	23369.00	001 (M)	23369.00	001 (M)	23369.00	001 (M)	23369.00	49		99.5
3616140-6	FAN ASSY SEE CMM 495107 INCPNR 3616140-10 INC 2 V99193 3616140-7 INC 2 V99193 NHAPNR 3800708-1 ATA 49 99193	99193	2	2	H	9000	0	001	15	1	15	1	47321.50	001 (M)	47321.50	001 (M)	47321.50	001 (M)	47321.50	49		99.5
3800708-1	APU-AUXILIARY POWER UNIT SEE IPC 492727 CONTAINS LMP CONTAINS LRU CSN 49110901 010	99193	2	2	H	6300	0	001	30	1	7	1	707420.00	001 (M)	707420.00	001 (M)	707420.00	001 (M)	707420.00	49	R	99.4
AIRLINE																					PAGE 258	
NOV 25/10																					49 / 1	

AIRBORNE AUXILIARY POWER

RSPL – Line Maintenance Breakdown Parts (LMP)
Breakdown Part Number Sort

PNR	DESCRIPTION	S P C	E S C	T C C	MTBUR	R R I	S C R	M S T	Q P A	L T M	C U R	UNP	REC 1		REC 2		REC 3		ATA	C H G	APTL
													QTY	TOTAL	QTY	TOTAL	QTY	TOTAL			
016001-1	CONTINUATION FIG.Item 10 080 FIG.Item 11 080 FIG.Item 15 080 FIG.Item 16 110 FIG.Item 17 110 RESTR 12281228 16981698 25682568 31043104 RESTR 08990899 09690969 14221422 15611561 20582058 22522252 25172517 27752775 CSN 25274402L090																				
016004	SPRING S4453 1 NHAPNR 1193000 ATA 25 S4453 FIG.Item 07 290 RESTR 12281228 16981698 25682568 31043104 RESTR 08990899 09690969 14221422 15611561 20582058 22522252 25172517 27752775 CSN 25274402L740	1	3	H	125000	1	399		1	28	8	72.00 74.73	000	0.00	000	0.00	000	0.00	25	C	0.0
016E1589-00	BRACKET NHAPNR 2100-1025-02 ATA 23 06141 FIG.Item 01 070 2100-1026-02 ATA 23 06141 FIG.Item 01 070 2100-4045-00 ATA 31 06141 FIG.Item 01 070 RESTR 42154215 42594259 RESTR 41184118 44574457 47014701 CSN 23713501E010	1	3	H	30000	0	399		4	30	1	33.00	001	33.00	002	66.00	002	66.00	23	R	89.6
020058	BOLT S4453 1 NHAPNR 1195000 ATA 25 S4453 FIG.Item 23 130 RESTR 12281228 16981698 25682568 CONTINUED	1	3	H	30000	0	399		1				001		001		001		25	R	91.0
AIRLINE																					PAGE 87
NOV 25/10																					

RSPL – Line Maintenance Breakdown Parts (LMP)

End Unit ATA Sort

PNR	DESCRIPTION	F0360	S P C	E S C	T S C	MTBUR	R R I	S C R	M S T	Q P A	L T M	C U R	UNP	REC 1		REC 2		REC 3		ATA	CH G	APTL
														QTY	TOTAL	QTY	TOTAL	QTY	TOTAL			
SPSA320-10-2-2	WINDOW-FIXED SEE LRU REC SEE ACIM 561125 CONTAINS LMP CONTAINS LRU	F0360								REF										56		
ASNA2026V3-18	□ BOLT SEE STD REC QTY per ASSY: 45 OSC 04795 2N935 C5543 FAPES3 OPLPFR HST755JB6-18 73197 CSN 56111201B100	F5442								REF											R	
ASNA2528-3	□ NUT SEE STD REC QTY per ASSY: 45 OSC 04795 2N935 C5543 F0188 F0224 OPLPFR HST1480-6 73197 CSN 53110104G020	F5442								REF											R	
SPSA320-6-2-2	□ WINDOW-FIXED SEE LRU REC SEE ACIM 561123 QTY per ASSY: 1 CSN 56111201B130A	F0360								REF												
SPSA320AR110	□ OUTER RETAINER QTY per ASSY: 1	F0360	1	2	H	18000	0	392		2	30	1	2200.00	003	6600.00	003	6600.00	003	6600.00		C	97.0
SPSA320AR120	□ INNER RETAINER QTY per ASSY: 1	F0360	1	2	H	18000	0	392		2	30	1	2200.00	003	6600.00	003	6600.00	003	6600.00		C	97.0
SPSA320AR130	□ SPACER QTY per ASSY: 45	F0360	1	2	H	18000	0	392		90	30	Q	22.00 30.49	063 1386.00 1920.87	1386.00 1920.87	063	1386.00 1920.87	064	1408.00 1951.36		R	94.5
SPSA320AR140	□ SEAL QTY per ASSY: 1	F0360	1	2	H	18000	0	392		2	30	1	2200.00	003	6600.00	003	6600.00	003	6600.00		C	97.0
AIRLINE																					PAGE 482	
NOV 25/10																					56 / 97	
WINDOWS																						

RSPL – Standard Hardware Material (STD)
Part Number Sort

PNR	DESCRIPTION	S P C	E T C	MTBUR	R R I	S C R	M S T	Q P A	L T M	C U R	UNP	REC 1		REC 2		REC 3		C H G	APTL
												QTY	TOTAL	QTY	TOTAL	QTY	TOTAL		
AN814-5J	CSN 71134270 040																		
	PLUG AND BLEEDER 80205	1	H	30000	0	999		20				000		000		000		27	
	OSC 01673 04795 14397 2N935																		
	50808 52930 C5543																		
	PPRPNR AS5169J05 V81343																		
	NHAPNR 2240A0000-01 ATA 27 D9893																		
EN6114V3-11	2241A0000-01 ATA 27 D9893																		
	CSN 27545902 030																		
EN6114V3-11	27545904 030																		
	BOLT 80205	1	H	30000	0	999		12				000		000		000		53	
EN6114V3-13	CSN 53190107B030																		
	BOLT, CSK 80205	1	H	30000	0	999		14				000		000		000		53	
EN6115V4-17	CSN 53190107B035																		
	BOLT, PRD 80205	1	H	30000	0	999		2				000		000		000		57	
EN6115V4-18	CSN 57160506 120A																		
	BOLT, CSK 80205	1	H	30000	0	999		2				000		000		000		57	
NAS1004-1A	CSN 57160508B045																		
	BOLT 80205	1	H	14000	0	999		12				000		000		000		71	
NAS1021C3	OSC 86735																		
	CSN 71404172 020																		
NAS1021N04	NUT 80205	1	H	30000	0	999		1				000		000		000		29	
	OSC 04795 2N935 99167 C5543																		
NAS1021N04	NHAPNR 772722E ATA 29 99167																		
	CSN 29245205A180																		
NAS1021N04	NUT 80205	1	H	30000	0	999		16				000		000		000		32	
	OSC 04795 2N935 C5543 K0654																		
AIRLINE	32111110F080																		
	32111110G080																		
PAGE 121																			

RSPL – Cockpit Push Buttons (CPB)

Part Number Sort

PNR	DESCRIPTION	S P C	E S C	T C	MTBUR	R R I	S C R	M S T	Q P A	L T M	C U R	UNP	REC 1		REC 2		REC 3		ATA	C H G	APTL		
													QTY	TOTAL	QTY	TOTAL	QTY	TOTAL					
ABS0951A0LP026	LIGHT-INDICATOR OSC 04795 2N935 81590 C5543 OPLPNR 101VL11BP026Y00 VF0214 CSN 73250801A060	FAPE3	1	2	H	30000	0	999		4	150	1	237.00	001	237.00	001	237.00	001	237.00	73			
ABS0951A0LP030	LIGHT-INDICATOR OSC 04795 2N935 81590 C5543 OPLPNR 101VL11BP030Y00 VF0214 CSN 32610801A020	FAPE3	1	2	H	30000	0	999		4	90	1	237.00	001	237.00	001	237.00	001	237.00	32			
ABS0951A0LP045	LIGHT-INDICATOR OSC 04795 2N935 81590 C5543 OPLPNR 101VL11BP045Y00 VF0214 CSN 33260801A020	FAPE3	1	2	H	30000	0	999		1	150	1	237.00	001	237.00	001	237.00	001	237.00	33			
ABS0951A0LP057	LIGHT-INDICATOR OSC 04795 2N935 81590 C5543 OPLPNR 101VL11BP057Y00 VF0214 CSN 26150801A010	FAPE3	1	2	H	30000	0	999		1	90	1	237.00	001	237.00	001	237.00	001	237.00	26			
ABS0951A0LP058	LIGHT-INDICATOR OSC 04795 2N935 81590 C5543 OPLPNR 101VL11BP058Y00 VF0214 CSN 35230801B050	FAPE3	1	2	H	30000	0	999		1	90	1	237.00	001	237.00	001	237.00	001	237.00	35			
ABS0951A0LP059	LIGHT-INDICATOR OSC 04795 2N935 81590 C5543 OPLPNR 101VL11BP059Y00 VF0214 CSN 24240801A010	FAPE3	1	2	H	30000	0	999		1	90	1	237.00	001	237.00	001	237.00	001	237.00	24			
ABS0951A0LP060	LIGHT-INDICATOR OSC 04795 2N935 81590 C5543 OPLPNR 101VL11BP060Y00 VF0214 CSN 33510801A030	FAPE3	1	2	H	30000	0	999		1	90	1	237.00	001	237.00	001	237.00	001	237.00	33			
ABS0951A0LP065	LIGHT-INDICATOR OSC 04795 2N935 81590 C5543 OPLPNR 101VL11BP065Y00 VF0214 CSN 27920802B080	FAPE3	1	2	H	30000	0	999		1	90	1	237.00	001	237.00	001	237.00	001	237.00	27			
AIRLINE																						PAGE 22	

RSPL – Airbus Proprietary Parts (AIB)

Part Number Sort

PNR	DESCRIPTION	FAPE3	S P C	E S C	T C H	MTBUR	R R I	S C R	M S T	Q P A	L T M	C U R	UNP	REC 1		REC 2		REC 3		ATA	C H G	APTL
														QTY	TOTAL	QTY	TOTAL	QTY	TOTAL			
A1111013820500	PATCH DPLPNR 5440GS CSN 27547230A220	FAPE3 VF7837	1	1	H	17000	0	999		32	30	1	12.30							27		
A2101037220000	SHACKLE CSN 21210401P250 21210402T300 21210402T344 21210418C300	FAPE3	1	2	H	240000	1	999		40	10	1	4.00							21		
A2101037220100	STUD CSN 21210401P240 21210402T290 21210402T342 21210418C290	FAPE3	1	1	H	200000	1	999		40	10	1	29.60							21		
A2101039620300	SLEEVE PPRPNR ASNA2634-203 CSN 21214030 070 21214032A090 21214034 050 21234016 160 21234019 080 21234027 030	FAPE3 VF5442	1	3	H	750000	1	999		12	90	1	69.20							21		
A2101039620500	SLEEVE PPRPNR ASNA2634-205 CSN 21214042 240 21232006A060 21232026A080 21234016 130	FAPE3 VF5442	1	3	H	280000	1	999		9	90	1	74.20							21		
A2101039620600	SLEEVE PPRPNR ASNA2634-206 CSN 21212033A070 21214033A180 21214033A181 21214033A182	FAPE3 VF5442	1	2	H	110000	2	999		9	90	1	74.20							21		
AIRLINE																						PAGE 30

W file

PNR	ATA	MFR	ADT	RTQ	LTM	UNP	REC QTY MB	REC QTY LS	MODEL01	TEM01	AMM01	UMT01	SMC01	RTQ01
98A08001006000	5	FAPE3	COLUMN-GRADUATED	1	90	0.00			A319	0820001617	0556006000	U		1
98D08103001000	5	FAPE3	WHEEL TOE-IN LINE BAR	1	105	8250.00			A319			U		1
98D08103001001	5	FAPE3	WHEEL TOE-IN LINE BAR	1	90	0.00			A319			U		1
98D08103001002	5	FAPE3	WHEEL TOE-IN LINE BAR	1	90	0.00			A319			U		1
98D08103001004	5	FAPE3	WHEEL TOE-IN LINE BAR	1	90	0.00			A319			U		1
98F05003000002	5	FAPE3	TARGET-MEASUREMENT	1	99	4010.00			A319	0556002223		U		1
SAV486-04	5	C6139	GAUSSMETER	1	22	607.00			A319			U		1
SAV890-71	5	C6139	DEMAGNETIZER-230V 50HZ	1	29	596.00			A319			U		1
SD7	5	8P674	DEMAGNETIZER - 110V 60HZ	1	90	0.00			A319	0554000606		U		1
98D07103000000	7	FAPE3	DYNAMOMETER-SAFETY STAY	1	105	6870.00	1		A319	0711000405	0711002000	C	4C	1
98D07103500000	7	FAPE3	JACK ADAPTER-FUSELAGE	1	113	258.00	1		A319	0711000101	0711002000	C	4C	1
98D07104000001	7	FAPE3	JACKING PAD SET	1	75	2180.00	1		A319	0711000203	0711002	C	4C	1
HAJ45P	7	H6394	JACK, AXLE - MLG A319 A320 A321	1	75	14750.00	1		A319	0700000000		W		1
TMHCP07-00-00	7	F8303	WHEEL CHANGE AXLE JACK	1	75	7060.00	1		A319	0712000202		L		1
950-318	8	F8537	DIGITAL PROTRACTOR	1	45	1020.00			A319				4C	1
98A08001004000	8	FAPE3	SET - PLUMB BOBS	1	113	6330.00			A319	0820001819	0556006000	U		1
98A08001005000	8	FAPE3	HOLDING SET - MEASURING CORD	1	113	2000.00			A319	0820002021	0556006000	U		1
98D08003000000	8	FAPE3	SET-PLUMB BOBS MLG NLG WHEELS	1	99	1040.00			A319	0820002223	0556006000	U		1
98D08103500000	8	FAPE3	SIGHTING RODS SET	1	99	30470.00			A319	0820000815	0556006000	U		1
98D08103501000	8	FAPE3	PLUMB LINE PYLON	1	99	22030.00			A319	0820000207	0556006000	U		1
98A09001002000	9	FAPE3	CABLE-TOWING, MLG	1	90	0.00			A319			U		1
98A09003000001	9	FAPE3	BAR-STEERING, NOSE WHEEL	1	106	3520.00			A319	0910001011	0910002000	U		1
98D09104000001	9	FAPE3	TOWING ATTACHMENT	1	75	4920.00			A319	0910001617	0910002000	U		1
98D09104001000	9	FAPE3	ATTACHMENT-DEBOGGING	1	90	6280.00			A319	0910000405	0910002000	U		1
98F09103500000	9	FAPE3	CABLE, TOWING-MLG	1	85	63170.00			A319	0910000000		U		1
D23156000	9	FAJX6	PIN-SAFETY	1	75	124.00			A319	0910000809	0911002000		DW	1
HTB318-321FA	9	H6394	TOW BAR, A318 A319 A320 A321 - FLY AWAY	1	85	8620.00	1		A319	0900000000		F		1
HTB319-320-321	9	H6394	TOW BAR, A319 A320 A321	1	46	7050.00	1		A319	0900000000		F		1
25-01-000	10	FA1W8	SUN SCREEN, SET-COCKPIT	1	20	2010.00			A319	1011001616		U		1
98A10001005000	10	FAPE3	COVER-PITOT PROBE	3	57	167.00	3		A319	1010000505	1011002000	L		3
98A10001013000	10	FAPE3	COVER-TOTAL TEMP SENSOR	2	71	152.00	2		A319	1010000606	1011002000	L		2

Recommended Spare Parts List – Spreadsheet Format

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	BQ	BR	BS	BT	BU
1	PNR	ATA	MFR	ADT	TPC	TPC_Ref	SPC	ESS	ATE	TCC	MTBUR	RRI	SCR	MST	CHG	MSN	MSN	MSN	MSN
1476	106-1-1100-02	49	D2638	ACTUATOR	CMM	491651	2	2		H	61538	0	1	10	C	1	1	1	1
1477	3886188-2	49	99193	ACTUATOR-IGV	CMM	495007	2	2		H	29000	0	1	30		1	1	1	1
1478	3800708-1	49	99193	APU-AUXILIARY POWER UNIT	IPC	492727	2	2		H	6300	0	1	30	R	1	1	1	1
1479	94830-04	49	13636	BRACKET-FWD	CMM	491214	2	2		H	150000	0	1	15		1	1	1	1
1480	94830-05	49	13636	BRACKET-FWD	CMM	491214	2	2		H	150000	0	1	15		1	1	1	1
1481	94830-06	49	13636	BRACKET-REAR	CMM	491214	2	2		H	150000	0	1	15		1	1	1	1
1482	3876132-13	49	99193	CABLE ASSY-IGNITION	CMM	494119	2	3		H	63000	0	10	15		1	1	1	1
1483	3860864-1	49	99193	CLUTCH-ASSY-STARTER			6	2		H	18000	0	10	15	R	1	1	1	1
1484	655CC04A0Y00	49	F0214	CONTACTOR-SINGLE POLE	ACMM	243123	6	2		H	340000	0	10	15		2	2	2	2
1485	441921-4	49	06848	CONTROL ASSY-FUEL	CMM	493099	2	2		H	7200	0	1	15		1	1	1	1
1486	160494-1	49	70210	COOLER-OIL	CMM	499434	2	2		H	36000	0	1	15		1	1	1	1
1487	3888394-221204	49	D4829	ECB-ELECTRONIC CONTROL BOX,VERSATILE	CMM	496370	2	2		AT	6000	0	1	15	R	1	1	1	1
1488	3888058-5	49	99193	EXCITER-IGNITION	CMM	494109	2	2		H	38000	0	1	15		1	1	1	1
1489	3616140-6	49	99193	FAN ASSY	CMM	495107	2	2		H	9000	0	1	15		1	1	1	1
1490	94830-09	49	13636	ISOLATOR-VIBRATION	CMM	492017	2	2		H	153846	0	1	15		1	1	1	1
1491	94830-10	49	13636	ISOLATOR-VIBRATION	CMM	492017	2	2		H	153846	0	1	15		1	1	1	1
1492	94830-11	49	13636	ISOLATOR-VIBRATION	CMM	492017	2	2		H	153846	0	1	15		1	1	1	1
1493	3876287-1	49	99193	MODULE-DATA MEMORY	CMM	496065	2	2		H	45000	0	1	15		1	1	1	1
1494	4131020-4	49	81833	MODULE-LUBE	CMM	499057	2	2		H	13400	0	1	15	R	1	1	1	1
1495	2704506-2	49	70210	MOTOR-STARTER	CMM	494120	2	2		H	5000	0	1	15		1	1	1	1
1496	3830416-1	49	99193	NOZZLE-FUEL	CMM	493001	2	2		H	205000	0	1	15	R	10	10	10	10
1497	S5505F01	49	F6172	RACK			1	3		H	125000	0	999	0		1	1	1	1
1498	4141028-3	49	81833	VALVE-DE OIL SOLENOID	ACMM	499055	6	2		H	45000	0	10	15		1	1	1	1
1499	3291432-1	49	59364	VALVE-LOAD CONTROL	CMM	495235	2	2		H	8550	0	1	15		1	1	1	1
1500	692546-4	49	99193	VALVE-SOLENOID			2	3		H	45000	0	1	15		1	1	1	1
1501	3291238-2	49	59364	VALVE-SURGE CONTROL	CMM	495231	2	2		H	7200	0	1	15		1	1	1	1

© AIRBUS S.A.S. All rights reserved. Confidential and proprietary document.

This document and all information contained herein is the sole property of AIRBUS S.A.S. No intellectual property rights are granted by the delivery of this document or the disclosure of its content. This document shall not be reproduced or disclosed to a third party without the express written consent of AIRBUS S.A.S.

This document and its content shall not be used for any purpose other than that for which it is supplied. The statements made herein do not constitute an offer. They are based on the mentioned assumptions and are expressed in good faith. Where the supporting grounds for these statements are not shown, AIRBUS S.A.S. will be pleased to explain the basis thereof.

AIRBUS, its logo, A300, A310, A318, A319, A320, A321, A330, A340, A350, A380, A400M are registered trademarks



Airbus Services Solutions
Integrated Provisioning Services
Weg beim Jäger 150
22335 Hamburg, Germany
email: material-readiness.provisioning@airbus.com
Phone: + 49 (40) 50 76 –0