

ToTokGameSDK API Document

(iOS)

Name	Date	version	remark
Yuanjun	2020.3.18	1.0.0	created
Yuanjun	2020.3.27	1.0.1	improvements
Yuanjun	2020.3.31	1.0.2	add game invite
Yuanjun	2020.4.07	1.0.3	add single sign-on
Yuanjun	2020.4.12	1.0.4	improvements
Yuanjun	2020.4.17	1.0.5	1.launch animation deleted (2.1.1) 2.add agreement view (4.1) & delete 4.2 of last version 3.Domain Changed 4.add login with apple (4.2)
Yuanjun	2020.4.27	1.0.6	improvements
Yuanjun	2020.5.13	1.0.7	improvements
Yuanjun	2020.5.27	1.0.8	SDK rename 1.Replace ToTokGameManager class name with TTKGameManager 2.Replace TTGCLoginType_ToTok with TTGCLoginType_TTk

1. Description and definition

1.1 API call

Every API is called by [TTkGameManager defaultManager] instance

1.2 Callback

`error` is a common field for every callback class. if `error` equals to `nil`, it means the api call is success.

1.3 Callback classes:

1.3.1 Login Callback

```
class: TTGCUserCompletionHandler
fields:
userInfo //the user information
error
```

1.3.2 Receive Notification Callback

```
class: TTGCNotificationCompletionHandler
fields:
result //the notification message
error
```

1.3.3 Logout Callback

```
class: TTGCLogoutCompleteHandler
fields:
success // BOOL type, indicate operation result
```

```
error
```

1.3.4 Get Friends Callback

```
class: TTGCFriendsCompletionHandler  
fields:  
list          //fields list, contains from 0 -> N friend object  
error
```

1.3.5 Share Callback

```
class: TTGCShareCompleteHandler  
fields:  
success       // BOOL type, indicate operation result  
error
```

1.3.6 Payment Callback

```
class: TTGCOderProgressHandler  
fields:  
TTGCOderStatus //Payment order status
```

1.3.7 Payment Result Callback

```
class: TTGCOderCompletionHandler  
fields:  
orderInfo     //the payment order object  
error
```

1.3.8 AppVersion Info Callback

```
class: TTGCVersionCompletionHandler  
fields:  
hasNewVersion //has new version
```

```
versionInfo      //the version detail information. class model <TTGCApVersion>

error
```

1.3.9 Common Callback

```
class:  TTGCCompletionHandler

fields:

result      //operation result

error
```

1.4 Errors

TTGCPlatformErrorType_Unknow	unkown error
TTGCPlatformErrorType_AuthorizeFailed	authorized failed
TTGCPlatformErrorType_ForUserInfoFailed	request user data failed
TTGCPlatformErrorType_LoginFailed	login failed
TTGCPlatformErrorType_FriendsListFailed	get firends failed
TTGCPlatformErrorType_MessageSendFailed	send message failed
TTGCPlatformErrorType_PayFailed	payment failed
TTGCPlatformErrorType_ShareFailed	share failed
TTGCPlatformErrorType_NotInstall	app is not installed
TTGCPlatformErrorType_NotNetWork	network exception
TTGCPlatformErrorType_SourceError	third error
TTGCPlatformErrorType_NoPermission	no permissions
TTGCPlatformErrorType_UnauthorizedRequest	unauthorized request, need login.

2. Setup Initialize (must)

2.1 Launch

Methods in AppDelegate are implement like below:

2.1.1 Setup Configuration:

The launch animation for SDK-1.0.5 has been removed and the specific launch animation needs to be implemented by the game developers.

```
- (BOOL)application:(UIApplication *)application
didFinishLaunchingWithOptions:(NSDictionary *)launchOptions {

    // set SDK Api Enviroment

    [[TTkGameManager defaultManager] setServerDomainTest];

    // set Pay Enviroment

    [[TTkGameManager defaultManager] setPayEnvironmentTest];

    // open log

    [[TTkGameManager defaultManager] openLogInfo];


    // launch SDK

    NSString *appId = @"xxxxx";

    NSString *appSecret = @"xxxxxxx";

    NSString *gameid = @"xxxxxxx";

    [[TTkGameManager defaultManager] setupWithAppId:appId Secret:appSecret
GameId:gameid Application:application Options:launchOptions];

    return YES;
}
```

2.1.2 External Callback:

```
- (BOOL)application:(UIApplication *)app openURL:(NSURL *)url
options:(NSDictionary<UIApplicationOpenURLOptionsKey,id> *)options {

    return [[TTkGameManager defaultManager] application:app openURL:url
options:options];
}
```

2.1.3 App Events:

```
- (void)applicationDidEnterBackground:(UIApplication *)application {  
    [[TTkGameManager defaultManager] applicationDidEnterBackground:application];  
}  
  
- (void)applicationWillEnterForeground:(UIApplication *)application {  
    [[TTkGameManager defaultManager] applicationWillEnterForeground:application];  
}  
  
- (void)applicationDidBecomeActive:(UIApplication *)application {  
    [[TTkGameManager defaultManager] applicationDidBecomeActive:application];  
}  
  
- (void)applicationWillTerminate:(UIApplication *)application {  
    [[TTkGameManager defaultManager] applicationWillTerminate:application];  
}
```

2.1.4 Push Register:

```
- (void)application:(UIApplication *)application  
didRegisterForRemoteNotificationsWithDeviceToken:(NSData *)deviceToken {  
    [[TTkGameManager defaultManager] registerDeviceToken:deviceToken];  
}  
  
- (void)application:(UIApplication *)application  
didReceiveRemoteNotification:(NSDictionary *)userInfo fetchCompletionHandler:(void  
(^)(UIBackgroundFetchResult))completionHandler {  
    [[TTkGameManager defaultManager] application:application  
didReceiveRemoteNotification:userInfo];  
}
```

2.1.5 Universal Link:

```
- (BOOL)application:(UIApplication *)application continueUserActivity:(NSUserActivity  
*)userActivity restorationHandler:(void (^) (NSArray<id<UIUserActivityRestoring>> *  
_Nullable))restorationHandler {  
    return [[TTkGameManager defaultManager] application:application  
continueUserActivity:userActivity restorationHandler:restorationHandler];  
}
```

2.2 Check App Version

After SDK is launched, be sure to check the version to ensure that the current version is available. If you need to force upgrade, you can go to the appstore to download the latest version, otherwise the SDK function may not be available.

example

```
- (void)checkVersion {  
    [[TTkGameManager defaultManager] checkAppVersionCompletion:^(BOOL hasNewVersion,  
TTGCAppVersionModel * _Nullable versionInfo, NSError * _Nullable error) {  
        if (hasNewVersion) {  
            BOOL forceUpdate = versionInfo.forceUpdate;  
            if (forceUpdate) {  
                // If you need to force update, you cannot continue to use it, and you need  
to jump to the appstore to update.  
                // Open appstore  
                [[TTkGameManager defaultManager]  
openAppStoreWithStoreIdentifier:@"xxx"];  
            } else {  
                // If update is not required, you can optionally prompt for an upgrade.  
            }  
        }  
    }  
};  
}
```

2.2.1 Check Version

Method	checkAppVersionCompletion
Callback	<div>TTGCVersionCompletionHandler</div> <div>hasNewVersion // has new version <BOOL></div> <div>versionInfo // the version detail information. class model <TTGCAppVersion></div> <div>build // app build code</div> <div>version // app new version</div> <div>versionInfo // the version information</div> <div>forceUpdate // need to force upgrade <BOOL></div> <div>currentVersionCode // current version code</div>

2.2.2 Open AppStore

Method	openAppStoreWithStoreIdentifier
Params	identifier //App Store item identifier (NSNumber) of the product

3. API: Configuration

3.1 Enbale Log Output

```
[[TTkGameManager defaultManager] openLogInfo];
```

3.2 Disable Log Output(default)

```
[[TTkGameManager defaultManager] closeLogInfo];
```

3.3 Set Test Environment

```
[[TTkGameManager defaultManager] setServerDomainTest];
```

3.4 Set Production Environment(default)

```
[[TTkGameManager defaultManager] setServerDomainProduction];
```

3.5 Set Sandbox Payment

```
[[TTkGameManager defaultManager] setPayEnvironmentTest];
```

3.6 Set Production Payment(default)

```
[[TTkGameManager defaultManager] setPayEnvironmentProduction];
```


4. API: Login&User Info

User must agree the User Agreement & Privacy before do Login action

4.1 Show Agreement View

```
- (IBAction)agreement:(id)sender {  
    [[TTkGameManager defaultManager] showAgreementView];  
}
```

4.2 Login with Apple

Login with Apple only supports iOS13 and higher.

Method	loginWithAppleCompletion
Callback	TTGCUUserCompletionHandler

example:

```
- (IBAction)appleLogin:(id)sender {  
    TTGCHUD_NO_Stop(@"login...")  
    __weak __typeof(self) weakSelf = self;  
    [[TTkGameManager defaultManager] loginWithAppleCompletion:^(id _Nonnull userInfo,  
NSError * _Nonnull error) {  
        if (!error) {  
            //login success  
            TTGCHUD_SUCCESS(@"success")  
            [weakSelf closeLoginView];  
        } else {  
            //error info  
            TTGCHUD_HINT([error.userInfo objectForKey:@"errorMsg"]);  
        }  
    }  
}
```

```

    }];
}

```

4.3 Login with GameCenter

Method	loginWithGameCenterCompletion
Callback	TTGCUUserCompletionHandler

example:

```

- (void)gamecenterLogin {
    TTGCHUD_NO_Stop(@"login...")

    __weak __typeof(self) weakSelf = self;

    [[TTkGameManager defaultManager] loginWithGameCenterCompletion:^(id _Nonnull
userInfo, NSError * _Nonnull error) {
        if (!error) {
            //login success

            TTGCHUD_HINT(@"success")

            [weakSelf closeLoginView];
        } else {
            //error info

            TTGCHUD_HINT([error.userInfo objectForKey:@"errorMsg"]);
        }
    }];
}

```

4.4 Login with Facebook

Method	loginWithFacebookCompletion
Callback	TTGCUUserCompletionHandler

example:

```

- (void)facebookLogin {
    TTGCHUD_NO_Stop(@"login...")

```

```

    __weak __typeof(self) weakSelf = self;

    [[TTkGameManager defaultManager] loginWithFacebookCompletion:^(id _Nonnull
userInfo, NSError * _Nonnull error) {

        if (!error) {

            //login success

            TTGCHUD_HINT(@"success")

            [weakSelf closeLoginView];

        } else {

            //error info

            TTGCHUD_HINT([error.userInfo objectForKey:@"errorMsg"]);

        }

    }];
}

```

4.5 Login with Guest

Method	guestLoginCompletion
Callback	TTGCUserCompletionHandler

example

```

- (void)guestLogin {

    TTGCHUD_NO_Stop(@"login...")

    __weak __typeof(self) weakSelf = self;

    [[TTkGameManager defaultManager] guestLoginCompletion:^(id _Nonnull userInfo,
NSError * _Nonnull error) {

        if (!error) {

            //login success

            TTGCHUD_HINT(@"success")

            [weakSelf closeLoginView];

        } else {

            //error info

            TTGCHUD_Stop

        }

    }];
}

```

```
}
```

4.6 Get User Info

Method	userInfoCompletion
Callback	TTGCUUserCompletionHandler
Params	<div>TTGCUUserModel</div> <div><div>userType</div><div>user type (TTGCLoginType by 3.7)</div></div> <div><div>userId</div><div>user's identifier</div></div> <div><div>nickname</div><div>nickname</div></div> <div><div>photoUrl</div><div>head image url</div></div> <div><div>pushOff</div><div>push switch 0:push switch on 1:push switch off</div></div>

example

```
- (void)getUserInfo {
    TTGCHUD_NO_Stop(@"")

    [[TTkGameManager defaultManager] userInfoCompletion:^(id _Nullable userInfo,
    NSError * _Nullable error) {
        if (!error) {
            TTGCHUD_HINT(@"success")

            TTGCUUserModel *model = userInfo;

            [self freshUserInfo:model];
        } else {
            //error info

            TTGCHUD_HINT([error.userInfo objectForKey:@"errorMsg"]);
        }
    }];
}
```

4.7 Get Login Type

Method	loginType
Return	TTGCLoginType

Definition:

Enum	TTGCLoginType
Description	Enum type for Login
Enum Values	
TTGCLoginType_unloggedIn	not login
TTGCLoginType_TTk	ToTok user
TTGCLoginType_GameCenter	GameCenter player
TTGCLoginType_Facebook	Facebook user
TTGCLoginType_Guest	ToTokGame guest

example:

```
- (void)showLoginView {  
    if ([[TTkGameManager defaultManager] loginType] == TTGCLoginType_unloggedIn) {  
        //unlogged in and show login UI  
        [self backgroundUI];  
        [self loginView];  
    } else {  
        dispatch_after(dispatch_time(DISPATCH_TIME_NOW, (int64_t)(2.5 * NSEC_PER_SEC)),  
dispatch_get_main_queue(), ^{  
            [self getUserInfo];  
        });  
    }  
}
```

4.8 Notification of offline

Method	accountKickedNotification
Callback	TTGCAccountKickedHandler

example:

```
[[TTkGameManager defaultManager] accountKickedNotification:^(NSString * _Nullable  
information) {
```

```

        //Your account has been logged in on another device, please login again.

        TTGCHUD_HINT(information);

        [self showLoginView];

    }];

```

5. API: Logout

Method	logout
Callback	TTGCLogoutCompleteHandler

example:

```

- (IBAction)logout:(id)sender {
    TTGCHUD_NO_Stop(@"logout...")

    [[TTkGameManager defaultManager] logout:^(BOOL success, NSError * _Nullable error) {
        if (success) {
            TTGCHUD_HINT(@"success")

            [self showLoginView];
        } else {
            //error info

            NSLog(@"%@",error.userInfo);

            TTGCHUD_HINT([error.userInfo objectForKey:@"errorMsg"]);
        }
    }];
}

```

6. API: Game Payment

6.1 Product Purchase

Order Status Definition:

TTGCOderStatus_ProductQuerying	query product
TTGCOderStatus_Generating	order init
TTGCOderStatus_ProductPurchasing	order in trading progress
TTGCOderStatus_ProductPurchased	order purchased
TTGCOderStatus_ReceiptChecking	order verifying

Method	buyProductWithSKU: Progress: Completion:
Params	
sku	String,product id
Progress	TTGCOderProgressHandler
Completion	TTGCOderCompletionHandler <pre> class TTGCOderModel orderId orderRef //transaction_id channel //1 env //0=sandbox, 1=production sku //product id amount //price createTime payTime cancelTime status //0=order created, 1=order payed, 2=order reset </pre>

remark:

the Game Server should send the product to user's account after the order be payed, then check the order status by server api, Order status check is necessary for anti-spam

Server API: <ToTokGame Server API Document (to Game Developer)>

example:

```
- (IBAction)pay:(id)sender {
    TTGCHUD_NO_Stop(@"pay...")

    [[TTkGameManager defaultManager] buyProductWithSKU:@"LangChaoJD001"]
Progress:^(TTGCOderStatus orderStatus) {

    NSLog(@"order status: %ld", (long)orderStatus);

} Completion:^(id _Nullable orderInfo, NSError * _Nullable error) {

    if (orderInfo) {

        TTGCHUD_HINT(@"success")

    }

    if (error) {

        NSLog(@"%@", error.userInfo);

        TTGCHUD_HINT([error.userInfo objectForKey:@"errorMsg"]);

    }

}];
}
```

6.2 Query Order

Method	queryOrderWithOrderId: Completion:
Params	
orderId	the order's id
Completion	TTGCOderCompletionHandler TTGCOderModel by 5.1

example:

```
- (IBAction)query:(id)sender {

    [[TTkGameManager defaultManager] queryOrderWithOrderId:@"xxx"]
Completion:^(id _Nullable orderInfo, NSError * _Nullable error) {

    if (orderInfo) {

        //get order info

    } else {

        //error message

    }

}];
}
```



```
}
```

7. API: SNS & Share

7.1 ToTok Friends

Not yet open

7.2 Share

Share to Facebook, WhatsApp.

ToTok Sharing is not yet open.

7.2.1 Share To Facebook

Method	facebookShareMessage: completion:
Params	
Message	1.TTGCSocialFBInvite quote //message text
	2.TTGCSocialFBImages photoImage //photo image <UIImage>
	3.TTGCSocialFBFriendsGameInvite inviteString //invite message text
completion	TTGCShareCompleteHandler

example:

```
// share invite link to facebook
- (IBAction)fbShare:(id)sender {
    TTGCSocialFBInvite *obj = [[TTGCSocialFBInvite alloc] init];
    obj.quote = @"Join us";
```

```

        [[TTkGameManager defaultManager] facebookShareMessage:obj completion:^(BOOL success,
NSError * _Nullable error) {

            if (success) {

            } else {

                if (error) {

                    TTGCHUD_HINT([error.userInfo objectForKey:@"errorMsg"]);

                }

            }

        }];
    }

//share image to facebook

- (IBAction)fbpic:(id)sender {

    UIImage *image = [UIImage imageNamed:@"totokgame_logo_1024"];

    TTGCSocialFBImages *obj = [[TTGCSocialFBImages alloc] init];

    obj.photoImage = image;

    [[TTkGameManager defaultManager] facebookShareMessage:obj completion:^(BOOL success,
NSError * _Nullable error) {

        if (success) {

        } else {

            if (error) {

                TTGCHUD_HINT([error.userInfo objectForKey:@"errorMsg"]);

            }

        }

    }];
}

//send invite to facebook friends(This feature is only available if you are logged in with
Facebook)

- (IBAction)fbGameInviteFriends:(id)sender {

    TTGCSocialFBFriendsGameInvite *obj = [[TTGCSocialFBFriendsGameInvite alloc] init];

    obj.inviteString = @"join us";

    [[TTkGameManager defaultManager] facebookShareMessage:obj completion:^(BOOL success,
NSError * _Nullable error) {

        if (success) {

            TTGCHUD_SUCCESS(@"sent the message");

        }

    }];
}

```

```

        } else {
            if (error) {
                TTGCHUD_HINT([error.userInfo objectForKey:@"errorMsg"]);
            }
        }
    }
}];
}

```

7.2.2 Share To WhatsApp

Method	whatsappShareMessage: completion:
Params	
Message	1.TTGCSocialWAInvite contentString // whatsapp message text
	2.TTGCSocialWAImages photos //NSArray image <UIImage>
completion	TTGCShareCompleteHandler

example:

```

// share invite link to whatsapp
- (IBAction)whatsappShare:(id)sender {
    TTGCSocialWAInvite *obj = [[TTGCSocialWAInvite alloc] init];
    obj.contentString = @"play games";
    [[TTkGameManager defaultManager] whatsappShareMessage:obj completion:^(BOOL success,
NSError * _Nullable error) {
        if (success) {
        } else {
            if (error) {
                TTGCHUD_HINT([error.userInfo objectForKey:@"errorMsg"]);
            }
        }
    }
}];

// share picture to whatsapp

```

```

- (IBAction)wapic:(id)sender {
    TTGCSocialWAImages *obj = [[TTGCSocialWAImages alloc] init];
    UIImage *image = [UIImage imageNamed:@"totokgame_logo_1024"];
    obj.photos = @[image];
    [[TTkGameManager defaultManager] whatsappShareMessage:obj completion:^(BOOL success,
NSError * _Nullable error) {
        if (success) {
        } else {
            if (error) {
                TTGCHUD_HINT([error.userInfo objectForKey:@"errorMsg"]);
            }
        }
    }];
}

```

8. API: Push

8.1 Register

in AppDelegate:

```

- (void)application:(UIApplication *)application
didRegisterForRemoteNotificationsWithDeviceToken:(NSData *)deviceToken {
    [[TTkGameManager defaultManager] registerDeviceToken:deviceToken];
}

```

8.2 Receive Push Message

Method	getRemoteNotification
Callback	TTGCNotificationCompletionHandler

example:

```

- (void)recieveMessage {

```

```
[[TTkGameManager defaultManager] getRemoteNotification:^(id _Nullable result,  
NSError * _Nullable error) {  
    //Receive a push message and can customize the event based on the message.  
    //Do something ...  
}];  
}
```