

Copyright Notice

These slides are distributed under the Creative Commons License.

[DeepLearning.AI](#) makes these slides available for educational purposes. You may not use or distribute these slides for commercial purposes. You may make copies of these slides and use or distribute them for educational purposes as long as you cite [DeepLearning.AI](#) as the source of the slides.

For the rest of the details of the license, see <https://creativecommons.org/licenses/by-sa/2.0/legalcode>



deeplearning.ai

Setting up your ML application

Train/dev/test sets

Applied ML is a highly iterative process


layers

hidden units

learning rates

activation functions


• • •



NLP, Vision, Speech, Structural Data

└─┬──┘
 | | | |
 ↓ ↓ ↓ ↓
 Ads Search Security Logistic ...

Train/dev/test sets



Mismatched train/test distribution

Certs

↙
Training set:

Cat pictures from
webpages }

↓ ↓
Dev/test sets:

Cat pictures from
users using your app }



→ Make sure dev and test come from Same Distribution.

↓ ↓
train / dev "test"
↑ ↑

train / test
↓ ↖
→ train / dev

Not having a test set might be okay. (Only dev set.)






deeplearning.ai

Setting up your ML application


Bias/Variance

Bias and Variance



Bias and Variance

Cat classification



Train set error:

1%

15% \swarrow

15%

0.5%

Dev set error:

11%

16% \swarrow

30%

1%

high variance
 \uparrow

high bias
 \uparrow

high bias
& high variance


low bias
low variance
 \uparrow

Human: ~0%

Optimal (Bayes) error: ~~~0%~~ 15%

Blurry images

High bias and high variance






deeplearning.ai

Setting up your ML application

Basic “recipe” for machine learning

Basic recipe for machine learning





deeplearning.ai

Regularizing your neural network

Regularization

Logistic regression

$$\min_{w,b} J(w,b)$$

$$\underline{w} \in \mathbb{R}^{n_x}, \underline{b} \in \mathbb{R}$$

λ = regularization parameter
lambda lambda

$$J(w,b) = \underbrace{\frac{1}{m} \sum_{i=1}^m \ell(y^{(i)}, \hat{y}^{(i)})}_{\text{common used}} + \frac{\lambda}{2m} \underbrace{\|w\|_2^2}$$

~~$+\frac{\lambda}{2m} b^2$~~
omit

just a single number

common used

L_2 regularization

$$\underline{\|w\|_2^2} = \sum_{j=1}^{n_x} w_j^2 = w^T w \leftarrow$$

L_1 regularization

$$\frac{\lambda}{2m} \sum_{j=1}^{n_x} |w_j| = \frac{\lambda}{2m} \|w\|_1$$

w will be sparse
compress the model

Neural network

$$\rightarrow J(w^{[1]}, b^{[1]}, \dots, w^{[L]}, b^{[L]}) = \underbrace{\frac{1}{n} \sum_{i=1}^n \ell(y^{(i)}, \hat{y}^{(i)})}_{\text{loss}} + \underbrace{\frac{\lambda}{2n} \sum_{l=1}^L \|w^{[l]}\|_F^2}_{\text{weight decay}}$$

$$\|w^{[l]}\|_F^2 = \sum_{i=1}^{n^{[l]}} \sum_{j=1}^{n^{[l-1]}} (w_{ij}^{[l]})^2$$

$w^{[l]}: \begin{matrix} n^{[l]} & n^{[l-1]} \\ \uparrow & \uparrow \end{matrix}$

"Frobenius norm"

$\|\cdot\|_2^2$

$\|\cdot\|_F^2$

$$dw^{[l]} = \left[(\text{from backprop}) + \frac{\lambda}{n} w^{[l]} \right]$$

$$\frac{\partial J}{\partial w^{[l]}} = dw^{[l]}$$

$$\rightarrow w^{[l]} := w^{[l]} - \alpha dw^{[l]}$$

"Weight decay"

$$\begin{aligned} w^{[l]} &:= w^{[l]} - \alpha \left[(\text{from backprop}) + \frac{\lambda}{n} w^{[l]} \right] \\ &= w^{[l]} - \frac{\alpha \lambda}{n} w^{[l]} - \alpha (\text{from backprop}) \\ &= \underbrace{\left(1 - \frac{\alpha \lambda}{n} \right)}_{< 1} w^{[l]} - \alpha (\text{from backprop}) \end{aligned}$$




deeplearning.ai

Regularizing your neural network

Why regularization reduces overfitting




How does regularization prevent overfitting?




$$J(w^{(L)}, b^{(L)}) = \frac{1}{n} \sum_{i=1}^n \ell(y^{(i)}, \hat{y}^{(i)}) + \frac{\lambda}{2n} \sum_{l=1}^L \|w^{(l)}\|_F^2$$

penalize large weights

$$\downarrow w^{(L)} \approx 0$$



How does regularization prevent overfitting?







deeplearning.ai

Regularizing your neural network

Dropout regularization

Dropout regularization



Implementing dropout ("Inverted dropout")

Illustrate with layer $l=3$. keep-prob = 0.8 0.2

→ $d3 = \text{np.random.rand}(a3.\text{shape}[0], a3.\text{shape}[1]) < \text{keep-prob}$

$a3 = \text{np.multiply}(a3, d3)$ # $a3 \neq d3$.

→ $a3 /= \text{keep-prob}$ ←

50 units. \leadsto 10 units shut off

$$z^{[4]} = w^{[4]} \cdot \underbrace{a^{[3]}}_{\text{reduced by } 20\%} + b^{[4]}$$

\uparrow

reduced by 20%

$$/= \underline{0.8}$$

Test

Making predictions at test time

$$a^{[0]} = X$$

No drop out.

don't want output to be random

$$\begin{aligned} z^{[1]} &= W^{[1]} a^{[0]} + b^{[1]} \\ a^{[1]} &= g^{[1]}(z^{[1]}) \\ z^{[2]} &= W^{[2]} \underline{a^{[1]}} + b^{[2]} \\ a^{[2]} &= \dots \end{aligned}$$

↓
y

/= keep-prob



deeplearning.ai



Regularizing your neural network

Understanding dropout

Why does drop-out work?

Intuition: Can't rely on any one feature, so have to spread out weights.

\leadsto Shrink weights. b_2
norm of 7 7





deeplearning.ai


Regularizing your neural network

Other regularization methods

Data augmentation





4



Early stopping

Separate tasks and tools
for these two tasks,
easier to decompose and search over
(Early stopping can't)

Orthogonalization.






deeplearning.ai

Setting up your
optimization problem

Normalizing inputs

Normalizing training sets

$$x = \begin{bmatrix} x_1 \\ x_2 \end{bmatrix}$$



Subtract mean:

$$\bar{\mu} = \frac{1}{n} \sum_{i=1}^n x^{(i)}$$

$$x := x - \mu$$

Use $\text{var } \mu \sigma^2$

Normalize variance

$$\sigma^2 = \frac{1}{n} \sum_{i=1}^n x^{(i)} * x^{(i)T}$$

← element-wise


$$x /= \sigma^2$$

to normalize test set.

Why normalize inputs?



$$J(w, b) = \frac{1}{m} \sum_{i=1}^m \mathcal{L}(\hat{y}^{(i)}, y^{(i)})$$

Unnormalized:




$w_1: x_1: \underline{1 \dots 1000} \leftarrow$
 $w_2: x_2: \underline{0 \dots 1} \leftarrow$
 $\quad \quad \quad -1 \dots 1$

Normalized:



$x_1: 0 \dots 1$
 $x_2: -1 \dots 1$
 $x_3: 1 \dots 2$






deeplearning.ai

Setting up your
optimization problem

Vanishing/exploding
gradients

Vanishing/exploding gradients



$g(z) = z$ $b^{(L)} = 0$

$\hat{y} = w^{(L,2)} \underbrace{w^{(L-1,2)} w^{(L-2,2)} \dots w^{(2,2)} w^{(1,2)}}_{a^{(1,2)}} x$

1.5^L
 0.5^L

$w^{(1,2)} > I$

$w^{(2,2)} < I$ $\begin{bmatrix} 0.9 & \\ & 0.9 \end{bmatrix}$


$w^{(2,2)} = \begin{bmatrix} 1.5 & 0 \\ 0 & 1.5 \end{bmatrix}$

$z^{(1,2)} = w^{(1,2)} x$
 $a^{(1,2)} = g(z^{(1,2)}) = z^{(1,2)}$
 $a^{(2,2)} = g(z^{(2,2)}) = g(w^{(2,2)} a^{(1,2)})$

$\hat{y} = w^{(L,2)} \begin{bmatrix} 1.5 & 0 \\ 0 & 1.5 \end{bmatrix}^{L-1} x$

$1.5^{L-1} x$
 $0.5^{L-1} x$

Single neuron example



$$z = w_1 x_1 + w_2 x_2 + \dots + w_n x_n$$

large $n \rightarrow$ Smaller w_i

$$\text{Var}(w_i) = \frac{1}{n} \frac{2}{n}$$

$$\underline{w^{[L]}} = \text{np.random.randn}(\text{shape}) * \text{np.sqrt}\left(\frac{2}{n^{[L-1]}}\right)$$

ReLU $g^{[L]}(z) = \text{ReLU}(z)$

Other variants:

tanh

$$\frac{1}{n^{[L-1]}}$$

Xavier initialization ↑

$$\sqrt{\frac{2}{n^{[L-1]} + n^{[L]}}}$$

↑




deeplearning.ai

Setting up your optimization problem

Numerical approximation of gradients

Checking your derivative computation

I $f(\theta) = \theta^3$
 $\theta \in \mathbb{R}.$



$$g(\theta) = \frac{d}{d\theta} f(\theta) = f'(\theta)$$

$g(\theta) = 3\theta^2$

$\frac{dw}{db}$

$g(\theta) = 3 \cdot (1)^2 = 3$
 when $\theta = 1$

$$\frac{f(\theta + \epsilon) - f(\theta)}{\epsilon} \approx g(\theta)$$


$$\frac{(1.01)^3 - 1^3}{0.01} = \frac{1.030301 - 1}{0.01} = \frac{0.0301}{0.01} = 3.0301 \approx 3$$

Annotations: 0.0301 is the numerator, 3.1 and 3.2 are the integer parts of the division, and 3 is the final result.

$\theta = 1$
 $\theta + \epsilon = 1.01$

Checking your derivative computation

$$\underline{f(\theta) = \theta^3}$$



$$\left[\frac{f(\theta + \epsilon) - f(\theta - \epsilon)}{2\epsilon} \approx \underline{g(\theta)} \right]$$

$$\frac{(1.01)^3 - (0.99)^3}{2(0.01)} = 3.0001 \approx 3$$

$$g(\theta) = 3\theta^2 = 3$$

approx error: 0.0001

(prev slide: 3.0301 , error: 0.03)

$$\left\{ \begin{array}{l} f'(\theta) = \lim_{\epsilon \rightarrow 0} \frac{f(\theta + \epsilon) - f(\theta - \epsilon)}{2\epsilon} \quad \begin{array}{l} O(\epsilon^2) \\ 0.01 \\ \underline{0.0001} \end{array} \quad \left| \quad \frac{f(\theta + \epsilon) - f(\theta)}{\epsilon} \quad \begin{array}{l} \text{error: } O(\epsilon) \\ 0.01 \end{array} \end{array} \right.$$



deeplearning.ai

Setting up your
optimization problem

Gradient Checking

Gradient check for a neural network

Take $W^{[1]}, b^{[1]}, \dots, W^{[L]}, b^{[L]}$ and reshape into a big vector θ .
Concatenate

$$J(w^{[1]}, b^{[1]}, \dots, w^{[L]}, b^{[L]}) = J(\theta)$$

Take $dW^{[1]}, db^{[1]}, \dots, dW^{[L]}, db^{[L]}$ and reshape into a big vector $d\theta$.
concatenate

Is $d\theta$ the gradient of $J(\theta)$?

Gradient checking (Grad check)

$$J(\theta) = J(\theta_1, \theta_2, \theta_3, \dots)$$

for each i :

$$\rightarrow \underline{d\theta_{\text{approx}}[i]} = \frac{J(\theta_1, \theta_2, \dots, \overset{\downarrow}{\theta_i + \epsilon}, \dots) - J(\theta_1, \theta_2, \dots, \overset{\downarrow}{\theta_i - \epsilon}, \dots)}{2\epsilon}$$

$$\approx \underline{d\theta[i]} = \frac{\partial J}{\partial \theta_i} \quad | \quad d\theta_{\text{approx}} \approx d\theta$$

Checks

$$\rightarrow \frac{\|d\theta_{\text{approx}} - d\theta\|_2}{\|d\theta_{\text{approx}}\|_2 + \|d\theta\|_2}$$
$$\underline{\epsilon = 10^{-7}}$$

$$\approx \frac{10^{-7}}{10^{-5}} - \text{great!} \leftarrow$$
$$\rightarrow 10^{-3} - \text{worry.} \leftarrow$$



deeplearning.ai

Setting up your
optimization problem

Gradient Checking
implementation notes

Gradient checking implementation notes

- Don't use in training – only to debug

$$\frac{d\theta_{\text{approx}}[\vec{i}]}{\uparrow \uparrow} \longleftrightarrow \frac{d\theta[\vec{i}]}{\uparrow}$$

- If algorithm fails grad check, look at components to try to identify bug.

$$\frac{db^{[L]}}{\uparrow} \quad \frac{dW^{[L]}}{\uparrow}$$

- Remember regularization.

$$\underline{J(\theta)} = \frac{1}{n} \sum_i \ell(y^{(i)}, \hat{y}^{(i)}) + \frac{\lambda}{2n} \sum_l \|W^{[l]}\|_F^2$$

$d\theta = \text{gradient of } J \text{ wrt. } \theta$

- Doesn't work with dropout.

$$\underline{J} \quad \underline{\text{keep-prob} = 1.0}$$

- Run at random initialization; perhaps again after some training.

Doesn't work
well when

$$\underline{W, b \approx 0}$$