

9.3 Hierarchical Clustering


Machine Learning 1: Foundations

Marius Kloft (TUK)

1 Hierarchical Clustering



Disadvantage

Big problem in k -means: do not know the number of clusters in advance






Disadvantage

Big problem in k -means: do not know the number of clusters in advance





Disadvantage

Big problem in k -means: do not know the number of clusters in advance




Disadvantage

Big problem in k -means: do not know the number of clusters in advance



7 clusters





vs.


3 clusters

Disadvantage

Big problem in k -means: do not know the number of clusters in advance



7 clusters



vs.


3 clusters

Quiz: what to do?

Hierarchical Clustering


Hierarchical Clustering

- Generates a tree (“hierarchy”) of clusters



Hierarchical Clustering

- Generates a tree (“hierarchy”) of clusters



- do not need to specify number of clusters

Hierarchical Clustering

1: **function** HIERARCHICALCLUSTERING(inputs $\mathbf{x}_1, \dots, \mathbf{x}_n \in \mathbb{R}^d$)

Hierarchical Clustering

- 1: **function** HIERARCHICALCLUSTERING(inputs $\mathbf{x}_1, \dots, \mathbf{x}_n \in \mathbb{R}^d$)
- 2: assign each input to a cluster

Hierarchical Clustering


```
1: function HIERARCHICALCLUSTERING(inputs  $\mathbf{x}_1, \dots, \mathbf{x}_n \in \mathbb{R}^d$ )  
2:   assign each input to a cluster  
3:   repeat  
4:     link the two clusters with minimal distance
```

Hierarchical Clustering

```
1: function HIERARCHICALCLUSTERING(inputs  $\mathbf{x}_1, \dots, \mathbf{x}_n \in \mathbb{R}^d$ )  
2:   assign each input to a cluster  
3:   repeat  
4:     link the two clusters with minimal distance  
5:   until finished
```



Hierarchical Clustering

```
1: function HIERARCHICALCLUSTERING(inputs  $\mathbf{x}_1, \dots, \mathbf{x}_n \in \mathbb{R}^d$ )  
2:   assign each input to a cluster  
3:   repeat  
4:     link the two clusters with minimal distance  
5:   until finished  
6:   return tree of cluster linkages  
7: end function
```





Hierarchical Clustering

```
1: function HIERARCHICALCLUSTERING(inputs  $\mathbf{x}_1, \dots, \mathbf{x}_n \in \mathbb{R}^d$ )  
2:   assign each input to a cluster  
3:   repeat  
4:     link the two clusters with minimal distance  
5:   until only a single root cluster left  
6:   return tree of cluster linkages  
7: end function
```



Hierarchical Clustering

```
1: function HIERARCHICALCLUSTERING(inputs  $\mathbf{x}_1, \dots, \mathbf{x}_n \in \mathbb{R}^d$ )  
2:   assign each input to a cluster  
3:   repeat  
4:     link the two clusters with minimal distance  
5:   until only a single root cluster left  
6:   return tree of cluster linkages  
7: end function
```



How to measure distance between two clusters?


Hierarchical Clustering

Quiz: How to measure distance $d(i, j)$ between two clusters i and j ?


Hierarchical Clustering

Quiz: How to measure distance $d(i, j)$ between two clusters i and j ?


- Simple linkage



- Average linkage




- Complete linkage




Hierarchical Clustering

Quiz: How to measure distance $d(i, j)$ between two clusters i and j ?


- Simple linkage



- Average linkage



- Complete linkage




- Let $S_j \subseteq \{\mathbf{x}_1, \dots, \mathbf{x}_n\}$ be the set of inputs contained in the j th cluster


Hierarchical Clustering

Quiz: How to measure distance $d(i, j)$ between two clusters i and j ?


- Simple linkage



- Average linkage



- Complete linkage




- ▶ Let $S_j \subseteq \{\mathbf{x}_1, \dots, \mathbf{x}_n\}$ be the set of inputs contained in the j th cluster
- ▶ **Simple linkage**: $d(i, j) := \min_{\mathbf{x} \in S_i, \tilde{\mathbf{x}} \in S_j} \|\mathbf{x} - \tilde{\mathbf{x}}\|$


Hierarchical Clustering

Quiz: How to measure distance $d(i, j)$ between two clusters i and j ?


- Simple linkage



- Average linkage



- Complete linkage




- ▶ Let $S_j \subseteq \{\mathbf{x}_1, \dots, \mathbf{x}_n\}$ be the set of inputs contained in the j th cluster
- ▶ **Simple linkage:** $d(i, j) := \min_{\mathbf{x} \in S_i, \tilde{\mathbf{x}} \in S_j} \|\mathbf{x} - \tilde{\mathbf{x}}\|$
- ▶ **Average linkage:** $d(i, j) := \text{mean}_{\mathbf{x} \in S_i, \tilde{\mathbf{x}} \in S_j} \|\mathbf{x} - \tilde{\mathbf{x}}\|$


Hierarchical Clustering

Quiz: How to measure distance $d(i, j)$ between two clusters i and j ?


- Simple linkage



- Average linkage



- Complete linkage




- ▶ Let $S_j \subseteq \{\mathbf{x}_1, \dots, \mathbf{x}_n\}$ be the set of inputs contained in the j th cluster
- ▶ **Simple linkage:** $d(i, j) := \min_{\mathbf{x} \in S_i, \tilde{\mathbf{x}} \in S_j} \|\mathbf{x} - \tilde{\mathbf{x}}\|$
- ▶ **Average linkage:** $d(i, j) := \text{mean}_{\mathbf{x} \in S_i, \tilde{\mathbf{x}} \in S_j} \|\mathbf{x} - \tilde{\mathbf{x}}\|$
- ▶ **Complete linkage:** $d(i, j) := \max_{\mathbf{x} \in S_i, \tilde{\mathbf{x}} \in S_j} \|\mathbf{x} - \tilde{\mathbf{x}}\|$


Hierarchical Clustering

Quiz: How to measure distance $d(i, j)$ between two clusters i and j ?


- Simple linkage



- Average linkage



- Complete linkage




- ▶ Let $S_j \subseteq \{\mathbf{x}_1, \dots, \mathbf{x}_n\}$ be the set of inputs contained in the j th cluster
- ▶ **Simple linkage:** $d(i, j) := \min_{\mathbf{x} \in S_i, \tilde{\mathbf{x}} \in S_j} \|\mathbf{x} - \tilde{\mathbf{x}}\|^2$
- ▶ **Average linkage:** $d(i, j) := \text{mean}_{\mathbf{x} \in S_i, \tilde{\mathbf{x}} \in S_j} \|\mathbf{x} - \tilde{\mathbf{x}}\|^2$
- ▶ **Complete linkage:** $d(i, j) := \max_{\mathbf{x} \in S_i, \tilde{\mathbf{x}} \in S_j} \|\mathbf{x} - \tilde{\mathbf{x}}\|^2$
- ▶ Note: again, all this can be kernelized...

Conclusion

Clustering:


- Organizing data into groups



Conclusion

Clustering:

- Organizing data into groups




k -means:

- Alternatingly, assign inputs to closest cluster center and re-compute centers

Conclusion

Clustering:

- ▶ Organizing data into groups




k -means:

- ▶ Alternatingly, assign inputs to closest cluster center and re-compute centers
- ▶ Can be kernelized
- ▶ Can be deepified using transfer learning

Conclusion

Clustering:

- ▶ Organizing data into groups



k -means:

- ▶ Alternatingly, assign inputs to closest cluster center and re-compute centers
- ▶ Can be kernelized
- ▶ Can be deepified using transfer learning

Hierarchical clustering:

- ▶ Consider clusters at various scales
- ▶ Helpful when the number of clusters is unknown

Refs I