

Algorithmns and Datastructures

Runtime analysis Minsort / Heapsort, Induction

Albert-Ludwigs-Universität Freiburg



**UNI
FREIBURG**

Prof. Dr. Rolf Backofen

Bioinformatics Group / Department of Computer Science
Algorithmns and Datastructures, March 2016

Feedback

Exercises

Lecture

Runtime Example

Minsort

Basic Operations

Runtime analysis

Minsort

Heapsort

Introduction to Induction

Logaritms

Feedback

Exercises

Lecture

Runtime Example

Minsort

Basic Operations

Runtime analysis

Minsort

Heapsort

Introduction to Induction

Logaritms

Feedback from the exercises

Feedback from the lecture

Feedback

Exercises

Lecture

Runtime Example

Minsort

Basic Operations


Runtime analysis

Minsort


Heapsort

Introduction to Induction

Logaritms




How long does the program run?



How long does the program run?

- In the last lecture we had a schematic
- **Observation:** It is going to be “disproportionally” slower the more numbers are being sorted



How long does the program run?

- In the last lecture we had a schematic
- **Observation:** It is going to be “disproportionally” slower the more numbers are being sorted
- How can we say more precisely what is happening?

How can we analyze the runtime?

- Ideally we have a formula which provides the runtime of the program for an specific input

How can we analyze the runtime?

- Ideally we have a formula which provides the runtime of the program for an specific input
- **Problem:** The runtime is also depending on many other influences, especially:
 - Which kind of computer is the code executed on
 - What is running in the background
 - Which compiler is used to compile the code

How can we analyze the runtime?

- Ideally we have a formula which provides the runtime of the program for an specific input
- **Problem:** The runtime is also depending on many other influences, especially:
 - Which kind of computer is the code executed on
 - What is running in the background
 - Which compiler is used to compile the code
- **Abstraction 1:** Analyze the number of basic operations, rather than analyzing the runtime

Feedback

Exercises

Lecture

Runtime Example

Minsort

Basic Operations

Runtime analysis

Minsort

Heapsort

Introduction to Induction

Logaritms

Incomplete list of basic operations:

- Arithmetic operation, for example: $a + b$
- Assignment of variables, for example: $x = y$
- Function call, for example: *minsort(lst)*

Intuitive:

lines of code

Better:

lines of machine
code

Best:

process cycles

Important:

The actual runtime has to be roughly proportional to the number of operations.

Feedback

Exercises

Lecture

Runtime Example

Minsort

Basic Operations

Runtime analysis

Minsort

Heapsort

Introduction to Induction

Logaritms

How many operations does *Minsort* need?

- **Abstraction 2:** We calculate the upper (lower) bound, rather than counting the operations exactly

Reason: Runtime is approximated by number of basic operations, but we can still infer:

- Upper bound
- Lower bound

How many operations does *Minsort* need?

- **Abstraction 2:** We calculate the upper (lower) bound, rather than counting the operations exactly

Reason: Runtime is approximated by number of basic operations, but we can still infer:

- Upper bound
 - Lower bound
-
- **Basic Assumption:**
 - n is size of the input data (i.e. array)
 - $T(n)$ number of operations for input n

How many operations does *Minsort* need?

- **Observation:** The number of operations depends only on the size n of the array and not on the content!

How many operations does *Minsort* need?

- **Observation:** The number of operations depends only on the size n of the array and not on the content!
- **Claim:** There are constants C_1 and C_2 such that:

$$C_1 \cdot n^2 \leq T(n) \leq C_2 \cdot n^2$$

How many operations does *Minsort* need?


- **Observation:** The number of operations depends only on the size n of the array and not on the content!
- **Claim:** There are constants C_1 and C_2 such that:

$$C_1 \cdot n^2 \leq T(n) \leq C_2 \cdot n^2$$

- This is called “quadratic runtime” (due to n^2)


Runtime Example

Number of Steps
(runtime [s])




$$T(n) = \frac{1}{2}n^2 + 3n$$

Runtime Example



Runtime Example



We declare:

- Runtime of operations: $T(n)$
- Number of Elements: n
- Constants: C_1 (lower bound), C_2 (upper bound)
$$C_1 \cdot n^2 \leq T(n) \leq C_2 \cdot n^2$$
- Number of operations in round i : T_i




Figure: *Minsort* at the iteration $i = 4$. We have to check $n - 3$ elements

Compares at each
iteration:




Figure: *Minsort* with start data

Compares at each iteration:

$$T_1 \leq C'_2 \cdot (n - 0)$$





Figure: *Minsort* at iteration $i = 1$




Compares at each iteration:

$$T_1 \leq C'_2 \cdot (n - 0)$$

$$T_2 \leq C'_2 \cdot (n - 1)$$

Figure: *Minsort* at iteration $i = 2$




Compares at each iteration:

$$T_1 \leq C'_2 \cdot (n - 0)$$

$$T_2 \leq C'_2 \cdot (n - 1)$$

$$T_3 \leq C'_2 \cdot (n - 2)$$

Figure: *Minsort* at iteration $i = 3$



Compares at each iteration:

$$T_1 \leq C'_2 \cdot (n - 0)$$

$$T_2 \leq C'_2 \cdot (n - 1)$$

$$T_3 \leq C'_2 \cdot (n - 2)$$

$$T_4 \leq C'_2 \cdot (n - 3)$$

Figure: Minsort at iteration $i = 4$




Figure: *Minsort* at iteration i

Compares at each iteration:

$$T_1 \leq C'_2 \cdot (n - 0)$$

$$T_2 \leq C'_2 \cdot (n - 1)$$

$$T_3 \leq C'_2 \cdot (n - 2)$$

$$T_4 \leq C'_2 \cdot (n - 3)$$

\vdots

$$T_{n-1} \leq C'_2 \cdot 2$$

$$T_n \leq C'_2 \cdot 1$$




Figure: Minsort at iteration

Compares at each iteration:

$$T_1 \leq C'_2 \cdot (n - 0)$$

$$T_2 \leq C'_2 \cdot (n - 1)$$

$$T_3 \leq C'_2 \cdot (n - 2)$$

$$T_4 \leq C'_2 \cdot (n - 3)$$

\vdots

$$T_{n-1} \leq C'_2 \cdot 2$$

$$T_n \leq C'_2 \cdot 1$$

$$T(n) = C'_2 \cdot (T_1 + \dots + T_n) \leq \sum_{i=1}^n (C'_2 \cdot i)$$

Alternative: Analyse the Code:

```
def minsort(elements):  
    for i in range(0, len(elements)-1):  
        minimum = i  
  
        for j in range(i+1, len(elements)):  
            if elements[j] < elements[minimum]:  
                minimum = j  
  
        if minimum != i:  
            elements[i], elements[minimum] = \  
                elements[minimum], elements[i]  
  
    return elements
```

Alternative: Analyse the Code:

```
def minsort(elements):  
    for i in range(0, len(elements)-1):  
        minimum = i  
  
        for j in range(i+1, len(elements)):  
            if elements[j] < elements[minimum]:  
                minimum = j  
        } const.  
        runtime  
  
    if minimum != i:  
        elements[i], elements[minimum] = \  
            elements[minimum], elements[i]  
  
    return elements
```

Alternative: Analyse the Code:

```
def minsort(elements):  
    for i in range(0, len(elements)-1):  
        minimum = i  
  
        for j in range(i+1, len(elements)):  
            if elements[j] < elements[minimum]:  
                minimum = j  
  
        if minimum != i:  
            elements[i], elements[minimum] = \  
                elements[minimum], elements[i]  
  
    return elements
```

} const. runtime } $n-i-1$ times

Alternative: Analyse the Code:

```
def minsort(elements):  
    for i in range(0, len(elements)-1):  
        minimum = i  
        for j in range(i+1, len(elements)):  
            if elements[j] < elements[minimum]:  
                minimum = j  
        if minimum != i:  
            elements[i], elements[minimum] = \  
                elements[minimum], elements[i]  
    return elements
```

const. runtime } n-i-1 times } n-1 times

Alternative: Analyse the Code:

```
def minsort(elements):  
    for i in range(0, len(elements)-1):  
        minimum = i  
        for j in range(i+1, len(elements)):  
            if elements[j] < elements[minimum]:  
                minimum = j  
        if minimum != i:  
            elements[i], elements[minimum] = \  
                elements[minimum], elements[i]  
    return elements
```

Diagram illustrating the runtime analysis of the Minsort algorithm:

- The inner loop (for j in range(i+1, len(elements))) is highlighted in a darker teal box. It is annotated with "const. runtime" and "n-i-1 times".
- The outer loop (for i in range(0, len(elements)-1)) is annotated with "n-1 times".

$$T(n) \leq \sum_{i=0}^{n-2} \sum_{j=i+1}^{n-1} C'_2$$

Alternative: Analyse the Code:

```
def minsort(elements):  
    for i in range(0, len(elements)-1):  
        minimum = i  
  
        for j in range(i+1, len(elements)):  
            if elements[j] < elements[minimum]:  
                minimum = j  
  
        if minimum != i:  
            elements[i], elements[minimum] = \  
                elements[minimum], elements[i]  
  
    return elements
```

const. runtime } n-i-1 times } n-1 times

$$T(n) \leq \sum_{i=0}^{n-2} \sum_{j=i+1}^{n-1} C'_2 = \sum_{i=0}^{n-2} (n-i-1) \cdot C'_2$$

Alternative: Analyse the Code:

```
def minsort(elements):  
    for i in range(0, len(elements)-1):  
        minimum = i  
  
        for j in range(i+1, len(elements)):  
            if elements[j] < elements[minimum]:  
                minimum = j  
  
        if minimum != i:  
            elements[i], elements[minimum] = \  
                elements[minimum], elements[i]  
  
    return elements
```

const. runtime } n-i-1 times } n-1 times

$$T(n) \leq \sum_{i=0}^{n-2} \sum_{j=i+1}^{n-1} C'_2 = \sum_{i=0}^{n-2} (n-i-1) \cdot C'_2 = \sum_{i=1}^{n-1} (n-i) \cdot C'_2$$

Alternative: Analyse the Code:

```
def minsort(elements):  
    for i in range(0, len(elements)-1):  
        minimum = i  
        for j in range(i+1, len(elements)):  
            if elements[j] < elements[minimum]:  
                minimum = j  
        if minimum != i:  
            elements[i], elements[minimum] = \  
                elements[minimum], elements[i]  
    return elements
```

const. runtime } n-i-1 times } n-1 times

$$T(n) \leq \sum_{i=0}^{n-2} \sum_{j=i+1}^{n-1} C'_2 = \sum_{i=0}^{n-2} (n-i-1) \cdot C'_2 = \sum_{i=1}^{n-1} (n-i) \cdot C'_2 \leq \sum_{i=1}^n i \cdot C'_2$$

Alternative: Analyse the Code:

```
def minsort(elements):  
    for i in range(0, len(elements)-1):  
        minimum = i  
  
        for j in range(i+1, len(elements)):  
            if elements[j] < elements[minimum]:  
                minimum = j  
  
        if minimum != i:  
            elements[i], elements[minimum] = \  
                elements[minimum], elements[i]  
  
    return elements
```

const. runtime } n-i-1 times } n-1 times

$$T(n) \leq \sum_{i=0}^{n-2} \sum_{j=i+1}^{n-1} C'_2 = \sum_{i=0}^{n-2} (n-i-1) \cdot C'_2 = \sum_{i=1}^{n-1} (n-i) \cdot C'_2 \leq \sum_{i=1}^n i \cdot C'_2$$

Remark: C'_2 is cost of comparison \Rightarrow assumed constant

Proof of upper bound: $T(n) \leq C_2 \cdot n^2$

$$T(n) \leq \sum_{i=1}^n C'_2 \cdot i$$

Proof of upper bound: $T(n) \leq C_2 \cdot n^2$

$$\begin{aligned} T(n) &\leq \sum_{i=1}^n C'_2 \cdot i \\ &= C'_2 \cdot \sum_{i=1}^n i \end{aligned}$$

Proof of upper bound: $T(n) \leq C_2 \cdot n^2$

$$\begin{aligned} T(n) &\leq \sum_{i=1}^n C'_2 \cdot i \\ &= C'_2 \cdot \sum_{i=1}^n i \\ &\quad \downarrow \text{Small Gauss sum} \\ &= C'_2 \cdot \frac{n(n+1)}{2} \end{aligned}$$

Proof of upper bound: $T(n) \leq C_2 \cdot n^2$

$$\begin{aligned} T(n) &\leq \sum_{i=1}^n C'_2 \cdot i \\ &= C'_2 \cdot \sum_{i=1}^n i \\ &\quad \downarrow \text{Small Gauss sum} \\ &= C'_2 \cdot \frac{n(n+1)}{2} \\ &\leq C'_2 \cdot \frac{n(n+n)}{2}, \quad 1 \leq n \end{aligned}$$

Proof of upper bound: $T(n) \leq C_2 \cdot n^2$

$$\begin{aligned} T(n) &\leq \sum_{i=1}^n C'_2 \cdot i \\ &= C'_2 \cdot \sum_{i=1}^n i \\ &\quad \downarrow \text{Small Gauss sum} \\ &= C'_2 \cdot \frac{n(n+1)}{2} \\ &\leq C'_2 \cdot \frac{n(n+n)}{2}, \quad 1 \leq n \\ &= C'_2 \cdot \frac{2 \cdot n^2}{2} \end{aligned}$$

Proof of upper bound: $T(n) \leq C_2 \cdot n^2$

$$\begin{aligned} T(n) &\leq \sum_{i=1}^n C'_2 \cdot i \\ &= C'_2 \cdot \sum_{i=1}^n i \\ &\quad \downarrow \text{Small Gauss sum} \\ &= C'_2 \cdot \frac{n(n+1)}{2} \\ &\leq C'_2 \cdot \frac{n(n+n)}{2}, \quad 1 \leq n \\ &= C'_2 \cdot \frac{2 \cdot n^2}{2} = C'_2 \cdot n^2 \end{aligned}$$

Excursion - Small Gauss Formula

Proof of lower bound: $C_1 \cdot n^2 \leq T(n)$

Like for the upper boundary there exists a C_1 . Summation analysis is the same

$$T(n) \geq \sum_{i=1}^{n-1} C'_1 \cdot (n-i)$$

Proof of lower bound: $C_1 \cdot n^2 \leq T(n)$

Like for the upper boundary there exists a C_1 . Summation analysis is the same

$$T(n) \geq \sum_{i=1}^{n-1} C'_1 \cdot (n-i) = C'_1 \sum_{i=1}^{n-1} i$$

Proof of lower bound: $C_1 \cdot n^2 \leq T(n)$

Like for the upper boundary there exists a C_1 . Summation analysis is the same

$$\begin{aligned} T(n) &\geq \sum_{i=1}^{n-1} C'_1 \cdot (n-i) = C'_1 \sum_{i=1}^{n-1} i \\ &\geq C'_1 \cdot \frac{(n-1) \cdot n}{2} \end{aligned}$$

Proof of lower bound: $C_1 \cdot n^2 \leq T(n)$

Like for the upper boundary there exists a C_1 . Summation analysis is the same, **only final approximation differs**

$$\begin{aligned} T(n) &\geq \sum_{i=1}^{n-1} C'_1 \cdot (n-i) = C'_1 \sum_{i=1}^{n-1} i \\ &\geq C'_1 \cdot \frac{(n-1) \cdot n}{2} \end{aligned}$$

How do we get to n^2 ?

Proof of lower bound: $C_1 \cdot n^2 \leq T(n)$

Like for the upper boundary there exists a C_1 . Summation analysis is the same, **only final approximation differs**

$$\begin{aligned} T(n) &\geq \sum_{i=1}^{n-1} C'_1 \cdot (n-i) = C'_1 \sum_{i=1}^{n-1} i \\ &\geq C'_1 \cdot \frac{(n-1) \cdot n}{2} \quad \text{How do we get to } n^2? \\ &\quad \Downarrow \quad n-1 \geq \frac{n}{2} \text{ for } n \geq 2 \end{aligned}$$

Proof of lower bound: $C_1 \cdot n^2 \leq T(n)$

Like for the upper boundary there exists a C_1 . Summation analysis is the same, **only final approximation differs**

$$\begin{aligned} T(n) &\geq \sum_{i=1}^{n-1} C'_1 \cdot (n-i) = C'_1 \sum_{i=1}^{n-1} i \\ &\geq C'_1 \cdot \frac{(n-1) \cdot n}{2} \quad \text{How do we get to } n^2? \\ &\quad \Downarrow \quad n-1 \geq \frac{n}{2} \text{ for } n \geq 2 \\ &\geq C'_1 \cdot \frac{n \cdot n}{2 \cdot 2} \end{aligned}$$

Proof of lower bound: $C_1 \cdot n^2 \leq T(n)$

Like for the upper boundary there exists a C_1 . Summation analysis is the same, **only final approximation differs**

$$\begin{aligned} T(n) &\geq \sum_{i=1}^{n-1} C'_1 \cdot (n-i) = C'_1 \sum_{i=1}^{n-1} i \\ &\geq C'_1 \cdot \frac{(n-1) \cdot n}{2} \quad \text{How do we get to } n^2? \\ &\quad \Downarrow \quad n-1 \geq \frac{n}{2} \text{ for } n \geq 2 \\ &\geq C'_1 \cdot \frac{n \cdot n}{2 \cdot 2} = \frac{C'_1}{4} \cdot n^2 \end{aligned}$$

Runtime Analysis:

- Upper bound: $T(n) \leq C'_2 \cdot n^2$

Runtime Analysis:

- Upper bound: $T(n) \leq C'_2 \cdot n^2$
- Lower bound: $\frac{C'_1}{4} \cdot n^2 \leq T(n)$

Runtime Analysis:

- Upper bound: $T(n) \leq C'_2 \cdot n^2$
- Lower bound: $\frac{C'_1}{4} \cdot n^2 \leq T(n)$

Summarized:

$$\frac{C'_1}{4} \cdot n^2 \leq T(n) \leq C'_2 \cdot n^2$$

Quadratic runtime proven:

$$C_1 \cdot n^2 \leq T(n) \leq C_2 \cdot n^2$$

- The runtime is growing quadratic with the number of elements n in the list

- The runtime is growing quadratic with the number of elements n in the list
- Let constants C_1 and C_2 for which $C_1 \cdot n^2 \leq T(n) \leq C_2 \cdot n^2$

- The runtime is growing quadratic with the number of elements n in the list
- Let constants C_1 and C_2 for which $C_1 \cdot n^2 \leq T(n) \leq C_2 \cdot n^2$
- $2 \times$ elements $\Rightarrow 4 \times$ runtime

- The runtime is growing quadratic with the number of elements n in the list
- Let constants C_1 and C_2 for which $C_1 \cdot n^2 \leq T(n) \leq C_2 \cdot n^2$
- $2 \times$ elements $\Rightarrow 4 \times$ runtime
 - $C = 1$ ns (1 simple instruction ≈ 1 ns)

- The runtime is growing quadratic with the number of elements n in the list
- Let constants C_1 and C_2 for which $C_1 \cdot n^2 \leq T(n) \leq C_2 \cdot n^2$
- $2 \times$ elements $\Rightarrow 4 \times$ runtime
 - $C = 1$ ns (1 simple instruction ≈ 1 ns)
 - $n = 10^6$ (1 million numbers = 4 MB with 4 B/number)
 - $C \cdot n^2 = 10^{-9} \text{ s} \cdot 10^{12} = 10^3 \text{ s} = 16.7 \text{ min}$

- The runtime is growing quadratic with the number of elements n in the list
- Let constants C_1 and C_2 for which $C_1 \cdot n^2 \leq T(n) \leq C_2 \cdot n^2$
- $2 \times$ elements $\Rightarrow 4 \times$ runtime
 - $C = 1 \text{ ns}$ (1 simple instruction $\approx 1 \text{ ns}$)
 - $n = 10^6$ (1 million numbers = 4 MB with 4 B/number)
 - $C \cdot n^2 = 10^{-9} \text{ s} \cdot 10^{12} = 10^3 \text{ s} = 16.7 \text{ min}$
 - $n = 10^9$ (1 billion numbers = 4 GB)
 - $C \cdot n^2 = 10^{-9} \text{ s} \cdot 10^{18} = 10^9 \text{ s} = 31.7 \text{ years}$

- The runtime is growing quadratic with the number of elements n in the list
- Let constants C_1 and C_2 for which $C_1 \cdot n^2 \leq T(n) \leq C_2 \cdot n^2$
- $2 \times$ elements $\Rightarrow 4 \times$ runtime
 - $C = 1 \text{ ns}$ (1 simple instruction $\approx 1 \text{ ns}$)
 - $n = 10^6$ (1 million numbers = 4 MB with 4 B/number)
 - $C \cdot n^2 = 10^{-9} \text{ s} \cdot 10^{12} = 10^3 \text{ s} = 16.7 \text{ min}$
 - $n = 10^9$ (1 billion numbers = 4 GB)
 - $C \cdot n^2 = 10^{-9} \text{ s} \cdot 10^{18} = 10^9 \text{ s} = 31.7 \text{ years}$
- **Quadratic runtime = “big” problems unsolvable**

Feedback

Exercises

Lecture

Runtime Example

Minsort

Basic Operations

Runtime analysis

Minsort

Heapsort

Introduction to Induction

Logaritms

Intuitive to extract minimum:

- **Minsort:** To determine the minimum value we have to iterate through all the unsorted elements.

Intuitive to extract minimum:

- **Minsort:** To determine the minimum value we have to iterate through all the unsorted elements.
- **Heapsort:** The root node is always the smallest (minheap). We only need to repair a part of the full tree after an delete operation

Intuitive to extract minimum:

- **Minsort:** To determine the minimum value we have to iterate through all the unsorted elements.
- **Heapsort:** The root node is always the smallest (minheap). We only need to repair a part of the full tree after an delete operation

Formal:

Intuitive to extract minimum:

- **Minsort:** To determine the minimum value we have to iterate through all the unsorted elements.
- **Heapsort:** The root node is always the smallest (minheap). We only need to repair a part of the full tree after an delete operation

Formal:

- Let $T(n)$ be the runtime for the *Heapsort* algorithm with n elements

Intuitive to extract minimum:

- **Minsort:** To determine the minimum value we have to iterate through all the unsorted elements.
- **Heapsort:** The root node is always the smallest (minheap). We only need to repair a part of the full tree after an delete operation

Formal:

- Let $T(n)$ be the runtime for the *Heapsort* algorithm with n elements
- On the next pages we will proof $T(n) \leq C \cdot n \log_2 n$

Depth of a binary tree:

- **Depth d :** longest path through the tree
- Complete binary tree has $n = 2^d - 1$ nodes
- Example: $d = 4$
 $\Rightarrow n = 2^4 - 1 = 15$




Figure: Binary tree with 15 nodes

Feedback

Exercises

Lecture

Runtime Example

Minsort

Basic Operations

Runtime analysis

Minsort

Heapsort

Introduction to Induction

Logaritms



Basics:

Basics:

- You want to show assumption $A(n)$ is valid $\forall n \in \mathbb{N}$

Basics:

- You want to show assumption $A(n)$ is valid $\forall n \in \mathbb{N}$
- We show induction in two steps:

Basics:

- You want to show assumption $A(n)$ is valid $\forall n \in \mathbb{N}$
- We show induction in two steps:
 - 1 **Induction basis:** we show that our assumption is valid at one point (for example: $n = 1, A(1)$).

Basics:

- You want to show assumption $A(n)$ is valid $\forall n \in \mathbb{N}$
- We show induction in two steps:
 - 1 **Induction basis:** we show that our assumption is valid at one point (for example: $n = 1, A(1)$).
 - 2 **Induction step:** we show that the assumption is valid for all n (normally one step forward: $n = n + 1, A(1), \dots, A(n)$).

Basics:

- You want to show assumption $A(n)$ is valid $\forall n \in \mathbb{N}$
- We show induction in two steps:
 - 1 **Induction basis:** we show that our assumption is valid at one point (for example: $n = 1, A(1)$).
 - 2 **Induction step:** we show that the assumption is valid for all n (normally one step forward: $n = n + 1, A(1), \dots, A(n)$).
- If both has been proven, then $A(n)$ holds for all natural numbers n by **induction**

Claim:

A **complete** binary tree of depth d has $n(d) = 2^d - 1$ nodes

Claim:

A **complete** binary tree of depth d has $n(d) = 2^d - 1$ nodes

- **Induction basis:** Assumption holds for $d = 1$

Root



$$n(1) = 2^1 - 1 = 1$$

Figure: Tree of depth 1 has 1 node

Claim:

A **complete** binary tree of depth d has $n(d) = 2^d - 1$ nodes

- **Induction basis:** Assumption holds for $d = 1$

Root



$$n(1) = 2^1 - 1 = 1$$

\Rightarrow correct ✓

Figure: Tree of depth 1 has 1 node

Induction - Example 1



Number of nodes $n(d)$ in a binary tree with depth d :

- **Induction assumption:** $n(d) = 2^d - 1$

Induction - Example 1



Number of nodes $n(d)$ in a binary tree with depth d :

- **Induction assumption:** $n(d) = 2^d - 1$
- **Induction basis:** $n(1) = 2^1 - 1 = 2^1 - 1 = 1$ ✓

Induction - Example 1

Number of nodes $n(d)$ in a binary tree with depth d :

- **Induction assumption:** $n(d) = 2^d - 1$
- **Induction basis:** $n(1) = 2^1 - 1 = 2^0 - 1 = 1$ ✓
- **Induction step:** to show for $d := d + 1$





Figure: Binary tree with subtrees

Induction - Example 1

Number of nodes $n(d)$ in a binary tree with depth d :

- **Induction assumption:** $n(d) = 2^d - 1$
- **Induction basis:** $n(1) = 2^1 - 1 = 2^1 - 1 = 1$ ✓
- **Induction step:** to show for $d := d + 1$




$$n(d+1) = 2 \cdot n(d) + 1$$

Figure: Binary tree with subtrees

Number of nodes $n(d)$ in a binary tree with depth d :

- **Induction assumption:** $n(d) = 2^d - 1$
- **Induction basis:** $n(1) = 2^1 - 1 = 2^0 - 1 = 1$ ✓
- **Induction step:** to show for $d := d + 1$




$$\begin{aligned} n(d+1) &= 2 \cdot n(d) + 1 \\ &= 2 \cdot (2^d - 1) + 1 \end{aligned}$$

Figure: Binary tree with subtrees

Induction - Example 1

Number of nodes $n(d)$ in a binary tree with depth d :

- **Induction assumption:** $n(d) = 2^d - 1$
- **Induction basis:** $n(1) = 2^1 - 1 = 2^1 - 1 = 1$ ✓
- **Induction step:** to show for $d := d + 1$



$$\begin{aligned} n(d+1) &= 2 \cdot n(d) + 1 \\ &= 2 \cdot (2^d - 1) + 1 \\ &= 2^{d+1} - 2 + 1 \end{aligned}$$

Figure: Binary tree with subtrees

Number of nodes $n(d)$ in a binary tree with depth d :

- **Induction assumption:** $n(d) = 2^d - 1$
- **Induction basis:** $n(1) = 2^1 - 1 = 2^1 - 1 = 1$ ✓
- **Induction step:** to show for $d := d + 1$




Figure: Binary tree with subtrees

$$\begin{aligned} n(d+1) &= 2 \cdot n(d) + 1 \\ &= 2 \cdot (2^d - 1) + 1 \\ &= 2^{d+1} - 2 + 1 \\ &= 2^{d+1} - 1 \quad \checkmark \end{aligned}$$

Number of nodes $n(d)$ in a binary tree with depth d :

- **Induction assumption:** $n(d) = 2^d - 1$
- **Induction basis:** $n(1) = 2^1 - 1 = 2^1 - 1 = 1$ ✓
- **Induction step:** to show for $d := d + 1$




Figure: Binary tree with subtrees

$$\begin{aligned} n(d+1) &= 2 \cdot n(d) + 1 \\ &= 2 \cdot (2^d - 1) + 1 \\ &= 2^{d+1} - 2 + 1 \\ &= 2^{d+1} - 1 \quad \checkmark \end{aligned}$$

⇒ **By induction:** $n(d) = 2^d - 1 \quad \forall n \in \mathbb{N} \quad \square$

Feedback

Exercises

Lecture

Runtime Example

Minsort

Basic Operations

Runtime analysis

Minsort

Heapsort

Introduction to Induction

Logaritms

Heapsort has the following steps:

- **Initially:** heapify list of n elements

Heapsort has the following steps:

- **Initially:** heapify list of n elements
- **Then:** until all n elements are sorted

Heapsort has the following steps:

- **Initially:** heapify list of n elements
- **Then:** until all n elements are sorted
 - Remove root as minimal element


Heapsort has the following steps:

- **Initially:** heapify list of n elements
- **Then:** until all n elements are sorted
 - Remove root as minimal element
 - Move last leaf to root position


Heapsort has the following steps:

- **Initially:** heapify list of n elements
- **Then:** until all n elements are sorted
 - Remove root as minimal element
 - Move last leaf to root position
 - Repair heap by sifting

Runtime of heapify depends on depth d :




Runtime of heapify depends on depth d :



Runtime of heapify with depth of d :

- No costs at depth d with 2^{d-1} (or less) nodes


Runtime of heapify depends on depth d :



Runtime of heapify with depth of d :

- No costs at depth d with 2^{d-1} (or less) nodes
- The cost for sifting with depth 1 is at most $1C$ per node


Runtime of heapify depends on depth d :



Runtime of heapify with depth of d :


- No costs at depth d with 2^{d-1} (or less) nodes
- The cost for sifting with depth 1 is at most $1C$ per node
- In general: Sifting costs are linear with path length **and** number of nodes

Heapify total runtime:




Depth	Nodes	Path length	Costs per node
d	2^{d-1}	0	$\leq C \cdot 0$

Heapify total runtime:




Depth	Nodes	Path length	Costs per node
d	2^{d-1}	0	$\leq C \cdot 0$
$d-1$	2^{d-2}	1	$\leq C \cdot 1$

Heapify total runtime:




Depth	Nodes	Path length	Costs per node
d	2^{d-1}	0	$\leq C \cdot 0$
$d-1$	2^{d-2}	1	$\leq C \cdot 1$
$d-2$	2^{d-3}	2	$\leq C \cdot 2$

Heapify total runtime:



Depth	Nodes	Path length	Costs per node
d	2^{d-1}	0	$\leq C \cdot 0$
$d-1$	2^{d-2}	1	$\leq C \cdot 1$
$d-2$	2^{d-3}	2	$\leq C \cdot 2$
$d-3$	2^{d-4}	3	$\leq C \cdot 3$


Heapify total runtime:



Depth	Nodes	Path length	Costs per node
d	2^{d-1}	0	$\leq C \cdot 0$
$d-1$	2^{d-2}	1	$\leq C \cdot 1$
$d-2$	2^{d-3}	2	$\leq C \cdot 2$
$d-3$	2^{d-4}	3	$\leq C \cdot 3$

In total:
$$T(d) \leq \sum_{i=1}^d \left(C \cdot (i-1) \cdot 2^{d-i} \right)$$


Heapify total runtime:



Depth	Nodes	Path length	Costs per node	Upper bound
d	2^{d-1}	0	$\leq C \cdot 0$	Standard Equation
$d-1$	2^{d-2}	1	$\leq C \cdot 1$	
$d-2$	2^{d-3}	2	$\leq C \cdot 2$	
$d-3$	2^{d-4}	3	$\leq C \cdot 3$	

In total:
$$T(d) \leq \sum_{i=1}^d \left(C \cdot (i-1) \cdot 2^{d-i} \right) \leq \sum_{i=1}^d \left(C \cdot i \cdot 2^{d-i} \right)$$

Heapify total runtime:



Depth	Nodes	Path length	Costs per node	Upper bound
d	2^{d-1}	0	$\leq C \cdot 0$	$\leq C \cdot 1$
$d-1$	2^{d-2}	1	$\leq C \cdot 1$	$\leq C \cdot 2$
$d-2$	2^{d-3}	2	$\leq C \cdot 2$	$\leq C \cdot 3$
$d-3$	2^{d-4}	3	$\leq C \cdot 3$	$\leq C \cdot 4$

In total:
$$T(d) \leq \sum_{i=1}^d \left(C \cdot (i-1) \cdot 2^{d-i} \right) \leq \sum_{i=1}^d \left(C \cdot i \cdot 2^{d-i} \right)$$

Heapify total runtime:

$$T(d) \leq C \cdot \sum_{i=1}^d (i \cdot 2^{d-i}) \leq C \cdot 2^{d+1}$$

Heapify total runtime:

$$T(d) \leq C \cdot \sum_{i=1}^d (i \cdot 2^{d-i}) \leq C \cdot 2^{d+1}$$

- **Hence:** Resulting costs for heapify:

$$T(d) \leq C \cdot 2^{d+1}$$

Heapify total runtime:

$$T(d) \leq C \cdot \sum_{i=1}^d (i \cdot 2^{d-i}) \leq C \cdot 2^{d+1}$$

- **Hence:** Resulting costs for heapify:

$$T(d) \leq C \cdot 2^{d+1}$$

- **However:** We want costs in relation to n



Heapify total runtime:

$$T(d) \leq C \cdot 2^{d+1}$$

Heapify total runtime:

$$T(d) \leq C \cdot 2^{d+1}$$

- A binary tree of depth d has $2^{d-1} \leq n$ nodes

Heapify total runtime:

$$T(d) \leq C \cdot 2^{d+1}$$

- A binary tree of depth d has $2^{d-1} \leq n$ nodes Why?

Heapify total runtime:

$$T(d) \leq C \cdot 2^{d+1}$$

- A binary tree of depth d has $2^{d-1} \leq n$ nodes Why?




Figure: Partial binary tree

Heapify total runtime:

$$T(d) \leq C \cdot 2^{d+1}$$

- A binary tree of depth d has $2^{d-1} \leq n$ nodes Why?
- $2^{d-1} - 1$ nodes in full tree till layer $d - 1$




Figure: Partial binary tree

Heapify total runtime:

$$T(d) \leq C \cdot 2^{d+1}$$

- A binary tree of depth d has $2^{d-1} \leq n$ nodes Why?
- $2^{d-1} - 1$ nodes in full tree till layer $d - 1$
- At least 1 node in layer d




Figure: Partial binary tree

Heapify total runtime:

$$T(d) \leq C \cdot 2^{d+1}$$

- A binary tree of depth d has $2^{d-1} \leq n$ nodes Why?
- $2^{d-1} - 1$ nodes in full tree till layer $d - 1$
- At least 1 node in layer d
- Equation multiplied by 2^2
 $\Rightarrow 2^{d-1} \cdot 2^2 \leq 2^2 \cdot n$




Figure: Partial binary tree

Heapify total runtime:

$$T(d) \leq C \cdot 2^{d+1}$$

- A binary tree of depth d has $2^{d-1} \leq n$ nodes Why?
- $2^{d-1} - 1$ nodes in full tree till layer $d - 1$
- At least 1 node in layer d
- Equation multiplied by 2^2
 $\Rightarrow 2^{d-1} \cdot 2^2 \leq 2^2 \cdot n$
- Cost for heapify:
 $\Rightarrow T(n) \leq C \cdot 4 \cdot n$




Figure: Partial binary tree

Feedback

Exercises

Lecture

Runtime Example

Minsort

Basic Operations

Runtime analysis

Minsort

Heapsort

Introduction to Induction

Logaritms

- We want to proof (induction assumption):

$$\underbrace{\sum_{i=1}^d (i \cdot 2^{d-i})}_{A(d)} \leq \underbrace{2^{d+1}}_{B(d)}$$

- We denote the left side with A , the right side with B

- **Induction basis:** $d := 1$:

$$A(d) \leq B(d)$$

- **Induction basis:** $d := 1$:

$$A(d) \leq B(d)$$

$$\sum_{i=1}^d (i \cdot 2^{d-i}) \leq 2^{d+1}$$

- **Induction basis:** $d := 1$:

$$A(d) \leq B(d)$$

$$\sum_{i=1}^d (i \cdot 2^{d-i}) \leq 2^{d+1}$$

$$\sum_{i=1}^1 (i \cdot 2^{1-i}) \leq 2^{1+1}$$

■ **Induction basis:** $d := 1$:

$$A(d) \leq B(d)$$

$$\sum_{i=1}^d (i \cdot 2^{d-i}) \leq 2^{d+1}$$

$$\sum_{i=1}^1 (i \cdot 2^{1-i}) \leq 2^{1+1}$$

$$2^0 \leq 2^2 \quad \checkmark$$

Induction step: ($d := d + 1$):

- **Idea:** Write down right hand formula and try to get $A(d)$ and $B(d)$ out of it

$$A(d) \leq B(d) \quad \Rightarrow \quad A(d+1) \leq B(d+1)$$

Induction step: ($d := d + 1$):

- **Idea:** Write down right hand formula and try to get $A(d)$ and $B(d)$ out of it

$$A(d) \leq B(d) \quad \Rightarrow \quad A(d+1) \leq B(d+1)$$

$$\sum_{i=1}^{d+1} (i \cdot 2^{d+1-i}) \leq 2^{d+1+1}$$

Induction step: ($d := d + 1$):

- **Idea:** Write down right hand formula and try to get $A(d)$ and $B(d)$ out of it

$$A(d) \leq B(d) \quad \Rightarrow \quad A(d+1) \leq B(d+1)$$

$$\sum_{i=1}^{d+1} (i \cdot 2^{d+1-i}) \leq 2^{d+1+1}$$

$$2 \cdot \sum_{i=1}^{d+1} (i \cdot 2^{d-i}) \leq 2 \cdot 2^{d+1}$$

\vdots

Induction step: ($d := d + 1$):

\vdots

$$2 \cdot \sum_{i=1}^{d+1} (i \cdot 2^{d-i}) \leq 2 \cdot 2^{d+1}$$

Induction step: ($d := d + 1$):

\vdots

$$2 \cdot \sum_{i=1}^{d+1} (i \cdot 2^{d-i}) \leq 2 \cdot 2^{d+1}$$

$$2 \cdot \sum_{i=1}^{d+1} (i \cdot 2^{d-i}) \leq 2 \cdot B(d)$$

Induction step: ($d := d + 1$):

\vdots

$$2 \cdot \sum_{i=1}^{d+1} (i \cdot 2^{d-i}) \leq 2 \cdot 2^{d+1}$$

$$2 \cdot \sum_{i=1}^{d+1} (i \cdot 2^{d-i}) \leq 2 \cdot B(d)$$

$$2 \cdot \sum_{i=1}^d (i \cdot 2^{d-i}) + 2 \cdot (d+1) \cdot 2^{d-(d+1)} \leq 2 \cdot B(d)$$

Induction step: ($d := d + 1$):

\vdots

$$2 \cdot \sum_{i=1}^{d+1} (i \cdot 2^{d-i}) \leq 2 \cdot 2^{d+1}$$

$$2 \cdot \sum_{i=1}^{d+1} (i \cdot 2^{d-i}) \leq 2 \cdot B(d)$$

$$2 \cdot \sum_{i=1}^d (i \cdot 2^{d-i}) + 2 \cdot (d+1) \cdot 2^{d-(d+1)} \leq 2 \cdot B(d)$$

$$2 \cdot A(d) + (d+1) \leq 2 \cdot B(d)$$

Induction step: ($d := d + 1$):

\vdots

$$2 \cdot \sum_{i=1}^{d+1} (i \cdot 2^{d-i}) \leq 2 \cdot 2^{d+1}$$

$$2 \cdot \sum_{i=1}^{d+1} (i \cdot 2^{d-i}) \leq 2 \cdot B(d)$$

$$2 \cdot \sum_{i=1}^d (i \cdot 2^{d-i}) + 2 \cdot (d+1) \cdot 2^{d-(d+1)} \leq 2 \cdot B(d)$$

$$2 \cdot A(d) + (d+1) \leq 2 \cdot B(d)$$

■ **Problem:** Does not work but claim still holds

Working proof:

- Show a **little bit stronger** claim

$$\sum_{i=1}^d (i \cdot 2^{d-i}) \leq 2^{d+1} - d - 2 \leq 2^{d+1}$$

Working proof:

- Show a **little bit stronger** claim

$$\sum_{i=1}^d (i \cdot 2^{d-i}) \leq 2^{d+1} - d - 2 \leq 2^{d+1}$$

- **Advantage:** Results in a stronger induction assumption
 \Rightarrow **exercise**

Feedback

Exercises

Lecture

Runtime Example

Minsort

Basic Operations

Runtime analysis

Minsort

Heapsort

Introduction to Induction

Logaritms

Runtime of the other operations:

Runtime of the other operations:

- Constant costs for taking out $n \times$ maximum

Runtime of the other operations:

- Constant costs for taking out $n \times$ maximum
- Maximum of d steps repairing the heap n times

Runtime of the other operations:

- Constant costs for taking out $n \times$ maximum
- Maximum of d steps repairing the heap n times
- Depth of heap at the start is $d \leq 1 + \log_2 n$ Why?

$$2^{d-1} \leq n \Rightarrow d-1 \leq \log_2 n \Rightarrow d \leq 1 + \log_2 n$$

Runtime of the other operations:

- Constant costs for taking out $n \times$ maximum
- Maximum of d steps repairing the heap n times
- Depth of heap at the start is $d \leq 1 + \log_2 n$ Why?

$$2^{d-1} \leq n \Rightarrow d-1 \leq \log_2 n \Rightarrow d \leq 1 + \log_2 n$$

- **Recall:** The depth and number of elements is decreasing

Runtime of the other operations:

- Constant costs for taking out $n \times$ maximum
- Maximum of d steps repairing the heap n times
- Depth of heap at the start is $d \leq 1 + \log_2 n$ Why?

$$2^{d-1} \leq n \Rightarrow d-1 \leq \log_2 n \Rightarrow d \leq 1 + \log_2 n$$

- **Recall:** The depth and number of elements is decreasing
 - **Hence:** $T(n) \leq n \cdot (1 + \log_2 n) \cdot C$

Runtime of the other operations:

- Constant costs for taking out $n \times$ maximum
- Maximum of d steps repairing the heap n times
- Depth of heap at the start is $d \leq 1 + \log_2 n$ Why?

$$2^{d-1} \leq n \Rightarrow d-1 \leq \log_2 n \Rightarrow d \leq 1 + \log_2 n$$

- **Recall:** The depth and number of elements is decreasing
 - **Hence:** $T(n) \leq n \cdot (1 + \log_2 n) \cdot C$
 - We can reduce this to:

$$T(n) \leq 2 \cdot n \log_2 n \cdot C \quad (\text{holds for } n > 2)$$

Runtime costs:

- Heapify: $T(n) \leq 4 \cdot n \cdot C$

Runtime costs:

- Heapify: $T(n) \leq 4 \cdot n \cdot C$
- Remove: $T(n) \leq 2 \cdot n \log_2 n \cdot C$

Runtime costs:

- Heapify: $T(n) \leq 4 \cdot n \cdot C$
- Remove: $T(n) \leq 2 \cdot n \log_2 n \cdot C$
- Total runtime: $T(n) \leq 6 \cdot n \log_2 n \cdot C$

Runtime costs:

- Heapify: $T(n) \leq 4 \cdot n \cdot C$
- Remove: $T(n) \leq 2 \cdot n \log_2 n \cdot C$
- Total runtime: $T(n) \leq 6 \cdot n \log_2 n \cdot C$
- Constraints:
 - Upper bound: $C_2 \cdot n \log_2 n \geq T(n)$ (for $n \geq 2$)
 - Lower bound: $C_1 \cdot n \log_2 n \leq T(n)$ (for $n \geq 2$)

Runtime costs:

- Heapify: $T(n) \leq 4 \cdot n \cdot C$
- Remove: $T(n) \leq 2 \cdot n \log_2 n \cdot C$
- Total runtime: $T(n) \leq 6 \cdot n \log_2 n \cdot C$
- Constraints:
 - **Upper bound:** $C_2 \cdot n \log_2 n \geq T(n)$ (for $n \geq 2$)
 - **Lower bound:** $C_1 \cdot n \log_2 n \leq T(n)$ (for $n \geq 2$)
 - $\Rightarrow C_1$ and C_2 are constant

Feedback

Exercises

Lecture

Runtime Example

Minsort

Basic Operations

Runtime analysis

Minsort

Heapsort

Introduction to Induction

Logaritms

Logarithm to different bases:

$$\log_a n = \frac{\log_b n}{\log_b a} = \log_b n \cdot \frac{1}{\log_b a}$$

The only difference is a constant coefficient $\frac{1}{\log_b a}$

Examples:

- $\log_2 4 = \log_{10} 4 \cdot \frac{1}{\log_2 10} = 0.602 \dots \cdot 3.322 \dots = 2 \checkmark$
- $\log_{10} 1000 = \log_e 1000 \cdot \frac{1}{\log_e 10} = \ln 1000 \cdot \frac{1}{\ln 10} = 3 \checkmark$

Runtime of $n \log_2 n$:

- Assume we have constants C_1 and C_2 with

$$C_1 \cdot n \cdot \log_2 n \leq T(n) \leq C_2 \cdot n \cdot \log_2 n \quad \text{for } n \geq 2$$

Runtime of $n \log_2 n$:

- Assume we have constants C_1 and C_2 with

$$C_1 \cdot n \cdot \log_2 n \leq T(n) \leq C_2 \cdot n \cdot \log_2 n \quad \text{for } n \geq 2$$

- $2 \times$ elements \Rightarrow only slightly larger than $2 \times$ runtime

Runtime of $n \log_2 n$:

- Assume we have constants C_1 and C_2 with

$$C_1 \cdot n \cdot \log_2 n \leq T(n) \leq C_2 \cdot n \cdot \log_2 n \quad \text{for } n \geq 2$$

- $2 \times$ elements \Rightarrow only slightly larger than $2 \times$ runtime
 - $C = 1 \text{ ns}$ (1 simple instruction $\approx 1 \text{ ns}$)

Runtime of $n \log_2 n$:

- Assume we have constants C_1 and C_2 with

$$C_1 \cdot n \cdot \log_2 n \leq T(n) \leq C_2 \cdot n \cdot \log_2 n \quad \text{for } n \geq 2$$

- $2 \times$ elements \Rightarrow only slightly larger than $2 \times$ runtime
 - $C = 1$ ns (1 simple instruction ≈ 1 ns)
 - $n = 2^{20}$ (1 million numbers = 4 MB with 4 B/number)
 - $C \cdot n \cdot \log_2 n = 10^{-9} \text{ s} \cdot 2^{20} \cdot 20 = 21.0 \text{ ms}$

Runtime of $n \log_2 n$:

- Assume we have constants C_1 and C_2 with

$$C_1 \cdot n \cdot \log_2 n \leq T(n) \leq C_2 \cdot n \cdot \log_2 n \quad \text{for } n \geq 2$$

- $2 \times$ elements \Rightarrow only slightly larger than $2 \times$ runtime
 - $C = 1$ ns (1 simple instruction ≈ 1 ns)
 - $n = 2^{20}$ (1 million numbers = 4 MB with 4 B/number)
 - $C \cdot n \cdot \log_2 n = 10^{-9} \text{ s} \cdot 2^{20} \cdot 20 = 21.0 \text{ ms}$
 - $n = 2^{30}$ (1 billion numbers = 4 GB)
 - $C \cdot n \cdot \log_2 n = 10^{-9} \text{ s} \cdot 2^{30} \cdot 30 = 32 \text{ s}$

Runtime of $n \log_2 n$:

- Assume we have constants C_1 and C_2 with

$$C_1 \cdot n \cdot \log_2 n \leq T(n) \leq C_2 \cdot n \cdot \log_2 n \quad \text{for } n \geq 2$$

- $2 \times$ elements \Rightarrow only slightly larger than $2 \times$ runtime
 - $C = 1$ ns (1 simple instruction ≈ 1 ns)
 - $n = 2^{20}$ (1 million numbers = 4 MB with 4 B/number)
 - $C \cdot n \cdot \log_2 n = 10^{-9} \text{ s} \cdot 2^{20} \cdot 20 = 21.0 \text{ ms}$
 - $n = 2^{30}$ (1 billion numbers = 4 GB)
 - $C \cdot n \cdot \log_2 n = 10^{-9} \text{ s} \cdot 2^{30} \cdot 30 = 32 \text{ s}$
- **Runtime $n \log_2 n$ is nearly as good as linear!**

■ General for this Lecture

[CRL01] Thomas H. Cormen, Ronald L. Rivest, and Charles E. Leiserson.

Introduction to Algorithms.

MIT Press, Cambridge, Mass, 2001.

[MS08] Kurt Mehlhorn and Peter Sanders.

Algorithms and data structures, 2008.

<https://people.mpi-inf.mpg.de/~mehlhorn/ftp/Mehlhorn-Sanders-Toolbox.pdf>.

■ Mathematical Induction

[Wik] [Mathematical induction](https://en.wikipedia.org/wiki/Mathematical_induction)

`https://en.wikipedia.org/wiki/Mathematical_induction`