

# Algorithms and Datastructures

## Runtime Complexity, Associative Arrays

Prof. Dr. Rolf Backofen

Bioinformatics Group / Department of Computer Science

Algorithms and Datastructures, November 2017

# Structure

## Runtime Complexity

## Associative Arrays

- Introduction

- Practical Example

  - Sorting

  - Associative Array

# Structure

## Runtime Complexity

### Associative Arrays

- Introduction

- Practical Example

  - Sorting

  - Associative Array

# Runtime Complexity

- ▶ The runtime does not entirely depend on the size of the problem, but also on the type of input
- ▶ This results in:
  - ▶ **Best runtime:**  
Lowest possible runtime complexity for an input of size  $n$
  - ▶ **Worst runtime:**  
Highest possible runtime complexity for an input of size  $n$
  - ▶ **Average / Expected runtime:**  
The average of all runtime complexities for an input of size  $n$

# Runtime Complexity

## Example 1 - Conditions

- ▶ Input: Field  $a$  with  $n$  elements  
 $a[i] \in \mathbb{N}$ ,  $0 \leq a[i] \leq n$ ,  $0 \leq i < n$
- ▶ Output: Field  $a$  with  $n$  elements  $a[0] \neq 1$

<pre>if a[0] == 0:     a[0] = 2 else:     for i in range(0, n):         a[i] = 2</pre>	$\left. \begin{array}{l} \frac{\mathcal{O}(1)}{\mathcal{O}(1)} \\ \frac{\mathcal{O}(n)}{\mathcal{O}(1)} \end{array} \right\} \left. \begin{array}{l} \mathcal{O}(1) \\ \mathcal{O}(n) \cdot \mathcal{O}(1) \\ = \mathcal{O}(n) \end{array} \right\} \mathcal{O}(?)$
--	---

- ▶ Best runtime:  $\mathcal{O}(1) + \mathcal{O}(1) = \mathcal{O}(1)$
- ▶ Worst runtime:  $\mathcal{O}(1) + \mathcal{O}(n) = \mathcal{O}(n)$

# Runtime Complexity

## Example 1 - Average Runtime

- ▶ The **average runtime** is determined by the average runtime for all input instances of size  $n$
- ▶ Every element of  $a$  can have  $n$  different values  
 $\Rightarrow n \cdot \dots \cdot n = n^n$  different input instances of size  $n$ 
  - ▶  $a[i] == 1$  in  $n^{n-1}$  instances
  - ▶  $a[i] != 1$  in  $n^n - n^{n-1} = n^{n-1} \cdot (n - 1)$  instances
- ▶ Sum of all runtime complexities:

$$\underbrace{n^{n-1} \cdot \mathcal{O}(1)}_{a[i] == 1} + \underbrace{n^{n-1} \cdot (n - 1) \cdot \mathcal{O}(n)}_{a[i] != 1}$$

- ▶ **Average runtime:**

$$\frac{n^{n-1} + n^{n-1} \cdot (n - 1) \cdot n}{n^n} = \frac{1}{n} + n - 1 \in \mathcal{O}(n)$$

# Runtime Complexity

## Example 2 - Binary Addition

- ▶ Input:  $n$  digit dual number  $a$
- ▶ Output:  $n$  digit dual number  $a + 1$
- ▶ Runtime of the algorithm is determined by the number of bits getting changed (steps)
  1. "0"  $\rightarrow$  "1"
  2. "1"  $\rightarrow$  "0"
- ▶ Best runtime: 1 step =  $\mathcal{O}(1)$
- ▶ Worst runtime:  $n$  steps =  $\mathcal{O}(n)$

Table: Binary addition

Digits ( $n$ )	Input	Output	Steps
10	1011100100	1011100101	1
4	1011	1100	3
8	11111111	00000000	8

# Runtime Complexity

## Example 2 - Average Steps

Table: Binary addition with  $n = 1$

Input	Output	Steps
0	1	1
1	0	1

$$\begin{aligned}\overline{\text{steps}} &= \frac{1 + 1}{2} = 1 \\ &= 2 - \frac{1}{1} = 2 - \frac{1}{2^{n-1}}\end{aligned}$$

Table: Binary addition with  $n = 2$

Input	Output	Steps
00	01	1
01	10	2
10	11	1
11	00	2

$$\begin{aligned}\overline{\text{steps}} &= \frac{1 + 2 + 1 + 2}{4} = \frac{3}{2} \\ &= 2 - \frac{1}{2} = 2 - \frac{1}{2^{n-1}}\end{aligned}$$



# Runtime Complexity

## Example 2 - Average Steps

Table: Binary addition with  $n = 3$

Input	Output	Steps
000	001	1
001	010	2
010	011	1
011	100	3
100	101	1
101	110	2
110	111	1
111	000	3

$$\begin{aligned}\overline{\text{steps}} &= \frac{1 + 2 + 1 + 3 + 1 + 2 + 1 + 3}{8} = \frac{7}{4} \\ &= 2 - \frac{1}{4} = 2 - \frac{1}{2^{n-1}}\end{aligned}$$

$$\Rightarrow \text{Average runtime:} \\ 2 - \frac{1}{2^{n-1}} \in \mathcal{O}(1)$$

# Runtime Complexity

## Example 2 - Average Steps

Table: Case analysis for instances of size  $n$

Input	Output	Instances	Steps
-----0	-----1	$2^{n-1}$	1
-----01	-----10	$2^{n-2}$	2
-----011	-----100	$2^{n-3}$	3
⋮	⋮	⋮	⋮
_01...1111	_10...0000	$2^1$	$n-1$
011...1111	100...0000	$2^0$	$n$
111...1111	000...0000	1	$n$

Average steps:

$$\frac{1 \cdot 2^{n-1} + 2 \cdot 2^{n-2} + \dots + (n-1) \cdot 2^1 + n \cdot 2^0 + n \cdot 1}{2^{n-1} + 2^{n-2} + \dots + 2^1 + 2^0 + 1} = \frac{\sum_{i=1}^n (i \cdot 2^{n-i}) + n}{\sum_{i=0}^{n-1} 2^i + 1}$$

# Runtime Complexity

## Example 2 - Average Steps

► Denominator:

$$\sum_{i=0}^{n-1} 2^i + 1 \quad \begin{array}{c} \text{geometric} \\ \text{series} \end{array} = 2^n - 1 + 1 = 2^n$$

► Counter:

$$\begin{aligned} & \sum_{i=1}^n \left( i \cdot 2^{n-i} \right) + n \stackrel{a=2^{a-a}}{=} 2 \sum_{i=1}^n \left( i \cdot 2^{n-i} \right) - \sum_{i=1}^n \left( i \cdot 2^{n-i} \right) + n \\ &= 1 \cdot 2^n + 2 \cdot 2^{n-1} + 3 \cdot 2^{n-2} + \dots + (n-1) \cdot 2^2 + n \cdot 2^1 \\ & \quad - 1 \cdot 2^{n-1} - 2 \cdot 2^{n-2} - \dots - (n-2) \cdot 2^2 - (n-1) \cdot 2^1 - n \cdot 2^0 \\ &= \underbrace{2^n + 2^{n-1} + \dots + 2^1 + 2^0}_{2^{n+1}-1} - 1 = 2^{n+1} - 2 \end{aligned}$$

# Runtime Complexity

## Example 2 - Average Steps

Average steps:

$$\overline{steps} = \frac{\sum_{i=1}^n (i \cdot 2^{n-i}) + n}{\sum_{i=0}^{n-1} 2^i + 1} = \frac{2^{n+1} - 2}{2^n} = 2 - \frac{1}{2^{n-1}}$$

$$\lim_{n \rightarrow \infty} \left( 2 - \frac{1}{2^{n-1}} \right) = 2 \in \mathcal{O}(1)$$

# Structure

Runtime Complexity

Associative Arrays

Introduction

Practical Example

Sorting

Associative Array

# Associative Arrays

## Introduction

### Normal array:

$$A = [0 \Rightarrow A_0, 1 \Rightarrow A_1, 2 \Rightarrow A_2, 3 \Rightarrow A_3, \dots]$$

- ▶ Searching elements by **index**
- ▶ Lookup of element with index "3":  
 $\Rightarrow A[3] = A_3$

# Associative Arrays

## Introduction

### Associative array:

$$A = \left[ \begin{array}{l} \text{"Europa"} \Rightarrow A_0, \text{"Amerika"} \Rightarrow A_1, \\ \text{"Asien"} \Rightarrow A_2, \text{"Afrika"} \Rightarrow A_3, \\ \dots \end{array} \right]$$

- ▶ Searching elements by **key**
- ▶ The keys can be of any type with unique elements
- ▶ Lookup of element with key "Afrika":  
 $\Rightarrow A[\text{"Afrika"}] = A_3$

# Structure

Runtime Complexity

Associative Arrays

Introduction

Practical Example

Sorting

Associative Array



# Associative Arrays

## Practical Example

**Table:** Country data query from <http://geonames.org>

ISO	ISO3	Country	Continent	...
AD	AND	Andorra	EU	...
AE	ARE	United Arab Emirates	AS	...
AF	AFG	Afghanistan	AS	...
AG	ATG	Antigua and Barbuda	NA	...
AI	AIA	Anguilla	NA	...
AL	ALB	Albania	EU	...
AM	ARM	Armenia	AS	...
AO	AGO	Angola	AF	...
AQ	ATA	Antarctica	AN	...
⋮	⋮	⋮	⋮	⋮



# Associative Arrays

## Practical Example

**Task:** How many countries belong to each continent?

- ▶ We are interested in column 2 (country) and 3 (continent)
- ▶ There are two typical ways to solve this:
  - ▶ Using Sorting
  - ▶ Using an associative array

# Structure

Runtime Complexity

## Associative Arrays

Introduction

Practical Example

Sorting

Associative Array

# Associative Arrays

## Practical Example

### **Idea using sorting:**

- ▶ We sort the columns 2 and 3 by continent, so that all countries with the same continent are grouped in one block
- ▶ We count the size of the blocks

### **Disadvantage:**

- ▶ Runtime of  $\Theta(n \log n)$
- ▶ We have to iterate the array twice (sort and then count)

### **Advantage:**

- ▶ Easy to implement (even with simple linux / unix commands)

# Associative Arrays

## Practical Example - Sorting With Linux / Unix Commands

### Input:

- ▶ The data is saved as tab separated text (countryInfo.txt)
- ▶ Comments begin with a hash sign #

### Commands:

- ▶ **grep**: Selects a specific set of lines (filter by ...)  
`grep -v '^#' countryInfo.txt`
  - v: not
  - ^#: # at start of line
- ▶ **cut**: Selects specific columns of each line (tab separated)  
`cut -f5,9`
  - f5,9: columns 5 and 9 (columns 2, 3 of Table 6)

# Associative Arrays

## Practical Example - Sorting With Linux / Unix Commands

### Commands:

- ▶ **sort**: Sorts lines by a key  
`sort -t ' ' -k2,2`  
    `-t ' ':` Separator: Tab (Insert with CTRL-V TAB)  
    `-k2,2:` Key from column 2 to 2
- ▶ **uniq**: Finds or counts unique keys  
`uniq -c`  
    `-c:` count occurrences of keys
- ▶ **head**: Displays a provided number of lines  
`head -n30`  
    `-n30:` Displays the first 30 lines
- ▶ **less**: Displays the file page wise

# Associative Arrays

## Practical Example - Sorting With Linux / Unix Commands

### Sort countries by continent:

```
grep -v '^#' countryInfo.txt | cut -f5,9 \  
| sort -t ' ' -k2,2 | less
```

Table: Resulting data

Algeria	AF
Angola	AF
Benin	AF
Botswana	AF
Burkina Faso	AF
Burundi	AF
Cameroon	AF
Cape Verde	AF
⋮	⋮

Figure: Data pipeline



# Associative Arrays

## Practical Example - Sorting With Linux / Unix Commands

### Count countries per continent:

```
grep -v '^#' countryInfo.txt | cut -f9 \  
| sort | uniq -c | sort -nr
```

Table: Resulting data

58	AF
54	EU
52	AS
42	NA
27	OC
14	SA
5	AN

Figure: Data pipeline





# Structure

Runtime Complexity

## Associative Arrays

Introduction

Practical Example

Sorting

Associative Array

# Associative Arrays

## Practical Example - Associative Array

### Idea using associative arrays:

- ▶ Take the continent as **key**
- ▶ Use a counter (occurences) or a list with all countries associated with this continent as **value**

### Advantage:

- ▶ Runtime  $\mathcal{O}(n)$ , implied we can find an element in  $\mathcal{O}(1)$  as in normal arrays

# Associative Arrays

## Python

### Python:

```
# creates a new map (called dictionary)
countries = {"DE" : "Deutschland", \
            "EN" : "England"}

# check if element exists
if "EN" in countries:
    print("Found %s!" % countries["EN"])

# map key "DE" to value 0
countries["DE"] = "Germany"

# delete key "DE"
del countries["DE"]
```

# Associative Arrays

## Efficiency

### Efficiency:

- ▶ Depends on implementation
- ▶ Two typical implementations:
  - ▶ **Hashing:** Calculates a checksum of the key used as key of a normal array  
search:  $\mathcal{O}(1) \dots \mathcal{O}(n)$   
insert:  $\mathcal{O}(1) \dots \mathcal{O}(n)$   
delete:  $\mathcal{O}(1) \dots \mathcal{O}(n)$
  - ▶ **(Binary-)Tree:** Creates a sorted (binary) tree  
search:  $\mathcal{O}(\log n) \dots \mathcal{O}(n)$   
insert:  $\mathcal{O}(\log n) \dots \mathcal{O}(n)$   
delete:  $\mathcal{O}(\log n) \dots \mathcal{O}(n)$

# Associative Arrays

## Efficiency

Table: Map implementations of programming languages

	Hashing	(Binary-)Tree
Python	all dictionaries	
Java	<code>java.util.HashMap</code>	<code>java.util.TreeMap</code>
C++11/14	<code>std::unordered_map</code>	<code>std::map</code>
C++98	<code>&lt;gnu_cxx::hash_map</code>	<code>std::map</code>

# Further Literature

## ► General

[CRL01] Thomas H. Cormen, Ronald L. Rivest, and Charles E. Leiserson.

*Introduction to Algorithms.*

MIT Press, Cambridge, Mass, 2001.

[MS08] Kurt Mehlhorn and Peter Sanders.

Algorithms and data structures, 2008.

<https://people.mpi-inf.mpg.de/~mehlhorn/ftp/Mehlhorn-Sanders-Toolbox.pdf>.

## Further Literature

### ► Map - Implementations / API

[Java] [Java - HashMap](#)

<https://docs.oracle.com/javase/7/docs/api/java/util/HashMap.html>

[Java] [Java - TreeMap](#)

<https://docs.oracle.com/javase/7/docs/api/java/util/TreeMap.html>

[Pyt] [Python - Dictionaries \(Hash table\)](#)

<https://docs.python.org/3/tutorial/datastructures.html#dictionaries>

## Further Literature

### ► Map - Implementations / API

[Cppa] [C++ - hash\\_map](#)

[http://www.sgi.com/tech/stl/hash\\_map.html](http://www.sgi.com/tech/stl/hash_map.html)

[Cppb] [C++ - map](#)

<http://www.sgi.com/tech/stl/Map.html>