



# Test Report - HomeSense 2026-001

## Test Information

Project: HomeSense\_Functional\_Test  
Operator: tobias  
Date: 21.04.2026  
Time: 20:57:52  
Duration: 30.13s

## Device Under Test

Serial Number: 2026-001  
Device Name: HomeSense  
Revision: B  
Variant: RTC +  $\mu$ SD  
Part Number: -

### Additional Notes:

The onboard sensors are tested via the device's self-test functionality.

# PASS

| Step | Name                           | Lower      | Measured      | Upper      | Result |
|------|--------------------------------|------------|---------------|------------|--------|
| 1    | VIN USB = 5V?                  | 4.5 V      | 4.9572 V      | 5.5 V      | ✓      |
| 2    | VOOUT Regulator = 3V3?         | 2.97 V     | 3.3023 V      | 3.63 V     | ✓      |
| 3    | Battery Detected?              | 2.97 V     | 3.3013 V      | 3.63 V     | ✓      |
| 4    | Test Battery Voltage           | 3.78 V     | 4.173 V       | 4.62 V     | ✓      |
| 5    | Test Battery Voltage Divider   | 2.79 V     | 3.0984 V      | 3.41 V     | ✓      |
| 6    | Battery Charge Indicator High? | 2.97 V     | 3.312 V       | 3.63 V     | ✓      |
| 7    | Battery Charge Indicator Low?  | -0.2 V     | 0.1643 V      | 0.2 V      | ✓      |
| 8    | Button 1 High?                 | 2.97 V     | 3.32 V        | 3.63 V     | ✓      |
| 9    | Button 1 Low?                  | -0.2 V     | 0.102 V       | 0.2 V      | ✓      |
| 10   | Button 2 High?                 | 2.97 V     | 3.315 V       | 3.63 V     | ✓      |
| 11   | Button 2 Low?                  | -0.2 V     | 0.099 V       | 0.2 V      | ✓      |
| 12   | Load Firmware V1.2             | 1          | 1             | 1          | ✓      |
| 13   | Firmware V1.2 Loaded?          | 1.2        | 1.2           | 1.2        | ✓      |
| 14   | Execute Self-Test              | 1          | 1             | 1          | ✓      |
| 15   | Active Current Consumption     | 0.0135 A   | 0.0148732 A   | 0.0165 A   | ✓      |
| 16   | Standby Current Consumption    | 3.15E-05 A | 3.68235E-05 A | 3.85E-05 A | ✓      |
| 17   | Forward Voltage LED 1 Red      | 1.62 V     | 1.78 V        | 1.98 V     | ✓      |
| 18   | Forward Voltage LED 1 Green    | 2.25 V     | 2.65 V        | 2.75 V     | ✓      |
| 19   | Forward Voltage LED 1 Blue     | 2.16 V     | 2.382 V       | 2.64 V     | ✓      |
| 20   | Forward Voltage LED 2 Red      | 1.62 V     | 1.82 V        | 1.98 V     | ✓      |
| 21   | Forward Voltage LED 2 Green    | 2.25 V     | 2.61 V        | 2.75 V     | ✓      |
| 22   | Forward Voltage LED 2 Blue     | 2.16 V     | 2.349 V       | 2.64 V     | ✓      |



# Test Report - HomeSense 2026-001

| Step | Name                        | Lower  | Measured | Upper  | Result |
|------|-----------------------------|--------|----------|--------|--------|
| 23   | Forward Voltage LED 3 Red   | 1.62 V | 1.79 V   | 1.98 V | ✓      |
| 24   | Forward Voltage LED 3 Green | 2.25 V | 2.57 V   | 2.75 V | ✓      |
| 25   | Forward Voltage LED 3 Blue  | 2.16 V | 2.43 V   | 2.64 V | ✓      |
| 26   | Forward Voltage LED 4 Red   | 1.62 V | 1.723 V  | 1.98 V | ✓      |
| 27   | Forward Voltage LED 4 Green | 2.25 V | 2.346 V  | 2.75 V | ✓      |
| 28   | Forward Voltage LED 4 Blue  | 2.16 V | 2.255 V  | 2.64 V | ✓      |

## Used Equipment

### Test Hardware:

Device Name: compact Test Interface Adapter

Serial Number: 2026001

Firmware Version: 0.4.2

### Devices:

OWON DMM: OWON,XDM1241,25240585,V4.3.0,3