



Test Report - HomeSense 2026-002

Test Information

Project: HomeSense_Functional_Test
Operator: tobias
Date: 21.04.2026
Time: 21:01:42
Duration: 29.99s

Device Under Test

Serial Number: 2026-002
Device Name: HomeSense
Revision: B
Variant: RTC + µSD
Part Number: -

Additional Notes:

The onboard sensors are tested via the device's self-test functionality.

FAIL

Step	Name	Lower	Measured	Upper	Result
1	VIN USB = 5V?	4.5 V	4.9572 V	5.5 V	✓
2	VOOUT Regulator = 3V3?	2.97 V	3.3023 V	3.63 V	✓
3	Battery Detected?	2.97 V	3.3013 V	3.63 V	✓
4	Test Battery Voltage	3.78 V	4.173 V	4.62 V	✓
5	Test Battery Voltage Divider	2.79 V	3.0984 V	3.41 V	✓
6	Battery Charge Indicator High?	2.97 V	3.312 V	3.63 V	✓
7	Battery Charge Indicator Low?	-0.2 V	0.1643 V	0.2 V	✓
8	Button 1 High?	2.97 V	3.32 V	3.63 V	✓
9	Button 1 Low?	-0.2 V	0.102 V	0.2 V	✓
10	Button 2 High?	2.97 V	3.315 V	3.63 V	✓
11	Button 2 Low?	-0.2 V	0.099 V	0.2 V	✓
12	Load Firmware V1.2	1	1	1	✓
13	Firmware V1.2 Loaded?	1.2	1.2	1.2	✓
14	Execute Self-Test	1	1	1	✓
15	Active Current Consumption	0.0135 A	0.0148732 A	0.0165 A	✓
16	Standby Current Consumption	3.15E-05 A	3.98235E-05 A	3.85E-05 A	✗
17	Forward Voltage LED 1 Red	1.62 V	1.78 V	1.98 V	✓
18	Forward Voltage LED 1 Green	2.25 V	2.65 V	2.75 V	✓
19	Forward Voltage LED 1 Blue	2.16 V	2.382 V	2.64 V	✓
20	Forward Voltage LED 2 Red	1.62 V	1.82 V	1.98 V	✓
21	Forward Voltage LED 2 Green	2.25 V	2.61 V	2.75 V	✓
22	Forward Voltage LED 2 Blue	2.16 V	2.349 V	2.64 V	✓



Test Report - HomeSense 2026-002

Step	Name	Lower	Measured	Upper	Result
23	Forward Voltage LED 3 Red	1.62 V	1.79 V	1.98 V	✓
24	Forward Voltage LED 3 Green	2.25 V	2.57 V	2.75 V	✓
25	Forward Voltage LED 3 Blue	2.16 V	2.43 V	2.64 V	✓
26	Forward Voltage LED 4 Red	1.62 V	1.723 V	1.98 V	✓
27	Forward Voltage LED 4 Green	2.25 V	2.346 V	2.75 V	✓
28	Forward Voltage LED 4 Blue	2.16 V	2.255 V	2.64 V	✓

Used Equipment

Test Hardware:

Device Name: compact Test Interface Adapter

Serial Number: 2026001

Firmware Version: 0.4.2