XPRO

SPARTUS®
XPRO CUT 70CNC

without HF

40mm max. cut

EMC compatibility

IP21S protection

400V power

PRECISION CUTTING AND FULL CNC INTEGRATION

A modern plasma cutter designed for cutting steel, aluminum, and other electrically conductive materials. The CNC socket, contactless arc ignition without HF, and three operating modes ensure precise manual cutting and efficient performance in automated processes.



CNC READY
The integrated CNC socket ensures reliable connection with plasma cutting tables and integration with industrial automation systems

STABILITY
Stable plasma arc, clean cut edges, and consistent performance even under intensive operation

RELIABILITY
Inverter technology, Fan Stop system, as well as contactless HF-free arc ignition increase durability and operating comfort

CUT | GRID | GOUGING

CNC | 60A | 2T/4T



FULL PLASMA ARC CONTROL

- non-HF ignition
- CUT / GRID / GOUGING
- CNC control socket
- max. cutting thickness: 40 mm
- pre-gas / post-gas
- 2T / 4T mode
- gas test

NON-CONTACT IGNITION STABLE ARC CNC CONTROL

MODERN HF-FREE TECHNOLOGY

Contactless pilot arc ignition **without HF:**

- reduces electromagnetic interference
- improves arc ignition stability
- increases working comfort around electronic equipment
- extends the service life of consumable parts

The ability to ignite the arc without nozzle contact with the material improves work ergonomics and reduces component wear.

CNC AUTOMATION READY

- integration with CNC cutting tables
- repeatable production
- higher cutting precision
- faster part processing
- stable communication with the control system



3 OPERATING MODES

- **CUT** – continuous cutting
- **GRID** – interrupted cutting
- **GOUGING** – plasma gouging

The machine is suitable for both standard cutting and material preparation for welding or weld removal.

INDUSTRIAL DESIGN

- **Fan Stop** – quiet operation and extended machine lifespan
- **IGBT technology** – high efficiency and reliability
- High **EMC compatibility**
- High **IP21S protection rating**

READY-TO-WORK SET



MANUAL PACKAGE

- XPro CUT 70CNC
- 6m SP80H torch equipped with consumable parts
- air filter with regulator
- 3m work clamp cable
- 3m gas hose with clamp and quick connector
- user manual

XPROCUT70CNC-PAK-80H-6



MECHANICAL PACKAGE

- XPro CUT 70CNC
- 6m SP80M torch equipped with consumable parts
- air filter with regulator
- 3m work clamp cable
- 3m gas hose with clamp and quick connector
- user manual

XPROCUT70CNC-PAK-80M-6

FREEDOM OF WORK









WITHOUT LIMITS

TECHNICAL DETAILS

Input	~3× 400V ± 10% 50 / 60 Hz	**Pilot arc ignition**	without HF
Cutting current	20 - 60A	**Current consumption**	17 / 13A
Max. cutting thickness	40mm	**Current consumption (cosφ)**	0.67
Duty cycle	60%	**Efficiency η**	84%
Output working voltage	88 - 104V	**Insulation class**	H
Recommended work pressure	3 - 6bar	**Protection class**	IP21S
Gas pre flow	yes	**Weight**	16.2kg
Gas post flow	yes	**Dimensions**	515 x 215 x 370mm



XPRO

ADVANCED TECHNOLOGY IN A MODERN DESIGN