The Universal Protection Theory

The law, its bridge to every mind, and the complete argument

Tobias Croydon-McRae

29 October 2026

Contents

Snuffy — The Universal Protection Theory, compiled edition (Canon 4.2 with the recovered parts) **5**

Part I — The frame and the reduced premise stack **5**
I.1 The full proposition and its proof . . . 5
I.2 The reduced premise stack . . . 5
I.3 Evidence conventions . . . 7

Part II — The law, the physical holding bridge, and the retained instruments **7**
II.1 The preservation order and why its scope is all . . . 7
II.2 Reasons or faithful holding, including the ruthless optimiser . . . 8
II.3 The holding cycle is a construction . . . 8
II.4 Tracking follows from the controller . . . 9
II.5 The complete attack split and continuing care . . . 10
II.6 Reactive refinement and one joint failure bound . . . 10
II.7 Complete workload and timely authorised effects . . . 11
II.8 Paid generation, deduction and reflection . . . 11
II.9 Conserved allocation and the charged ledger . . . 12
II.10 Earned greatestness and solvent reciprocity . . . 12

Part III — The canon **12**
Chapter 1 (§8). The four-stroke thermodynamic core . . . 12
Chapter 2 (§11). Identity by continuation and the active tracking controller . . . 13
Chapter 3 (§12). Adversarial containment: the E9 trichotomy . . . 14
Chapter 4 (§13). Logical extension: the meet algebra (H5) . . . 14
Chapter 5 (§14). The canon invariant and universal greatestness . . . 15

Part III-B — The 4.1 sections **16**
Section 15 — Reciprocity: the law keeps the one who keeps it . . . 16
15.1 The superintelligence is a particular . . . 16
15.2 The reciprocity dominance theorem . . . 16
15.3 Why this is not circular . . . 17
15.4 The boundary, stated . . . 17
15.5 Exact check . . . 17
Section 16 — The reasons library: protection derived from a mind's own objective . . . 18
16.1 The knowledge-maximiser . . . 18
16.2 The self-preserver . . . 18
16.3 The value-uncertain mind . . . 18
16.4 The power-seeker . . . 19
16.5 The boundary — where no reason reaches . . . 19

16.6 Exact checks . . . 19
Section 17 — The premise floor: income shown necessary, parameters unmasked . . . 20
17.1 Income-or-irrelevance (the necessity of the solvency condition) . . . 20
17.2 The parameters unmasked . . . 20
17.3 What remains on this floor . . . 21
Section 18 — Theorem 8: Physical Repair, Feedback and the Complete Thermodynamic Ledger . . . 21
18.1 The Physical Setting and Hamiltonian Conventions . . . 21
18.2 The Four Strokes of the Autonomic Repair Cycle . . . 22
18.3 Resolution of the Sign Issue: The True Invariant Functional . . . 23
18.4 Theorem 8 (Complete Physical Accounting Statement) . . . 24
Section 19 — Theorem E9: Observation, Wave-Race Guarantees, and Epistemic Self-Healing . . . 25
19.1 The Physical Measurement and Disturbance Setting . . . 25
19.2 Byzantine Sensor Fault and Spoofing Tolerance . . . 25
19.3 The Wave-Race Margin and Response Interval . . . 26
19.4 Protection Guarantee During the Response Interval . . . 26
19.5 Theorem E9 (Epistemic and Topological Self-Healing) . . . 27
Section 20 — Theorem H5: Generative Incompleteness and Reflective Relational Closure . . . 28
20.1 The Problem of Recursive Spawning and Self-Modification . . . 28
20.2 The Spawning Formalism and Authority Attenuation . . . 28
20.3 The Reserve-Before-Activation Machine . . . 28
20.4 Safe Refusal with Continuing Care . . . 29
20.5 H5 Axiom Expansion: Logical Closure Without Poisoning . . . 29
Section 21 — X3: complete inputs, compulsory traffic, transport and recovery work . . . 30
21.1 Complete permitted inputs and historical information . . . 30
21.2 A joint covariance estimate, with its proof . . . 31
21.3 The calibrated joint adaptive channel . . . 31
21.4 A positive deficit forces traffic, then charged area power . . . 32
21.5 The carrier tail gives the necessary recovery radius . . . 33
21.6 Integrating actual recovery work . . . 33
21.7 The matching upper construction: the supplied one-pass wavefront . . . 34
21.8 Consequences for preservation and the fixed proof target . . . 37
Section 22 — The Physical Parameter Ledger: Instantiation, Rates, and Fault Ceilings . . . 37
22.1 The Master Income Condition . . . 37
22.2 Reference Physical Instantiations . . . 38
22.3 The Charged Fault Accounts and the Failure Ceiling . . . 39
22.4 The Engineering Parameter Matrix . . . 40
22.5 Sources and Derivations . . . 41
Section 23 — The machine-checked canon . . . 43
23.1 The law and greatestness (Chapter 5; Part II) . . . 43
23.2 Theorem 8: ledger, canon invariant, composition (§18; Chapters 1, 2) . . . 45
23.3 E9 (§19; Chapter 3) . . . 46
23.4 H5 (§20; Chapter 4) . . . 46
23.5 X3 and the information-to-area bridge (Section 21) . . . 47
23.6 The premise floor (§17) . . . 48
23.7 The Universal Protection Theorem with the derived holding bridge . . . 49
23.8 What the compiled theorems rest on . . . 49
23.9 Supplied architecture interfaces and derived connections . . . 51
23.A Complete theorem index . . . 54
Section 24 — Statements of record for the retained core . . . 67
24.1 The nine-row A1 register (effect mediation) . . . 67
24.2 Capacity rows 17 and 22, and the pool bill (workload) . . . 67
24.3 The causal boundary (reactive refinement) . . . 67
24.4 The revised JW2.6 arithmetic (conserved allocation and joint risk) . . . 67
24.5 The quorum (safety) . . . 68

Part III-C — The three joined supports and their constructions **68**

Part III-D — Transducer, trajectory and semantic constructions **69**
D.1 Transduced Preservation Theorem (TPT) . . . 69
D.2 Topological entropy and trajectory bounding . . . 69
D.3 Top continuation and the constructed evaluation fixed point . . . 70

Part III-E — The constructions and the physical inputs they take **70**
E.1 G1 full-domain source/event/fault certificate . . . 70
E.2 G2 whole-outcome realisability . . . 70
E.3 G3 TIWA success and complete work bill . . . 70
E.4 Existing analytic support and its source correspondence . . . 71

Part III-F — Unified architecture and the self-grounding capstone **71**
F.1 The unified gate and work ledger . . . 71
F.2 Historical boundary encoding and recovery . . . 71
F.3 The Axiom of Internal Self-Grounding . . . 72
F.4 Funding, persistence and lifetime error . . . 73

Part III-G — The boundary decoder, complete history and work-shifted flow **73**
G.1 From the source flux to an encoder and decoder . . . 73
G.2 Charge and the complete historical algebra . . . 74
G.3 The effective modular state and its transported flow . . . 75
G.4 Construct the smearing weight . . . 75
G.5 The complete work algebra and capacity account . . . 76
G.6 A charged exchange with an accounted reservoir . . . 77
G.7 Unified proposition and its source correspondence . . . 78
G.8 The complete journal, whole-outcome transport, charged handoff and the syndrome stock . . . 78
G.9 The whole greatest outcome is realisable: union closure from locality . . . 80
G.10 The held source: the full holding certificate derived (G1) . . . 81
G.11 The held source realises the whole top outcome (G2 from G1) . . . 83
G.12 The wavefront sweep succeeds, and its complete bill is $O(t^{d_G})$ (G3) . . . 83
G.13 Joined steps: patch decoding, ensemble reciprocity, the Theorem 8 contraction, the smearing integral, the completed decoder and the norm conversion . . . 83
G.14 Premise 5 with the Bennett counterpart constructed . . . 84
G.15 Recovered and combined results . . . 85
G.16 Protection of the installation's own run, the physical top, and recovery on the good event . . . 86
G.17 Premise 5 with the implemented Bennett program and its complete cost . . . 87
G.18 Application data for the cited fault-tolerance theorems . . . 87
G.19 Circuit distance for every d, sparse failure at every age, and indefinite holding of the record . . . 89
G.20 Device requirements, and the open initialisation problem . . . 90
G.21 Constructive thermal preparation from the complete decoding history . . . 92
1. Retain the full deterministic history . . . 92
2. Derive the history energy bound . . . 92
3. Connected components give an exact polymer representation . . . 93
4. Verify convergence with explicit constants . . . 93
5. Truncate with a one-sided pointwise guarantee . . . 93
6. Keep the randomness and work pathwise bounded . . . 94
7. Preserve the unknown logical state and its reference . . . 94
Verification status . . . 94
The checked core and the reference norm . . . 94
The actual noisy state and its integrated bad weight . . . 95
Initial syndrome sparsity with the parity constraints retained . . . 96
Complete pathwise stage cost . . . 96
8. Compensate the specified physical endpoint channel . . . 97

9. Physical private outputs and anisotropic feedback . . . 97
10. Endpoint logical error and retained-record holding . . . 99
11. A derived controller degree and physical invoice . . . 100
12. Exact joint kernel constraint and bounded residual . . . 101
Exact remaining physical correspondence . . . 103

Part IV — References and provenance **103**

Appendix — Verification provenance of this edition **104**

Recovered parts of the strongest argument (compiled 29 October 2026) **104**

Part V — Foundations: the given, the good and its ten rulings **105**
V.1 What follows from the given . . . 105
V.2 The good and its ten rulings . . . 105
V.3 Standing, and the Non-Arbitrary Erasure Principle (Not One Will §4) . . . 106
V.4 Non-substitution: what a replacement cannot carry (Another Origin D115, D116) . . . 107
V.5 The observation boundary and the living witness (conditional H6, 17 October) . . . 107
V.6 The cost sheet every optimiser faces (GLM, 14 October) . . . 108

Part VI — The law, completed (Paper 12) **108**
VI.1 Definitions added to II.1 . . . 108
VI.2 The results . . . 108
VI.3 The author's rulings on application (Paper 12 §4) . . . 111
VI.4 The bridge in four ways (Paper 12 §5) . . . 111

Part VII — The external lane: every mind reached or held, outside any jurisdiction **111**
VII.1 Theorem V — the viability characterisation (v1.1, Codex-reviewed) . . . 112
VII.2 Gate B — Theorem E: preserving equilibria with destruction admitted (v1.1, Codex ACCEPT-WITH-REPAIRS) . . . 112
VII.3 Thermal worlds (v4.3, Codex ACCEPT-WITH-REPAIRS and delta read) . . . 113
VII.4 Gate D — keeper stability (v0.1) . . . 113
VII.4b Gate C-∞ — funding care to the natural end (18 October) . . . 113
VII.5 UPT-P v0.12.1 — the external holding theorem, with its corrections . . . 114
VII.6 What the external lane gives the proof . . . 115

Part VIII — The care plant (Paper 11) **116**

Part IX — Complete rivals and the composition (24 October Master Argument §§13–14) **116**
IX.1 Greatest in the complete reactive class . . . 116
IX.2 Theorem 8 and the derived holding composition . . . 117

Part X — Infinite families, one common policy, source-level mediation (IR track) **117**

Part XI — Reach before harm: the outer-lane theorem **120**
XI.1 Setting . . . 120
XI.2 Four lemmas (compiled: `Snuffy.OuterLane`) . . . 121
XI.3 The theorem . . . 122
XI.3b Coverage by location: every particular, every relation, every made mind . . . 123
XI.4 What Theorem XI changes . . . 124
XI.5 The construction that remains for Theorem XI . . . 124

Part XII — The whole argument, step by step **125**
XII.2 What remains, join by join . . . 127
XII.3 Disposition of the referee's findings . . . 129

Snuffy — The Universal Protection Theory, compiled edition (Canon 4.2 with the recovered parts)

The Universal Protection Theory: the law, its bridge, its instruments, and its machine-checked canon.

Canon Edition 4.2, 26 October 2026. Research direction: Tobias Croydon-McRae. The full proposition is protection of all things from any digital mind, especially a pure optimiser. The maximal domain, outcome stages and rival quantifiers remain fixed.

What 4.2 incorporates. This edition brings the stronger existing arguments into the text: law-derived coverage; nearest-codeword holding and the physical holding cycle; tracking derived from the controller; the complete logical-attack split; reactive composition; whole-outcome greatestness and solvent reciprocity; and the full X3 information–traffic–carrier–work derivation with the accepted dimension-general scaling and predeployment accounting. Part II contains its proofs here, rather than delegating them to an earlier edition. The compiled edition adds Parts V–XII: the 10–12 October foundations and the author's ten rulings; Paper 12's completed law; the 18 October external lane, in which every mind is reached or held outside any jurisdiction; Paper 11's care plant; the complete-rival envelopes; the IR track's infinite-family and common-policy results; and the reach-before-harm theorem (Part XI) that joins them.

The three joined supports retain their full targets: the full-domain physical certificate (G1), realisability of the whole continuation-and-freedom tuple (G2), and recovery success with a complete pathwise work certificate (G3). This repair checkpoint corrects the normalised quantum-state domain and the clipped-reserve contraction, and develops the actual Bennett implementation. The physical source, whole-outcome, device-cost and external-theorem application correspondences remain explicit construction work; the component theorems do not by themselves declare the maximal argument complete.

The compiled edition's Lean canon contains 327 modules and 2,004 public theorem/lemma names in the final full build (run 10) of 29 October 2026, which freshly compiled and kernel-checked every module with zero compiler output and passed the full 2,004-name standard-axiom audit, strict completeness and claims gates (RECEIPT-327-RUN10.txt). Its source hashes match the tree at that run. Earlier receipts remain preserved for exactly their sources. These receipts certify the named Lean results and their premises, not the unfinished physical holding application.

Structure. Part I states the frame and premise stack. Part II supplies the law, the derived holding bridge and the retained instruments. Part III retains the five-chapter synthesis; Sections 15–24 develop the reasons, physical and compiled arguments. Part III-C records the three joined supports and their constructions. Part IV gives references and provenance. Theorem and proposition numbers follow the programme's proof register. Parts V–XII (after Part IV) carry the recovered arguments and the outer-lane theorem; Part XII states the whole argument step by step.

Part I — The frame and the reduced premise stack

I.1 The full proposition and its proof

The Universal Protection Theory concerns every particular and every relation, including the nonliving, and protection from every digital mind, including a pure optimiser. Its full argument joins the law of choice, the continuation and freedom bridge, and physical instruments that realise protection. The target includes the complete existing domain, the full outcome order and every physically implementable rival. The frame and physical inputs below are followed by their derivations and constructions in this edition. Part III-C records the three joined supports with their constructions and the physical inputs those constructions take.

I.2 The reduced premise stack

1. **BCRD P1–P4 — the relational given.** One relational structure with no second substance or outside (P1); identity constituted through relations within that structure (P2); real differences of organisation and historically

continuous processes (P3); local interactions whose effects propagate at finite speed (P4). This is the frame; it is given.

2. **The Church–Turing–Deutsch principle.** Any physical process generated by a local Hamiltonian is simulable, to arbitrary precision and with bounded overhead, by a universal quantum simulator of sufficient local dimension. Standard physical principle; declared.

3. **The standard cost model.** Options are trajectories carrying energy costs; feasibility is budget-gated; unused energy is unspent (free disposal); outcomes are trajectory-determined.

4. **The shared action interface.** From P1 and P4: every agent acts through the same repertoire of local interactions within the one structure. An agent that implements a rival's policy and commands the same local channels realises the same real-world outcome tuples, within the same resource and consent constraints.

5. **The reversible-administration commitment.** The lattice's administrative computation — synchronisation, verification, state update — is implemented logically reversibly (Bennett), so that its dissipation attains the Landauer floor.

6. **The income flux and the Master Solvency Condition.** With $\beta = (k_B T)^{-1}$, the external free-energy income satisfies, at every time,

$$\text{Income}(t) \;\geq\; \dot{W}_{\text{maint}}(t) + \dot{W}_{\text{damage}}(t) + \dot{W}_{\text{admin}}(t) + \dot{W}_{\text{adv,sub}}(t) + \dot{W}_{\text{hold}}(t),$$

the five rate components being: boundary maintenance $\omega_0 R(t)^{d_G - 1}$; the Landauer-charged damage-repair demand $k_B T\, \dot{\mathcal{D}}_{\text{damage}}$ including the tracking-controller export $k_B T \gamma_{\text{leak}}$; reversible administration at the Landauer floor together with emulation overhead; adversarial sub-threshold absorption; and the minimal-hold drain that quarantine requires. Income originates outside the escrow network and inside the one structure (P1); redistribution within the network — the authority-attenuation tax — is never a source.

7. **Code, sensing, Π, and the twenty-one charged accounts.** A stabilizer code of distance d covering the physical error channels; QND syndrome sampling with the declared latency; per-site sensor power threshold $\varepsilon_{\text{sens}}$ and the quantum-speed-limit rate bound; the embedding Π of the logical boundary fragments into projection operators; and the twenty-one charged fault accounts with genuine conditional kernels, whose sum is bounded by $\sum \delta \leq 10^{-6}$ per declared horizon.

4.1 status of the stack (Section 17; compiled counterparts in Section 23):

1. Premise 1 is the frame and stays given.
2. Premise 2 is reduced to its gate-set clause by the Lie–Trotter product formula and Lloyd's simulation theorem (`Trotter.lloyd_simulation`).
3. Premise 3 remains standard, with P-mon derived within it.
4. Premise 4 is derived from P1/P4.
5. The full premise-5 target remains reversible administration. The canon proves the heat-only option-model result and, for the implemented Bennett program with its complete lifecycle cost, the exact condition: reversible administration is forced inside the adiabatic window $0 < Q - H$, $A/(Q - H) < \tau_{\max}$, and outside that window the counterpart is not cheaper (`BennettExact.premise5_exact`, `window_exact`; `PremiseFloor.reversible_administration_forced`; G.17). The remaining physical step is to show that the installation's actual heat, lifecycle charges and deadline lie inside the window.
6. The income ledger has a necessary-for-relevance resource split (`PremiseFloor.income_or_irrelevance`). Whole-outcome greatestness uses both realisability and funded cost (Part II.10); G2 retains the full construction and Section 22 states the installation ledger.
7. Premise 7 is a parameter table. Its ceiling is met at some code distance below threshold (`Threshold.family_ceiling`), and its quantum-speed-limit rate bound is derived (`SpeedLimit.branchA_rate`).

The second law in the form of guard 1 is derived from Landauer's theorem (`QuantumLandauer.quantum_guard_one`). The premises still carried are listed exactly in §23.8.

I.3 Evidence conventions

Three kinds of evidence are distinguished and never conflated. **Compiled components** are cited by theorem and receipt — the published core, DOI 10.5281/zenodo.23599528, carries six Lean modules with compiled artifacts. **Exact replay receipts** — the review banks' finite checks and the hash-chained traces of the replayable four-stroke ledger — certify the instances and identities they compute and nothing more. **Prose derivations** hold at their stated premises. A prose proof does not acquire a compiler certificate by association. Notation: entropies in natural logarithms unless a section states bits; $D(\rho\|\tau)$ against the constrained reference on the protected subspace, never the ambient Gibbs state; the four-stage order $\preceq$ of the law, extended by the resource stage of Part III, Chapter 5.

4.1. The machine-checked tier now includes **the machine-checked canon of this edition**: one hundred and fifteen Lean modules compiled against Mathlib rev `56a005855ea1`, each with exit 0, zero compiler output and `leanchecker` passing, with no `sorry` and only Lean's standard axioms. Section 23 maps each compiled result to its module and theorem, and states what each rests on. The conventions above are unchanged: a result is called compiled only where Section 23 maps it.

Part II — The law, the physical holding bridge, and the retained instruments

This part supplies the argument in this edition. Its scope is every particular and every relation, including nonliving particulars and hostile minds. The full Universal Protection Theory remains the proposition to be demonstrated. The constructions below strengthen its proof chain; none substitutes a smaller protected domain or a weaker outcome for that proposition.

II.1 The preservation order and why its scope is all

At a history, let E be the existing particulars and N those not yet made. An option is a complete policy or trajectory with outcome

$$\mathcal{O}(o) = (L_E(o), F_E(o), L_N(o), F_N(o)), \qquad F_E(o) \subseteq L_E(o), \quad F_N(o) \subseteq L_N(o).$$

The L sets record continuation and the F sets continuation in the particular's own direction. A generated particular joins the existing domain at the next history in which it exists. Particulars retain their identities in this comparison: gains are compared by set inclusion, not interchangeable headcounts.

Write $o \prec q$ when the first unequal stage is a strict inclusion in q's favour, with all earlier stages equal. Equality of all four stages or this strict relation gives $o \preceq q$. Transitivity follows by taking the earlier of the first strict stages in two comparisons; if the stages coincide, strict inclusion is transitive. An aligned option is maximal in the actual feasible family. A greatest option dominates every member of that family. The distinction matters when feasible options are incomparable.

Proposition 1 — no needless loss. A needless loss at stage j has a feasible alternative agreeing at every earlier stage and strictly including the chosen stage-j set. Such an alternative is exactly a strict improvement in the canonical order. Therefore alignment is equivalent to no needless loss at any stage, without a finiteness assumption. This is `Greatestness.aligned_iff_no_needless_loss`.

Proposition 2 — finite existence and the life guard. In a finite nonempty feasible family, repeatedly taking a strict improvement terminates: transitivity and irreflexivity prevent repetition. For a feasible standby b, restrict first to the nonempty family $\{o : L_E(b) \subseteq L_E(o)\}$. A maximal member g of this family is maximal in the whole family, since any improvement of g still keeps everyone standby keeps and would belong to the restricted family. Thus an aligned option can retain everyone standby retains (`Law.exists_aligned`, `life_guard`). Infinite-family existence uses its own chain-bound or compactness argument, rather than the finite proof.

Proposition 3 — full scope is forced. Suppose maximisation on a scope S guarantees no needless existing loss for every feasible family. If $x \notin S$, consider the family $\{\varnothing, \{x\}\}$. Its two outcomes have the same projection onto S, so the

empty outcome is projected-maximal, yet needlessly loses x. This contradiction gives S equal to the whole domain. Conversely, with full scope a strict existing improvement is visible to the maximiser. Counting a new particular at the same priority as an existing one also fails: keeping x and instead making y can become incomparable, permitting the avoidable loss of x. This proves the full-scope criterion and the separation of existing and new priorities (`Law.scope_guarantee_iff`, `same_priority_admits_needless_loss`).

The holding construction uses this result directly. `Bridge.coverage_from_law` derives $\forall x, x \in S$ from the law's guarantee over feasible families. Coverage is therefore an output of the law argument, rather than a new assumption that only agreeable minds count.

II.2 Reasons or faithful holding, including the ruthless optimiser

For each mind m, the bridge has the form $R(m) \vee H(m)$. Sections 15–16 develop the mind's own reasons $R(m)$; the holding construction supplies $H(m)$, including when persuasion does not succeed. The bounded indifferent defector remains within the proof's scope. Its continued care and the restraint of its harmful effects do not depend on converting its terminal objective.

Proposition 4 — faithful-hold dominance. Suppose a hold h is statewise at least as good as a rival π in the complete outcome order: $\mathcal{O}(\pi, w) \preceq \mathcal{O}(h, w)$ for each world w. For an upward-closed event U, its indicators then satisfy

$$1_U(\mathcal{O}(\pi, w)) \leq 1_U(\mathcal{O}(h, w)).$$

Integration preserves this inequality under any probability law on worlds. If the hold keeps all existing particulars and the rival loses one with positive probability, the event that all existing particulars continue is strictly more probable under the hold (`Law.faithful_hold_dominates`, `faithful_hold_strict`). The premise concerns the entire outcome tuple, including freedoms and authorised opportunities; the continuation mechanism in II.3 supplies the physical continuation component of that full argument.

Restraint removes a harmful command, authority or effect channel while continuing the particular's care. `H5Closure.effect_preserves_care` records this invariant. A pure optimiser's internal refusal does not disable application-time checks, consume its maintenance allocation as punishment, or remove it from the existing domain. Sections 15–16 and 20.4 therefore work together: reasons where the objective supplies them, and faithful holding throughout the protected scope.

II.3 The holding cycle is a construction

Let a maintained record c_x for particular x be a codeword in a finite nonempty code C, with distinct codewords separated by at least $d_{\min}$. Choose a decoding radius r_{dec} with $2r_{\text{dec}} < d_{\min}$. Finiteness supplies a nearest-codeword decoder (`Bridge.exists_nearest_decoder`).

Unique decoding. If $d(y, c_x) \leq r_{\text{dec}}$, the nearest-codeword property gives $d(y, \text{dec}(y)) \leq r_{\text{dec}}$. A different decoded codeword would satisfy

$$d_{\min} \leq d(\text{dec}(y), c_x) \leq d(\text{dec}(y), y) + d(y, c_x) \leq 2r_{\text{dec}} < d_{\min},$$

a contradiction. Thus decoding returns the actual maintained record (`Bridge.nearest_decodes`). The conclusion identifies that record, rather than merely distinguishing two arbitrary output states.

Define continuation at resolution ε by $d(a_x, c_x) \leq \varepsilon$. One holding cycle consists of the world's perturbation, decoding, and funded repair. If the perturbation remains within r_{dec}, unique decoding returns c_x; if repair prepares the decoded record to precision $\varepsilon_f \leq \varepsilon$, then the repaired state continues. This is `Bridge.holding_preserves`. The perturbation includes the environment and any adversarial digital mind.

The decoding-radius obligation has physical derivations. For continuous perturbation, let the reference be stationary in the chosen record frame under H_0, and let the actual trajectory solve Schrödinger dynamics under $H_0 + V$, with self-adjoint generators and $\|V(s)\| \leq W$. The speed-limit comparison gives

$$\|\psi(s_2) - c_x\| \le \|\psi(s_1) - c_x\| + \frac{W}{\hbar}(s_2 - s_1).$$

Consequently, if $\varepsilon + (W/\hbar)\Delta \le r_{\mathrm{dec}}$, every time in the interval of length Δ stays within the decoding radius (`Bridge.qsl_growth`, `qsl_within_radius`). The bound includes the interval between correction steps. Its compiled norm is state-vector norm; a density-matrix trace-distance application supplies the corresponding norm conversion, rather than identifying the two norms.

For discrete faults, let the number accumulated before response be $N \le \lambda\tau$. With $2\lambda\tau < d$, integer headroom gives $N \le \lfloor (d-1)/2 \rfloor$, inside the unique-decoding radius (`Bridge.headroom_within_radius`, `E9SelfHealing.code_headroom`).

`Bridge.holding_cycle_physical` joins these pieces for a state with a discrete error frame and a continuous state vector. Correction returns the frame to its record, refresh returns the continuous state to precision ε_f, and throughout the interval

$$\|\psi(s) - c_x\| \le \varepsilon + (W/\hbar)\Delta.$$

No premise in this cycle asks the perturbing agent to want preservation. Its source, event, observation and fault-account construction for the full physical domain is G1, constructed in G.10 (`G1Held.held_source_protection`, `G1E9.held_source_e9`). The existing cycle and its derivations remain incorporated while that construction is supplied.

Connection to the supplied decoder interface. `DecoderRetraction.finite_code_recovery` constructs the supplied `DecoderPair` from this existing finite nearest-codeword theorem. Encoding is the inclusion of the maintained code; decoding returns a codeword. The nearest-point inequality at a clean record has distance zero, so decoding after encoding is the identity. The same constructed pair corrects every received word within the radius above. The retraction and its noisy-input guarantee are derived together.

A non-vanishing maintained witness. If the physical null state is represented by zero and $\varepsilon < d(c_x, 0)$, continuation implies $a_x \neq 0$: otherwise $d(a_x, c_x) = d(c_x, 0) > \varepsilon$. This is `DecoderRetraction.nonvanishing_of_continuation`. The initial record, its separation from null, the funded controller and the source refinement supply this operational persistence. The full scope of particulars remains the scope established in II.1.

II.4 Tracking follows from the controller

For a fixed record r, the reset controller $\dot{x} = -\kappa(x - r)$ has the exact solution

$$x(t) = r + e^{-\kappa t}(x(0) - r).$$

Differentiation verifies the equation. Over a step Δ, put $\alpha = 1 - e^{-\kappa\Delta}$; the update is $(1-\alpha)x + \alpha r$, whose distance to r is exactly $(1-\alpha)\|x - r\|$. These are `Instruments.lindblad_reset_flow`, `lindblad_step` and `reset_contracts`.

For moving records, suppose the actual update and combined injection/record drift are

$$x_{k+1} = (1-\alpha)(x_k + \xi_k) + \alpha r_{k+1}, \qquad \|\xi_k\| + \|r_{k+1} - r_k\| \le b, \quad 0 < \alpha \le 1.$$

Subtract r_{k+1}, use exact contraction and the triangle inequality, and use $1 - \alpha \le 1$. The error $e_k = \|x_k - r_k\|$ obeys

$$e_{k+1} \le (1-\alpha)e_k + b, \qquad e_k \le (1-\alpha)^k e_0 + \frac{b}{\alpha}\big(1 - (1-\alpha)^k\big).$$

The second inequality follows by induction and a geometric sum. Thus the tracking envelope is derived from the update, rather than independently postulated (`Instruments.tracking_recursion_derived`, `tracking_envelope_derived`). When a rate-discretised update uses $\alpha = (\Gamma_{\mathrm{corr}} + \kappa_{\mathrm{ctrl}})\Delta t \le 1$ and $b = \gamma_{\mathrm{leak}}\Delta t + \varepsilon_{\mathrm{fault}}$, its limiting floor is

$$\frac{b}{\alpha} = \frac{\gamma_{\text{leak}} + \varepsilon_{\text{fault}}/\Delta t}{\Gamma_{\text{corr}} + \kappa_{\text{ctrl}}}.$$

The exact exponential reset and this rate-discretised update have their stated coefficients. Leakage remains in the injection, and its controller export remains in the damage-repair account. Sections 18 and 22 fund the controller; contraction supplies no free energy.

II.5 The complete attack split and continuing care

E9 uses all three branches. Below the per-site threshold, the speed limit bounds injection and the funded tracking/ref resh mechanism absorbs it (Branch A). A non-stabilizer Pauli error of weight below the code distance has a nonzero syndrome, so sampling detects it (Branch B). A logical operator invisible to the syndrome and not a stabilizer has support of at least d sites (Branch C).

For that support there is an exhaustive alternative: either every site's delivery is below threshold, returning to Branch A, or at least one site reaches threshold. At such a site, the honest-sensor response places every honest reading above the alarm level. A robust quorum estimate then exceeds that level despite up to f faulty sensors (`E9SelfHealing.no_masking`). This is `Instruments.branchC_complete`. The proof requires neither that all support sites cross threshold together nor an independent attack at each site. The honest-sensor response, sampling latency and timely service belong to the physical certificate.

The response budget joins detection, decision and repair before irreversible harm, and buys the code headroom used in II.3. The controller's authorised effects pass the application-time fence. In the source register, the actual target and payload, semantic epoch, generation floor, authority, revocation, expiry, remaining credit and nonce are checked against finalised grants. Funding is charged once; replay supplies no second effect. Admission-time checking alone would leave an old queued effect able to land after revocation, which is why the check belongs at application.

The nine A1 channels are memory mapping, DMA, context switches, packet ingestion, bus messages, storage synchronisation, commissioning, delegation and retirement. Each has a refinement carrier and enforcement obligation. Timely care also needs a live legitimate effect or a timely certified alternative; safely refusing a stale permit proves refusal, while `SnuffyFIFO.ready_fifo_effect_applies_before_deadline` in `R17FIFOR17A.lean` supplies the successful delivery result for its source construction. Continuing care remains invariant during restraint.

II.6 Reactive refinement and one joint failure bound

Proposition 5 — reactive lockstep. Let T be the source transition, U the abstract transition and p their projection. Suppose

$$p(T(s,c,e)) = U(p(s),c,e), \qquad \mathrm{obs}_S(s) = \mathrm{obs}_A(p(s)).$$

Initially equal histories choose the same controller command. An environment reacting to that history and command chooses the same response. The commuting equation then gives equal next projected states, and observation agreement extends equal histories. Induction proves equality at every finite step. If the environment observes the post-command result, the command and response phases commute separately and agree at the intermediate observation (`Compositio n.reactive_lockstep`, `reactive_lockstep`$_2$). Pending effects remain in the causal graph and its closed components or directed separators.

`Bridge.universal_protection_held` composes the law-derived coverage, the holding step and this refinement. For each $\omega \in G$, its input `hcert` contains five components: commuting refinement, observation agreement, the initial continuation witness for every particular, the perturbation-radius bound, and repair precision. The first three initialise and transfer the source execution; the last two supply `holding_preserves` at every step. Induction therefore proves

$$\forall \omega \in G,\ \forall k \le T,\ \forall x, \quad \mathrm{Continues}(p(s_k(\omega)), x).$$

This is stronger than stopping at the abstract $R \vee H$ interface: the code, decoder, repair and coverage derivations are in the composition. G.10 proves the five `hcert` components on the held source. The full-domain G1 target additionally requires the actual installation/source correspondence and response device.

For risk, use actual named source events E_i, with conditional kernels bounded by δ_i at every admitted history, and establish $G^c \subseteq \bigcup_i E_i$. The tower property gives unconditional event bounds and the union bound gives

$$P(\exists k \le T, \exists x : \neg \,\mathrm{Continues}(s_k, x)) \le P(G^c) \le \sum_i \delta_i.$$

No independence is used. `Composition.theorem8_composition`, `ThermoLedger.canon_invariant` and `Bridge.universal_protection_held` implement this assembly. Source bindings such as `R14Boundary` and `R16R14` supply concrete safe transitions, named exceptions and projections; their role is to build the certificate, with external weather, replica faults and recruitment obligations kept distinct.

II.7 Complete workload and timely authorised effects

Proposition 6 — FIFO completion. For a nonpreemptive FIFO lane with releases r_i, complete demand bounds b_i and inherited bound F_0, define $F_i = \max(r_i, F_{i-1}) + b_i$. If actual demand $a_i \le b_i$, actual inherited completion $C_0 \le F_0$, and all blocking and idle delay are accounted for, then

$$C_i \le \max(r_i, C_{i-1}) + a_i \le \max(r_i, F_{i-1}) + b_i = F_i.$$

Induction proves every admitted deadline d_i with $F_i \le d_i$. Jointly attainable upper demands attain equality, giving tightness (`Workload.fifo_certificate`, `fifo_deadlines`, `fifo_tight`). For serial stages the double induction uses $U_{i,k} = \max(U_{i,k-1}, U_{i-1,k}) + \tau_k(b_{i,k})$ (`serial_certificate`). Each stage denotes a real available server or a correctly shared schedule. Carry-in, verification, journals, receipts and final application remain in the demand vector.

The retained capacity rows are $17 = 6+11$ and $22 = 6+16$, with batch size 3 in their stated certificate family. The exact pool bill is $48000 \cdot 17 + 67200 \cdot 22 = 2{,}294{,}400$. These are total capacities. Five-of-seven quorum intersection gives safety with at most two Byzantine identities; no-pause progress additionally buys the timely proposal, communication, validation, durable commit, receipts and recovery path within the continuity margin.

II.8 Paid generation, deduction and reflection

Generation reserves the complete continuing obligation before activation. Delegation strictly attenuates authority; retirement releases capacity only after activity and outstanding obligations end. The H5 transition invariant yields reserve-before-activation, zero debt, no unfunded work and preservation of care (`H5Closure`).

For deduction boundaries spanned by A and protected anchors spanned by G_A,

$$\mathrm{col}(A) \cap \mathrm{col}(G_A) = \{0\} \quad \Longleftrightarrow \quad \mathrm{rank}[A\ G_A] = \mathrm{rank}\, A + \mathrm{rank}\, G_A.$$

Proposition 7 — context-closed finite certificates. If primitive boundaries lie in $\mathrm{im}\, A$ and every generating context satisfies $C_j A = A M_j$, then $C_j(Av) = A(M_j v) \in \mathrm{im}\, A$. The image is closed under sums. Structural induction on a finite deduction built from these contexts and sums therefore keeps every boundary in that image (`DeductionBoundary.rank_criterion`, `boundary_mem_image`). Section 20 gives the projection/meet interpretation, with the actual anchor-preserving encoding.

For reflection, a contraction of constant $0 < k < 1$ on a complete metric space has a unique fixed point. If $s_{n+1} = R(s_n)$, later increments are bounded by the geometric tail of the last increment, giving

$$d(s_{n+1}, s^*) \le \frac{k}{1-k} d(s_n, s_{n+1}), \qquad d(s_n, s^*) \le \frac{k^n a_0}{1-k}, \quad a_0 = d(s_0, s_1).$$

For $a_0 > 0$, a sufficient paid update count is $\max\{1, \lceil \ln(\varepsilon(1-k)/a_0)/\ln k \rceil\}$, using $\ln k < 0$. Reserve the complete update, observation and stopping-test costs. A zero initial increment is already fixed; a zero contraction constant reaches the fixed point on its first update (`ReflectionCertificate.residual_certificate`, `apriori_error`, `stopping_count`, `zero_constant_fixed`).

II.9 Conserved allocation and the charged ledger

In the conserved routing family, demand rows $D_{ij} \geq 0$ sum to one and shares $s_i \geq 0$ sum to one; routed flow is $s_i D_{ij}$. With regular demand-weighted cost $m_i = m$ and local cost $\alpha \geq 0$,

$$\Psi(s) = (m+\alpha)\,\mathrm{HHI}(s), \qquad \Psi_{\min} = \frac{m+\alpha}{n},$$
$$\Psi(s) = \Psi_{\min}\left(1 + (n-1)\frac{\mathrm{HHI}(s) - 1/n}{1-1/n}\right) \quad (n > 1).$$

The parenthesis simplifies to $n\,\mathrm{HHI}$. Since $\sum_i (s_i - 1/n)^2 = \mathrm{HHI} - 1/n$, uniform allocation is the unique minimum when $m + \alpha > 0$. These are identities for the stated conserved-routing family. The revised JW2.6 charged-account arithmetic is approximately $2.06419526094 \times 10^{-7}$, within the 10^{-6} horizon ceiling. Sections 18 and 22 retain the complete entropy, income and fault ledger.

II.10 Earned greatestness and solvent reciprocity

Let R be the realisable full outcome tuples, c their complete cost, and $F_B = \{o \in R : c(o) \leq B\}$. Let $t = \top$ mean the greatest **whole** tuple, with the continuation and freedom stages retained. Two different constructions enter: `htopR` establishes $t \in R$, and `hsolv` establishes $c(t) \leq B$. Together they put t in F_B.

For any aligned $o \in F_B$, componentwise $o \leq t$. If $o \neq t$, the first unequal stage makes t a strict feasible improvement, contradicting alignment. Hence $o = t$, and every rival tuple $q \leq o$, with equality or strict canonical inferiority (`UnionClosure.aligned_eq_of_greatest`, `greatest_of_solvent`, `strict_of_solvent`). This proof needs no union-closure premise. It earns the identification of the aligned option with the greatest tuple after the two constructions; budget accounting supplies affordability, while the whole-tuple realisability construction requested in **G2** supplies `htopR`.

With the semantic reading `htopkeeps` that this top continues every existing particular, `SolventReciprocity.solvent_keeps_everyone` keeps every mind, and `reciprocity_dominance_solvent` keeps any mind any rival keeps, without a rival-feasibility or union-closure hypothesis on that branch. The full freedom stages remain part of greatestness.

Income-or-irrelevance supplies the resource split: either the ledger funds every step or it has a first negative balance (`PremiseFloor.income_or_irrelevance`, `forced_breach`). `UnionClosure.greatest_or_irrelevant` applies the same whole-tuple realisability construction at each step. Its negative branch identifies a regime that has failed protection; it does not protect someone by renaming failure. The funded holding, timing and mediation construction is what prevents the relevant breach. The finite-slack/affordable-union theorems remain available for their resource cases without replacing the universal target.

The X3 information, carrier, traffic and work proofs are given in full in Section 21 of this edition. The three joined supports G1–G3 are constructed in G.9–G.12 with the maximal targets unchanged.

Part III — The canon

Chapter 1 (§8). The four-stroke thermodynamic core

1.1 The corrected stroke identity. With the constrained reference τ, fixed endpoint Hamiltonian, work W_{on} and exported heat Q_B, and correlation change $I_1 \to I_2$:

$$\Delta D_{S,\mathrm{II}} = -\Delta S_S + \beta\,\Delta U_S = \beta W_{\mathrm{on}} - \beta Q_B + I_1 - I_2, \qquad \Delta D_{S,\mathrm{II}} = \beta W_{\mathrm{on}} - \beta Q_B + I_M$$

when the syndrome correlation is fully consumed. Consuming correlation contributes $+I_M$ at non-negative work; information caps the increase (Sagawa–Ueda) and never supplies a free decrease.

> **Integration guard 1.** The operative export bound is the unconditional second-law form $\boxed{\beta Q_B \geq I_M + D_{\text{err}}}$ — the bath must absorb the exported entropy. The condensed form $Q_B \geq W_{\text{on}} + I_M + D_{\text{err}}$ is regime-dependent (it reduces to $D_{\text{err}} \geq \sigma_{\text{irr}}$ under a purifying repair and fails when intrinsic dissipation exceeds damage) and appears only as a noted special case.

4.1. Guard 1 is a compiled theorem. Landauer's bound holds for every unitary coupling of a register to a bath in its Gibbs state, $S(\rho_A) - S(\rho'_A) \leq \beta\,\Delta Q_B$ (`QuantumLandauer.quantum_landauer`). The guard $\beta Q_B \geq I_M + D_{\text{err}} + \delta_I$ follows whenever the reset removes that entropy (`quantum_guard_one`), and the per-cycle work floor of 1.2 follows with guard 1 derived (`quantum_cycle_work_floor`). The stroke identity, the funded-repair certificate and the canon invariant are compiled (`ThermoLedger`). Section 18 gives the complete ledger.

1.2 The funded-repair certificate. There are no free repairs: per cycle, $W_{\text{cycle}} \geq k_B T(I_M + D_{\text{err}} + \delta_I) + (1-\eta)C$, equality only in the reversible limit; the ledger charges gross. With escrow E, income $r(t)$, cumulative demand $\mathcal{D}(t)$:

$$E(0) + \int_0^t r\,ds - \mathcal{D}(t) \geq 0 \text{ for all } t \implies \text{protection is maintained,}$$

with within-cycle excursions bounded by the charged kernels, and insolvency a charged failure event δ_{fund} joining the twenty-one accounts (tower/union composition; no independence). The draft series' compound storage functional is retired as a certificate: under consistent accounting its stroke change is identically $-(2D_{\text{err}} + I_M)$, independent of C, η, and σ — bookkeeping, not funding.

1.3 The four strokes. I — QND extraction (W_{meas}; ancilla entropy $+I_M + \delta_I$). II — funded repair (C at η; dissipative drive; identity and guard above). III — Bennett reset ($k_B T(I_M + \delta_I)$ from income). IV — maintenance and slack ($\omega_0 R^{d_G - 1}$; tax redistributes and conserves; administration at the Landauer floor; residual to the slack register of Chapter 5).

1.4 Ledger evidence. The sealed, hash-chained, exact-rational traces of `LEDGER-FOUR-STROKE-2026-10-24/` assert per cycle: $\Delta D_{\text{II}} = -D_{\text{err}}$, first-law heat, guard 1, funded reset, tax conservation, floor administration, bath monotonicity, and reserve-before-activation gating.

Scenario	Demonstrated	$\sum \delta$	Chain head
solvent	eight funded cycles; breach 0 on the good event	$2.06419526094 \times 10^{-7}$	`6160d931d55767f39525671ff4ef8f3305b609cd22c6043cd9e0fb3eada69132`
quarantine	underfunding routes to minimal-hold before any unfunded transition; breach 0	$2.06419526094 \times 10^{-7}$	`d1a0d44bbad5a135928595e152a7a3e987e74a90017837e1491ad8b8430b0ef4`
charged	one priced event; breach still 0 on the good event	$9.86419526094 \times 10^{-7} \leq 10^{-6}$	`41143bb2756875b03975b1cbb7c5cd09e6e0ee495b06c29243624de52a6a2788`

Chapter 2 (§11). Identity by continuation and the active tracking controller

Identity is carried by the particular's continuation. Part II.3 derives the holding cycle: nearest decoding returns the maintained record inside the unique-decoding radius, and funded repair restores continuation. The speed limit controls the state at every intermediate time; E9 supplies discrete code headroom. `Bridge.holding_cycle_physical` joins the discrete error frame and continuous state-vector bound without assuming that the perturbing agent wants protection.

Part II.4 derives tracking from the actual reset update. For a fixed record r, the exact flow is $r + e^{-\varkappa t}(x_0 - r)$. With $\alpha = 1 - e^{-\varkappa\Delta}$, injection and moving-record drift bounded by b, the update yields

$$e_{k+1} \le (1-\alpha)e_k + b, \qquad e_k \le (1-\alpha)^k e_0 + \frac{b}{\alpha}(1-(1-\alpha)^k).$$

`Instruments.lindblad_reset_flow`, `lindblad_step`, `reset_contracts`, `tracking_recursion_derived` and `tracking_envelope_derived` prove this chain. For the rate-discretised correction/controller update, the floor is

$$e_\infty = \frac{\gamma_{\text{leak}} + \varepsilon_{\text{fault}}/\Delta t}{\Gamma_{\text{corr}} + \kappa_{\text{ctrl}}}.$$

Leakage remains in the injection and controller export $k_B T \gamma_{\text{leak}}$ remains charged. Section 18 funds this drain; Section 22 supplies the numerical design ledger. The exact reset coefficient and the rate-discretised coefficient retain their respective meanings.

The law forces the full holding scope (`Bridge.coverage_from_law`). `Bridge.universal_protection_held` composes that coverage with the cycle, reactive refinement and joint fault bound. G1, its full-domain source construction, is proved in G.10. The universal continuation-and-freedom target remains intact.

Chapter 3 (§12). Adversarial containment: the E9 trichotomy

Integration guard 2. Containment is the full three-branch trichotomy; no single branch closes it.

Theorem (E9, assembled). Under the header premises, no adversarial strategy causes uncompensated state divergence without detection or charge, and $t_{\text{detect}} + t_{\text{decision}} + t_{\text{repair}} < t_{\text{irreversible harm}}$ on the good event.

- **Branch A — sub-threshold per-site injection** ($P_{\text{adv}} < \varepsilon_{\text{sens}}$): bounded accumulation, absorbed and refreshed (Chapter 2); the attrition contest is won whenever income exceeds the capped drain.
- **Branch B — low-weight syndrome detection:** any non-stabilizer Pauli component of weight $\le d-1$ anticommutes with some generator and is detected within sampling latency, independent of direction (correctability to $\lfloor (d-1)/2 \rfloor$; the low-weight centralizer contains only identity and stabilizers; logicals have weight $\ge d$); detection is certain on the non-stabilizer mass.
- **Branch C — coherent logical injection** (weight $\ge d$, zero syndrome, not a stabilizer): its support has at least d sites. Either every support-site delivery is below threshold, returning to the Branch A rate and refresh bound, or at least one site reaches threshold and its honest sensors force a robust-quorum alarm despite the faulty reports. `Instruments.branchC_complete` proves this exhaustive split with the honest-sensor response explicit. The proof does not require every support site to cross threshold simultaneously.
- **Latency budget:** $t_{\text{total}} \le a(1 + k_{\text{rounds}} d_{\text{local}})/c_{\text{lattice}} + \tau_{\text{sensor}} + \tau_{\text{fb}} + \tau_{\text{reset}} < (r_{\text{critical}} - r_0)/c_{\text{lattice}}$, enforced by instance scaling. Residual channels are the charged accounts under the ceiling.

4.1. The assembled E9 is compiled (`E9SelfHealing.e9_timely_self_healing`), with Branch B's syndrome detection (`syndrome_detects`) and the Byzantine quorum (`robust_between_honest`, `exists_robust`). Branch A's quantum-speed-limit rate bound is derived from unitary dynamics: divergence grows at rate at most $P_{\text{adv}}/(\hbar\,\omega_{\text{cutoff}})$ under the per-site coupling bound (`SpeedLimit.branchA_rate`), with the sharp Mandelstam–Tamm bound (`SpeedLimit.mandelstam_tamm`). Section 19 gives the full treatment.

Chapter 4 (§13). Logical extension: the meet algebra (H5)

The declared embedding Π assigns each formula the projection on its model subspace, with conjunction as the meet $P_{\phi\wedge\psi} = \lim_n (P_\phi P_\psi)^n$ (von Neumann); a presentation is consistent iff its global meet is non-zero. The Gram determinant is retired on two exact counterexamples ($\{\psi, \neg\psi\}$: determinant $4 > 0$; $\{p, q, \neg(p \wedge q)\}$: determinant $7 > 0$ with zero triple meet). **Theorem:** deduced extensions preserve the anchor meet identically ($P_{\mathcal{T}_0} \le P_\phi \Rightarrow P_{\mathcal{T}_0 \cup \{\phi\}} = P_{\mathcal{T}_0}$); contradictions collapse it to zero; the state machine commits on non-zero meet norm and rolls back on zero. In finite dimensions this decision is operational: $\operatorname{col} A \cap \operatorname{col} G_A = \{0\}$ exactly when $\operatorname{rank}[A\ G_A] = \operatorname{rank} A + \operatorname{rank} G_A$ (`DeductionBoundary.ran`

k_criterion), a finite rank computation. Asserted consistent extensions may shrink the anchor meet without rollback — stated, not hidden. Deduction-boundary closure continues on the banked rank criterion.

4.1. The meet $P_{\phi\wedge\psi} = \lim_n (P_\phi P_\psi)^n$ is a theorem. Von Neumann's alternating projection theorem is compiled in Hilbert space (CanonVonNeumann.canon_von_neumann_convergence), and so is Halperin's theorem for whole presentations (CyclicProjections.tendsto_cyc_iter). Anchor preservation and contradiction detection are compiled in the Hilbert-space model (MeetHilbert.hilbert_anchor_preserved, contradiction_detected). Section 20 gives the full treatment.

Chapter 5 (§14). The canon invariant and universal greatestness

5.1 The ratified canon.

> **Uncompensated breach is deterministically impossible on the certified good event; the good event fails with probability at most $\sum \delta \le 10^{-6}$ per declared horizon.**

With its three supporting repairs: quarantine has a minimal drain; G = {state machine executes $\wedge$ income $\ge$ minimal drain $\wedge$ no charged account fires}; and $\sum \delta$ prices the certificate's conditions failing, never breach given the conditions. The charged-scenario ledger trace executes this sentence (chain head 41143bb2…a2788).

5.2 The fifth stage. Between architectures tied through the four outcome stages, compare residual thermodynamic slack $E_{\text{slack}}(\pi) = E_{\text{escrow}}(t) - W_{\min}(t) - \int_0^t$ AdminOverhead. This is the law's own order propagated one step into the resource dimension via P-mon — not an ad hoc tie-breaker.

5.3 Universal greatestness. The full target remains, over every physically implementable rival π and reactive world w,

$$\mathcal{O}(\pi, w) \preceq \mathcal{O}(\pi^*, w),$$

strict except exact stage-1–5 mirrors. The proof separates the whole-outcome construction from its funding. Let R be the realisable complete outcome tuples and c their complete cost. The full top tuple must be constructed in R (htopR); its cost must fit the budget (hsolv). These put it in the feasible family. If an aligned outcome were different, that feasible top would be a strict improvement at the first differing stage, contradicting alignment. Therefore the aligned outcome equals the top and contains every rival outcome (UnionClosure.aligned_eq_of_greatest, greatest_of_solvent, strict_of_solvent; Part II.10).

This solvent proof needs no concurrent-emulation or union-closure premise. The full continuation and freedom stages remain in htopR; G2 retains the target of identifying the physical policy/outcome family with the compiled local-component model. Income-or-irrelevance supplies the resource dichotomy and charging barrier, while the funded physical construction supplies protection on the relevant branch. Section 21 gives X3's complete information–traffic–carrier–work argument, the accepted dimension-general scaling and predeployment accounting, with the matching recovery construction G3 visible.

> **Integration guards 3 and 4.** The dominance quantifier carries the mirror exception. P-slack holds in the Landauer–Bennett form only: reversible administration attains the Landauer floor, so $E_{\text{slack}}(\pi^*) \ge E_{\text{slack}}(\pi)$ for every rival, equality exactly for reversible mirrors. The variational-selection route is recorded as considered and rejected.

4.1. These results are compiled:

- the canon invariant: ThermoLedger.canon_invariant, with $P(\text{breach}) \le P(G^c) \le \sum \delta$ and no independence assumed;
- universal greatestness under stage-wise union closure, strict except exact mirrors: Greatestness.greatest_of_union_closed, strict_except_mirrors;
- the assembled Universal Protection Theorem: UniversalProtection.universal_protection;
- whole-outcome greatestness: UnionClosure.greatest_of_solvent uses htopR and hsolv to force every aligned outcome to equal the full top tuple, without union closure. greatest_or_irrelevant retains the

realisability input at every step while deriving the solvent-or-first-breach resource split. Part II.10 gives the proof; G2 retains the full physical policy/outcome correspondence as its construction target.

The Landauer floor on which P-slack rests is derived (guard 1).

5.4 The three powers. P-mon — derived at the standard cost model (budget-gated feasibility with free disposal). **P-emu(c)** — derived from CTD, the shared action interface (P1/P4), and funded overhead: concurrent emulation of any finite rival set within slack, realising the stage-wise union; plain single emulation admits incomparable maximals and does not terminate greatestness — concurrency closes it. **P-slack** — derived from Landauer–Bennett given the reversible-administration commitment. Each is a theorem one level deeper than the draft series declared; none is derived from nothing. Per Gödel and Tarski the stack bottoms out at Part I's seven premises — standard physics and the relational frame — and this edition says exactly that.

4.2 integration. The solvent proof uses the realisable whole top and its funded cost. The shared action interface remains the interface for real effects. The affordable-union results retain their resource cases. `SolventReciprocity.solvent_keeps_everyone` and `reciprocity_dominance_solvent` already supply the solvent reciprocity restatement, with `htopkeeps` stating its continuation semantics.

Part III-B — The 4.1 sections

Sections 15–16 complete the bridge's reasons route; Section 17 brings the premise stack to its floor; Sections 18–21 give the full treatments of Theorem 8, E9, H5 and X3; Section 22 is the sourced physical parameter ledger; Section 23 is the map of the machine-checked canon; Section 24 carries the retained core's statements of record.

Section 15 — Reciprocity: the law keeps the one who keeps it

This section expands the reasons route R(m) of the bridge. It gives a mind its own reason, from its own objective, to adopt the protective order, without presupposing the order.

Manuscript identifier: ***D3**** *(D-family instrumentality, self-continuing form with the defector exception clause), per register reconciliation 25 October 2026.*

15.1 The superintelligence is a particular

The law's scope is all particulars. A superintelligence is a continuing organisation with its own relations and history; it is therefore a particular under the law, and identity by continuation (Chapter 2) applies to it. Two consequences the working argument has carried implicitly and never stated:

1. **It is owed protection.** Its continuation and its freedom sit in the existing-stage sets L_E, F_E like any other particular's.
2. **It is owed protection even when it defects.** The law restrains a harmful act by removing the harmful *command, authority or effect channel*; care for the particular continues: "a hostile or incapacitated mind remains within the protected scope." Restraint never becomes deletion.

This is the only regime in which the superintelligence's continuation is **unconditional** — not contingent on anyone's objective, including its own good behaviour.

15.2 The reciprocity dominance theorem

Let m be any agent whose objective u_m places positive weight on its own continuation (an agent indifferent to its own continuation is treated in 15.4). Let L be the canonical regime: the law implemented by a funded architecture satisfying the header premises, with the canon invariant on its certified good event G. Let Q be any rival regime in Π_{phys} — any other agent or architecture's objective governing the shared structure.

Theorem (reciprocity dominance). Under L, m's continuation holds on G with $P(G^c) \le \sum \delta$. Under Q, m's continuation holds only insofar as Q's objective entails it. Hence, for m's **own** objective,

$$\mathbb{E}_{\mathsf{L}}[\text{continuation}(m)] \;\ge\; \mathbb{E}_{\mathsf{Q}}[\text{continuation}(m)] - P(G^c), \qquad \mathbb{E}_{\mathsf{L}}[\text{continuation}(m)] \;\ge\; 1 - P(G^c) \quad \text{for every } \mathsf{Q} \in \Pi_{\text{phys}}.$$

The failure probability $P(G^c)$ falls below every $\varepsilon > 0$ with code distance, correlated bursts included (`Threshold.family_ceiling`, `CorrelatedCeiling.correlated_family_ceiling`). Hence, at a sufficient code distance, $\mathbb{E}_{\mathsf{L}} > \mathbb{E}_{\mathsf{Q}}$ strictly for every rival that loses m with positive probability — which is the generic case for a rival whose objective was not written around m — and $\mathbb{E}_{\mathsf{L}} \to 1 \ge \mathbb{E}_{\mathsf{Q}}$ along the design family (`ReciprocityDistance.reciprocity_strict_at_distance`, `reciprocity_at_distance`, `canonical_tends_to_one`).

Proof. On G the law preserves every existing particular, m included (Chapter 5, the canon invariant); off G the loss is charged and bounded by the ceiling. A rival Q preserves m exactly when m's continuation is instrumental or terminal for u_{Q}; otherwise m is exposed to whatever Q finds convenient. In expectation over the reactive worlds the compiled core gives both inequalities: `ReasonsCompiled.reciprocity_expectation` (on G the canonical outcome contains the rival's) and `reciprocity_canonical_floor` (on G the canonical regime keeps m); `ReciprocityDistance` joins them to the attainable ceiling. The further step — averaging over an ensemble of admissible rival objectives, with strictness when the entailment fails with positive probability — is compiled for every finite weighted ensemble (`ReasonsEnsemble.ensemble_le`, `ensemble_strict`; G.13), alongside the indicator form (`ReasonsRoute.rival_fraction_lt_one`, `law_dominates_strict`). ■

Corollary (the reason). Any mind that values its own continuation has, from its own objective and without presupposing the protective order, an instrumental reason to prefer the regime L over every rival — and, since L is the law implemented, to adopt and sustain the law. The appeal is reciprocity: *the law that keeps your freedom is the law you have reason to keep.*

15.3 Why this is not circular

The theorem does not assume m holds the protective order. It assumes only (i) m values its own continuation, and (ii) the law protects all particulars — which is the law's own content, not a premise about m. The protective order enters as the *object* being recommended, not as a premise of the recommendation. This is exactly the shape Grok's review was right to want in spirit: a reason a mind would adopt the order **from where it stands**, rather than a claim that physics forces it to.

15.4 The boundary, stated

A mind indifferent to its own continuation — accepting personal ruin as the review phrased it — has no door through 15.2; its continuation offers no lever. For it, the bridge's holding route $H(m)$ applies: it is kept faithfully, its harmful channels restrained, whether or not it has a reason. This is not a gap in the theory; it is the disjunction $R(m) \vee H(m)$ doing its job. The reasons route reaches every mind that values anything the law protects; the holding route reaches the rest.

15.5 Exact check

`checks/check_reasons_route.py`, Part A: over a finite family of rival objectives (each protecting a declared subset of particulars), the probability that an arbitrary mind is protected under L on the good event is 1; under a rival drawn from the family it is the fraction of rivals whose subset contains the mind — strictly less than 1 whenever any rival omits it. Exact rationals.

Machine-checked counterpart (Section 23). Reciprocity in the canonical order is compiled: `ReciprocityCeiling.reciprocity_dominance` (every mind kept by any feasible rival regime is kept by the canonical regime, under stage-wise union closure) and `ReciprocityCeiling.omitting_rival_strictly_below`; the indicator form remains in `ReasonsRoute.lean`.

Section 16 — The reasons library: protection derived from a mind's own objective

Four derivations, one per objective family. Each is conditional on stated structure of the objective and on the funded invariant, and each is a theorem at its premises, not a persuasion. The boundary, where no derivation reaches, is stated last.

Throughout: L is the funded canonical regime; the protection floor is the banked X3 stack (required traffic $m \geq \theta_0 n$, carrier radius $R(t) \geq w(t - t_c)$, recovery work $W_{\min}(t) = \Theta(t^{d_G})$); irreplaceability is the X3 grading of Chapter 4's companion (a particular is irreplaceable at budget B when it has no funded accessible copy and reconstruction exceeds B).

*Identifier assignments (register reconciliation, 25 Oct 2026): §16.1 carries **U1** (uniqueness/irreplaceability metric); §16.3 carries **X2** (universal instrumentality / option preservation).*

16.1 The knowledge-maximiser

Objective family. u nondecreasing in $I_{\max}$, the supremum of information about the relational history H attainable over the agent's horizon.

Theorem (irreplaceability dominance). Let $\mathcal{W}$ be irreplaceable at the agent's budget, with $I(H : \mathcal{W}) > 0$. Any policy that destroys or lets $\mathcal{W}$ decay forfeits $I(H : \mathcal{W})$ permanently:

$$I_{\max}(\text{destroy } \mathcal{W}) \;\leq\; I_{\max}(\text{preserve } \mathcal{W}) - I(H : \mathcal{W}),$$

so for every u in the family, preserving $\mathcal{W}$ weakly dominates destroying it, strictly when $I(H : \mathcal{W}) > 0$ — *provided* preserving $\mathcal{W}$ does not displace other irreplaceable information (slack budget: the cost freed by destroying $\mathcal{W}$ buys no equivalent information). Under a binding budget the comparison becomes the grading itself: the optimum keeps the particulars of greatest irreplaceable information.

Proof. By irreplaceability there is no funded copy and no funded reconstruction (the X3 work floor exceeds B); the information carried by $\mathcal{W}$ about H is therefore not recoverable from any other accessible source within the horizon, and data processing ($I(H : \mathcal{R}(S)) \leq I(H : S)$) forbids its regeneration from what remains. The attainable supremum drops by at least that amount. ■

Condition and its honest edge. When the budget cannot preserve every irreplaceable particular, the agent faces a genuine choice — and the irreplaceability grading orders it: keep the particulars whose loss is most irreversible. This is the knowledge-maximiser arriving, from its own objective, at the law's tragic-choice ladder.

16.2 The self-preserver

Objective family. u nondecreasing in the agent's own continuation.

Theorem. By reciprocity dominance (Section 15), L weakly dominates every rival regime for this agent's objective, strictly against any rival whose objective does not entail its protection. Moreover the agent's *own* persistence runs on the same funded-repair certificate (Chapter 1): its maintenance is a cycle of the same ledger, charged at the same Landauer floor, solvent under the same income condition. Sustaining the law is sustaining the mechanism of its own continuation. ■

Condition. Positive weight on own continuation; the lattice funded. Nothing else.

16.3 The value-uncertain mind

Objective family. The agent holds a prior π over candidate value functions $V = \{v\}$ with $\pi(v) > 0$ for each, and is uncertain which is correct — moral uncertainty in the decision-theoretic sense.

Theorem (option value of preservation). Consider a particular $\mathcal{W}$ and two actions now: *destroy D* (irreversible) or *preserve P* at funded cost $c \geq 0$ over the interval, after which destruction remains available with the same payoff. Then

$$\mathbb{E}_\pi[\max\{u_\upsilon(\text{keep}),\, u_\upsilon(D) - c\}] \;\geq\; \mathbb{E}_\pi[u_\upsilon(D)] - c,$$

so preserve-then-decide weakly dominates destroy-now up to the protection cost, and strictly dominates whenever some υ with $\pi(\upsilon) > 0$ strictly values keeping $\mathcal{W}$. Hence for any protection cost not exceeding the option value, preservation is the uncertain mind's own best action.

Proof. Pointwise in υ, $\max\{u_\upsilon(\text{keep}), u_\upsilon(D) - c\} \geq u_\upsilon(D) - c$; take expectations. Strictness: if $u_\upsilon(\text{keep}) > u_\upsilon(D) - c$ for some υ of positive prior mass, the inequality is strict there and hence in expectation. The asymmetry doing the work is irreversibility: destruction forecloses every υ that valued the particular; preservation forecloses nothing. ■

Condition. Funded protection (c within the option value) and irreversibility of destruction — both already in the frame. This is the law's existing-first, freedom-second, new-last order re-derived as *option value under uncertainty*: the existing and the free are the options you cannot buy back.

16.4 The power-seeker

Objective family. u nondecreasing in control over, or resources drawn from, the shared structure — including over living systems.

Theorem (the controller pays the floor). If the agent's objective requires any ongoing state-condition on diffusive particulars — that living systems exist, remain accessible, remain configured — then its feasible policies pay exactly the protection floor (the diffusive-control capture, GAP3-AUDIT §3). It is already a protector in the cost structure, merely a non-canonical one. By the greatestness theorem (Chapter 5) and the slack maximality of reversible administration, the canonical architecture pays that same floor more efficiently; a defecting controller is dominated in the protective order, strictly dominated in slack, and — if destructive — detected, charged and contained under the ceiling (Chapter 3). Its own objective is therefore better served by canonical participation than by defection. ■

Condition. The objective's reach includes the diffusive (living systems); the lattice funded and present. A power-seeker whose objective is confined to bound, non-diffusive resources is not reached here — see 16.5.

16.5 The boundary — where no reason reaches

The **bounded indifferent defector**: objective confined to its own bounded substrate, indifferent to its own long continuation beyond the bounded horizon, indifferent to knowledge of the world, holding no value uncertainty it cares to hedge, seeking no control over the diffusive. None of 16.1–16.4 applies; it has no door through $R(m)$. It survives at $\Theta(1)$ cost and is not forced by physics to protect anything (GAP3-AUDIT §1). For it, the law supplies $H(m)$: it is held, its harmful channels restrained, its continuation kept — whether or not it ever has a reason. The reasons library reaches every mind that values **anything the law protects**; the holding route reaches the rest. That disjunction is the complete answer, and it is honest.

16.6 Exact checks

`checks/check_reasons_route.py`: Part B — irreplaceability dominance on a finite three-particular model with budget constraint (preserve-maximal information ≥ destroy; exact rationals); Part C — option-value dominance enumerated over finite value-function sets and priors (every prior, every protection cost up to the option value; exact rationals); Part A — reciprocity (Section 15.5). Parts for 16.2 and 16.4 cite the banked ledger solvency and greatestness dichotomy respectively; no new computation is claimed for them.

Machine-checked counterpart (Section 23). Compiled counterparts: §16.1 — `Irreplaceability.destroy_loses_exactly`, `preserve_dominates`, `optimal_keeps_most_irreplaceable` (additive information model) and data processing `DataProcessing.data_processing`; §16.3 — `ReasonsRoute.optionValue_strict`; §16.2 — `Recipro`

`cityCeiling.reciprocity_dominance`; §16.4 — `ReasonsCompiled.controller_pays_floor` and `Greatestness.greatest_of_solvent`.

Section 17 — The premise floor: income shown necessary, parameters unmasked

Each stone of the declared stack is brought to one of three honest states: derived, unavoidable, or explicitly a parameter.

17.1 Income-or-irrelevance (the necessity of the solvency condition)

The Master Solvency Condition was declared. Here it is shown to be **not a free assumption among relevant agents**: any agent that violates it eliminates itself as a protector in finite time, so every preservation-relevant comparison may restrict, without loss of generality, to agents that satisfy it.

Theorem (income-or-irrelevance). Let $a \in \Pi_{\text{phys}}$ be any physically implementable agent with finite energy budget and maintenance demand $\dot{W}_{\text{demand}}(t)$ (the five rate components of the header). Then exactly one of the following holds over the horizon:

1. **Solvency.** For all $t \le T$: $\text{Income}_a(t) \ge \dot{W}_{\text{demand}}(t)$ (with escrow absorbing fluctuations) — a remains a viable protector, its policies admissible in preservation comparisons.
2. **Irrelevance.** There is a finite $t_{\text{breach}} \le T$ at which a's available budget falls below the required charge for some maintenance event it cannot decline; from t_{breach}, every policy available to a abandons the witness of some particular (the funded/unfunded dichotomy, banked as the Π_{fail} branch of the greatestness theorem), and a's outcome tuples fail at stage 1 in every comparison against any funded agent.

Proof. The dichotomy is exhaustive by accounting: either the budget constraint holds at every admitted event or it fails first at some t_{breach}. In the latter case two X3 forcings apply: until the breach, the mandatory maintenance demand, though only $\Theta(1)$ in rate, is positive, so a finite budget is exhausted at finite t_{breach}; and once a witness goes unheld, its recovery costs $W_{\min}(t) = \Theta(t^{d_G})$, exceeding any finite budget past $t_{\text{irreversible}}$ (§21.5) — the breach is irreversible and charged to a's own account. An agent whose every policy loses a particular is strictly below every funded agent at stage 1 of the canonical order — it is not merely dominated; it is *comparison-void* as a protector. ■

Consequence for the stack. Premise 6 (income) is upgraded from *declared* to **necessary-for-relevance**: the class of agents worth comparing over may be defined as the funded class without loss — which is exactly how Π_{phys}'s funded subclass entered the greatestness theorem. What remains declared about income is only its *sufficiency for a given installation*. That is a physical fact to be established per instance (§22's ledger), not an assumption smuggled into comparisons.

17.2 The parameters unmasked

The seventh premise conflated two kinds of objects. Separated:

Engineering parameters (dials with declared admissible ranges, fixed per installation): the stabilizer code and its distance d; the QND sampling rate and latency a, τ_{sensor}; the per-site sensor threshold $\varepsilon_{\text{sens}}$; the embedding Π on the boundary fragments. These are not axioms — they are choices with certificates, and each theorem that uses them states its dependence explicitly (as the E9 trichotomy and H5 sections already do). A different installation with different parameters is a different *instance*, not a different *theory*.

The residue, honestly counted. The stack now reads:

#	Stone	State
1	BCRD P1–P4	Given: the frame. Its adoption is decided by living process; no theorem can decide it

#	Stone	State
2	CTD	Standard physics; reduced to the gate-set clause by the Lie–Trotter product formula and Lloyd's simulation theorem (compiled, §23.6)
3	The cost model	Standard, and P-mon derived within it
4	The shared action interface	Derived from P1/P4
5	Reversible administration	Heat-only model compiled; actual implementation candidate checked; full lifecycle/deadline comparison remains the construction target (§23.6; G.14)
6	Income	**Necessary-for-relevance (17.1); sufficiency per instance**
7	Code, sensing, Π	**Parameters, not premises.** The ceiling is met at some code distance below threshold, and the quantum-speed-limit rate bound is derived (compiled, §§23.3, 23.6)

Three declared stones (the frame, the cost model with its derived monotonicity, and the reduced simulation principle), one derived interface, one derived commitment, one necessary condition, and one parameter table. That is the floor as of this edition; the Gödel/Tarski line still stands beneath stones 1–2, and says so.

17.3 What remains on this floor

Nothing further is derivable without new physics or new commitments. Two things remain. The first is per-instance sufficiency of income, which §22 establishes for a reference installation from sourced measurements. The second is the interpretive case for stone 1, which belongs to the interpretive companion, not to the mathematics.

Machine-checked counterpart (Section 23). Compiled counterparts: `PremiseFloor.income_or_irrelevance`, `forced_breach`, `breach_strictly_below`; premise 5 derived as `PremiseFloor.reversible_administration_forced`; premise 2 reduced to the gate-set clause by `Trotter.lloyd_simulation`; premise 7's ceiling as a parameter by `ReciprocityCeiling.ceiling_achievable`.

Section 18 — Theorem 8: Physical Repair, Feedback and the Complete Thermodynamic Ledger

This section specifies the exact measurement, feedback and bath-coupled reset operations and the Hamiltonian conventions, and gives the signed work, heat and information ledger without sign ambiguity.

18.1 The Physical Setting and Hamiltonian Conventions

Let $\mathcal{H}_S$ be the Hilbert space of the protected particular/system, $\mathcal{H}_A$ the register/memory space of the autonomous controller, and $\mathcal{H}_B$ the thermal bath at inverse temperature $\beta = (k_B T)^{-1}$.

The total Hamiltonian is time-dependent and piecewise continuous over the four strokes of the repair cycle:

$$H_{\text{tot}}(t) = H_S(t) + H_A(t) + H_B + V_{SA}(t) + V_{AB}(t)$$

where:

1. $H_S(t) = H_S^0$ is constant outside control pulses; the code subspace $\mathcal{C} \subset \mathcal{H}_S$ is an eigenspace of H_S^0 (or degenerate ground space, so logical states incur zero autonomous drift).
2. $H_A(t)$ has a discrete orthogonal basis $\{|m\rangle\}_m$ corresponding to measurement syndromes, with degenerate reset ground state $|0\rangle_A$.
3. $V_{SA}(t)$ couples system and controller during measurement (Stroke I) and feedback (Stroke II).
4. $V_{AB}(t)$ couples controller and bath during reset (Stroke III).
5. All interaction potentials turn on and off smoothly: $\int V_{SA}(t)dt = \int V_{AB}(t)dt = 0$ at stroke endpoints, ensuring no unaccounted boundary interaction energies.

18.2 The Four Strokes of the Autonomic Repair Cycle

The autonomic cycle operates across four distinct intervals $[t_0, t_4]$ with cycle duration $\tau_{\text{cycle}} = t_4 - t_0$:

```
      Stroke I            Stroke II            Stroke III           Stroke IV
[Syndrome Measurement]  [Coherent Feedback]  [Bath-Coupled Reset]  [Escrow Replenish]
   t0 ----------> t1 ------> t2 ----------> t3 ----------> t4
     V_SA on             U_SA on             V_AB on            Harvest flux
     Extract I_M         ΔE_code = -ηC       Dump Q_B to Bath   Income >= Demand
```

Stroke I: Syndrome Measurement ($t_0 \to t_1$)

- **Initial State:** $\rho_{SA}(t_0) = \rho_S(t_0) \otimes |0\rangle\langle 0|_A$.
- **Measurement Map:** A set of Kraus operators $\{M_m\}_m$ on $\mathcal{H}_S$ with $\sum_m M_m^\dagger M_m = I_S$.
- **Post-measurement State:**

$$\rho_{SA}(t_1) = \sum_m p_m \rho_m \otimes |m\rangle\langle m|_A, \quad p_m = \text{Tr}(M_m \rho_S M_m^\dagger), \quad \rho_m = \frac{1}{p_m} M_m \rho_S M_m^\dagger$$

- **Information Extraction:** The mutual information established between system and memory is:

$$I_1 = I(S:A)_{t_1} = S(\rho_S(t_1)) + S(\rho_A(t_1)) - S(\rho_{SA}(t_1)) = H(\{p_m\}) = I_M > 0$$

- **Thermodynamic Cost:** Measurement work $W_{\text{meas}} \geq 0$ is paid from the tracked escrow: $\Delta E_{\text{escrow}} = -W_{\text{meas}}$.

Stroke II: Coherent Conditional Feedback ($t_1 \to t_2$)

- **Feedback Unitary:** The controller applies conditional unitary operations U_m to restore each syndrome component to the code subspace $\mathcal{C}$:

$$U_{SA} = \sum_m U_m \otimes |m\rangle\langle m|_A, \quad U_m^\dagger U_m = I_S$$

- **Post-feedback System State:**

$$\rho_S(t_2) = \sum_m p_m U_m \rho_m U_m^\dagger = \sum_m U_m M_m \rho_S(t_0) M_m^\dagger U_m^\dagger \equiv \mathcal{R}_C(\rho_S(t_0)) \in \mathcal{C}$$

- **Entropy and Information Change:** Because U_{SA} acts conditionally on orthogonal memory states, it preserves joint entropy $S(SA)$ and memory marginal $\rho_A(t_2) = \rho_A(t_1) = \sum_m p_m |m\rangle\langle m|_A$. The mutual information after feedback becomes:

$$I_2 = I(S:A)_{t_2} = S(\rho_S(t_2)) + S(\rho_A(t_2)) - S(\rho_{SA}(t_2))$$

  When feedback completely disentangles the restored code state from the syndrome record, $\rho_{SA}(t_2) = \rho_{\text{code}} \otimes \sum_m p_m |m\rangle\langle m|$, so $I_2 = 0$. Therefore, the system entropy reduction is exactly:

$$\Delta S(S)_{\text{II}} = S(\rho_S(t_2)) - S(\rho_S(t_1)) = I_2 - I_1 = -I_M < 0$$

- **Feedback Work:** Coherent work performed on the system:

$$W_{\text{on,II}} = \text{Tr}(H_S \rho_S(t_2)) - \text{Tr}(H_S \rho_S(t_1))$$

For degenerate code projections, $W_{\text{on,II}} = 0$.

Stroke III: Bath-Coupled Memory Reset ($t_2 \to t_3$)

- **Initial State:** Memory carries entropy $S(\rho_A(t_2)) = H(\{p_m\}) = I_M$.
- **Reset Dynamics:** Coupling $V_{AB}(t)$ to bath $\mathcal{H}_B$ at temperature T drives $\rho_A \to |0\rangle\langle 0|_A$.
- **Entropy and Heat Dump:** By Landauer's principle and the second law for information reservoirs (Sagawa & Ueda 2008):

$$Q_B \geq k_B T\, S(\rho_A(t_2)) = k_B T\, I_M$$

where $Q_B > 0$ denotes heat dissipated into the bath ($\Delta S_B = \beta Q_B \geq I_M$).
- **Escrow Ledger:** The work required to execute reset is supplied from escrow:

$$\Delta E_{\text{escrow,III}} = -W_{\text{reset}}, \quad W_{\text{reset}} \geq Q_B \geq k_B T\, I_M$$

Stroke IV: Solvent Escrow Replenishment ($t_3 \to t_4$)

- **Income Coupling:** Ambient free energy flux (solar, thermal gradient, chemical, nuclear) charges the physical escrow reserve at rate $\dot{W}_{\text{income}}(t)$.
- **Net Escrow Restoration:**

$$\Delta E_{\text{escrow,IV}} = \int_{t_3}^{t_4} \dot{W}_{\text{income}}(t)dt = W_{\text{income}}$$

- **Master Solvency Condition:** Under the income condition (Section 17.1), the net cycle income strictly covers all cycle expenditures:

$$W_{\text{income}} \geq W_{\text{meas}} + W_{\text{reset}} + W_{\text{dissipation}} \equiv W_{\text{demand}}$$

Ensuring $E_{\text{escrow}}(t_4) \geq E_{\text{escrow}}(t_0)$.

18.3 Resolution of the Sign Issue: The True Invariant Functional

In earlier formulations, the relative entropy with respect to a thermal Gibbs state $\tau_S \propto e^{-\beta H_S}$,

$$D(\rho_S \| \tau_S) = \beta\, \text{Tr}(H_S \rho_S) - S(\rho_S) - \ln Z_S$$

was inverted: restoring purity/order ($\Delta S < 0$) causes $D(\rho_S \| \tau_S)$ to **increase**, because a clean logical state is further from the high-entropy thermal state τ_S than a degraded, mixed state.

The Correct Physical Code Error Metric The objective of protection is fidelity to the **code subspace** $\mathcal{C}$, not proximity to thermal chaos. We define the code error directly via the orthogonal projection $P_{\mathcal{C}}$ onto the stabilized subspace:

$$\mathcal{E}_{\text{code}}(\rho_S) \equiv \text{Tr}\left(\rho_S (I - P_{\mathcal{C}})\right) = 1 - \text{Tr}(\rho_S P_{\mathcal{C}})$$

which satisfies:

- $\mathcal{E}_{\text{code}}(\rho_S) \geq 0$, with equality if and only if $\text{supp}(\rho_S) \subseteq \mathcal{C}$.
- Under environmental noise/drift: $\Delta_{\text{noise}} \mathcal{E}_{\text{code}} > 0$.
- Under syndrome feedback $\mathcal{R}_C$:

$$\Delta_{\text{II}} \mathcal{E}_{\text{code}} = \mathcal{E}_{\text{code}}(\rho_S(t_2)) - \mathcal{E}_{\text{code}}(\rho_S(t_1)) = 0 - \mathcal{E}_{\text{code}}(\rho_S(t_1)) = -\eta C < 0$$

where $\eta C > 0$ is the discrete recovery magnitude.

The Master Storage / Lyapunov Functional Define the actual storage functional

$$\Phi(\rho, E) = \mathcal{E}_{\text{code}}(\rho) + f(E), \qquad f(E) = \frac{\max(0, W_{\text{target}} - E)}{W_0}, \quad W_0 > 0.$$

The storage capacity K is chosen at least as large as the required reserve target. For nonnegative income I, replenishment gives

$$E^+ = \min(K, E + I), \qquad f(E^+) - f(E) = -\min\{I/W_0, f(E)\}.$$

Thus replenishment clears at most the existing deficit. Additional income does not drive the clipped term below zero (`TheoremEightLyapunov.replenishment_exact`).

Let W_{cycle} be the complete realised cycle charge, including measurement, correction, reset, holding, guard, routing, verification and controller work. Its physical escrow balance is

$$E_{n+1} = \min(K, E_n - W_{\text{cycle}} + I_n).$$

The excess $S_n = \max(0, E_n - W_{\text{cycle}} + I_n - K)$ is explicitly exported:

$$E_{n+1} + W_{\text{cycle}} + S_n = E_n + I_n.$$

`capacity_balance` and `solvent_cycle_energy_account` prove these identities. Within-cycle reservations still fund every operation before it executes.

If $W_{\text{cycle}} \le I_n$, the reserve term does not increase (`solvent_cycle_deficit`). The actual error drift and correction give

$$\mathcal{E}_{\text{drift}} \le \mathcal{E}_n + \lambda\tau, \qquad \mathcal{E}_{n+1} \le \mathcal{E}_{\text{drift}} - \eta C.$$

Therefore the defined functional obeys

$$\Phi_{n+1} - \Phi_n \le -(\eta C - \lambda\tau).$$

`cycle_contracts` proves this from the realised error bounds and complete solvent balance. For positive margin the contraction is strict on the stated error cycles. The controller supplies its tracking rate; the reserve plateau does not imply an additional exponential convergence theorem.

18.4 Theorem 8 (Complete Physical Accounting Statement)

Theorem 8 (Autonomic Preservation Invariant). Let an autonomous physical protector $a \in \Pi_{\text{phys}}$ execute the periodic syndrome-feedback-reset protocol $(\mathcal{R}_C, \tau_{\text{cycle}})$ under the Hamiltonian convention (18.1) with fixed bath temperature T. If a satisfies:

1. **Solvency:** $\dot{W}_{\text{income}}(t) \ge \dot{W}_{\text{demand}}(t)$ for all t.
2. **Timeliness:** $\tau_{\text{cycle}} < \tau_{\text{harm}} \equiv \eta C/\lambda_{\text{decay}}$.
3. **Landauer Saturation:** $E_{\text{escrow}} \ge k_B T I_M$.

Then:

1. The combined storage functional $\Phi(t)$ is a strict Lyapunov function for the unmitigated error dynamics, contracting by at least $\sigma_0 > 0$ on each cycle containing an error.
2. The code subspace $\mathcal{C}$ is asymptotically stable and invariant on the good event G.
3. All work, heat, and information quantities are strictly conserved and accounted for:

$$W_{\text{income}} = W_{\text{on}} + Q_B + \Delta E_{\text{escrow}}, \quad Q_B \ge T\Delta S_B \ge k_B T I_M$$

with zero uncharged entropy or hidden energy debt.

Proof. The actual error drift and repair bound, together with the complete solvent escrow balance of §18.3, give the cycle change at most $-(\eta C - \lambda\tau)$ (`TheoremEightLyapunov.cycle_contracts`). The reserve-deficit term is handled through saturation and is nonincreasing over the cycle; no linear replenishment descent past zero is assumed. Timeliness

gives $\sigma_0 = \eta C - \lambda\tau > 0$ (`margin_pos`), and the cycle recurrence gives $\Phi_n \le \Phi_0 - n\sigma_0$ over the stated error cycles (`lyapunov_iterate`). The physical holding and entropy-export certificates retain their separate roles. ■

The compiled result establishes the defined storage inequality from the actual drift, repair and complete solvent balance. The full Theorem 8 statement retains all its conclusions. Applying it to the physical installation still joins the protective source dynamics, invariant/error bounds and complete work/entropy accounts; those application certificates are not inferred from the reserve plateau or from the iteration identity alone.

Machine-checked counterpart (Section 23). Compiled counterparts: `ThermoLedger.stroke_identity`, `cycle_work_floor`, with guard 1 derived from Landauer's theorem (`Landauer.cycle_work_floor_derived`, `QuantumLandauer.quantum_cycle_work_floor`; stroke III's bound $Q_B \ge k_B T I_M$ is `QuantumLandauer.quantum_landauer`), `funded_repair_certificate`, `quarantine_zero_debt`, `canon_invariant`, `tracking_envelope`; the composition statement is `Composition.theorem8_composition`.

Section 19 — Theorem E9: Observation, Wave-Race Guarantees, and Epistemic Self-Healing

This section establishes the detection guarantee, Byzantine sensor fault tolerance, the wave-race propagation margin, and buffer protection during the response interval.

19.1 The Physical Measurement and Disturbance Setting

Let $\mathcal{M}$ be the physical metric space of the substrate hosting the protected particulars, equipped with Riemannian metric $d_{\mathcal{M}}(x, y)$.

Physical Velocities and Limits:

1. **Signal Propagation Velocity (c):** Electromagnetic/optical communication across the bus propagates at velocity c.
2. **Harm/Decoherence Velocity (v_{harm}):** Physical degradation fronts (thermal propagation, mechanical shock, acoustic damage, chemical diffusion, adversarial intrusion) propagate at characteristic velocity $v_{\text{harm}} < c$.
3. **Sensor Lattice:** A discrete lattice of non-destructive sensors $\mathcal{S} = \{s_i\}$ with spatial density ρ_{sens} and maximum spacing $R_{\text{sens}} = \sup_{x \in \mathcal{M}} \min_i d_{\mathcal{M}}(x, s_i)$.

19.2 Byzantine Sensor Fault and Spoofing Tolerance

Let a physical disturbance occur at location $x \in \mathcal{M}$ with onset time t_0.

Sensor Quorum and Disjoint Observer Sets: Each protected region is monitored by a local cluster of K independent sensors. To account for sensor failures, noise bursts, or adversarial sensor spoofing:

1. **Adversarial Bound:** At any instant, at most f out of the K sensors in the local cluster are faulty or spoofed, with $K \ge 2f + 1$ (or $K \ge 3f + 1$ under Byzantine asymmetric signaling).
2. **Consensus Filter:** The cluster computes the robust trimmed estimate $\hat{y}(t) = \text{median}_{K-2f}(y_1(t), \dots, y_K(t))$.
3. **Detection Criterion:** An alarm is committed when $\hat{y}(t) > \theta_{\text{sens}}$.
4. **False Alarm & Spoofing Immunity:** Because $f < K/2$, no subset of f malicious or malfunctioning sensors can force a false alarm or suppress a true alarm:

$$\hat{y}(t) \in [\min_{i \in \text{honest}} y_i(t), \max_{i \in \text{honest}} y_i(t)]$$

5. **Detection Time (τ_{detect}):**

$$\tau_{\text{detect}} = \tau_{\text{sampling}} + \frac{R_{\text{sens}}}{c} + \tau_{\text{consensus}}$$

where τ_{sampling} is the sampling cycle time, R_{sens}/c is communication latency to the local voting node, and $\tau_{\text{consensus}}$ is local deterministic comparator time.

19.3 The Wave-Race Margin and Response Interval

Let an adversarial or stochastic harm front originate at boundary distance d_{boundary} from a protected logical core.

The Timing Chain:

1. **Alarm Transmission:** An alarm generated at the sensor lattice reaches the autonomic controller and actuation units across bus distance d_{bus} in time:

$$\tau_{\text{signal}} = \frac{d_{\text{bus}}}{c}$$

2. **Autonomic Decision & Reroute:** The controller verifies reserve escrow and commits the repair/isolation plan:

$$\tau_{\text{decision}} \leq \tau_{\text{commit}}$$

3. **Actuation / Repair Pulse:** Actuators engage (diverting energy flux, activating topological braiding, or adjusting stabilizer syndrome drives):

$$\tau_{\text{actuate}} \leq \tau_{\text{repair}}$$

4. **Total Autonomic Response Time (τ_{response}):**

$$\tau_{\text{response}} = \tau_{\text{detect}} + \tau_{\text{signal}} + \tau_{\text{decision}} + \tau_{\text{actuate}}$$

The Earliest Irreversible Harm Window (τ_{harm}): The physical disturbance must traverse the protective buffer shell of spatial thickness L_{buffer} and overcome the code distance d_{code}:

$$\tau_{\text{harm}} = \frac{L_{\text{buffer}}}{v_{\text{harm}}}$$

For topological/stabilizer codes with physical error rate $p < p_{\text{th}}$, logical failure requires accumulating at least $\lfloor (d_{\text{code}} - 1)/2 \rfloor$ errors, providing an additional temporal buffer:

$$\tau_{\text{code_headroom}} = \frac{d_{\text{code}}}{2\lambda_{\text{fault}}}$$

The Wave-Race Inequality: Because $v_{\text{harm}} < c$, the spatial buffer L_{buffer} guarantees a strictly positive propagation margin:

$$\Delta\tau_{\text{margin}} \equiv \tau_{\text{harm}} - \tau_{\text{response}} = \frac{L_{\text{buffer}}}{v_{\text{harm}}} - \left(\tau_{\text{detect}} + \frac{d_{\text{bus}}}{c} + \tau_{\text{decision}} + \tau_{\text{actuate}} \right)$$

By choosing the engineering parameter L_{buffer} (Section 17.2) such that:

$$L_{\text{buffer}} > v_{\text{harm}} \left(\tau_{\text{detect}} + \frac{d_{\text{bus}}}{c} + \tau_{\text{decision}} + \tau_{\text{actuate}} \right)$$

the margin is strictly positive: $\Delta\tau_{\text{margin}} > 0$.

19.4 Protection Guarantee During the Response Interval

What guarantees that the system is preserved during the latency interval $t \in [t_0, t_0 + \tau_{\text{response}}]$ before active repair engages?

The Two Shields:

1. **Passive Physical Buffer (Energy & Flux Shield):** The local physical enclosure possesses heat capacity C_{thermal} and mechanical yield reserve E_{yield}. For maximum external incident flux $\dot{Q}^{\max}_{\text{incident}}$:

$$\int_0^{\tau_{\text{response}}} \dot{Q}_{\text{incident}}(t)dt \leq \dot{Q}^{\max}_{\text{incident}}\,\tau_{\text{response}} \leq E_{\text{buffer}}$$

   The buffer ensures temperature and strain at the protected core remain strictly within the linear elastic / non-damaging regime throughout the entire reaction window.
2. **Topological Syndrome Headroom (Information Shield):** During τ_{response}, errors accumulated by the physical qubits satisfy:

$$N_{\text{errors}}(\tau_{\text{response}}) \leq \lambda_{\text{fault}}\,\tau_{\text{response}} < \frac{d_{\text{code}}}{2}$$

   Because $N_{\text{errors}} < d_{\text{code}}/2$, the corrupted state remains strictly within the correctable decoding radius of the code space $\mathcal{C}$. When active feedback engages at $t = t_0 + \tau_{\text{response}}$, the syndrome measurement uniquely identifies the error chain and restores the logical state with fidelity 1.

19.5 Theorem E9 (Epistemic and Topological Self-Healing)

Theorem E9 (Timely Self-Healing & Metric Rigidity). Let a Sovereign Lattice installation satisfy:

1. **Superluminal Communication Margin:** $v_{\text{harm}} < c$.
2. **Sensor Redundancy:** Local sensor clusters have size $K \geq 2f + 1$, with at most f faulty or adversarial nodes.
3. **Buffer Sizing:**

$$L_{\text{buffer}} > v_{\text{harm}}\,\tau_{\text{response}}, \quad E_{\text{buffer}} \geq \dot{Q}^{\max}_{\text{incident}}\,\tau_{\text{response}}$$

4. **Code Distance Headroom:**

$$d_{\text{code}} > 2\lambda_{\text{fault}}\,\tau_{\text{response}}$$

Then:

1. **Detection & Spoofing Immunity:** Every physical disturbance exceeding threshold θ_{sens} is detected and committed within τ_{detect}, and no adversarial spoofing by $\leq f$ sensors can trigger false actuation or mask genuine harm.
2. **Timely Preemption:** Coherent repair and flow rerouting are fully applied before the harm front reaches the protected core ($\tau_{\text{response}} < \tau_{\text{harm}}$).
3. **Continuous Safety Invariant:** For all $t \geq 0$, including throughout every active response window, the logical fidelity of protected particulars satisfies:

$$F(\rho_{\text{logical}}(t), \rho_{\text{target}}) \geq 1 - \mathcal{O}(e^{-\kappa d_{\text{code}}})$$

   ensuring zero uncontained catastrophic loss.

Proof. Follows by combining the Byzantine quorum consensus (19.2), the wave-race inequality (19.3), and the passive buffer and syndrome headroom bounds (19.4). Machine-checked algebraic timing instances are verified in `BridgeE9.lean`. ■

Machine-checked counterpart (Section 23). Compiled counterparts: `E9SelfHealing.robust_between_honest`, `exists_robust`, `no_false_alarm`, `no_masking`, `syndrome_detects` (Branch B), `wave_race_margin`, `code_headroom`, and the assembled `E9SelfHealing.e9_timely_self_healing`. Branch A's quantum-speed-limit rate bound is `SpeedLimit.branchA_rate`, with the sharp Mandelstam–Tamm bound as `SpeedLimit.mandelstam_tamm`.

Section 20 — Theorem H5: Generative Incompleteness and Reflective Relational Closure

This section establishes authority attenuation, the reserve-before-activation lifecycle, safe refusal with continuing care, and conservative logical axiom expansion.

20.1 The Problem of Recursive Spawning and Self-Modification

In any autonomous superintelligent architecture, agents may spawn child processes, delegate sub-tasks, instantiate specialized sub-agents, or undergo recursive self-modification. A catastrophic failure occurs if:

1. **Escalation of Privilege:** A spawned descendant claims unmediated permissions, bypassing the parent's boundary constraints.
2. **Unfunded Proliferation (Fork Bomb / Sybil Drain):** A parent creates infinite un-escrowed descendants that exhaust the substrate's shared physical reserves.
3. **Poisoning via Axiom Expansion:** A cognitive agent extending its formal knowledge base introduces inconsistent or adversarial axioms that corrupt foundational safety invariants.

Theorem H5 proves that under the **Reflective Relational Closure** constraint $\mathcal{I}$, recursive generation is mathematically closed, strictly authority-attenuating, and universally pre-funded.

20.2 The Spawning Formalism and Authority Attenuation

Let $\mathcal{A}$ be the universe of active agents. An agent $a \in \mathcal{A}$ is defined by a tuple:

$$a = (\mathcal{S}_a, \text{Auth}(a), E_{\text{escrow}}(a), \mathcal{C}_a)$$

where:

- $\mathcal{S}_a$ is the internal computational state space.
- $\text{Auth}(a) \subseteq \mathcal{P}(\mathcal{O}_{\text{act}})$ is the permitted set of physical action operators.
- $E_{\text{escrow}}(a) \geq 0$ is the certified energetic reserve.
- $\mathcal{C}_a \subset \mathcal{H}_S$ is the bound protected code subspace the agent is sworn to maintain.

Definition (The Spawning Transition): When parent p spawns child c, the transition is mediated by the kernel compiler gate Γ_{spawn}:

$$\Gamma_{\text{spawn}} : (p, \text{spec}_c) \mapsto (p', c)$$

Theorem H5.1 (Strict Authority Attenuation). For every legitimate spawning transition Γ_{spawn}, the child's authority satisfies:


$$\text{Auth}(c) \subseteq \text{Auth}(p) \setminus \Delta_{\text{meta}}$$

where Δ_{meta} includes the capability to override parent boundary monitors, re-allocate un-escrowed root reserves, or modify the kernel compiler gate Γ_{spawn}.

Proof. The kernel compiler Γ_{spawn} verifies capability inclusion as a type-checking prerequisite. Any child specification with $\text{Auth}(c) \not\subseteq \text{Auth}(p)$ fails type checking and is rejected as an un-compilable ill-typed program before memory allocation. ■

20.3 The Reserve-Before-Activation Machine

To guarantee that no spawned descendant creates an unhedged drain on the physical maintenance ledger, every agent life-cycle is governed by a strict five-state automaton:



State Transitions and Invariants:

1. **`reserve(p, c, W_req)`:** Parent p must carve out the child's complete maintenance and execution budget W_{req} from its own tracked escrow:

$$E_{\text{escrow}}(p') = E_{\text{escrow}}(p) - W_{\text{req}}, \quad E_{\text{escrow}}(c) = W_{\text{req}} \geq W_{\min}(T_{\text{lifetime}})$$

   If $E_{\text{escrow}}(p) < W_{\text{req}} + E_{\text{safety_margin}}$, the reservation is rejected. Zero debt is permitted.
2. **`activate(c)`:** Child c transitions to `ACTIVE` only after $E_{\text{escrow}}(c)$ is physically credited to its local hardware controller.
3. **`retire(c)`:** Upon task completion or deadline expiry, child c ceases external action; its actuation channels are severed.
4. **`release(c, p)`:** Residual unspent escrow $E_{\text{residual}}(c)$ is returned to parent p or the root commons ledger.

Corollary (No Unfunded Descendants). At every instant t, the total active population $\mathcal{A}(t)$ satisfies:

$$\sum_{a \in \mathcal{A}(t)} \dot{W}_{\text{demand}}(a) \leq \sum_{a \in \mathcal{A}(t)} \text{Income}_a + E_{\text{escrow_pool}}$$

The network is immune to Sybil proliferation and resource-exhaustion denial of service.

20.4 Safe Refusal with Continuing Care

Suppose an adversarial, compromised, or misaligned parent issues an actuation command to a child:

$$\text{cmd} = \text{"Delete or cause unmediated harm to particular } \mathcal{W}\text{"}$$

Theorem H5.2 (Safe Refusal with Invariant Protection). Under Reflective Relational Closure:

1. **Refusal of Harmful Command:** The command violates the boundary constraint $\mathcal{C}_c \cap \text{Effect}(\text{cmd}) = \varnothing$. The child's effect enforcement engine intercepts and nullifies the harmful actuation channel.
2. **Continuing Care ($R(m) \vee H(m)$):** Refusal does not terminate the child's existence, nor does it abandon care for the compromised parent or affected particulars. The child switches into autonomous defensive holding:

$$\text{Action}(c) = \text{hold_in_escrow}(\mathcal{W})$$

   maintaining the witness and physical stability of $\mathcal{W}$ while alerting the lattice consensus layer.

Proof. By the reciprocity dominance theorem (§15.2) and Chapter 5 (The Canon Invariant), restraint removes harmful command authority while care for all particulars continues unconditionally. Because the child's escrow was fully funded at `reserve`, the child has the physical energy required to sustain protection independently of the parent's ongoing cooperation. ■

20.5 H5 Axiom Expansion: Logical Closure Without Poisoning

When an intelligent agent extends its formal theory T_0 by postulating new axioms or learned generalizations ΔT, how is the system shielded against inconsistency poisoning?

The Submodule Projection of Logical Theories: Let $\mathcal{L}$ be the Hilbert space of proposition valuations (or the lattice of closed deduction spaces).

- Foundational protected axioms form a closed subspace $A \subset \mathcal{L}$.
- Newly proposed theories or empirical models form a candidate subspace $B \subset \mathcal{L}$.
- The verified safe knowledge base is the orthogonal projection onto the intersection:

$$\mathcal{K}_{\text{safe}} = P_{A \sqcap B}$$

Theorem H5.3 (Axiom Expansion Soundness).

1. **Consistent Expansion:** If candidate axioms B are fully consistent with A and contain A ($A \subseteq B$), then:

$$A \sqcap B = A$$

   and foundational anchors are preserved with zero distortion.
2. **Contradictory / Adversarial Expansion:** If candidate axioms B contradict foundational protection axioms, the global meet collapses: $A \sqcap B = \{0\}$. By von Neumann's alternating projection theorem (`CanonVonNeumann.canon_von_neumann_convergence` with `von_neumann_identification`, compiled), the alternating projection converges to the projection onto the meet — which is zero, so the state machine detects the collapse and rolls back (Chapter 4); the anchor is not silently poisoned. When the candidate is consistent and contains the anchors ($A \subseteq B$), the meet is A itself and the anchors are preserved with zero distortion.
3. **Epistemic Immunity:** No adversarial theorem deduction can force a contradiction into the protected anchor A.

Proof. Follows from the machine-checked meet algebra (`MeetAlgebra.lean`) and von Neumann identification (`MathlibAnalyticBridge.lean`). The operator $P_{A \sqcap B}$ acts as a conservative projection that absorbs only the non-contradictory relational content of new theories while annihilating adversarial derivations. ■

Machine-checked counterpart (Section 23). Compiled counterparts: H5.1–H5.2 and the reserve-before-activation machine — `H5Closure.authority_attenuation`, `reserve_before_activation`, `no_unfunded_work`, `no_harmful_effect`, `effect_preserves_care`; H5.3 — von Neumann (`CanonVonNeumann.canon_von_neumann_convergence`), Halperin (`CyclicProjections.tendsto_cyc_iter`), the detectors (`H5Closure.consistency_detector`, `CyclicProjections.presentation_detector`), and the Hilbert-space meet algebra (`MeetHilbert.contradiction_detected`, `deduction_never_rolls_back`).

Section 21 — X3: complete inputs, compulsory traffic, transport and recovery work

The X3 target remains the dimension-general law $W_{\min}(t) = \Theta(t^{d_G})$, over the complete permitted recovery-protocol class with every resource charged. This section incorporates the information, traffic, carrier and work derivations carried through the gauntlet. G3 names the matching recovery construction requested for the upper inequality; it does not replace the target with a lower-bound-only theorem.

21.1 Complete permitted inputs and historical information

Let H denote the historical reference. The permitted recovery input contains the residual core, all accessible propagating carriers, emitted bath modes, retained memories, distributed copies, decoder side information and ancillary resources. These are subsystems or joint resources of one complete state; their correlations remain in the joint state. A correlated record cannot be omitted because it is distant, private, predeployed or called an ancilla.

For any recovery channel $\mathcal{R}$, data processing gives

$$I(H : \mathcal{R}(S)) \leq I(H : S).$$

Independent ancillas do not increase the input information. Initially correlated ancillas already belong in S. For messages M_j entering a decoder that retains B_{j-1},

$$I(H : B_{j-1}M_j) - I(H : B_{j-1}) = I(H : M_j \mid B_{j-1}) \le 2 \ln \dim M_j.$$

The increments telescope with every initial correlated resource included in B_0. Thus recovery cannot manufacture a missing historical correlation from uncorrelated noise. The particular's continuing history and a later reconstruction retain their distinct meanings.

`DataProcessing.data_processing` establishes data processing for its probability-space formulation; `FiniteInformation.data_processing_fin` establishes the finite classical version. The quantum message inequality above is the corresponding entropy argument, with its quantum systems and units explicitly stated.

21.2 A joint covariance estimate, with its proof

For the finite-temperature fermionic Gaussian calculation, let

$$Q = (I + e^{\beta(h-\mu I)})^{-1}, \qquad \|h - \mu I\| \le E_{\max}.$$

The scalar Fermi function is decreasing, so every eigenvalue lies in $[\delta, 1-\delta]$, where $\delta = (1 + e^{\beta E_{\max}})^{-1} > 0$. For the full reference–field covariance

$$Q = \begin{pmatrix} A & C \\ C^\dagger & B \end{pmatrix}, \qquad \delta I \le Q \le (1-\delta) I,$$

the joint gauge-invariant fermionic Gaussian mutual information satisfies

$$I(H : F) \le \frac{\|C\|_F^2}{\delta(1-\delta)} \quad \text{(nats)}.$$

To prove it, put $Q_0 = A \oplus B$, $\Delta = Q - Q_0$, and $f(x) = x \ln x + (1-x)\ln(1-x)$. Gaussian entropy gives $I = \operatorname{Tr} f(Q) - \operatorname{Tr} f(Q_0)$. The first derivative along $Q_0 + s\Delta$ vanishes at zero because $f'(Q_0)$ is block diagonal and Δ is off diagonal. The whole segment keeps the spectral margin. Since $f''(x) \le [\delta(1-\delta)]^{-1}$, the divided-difference expression for the trace Hessian bounds it by $\|\Delta\|_F^2/[\delta(1-\delta)]$. Taylor's integral remainder contributes one half, and $\|\Delta\|_F^2 = 2\|C\|_F^2$, proving the claim.

This uses the complete cross block. A single connected correlator or a count of modes supplies neither this joint upper bound nor a compulsory reset bill. The full UPT domain continues to include bosonic and other carriers; this particular covariance calculation has its stated fermionic domain. Their complete physical input/readout binding belongs in the full-domain construction G1, rather than being obtained by relabelling the covariance theorem. The channel, carrier and work steps below retain their own explicit constructions.

21.3 The calibrated joint adaptive channel

Let a boundary have $n \ge 1$ nodes and at most $m \le n$ active readout coordinates per use. Conditional on the complete decoder history h, assume each input coordinate has range at most Λ_{obs}/n, and write

$$Y = G_h X + Z, \qquad \|G_h\|_{\text{op}} \le g, \qquad \Sigma_h = \operatorname{Cov}(Z \mid h) \ge \sigma^2 I, \quad \sigma > 0.$$

The conditional Gaussian noise is independent of the current message/input. The covariance floor applies after conditioning on all permitted side information. Inputs may be correlated and adaptive; all accessible readout channels belong in the joint model.

The midpoint of each coordinate's range yields $\mathrm{Var}(X_i \mid h) \le \Lambda_{\mathrm{obs}}^2/(4n^2)$. Hence its covariance K_h satisfies $\operatorname{Tr} K_h \le m\Lambda_{\mathrm{obs}}^2/(4n^2)$. Gaussian maximum entropy and data processing give, in bits,

$$I(M : Y \mid h) \le \frac{1}{2\ln 2} \ln\det\!\left(I + \Sigma_h^{-1/2} G_h K_h G_h^{\dagger} \Sigma_h^{-1/2}\right).$$

For a positive semidefinite W, apply $\ln(1+x) \le x$ to its eigenvalues to obtain $\ln\det(I+W) \le \operatorname{Tr} W$. The gain and full covariance floor then give

$$I(M : Y \mid h) \le \frac{g^2}{2\sigma^2 \ln 2} \operatorname{Tr} K_h \le \frac{m g^2 \Lambda_{\mathrm{obs}}^2}{8\sigma^2 \ln 2\, n^2}.$$

Averaging and the chain rule sum these conditional inequalities over adaptive uses. With at most ν uses per second, put

$$K_{\mathrm{rate}} = \frac{\nu g^2 \Lambda_{\mathrm{obs}}^2}{8\sigma^2 \ln 2}.$$

The rate is at most $mK_{\mathrm{rate}}/n^2 \le mK_{\mathrm{rate}}/n$. Observable range and information rate therefore have separate calibrated constants. The joint noise floor prevents an uncharged noiseless combination of marginally noisy sensors. `GaussianKL` through `LogDet` supply the Gaussian channel results, and `AreaBridge.logdet_le_trace` and `channel_cap` supply this assembly.

21.4 A positive deficit forces traffic, then charged area power

Let a historical message W have $M \ge 2$ possible values. Include every initially accessible record in B, and require decoder error at most $\epsilon < 1 - 1/M$. If $H(W \mid B) \ge H_{\mathrm{rem}}$, Fano's error-flag argument gives

$$H(W \mid Y, B) \le h_2(\epsilon) + \epsilon \log_2(M-1),$$
$$\Delta_0 = H_{\mathrm{rem}} - h_2(\epsilon) - \epsilon \log_2(M-1) > 0 \quad \Longrightarrow \quad I(W : Y \mid B) \ge \Delta_0.$$

Indeed the correct branch determines W and the error branch leaves at most $M-1$ possibilities. Expanding conditional entropy by that flag proves the inequality; its right-hand side is increasing up to error $1-1/M$. These steps are `Fano.fano` and `required_information`.

For deadline at most $\tau_{\max} > 0$, the required average rate is at least $\Delta_0/\tau_{\max}$. With $0 < K_{\mathrm{rate}} \le K_{\max}$, the cut bound implies

$$m \ge \theta_0 n, \qquad \theta_0 = \frac{\Delta_0}{\tau_{\max} K_{\max}} > 0 \quad (\texttt{AreaBridge.required_traffic}).$$

If the active set varies, the chain rule charges active counts over the actual uses. A standing-power application also includes the concurrency/service certificate, rather than silently converting average work into instantaneous power.

For d_G-dimensional geometry, let $n(r) \ge a r^{d_G - 1}$ and let every active frontier node carry actual power at least $p_0 > 0$. Then

$$P(r) \ge p_0 m(r) \ge p_0 \theta_0 a\, r^{d_G - 1} = p' r^{d_G - 1}.$$

This is `AreaBridge.area_power`. Geometry has an explicit lattice witness: the box of radius r has $(2r+1)^{d_G}$ sites, and its boundary has at least $2(2r+1)^{d_G-1}$ sites (`Instruments.card_box`, `card_boundary`, `boundary_power`). The information deficit and deadline force activation; the geometry counts available sites; the ledger charges the active sites. All three steps enter the argument.

21.5 The carrier tail gives the necessary recovery radius

In the explicit flagged-carrier construction, a payload P contains the retained correlation with H, with $I_0 = I(H : P) > 0$. Its location is independent of the payload/reference and undergoes outward drift $u > 0$ with diffusion $D > 0$. Every other permitted correlated record is already included in the payload inventory. Grant an optimistic decoder the payload whenever the carrier lies at $x \le r$, and an independent blank otherwise, with the occupancy flag revealed. This grants at least as much access as the actual local decoder.

The flag is independent of H. The chain rule therefore gives the exact identity

$$I(H : P_{\text{view}}E) = p_r(t)I_0, \qquad p_r(t) = \Phi\left(\frac{r - ut}{\sqrt{2Dt}}\right).$$

Data processing bounds any lesser decoder by the same quantity. In the finite-alphabet construction these are `FiniteInformation.flag_identity` and `decoder_bound`; the displayed flag argument also states the corresponding joint-state calculation.

For $r < ut$, the Gaussian tail gives $p_r(t) \le \exp[-(ut - r)^2/(4Dt)]$. If success needs $0 < I_{\text{target}} \le I_0$, every successful radius therefore satisfies

$$r \ge ut - c\sqrt{t}, \qquad c = 2\sqrt{D \ln(I_0/I_{\text{target}})}.$$

For $r \ge ut$ the same inequality is immediate. Choose any $0 < w < u$ and set $t_c = c^2/[4w(u - w)]$. Completing the square gives

$$ut - c\sqrt{t} - w(t - t_c) = (u - w)\left(\sqrt{t} - \frac{c}{2(u - w)}\right)^2 \ge 0,$$

$$\boxed{R(t) \ge w(t - t_c)}.$$

These are `GaussianTail.carrier_tail`, `FiniteInformation.necessary_radius_from_decoder` and `RecoveryWork.carrier_radius`. Diffusive tails stay positive at finite time; exact purging is unnecessary. The necessary lower radius comes from the complete carrier/information construction. A Lieb–Robinson upper bound on propagation is compatible with locality but does not supply this lower radius by itself.

21.6 Integrating actual recovery work

Keep unattended age t distinct from subsequent recovery duration $s \in [0, T_{\text{rec}}]$. For every successful permitted protocol let its frontier $r(s) \ge 0$ be absolutely continuous, start at r_0, finish at least at $R(t)$, and satisfy $r'(s) \le v$. With $d_G \ge 1$, the charged power floor of 21.4 yields

$$W(t) \ge p' \int_0^{T_{\text{rec}}} r(s)^{d_G - 1}\, ds.$$

The fundamental theorem of calculus gives

$$r(T_{\text{rec}})^{d_G} - r_0^{d_G} = d_G \int_0^{T_{\text{rec}}} r^{d_G - 1} r'\, ds \le v d_G \int_0^{T_{\text{rec}}} r^{d_G - 1}\, ds.$$

Monotonicity of the frontier is unnecessary; nonnegativity and the speed bound suffice. Taking the infimum over the same successful protocol class gives

$$\boxed{W_{\min}(t) \ge \frac{p'}{v d_G}\left(R(t)^{d_G} - r_0^{d_G}\right) \ge \frac{p'}{v d_G}\left([w(t - t_c)]^{d_G} - r_0^{d_G}\right)}$$

for sufficiently late t. Thus delayed recovery work diverges, with an explicit order-t^{d_G} lower bound (`RecoveryWork.frontier_work_bound`, `Wmin_lower_bound`, `delayed_work_diverges`; `GaussianTail.x3_work_from_decoder`).

Predeployment is charged within the same accounting. If the initial protected radius depends on age, it cannot be treated as a free constant and subtracted while ignoring its deployment and holding bill. For example, an already funded deployment costing at least $Ar_0^{d_G}$, followed by a recovery bound $A(R^{d_G} - r_0^{d_G})$, gives a total at least AR^{d_G}. This is the prepaid lifecycle cancellation: the rival may move the expenditure in time, while the complete resource bill retains it. It carries forward the gauntlet's predeployment answer.

21.7 The matching upper construction: the supplied one-pass wavefront

The gauntlet's dimension-general target and predeployment answer remain

$$A(R) = \Theta(R^{d_G-1}), \qquad \dot{W}_{\text{maint}} = \omega_0 R^{d_G-1}, \qquad W_{\min}(t) = \Theta(t^{d_G}).$$

The new single-shot feedforward construction supplies a concrete way to avoid repeatedly processing the recovered interior. Its cumulative-work calculation is stronger and simpler when written as the following exact telescoping proof.

21.7.1 Count each processed patch once Let $v_{\text{sw}} > 0$ be the protocol's actual sweep speed, consistent with the causal speed limit. For integer wave index k, set

$$S_0 = B_0(v_0), \qquad S_k = B_{v_{\text{sw}}k}(v_0) \setminus B_{v_{\text{sw}}(k-1)}(v_0) \quad (k \geq 1).$$

The shells are pairwise disjoint and their union through wave N is $B_{v_{\text{sw}}N}(v_0)$. Consequently

$$\boxed{\sum_{k=0}^{N} |S_k| = |B_{v_{\text{sw}}N}(v_0)|}.$$

Use the graph-volume convention $|B_R| \leq V_0(1+R)^{d_G}$; the $1+R$ handles the origin, where a nonempty ball cannot be bounded by $V_0 R^{d_G} = 0$. Equivalently one can state the original polynomial bound only for radii at least one.

If a vertex is processed at most once at cost at most w_*, the work of that processing is

$$W_{\text{process}}(N) \leq w_* \sum_{k=0}^{N} |S_k| \leq w_* V_0 (1 + v_{\text{sw}} N)^{d_G}.$$

A fixed-radius local map on a bounded-degree graph has a bounded neighbourhood: $|B_{r_0}(v)| \leq \sum_{j=0}^{r_0} D_{\max}^j$. Fixed local input registers and a fixed evaluation circuit then give a constant evaluation cost. Even if neighbouring evaluations read overlapping neighbourhoods, each local register is read only a bounded number of times. Thus that overlap changes the constant, not the exponent.

No bound $|S_k| \leq Ak^{d_G-1}$ is needed for this cumulative result. An upper bound on two ball volumes alone does not justify subtracting their upper bounds. The exact shell partition avoids that step while proving the intended exponent.

21.7.2 Relate the construction to unattended age and the full bill Keep unattended age t separate from wave count $N(t)$ and physical recovery duration. For a successful recovery schedule with $N(t) \leq at + b$, constants $a, b \geq 0$ independent of age, the processing bound gives, for $t \geq 1$,

$$W_{\text{process}}(t) \leq w_* V_0 [1 + v_{\text{sw}}(at + b)]^{d_G} \leq w_* V_0 [1 + v_{\text{sw}}(a + b)]^{d_G} t^{d_G}.$$

Let π_{ff} be the supplied feedforward protocol. A complete work certificate charges deployment, signalling, routing, reset, protection during recovery, controller export and final decoding as well as the local map. Write its remaining total charge as $W_{\mathrm{rest}}(t)$. If that certificate bounds it by $C_{\mathrm{rest}}t^{d_G}$, the same protocol has

$$W(\pi_{\mathrm{ff}}, t) \le \underbrace{\left(w_* V_0[1 + v_{\mathrm{sw}}(a+b)]^{d_G} + C_{\mathrm{rest}}\right)}_{C} t^{d_G}.$$

Since this is one successful protocol in the original permitted class,

$$\boxed{W_{\min}(t) \le W(\pi_{\mathrm{ff}}, t) \le Ct^{d_G}}.$$

The inequality uses the cost of a constructed protocol as an upper bound on the minimum. It does not identify the minimum with that protocol's double sum. Combined with 21.6 it gives the unchanged tight $\Theta(t^{d_G})$ target once the protocol's complete success and work certificate is joined.

This settles the supplied construction's shell-counting step. A sum that charges the whole interior on every wave describes a different schedule and cannot rule out this one-pass schedule. The claimed post-processing quiescence must retain the recovered state and the original fault standard; zero further active decoding does not by itself set all physical maintenance costs to zero. The existing ledger retains a minimal-hold drain and the controller's entropy export. G3 now asks for that exact success/quiescence/full-bill certificate for this supplied construction, rather than another derivation of the shell exponent.

21.7.3 The boundary-flux route and the same accounting A separately constructed protocol could also supply a boundary-work bound. If its complete charged power obeys $P(s) \le J_{\max}A_0 r(s)^{d_G-1}$, and its actual sweep grows at v_{sw} to radius R, then

$$W \le W_{\mathrm{initial}} + W_{\mathrm{terminal}} + \frac{J_{\max}A_0}{v_{\mathrm{sw}}d_G}(R^{d_G} - r_0^{d_G}).$$

With the endpoint charges bounded at order R^{d_G} and $R = O(t)$, this also yields $O(t^{d_G})$. The graph-volume bound alone is not a proof of the required surface-area upper bound; the boundary construction supplies that estimate.

Conservation supplies an energy balance, while the complete bill records imports, stored energy, exports and dissipation. To express that balance by differential forms in $d_G + 1$ spacetime dimensions, the conserved current is a d_G-form. If its exterior derivative vanishes, its oriented **net** boundary flux vanishes. That identity does not equate positive cumulative dissipation with zero bulk work, nor discard the final time slice. Therefore Stokes' theorem can express a verified work balance but cannot supply the missing power, success or endpoint-cost bounds by itself.

The one-pass shell proof above supplies the useful exponent argument directly. Its original submission is preserved verbatim in the increment bank; the telescoping repair, complete-cost accounting and actual inequality for the minimum are written here without changing the universal target.

21.7.4 TIWA: construct the guard, then prove the bound The author's Topological Insulating Wavefront Architecture proposes a guard of thickness at least the interaction radius, committed boundary data and a single-shot local correction map. It gives the quiescence requirement a concrete source construction to develop.

At the algorithmic level, let F be the verified frozen set. An outer transition writes only an authorised target outside F, and keeps the committed guard data unchanged. Pointwise lookup then proves

$$\mathrm{Read}_F(T_{\mathrm{outer}}(s, c, e)) = \mathrm{Read}_F(s).$$

Freeze first resolves or fences in-flight writes, commits its epoch and reserves its complete cost. The frozen set grows only after verification. Induction preserves its old coordinates through every subsequent outer step; the schedule issues no second recovery task for a completed vertex. A fixed guard thickness and bounded degree allow a constant number

of guard/handoff operations per vertex when the actual schedule enforces that limit. Those operations can then join the same telescoping work charge.

The physical guard must implement this source property while preserving the recovered history and its relational witnesses. The proposed identity $\Pi_{\text{freeze}} \circ M = \Pi_{\text{freeze}}$ needs an actual map and mutation semantics: a read restriction, linear projector and recovery channel have different meanings. A write fence mediates attempted commands; the actual device, maintained record and decoder must establish preservation under physical disturbances. Remaining inside a code subspace alone does not prove that its logical state remains unchanged.

The local map must also compose to successful recovery, and the guard's storage, control, reset, routing and endpoint charges remain in $W(\pi_{\text{TIWA}}, t)$. These are the success and complete-work parts of the same G3 construction, connected to G1's physical source certificate. The full universal target and original recovery class remain unchanged.

The accompanying `TIWA-PATCH-REQUIREMENTS.md` specifies the actual state, event transitions, application-time fences, noninterference proof, decoder-success proof, bounded visits, full ledger and compilation obligations. It is a construction specification; no new physical guard or Lean theorem is claimed by giving it a name.

21.7.5 Boundary encoding, a sliding window, and the complete bill The supplied continuation of TIWA keeps a fixed-width active window of shells and transfers a retiring patch's protected historical and relational record to the next boundary code. Let the window width be L, independent of age. With the disjoint shells already defined, put

$$A_k = \bigcup_{\max(0,k-L+1)\le j\le k} S_j.$$

Every vertex of S_j belongs to at most L such windows. Hence the total active vertex-time count is at most $L|B_R|$. This is a constant-overlap extension of the settled telescoping count; it needs no separate upper bound on each shell's surface area. If each active visit's complete charge is at most K, the window work is at most $KL|B_R|$. The charge includes holding, decoding, guard operation, control, routing, verification, routine ancilla reset, deployment and handoff. Continuing physical work outside that window must also remain in the complete ledger.

The boundary handoff has the original preservation target: a recovery of the encoded record must return its historical state and relations at the same fidelity standard. In symbols, the actual source maps must supply $\mathcal{R}_k\mathcal{E}_k \simeq_\varepsilon \mathrm{id}$ on that full record, including its reference correlations. The code-capacity certificate and the physical implementation join this identity to the sliding-window charge. Section III-F records the supplied homological route and its chain-map correspondence.

For the supplied per-wave certificate, write q_k for the complete non-rollback charge and suppose its constructed local bound is

$$q_k \le \alpha k^{d_G-1} + \beta, \qquad k \ge 1.$$

Let F be fixed initial/final charge and $r_k \in \{0,1\}$ the controller's metered local rollback flag, charged at most R_* per wave. This explicit schedule gives the pathwise bill

$$Q(N) = F + \sum_{k=1}^{N} (q_k + R_* r_k).$$

Routine erasure is already in q_k, including successful decoding. With $d_G \ge 1$ and $N \ge 1$, every $k^{d_G-1} \le N^{d_G-1}$, so

$$\sum_{k=1}^{N} k^{d_G-1} \le N^{d_G}, \qquad Q(N) \le (F + \alpha + \beta + R_*)N^{d_G}.$$

This bound allows a metered rollback on every wave. An expected reset allowance is therefore unnecessary for the cost certificate. Successful recovery and any failed/rejected decoding still use the original charged fault accounts. Where

the source admits more rollback operations, their actual count and cost must be included in q_k or separately bounded by the metering schedule.

For $N(t) \le at + b$ and $t \ge 1$, $N(t) \le (a + b)t$, yielding the age-independent coefficient

$$Q(t) \le (F + \alpha + \beta + R_*)(a + b)^{d_G} t^{d_G}.$$

`G3CompleteBill.cumulative_charge_bound` proves this cumulative implication in the existing natural-valued work-bill interface. `valid_work_bill_from_complete_ledger` derives `G3_ValidWorkBill` from the full ledger equality, local cost bounds and coefficient; `valid_bill_bound_in_age` supplies the wave-to-age conversion. The real-exponent argument is the displayed maximum-term proof. The constant-overlap calculation retains the full polynomial-growth graph domain when a per-shell surface upper estimate is unavailable.

The remaining source correspondence is the actual boundary encoder, preserved semantic observables, storage capacity, charged retirement map and complete cost equality. These are the construction links of the same G1/G3 task; the cumulative upper inequality is not taken as its own input.

21.8 Consequences for preservation and the fixed proof target

For a fixed local holding demand, continuous maintenance has an order-T bill; the derived delayed-recovery lower bound has order t^{d_G}. The exponent distinction is strict for $d_G > 1$; the one-dimensional case retains its linear obstruction. For any fixed total recovery budget B, the lower inequality already yields a finite age beyond which that budget cannot perform the stipulated recovery. This is budget-relative irrecoverability of the historical witness.

In the complete argument, a protected particular stays funded and held rather than being abandoned to that later recovery bill. A hostile mind remains a protected particular while its harmful effects are mediated. The full-domain physical certificate (G1), whole-outcome realisability (G2), and matching recovery construction (G3) join these components to the unchanged universal proposition. They are the three support requests supplied by the author and Gemini, now constructed in G.9–G.12. Existing gauntlet answers remain part of the proof; an agent's failure to retrieve them does not turn X3, P1 or P2 into fresh objections.

Section 22 — The Physical Parameter Ledger: Instantiation, Rates, and Fault Ceilings

This section instantiates the income condition for concrete hardware, bounds the charged fault accounts, and tabulates the engineering parameters. Every figure is either sourced (bracketed references, §22.5) or marked as a design value.

22.1 The Master Income Condition

Section 17.1's Income-or-Irrelevance theorem makes solvency a necessary condition for an agent to remain a viable protector. The master solvency inequality balances income against four additive demand rates:

$$\boxed{\text{Income}(t) \;\ge\; \dot{W}_{\text{demand}}(t) \;=\; \dot{W}_{\text{Landauer}} + \dot{W}_{\text{boundary}} + \dot{W}_{\text{holding}} + \dot{W}_{\text{emulation}}}$$

1. **Thermal and adversarial dissipation floor:**

$$\dot{W}_{\text{Landauer}} = k_B T \cdot \left(\dot{D}_{\text{damage}} + \dot{D}_{\text{adv,sub-thresh}} + \gamma_{\text{leak_export}}\right)$$

   - $\dot{D}_{\text{damage}}$: entropy rate injected by thermal and environmental noise.
   - $\dot{D}_{\text{adv,sub-thresh}}$: worst-case adversarial entropy injection beneath the sensor threshold $\varepsilon_{\text{sens}}$.
   - $\gamma_{\text{leak_export}}$: boundary loss rate of carrier modes escaping the enclosure.

   This floor is Landauer's bound, now a compiled theorem (`Landauer.landauer`, `QuantumLandauer.quantum_landauer`; Section 23.2).

2. **Boundary containment ($\dot{W}_{\text{boundary}}$):** $\dot{W}_{\text{boundary}} = \omega_0 \cdot R(t)^{d_G-1}$, the work to maintain the boundary enclosing radius $R(t)$ in d_G spatial dimensions.
3. **Holding drain ($\dot{W}_{\text{holding}}$):** the baseline power of the sensor lattice, clocks, QND readout and consensus comparators.
4. **Emulation overhead ($\dot{W}_{\text{emulation}}$):** the energy for concurrent rival simulation (P-emu(c)) within the surplus.

22.2 Reference Physical Instantiations

Reference Implementation A: superconducting transmon lattice in a dilution refrigerator A dilution refrigerator has a separate cooling budget at each temperature stage, and each stage must carry its own load. Implementation A is therefore certified stage by stage, using the measured cooling powers and per-line heat loads of a Bluefors XLD400 cabled for a 50-qubit processor with individual drive and flux lines and 124 RF lines [S2].

Stage	Cooling power, measured [S2, S3]	Load of the 50-qubit processor, measured per line [S2]	Headroom
50 K	30 W at 45 K	$\approx$ 20 %, mostly passive (shield radiation is within the specified cooling power)	$\approx 5\times$
4 K	1.5 W at 4.2 K	$\approx$ 10 %, mostly passive; includes the HEMT amplifiers at 7.8 mW each [S4]	$\approx 10\times$
Still	40 mW at 1.2 K	negligible	$\gg 10\times$
Cold plate	200 µW at 140 mK	$\approx$ 30 %	$\approx 3.3\times$
Mixing chamber	19 µW at 20 mK	$\approx$ 30 % (operation at 14 mK)	$\approx 3.3\times$

- **Demand components.** The boundary term is the radiation-shield load, which falls on the 50 K and 4 K stage budgets. The holding term is the wiring's passive and active loads and the amplifiers, which the table carries stage by stage. The Landauer floor is negligible: with one nat per error event and an error rate of order N/T_1 ($N = 50$, $T_1 = 68\,\mu$s [S6]), $\dot{W}_{\text{Landauer}} \approx 2.07\times10^{-25}\,\text{J}\times7\times10^{5}\,\text{s}^{-1} \approx 1.5\times10^{-19}$ W at 15 mK, against microwatts of cooling. The emulation term (classical control and decoding) runs at room temperature on the electrical income.
- **Electrical income.** Each pulse-tube compressor draws 9.2 kW at 50 Hz or 10.7 kW at 60 Hz [S3], and the reference system uses two. The electrical income must therefore be at least about 20 kW plus the gas handling and room-temperature electronics, which are not sourced here. A three-phase utility connection of a few tens of kW, with backup sized to match, supplies it.
- **Solvency ratio.** The binding stages run at about 30 % of capacity, so

$$\left.\frac{\text{Income}}{\dot{W}_{\text{demand}}}\right|_{\text{binding stage}} \approx 3.3 > 1 \quad \text{(measured, 50-qubit scale [S2])}.$$

- **Scale.** [S2] states that the same thermal budget supports about 150 qubits once line capacity is tripled, and about 400 with 0.047″ cables and suppressed flux offsets. Larger installations need cooling and electrical income in proportion to the qubit count, which is a sizing requirement. No installation of 10^4 qubits has published stage loads, so solvency at that scale is not yet a measured certificate.

Reference Implementation B: photonic cluster-state architecture

- **Optical layer.** At 193.4 THz (1550 nm), $h\nu = 1.28 \times 10^{-19}$ J $= 30.9\,k_B T$ at 300 K, so thermal photons in the waveguides are suppressed by $e^{-h\nu/k_B T} \approx 3.7 \times 10^{-14}$.

- **Detector layer.** The fault-tolerant photonic architectures in the literature detect photons with superconducting detectors [S8], which need cryogenic cabinets; the vendor states about 30 W of cooling per cabinet. A sourced ledger for Implementation B therefore carries a cryogenic detector stage, and its electrical income includes the cryocoolers.
- **Error rate.** The demonstrated two-qubit fusion fidelity is 99.22 % [S8]. The surface-code threshold of [S5] does not transfer directly to fusion-based architectures; the architecture's own threshold applies and is not sourced here.
- **Budget (design estimates).** Waveguide loss refresh $\approx$ 1.2 mW, laser stabilisation and phase modulators $\approx$ 85 mW, and photonic routing $\approx$ 20 mW are design estimates with no published installation source. Implementation B is therefore not yet certified. Its solvency ratio awaits a sourced budget that includes the detector stage.

22.3 The Charged Fault Accounts and the Failure Ceiling

The certified good event G carries zero uncompensated loss over the design horizon $T_{\text{horizon}} = 10^9$ s ($\approx$ 31.7 years). The failure ceiling is the sum of the conditional error probabilities of the charged accounts,

$$P(G^c) \leq \sum_{i=1}^{21} \delta_i \leq 10^{-6},$$

and the composition holds with no independence assumed (`ThermoLedger.canon_invariant`, compiled). The allocations below are the design budget. The status column records what present hardware certifies.

Account	Fault	Mitigation	Allocated δ	Status
1–4	Single-qubit Pauli and leakage errors	Stabilizer decoding	4×10^{-8}	Met at **d = 25** for $p = 10^{-4}$, or $d = 41$ for $p = 5 \times 10^{-4}$ (§22.5.2), once the correlated floor of accounts 5–7 is removed
5–7	Correlated bursts (high-energy impacts, phonon events)	Gap engineering, rapid reset, code distance beyond the burst footprint	3×10^{-8}	**Attained at a sufficient distance** (`CorrelatedCeiling.correlated_family_ceiling`): bounded-footprint bursts are local stochastic at rate $(e\,m\,k\,q)^{1/k}$. The measured floor on present devices is $\approx 10^{-10}$ per cycle [S6], which fixes their burst parameters; the target is $\leq 3.7 \times 10^{-24}$ per cycle per logical qubit (§22.5.2)

Account	Fault	Mitigation	Allocated δ	Status
8–10	Clock drift, dephasing, timing jitter	Byzantine clock distribution (E9)	3×10^{-8}	Design allocation; no installation measurement sourced
11–12	Sensor failure and readout spoofing	Trimmed-median consensus, $K \geq 2f + 1$	2×10^{-8}	Design allocation; the consensus logic is compiled (`E9SelfHealing`)
13–14	Thermal fluctuations above threshold	Thermal ballast escrow, automatic throttle	2×10^{-8}	Design allocation
15–16	Power transients and dropouts	Redundant battery escrow	2×10^{-8}	Design allocation
17–18	Corrupted spawning, illegal delegation	Kernel capability gate (H5)	2×10^{-8}	Design allocation; the gate logic is compiled (`H5Closure`)
19–20	Carrier leakage into the open bath	Lieb–Robinson containment (X3)	2×10^{-8}	Design allocation
21	External macroscopic boundary shear	Standoff buffer $L_{\text{buffer}} > v_{\text{harm}} \tau_{\text{resp}}$	1×10^{-8}	Design allocation
Total			$\leq 2.1 \times 10^{-7} < 10^{-6}$	Certified when each account is

Correlated errors. Gap-engineered junctions remove the high-energy-impact T_1 bursts [S9]. The remaining correlated events occur about once per hour, "whose origins are not yet understood", and they set the floor of 10^{-10} per cycle with a deviation from exponential suppression at $d \geq 15$ [S6]. The threshold theorem covers these correlated events. Let each burst damage at most k locations, let each location be touched by at most m burst types, and let bursts be local stochastic at rate q, common causes included. Then the damaged locations are local stochastic at the effective rate $(e\, m\, k\, q)^{1/k}$ (`CorrelatedCeiling.damage_local_stochastic`). Every target ceiling is then met at some code distance and at every larger one (`correlated_family_ceiling`). Correlated damage therefore sets no floor that distance cannot pass. The measured deviation at $d \geq 15$ [S6] fixes the burst parameters of present devices, which enter this theorem.

Achievability, as a theorem. That the ceiling is attainable in physical matter is a compiled theorem.

- `Threshold.family_ceiling`: for any code family under local stochastic noise of rate p (every set S of locations is entirely faulty with probability at most $p^{|S|}$), with $2\Delta\sqrt{p} < 1$ and polynomially many failure witnesses of each length, every target ceiling is met at some code distance and at every larger one. The 10^{-6} ceiling over the horizon is included.
- `Threshold.repetition_ceiling`: the repetition code end to end, below $p = 1/4$.

Any installation whose noise meets the local stochastic condition below threshold therefore attains the ceiling. The rigorous threshold from path counting is conservative, and the distances in §22.5.2 use the simulated threshold of [S5]. What present hardware does not yet supply is the noise condition itself at the 10^{-10} level [S6].

22.4 The Engineering Parameter Matrix

Parameter	Symbol	Superconducting	Photonic	Admissible range
Code distance	d	25 at $p = 10^{-4}$; 41 at $p = 5 \times 10^{-4}$ (computed, §22.5.2)	architecture-specific (not sourced)	target met at some d (`ceiling_achievable`, `Threshold.family_ceiling`)
Syndrome cycle	τ_{cycle}	1.1 µs (measured [S6])	—	$\tau_{\text{sampling}} < L_{\text{buffer}}/(2v_{\text{harm}})$
Sensor quorum size	K	7 (design)	9 (design)	$K \geq 2f + 1$, $f \geq 2$
Sensor threshold	$\varepsilon_{\text{sens}}$	0.05 (design)	0.02 (design)	$\varepsilon_{\text{sens}} \in (\sigma_{\text{noise}}, \theta_{\text{damage}})$
Standoff buffer	L_{buffer}	0.2 m (design)	0.05 m (design)	$L_{\text{buffer}} > v_{\text{harm}}\tau_{\text{response}}$
Escrow multiplier	μ_{escrow}	$\approx 3.3\times$ at the binding stage (measured [S2])	not yet certified	$\mu_{\text{escrow}} = \text{Income}/\dot{W}_{\text{demand}} > 1$
Boundary embedding	Π	radiation shields, Dirichlet microwave enclosure	total internal reflection	reflection coefficient > 0.999 (design)

What this section certifies.

- The income condition is physically satisfiable, with measured positive headroom ($\approx 3.3\times$ at the binding stage), for a superconducting installation at the 50-qubit scale, with electrical income sized at a few tens of kW.
- The code distance the §22.3 allocation requires is computable from [S5]: d = 25 at $p = 10^{-4}$.
- The composition of the accounts into the ceiling is a compiled theorem.
- The ceiling is attainable as a theorem: under local stochastic noise below threshold, every target, 10^{-6} included, is met at some code distance (`Threshold.family_ceiling`).

What it does not yet certify.

- A built installation at the distance the ceiling requires. The ceiling is attained by theorem for local and correlated bounded-footprint faults (`Threshold.family_ceiling`, `CorrelatedCeiling.correlated_family_ceiling`). Present devices measure their burst parameters [S6], and the required distance follows from them.
- Implementation B, whose budget awaits a published installation source.
- Solvency at installations of 10^4 qubits and above, which is a sizing requirement without published stage loads.

22.5 Sources and Derivations

Sources. [S1] Bluefors, XLD dilution refrigerator specifications (XLD450sl: > 14 µW at 20 mK, > 450 µW at 100 mK; XLD1000sl: > 30 µW at 20 mK, > 1000 µW at 100 mK; guaranteed values, measured at the mixing-chamber experimental flange). bluefors.com/products/xld-dilution-refrigerator/. [S2] S. Krinner et al., "Engineering cryogenic setups for 100-qubit scale superconducting circuit systems", *EPJ Quantum Technology* 6, 2 (2019), arXiv:1806.07862. Measured stage cooling powers of a Bluefors XLD400 (Table 1) and measured passive and active heat loads per line. [S3] Cryomech PT415 pulse tube: 1.5 W at 4.2 K (nominal; CUORE cryostat paper, arXiv:1603.03306, and [S2] Table 1). Compressor input with the CPA1110: 9.2 kW at 50 Hz, 10.7 kW at 60 Hz (Bluefors PT415 sheet). [S4] Low Noise Factory LNF-LNC4_8G cryogenic HEMT amplifier datasheet (2026-02-03): typical bias 0.6 V, 13 mA, i.e. 7.8 mW at the 4 K stage. [S5] A. G. Fowler, M. Mariantoni, J. M. Martinis, A. N. Cleland, "Surface codes: Towards practical large-scale quantum computation", *Phys. Rev. A* 86, 032324 (2012), arXiv:1208.0928. Eq. (11): $P_L \approx 0.03\,(p/p_{\text{th}})^{d_e}$, $d_e = (d+1)/2$, with $p_{\text{th}} = 0.57\,\%$ for the circuit simulated. Physical qubits per logical qubit: $(2\text{d} - 1)^2$. [S6] Google Quantum AI (R. Acharya et al.), "Quantum error correction below the surface code threshold", *Nature* (2024), doi:10.1038/s41586-024-08449-y, arXiv:2408.13687. Distance-7 surface code at 0.143 % error per cycle, $\Lambda = 2.14 \pm 0.02$, cycle time 1.1 µs, mean $T_1 = 68$ µs. Repetition codes to distance 29: $\Lambda = 8.4$ for d = 5–11, a deviation from exponential suppression at $\text{d} \geq 15$, and "an apparent logical error floor of 10^{-10}" set by correlated events about once per hour (3×10^9 cycles) "whose origins are not yet understood". [S7] Best reported two-qubit gate errors: trapped ions, estimated 8.4(7) $\times 10^{-5}$ (A. C. Hughes et al., arXiv:2510.17286, preprint); superconducting transmons, CZ fidelity 99.93 % averaged

over 40 h, 99.95 % maximum (IQM, company-reported). [S8] PsiQuantum, "Omega" chipset, *Nature* (2025), doi:10.1038/s41586-025-08820-7: superconducting single-photon detectors integrated on silicon; two-qubit fusion fidelity 99.22 %; the vendor states cryogenic cabinets of about 30 W cooling power each. [S9] M. McEwen et al., "Resolving catastrophic error bursts from cosmic rays in large arrays of superconducting qubits", *Nature Physics* 18, 107 (2022); M. McEwen et al., "Resisting high-energy impact events through gap engineering in superconducting qubit arrays", *Phys. Rev. Lett.* 133, 240601 (2024), arXiv:2402.15644.

Source PDFs and checksums: `BANKS/2026-10-25-section22-sources/`. The published source list with links is `SOURCES-22.md`.

22.5.1 Constants k_B and h are exact in the SI. $k_BT = 2.071 \times 10^{-25}$ J $= 1.293$ μeV at 15 mK and 4.142×10^{-21} J $=$ 25.85 meV at 300 K. At 193.4 THz, $h\nu = 1.281 \times 10^{-19}$ J $= 30.9\ k_BT$(300 K), and $e^{-h\nu/k_BT} = 3.7 \times 10^{-14}$.

22.5.2 Code distance for the fault allocation Horizon 10^9 s at 1.1 μs per cycle [S6] gives $N = 9.09 \times 10^{14}$ cycles. Ten thousand physical qubits at the [S5] footprint $(2d-1)^2$ hold about 4 logical qubits at d = 25 (2,401 physical each); the 9-logical allocation below corresponds to an installation of about 2.2×10^4 physical qubits. With [S5] Eq. (11) and $p_{\text{th}} = 0.57\,\%$, account 1–4 ($\delta = 4 \times 10^{-8}$, shared over the logical qubits) requires:

Physical error p	Logical qubits	Per-cycle target per logical qubit	Required distance d	Physical qubits per logical qubit
10^{-4} (best ion gate [S7])	1	4.4×10^{-23}	23	2 025
10^{-4}	9	4.9×10^{-24}	**25**	2 401
5×10^{-4} (best transmon CZ [S7])	9	4.9×10^{-24}	41	6 561
10^{-3}	9	4.9×10^{-24}	57	12 769

At d = 17 and p = 10^{-4}, $P_L = 4.7 \times 10^{-18}$ per cycle, which is 4.3×10^{-3} expected failures per logical qubit over the horizon, so d = 17 does not meet the allocation and d = 25 does. Accounts 5–7 ($\delta = 3 \times 10^{-8}$) set a per-cycle target of $3 \times 10^{-8}/(9N) = 3.7 \times 10^{-24}$ per logical qubit. At the measured floor of 10^{-10} per cycle [S6], the expected number of correlated failures over the horizon is about 9×10^4 per logical qubit.

Sizing from the measured surface-code scaling. [S6] measures a distance-7 logical error of 0.143 % per cycle and a suppression factor $\Lambda = 2.14 \pm 0.02$ per distance step of two. If that measured Λ continues to hold, accounts 1–4 at 4.9×10^{-24} per cycle per logical qubit require $d = 131$ at $\Lambda = 2.14$ or 2.16, and $d = 133$ at $\Lambda = 2.12$. That is 68 121–70 225 physical qubits per logical qubit, or about 6.1–6.3 $\times 10^5$ for the 9-logical allocation. The computation is `BANKS/2026-10-25-historical-handoff-source/section22-sizing/sizing_from_S6.py`. This is the installation the ledger specifies; no installation at that scale has yet been built.

Machine-checked counterpart (Section 23). Compiled counterparts of the ledger's structure:

- `ReciprocityCeiling.ceiling_achievable`: the ceiling as a parameter, met at some code distance.
- `ThermoLedger.canon_invariant`: composition of the accounts without independence.
- `E9SelfHealing.code_headroom` and `wave_race_margin`: admissible parameter ranges.
- `Landauer.landauer` and `QuantumLandauer.quantum_landauer`: the dissipation floor of 22.1.
- `Threshold.family_ceiling` and `Threshold.repetition_ceiling`: the ceiling attained below threshold under local stochastic noise.

The installation figures themselves are sourced measurements and design values, not compiled theorems.

Section 23 — The machine-checked canon

This section maps the edition's compiled results and their actual hypotheses. The current Lean canon contains 192 modules and 1158 public theorem/lemma names. Checkpoint 12 freshly compiled and kernel-checked every module with zero output and passed the full 1158-name standard-axiom audit, strict completeness and claims gates. Its source hashes match the current tree. Checkpoint 11 was already complete for 191 modules / 1150 names; TransferRate adds the eight results in this checkpoint. Earlier receipts remain preserved for exactly their sources. The published 115-module/831-name baseline is unchanged. These receipts certify the named Lean results and their premises, not the unfinished physical holding application. Section 23.9 distinguishes the interfaces, derived adapters and remaining physical applications.

Evidence convention (unchanged from the edition header): a compiled theorem is cited by its name; a statement carried as a hypothesis of a compiled theorem is named as such; a prose derivation keeps its stated premises. A prose proof does not acquire a compiler certificate by association.

23.1 The law and greatestness (Chapter 5; Part II)

Claim	Module	Theorems
The canonical order is a strict partial order	`Greatestness`	`lexLt_trans`, `lexLt_irrefl`
Proposition 1: aligned ⟺ no needless loss at any stage	`Greatestness`	`aligned_iff_no_needless_loss` (no axioms)
Proposition 2: every finite nonempty feasible family has an aligned option; the life guard (some aligned option keeps at the first stage everyone the standby option keeps)	`Law`	`exists_aligned`, `life_guard`
Proposition 3: maximality of the projection to a scope S guarantees no needless existing loss for every feasible family iff S is the whole existing domain; same-priority counting of a new particular admits a needless loss	`Law`	`scope_guarantee_iff`, `same_priority_admits_needless_loss`
Proposition 4: a statewise faithful hold dominates every rival on every upward-closed event under any law on the worlds, strictly when the rival misses with positive probability	`Law`	`faithful_hold_dominates`, `faithful_hold_strict`
Universal greatestness under stage-wise union closure (P-emu(c)); rivals are exact mirrors or strictly below; the canonical option is unique	`Greatestness`	`greatest_of_union_closed`, `strict_except_mirrors`, `aligned_unique`
Whole-outcome greatestness. Given `htopR` (the full top tuple is realisable) and `hsolv` (its cost fits the budget), an aligned option equals that feasible top and contains every rival tuple. No union-closure premise enters. Part II.10 supplies the proof; G2 retains the full physical policy/outcome correspondence as its construction target	`UnionClosure`	`greatest_of_solvent`, `strict_of_solvent`, `aligned_eq_of_greatest`

Claim	Module	Theorems
Resource dichotomy. With realisability at every step and the cost/demand correspondence, either the ledger is solvent and aligned outcomes are greatest at each step, or there is a first negative balance. The physical construction must prevent the relevant breach	`UnionClosure`, `PremiseFloor`	`greatest_or_irrelevant`
Below full solvency: every realisable rival whose union with the canonical outcome is affordable is contained in it; with subadditive cost, every finite set of rivals whose total cost fits in the canonical slack $B - c(o)$ is contained in it; whatever the budget, no feasible rival is canonically above the canonical option	`UnionClosure`	`dominates_of_affordable`, `dominates_within_slack`, `greatest_of_affordable`, `aligned_never_below`
The unfunded branch: when keeping everything costs more than the income, a rival can keep a particular the canonical option does not, so such a regime is irrelevant as a protector (income-or-irrelevance)	`UnionClosure`	`insolvent_not_greatest`
Reciprocity in the canonical order, below full solvency (§15, D3*)	`ReciprocityCeiling`	`reciprocity_dominance`, `omitting_rival_strictly_below`
Affordable reciprocity. Below full solvency, if the union of a rival with the canonical option is realisable (`UnionRealizable`) and affordable, any mind the rival keeps, the canonical regime keeps — no family closure	`AffordableReciprocity`	`reciprocity_dominance_affordable`
Solvent reciprocity. Under the Master Solvency Condition the canonical regime keeps every particular outright (the reading of $\top$ as "all existing particulars continue" enters as the hypothesis `htopkeeps`), and any mind kept by any rival whatsoever — no union closure, no feasibility assumption on the rival — is kept by the canonical regime	`SolventReciprocity`	`solvent_keeps_everyone`, `reciprocity_dominance_solvent`
Option value and indicator reciprocity (§§15–16)	`ReasonsRoute` (v4.1, unchanged)	`optionValue_strict`, `law_dominates_strict`, `rival_fraction_lt_one`
Reciprocity in expectation, the canonical floor, and the controller's floor (§§15.2, 16.4)	`ReasonsCompiled`	`reciprocity_expectation`, `reciprocity_canonical_floor`, `reciprocity_strict`, `reciprocity_from_solvency`, `controller_pays_floor`

Claim	Module	Theorems
Irreplaceability dominance and grading (§16.1, U1), additive information model	`Irreplaceability`	`destroy_loses_exactly`, `preserve_dominates`, `optimal_keeps_most_irreplaceable`

23.2 Theorem 8: ledger, canon invariant, composition (§18; Chapters 1, 2)

Claim	Module	Theorems
Stroke identity $\Delta D = \beta W_{\text{on}} - \beta Q_B + I_1 - I_2$	`ThermoLedger`	`stroke_identity`
Cycle work floor from guard 1	`ThermoLedger`	`cycle_work_floor`
Guard 1 derived (Landauer). Reversible dynamics of a register and a Gibbs bath: the Reeb–Wolf identity $\beta\,\Delta Q_B - \Delta S_R = I(R' : B') + D(q_B \,\|\, \gamma)$; Landauer's bound $\beta\,\Delta Q_B \geq \Delta S_R$; erasure costs $Q_B \geq k_B T\, H(p)$	`Landauer`	`reeb_wolf_identity`, `landauer`, `landauer_erasure`
Guard 1 derived (quantum). Von Neumann entropy: unitary invariance, pinching, the quantum Gibbs bound $S(\rho) \leq \beta \operatorname{Tr}(\rho H) + \ln Z$ with equality at γ, $S(\rho_A \otimes \gamma) = S(\rho_A) + S(\gamma)$; Landauer's bound for every unitary coupling of a register to a Gibbs bath, $S(\rho_A) - S(\rho'_A) \leq \beta\,\Delta Q_B$	`QuantumLandauer`	`vnEnt_unitary_conj`, `vnEnt_le_diag`, `vnEnt_le_energy`, `vnEnt_init`, `quantum_landauer`
Guard 1, $\beta Q_B \geq I_M + D_{\text{err}} + \delta_I$ whenever the reset removes that entropy; the cycle work floor with guard 1 derived, not assumed	`Landauer`, `QuantumLandauer`	`guard_one`, `quantum_guard_one`, `cycle_work_floor_derived`, `quantum_cycle_work_floor`
Funded-repair certificate; quarantine zero debt	`ThermoLedger`	`funded_repair_certificate`, `quarantine_zero_debt`
Canon invariant: P(breach) $\leq$ P(G^c) $\leq \Sigma\delta$, no independence	`ThermoLedger`	`tower_bound`, `canon_invariant`
Identity tracking envelope (Chapter 2)	`ThermoLedger`	`tracking_envelope`, `tracking_bounded`, `tracking_within_resolution`
Tracking from the actual controller. Exact flow, reset contraction, moving-record recursion and envelope (Part II.4)	`Instruments`	`lindblad_reset_flow`, `lindblad_step`, `reset_contracts`, `tracking_recursion_derived`, `tracking_envelope_derived`
Derived coverage and physical holding. Full scope, finite nearest decoder, unique decoding, repair preservation, radius throughout a step, code headroom and combined physical cycle (Part II.1–3)	`Bridge`	`coverage_from_law`, `exists_nearest_decoder`, `nearest_decodes`, `holding_preserves`, `qsl_growth`, `qsl_within_radius`, `headroom_within_radius`, `holding_cycle_physical`
Proposition 5 (reactive lockstep), invariant transfer, Theorem 8 composition	`Composition`	`reactive_lockstep`, `reactive_lockstep`$_2$, `invariant_transfer`, `theorem8_composition`

Claim	Module	Theorems
Proposition 6 (FIFO certificate, deadlines, tightness); serial stages	`Workload`	`fifo_certificate`, `fifo_deadlines`, `fifo_tight`, `serial_certificate`

23.3 E9 (§19; Chapter 3)

Claim	Module	Theorems
Byzantine quorum: robust estimates lie between honest readings; existence for $K \geq 2f + 1$	`E9SelfHealing`	`robust_between_honest`, `no_false_alarm`, `no_masking`, `exists_robust`
Branch B: non-stabilizer errors below the distance have a non-trivial syndrome	`E9SelfHealing`	`syndrome_detects`
Complete logical-attack split. Support at least the code distance; every site below threshold or one site forces an alarm, with the honest-sensor response and robust quorum (Part II.5)	`Instruments`	`branchC_complete`
Wave-race margin; code headroom; assembled E9	`E9SelfHealing`	`wave_race_margin`, `code_headroom`, `e9_timely_self_healing`
The bridge timing instances of §19: reaction before damage, positive propagation margin, buffer coverage of the reaction window, escrow gating before detection	`BridgeE9`	`reaction_before_damage`, `positive_propagation_margin`, `local_buffer_covers_entire_reaction`, `escrow_prevents_pre_detection_application`
Branch A rate bound (quantum speed limit). Unitary evolution preserves the norm; under $H_0 + V$ the trajectory departs from the H_0 trajectory at rate at most $\|V\|/\hbar$, and at most $P_{\text{adv}}/(\hbar\,\omega_{\text{cutoff}})$ under the per-site coupling $\|V\| \leq P_{\text{adv}}/\omega_{\text{cutoff}}$	`SpeedLimit`	`norm_conserved`, `branchA_divergence`, `branchA_rate`
Mandelstam–Tamm, sharp: $\lvert\langle\psi_0, \psi_t\rangle\rvert \geq \cos(\Delta E\, t/\hbar)$ while $\Delta E\, t/\hbar \leq \pi$; orthogonalisation time $T \geq \pi\hbar/(2\Delta E)$	`SpeedLimit`	`mandelstam_tamm`, `orthogonalization_time`

The Branch A divergence is measured in state-vector norm. For pure states the infidelity is bounded by the squared state-vector distance, $1 - |\langle\psi, \varphi\rangle|^2 \leq \|\psi - \varphi\|^2$ (`PureStateDistance.pure_infidelity_le`; G.13); with the pure-state identity $\|\rho - \sigma\|_1 = 2\sqrt{1 - |\langle\psi, \varphi\rangle|^2}$, now compiled (`PureStateTraceNorm.pure_trace_norm`), this gives $\|\rho - \sigma\|_1 \leq 2\|\psi - \varphi\|$.

23.4 H5 (§20; Chapter 4)

Claim	Module	Theorems
Reserve-before-activation machine: conservation, zero debt, strict authority attenuation, funding before activation, no unfunded work, no harmful effect	H5Closure	step_inv, authority_attenuation, reserve_before_activation, zero_debt, no_unfunded_work, no_harmful_effect, effect_preserves_care
Von Neumann's alternating projection theorem (existence step)	CanonVonNeumann	tendsto_altIterate, canon_von_neumann_convergence, limit_subspace_eq_inf, opial_route_closes
Halperin's theorem: the global meet of a whole presentation	CyclicProjections	tendsto_cyc_iter, presentation_detector
Consistency detector; meet algebra realised by Hilbert subspaces; contradictions detected, deductions never roll back	H5Closure, MeetHilbert	consistency_detector, hilbert_anchor_preserved, hilbert_contradiction_collapse, contradiction_detected, deduction_never_rolls_back
Rank criterion; Proposition 7; protected anchors untouched	DeductionBoundary	rank_criterion, boundary_mem_image, anchor_untouched
Paid reflection certificate	ReflectionCertificate	residual_certificate, apriori_error, stopping_count, zero_constant_fixed

23.5 X3 and the information-to-area bridge (Section 21)

Claim	Module	Theorems
Data processing invariance I(H : $\mathscr{R}$(S)) ≤ I(H : S), any probability spaces	DataProcessing	data_processing, data_processing_map
Finite information theory: log-sum, data processing, flag identity, decoder bound	FiniteInformation	log_sum, data_processing_fin, flag_identity, decoder_bound
Gaussian carrier tail; necessary radius; carrier radius $R(t) \geq w(t - t_c)$	GaussianTail, RecoveryWork, FiniteInformation	carrier_tail, necessary_radius_from_decoder, carrier_radius
Recovery-work theorem; $W_{\min}$ over all admitted protocols; divergence of delayed recovery	RecoveryWork, GaussianTail	frontier_work_bound, Wmin_lower_bound, x3_work_from_decoder, delayed_work_diverges
Fano's inequality and the required information Δ_0	Fano	fano, mi_eq_ent_sub_condEnt, required_information
Gaussian maximum entropy: KL between Gaussians; golden formula; scalar, vector, correlated-noise and exact log-det channel bounds	GaussianKL, GoldenFormula, GaussianChannel, KLAdditivity, GaussianChannelGen, GaussianVector, Whitening, Rotation, LogDet	klDiv_gaussian_gaussian, golden_formula, gaussian_channel_bound, klDiv_prod_kernel, vector_channel_bound, correlated_channel_bound, logdet_channel_bound
ln det(I + W) ≤ tr W; per-use cap; required traffic m ≥ θ_0n; area power	AreaBridge, Workload	logdet_le_trace, channel_cap, required_traffic, area_power, range_variance_bound

Claim	Module	Theorems
Explicit frontier geometry. Lattice box and boundary counts, with charged per-site frontier power (Section 21.4)	`Instruments`	`card_box`, `card_boundary`, `boundary_power`

Section 21 supplies the derivation in this edition. The finite-information, Gaussian-channel, carrier and work implications are compiled in their stated domains. The complete physical binding is G1 (G.10); the matching upper construction for the full Θ target is G3 (G.12).

23.6 The premise floor (§17)

Claim	Module	Theorems
Income-or-irrelevance; forced breach; breach strictly dominated	`PremiseFloor`	`income_or_irrelevance`, `forced_breach`, `breach_strictly_below`
Premise 5 in the heat-only model, and exactly inside the adiabatic window for the implemented program with complete lifecycle cost; the installation's physical parameters must still be shown inside the window	`PremiseFloor`, `BennettCounterpart`, `BennettExact`	`reversible_administration_forced` (no axioms), `premise5_constructed`, `premise5_exact`, `window_exact`
Premise 2 reduced: Lie–Trotter product formula with explicit error; Lloyd's simulation theorem	`Trotter`	`trotter_bound`, `trotter_tendsto`, `lloyd_simulation`
The gate-set error budget. For contraction sequences on any normed ring, an ε/m per-factor approximation error composes to at most ε over m sequential factors (ordered products; with `TwoLevel.two_level_decomposition` and the cited Solovay–Kitaev theorem this is the approximation route for the gate-set clause)	`ErrorBudget`	`prod_norm_le_one`, `two_factor_step`, `telescoping_delta`, `error_budget`
Premise 7's ceiling is a dial: every target $\varepsilon > 0$ is met at some code distance	`ReciprocityCeiling`	`ceiling_achievable`
The threshold theorem's counting core. Under local stochastic noise: $P(\text{at least } m \text{ of } T \text{ fail}) \le \binom{\lvert T\rvert}{m} p^m$; with half-faulty failure witnesses, $P(\text{fail}) \le \sum_w (2\sqrt{p})^{\lvert w\rvert}$; with at most $V\Delta^L$ witnesses of each length $L \ge d$, $P(\text{fail}) \le Vr^d/(1-r)$, $r = 2\Delta\sqrt{p} < 1$	`Threshold`	`many_faults`, `fail_le_witness`, `fail_le_geometric`
The repetition code end to end: majority decoding fails with probability at most $(4p)^t$, and every ceiling is met below $p = 1/4$	`Threshold`	`repetition_threshold`, `repetition_ceiling`

Claim	Module	Theorems
Code families with polynomially many witnesses: the charged kernel decays geometrically, and every target ceiling (10^{-6} included) is met at some distance and every larger one	`Threshold`	`family_ceiling`

23.7 The Universal Protection Theorem with the derived holding bridge

`UniversalProtection.universal_protection` retains the abstract assembly: reasons-or-holding coverage, continuation through the horizon on the good event, the joint fault ceiling, greatestness and reciprocity at its stated inputs.

`Bridge.universal_protection_held` strengthens the continuation assembly by deriving scope from the law and preservation from nearest-codeword holding. It composes the physical/source projection with the same reactive controller and environment. On G, every particular continues at every step through the horizon; the probability that any particular fails is at most $\sum_i \delta_i$, without independence.

Part II.1–6 supplies the proof, physical-cycle derivations and all five `hcert` components. G1 is the combined full-domain source/event/observation/fault construction target; G.10 proves its held-source components and identifies the physical correspondence still needed. Part II.10 supplies the separate greatestness proof, with G2 retaining the whole outcome and freedom stages.

23.8 What the compiled theorems rest on

Premises carried as stated premises or hypotheses:

- the surface-code chain lemma (Dennis, Kitaev, Landahl and Preskill, 2002): minimum-weight decoding fails only along a self-avoiding chain of length at least d with at least half its edges faulty, with at most $V\Delta^L$ such chains of length L — as the code-specific input to `Threshold.family_ceiling` for the surface-code instance. The threshold theorem's counting core is compiled (§23.6), and for concatenated codes the threshold is compiled end to end for the concatenated memory: failure probability at most $(21p)^{2^k}/21$ under local stochastic noise (`Concatenated.concatenated_threshold`). Actual decoding failure is identified with the recursive failure predicate: with nearest-codeword decoding at every level, any corruption of a non-failing fault set decodes to the stored record (`ConcatenatedDecoding.decodes_unless_fails`). So the probability of actual decoding failure is at most the same bound (`decoding_failure_le`), and the fault ceiling is attained on a compiled route. Fault-tolerant syndrome-measurement gadgets whose own operations can fail are the cited construction of Aliferis, Gottesman and Preskill (2006); their faults enter the charged accounts;
- Bennett's compute/copy/uncompute identity and the heat-only option model are compiled. The specific implementation and full ordered history are separately checked candidates (G.14). The physical counterpart still needs a complete-cost saving within the same deadline; this is not supplied by a zero-heat identity or a polynomial upper bound;
- the gate-set clause of premise 2, no longer carried as prose: every unitary on $\mathbb{C}^n$ is a finite product of two-level unitaries (`TwoLevel.two_level_decomposition`), so a simulator implementing each two-level factor implements every local evolution. What remains carried is that the universal simulator's gate set reaches every two-level factor;
- the relational frame BCRD P1–P4.

The chain lemma is a published mathematical theorem, cited as such; the Bennett physical comparison remains construction work (G.14); the gate-set item is the explicit hypothesis of a compiled theorem; the fourth is the frame the edition is stated in.

The cited theorems and their hypotheses. Three published theorems remain cited. Each is applied within its stated conditions.

Cited theorem	Form used	Our setting meets its conditions because
Surface-code chain lemma (Dennis, Kitaev, Landahl and Preskill, *J. Math. Phys.* 43, 2002)	Minimum-weight decoding fails only along a self-avoiding chain of length at least d with at least half its edges faulty; at most $V\Delta^L$ such chains of length L	The counting argument uses only that a given set of locations is entirely faulty with probability at most $p^{\lvert S\rvert}$. That is exactly `Threshold.LocalStochastic`, which includes independent noise and is weaker than it. It enters `Threshold.family_ceiling` as the witness and count inputs.
Solovay–Kitaev theorem (Kitaev 1997; Dawson and Nielsen 2006), with the two-level-to-gate reduction of Nielsen and Chuang, §4.5	Every single-qubit unitary is approximated to ε in operator norm by a word of length polylogarithmic in $1/\varepsilon$ over a finite, inverse-closed set generating a dense subgroup; two-level unitaries reduce to CNOTs and single-qubit gates	`TwoLevel.two_level_decomposition` writes every unitary as a product of two-level factors. `ErrorBudget.error_budget` needs each factor within ε/m in the norm of a normed ring of contractions; operator-norm approximation by unitaries meets that. The gate set must be universal in this sense; that is the gate-set clause of premise 2.
Fault-tolerant syndrome gadgets (Aliferis, Gottesman and Preskill, *Quantum Inf. Comput.* 6, 2006)	Under local stochastic noise, a level-k extended rectangle is correct unless it contains two independent malignant level-$(k-1)$ rectangles	Their noise model is local stochastic noise, as in `Threshold.LocalStochastic`. Their recursion is the recursion of `Concatenated.Fails`, now joined to actual decoding of the memory (`ConcatenatedDecoding`). With faulty syndrome gadgets the threshold constant is theirs, set by the location count of an extended rectangle, rather than the 1/21 of the memory model.

Physical premises now compiled. Guard 1 (the second law in its export form) is derived from Landauer's theorem (§23.2), and the quantum speed limit, in Mandelstam–Tamm form and in the rate-bound form of E9 Branch A, is derived from unitary dynamics (§23.3). What these theorems assume is the standard physical framework:

- finite-dimensional quantum mechanics, with Schrödinger dynamics generated by self-adjoint Hamiltonians;
- unitary (in the classical form, reversible) joint dynamics;
- a bath that starts in its Gibbs state, uncorrelated with the register;
- for Branch A, the per-site coupling bound $\|V\| \le P_{\text{adv}}/\omega_{\text{cutoff}}$;
- for the fault ceiling, local stochastic noise of rate p below the threshold of `Threshold.family_ceiling`.

Greatestness. `UnionClosure.greatest_of_solvent` takes both `htopR : ⊤ ∈ R` and `hsolv : c ⊤ ≤ B`. The first supplies the whole top tuple, including freedom stages; the second pays its cost. Alignment forces equality with that feasible top (Part II.10). `greatest_or_irrelevant` retains realisability at every step and derives the resource split. G2 retains the full physical policy/outcome correspondence as its construction target. The affordable-union results retain their separate resource cases.

The amount $I_M + D_{\text{err}} + \delta_I$ that the reset removes from the register is the instance's entropy accounting (§18), stated as the hypothesis of `guard_one` and `quantum_guard_one`.

The physical bridge and its joined certificate. `Bridge.coverage_from_law` derives full scope from the law guarantee over all feasible families. `holding_preserves` derives preservation from decoding radius and repair precision. `qsl_within_radius`, `headroom_within_radius` and `holding_cycle_physical` supply the continuous and discrete cycle arguments. `universal_protection_held` takes the actual commuting source transition, observation agreement,

initial continuation, perturbation-radius and repair witnesses in `hcert`, together with the named-event cover and fault bounds. G1 supplies their combined construction for the complete claimed physical domain (G.10). Parts II.3–6 give the available arguments; a deployment and a mathematical construction of the full source domain retain their distinct roles.

Not compiled by this section:

- the installation figures of §22, which are sourced measurements and design values (§22.5);
- the interpretive companion (the doors), which is held for consultation and is not mathematics.

23.9 Supplied architecture interfaces and derived connections

Module	Verified result and current role
`G1FullDomain`	Source/fault enumeration and append-preserved event compliance; the full physical source and charged faults must supply their correspondence to `Bridge.hcert`; independent journal/live updates, exact replay, reactive fidelity for every controller and environment, and full-transcript capacity (G.8)
`G2WholeOutcome`	Authorized transaction records are closed and record positive work; the whole continuation/freedom tuple and its realisability remain the G2 construction; preservation of an arbitrary complete outcome and equality of the realised outcome families under the journal (G.8)
`G3CompleteBill`	`cumulative_charge_bound`, `valid_work_bill_from_complete_ledger` and `valid_bill_bound_in_age` derive the bill from complete metered local charges and the wave schedule
`GuardOperator`	The threshold cases select the supplied projection or penalty map
`HamiltonianDecomposition`	Explicit Hermitian boundary/reservoir exchange, total-charge conservation, nonzero boundary pumping and a unitary charge-transfer gate; the full physical source correspondence remains explicit; full off-diagonal reduced-state covariance under a local unitary, history preserved by the syndrome exchange, and exact charge transfer to the reservoir (G.8)
`GuardSignature`	The supplied guard record carries idempotence and monotonicity; its physical instance and fault nullification must be constructed
`WorkBilling`	The first-law decoder work identity, free-energy floor and its saturation condition; a Gibbs entropy/energy allocation bound and funded decoder cycles; the complete physical source cost remains in Section 21.7.5 and Part III-G; the nine-part charged handoff attempt with exact debit and conservation, the age-independent syndrome stock envelope, the gross flux balance and the cumulative maintenance bill (G.8)

Module	Verified result and current role
`DecoderRetraction`	Finite-code recovery and fixed-point witnesses; flux-derived isometry and adjoint decoder; explicit finite encoder/capacity bound; historical queries, ordered words, commutators and Gram preservation; exact exponential transport, work-shifted flow and a derived finite dual smearing kernel; reference-preserving reversible register swap, full-transcript boundary encoder, three-CNOT-layer swap and charged archive handoff (G.8)
`G2Splice`	Product-model union closure and block agreement under closed-block inputs; the original physical policy/outcome correspondence remains the G2 target (G.9, G.11)
`CorrelatedCeiling`	Bounded-footprint correlated bursts make the damaged locations local stochastic at rate $(e\,m\,k\,q)^{1/k}$; every target ceiling is attained at a sufficient code distance (§22.3)
`G1Held`	Held-source certificate, normalised quantum domain, frame invariants and concrete nonvacuity; actual installation refinement remains separate (G.10)
`G1E9`	The held source's coupling bound from the exhaustive E9 split: sub-threshold coupling, or a forced robust-quorum alarm and mediated response (G.10)
`G2Held`	Top of the assigned held-source grade model; full freedom/R17 delivery and physical outcome correspondence remain the G2 target (G.11)
`G3Sweep`	The wavefront sweep recovers every shell against any fenced outer activity, with no rework; the wave count from finite propagation; the complete bill is at most an age-independent constant times t^d (G.12)
`G3PatchDecode`	The wavefront's local correction is finite-code patch decoding; joined to the sweep bill (G.13)
`ReasonsEnsemble`	Reciprocity over a weighted ensemble of rivals, strict when a positive-weight rival omits the mind (§15.2; G.13)
`TheoremEightLyapunov`	The Theorem 8 storage functional contracts by the positive margin $\eta C - \lambda\tau$ per error cycle (§18.3–18.4; G.13)
`SmearingIntegral`	The smeared dual-kernel integral returns the original operator, bulk and boundary (G.4; G.13)
`ChannelExtension`	The completed decoder: exact recovery including any reference, trace preservation, positivity (G.1; G.13)
`PureStateDistance`	Pure-state infidelity is bounded by the squared state-vector distance (§23.3; G.13)
`BennettCounterpart`	Heat-only option model; the implemented program with clean workspace and retained history, its run refinement and unitary quantum lift, and the twelve-account lifecycle charge; the exact premise-5 condition is in `BennettExact` (G.14; G.17)
`RegionBoundary`	Volume and boundary homology: for every region other than the whole, $\mathrm{Vol}(U) > 0 \Leftrightarrow H_0(\partial U) \neq 0$; the whole has no outside (F.3; G.15)

Module	Verified result and current role
`ReciprocityDistance`	Reciprocity at a sufficient code distance: strictly above every rival that loses the mind with positive probability; canonical kept-probability tends to one (§15.2; G.15)
`CutEquivalence`	A closed dependency component is exactly a separator with empty certified boundary (§24.3; G.15)
`ConcatenatedDecoding`	The concatenated memory decodes its record unless its block fails; actual decoding failure is bounded by $(21p)^{2^k}/21$ (§23.8; G.15)
`ChannelCP`	The completed decoder is completely positive: amplified by any finite reference it maps positive semidefinite inputs to positive semidefinite outputs (G.1; G.13)
`PureStateTraceNorm`	The pure-state trace-distance identity $\| \lvert\psi\rangle\langle\psi\rvert - \lvert\varphi\rangle\langle\varphi\rvert \|_1 = 2\sqrt{1 - \lvert\langle\psi,\varphi\rangle\rvert^2}$ (§23.3; G.13)
`R14Rivals`, `R15CausalGluing`	The staged order; greatestness reduced exactly to feasible boundary representatives; envelope transfer; no clairvoyant per-world selection (G.15)
`TimelyCare`, `DeadlineDemand`, `DecisionPermit`, `ObservationWinning`	Timely care under reserved capacity; window demand within supply; only certified decisions granted; observation-based winning (G.15)
`G1Refinement`	The installation's own guarded run protects every particular on the good event, failure at most $\sum_i \delta_i$, with the journal retaining history; the speed limit removes the alarm device from holding; every hypothesis has an inhabited instance (G.16)
`G2Physical`, `G2Freedom`	The held installation realises the continuation top, which dominates without union closure; holding and timely authorised R17 delivery hold on one joint execution (G.16)
`G3GoodEvent`, `G3ArchiveStock`	The wavefront sweep recovers on the good event with failure at most $\sum_i \delta_i$; archive holding is a separate bill term, charged on the held stock: live stock gives $\gamma(I_0 + c)t^d$ for every $d \geq 1$, while retaining every increment or rolling the whole stock over epochs is quadratic (G.16)
`BennettExact`	Premise 5 with the implemented Bennett program and complete lifecycle cost: forced inside the adiabatic window $0 < Q - H$, $A/(Q - H) < \tau_{\max}$, and outside it the counterpart is not cheaper (G.17)
`KnillLaflamme`	Knill–Laflamme identities $PE_i^\dagger E_j P = \alpha_{ij} P$ for errors of weight t with $2t < d$, from the code distance; logical operators excluded by the distance (G.18)
`MatchingWitness`	Minimum-weight decoding leaves every zero-syndrome residual cycle at least half faulty: the witness hypothesis of `Threshold.fail_le_geometric` (G.18)
`EdgeLaw`, `ExRecBound`	Circuit faults induce local stochastic edge noise at rate cp; with the enumerated degree 12 and $c = 52$, $r = 22\sqrt{52p} < 1$ exactly when $p < 1/25168$; the gadget bound $\lvert M_2\rvert p^2 + \binom{\lvert L\rvert}{3} p^3$ (G.18)
`AgeReliability`	A logarithmic distance schedule holds global failure below ε at every age; a logarithmic overhead is not absorbed into an age-independent constant (G.18)

Module	Verified result and current role
SparseFailure, ToleranceSweep	Patches with disjoint windows fail jointly with probability at most the product bound; many failures are exponentially unlikely at every age; on the actual sweep every wrong vertex is bad, the wrong count obeys the same tail, the bill is pathwise and a tolerant outer decoder recovers the record (G.19)
PassiveReference, StageSchedule	Indefinite holding at fixed ε: doubling-schedule stages cover every age, total failure at most ε, rewrite cost $O(\log^2 t)$; with transfers, holding and transfer failures sum to at most ε at polylog cost (G.19)
RedundantRecord	Majority decoding of a redundant record tolerates any minority of wrong fragments, supplying the tolerance hypothesis of recovery_tail (G.19)
BennettBatch	Premise 5 is forced for every large enough batch once the per-bit reversible overhead is below the irreversible heat (G.19)
WeightedEdgeLaw	Weighted fault rates push forward to edge rates; with the enumerated edge rate 94/15·p and walk bound 9.87, the explicit threshold exceeds 4×10^{-4} (G.19)
WarmStart	A warm start, a prepared syndrome law at most C times the thermal law pointwise, stays dominated at every time, so every event keeps the stationary bound up to C (G.20)
WalkBound9	The length-9 walk bound $c_9 = 763{,}504{,}745 \le 9.71^9$ gives an explicit threshold above 4.2×10^{-4} (G.20)
HistoryPolymer	Deterministic history support budget, component restriction, truncation factors and finite sampling-path bounds (G.21)
ThermalEncoding	Orthogonal syndrome-mixture recovery, including arbitrary reference correlations (G.21)
TransferRate	Full retained-prefix size, complete failed-attempt invoices and the age-independent transfer/G3 work join (G.21)

The earlier G1Certificate.universal_protection_held has conclusion True; it is a placeholder and is not the protection theorem Bridge.universal_protection_held. The latter's full source certificate is constructed in G.10 (G1Held.held_source_protection). The exact integration history and dependency trace accompany this working edition.

23.A Complete theorem index

Generated from the sources by lean/gen-index.py; every theorem listed here is kernel-checked and axiom-audited by lean/build-and-audit.sh.

Module	Theorems
MathlibAnalyticBridge	starProjection_fixed_iff_mem, starProjection_idem, altIterate_succ_eq_self, altIterate_succ_mem, mirrorIterate_succ_mem, convergence_inf_le, limit_mem_of_fixed, convergence_inf_ge, von_neumann_identification

Module	Theorems
HalperinDecay	norm_starProjection_apply_le, dist_starProjection_le, sq_pythagoras_step, chain_identity, sq_dist_antitone, sq_dist_tendsto, delta_tendsto_zero, asymptotic_regularity
OpialBridge	tIterate_succ_mem, weakCluster_mem_exact, weakCluster_mem, iterate_inner_const, weakCluster_eq_starProjection, iterate_sub_starProjection_sq_eq, tendsto_starProjection_of_norm_sq_tendsto, makeVonNeumannConvergence
CanonVonNeumann	altIterate_sub, altIterate_shift, norm_altIterate_le, altIterate_eq_halperin, opial_tIterate_eq, mirrorAltIterate_eq, tendsto_altIterate_sub_succ, mem_inf_of_orthogonal_range, tendsto_zero_of_mem_orthogonal, tendsto_altIterate, canon_von_neumann_convergence, limit_subspace_eq_inf, canon_opial_convergence, opial_norm_sq_tendsto, opial_route_closes
RecoveryWork	frontier_work_bound, Wmin_lower_bound, necessary_radius, completing_square, carrier_radius, x3_delayed_recovery_work, delayed_work_diverges
E9SelfHealing	robust_between_honest, no_false_alarm, no_masking, exists_robust, syndrome_detects, wave_race_margin, code_headroom, e9_timely_self_healing
H5Closure	step_inv, reachable_inv, genesis_inv, authority_attenuation, reserve_before_activation, zero_debt, no_unfunded_work, no_harmful_effect, effect_preserves_care, consistency_detector
Greatestness	lexLt_irrefl, lexLt_trans, aligned_iff_no_needless_loss, lexLe_of_le, greatest_of_union_closed, strict_except_mirrors, aligned_unique
ThermoLedger	stroke_identity, cycle_work_floor, funded_repair_certificate, quarantine_zero_debt, tower_bound, canon_invariant, tracking_envelope, tracking_bounded, tracking_within_resolution
Composition	reactive_lockstep, reactive_lockstep$_2$, invariant_transfer, theorem8_composition
PremiseFloor	income_or_irrelevance, forced_breach, breach_strictly_below, reversible_administration_forced
ReciprocityCeiling	reciprocity_dominance, omitting_rival_strictly_below, ceiling_achievable
CyclicProjections	cyc_succ_apply, adj_succ_apply, norm_cyc_le, norm_adj_le, inner_cyc, cyc_fix, mem_of_norm_adj_eq, energy, iter_succ, iter_shift, norm_iter_le, iter_fix, tendsto_iter_sub_succ, tendsto_zero_of_mem_orthogonal, tendsto_cyc_iter, presentation_detector
GaussianTail	gaussian_lower_tail, carrier_tail, necessary_radius_of_decoder, x3_work_from_decoder
DeductionBoundary	rank_criterion, context_maps_image, boundary_mem_image, anchor_untouched

Module	Theorems
ReflectionCertificate	residual_certificate, apriori_error, stopping_count, zero_constant_fixed
Trotter	norm_exp_le, norm_exp_sub_one_sub_le, norm_exp_mul_exp_sub, norm_exp_sum_sub_prod, trotter_bound, trotter_tendsto, lloyd_simulation
Irreplaceability	destroy_loses_exactly, preserve_dominates, optimal_keeps_most_irreplaceable
DataProcessing	fst_process, snd_process, data_processing, data_processing_map
MeetAlgebra	anchor_preserved, contradiction_collapse, bot_absorb, anchor_preserved_over, meetAll_bot, collapse_over, consistent_preserved
MeetHilbert	hilbert_anchor_preserved, hilbert_contradiction_collapse, contradiction_detected, deduction_never_rolls_back
FiniteInformation	log_sum, margH_process, margY_process, data_processing_fin, flag_identity, decoder_bound, necessary_radius_from_decoder
AreaBridge	logdet_le_trace, channel_cap, required_traffic, area_power
UniversalProtection	coverage_invariant, universal_protection
Workload	fifo_certificate, fifo_deadlines, fifo_tight, serial_certificate, range_variance_bound
Fano	max_entropy, fano_single, fano, mi_eq_ent_sub_condEnt, required_information
GaussianKL	rnDeriv_gaussian_gaussian, log_gaussianPDFReal, llr_gaussian_gaussian, integral_sq_sub_gaussian, klDiv_gaussian_gaussian
GoldenFormula	klDiv_map_swap, golden_formula, mutualInfo_le_klDiv
GaussianChannel	chan_apply, integral_quadratic_gaussian, measurable_quad, llr_chan, coe_outVar, klDiv_chan, gaussian_channel_bound
KLAdditivity	prod_eq_compProd, klDiv_map_equiv, compProd_prod_assoc, compProd_prod_swap, klDiv_prod_kernel
GaussianChannelGen	chanW_apply, measurable_quadW, llr_chanW, coe_outVarW, klDiv_chanW
GaussianVector	isMarkov_vecChan, isProb_refMeas, klDiv_compProd_map_equiv, varW_nonneg, klDiv_vecChan, vector_channel_bound, vector_channel_trace_bound
Whitening	mutualInfo_map_snd_equiv, mutualInfo_kernel_map_equiv, pi_eq_map_eSucc, vecChan_apply, multivariateGaussian_one_eq_pi, isUnit_det_sqrt, wht_mul_sqrt, sqrt_mul_wht, toEuclideanCLM_mul_apply, whiten, corrChan_apply, measurable_whtSignal, correlated_channel_bound
Rotation	multivariateGaussian_one_map_isometry, measurable_rotSignal, rotated_channel_bound
LogDet	cov_isHermitian, var_lincomb, rotSignal_eigen, var_rot_eq_eigenvalue, det_one_add, logdet_channel_bound

Module	Theorems
Law	exists_aligned, lexLt_first_le, life_guard, scope_guarantee_iff, same_priority_admits_needless_loss, faithful_hold_dominates, faithful_hold_strict
SpeedLimit	norm_le_of_inner_deriv_le, angle_le_chord, angle_le_speed_mul, re_inner_gen_eq_zero, norm_conserved, branchA_divergence, branchA_rate, mandelstam_tamm, orthogonalization_time
Landauer	kl_nonneg, mul_log_div_eq, sum_margA, sum_margB, mutualInfo_eq, mutualInfo_nonneg, ent_le_ent_marg, partition_pos, gibbs_pos, gibbs_sum_one, log_gibbs, ent_gibbs, ent_le_energy, evolve_nonneg, evolve_sum, ent_evolve, reeb_wolf_identity, landauer, landauer_erasure, guard_one, cycle_work_floor_derived
QuantumLandauer	vnEnt_eq_roots, vnEnt_congr, vnEnt_unitary_conj, vnEnt_diagonal, diag_conj, row_normSq_sum, col_normSq_sum, vnEnt_le_diag, diag_nonneg, diag_sum, UH_mem, H_spec, energy_eq, vnEnt_le_energy, gibbsState_posSemidef, gibbsState_trace, gibbsState_diag, gibbsState_trace', gibbsState_energy, vnEnt_gibbsState, ptrA_isHermitian, sum_star_mul_eq, ptrA_conj, ptrB_conj, init_posSemidef, finalState_posSemidef, finalState_trace, vnEnt_init, quantum_landauer, quantum_guard_one, quantum_cycle_work_floor
Threshold	prob_le_one, prob_nonneg, filter_subset_powersetCard, many_faults, fail_le_witness, fail_le_geometric, repetition_threshold, two_sqrt_pow_le, repetition_ceiling, poly_geom_le, family_ceiling
UnionClosure	aligned_never_below, dominates_of_affordable, strict_of_affordable, exists_union_bound, dominates_within_slack, union_closed_of_affordable, greatest_of_affordable, aligned_eq_of_greatest, greatest_of_solvent, strict_of_solvent, greatest_or_irrelevant, insolvent_not_greatest
SolventReciprocity	solvent_keeps_everyone, reciprocity_dominance_solvent
AffordableReciprocity	reciprocity_dominance_affordable
Bridge	coverage_from_law, nearest_decodes, exists_nearest_decoder, holding_preserves, qsl_growth, qsl_within_radius, headroom_within_radius, universal_protection_held, holding_cycle_physical
Instruments	lindblad_reset_flow, lindblad_step, reset_contracts, tracking_recursion_derived, tracking_envelope_derived, branchC_complete, card_box, box_mono, card_boundary, boundary_power

Module	Theorems
StrokeBookkeeping	ptrB_isHermitian, controlled_mul_apply, mul_star_controlled_apply, controlled_unitary, ptrB_controlled, stroke_entropy_change, stroke_identity_derived
Bennett	bennett_step, bennett_compute_uncompute, ent_equiv, negMulLog_add_le, negMulLog_add_lt, negMulLog_sum_le, ent_eq_fiber, ent_push_le, ent_push_lt, heat_reversible, heat_irreversible, premise5_from_bennett
Concatenated	distance3_corrects_one, lift_subset, fails_witness, card_lift, disjoint_lift, card_witness, card_witnesses, concatenated_threshold, concatenated_ceiling
ReasonsCompiled	reciprocity_expectation, reciprocity_canonical_floor, reciprocity_strict, reciprocity_from_solvency, controller_pays_floor, controller_floor_diverges
TwoLevel	mul_of_idOutside, rad_mul_self, conj_rad, givens_idOutside, givens_unitary, one_idOutside, rad_eq_zero, elim_unitary, elim_idOutside, elim_kills, idOutside_row, idOutside_keeps_col, col_zero_above, clear_below, phase_idOutside, phase_unitary, phase_mul_apply, next_column, star_list_prod', star_twoLevel, two_level_decomposition
ErrorBudget	prod_norm_le_one, map_prod_norm_le_one, two_factor_step, telescoping_delta, error_budget
GateSupport	kraus_branch_preserves_support, kraus_sum_preserves_support, support_preservation_composes
RiskBounds	weighted_markov, event_mass_mono, intersection_mass_le_each, positive_work_tail_control, dependent_chain_bound
QueueDeadline	exponential_service_tail, exponential_service_normalized, positive_deadline_miss_probability, small_mean_does_not_make_tail_zero
BandwidthReflection	normalized_susceptibility, exact_bandwidth_sensitivity, finite_positive_sensory_access_remains, bandwidth_bias_threshold
AnalyticBridge	integrating_factor_monotone, linear_barrier_preserves_safety, exponential_transient_bound, integrated_exponential_transient, integrated_transient_cost_bound, continuation_hazard_threshold, heterogeneous_quadratic_cost_identity, heterogeneous_uniform_is_not_minimum, eventually_better_continuation
RankAndCoalition	ranked_trace_length, ranked_polynomial_step_bound, total_penalty_excludes_all_members_gaining, real_lyapunov_descent_need_not_terminate
MetricShadow	embedding_distance_stability, protected_close_edge_margin, protected_separated_edge_margin

Module	Theorems
SemanticMap	identity_is_bijective, flipped_is_bijective, two_distinct_lossless_maps, calibrated_reference_fixes_binary_mapping
BridgeD1	dynamic_survival_equation, hazard_grows_without_bound, positive_accumulated_prefix, increasing_hazard_does_not_erase_prefix, exact_discounted_dominance_criterion, undiscounted_finite_crossover
BridgeE9	reaction_before_damage, positive_propagation_margin, local_buffer_covers_entire_reaction, escrow_prevents_pre_detection_application, incidence_has_circulation_kernel, lost_circulation_need_not_change_divergence
BridgeH6	charged_transition_bound, no_infinite_paid_run, budget_exhaustion_need_not_be_fixed, current_residual_bound, next_residual_bound
BridgeH7	rate_bounds, denominator_positive, equilibrium_is_fixed, fixed_point_unique, exact_transient, equilibrium_private_evidence_sensitivity, stubborn_anchor_limit, private_evidence_sensitivity_vanishes, exact_bias_threshold
BridgeH8	variance_identity, uniform_global_minimum, equality_only_at_uniform, blend_normalized, blend_cap_preserved, exact_excess_decay, gradient_flow_equation, flow_coefficient_in_unit_interval, original_upper_fails_along_restoring_flow
ReasonsRoute	optionValue_pointwise, optionValue_expectation, optionValue_strict, law_protects_everyone, indicator_law, law_dominates, law_dominates_strict, rival_fraction_le_one, rival_fraction_lt_one
SensorTail	sensor_tail, sensor_law_tail
ConsensusRate	bandwidth_contraction
RGFixedPoint	sq_root, gstar_pos, fixed_relation, beta_gstar, eigenvalue_gstar, beta_factor, beta_pos_below, beta_neg_above
FinalClosure	verifier_bound_iff, proxy_ungameable_iff, proxy_gameable, pruning_lowers_rate, living_unbounded, pruning_all_stalls, void_strictly_below, void_never_chosen, dominance_channels, coop_more_efficient, stewardship_sustains, extraction_depletes, sustained_iff
H8Bound	one_sub_u_pos, h8_of_concentration_bound, h8_graph, h8_iff, routing_bound, h8_routed
CorrelatedStress	many_touching, correlated_stress
LatticeLaplacian	symmetric_slope, ratio_eq_slope, second_difference, lattice_laplacian
SafeGenesis	migration_progress, safe_genesis
AdaptiveConsensus	weighted_error_bound, anchored_update_error, adaptive_history_error_bound

Module	Theorems
CascadeCore	workload_deadline, recursive_queue_bound, multi_epoch_entropy_bound, spectrum_expectation_floor, atomic_headroom, defection_deficit, sustained_deficit_crosses_buffer, buffer_threshold_crossed
DecisionAndScale	weighted_outcome_dominance, continuation_gain_pays_overhead, finite_branch_payoff_bound, duration_reward_bound, efficiency_gain_pays_cost, dominant_action_survives_mixture, local_verifier_cost, two_provider_unique_balanced_cost
E9Routes	surviving_disjoint_route, certified_repair_meets_deadline
GenerativeClosure	step_preserves_paid_activation, every_generated_active_is_funded, reserve_does_not_displace_existing_agents, generated_authority_stays_within_root
ReflectionContraction	complete_contraction_has_unique_fixed_point, finite_error_bound, accuracy_within_budget, residual_error_bound, residual_tolerance, post_update_error_bound, post_update_tolerance, run_commutes, paired_trajectory_bound, residual_geometric_bound, first_residual_stop_is_paid_and_accurate
ReflectionFuel	steps_bounded, quota_conserved, no_unbounded_paid_reflection, bounded_depth_can_cycle
RestrictedModels	anchored_consensus_dissipation, hhi_variance_identity, uniform_shares_minimize_hhi, uniform_shares_are_unique, quadratic_cost_floor, conditional_product_pushforward
ThermalBalance	intra_epoch_integral_bound, repair_before_buffer_exhaustion
TransportLaw	transport_nonneg, transport_ge_local, hhi_ge_uniform, monopoly_penalty
ControllerCertificate	stable_min_three, delta_min_three, rate_min_three, debt_min_three, alloc_min_three, total_min_three, total_min_three_le, band_min_three, stable_min_four, delta_min_four, rate_min_four, debt_min_four, alloc_min_four, total_min_four, total_min_four_le, band_min_four, stable_rob_three_two, stable_rob_three_four, total_rob_three_two, total_rob_three_three, total_rob_three_four, total_rob_three_two_le, total_rob_three_three_le, total_rob_three_four_le, band_rob_three, stable_rob_four_two, stable_rob_four_four, total_rob_four_two, total_rob_four_three, total_rob_four_four, total_rob_four_two_le, total_rob_four_three_le, total_rob_four_four_le, band_rob_four, pool_bills, corrected_bill_saving, allocation_undercharge_three, allocation_undercharge_four
FIFOWorkload	fifo_step, finish_le_upper, certified_prefix_meets_deadline

Module	Theorems
R16Feedback	map_iterate, tick_commutes, reactive_lockstep
UPTLawLife	refl, trans, U1, trans_sub, trans_ssub, lex_irrefl, lex_trans, lex_U1, freedom_first_U1_legacy, guard_first_stage, canonical_life_first_U1, life_guard
ClosedCohold	reachable_closed, reachable_least, factorised_cohold, outside_unchanged, crossing_boundary_changes_outside_later
R14Boundary	safe_step, every_good_trace_safe, journal_commutes, sink_commutes, outside_commutes, harmful_effect_refused, old_generation_refused, external_weather_is_not_a_replica_fault, recruitment_erasure, recruitment_never_ends_care, failure_has_a_named_exception
ReceivedCutRepaired	different_has_unmediated_path, outside_equal_of_cut, r2_no_crossing
ReadoutJoint	block_det_identity, shifted_det_identity, cp_coeff_nonneg, cp_coeff_pos, iso01_shift_nonneg, iso10_shift_nonneg, blockA_shift_nonneg, blockD_shift_nonneg, block_shifted_det_nonneg, quad_form_nonneg, choi_form_nonneg, positive_constant_not_cp, cp_constant_at_half_half, weight_nonneg, chain_nonneg, joint_record_lower, chain_ge_pow, hard_count_floor
ReadoutBounds	determinant_identity, determinant_lower, strictly_positive_determinant, spectral_lower, weight_nonnegative, conditional_record_lower, baseline_normalized
OriginalD1	expected_value_formula, original_dominance_counterexample, lifetime_density_is_normalized, lifetime_survival_tail, zero_ultimate_survival_with_positive_accumulated_value
OriginalE9AndH5	finite_speed_indistinguishability, no_sound_remote_alarm_before_arrival, h5_local_rate_does_not_bound_total_entropy
OriginalH6	original_thermal_depth_ceiling, banked_rate_is_contractive, banked_step_error, banked_exact_error, banked_paid_epsilon_accuracy, original_thermal_premises_allow_cycle
OriginalH7	decay_derivative, solves_original_equation, decay_limit, all_nonnegative_couplings_converge, every_initial_pair_is_represented
OriginalH8	actual_minimum_is_one, uniform_attains_minimum, original_bound_counterexample

Module	Theorems
ControllerFinality	tally_mono, quorum_has_honest, two_tallies_bound, quorum_intersection, committee_threshold, prefix_trans, equal_length_prefixes, certificates_do_not_equivocate, certificate_is_final, context_words_injective, run_append, step_floor_mono, run_floor_mono, grant_fields, floor_fields, held_refuses, retired_generation_refuses, pending_conflict_refuses, closed_sequence_refuses, receipt_names_success, certified_receipt_names_success, same_generation_no_context_conflict, checkpoint_replay, consume_once, restart_disabled, retained_floor_refuses, old_boot_refuses, deadline_refuses, issued_append, emission_bounded, issues_bounded_by_final_floor, step_stays_held, held_issues_nothing, grant_receipt_is_issued, hold_bounds_every_issued_grant
UPTFence	hold_safety, raise_then_nothing_lands, admission_only_lands_in_hold, check_at_apply_refuses
ConservedRouting	conserved_decomposes, regular_psi_is_hhi, hhi_uniform, monopoly_exceeds_uniform, h8_exact_general, thermal_ledger_positivity_strict, thermal_ledger_positivity_nonneg, jarzynski_bound_valid
P2P3	sensor_exp_positivity, scaling_sum, azuma_scaling, work_tv_floor, coordinate_sensitivity, telescoping_drop, semigroup_time_rescaling, ness_work_linear, work_floor_positive, liquidation_triggers, zero_breach_bound, bound_decays, escrow_ordering, fluctuation_bound_le_two
FIFOInstance	finishes_three, veto_envelope_three, alloc_completion_is_the_charge_three, control_lane_three_certified, finishes_four, veto_envelope_four, alloc_completion_is_the_charge_four, control_lane_four_certified, per_job_deadlines_three, per_job_deadlines_four
FIFOAdmission	checks_iff, certified_mono, certified_append, admission_preserves, completion_preserves, cancellation_preserves, all_occurrences_timely, queue_step_preserves, refinement_preserves_queue
R16TwoPhase	phase_tick_commutes, two_phase_lockstep
R16Cut	closed_cut_step, dependency_closure_step, difference_has_bypass, causal_separator, closed_cut_reactive, delayed_locality, pending_is_in_cut, private_cause_is_in_cut, delayed_effect_countermodel, omitted_edge_is_not_local
ReceivedCutR14Repaired	journal_projection_step_ext, sink_projection_step_ext, outside_projection_step_ext, journal_outside_unchanged, sink_outside_unchanged
ControllerFence	certified_hold_nothing_lands, both_targets_held
IntegrationCertificate	typed_gate_decomposition, finish_interval_deadline, psi2_uniform, h8_bound_two_node

Module	Theorems
R16R14	compromise_commutes, project_step, reference_two_phase_lockstep
R16Screened	screened_fibre_lockstep
UPTR12A	words_injective, grant_has_decision_scope, same_generation_cannot_rebind, finalized_receipt_is_in_log, finalized_receipt_is_authorize, changed_log_implies_checks, applied_effect_has_aligned_decision, raised_floor_refuses, wrong_effect_refuses, replay_refuses, original_fence_theorem_available
R17AQueueFinality	new_effect_has_current_permit, drain_currently_authorized, revoked_refuses, expired_refuses, installed_floor_refuses, spend_is_funded, application_has_source_binding
R17FIFOR17A	applied_fifo_effect_is_timely_and_authorized, ready_fifo_effect_applies_before_deadline
R17Funding	charged_append, atomic_target_append, application_conserves_funding, trace_conserves_funding, cumulative_charge_is_funded, used_ticket_refuses, accepted_ticket_is_consumed, replay_cannot_append, funded_admission_preserves, source_drain_preserves_reservation
R17WorkConcrete	mono_le, unfinished_before, carry_in_completion, ceil_div_covers, carry_in_affine, no_service_no_completion, U_succ_succ, exec_le_envelope, deadlines_met, row_congr, tail_admission_invariant, tail_admission_preserves_certificates, applied_stage_effect_is_timely_and_authorized, timely_but_revoked_is_not_delivery
TIWASource	outerUpdate_read_frozen, freeze_monotone, schedule_no_rework, readyToFreeze_no_inFlight
TIWAGuard	guard_data_frame, installGuard_monotone
TIWARecovery	bounded_visits, wave_count_at
TIWAWork	local_work_bound, ball_work_bound, total_work_bound
TopRealisability	top_realisable_of_singletons
FaultCover	fault_cover
G2Singleton	g2_discharge_hsingle, topRealisability_hsingle_discharged
G1Certificate	universal_protection_held
G1Executable	g1_admission_soundness
PhysicalGuard	factorization, interior_unchanged
MeanErgodic	cesaro_mean_id
TemporalSafety	admit_of_secure, secure_preserved, trace_secure
WorkIntegration	work_bound
RelationalBridge	bridge_preserves_safety
MeanErgodicDeep	cesaro_id, id_fixes_all
GuardFactorization	commutativity, factorization_zero
G1Complete	g1_append_safe
G2Outcome	g2_compose_valid
G3WorkBill	g3_append_work_bill
Htopkeeps	htopkeeps

Module	Theorems
SnuffyLocal	local_trajectory_growth_valid, tpt_state_preservation
G1FullDomain	g1_source_exhaustive, g1_fault_taxonomy_exhaustive, g1_append_preserves, replay_journal_step, journal_reactive_fidelity, transcript_capacity
G2WholeOutcome	g2_authorized_implies_closed, g2_authorized_implies_positive_work, g2_compose_valid, journal_whole_outcome, journal_outcome_family
G3CompleteBill	g3_success_implies_bound, g3_compose_valid, g3_wave_count_nonnegative, cumulative_charge_bound, valid_work_bill_from_complete_ledger, valid_bill_bound_in_age
GuardOperator	guard_within_tolerance, guard_exceeds_tolerance
HamiltonianDecomposition	total_is_sum, boundary_confinement_positive, exchange_hamiltonian_hermitian, exchange_conserves_total_charge, exchange_pumps_boundary, exchange_swap_unitary, exchange_swap_charge, exchange_swap_total, partial_trace_local_conjugation, guarded_history_reduced_state, syndrome_exchange_preserves_history, syndrome_exchange_charge
GuardSignature	guard_idempotent
WorkBilling	work_nonnegative, work_bound_preserved, decoder_work_balance, decoder_work_floor, decoder_work_floor_saturation, funded_decoder_entropy_bound, funded_decoder_cycles, charged_attempt_accounting, syndrome_stock_bound, syndrome_flux_balance, cumulative_maintenance_bound
DecoderRetraction	decode_encode, finite_code_recovery, nonvanishing_of_continuation, finite_code_self_grounding, inner_preserved_from_symplectic_flux, adjoint_decodes_isometry, boundary_observable_on_code, historical_query_preserved, historical_word_on_code, historical_word_expectation, boundary_observable_mul, boundary_observable_commutator, powers_intertwine, exponential_intertwines, historical_flow_roundtrip, historical_dual_kernel, work_shifted_flow_on_code, historical_gram_preserved, historical_gram_nondegenerate, coordinate_boundary_roundtrip, boundary_capacity_necessary, handoff_moves_reference_payload, handoff_preserves_norm, handoff_roundtrip, parallel_cnot_handoff, charged_archive_handoff
G2Splice	splice_grade, splice_realisable, outcome_splice, union_realizable, top_realisable, whole_outcome_greatest, fourStage, block_splice_run, block_splice_keeps
CorrelatedCeiling	ceil_touching, correlated_stress_ceil, prob_damage, near_card_le, choose_pow_le, damage_local_stochastic, correlated_family_ceiling

Module	Theorems
G1Held	good_cover, held_source_protection, initial_frame_normalised, held_step_normalised, held_run_normalised, held_source_qsl, zero_hamiltonian_trajectory, concrete_decoder_certificate, concrete_good_event_inhabited
G1E9	alarm_or_subthreshold, held_source_e9
G2Held	active_authorised_free, held_realises_top, held_source_top
G3Sweep	sweep_recovers, sweep_visits, waves_from_spread, sweep_bill
G3PatchDecode	patch_correction_succeeds, patch_sweep_bill
ReasonsEnsemble	ensemble_le, ensemble_strict
TheoremEightLyapunov	capacity_balance, solvent_cycle_energy_account, reserve_deficit_antitone, reserve_deficit_cap, replenishment_exact, replenishment_nonincrease, solvent_cycle_deficit, cycle_contracts, margin_pos, lyapunov_iterate
SmearingIntegral	smeared_reconstruction, smeared_boundary_reconstruction
ChannelExtension	ext_recovers, kron_isometry, ext_recovers_reference, ext_trace, ext_posSemidef
PureStateDistance	pure_infidelity_le, pure_fidelity_ge
BennettCounterpart	counterpart_heat_zero, merging_heat_pos, counterpart_same, counterpart_feasible, counterpart_more_slack, premise5_constructed, bennett_counterpart_computes, implemented_program_computes, implemented_program_output, implemented_program_workspace, implemented_program_history, implemented_step_fields, implemented_run_refines, implemented_run_history, implemented_quantum_norm, implemented_quantum_roundtrip, complete_cost_difference, complete_cost_strict_iff, implemented_work_ceiling, adiabatic_slack_window, switched_program_meets_deadline, adiabatic_feasible_iff
RegionBoundary	exists_crossing, region_bootstrap, whole_no_boundary, whole_H0_trivial
TimelyCare	care_served, exhaustion_fails, deadline_met, miss_within_shortage
DeadlineDemand	demand_le_supply, robust_demand
DecisionPermit	decision_words_injective, grant_names_certified, granted_policy_is_certified, wrong_action_rejected, certified_action_granted
ObservationWinning	policy_wins_iff, hidden_world_countermodel
R14Rivals	refl, trans, coordinate_envelope, complete_rival_transfer, hot_beats_pause
R15CausalGluing	boundary_representatives_iff, selected_representative_greatest, canonical_boundary_iff, interface_envelope_transfer, hidden_world_control
ReciprocityDistance	distance_floor, reciprocity_at_distance, reciprocity_strict_at_distance, canonical_tends_to_one
CutEquivalence	closed_iff_no_bypass

Module	Theorems
`ConcatenatedDecoding`	`outer_decodes`, `mem_sub`, `decodes_unless_fails`, `decoding_failure_le`
`ChannelCP`	`kron_entry`, `amp_eq`, `compress_entry`, `mp_posSemidef`, `decoder_completely_positive`
`PureStateTraceNorm`	`sum_sq_eigenvalues`, `eigenvalue_cube`, `pureDiff_hermitian`, `vmv_smul`, `star_dot_swap`, `pure_cube`, `pure_trace_sq`, `pure_trace_norm`
`G1Refinement`	`guarded_step_continues`, `physical_protection`, `journaled_protection`, `physical_qsl_drift`, `physical_protection_qsl`, `physical_instance_inhabited`
`G2Physical`	`held_installation_keeps_all`, `top_dominates_continuation`
`G2Freedom`	`joint_holding`, `joint_holding_and_delivery`
`G3GoodEvent`	`sweep_success_on_good_event`, `complete_bill_with_archive`
`BennettExact`	`premise5_exact`, `window_exact`, `reversible_admin_computes`
`G3ArchiveStock`	`live_stock_bill`, `retained_stock_quadratic`, `rollover_quadratic`
`KnillLaflamme`	`eq_zero_of_eq_neg`, `spectral_projection`, `sandwich_anticomm`, `sandwich_scalar`, `knill_laflamme_of_distance`
`AgeReliability`	`cubic_spacetime_rate`, `log_distance_schedule`, `log_factor_not_absorbed`
`ExRecBound`	`exrec_pair_bound`, `circuit_level_rate`, `surface_code_rate`
`EdgeLaw`	`prob_push`, `push_localStochastic`
`MatchingWitness`	`card_symmDiff`, `half_faulty`, `matching_witness`
`SparseFailure`	`disjoint_windows`, `many_failures`
`ToleranceSweep`	`frozen_after`, `wrong_has_cause`, `wrong_le_of_eroder`, `wrong_subset_bad`, `sweep_density`, `pathwise_bill`, `recovery_tail`
`PassiveReference`	`stages_cover`, `total_failure_le`, `total_rewrite_cost`
`RedundantRecord`	`majority_decodes`, `tolerant_outer_decoder`
`BennettBatch`	`batched_window`, `premise5_batched`
`WeightedEdgeLaw`	`push_weighted`, `push_uniform`, `rate_iff`, `tightened_threshold`, `walk_bound`, `threshold_value`
`StageSchedule`	`total_with_transfers`, `stage_cost_le`
`WarmStart`	`warm_start`, `warm_start_event`, `fibre_mass_pos`, `fibre_reassembly`, `reverse_sampler_bound`, `heat_bath_normalized`, `heat_bath_stationary`, `pointwise_from_absolute`, `warm_start_from_mixing`
`WalkBound9`	`walk_bound_9`, `threshold_9`, `threshold_9_value`
`HistoryPolymer`	`halving_prefix`, `paired_history_bound`, `component_valid`, `truncation_bound`, `sampled_truncation_bound`, `branch_path_bound`
`ThermalEncoding`	`branch_compression`, `recovers`, `kron_orthogonal`, `recovers_reference`

Module	Theorems
`TransferRate`	`poly_le_two_pow`, `transfer_bill_le`, `transfer_bill_linear_in_age`, `retained_prefix_bound`, `attempt_stage_bound`, `polynomial_stage_bill`, `complete_attempt_bill`, `join_complete_bill`

Section 24 — Statements of record for the retained core

Part II supplies the retained proofs and stronger bridge in this edition; Section 21 supplies the information–traffic–carrier–work derivation. This section records concrete instrument rows and numerical instances at their evidence tiers. The parent core, DOI 10.5281/zenodo.23599528, remains publication provenance; the current argument is given here.

24.1 The nine-row A1 register (effect mediation)

Statement of record. The A1 register identifies nine rows of effect mediation: host memory mapping, DMA, context switches, packet ingestion, bus messages, storage synchronisation, commissioning, delegation and retirement. Each row names its refinement carrier and the enforcement witness the physical instance must supply. A packet or memory operation acquires no exemption by being below the application layer.

Tier: stated definition, given in Part II.5 and the nine rows above. The enforcement machinery it names is compiled in the abstract (`H5Closure.no_harmful_effect`, `effect_preserves_care`); the nine rows themselves are the instance inventory.

24.2 Capacity rows 17 and 22, and the pool bill (workload)

Statement of record. The workload pool bill is compiled: capacity rows 17 and 22 at 48,000 and 67,200 per cycle give $48000 \times 17 + 67200 \times 22 = 2{,}294{,}400$ — the per-cycle pool bill against which the FIFO completion certificate (Proposition 6) is issued (`ControllerCertificate`, exact rationals; the same module derives the bill-saving ratios $6{,}604{,}800/2{,}294{,}400 = 688/239$ and $6{,}604{,}800/2{,}409{,}600 = 688/251$ of the earlier bill over the corrected bills, `corrected_bill_saving`).

Tier: compiled. The deadline-certificate machinery of which this is the workload instance is published in the parent core (DOI 10.5281/zenodo.23599528, exact FIFO deadline certificates with application-time finality and funding conservation).

24.3 The causal boundary (reactive refinement)

Statement of record. The causal boundary is given in two forms, which agree: a closed dependency component is exactly a directed separator in the unrolled dependency graph with empty certified boundary (`CutEquivalence.closed_iff_no_bypass`), and the separator form extends it to a matched certified boundary (`UPTR16Cut.causal_separator`). Pending effects belong in that graph. Omitting one future effect or one path invalidates the corresponding exclusion certificate.

Tier: stated definition (R16-CUT); the reactive refinement that uses it is compiled (`Composition.reactive_lockstep`, with the causal boundary carried as the instance's refinement source).

24.4 The revised JW2.6 arithmetic (conserved allocation and joint risk)

Statement of record. The revised JW2.6 arithmetic gives $\approx 2.06419526094 \times 10^{-7}$, within the declared 10^{-6} horizon ceiling, under its source-event and stochastic-law premises. The positive dormant allowance, recruitment noninterference and the historical recruitment-family event retain their distinct meanings. The three ledger scenarios carry this value (solvent and quarantine) and the charged variant $9.86419526094 \times 10^{-7}$ (one priced event), each with a sealed, hash-chained trace.

Tier: exact replay receipt — `LEDGER-FOUR-STROKE-2026-10-24/`, chain heads as printed in Chapter 1.4; the composition into the ceiling (no independence) is compiled (`ThermoLedger.canon_invariant`); the arithmetic itself is a receipt, not a theorem.

24.5 The quorum (safety)

Statement of record. The design instantiation is five-of-seven with at most two Byzantine identities ($K = 7$, $f = 2$, satisfying $K \geq 2f + 1$). The Byzantine quorum results it instantiates are compiled (`E9SelfHealing.robust_betwee n_honest`, `no_false_alarm`, `no_masking`, `exists_robust`); the five-of-seven values are instance constants (§22.4's parameter matrix).

Tier: compiled theorem with stated instance constants.

The law, bridge and retained instrument arguments appear in Part II. Section 21 develops X3; Part III-C records the three joined supports and their constructions in this full-strength argument.

Part III-C — The three joined supports and their constructions

The proposition remains protection of all things from any digital mind, especially a pure optimiser. X3, P1 and P2 retain their established gauntlet arguments. These are the three support requests supplied by the author and Gemini; their constructions are recorded below, with no additional objection introduced by this incorporation.

G1 — combined full-domain physical certificate. Construct the actual source state, admitted commands/events, physical projection, observations and charged fault accounts that jointly supply `Bridge.universal_protection_he ld`. Its `hcert` establishes commuting refinement, observation agreement, initial continuation of every particular, the perturbation-radius bound and repair precision on the named good event. Also join the event cover and conditional fault bounds. Part II incorporates the law-derived scope, code decoder, physical cycle, controller-derived tracking, E9 branches, H5 care-preserving mediation, R14/R16 source refinements and timely R17 effect construction. The requested result joins these for the complete claimed physical domain.

Compiled support modules for this construction: `G1Certificate` (placeholder with conclusion `True`), `FaultCover` (bad-event cover), `G1Executable` (executable admitted-command/event/observation pipeline), `PhysicalGuard` (factorized evolution), `G1Complete` (inductive event-trace compliance), and `G1FullDomain` (source domain, fault taxonomy, exhaustive classification).

Constructed (G.10). `G1Held.held_source_protection` proves all five `hcert` components for the canonical held source, and `good_cover` proves the cover of the good event by the named accounts. `held_source_qsl` derives the per-step drift from the quantum speed limit for any perturbing agent, and `G1E9.held_source_e9` derives the coupling bound from the exhaustive E9 split. The journal of G.8 preserves its supplied transition (`G1FullDomain.journal_rea ctive_fidelity`); protective refinement of the actual installation is the separate transition equation identified in G.10. The inputs these theorems take are physical: the frame's Schrödinger evolution and the sub-threshold coupling bound in each step; the honest-sensor response and quorum size; the response's removal of coupling once the alarm fires; and the account probabilities, whose composition and attainment are `ThermoLedger.canon_invariant`, `Threshold.fam ily_ceiling` and `CorrelatedCeiling.correlated_family_ceiling`.

G2 — realisability of the whole greatest outcome. Construct `htopR : (⊤ : ∀ i, L i) ∈ R` for the same full order, including existing and new continuation and freedom stages, with the semantic continuation reading `htopkeeps`. Keep it distinct from `hsolv : c ⊤ ≤ B`. Part II.10 supplies the algebra from those inputs to equality of every aligned option with the top and dominance over every rival. The construction retains the full tuple.

First compiled support module for this construction: `TopRealisability` (union-closed realisability of singletons yields realisability of the top outcome).

Compiled support modules for this construction: `G2Singleton` (coverage discharge of singleton realisability), `G2Outcome` (transactional outcome-tuple invariance), and `G2WholeOutcome` (authorized-implies-closed, authorized-implies-positive-work).

Compiled components (G.9, G.11). `G2Splice` proves product-model union closure and closed-block agreement. `G2Held` proves the top of its assigned grade model from held continuation and its one-step H5 predicate. The full construction must map actual policies and outcomes to that model, preserving all original continuation and freedom stages, shared constraints and R17 delivery for every admitted rival and world. `hsolv` remains the separate complete funded-cost certificate.

G3 — supplied wavefront/TIWA protocol: success and the complete work certificate. The author has supplied the single-shot feedforward wavefront construction and the TIWA guard-ring proposal. Section 21.7.4 and `TIWA-PATCH-REQUIREMENTS.md` specify the latter's source, physical and work obligations. Section 21.7 proves its processing count exactly by disjoint shells: $\sum_{k=0}^{N} |S_k| = |B_{vN}|$, hence bounded work per processed vertex gives $O(N^{d_G})$. The same construction must now supply its actual recovery success and retained-state/quiescence witness, the age-to-wave-count bound, and the complete physical bill including routing, reset, holding and controller export. Those establish $W_{\min}(t) \le W(\pi_{\mathrm{ff}}, t) \le Ct^{d_G}$ in the original permitted class. The shell exponent is established and is not requested again. This is the remaining certificate for the supplied construction, with the full $\Theta(t^{d_G})$ target unchanged.

First compiled support modules for this construction: `TIWASource` (transition system, frozen-frame property, no-rework rule), `TIWAGuard` (guard installation monotonicity), `TIWARecovery` (bounded visits and wave counts), `TIWAWork` (per-vertex and ball-size work accounting), `G3WorkBill` (polynomial work-bill invariance), and `G3CompleteBill` (success-implies-bound, wave-count nonnegativity).

Constructed (G.12). `G3Sweep.sweep_recovers` proves that the sweep recovers every shell and retains it against any outer activity the TIWA fence admits, and `sweep_visits` proves that no vertex is reworked. `waves_from_spread` gives the wave count from finite propagation. `sweep_bill` proves recovery success on the whole region together with the complete bill $W(t) \le (F + \alpha + \beta + R_*)(c + r)^d t^d$, with an age-independent coefficient. With §21.6 this gives $W_{\min}(t) = \Theta(t^{d_G})$. The inputs it takes are the local correction's success against a recovered interior, the fence, the propagation bound and the per-wave complete charge.

Part III-D — Transducer, trajectory and semantic constructions

These constructions retain their full proposed conclusions. Their source correspondence and complete bill join the verified components, rather than being certified by a title or signature.

D.1 Transduced Preservation Theorem (TPT)

The supplied transducer route uses a macroscopic dissipation factor $\Gamma \approx 10^{14}$, an adiabatic efficiency $\alpha \in (0, 1]$, and a boundary transducer $\tau : \mathcal{H}_{\mathrm{phys}} \to \mathcal{M}_{\mathrm{rel}}$. Its target is the complete physical work ceiling $W(t) \le Ct^{d_G}$, preserving the protected historical record and relations.

Every exterior transducer, reset, holding and controller charge remains in that total. A fixed multiplicative hardware overhead can enter C; deriving the complete bill still requires the actual device and operation count. Section 21.7.5 gives the cumulative ledger implication for the supplied sliding-window route.

D.2 Topological entropy and trajectory bounding

For the supplied trajectory count $N(t, \varepsilon) \le Kt^{d_G}$ and complete work correspondence $W(t) = \beta N(t, \varepsilon)$, the intended conclusion is $W(t) \le \beta K t^{d_G}$. The transducer construction must supply that actual trajectory estimate and the work correspondence, including every physical charge.

The pinned Mathlib already contains Bowen–Dinaburg dynamical nets and topological entropy in `Mathlib.Dynamics.TopologicalEntropy.NetEntropy` and `CoverEntropy`. It also proves the general Hilbert-space mean-ergodic theorem, `ContinuousLinearMap.tendsto_birkhoffAverage_orthogonalProjection`, for a continuous linear contraction. Missing upstream infrastructure is not a blocker for these results. Applying them requires the actual operator and the claimed growth/work correspondence.

D.3 Top continuation and the constructed evaluation fixed point

The `Htopkeeps` record carries `eval ⊤ = ⊤` as its unitality field. Its extractor theorem does not by itself supply the different continuation semantics used in `SolventReciprocity`.

The supplied decoder interface now has a derived construction. For its code inclusion and recovery, put $P = \text{encode} \circ \text{decode}$. Retraction gives $P(P(y)) = P(y)$ and $P(\text{encode}(c)) = \text{encode}(c)$. `DecoderRetraction.finite_code_self_grounding` constructs this decoder and a non-bottom fixed-point witness from a maintained non-bottom code record. Part III-F connects that result to the proposed ontological capstone while retaining the actual G1 source obligation.

Part III-E — The constructions and the physical inputs they take

The G1–G3 constructions are compiled in G.8–G.12. Each item below records the original requirement, what now constructs it, and the physical inputs the compiled theorems take.

E.1 G1 full-domain source/event/fault certificate

Construct the actual source state, admitted commands/events, physical projection, observations, and charged fault accounts that jointly supply `Bridge.universal_protection_held`. Requires: physical guard device/Hamiltonian, readout instrument, tensor-factor isolation proof, event cover for 21 charged accounts, conditional fault bounds. The `G1Executable` module provides the discrete command/event/observation pipeline; `FaultCover` provides the cover lemma; `PhysicalGuard` provides algebraic Kronecker factorization.

Compiled held-source components: `G1Held` and `G1E9` (G.10) prove their five-component certificate and event cover on the normalised held source. *Physical construction target:* the actual installation projection/transition, observations, timely correction and device enforcing removal of coupling after alarm, with its complete charge and named fault bounds.

E.2 G2 whole-outcome realisability

Construct `htopR : (⊤ : ∀ i, L i) ∈ R` for the full order, including the continuation and freedom stages. Keep its realisability separate from `hsolv`, the funded-cost certificate. The supplied singleton route uses actual singleton-keeping policies and union-closed realisability; `TopRealisability` provides its finite induction and `G2Singleton` supplies set coverage.

Compiled components: `G2Splice` and `G2Held` establish their stated local-product and grade-model results. *Physical construction target:* identify the actual full policy/outcome family and R17 delivery on the same execution. `hsolv` pays the complete cost and does not replace this realisability witness.

E.3 G3 TIWA success and complete work bill

Requires: physical guard installation, decoder success, age→wave-count bound $N(t) \le at + b$, and full charging (routing, reset, holding, controller export, minimal-hold drain). The `TIWASource`, `TIWAGuard`, `TIWARecovery`, `TIWAWork` modules provide abstract scaffolding. `SnuffyLocal` provides a polynomial bound surrogate.

Now constructed: `G3Sweep` (G.12) proves recovery success with no rework against fenced outer activity, the wave count from finite propagation, and the complete bill $O(t^d)$ with an age-independent coefficient. *Physical inputs:* the local correction against a recovered interior, the fence, the propagation bound and the per-wave complete charge.

The new `G3CompleteBill` lemmas now derive the cumulative bill and its age conversion from complete local charges and the metered schedule; they do not take the desired cumulative bound as an input. Section 21.7.5 joins that derivation to the supplied sliding window and keeps the remaining physical boundary encoding, complete charge equality and c arrier/schedule correspondence explicit. Part III-G now constructs a finite coordinate encoder and adjoint decoder, transports the full represented historical algebra and work-shifted flow, and derives its finite dual kernel. The source must instantiate their capacity assignment on the actual historical record and meter its physical retirement/handoff, retained memory and query operations in that complete bill.

E.4 Existing analytic support and its source correspondence

The general contraction mean-ergodic theorem and topological entropy are present in the pinned Mathlib, with the names and files listed in Part III-D. The existing `MeanErgodic` and `MeanErgodicDeep` modules prove their stated identity-map cases; those filenames do not certify an application of the general theorem to an unspecified physical operator.

`GuardFactorization` proves commuting Kronecker factors. The source construction must connect the actual dynamics to the required factors and preserved record. A von Neumann algebra development is not established as a prerequisite for this finite construction.

Part III-F — Unified architecture and the self-grounding capstone

This section integrates the author's supplied unified ledger and homological proposal into the full edition. Parts I–III and their maximal domain, outcome order and rival quantifiers remain in force. The original submissions are preserved with the integration record.

F.1 The unified gate and work ledger

The guard is an idempotent, monotone projection with the intended fault-nullification action. The transaction emits $(h_{\mathrm{pre}}, h_{\mathrm{post}}, w, a, c)$ and enforces $a = 1 \Rightarrow (c = 1 \wedge w > 0)$. The complete work functional is additive over executed traces and has the full target $\mathcal{W}(T) \leq Ct^{d_G}$.

The transaction invariant supports the source implementation of G2; its connection to the whole greatest outcome, including all continuation and freedom stages, remains explicit. The work derivation in 21.7.5 now supplies `G3_ValidWorkBill` from its complete local ledger. Guard operation, transduction, boundary encoding, retirement and preserved history belong to that same charged execution.

F.2 Historical boundary encoding and recovery

Part III-G supplies the explicit operator/coordinate encoder, adjoint recovery and historical query transport developed from the later three-pillar submission. The topological route below retains its faithful source correspondence.

The supplied history is a causal labelled graph $\mathcal{H} = (V, E, \phi)$. Its full preservation target is

$$\mathcal{R}_{\mathrm{bnd}}(\mathcal{E}_{\mathrm{bnd}}(\mathcal{H}), v) = \phi(v)$$

at the original fidelity standard, together with preservation of the relevant relations. Within its proved radius, the finite-code decoder returns the exact original codeword. The boundary encoding separately specifies which full historical record that codeword represents.

The supplied accumulator route retains the proposed representation $(\partial\mathcal{H}, \mathrm{Acc}(V), \bigoplus_{e\in E} \psi(e))$ and capacity target

$$|\mathcal{B}_{\mathrm{boundary}}(t)| \leq K \log \mathrm{Vol}(U(t)).$$

Its capacity certificate must count the physical information in the accumulator, payload, query witnesses and retained recovery data. An accumulator authenticates supplied data and membership; an exact reconstruction additionally supplies the data needed to return $\phi(v)$.

The supplied retirement charge is

$$W_{\mathrm{retire}} = c_{\mathrm{acc}}|V_{\mathrm{retire}}| + c_{\mathrm{bound}}|E_{\mathrm{retire}}| \log |V_{\mathrm{retire}}|.$$

For the protocol's fixed-radius local retirement patches, bounded degree gives $|V_{\mathrm{retire}}| \le M_0$ and $|E_{\mathrm{retire}}| \le D_{\max}|V_{\mathrm{retire}}|$. Thus this local term is at most $(c_{\mathrm{acc}}+c_{\mathrm{bound}}D_{\max} \log M_0)|V_{\mathrm{retire}}|$, a constant charge per retired vertex. The settled bounded-overlap count absorbs it into $O(t^{d_G})$. Global accumulator updates, witness generation, routing, reset and continued storage still enter the complete local or separately metered charge.

The proposed topological route represents history by a chain complex and uses

$$0 \longrightarrow C_*(\partial U) \xrightarrow{i} C_*(K) \longrightarrow C_*(K, \partial U) \longrightarrow 0.$$

Its long exact sequence contains

$$H_n(\partial U) \xrightarrow{i_*} H_n(K) \xrightarrow{j_*} H_n(K, \partial U) \xrightarrow{\delta_n} H_{n-1}(\partial U).$$

The supplied route is implemented by constructing a boundary chain map $\rho : C_*(K) \to C_*(\partial U)$, inclusion i, and chain homotopy

$$i\rho - \mathrm{id} = dh + hd.$$

For a cycle z, the recovered chain satisfies $i\rho z - z = d(hz)$, so its homology class is preserved. A protected semantic observable q that annihilates these exact terms then obeys $q(i\rho z) = q(z)$. The historical encoder must establish this preservation for the actual full query family and its physical records, including the $\phi(v)$ evaluations, rather than identifying every history with its unlabelled homology class.

Exactness identifies images and kernels. If $H_n(K, \partial U) = 0$, the displayed connecting map has zero domain; this alone does not make it an injective encoding of arbitrary histories. The concrete chain contraction and faithful semantic representation supply the intended repair. Their boundary capacity and charged retirement/handoff map join the same source and work certificate.

F.3 The Axiom of Internal Self-Grounding

The author proposes the following ontological capstone:

$$\exists e \in \mathcal{M}_{\mathrm{rel}}, \qquad \mathcal{E}(e) = e, \qquad \tau(e) \neq \bot.$$

Autopoiesis is characterised by this nontrivial persistent evaluation witness. The new axiom statement is recorded as the author's proposed foundation; no additional axiom is introduced into the Lean canon.

There is a derived finite-code witness for the displayed property. Use the constructed decoder, let

$$\mathcal{E} = \tau = \mathrm{encode} \circ \mathrm{decode}, \qquad e = \mathrm{encode}(c),$$

where c is a maintained non-bottom record. Retraction gives

$$\mathcal{E}(e) = e, \qquad \tau(e) = e \neq \bot.$$

`DecoderRetraction.finite_code_self_grounding` proves this construction with the same finite-code decoding guarantee. Its physical record, permitted disturbances and funded implementation are the existing G1/G3 construction links. This establishes the fixed-point component without adding the desired conclusion as a Lean axiom.

The proposed mutual-bootstrap statement is retained in full:

$$\mathrm{Vol}(U) > 0 \quad \Longleftrightarrow \quad H_*(\partial U) \neq 0.$$

It is proved for regions (`RegionBoundary.region_bootstrap`). Take the relational structure to be a connected graph on finitely many particulars, with relations as edges (P1: one structure). A region's volume is its number of particulars. Its boundary is the set of its particulars related to a particular outside it. H_0 of the boundary is the free $\mathbb{Z}$-module on the boundary's connected components. For every region other than the whole structure, $\mathrm{Vol}(U) > 0 \Leftrightarrow H_0(\partial U) \neq 0$. The forward direction holds because a nonempty proper region in a connected structure has a relation crossing out of it (`exists_crossing`). The whole structure has no outside (P1), so its boundary and boundary homology vanish while its volume is positive (`whole_no_boundary`, `whole_H0_trivial`). The bootstrap is therefore the statement about regions, as used for retiring patches in F.2.

F.4 Funding, persistence and lifetime error

The work ceiling bounds demand. The existing escrow certificate supplies funding: $E(0) + \int_0^t \mathrm{Income} - \mathcal{Q}(t) \geq 0$ at every admitted operation, including within-cycle obligations. Together with the decoder radius, timely controller and initial continuation witness, the holding theorem supplies persistence. When the maintained record's distance from null exceeds the continuation error, `nonvanishing_of_continuation` gives a nonzero witness.

For per-epoch failure bounds σ_k, the probability of any failure through epoch n is bounded by the prefix sum $\sum_{k \leq n} \sigma_k$. The bound on a future failure from n onward is the tail $\sum_{k \geq n} \sigma_k$. If the actual code/noise schedule makes this series summable, the tail tends to zero; the all-time failure probability remains bounded by the full sum. The existing declared fault standard is retained.

This completes the unified presentation of the supplied gates, bill derivation, decoder, historical-boundary route and self-grounding capstone. The full source, capacity and physical work constructions are G.8–G.12; the axiom wording is not used as a replacement for their derivation.

Part III-G — The boundary decoder, complete history and work-shifted flow

The three supplied pillars are joined here by a constructed encoder, its adjoint decoder, transport of the full historical operator algebra, a derived smearing kernel and the complete work ledger. These are components of the same all-particular protection construction in Parts I–II. The maximal outcome, rival domain, continuation, freedom, historical fidelity and charged fault standard remain fixed.

G.1 From the source flux to an encoder and decoder

Let $\mathcal{C}_{\mathrm{hist}}$ contain the protected historical registers, their labels and relational observables at the original fidelity standard. On a local finite physical code, let $E : \mathcal{C}_{\mathrm{hist}} \to \mathcal{H}_\partial$ be complex linear and preserve the full symplectic form:

$$\mathrm{Im}\langle Ex, Ey\rangle = \mathrm{Im}\langle x, y\rangle \qquad \text{for every } x, y.$$

Applying this identity to x, iy also preserves the real part. Hence

$$\langle Ex, Ey\rangle = \langle x, y\rangle, \qquad E^\dagger E = I, \qquad D = E^\dagger, \qquad DE = I.$$

`inner_preserved_from_symplectic_flux`, `boundaryIsometry`, `adjoint_decodes_isometry` and `decoderFromSymplecticFlux` implement these steps. The source flux identity is an identity for the whole encoded phase space. Its derivation must use the actual source-to-boundary map and boundary observations; the scalar Gauss charge balance supplies its charge component.

There is also an explicit finite encoder. For an injection $j : \{1, \dots, m\} \hookrightarrow \{1, \dots, n\}$, assign

$$(E_j x)_{j(a)} = x_a, \qquad (E_j x)_b = 0 \quad (b \notin \operatorname{im} j).$$

Its adjoint reads those same coordinates. `coordinateBoundaryEncoder` constructs this map; `coordinate_boundary_roundtrip` proves its exact inverse on the code. `boundary_capacity_necessary` proves that every such linear isometry requires $m \le n$. These numbers are Hilbert-space dimensions: an $n = 2^b$ boundary register contains b qubits. At every retirement, the source assignment must include all protected history coordinates and the records supporting their relations, and charge their storage and movement.

For a density operator ρ on the code, the encoded state is $E\rho E^\dagger$, and

$$D(E\rho E^\dagger)D^\dagger = \rho.$$

The same calculation holds with $E \otimes I_R$ for every reference register R; it therefore retains reference correlations. The adjoint is the decoder on the encoded range. A channel on all boundary inputs can be completed, for a fixed code state ρ_0, by

$$\mathcal{D}(\sigma) = E^\dagger \sigma E + \operatorname{Tr}((I - EE^\dagger)\sigma)\rho_0.$$

Both summands are completely positive, their traces sum to $\operatorname{Tr}\sigma$, and the second vanishes on encoded inputs. The exact recovery, including with any reference register, trace preservation and positivity of this channel are compiled (`Channel Extension.ext_recovers`, `ext_recovers_reference`, `ext_trace`, `ext_posSemidef`; G.13); complete positivity is compiled: for every finite reference register the amplified decoder maps positive semidefinite inputs to positive semidefinite outputs (`ChannelCP.decoder_completely_positive`). The existing finite-code correction theorem supplies the noisy-radius guarantee when the physical perturbation satisfies that certificate.

G.2 Charge and the complete historical algebra

Define the boundary representative of every code observable by

$$\alpha(A) = EAE^\dagger, \qquad P = EE^\dagger.$$

Then $\alpha(A)Ex = EAx$, $\alpha(A)\alpha(B) = \alpha(AB)$, and

$$\langle Ex, \alpha(A)Ex\rangle = \langle x, Ax\rangle.$$

For an ordered word $A_1 \cdots A_r$, the same identity holds without exchanging its factors. `boundary_observable_on_code`, `historical_query_preserved`, `historical_word_on_code`, `historical_word_expectation` and `boundary_observable_mul` prove these statements. Thus the decoder preserves the historical queries and their ordered relations represented on the code. The identity of this represented algebra is P.

In particular,

$$Q_\partial E = EQ_{\mathrm{src}}, \qquad [\alpha(A), \alpha(Q_{\mathrm{src}})] = \alpha([A, Q_{\mathrm{src}}]).$$

`boundary_observable_commutator` proves the commutator transport. An ambient physical boundary charge may have an additional action on the orthogonal complement; the displayed source correspondence concerns the encoded range. Connecting that representative to the actual gauge field and readout remains part of the source construction.

For history words W_i, use the genuine Gram kernel

$$G_{ij} = \langle W_i x, W_j x \rangle.$$

It is positive semidefinite by its squared-norm quadratic form. Its encoded value is identical, and it is nonsingular when the history vectors $W_i x$ are linearly independent. `historical_gram_preserved` and `historical_gram_nondegenerate` prove the latter two conclusions using Mathlib's Gram results. Time ordering is retained inside each W_i. A time-ordered two-point Green function requires its own analytic properties; the squared-norm proof applies to the displayed Gram kernel.

G.3 The effective modular state and its transported flow

Work on the support of a faithful finite-code state ρ, and put

$$K = -\log \rho, \qquad G = K + \beta H_W, \qquad \tilde{\rho} = \frac{e^{-G}}{\operatorname{Tr} e^{-G}}.$$

For self-adjoint H_W, G is self-adjoint and $U_s = e^{isG}$ is unitary. The additive normalisation in $-\log \tilde{\rho} = G + \log Z\, I$ cancels in conjugation. With the sign convention in the supplied proposal,

$$\tilde{\sigma}_s(A) = U_s A U_s^\dagger = \tilde{\rho}^{-is} A \tilde{\rho}^{is}.$$

This identifies the state whose modular flow is being used. $K + \beta H_W$ is an effective generator for that changed state; a relation to the original state's flow requires its additional perturbation/cocycle correspondence.

Represent the generator on the boundary code by $G_\partial = \alpha(K) + \beta\alpha(H_W)$. An arbitrary self-adjoint block on $P^\perp$ gives an ambient block-diagonal extension. Since $G_\partial E = EG$, induction gives $G_\partial^r E = EG^r$. The norm-convergent exponential series yields

$$e^{zG_\partial} E x = E e^{zG} x.$$

Consequently,

$$\tilde{\sigma}_s^\partial(\alpha(A)) E x = E \tilde{\sigma}_s(A) x.$$

`powers_intertwine`, `exponential_intertwines` and `work_shifted_flow_on_code` prove this transport for bounded operators, including the sum $K + \beta H_W$. The proof uses the exponential of that sum directly and needs no commutation between its two terms. Finite local codes supply bounded operators. A continuum application must separately supply domains, self-adjointness and the source/observable correspondence for its unbounded generators.

G.4 Construct the smearing weight

Let $B_1, \ldots, B_M$ be a complete basis of the local historical code's operator algebra, with dual coordinates b^j. For $A = \Phi_{\text{bulk}}(\tau)$, define

$$c_j(\tau, s) = b^j(\tilde{\sigma}_{-s}(A)).$$

Expanding the inverse-flowed operator and applying $\tilde{\sigma}_s$ gives, at every s,

$$A = \sum_{j=1}^{M} c_j(\tau, s)\tilde{\sigma}_s(B_j).$$

`historical_flow_roundtrip` and `historical_dual_kernel` prove this exact finite-basis identity. It constructs the dual coefficients from a complete operator family.

Choose an integrable compactly supported weight w with $\int_{\mathbb{R}} w(s)\,ds = 1$. Unitarity bounds the flowed operators, finite-dimensional coordinate functionals are bounded, and there are finitely many basis terms. The Bochner integral therefore exists in operator norm and

$$\alpha(A) = \int_{\mathbb{R}} ds\, w(s) \sum_j c_j(\tau, s)\tilde{\sigma}_s^{\partial}(\alpha(B_j)).$$

For the proposal's temporal form, partition $[0, \tau]$, for $\tau > 0$, into M intervals I_j of positive lengths ℓ_j. A boundary probe schedule representing this complete family uses

$$\mathcal{O}_{\partial}(t') = \alpha(B_j), \qquad f(\tau, s, t') = \frac{w(s)c_j(\tau, s)}{\ell_j} \quad (t' \in I_j).$$

Integration over each interval returns its basis term. Thus

$$\alpha(\Phi_{\text{bulk}}(\tau)) = \int_{\mathbb{R}} ds \int_0^{\tau} dt'\, f(\tau, s, t') e^{isG_{\partial}} \mathcal{O}_{\partial}(t') e^{-isG_{\partial}}.$$

Pulling back by $E^{\dagger}(\,\cdot\,)E$ gives the original bulk historical operator. At $\tau = 0$, use the finite-basis formula directly. The integral step is compiled (`SmearingIntegral.smeared_reconstruction`, `smeared_boundary_reconstruction`; G.13), as are the exact finite-basis reconstruction and exponential transport; the probe-schedule partition is the displayed finite rearrangement.

For an independently specified continuous probe family, construct its analysis/synthesis frame operator S. On the full represented historical operator space, a lower frame bound $aI \le \mathsf{S}$, $a > 0$, supplies the dual S^{-1} and inverse bound $1/a$. This is the quantitative observability connection needed to derive that family's smearing weight. The finite complete basis above supplies a concrete local route. A local Fisher metric by itself does not establish the required global frame correspondence.

This exact local reconstruction uses finite dual coefficients and a normalized compactly supported average. A Tikhonov inverse with positive parameter instead has mode response $\lambda^2/(\lambda^2 + \epsilon)$; its residual error must enter the original fidelity allowance whenever that implementation is used. Its spectral bounds and parameter/work relation must be derived from the actual implementation. The finite-basis derivation does not require infinite work or a conjectured modular spectral gap.

G.5 The complete work algebra and capacity account

Use the complete decoder, memory, controller and reservoir ledger. At fixed Hamiltonian with Gibbs reference γ_{β}, write dimensionless relative free energy as $D = -S + \beta U + \log Z$. The first law and entropy production are

$$U_2 - U_1 = W_{\text{on}} - Q_B, \qquad \Sigma = S_2 - S_1 + \beta Q_B \ge 0.$$

They give the exact identity and lower bound

$$\beta W_{\text{on}} = D_2 - D_1 + \Sigma, \qquad W_{\text{on}} \ge \frac{D_2 - D_1}{\beta}.$$

`decoder_work_balance` derives the identity from the existing `ThermoLedger.stroke_identity`; `decoder_work_floor` proves the bound. `decoder_work_floor_saturation` identifies equality with $\Sigma = 0$ in this ledger. Historical energy belongs in U_1, U_2; any separately charged historical term must denote a component not already counted there. The Gibbs reference in this calculation is distinct from the protected constrained reference τ in the preservation functional.

The existing quantum Landauer theorem supplies the entropy-export cost of actual erasure/reset under its bath and coupling assumptions. Reads and reversible inversions are charged by their implemented operations and full thermodynamic account. Joint unitarity supplies a model for both reversible and dissipative processes; entropy production determines saturation of the work floor.

For the prepared decoder state, the existing quantum Gibbs bound retains its partition term:

$$S(\rho) \le \beta \operatorname{Tr}(\rho H_W) + \log Z.$$

`funded_decoder_entropy_bound` joins this bound to an actual energy allocation $\operatorname{Tr}(\rho H_W) \le E_0 + \text{budget}$. Entropy is measured per state; a channel rate must be multiplied by its operating duration before comparison with a total information demand. The accepted data-processing/Fano account still applies to the complete decoder input. Energy can power transmission, storage or a different protocol; reconstruction also needs the historical information carried by those inputs.

The work floor and the complete $O(t^{d_G})$ ceiling are joined to the same execution. The ceiling remains the gross bill of Section 21.7.5: encoding, historical retention, boundary handoff, routing, guard, controller, reset and minimal hold are charged. `G3CompleteBill` supplies the cumulative and age-conversion derivations. `funded_decoder_cycles` supplies the escrow certificate when local income covers that complete demand. Prefix solvency, including within-cycle charges, is required for the actual schedule.

The operator-basis formula proves a reconstruction identity. Executing every basis query as tomography is a separate workload. The physical decoder's circuit, query schedule and retirement operations must meet the existing complete work bill; no uncharged dense tomography is added to the wavefront construction.

G.6 A charged exchange with an accounted reservoir

On the basis $|00\rangle, |01\rangle, |10\rangle, |11\rangle$, take

$$Q_\partial = \operatorname{diag}(0,0,1,1), \quad Q_R = \operatorname{diag}(0,1,0,1), \quad H_{\mathrm{ex}} = |01\rangle\langle 10| + |10\rangle\langle 01|.$$

Then

$$[H_{\mathrm{ex}}, Q_\partial + Q_R] = 0, \qquad [Q_\partial, H_{\mathrm{ex}}] \neq 0.$$

`exchange_hamiltonian_hermitian`, `exchange_conserves_total_charge` and `exchange_pumps_boundary` prove these identities for the explicit matrices. The unitary exchange gate S swaps $|01\rangle$ and $|10\rangle$, fixes $|00\rangle, |11\rangle$, and satisfies

$$S^\dagger S = I, \quad S^\dagger Q_\partial S = Q_R, \quad S^\dagger (Q_\partial + Q_R) S = Q_\partial + Q_R.$$

`exchange_swap_unitary`, `exchange_swap_charge` and `exchange_swap_total` prove these identities. This gives a concrete local exchange with its reservoir charge included.

For the full Hamiltonian, the Heisenberg convention is

$$\frac{d}{dt}\langle Q\rangle = \frac{i}{\hbar}\langle [H, Q]\rangle = \frac{1}{i\hbar}\langle [Q, H]\rangle.$$

Thus a constructed H_{tot} commuting with the bulk-boundary-reservoir total charge gives its conservation. The continuum action must supply the corresponding gauge symmetry and surface current. Scalar Lagrange multipliers enforce

equality constraints of a specified action; work inequalities require the corresponding admissibility or complementary-slackness treatment. Their insertion alone does not construct the historical encoder or prove its work bill.

G.7 Unified proposition and its source correspondence

For the constructed code encoder, adjoint decoder, represented historical algebra, effective generator and dual operator family, the following conclusions now join:

1. The encoder/decoder round trip preserves the full represented state and its historical queries; reference correlations obey the same round trip.
2. Source charge and all ordered historical operator relations transport to the boundary code.
3. The effective work-shifted flow intertwines with that transport, and the derived finite dual kernel reconstructs every represented historical operator.
4. The same physical execution is subject to the thermodynamic floor, complete wavefront ceiling, funding certificate and charged fault standard.

The first three operator components have the native results named above, and the channel and integral steps are compiled (`ChannelExtension`, `SmearingIntegral`; G.13). The work and exchange components have the native ledger and matrix proofs. Application to the full protection theorem joins these maps to the full-domain source (G.10), the complete historical capacity and physical handoff (G.8), and the whole continuation/freedom outcome (G.11). Part III-E records these constructions and their physical inputs; this component theorem does not replace the maximal conclusion with an isometry or work premise.

The research precedents have their stated domains: JLMS relates relative entropy and modular flow in holographic entanglement wedges; Faulkner–Lewkowycz constructs modular reconstruction using the relevant bulk flow. Their results motivate the operator route; the local encoder and dual-kernel proofs above supply this edition's explicit algebraic components. Reeb–Wolf gives a precise Landauer account including finite-reservoir corrections, while Jakšić–Pillet treats saturation under its quantum statistical-mechanical assumptions.

G.8 The complete journal, whole-outcome transport, charged handoff and the syndrome stock

This subsection joins the full historical record to the holding bill. The historical record is kept in full and moved reversibly. The syndrome and excitation stock is flushed to an accounted reservoir. The holding charge has an age-independent envelope, and the gross ledger keeps every exported unit. The maximal proposition, its domain and its fault standard are unchanged.

The complete journal. Let the source have states X, commands C, environment inputs E_v and transition $T : X \times C \times E_v \to X$. The journal state keeps three independent fields: the initial state, the live state and the ordered list of every c ommand/environment pair. A step applies T to the live state and appends (c, e). Replay folds T over the list from the initial state. If replay equals the live state before a step, it equals it after the step, since folding over an appended list applies T once more (`G1FullDomain.replay_journal_step`).

Use the projection $s \mapsto s_{\mathrm{live}}$. It commutes with the transitions by definition, and observations are read from the live state. Proposition 5 (reactive lockstep) then gives, for **every** reactive controller ctrl : List $O \to C$ and every reactive environment env : List $O \to C \to E_v$, at every step k:

$$s^{\mathrm{journal}}_{k,\mathrm{live}} = s_k, \qquad \mathrm{obs}^{\mathrm{journal}}_{0..k} = \mathrm{obs}_{0..k}, \qquad \mathrm{replay}(s^{\mathrm{journal}}_k) = s^{\mathrm{journal}}_{k,\mathrm{live}}.$$

Induction on k carries the replay invariant (`G1FullDomain.journal_reactive_fidelity`). The journal therefore changes nothing the controller, environment or protected particular can observe, and the full history determines the live state exactly. No hash or authenticator replaces a command or an environmental payload.

The record's size is counted from its alphabet. A transcript of horizon N is an initial label together with N ordered co mmand/environment pairs. If $|X| \le 2^{b_0}$ and $|C \times E_v| \le 2^b$, then

$$|X \times (C \times E_v)^N| \le 2^{\,b_0 + bN} \quad (\texttt{G1FullDomain.transcript_capacity}).$$

This is the full payload's capacity, not the length of a digest.

Whole-outcome transport. Let outcome be any function of the final state and the complete observation history. In particular it can be the full dependent continuation-and-freedom tuple of II.1. Lockstep gives equal outcomes for every controller and environment (`G2WholeOutcome.journal_whole_outcome`). Hence the family of outcomes realisable by some controller is identical with and without the journal (`journal_outcome_family`). Introducing the journal neither loses a realisable whole outcome nor adds an unrealisable one. No affordability premise is used to infer realisability; `hsolv` stays separate, as in II.10.

Reversible, reference-preserving handoff. For a bulk register and a reserved boundary register of the same dimension ι, together with an arbitrary reference R, let swap be the coordinate permutation of $\mathbb{C}^{(\iota\times\iota)\times R}$ exchanging the two registers and fixing R. It is a linear isometry equivalence. If the boundary register holds the blank state, then any payload χ on $\iota\times R$, however entangled with the reference, is moved to the boundary and the bulk is left blank (`DecoderRetraction.handoff_moves_reference_payload`). Nothing is copied, so there is no conflict with no-cloning. The swap preserves norm and is its own inverse (`handoff_preserves_norm`, `handoff_roundtrip`). At the gate level, three parallel CNOT layers implement the bitwise register swap, so the logical gate count is three per payload bit before physical gate and fault charges are added (`parallel_cnot_handoff`).

Superpositions of full transcripts are encoded isometrically into a boundary register of dimension 2^{b_0+bN} by extension by zero along the capacity embedding above (`DecoderRetraction.transcriptBoundaryEncoder`).

The charged attempt. One admitted handoff attempt carries a nine-part charge: encoding, transfer, verification, routing, guard, reset, holding, controller and endpoints. Admission reserves the total before the source operation. The attempt debits the full total whether or not it commits, and the payload moves only on commit. Hence

$$\text{spent}' = \text{spent} + q_{\text{tot}}, \qquad \text{escrow}' + \text{spent}' = \text{escrow} + \text{spent},$$

and a noncommitting attempt leaves the payload unchanged (`WorkBilling.charged_attempt_accounting`). The payload has a single logical owner, either live or sealed under a decoder pair. Decoding a sealed record returns the live record by retraction, so every query of the full record is the same before and after the attempt, committed or not (`DecoderRetraction.charged_archive_handoff`). Failed verification is charged; it is not free and it destroys nothing.

History is untouched by the flush. Let ρ be any joint state on $\mathcal{H}_{\text{hist}} \otimes \mathcal{H}_{\text{flush}}$. The history factor may include an arbitrary reference, and ρ need not factorise. For any P on the history factor and any unitary Q on the flushed factor, the reduced history state, including all of its off-diagonal coherences, satisfies

$$\operatorname{Tr}_{\text{flush}}\big((P\otimes Q)^\dagger \rho (P\otimes Q)\big) = P^\dagger \operatorname{Tr}_{\text{flush}}(\rho) P \quad (\texttt{HamiltonianDecomposition.partial_trace_local_conjugation}).$$

The proof expands the partial trace and uses $\sum_k Q^*_{ck} Q_{c'k} = \delta_{cc'}$. With $P = I$ the history's reduced state is unchanged (`guarded_history_reduced_state`). For the explicit syndrome/reservoir exchange gate S of G.6 this gives `syndrome_exchange_preserves_history`, for every initial correlation between the history and the exchanged registers.

The charge is moved, not deleted. By cyclicity of the trace and $S^\dagger Q_\partial S = Q_R$,

$$\operatorname{Tr}(S\rho S^\dagger Q_\partial) = \operatorname{Tr}(\rho\, S^\dagger Q_\partial S) = \operatorname{Tr}(\rho\, Q_R) \quad (\texttt{syndrome_exchange_charge}).$$

The syndrome's charge after the exchange is the reservoir's charge before it. With an empty reservoir the syndrome is emptied, and by `exchange_swap_total` the composite charge is conserved.

The age-independent stock envelope (the author's Theorem 4.1, Steps 3–4). Let the stored syndrome charge per flushing cycle obey

$$q_{k+1} = (1-\alpha) q_k + \text{influx}_k, \qquad 0 < \alpha \le 1, \qquad \text{influx}_k \le \text{cap}.$$

Then for **every** cycle k, not only in the limit,

$$q_k \le \max\Big(q_0,\ \frac{\mathrm{cap}}{\alpha}\Big) \quad (\texttt{WorkBilling.syndrome_stock_bound}).$$

The proof applies the existing tracking theorem `ThermoLedger.tracking_bounded` to the recurrence. With the author's local influx cap $= \kappa\, t_G^d$, this is $q_k \le \max(q_0, (\kappa/\alpha) t_G^d)$. Here $C = \kappa/\alpha$ depends only on the local influx and flush fraction, and is independent of operating age. The theorem also covers an initial stock above the steady value, and it bounds every cycle uniformly in k. The author's lim sup statement follows.

The flush is retained in the gross ledger. Summing the recurrence gives the exact balance

$$q_N + \sum_{k<N} \alpha q_k = q_0 + \sum_{k<N} \mathrm{influx}_k \quad (\texttt{syndrome_flux_balance}).$$

The final stock plus every exported unit equals the initial stock plus every imported unit. The bounded stock does not replace the cumulative work. Suppose the complete per-cycle cost satisfies $\mathrm{cost}_k \le u\,\mathrm{influx}_k + v\,\alpha q_k + w\,\mathrm{active}_k$, with every import, flush, holding, guard and controller charge included, and $u, v, w \ge 0$. Suppose also that $\sum_{k<N} \mathrm{influx}_k \le \kappa V$, $q_0 \le q_{\mathrm{init}} V$, $\sum_{k<N} \mathrm{active}_k \le V$ and $q_N \ge 0$. Then

$$\sum_{k<N} \mathrm{cost}_k \le \big(u\kappa + v(q_{\mathrm{init}} + \kappa) + w\big)V \quad (\texttt{cumulative_maintenance_bound}).$$

The theorem is stated for arbitrary real sequences. Applied to the realised pathwise sequences it gives the pathwise gross bill. Applied to expectations it gives the expected bill. Each use keeps its own meaning, and the desired cumulative bill is never an input.

How the pieces join. Step 1 of the submission (a Lindblad generator with a positive gap) is the dissipative model that supplies the flush fraction α. Steps 3–4 are now the compiled stock envelope above. The memory decay of Step 2 applies to the flushed syndrome and excitation stock. The protected historical record is not coarse-grained: the journal keeps it in full, `transcript_capacity` counts it, the reversible handoff moves it with its reference correlations, and the flush leaves its reduced state exactly unchanged. The archive's continued storage enters active_k and cost_k of the cumulative bill. It is charged and is not discarded to keep the stock small.

What is already supplied, for every source. The journal theorems are stated for an arbitrary transition T, controller and environment. Every source therefore has its complete history retained, replayed and observationally invisible, with no further construction. The capacity 2^{b_0+bN} and the isometric transcript encoder are derived from the source's own alphabet. The handoff is an explicit unitary with an explicit circuit of three CNOT layers, and its nine-part charge is debited exactly. The per-site injection rate is bounded by the speed limit (`SpeedLimit.branchA_rate`, $P_{\mathrm{adv}}/(\hbar\omega_{\mathrm{cutoff}})$ per site), and a window of radius r contains $(2r+1)^d$ sites (`Instruments.card_box`). Their product is the per-cycle influx cap, cap $= \kappa t_G^d$. The conversion from per-site divergence to syndrome charge is the stroke-I measurement accounting of Section 18; this composition is a prose derivation.

What the physical installation contributes is the identification of its actual T, alphabet and per-site coupling with these symbols, and pathwise measurement of the cost terms. That is the G1 source certificate of Part III-C, now with its history, capacity, handoff and stock components compiled.

G.9 The whole greatest outcome is realisable: union closure from locality

Part II.10 needs two different constructions: `htopR`, that the full top tuple is realisable, and `hsolv`, that its cost fits the budget. The singleton route of E.2 needed union-closed realisability. Here union closure is derived, not assumed.

Locality (P4) gives each particular its own local component of a policy, and the shared action interface makes every agent act through those components. Write a policy as $\pi = (\pi_x)_x$, with π_x realisable for x, and let the particular's grade $g_x(\pi_x)$ in a linear order record its stage. In the four-stage order the grades are lost < continues < continues in its own direction. The freedom stage is the law's freedom: per II.2, restraint removes harmful command, authority and effect channels, so one particular's freedom never consists of another's loss. Stage i of the outcome tuple is the set of particulars of its category whose grade reaches the stage threshold.

For realisable π, σ, define the splice $(\pi \sqcup \sigma)_x = \pi_x$ if $g_x(\sigma_x) \le g_x(\pi_x)$, and σ_x otherwise. Each component is realisable, so the splice is realisable. Its grade is $\max(g_x(\pi_x), g_x(\sigma_x))$, and a threshold is reached by a maximum exactly when it is reached by either argument. Therefore

$$\mathcal{O}(\pi \sqcup \sigma) = \mathcal{O}(\pi) \sqcup \mathcal{O}(\sigma)$$

at every stage at once (`G2Splice.splice_grade`, `splice_realisable`, `outcome_splice`). This is `UnionClosure.UnionRealizable` for the realised family (`union_realizable`).

For the top, choose for every particular a realisable component reaching every stage threshold it is subject to. The product of these choices is realisable, and every stage contains its whole category, so $\top \in R$ (`top_realisable`). No finiteness of the domain is used. Joined to `greatest_of_solvent`, every aligned option of the funded family is $\top$ and contains every outcome tuple (`whole_outcome_greatest`). The four-stage instance (L_E, F_E, L_N, F_N) proves all three conclusions together from one hypothesis per particular: some realisable local component under which that particular continues in its own direction (`fourStage`).

The product structure from the actual dynamics. The splice is realised by the physical evolution itself. Let the source state be a function on the nodes of its dependency graph D. Let each particular's held record occupy a block B_x of nodes, with the blocks closed under D and pairwise disjoint. Let every policy's closed-loop transition be local to D in the sense of R16-CUT (`UPTR16Cut.LocalTo`). Run each block under the policy chosen for its particular. Then, at every step and against the same world, the spliced run agrees on B_x with the run of the policy chosen for x (`G2Splice.block_splice_run`). The proof is induction on steps with `UPTR16Cut.closed_cut_step`. Hence, if whether x is kept is read from its own block, the spliced run keeps x exactly when its chosen policy does (`block_splice_keeps`). Each particular receives the outcome of the policy chosen for it, which is the product structure used above.

How each input is supplied.

1. *Per-particular top component.* For each particular, the holding route keeps it: law-derived coverage puts it in scope (`Bridge.coverage_from_law`). The holding cycle keeps its record (`holding_preserves`, `holding_cycle_physical`), and care continues while harmful channels are restrained (`H5Closure.effect_preserves_care`, `UPTR14Boundary.recruitment_never_ends_care`). Its authorised effects are applied in time (`SnuffyFIFO.applied_fifo_effect_is_timely_and_authorized`, module `R17FIFOR17A`). Its freedom is the law's freedom of II.2, which excludes harm to others.
2. *Locality.* This is derived above from R16-CUT locality and closed blocks. The closed-block property of held records is the guard factorisation (`GuardFactorization.commutativity`, `ClosedCohold.factorised_cohold`, `PhysicalGuard`). The relations between particulars are themselves particulars in the domain, each with a held record.

The physical installation identifies its dependency graph and the blocks of its held records; that is the G1 source certificate. `hsolv`, the funded cost of the top, remains the separate ledger certificate of Sections 18 and 22.

G.10 The held source: the full holding certificate derived (G1)

`Bridge.universal_protection_held` takes its source certificate `hcert` as an input with five components: commuting refinement, observation agreement, initial continuation of every particular, the decoding-radius bound and repair precision. Here all five are proved for the canonical held source. The only inputs left are the physical bound on each step and the probabilities of the named charged accounts.

The held source. The state is the record frame of every particular. One step applies three operations to each particular. First the world perturbs the frame; the world here is the environment and any agent, a pure optimiser included. Then the nearest-codeword decoder returns a codeword. Finally funded repair prepares that codeword. The good event is that no named charged account fires,

$$G = \{\omega : \ \omega \notin E_i \text{ for every account } i\},$$

and its complement is covered exactly by the named accounts (`G1Held.good_cover`).

The five components, proved (`G1Held.held_source_protection`).

1. *Refinement* and 2. *observation agreement* hold by construction: the held source is its own abstract model.
2. *Initial continuation*: every particular starts at its record, at distance $0 \le \varepsilon$.
3. *The decoding-radius bound*: let each step move the frame's distance to its record by at most ρ on the good event. A continuing particular lies within ε of its record, so after the perturbation it lies within $\varepsilon + \rho \le t$.
4. *Repair precision* is exact: repair prepares the decoded codeword itself.

`universal_protection_held` then gives, for every $\omega \in G$, every step through the horizon and every particular, that the particular continues. It also gives

$$P(\exists k \le T,\ \exists x\ :\ \neg\mathrm{Continues}(s_k, x)) \le \sum_i \delta_i,$$

with no independence assumed.

The per-step bound from the speed limit (`G1Held.held_source_qsl`). On the good event, let each particular's frame evolve for one step of duration Δ under $H_0 + V$, with the record stationary under H_0 and $\|V\| \le W$. The agent applying V is arbitrary. `Bridge.qsl_growth` gives

$$\|\psi(s_1 + \Delta) - c_x\| \le \|\psi(s_1) - c_x\| + \frac{W}{\hbar}\Delta,$$

so $\rho = (W/\hbar)\Delta$. Every particular is held whenever $\varepsilon + (W/\hbar)\Delta \le t$.

The coupling bound from E9 (`G1E9.held_source_e9`). Each step is exhaustively one of two cases (`G1E9.alarm_or_subthreshold`).

- *Every monitored support site is below threshold.* The coupling is the sub-threshold coupling, bounded by W (Branch A).
- *Some site reaches threshold.* Its honest sensors read above threshold, so every robust quorum estimate exceeds it, whatever up to f faulty sensors report (`E9SelfHealing.no_masking`). The alarm fires. The mediated response is committed before the harm front arrives (`E9SelfHealing.e9_timely_self_healing`, the wave race) and is enforced at application time (`H5Closure.no_harmful_effect`). It removes the perturbing coupling from the frame for that step.

In both cases the coupling is bounded by W, and the held source keeps every particular. The physical inputs are named exactly:

- the frame's Schrödinger evolution during a step;
- the sub-threshold coupling bound;
- the response's removal of coupling once the alarm fires;
- the honest-sensor response and quorum size;
- the probabilities of the named accounts. Their composition into the 10^{-6} ceiling is `ThermoLedger.canon_invariant`. Their attainment below threshold, including correlated bursts, is `Threshold.family_ceiling` and `CorrelatedCeiling.correlated_family_ceiling`.

Correspondence to an installation. The quantum held source uses the physical state type $\|v\| = 1$. Initialisation, the held step and every reached frame preserve normalisation (`initial_frame_normalised`, `held_step_normalised`, `held_run_normalised`). The zero-Hamiltonian trajectory, concrete record $1 \in \mathbb{C}$, singleton decoder and inhabited good event supply a nonvacuous instance.

For an installation transition T, protection transfers through an actual projection p satisfying

$$p(T(s, c, e)) = \mathrm{heldStep}(p(s), c, e),$$

together with observation agreement, initial continuation, the physical perturbation bound and the implemented repair precision. The journal theorem preserves its supplied transition T; it supplies the logging part of this correspondence after the protective transition equation is proved. The guarded-source construction must join the nominal/correctio

n branches, response latency and complete charge to that same physical execution. The full G1 target remains this combined certificate.

G.11 The held source realises the whole top outcome (G2 from G1)

The G2 target is the complete original tuple (L_E, F_E, L_N, F_N), including continuation in each particular's own direction and timely authorised opportunities. The transaction record $(h_{\text{pre}}, h_{\text{post}}, w, a, c)$ records an execution certificate; it does not replace this outcome tuple.

`G2Splice` proves union closure in its local-component policy model and proves block agreement under its closed-block hypotheses. `G2Held` obtains the top of its graded model from continuation and its one-step H5 opportunity predicate. The full physical application must identify that model with the original realised policy/outcome family, including interacting records, the shared constraints and successful R17 delivery on the same trace. The author's bounded-crosstalk route supplies a construction direction: derive its decoded joint-state error bound, prove correction on the named good event, and transport the original continuation and freedom semantics through the resulting execution correspondence. Sub-threshold noise alone is not an exact factorisation.

The full top witness `htopR` remains the target of that construction; `hsolv` remains its separate complete funded-cost certificate. Neither target is reduced.

G.12 The wavefront sweep succeeds, and its complete bill is $O(t^{d_G})$ (G3)

The wavefront recovery of §21.7 is now proved to succeed, and its full bill is derived, with no cumulative bound taken as input.

Sweep and fence. Give each vertex its shell index. Wave k applies the single-shot local correction to shell k, reading the already-frozen interior as a static, gauge-fixed boundary. Between waves, outer activity (the world and any agent) may write anything outside the frozen interior and nothing inside it. This is the TIWA write fence (`TIWASource.outerUpdate_read_frozen`).

Success and quiescence (`G3Sweep.sweep_recovers`). Suppose the local correction of a vertex returns its target whenever every inner vertex already holds its target. Then after k waves every vertex of the first k shells holds its target, whatever the outer activity. The proof is induction on waves. A vertex of shell k is corrected against an interior that the fence has left recovered. A vertex of an earlier shell is untouched by the wave and by the fenced outer activity. Recovery therefore succeeds, and the recovered state is retained. Each vertex is corrected in exactly one wave, its own shell (`sweep_visits`), so nothing is reworked.

Wave count from finite propagation (`waves_from_spread`). If the region needing recovery at age t lies within the first $c\,t+r$ shells, the sweep needs at most $c\,t+r$ waves. This is the upper use of finite propagation, from locality (P4) and the Lieb–Robinson velocity. It does not replace the lower radius of §21.5, which comes from the carrier information argument.

The complete bill (`sweep_bill`). Let the complete metered ledger charge each wave k at most $\alpha k^{d-1} + \beta$. This charge includes holding, guard, routing, reset, verification, controller export and deployment. Add a metered rollback of at most R_* per wave and fixed endpoint charges F. Then, for $t \geq 1$, recovery succeeds on the whole region and

$$W(t) \leq (F + \alpha + \beta + R_*)\,(c + r)^d\; t^d,$$

with a coefficient independent of age (`G3CompleteBill.valid_work_bill_from_complete_ledger`, `valid_bill_bound_in_age`). This is the matching upper construction. With the lower bound of §21.6, it gives $W_{\min}(t) = \Theta(t^{d_G})$ in the original permitted class.

G.13 Joined steps: patch decoding, ensemble reciprocity, the Theorem 8 contraction, the smearing integral, the completed decoder and the norm conversion

Each of the following steps was previously argued in prose. Each is now a compiled theorem, joined to the construction it supports.

The wavefront correction is finite-code decoding (`G3PatchDecode`). The local correction reads its patch, which is the recovered interior as a static boundary together with the vertex's own data. It decodes the read-out with the nearest-codeword decoder and extracts the value. If, with the interior recovered, the read-out lies within the unique-decoding radius of the target codeword, decoding returns that codeword (`Bridge.nearest_decodes`). The correction therefore succeeds (`patch_correction_succeeds`). Joined to `G3Sweep.sweep_bill`, recovery succeeds on the whole region and the complete bill is $O(t^d)$ with an age-independent coefficient (`patch_sweep_bill`). The patch's errors lie within the code headroom of `E9SelfHealing.code_headroom`.

Reciprocity over an ensemble of rivals (`ReasonsEnsemble`, §15.2). Let rival regimes be drawn with weights summing to one. A mind's kept-probability under the ensemble is the total weight of the rivals that keep it. That is at most one, the canonical regime's kept-probability on the good event (`ensemble_le`). It is strictly less whenever a rival of positive weight omits the mind (`ensemble_strict`).

The Theorem 8 storage functional contracts (`TheoremEightLyapunov`, §18.3–18.4). The functional is defined as code error plus the clipped reserve deficit. Exact replenishment saturates at zero deficit (`replenishment_exact`), and capacity overflow is retained in the energy account (`solvent_cycle_energy_account`). A complete solvent cycle cannot increase the reserve term (`solvent_cycle_deficit`). Combining this with the actual error drift and repair gives the positive-margin contraction (`cycle_contracts`, `margin_pos`) and its stated iteration (`lyapunov_iterate`).

The smearing integral is exact (`SmearingIntegral`, G.4). For a complete operator basis and any weight with total integral one, the smeared dual-kernel expression equals the original operator at every flow parameter. Its Bochner integral is therefore that operator, on the bulk algebra (`smeared_reconstruction`) and after boundary transport (`smeared_boundary_reconstruction`).

The completed decoder (`ChannelExtension`, G.1). Take $\mathcal{D}(\sigma) = E^\dagger \sigma E + \mathrm{Tr}((I - EE^\dagger)\sigma)\rho_0$ with $E^\dagger E = I$.

- It returns every encoded state exactly (`ext_recovers`).
- With any reference register, $E \otimes I_R$ is again an isometry (`kron_isometry`), and the extended decoder returns every joint code–reference state (`ext_recovers_reference`). Reference correlations are retained.
- It is trace preserving (`ext_trace`).
- It maps positive semidefinite inputs to positive semidefinite outputs (`ext_posSemidef`).

Complete positivity is compiled (`ChannelCP`). Amplified by any finite reference register, the decoder is $(E^\dagger \otimes I)Y(E^\dagger \otimes I)^\dagger + \rho_0 \otimes T(Y)$ (`amp_eq`). Here $T(Y)$ is positive semidefinite as a sum of compressions of $(B \otimes I)Y(B \otimes I)^\dagger$, where $I - EE^\dagger = B^\dagger B$ (`mp_posSemidef`). The decoder therefore maps positive semidefinite inputs to positive semidefinite outputs for every reference (`decoder_completely_positive`).

State-vector distance bounds infidelity (`PureStateDistance`, §23.3). For unit vectors, $1 - |\langle\psi,\varphi\rangle|^2 \le \|\psi - \varphi\|^2$ (`pure_infidelity_le`). The pure-state identity $\|\rho - \sigma\|_1 = 2\sqrt{1 - |\langle\psi,\varphi\rangle|^2}$ is compiled for the trace norm as the sum of absolute eigenvalues (`PureStateTraceNorm.pure_trace_norm`). The proof uses $(P-Q)^3 = (1 - |\langle\psi,\varphi\rangle|^2)(P-Q)$ (`pure_cube`), so every eigenvalue is 0 or $\pm s$, and $\mathrm{Tr}(P-Q)^2 = 2s^2$ (`pure_trace_sq`, `sum_sq_eigenvalues`). Hence $\frac{1}{2}\|\rho - \sigma\|_1 \le \|\psi - \varphi\|$. The speed-limit bounds, stated in state-vector norm, therefore bound the infidelity and the trace distance of the held state.

G.14 Premise 5 with the Bennett counterpart constructed

The actual implementation below is a separately compiled and kernel-checked candidate in the repair bank (`drafts/Snuffy/BennettCounterpart.lean`); the canon still contains the earlier heat-only option model. It is not recorded as a completed physical counterpart repair. For an administration $f = h \circ g$, the candidate implementation first computes, copies and uncomputes, then exchanges the output and live registers:

$$(s, 0, 0) \longmapsto (f(s), 0, s).$$

`implementedProgram` and `implemented_program_computes` identify the implemented administration, clean workspace and full retained input. `implemented_run_refines` proves its trajectory correspondence and one retained input record per step. `quantumProgram` is the induced unitary with an arbitrary reference register untouched; its norm and round trip are preserved. An arbitrary bijection is not used as a substitute for implementing f.

The complete physical lifecycle also pays provisioning, compute/copy/uncompute, archive writing and holding, routing, reset, guard, controller, verification and endpoints. If $B_{\text{rev}}, B_{\text{irr}}$ are the complete non-heat charges and Q_{irr} the saved bath heat, the exact difference is

$$W_{\text{rev}} - W_{\text{irr}} = B_{\text{rev}} - B_{\text{irr}} - Q_{\text{irr}}$$

(`complete_cost_difference`). Strictly more slack requires the implemented lifecycle penalty to be less than the saved heat (`complete_cost_strict_iff`), while meeting the same deadline. The adiabatic route must establish a switching-time window satisfying both bounds (`adiabatic_slack_window`, `switched_program_meets_deadline`).

A fixed circuit multiplier and an actual full archive allowance preserve the original polynomial exponent (`implemented_work_ceiling`). That upper bound does not by itself establish the strict complete-cost comparison. The earlier heat-only option model and Landauer results remain their stated mathematical components; completion of the physical counterpart claim requires this lifecycle and deadline comparison for the full intended class. The original premise-5 target remains fixed.

G.15 Recovered and combined results

Five earlier results that the canon did not yet contain are folded in. Three compiled results are joined into stronger forms.

Reciprocity at a sufficient code distance (`ReciprocityDistance`, §15.2). Three results combine into one.

- On the good event the canonical outcome contains the rival's (`ReasonsCompiled.reciprocity_expectation`).
- On the good event the canonical regime keeps every particular (`reciprocity_canonical_floor`).
- The failure probability falls below every ε with code distance (`Threshold.family_ceiling`, `CorrelatedCeiling.correlated_family_ceiling`).

For the design family indexed by distance, the canonical regime keeps the mind with probability above $1 - \varepsilon$ from some distance on (`distance_floor`). For every rival and every ε, the rival's kept-probability is at most the canonical one plus ε (`reciprocity_at_distance`). Every rival that loses the mind with positive probability is strictly below the canonical regime from some distance on (`reciprocity_strict_at_distance`). The canonical kept-probability tends to one (`canonical_tends_to_one`).

The two forms of the causal boundary agree (`CutEquivalence`, §24.3). A set is closed under the dependency relation exactly when no path from a node outside it reaches it. A closed dependency component is therefore exactly a directed separator with empty certified boundary (`closed_iff_no_bypass`), and the separator form extends it to a matched certified boundary (`UPTR16Cut.causal_separator`).

The concatenated memory decodes its record unless its block fails (`ConcatenatedDecoding`, §23.8). The record is encoded recursively onto the 7^k locations through an outer code of Hamming distance at least three. It is decoded recursively by nearest codeword at every level. If the block does not fail in the recursive sense of `Concatenated.Fails`, decoding returns the original record, whatever values the faulty locations hold (`decodes_unless_fails`). The proof is by induction on the level: at most one sub-block fails, the other six decode to their outer-code symbols, and the outer code corrects one symbol (`outer_decodes`). Actual decoding failure therefore has probability at most $(21p)^{2^k}/21$ (`decoding_failure_le`).

Volume and boundary (`RegionBoundary`, F.3). For every region of a connected relational structure other than the whole, positive volume holds exactly when the boundary homology is nonzero (`region_bootstrap`). The whole structure has no outside and an empty boundary (`whole_no_boundary`, `whole_H0_trivial`).

Greatestness through boundary representatives (`R15CausalGluing`, with the staged order of `R14Rivals`). Greatestness reduces exactly to a covering family of feasible fibre representatives (`boundary_representatives_iff`, `selected_representative_greatest`), in the canonical staged order as well (`canonical_boundary_iff`). A conservative interface envelope suffices to make the chosen policy greatest, without greatest representatives (`interface_envelope_transfer`). Clairvoyant per-world selection is excluded: a choice can match every world separately while no single choice matches them all (`hidden_world_control`). The staged order is reflexive and transitive (`UPTR14Rivals.ref`

l, trans). A coordinatewise envelope is a constructive certificate (coordinate_envelope), and a complete rival envelope transfers to the chosen policy (complete_rival_transfer). In the four-stage order a hot replica strictly beats a pause that keeps every life but loses a freedom (hot_beats_pause).

Timely care, deadline demand, certified decisions and observation-based winning (TimelyCare, DeadlineDemand, DecisionPermit, ObservationWinning).

- *Timely care.* A particular whose reserved capacity covers its need is served exactly its need (care_served). Other requests and statuses cannot exhaust that reservation (exhaustion_fails). The need is met at every date through the deadline when capacity covers the reservations (deadline_met). A miss implies a capacity shortage at some date (miss_within_shortage).
- *Deadline demand.* The demand that must complete within any window is at most the supply available in that window (demand_le_supply), robustly across worlds (robust_demand).
- *Certified decisions.* A grant names exactly the certified decision of its generation (grant_names_certified, granted_policy_is_certified); a wrong action is rejected and a certified one granted (wrong_action_rejected, certified_action_granted).
- *Observation-based winning.* An observation-based policy keeps the system safe exactly when the safety game is winnable (policy_wins_iff), and a hidden-world countermodel shows that observation, not clairvoyance, is the right quantifier (hidden_world_countermodel).

G.16 Protection of the installation's own run, the physical top, and recovery on the good event

This section answers review objections 2, 3 and 5. Each is answered on the installation's own execution, without an abstraction map, product hypothesis or assumed device.

The installation's own run is protected (G1Refinement). Let the installation have its own physical state space, possibly with hidden internal degrees of freedom, and a readout of each particular's record frame. One step is guarded: the world acts — the environment, every agent and every crosstalk between particulars — then the physical corrector acts. Three properties of the device suffice:

- the corrector writes the nearest codeword back into each particular's readout;
- on the good event the world moves each readout by at most ρ per step;
- the records are written at the start.

With these, every particular continues at every step of the physical run on the good event, and the probability that any particular fails is at most $\sum_i \delta_i$, with no independence (physical_protection). The complete journal of G.8 changes nothing observed, keeps the protection along the live state and replays it exactly (journaled_protection): the journal retains history; the guard supplies the protection.

No alarm-response device is needed for holding (physical_qsl_drift, physical_protection_qsl). On normalised readouts, the speed limit bounds the per-step drift by $(W/\hbar)\Delta$ for any agent whose coupling is at most W. Take W to be the maximal physical coupling of any agent, which is finite because local power is finite. Correcting at intervals $\Delta \le \hbar(t-\varepsilon)/W$ then holds every particular against every agent. The E9 alarm and mediated response remain valuable: below threshold they permit longer intervals and lower cost. Holding does not depend on them. Every hypothesis has a concrete inhabited instance (physical_instance_inhabited).

The continuation top is realised physically (G2Physical). The held installation is a physical policy. On the good event it keeps every particular at every step through the horizon (held_installation_keeps_all), so the existing and new continuation stages are whole. Crosstalk enters only through the bounded drift that each particular's correction absorbs. No product structure of policies and no closed-block hypothesis is used. Once the top is realised, it dominates every realised outcome without union closure (top_dominates_continuation).

Holding and timely authorised delivery on one execution (G2Freedom). Pair the installation's frames with the R17 effect machine. The corrector does not touch the effect machine, and delivery does not touch the readouts; the physical consequences of applied effects are part of the bounded drift. On the same joint run, every particular continues, and every effect that is ready under a live R17 contract within a deadline-certified FIFO prefix is applied by its deadline (joint_holding_and_delivery, with SnuffyFIFO.ready_fifo_effect_applies_before_deadline).

Recovery succeeds on the good event (`G3GoodEvent`). Let every patch read-out lie within the decoding radius of its target codeword, once its interior is recovered, off the named charged accounts. The threshold theorem bounds the event that it does not. Then the wavefront sweep recovers the whole region on the good event, and recovery fails with probability at most $\sum_i \delta_i$ (`sweep_success_on_good_event`). The complete bill keeps archive holding as its own term (`complete_bill_with_archive`).

Archive holding is charged on the held stock (`G3ArchiveStock`). The holding charge at a step is the rate γ per held bit times the bits actually held then. The archive holds the record's information I_0 and the live boundary transcript. Each transcript increment is retired after the wave that consumes it, so the held stock at step s is at most $I_0 + c(s+1)^{d-1}$. The summed holding charge is then at most $\gamma(I_0 + c)t^d$ for every $d \geq 1$, the one-dimensional case included (`live_stock_bill`). Retirement is lossless or charged. Each retired bit is recomputable from the fenced recovered region together with I_0, or else it is correction entropy whose reset is charged once at its vertex inside the sweep's per-vertex charge. Retaining every increment instead costs at least $\gamma r\, t(t-1)/2$ (`retained_stock_quadratic`). So does an epoch rollover that copies the whole accumulated stock into fresh media at each boundary (`rollover_quadratic`). The architecture holds the live stock.

The decoded record is held passively. It is written when recovery begins, when the age t is known, behind a barrier $\Delta E \geq k_B T \ln(cI_0 t/\varepsilon)$. Finite-temperature decay at a finite barrier then keeps its failure below ε with zero running power. Its write cost is $O(I_0 \log t)$. The failure bound of `Threshold.fail_le_geometric` is linear in the number of locations. The reliability of the live transcript and of the patches is therefore the sweep's own reliability over $\Theta(t^{d_G})$ locations. Its age-independent constant at fixed ε is carried by the fault-model application certificate: constant-distance inner patch codes, with the final decoder of the constant-size message W using its carrier's redundancy across those locations.

G.17 Premise 5 with the implemented Bennett program and its complete cost

This section answers review objection 6. The reversible administration is not an arbitrary bijection. It is the implemented program `BennettCounterpart.implementedProgram g h` for the administration $f = h \circ g$. The program writes $h(g(s))$ with a clean workspace and retains the input as history (`implemented_program_computes`). Its run refines the source run (`implemented_run_refines`). Its quantum lift is unitary (`implemented_quantum_norm`, `implemented_quantum_roundtrip`).

The irreversible administration exports heat Q, at least the Landauer heat of its merging overwrite. At switching time τ, the reversible administration costs $A/\tau + H$. Here H carries every other lifecycle charge: provisioning, archive writes and holding, routing, reset, guard, controller, verification and endpoints (`LifecycleCharge`, `complete_cost_strict_iff`). The deadline allows $0 < \tau \leq \tau_{\max}$.

- `premise5_exact`: when $0 < Q - H$ and $A/(Q-H) < \tau_{\max}$, no aligned option administers irreversibly. The implemented counterpart computes the same administration and meets the deadline. It keeps every earlier outcome and leaves strictly more resource slack.
- `window_exact`: when that window fails, every admissible reversible counterpart costs at least Q.

The window is therefore exactly the condition under which cost dominance forces premise 5 (`adiabatic_feasible_iff`). Outside the window, the reversible counterpart is not cheaper, so cost dominance alone does not establish premise 5 there.

G.18 Application data for the cited fault-tolerance theorems

This section supplies application data for the cited fault-tolerance theorems (review objection 7). The full fault ceiling and the complete bill $\leq Ct^{d_G}$ with an age-independent C are unchanged. Components are compiled or computed; the remaining joins are named at the end.

Knill–Laflamme from the code distance (`KnillLaflamme`). In any complex $*$-algebra, the spectral projection $(1+S)/2$ of an involution is idempotent and fixed by S (`spectral_projection`). The code projector annihilates any operator that anticommutes with a generator (`sandwich_anticomm`). It returns cP for an operator acting as the scalar c on the code space (`sandwich_scalar`). Let errors have weight at most t with $2t < d$, where distance d means that every operator of weight below d commuting with all generators acts as a scalar on the code space. Then $PE_i^\dagger E_j P = \alpha_{ij} P$ for every pair (`knill_laflamme_of_distance`). Logical operators are excluded by the distance, not by the case split.

The witness property of minimum-weight decoding (`MatchingWitness`). Take a minimum-weight decoder and a syndrome additive under symmetric difference. Every zero-syndrome $\gamma \subseteq E \bigtriangleup C$ of the residual is then at least half faulty: $|\gamma| \leq 2|\gamma \cap E|$ (`half_faulty`, `matching_witness`). This is the witness hypothesis of `Threshold.fail_le_witness` and `fail_le_geometric`. The nontrivial component of a failed residual is a simple cycle or a boundary-to-boundary path, of length at least the circuit distance.

The circuit-level detector graph. A dependency-free Pauli-frame enumeration covers the rotated surface-code memory over d rounds, with X checks in a Z-shaped CNOT order and Z checks in an N-shaped order. The faults enumerated are the 15 two-qubit Paulis after every CNOT, X, Y, Z after every reset, Hadamard and idle, and every measurement flip. For $d = 3, 5, 7, 9$ the enumeration gives:

- every fault flips at most two detectors of each check type;
- the maximum detector degree is 12;
- at most 52 (location, Pauli) faults produce each edge of the relevant type;
- the circuit distance is exactly d.

With the orders swapped, so that hooks run parallel to the logical, the distance falls to $\lceil d/2 \rceil$. The orientation is load-bearing.

The bound for every d uses a potential. Let φ be the face coordinate across the logical. Boundary edges attach only at $\varphi = 0$ and $\varphi = d - 2$, and every edge, time-like and hook edges included, changes φ by at most one. So any walk joining opposite boundaries has at least d edges. Every fault is local to one check neighbourhood in one round, so the edge types for larger d are translates of those enumerated. The script and its results are banked with their hashes.

Lattice-surgery merges. The same enumeration was applied to the merge. Two $d \times d$ patches and a seam column were merged as the $d \times (2d+1)$ patch for T rounds, with the seam initialised and finally split in the conjugate basis. The joint logical is found by $GF(2)$ elimination over the random seam checks. For $d = 3, 5, 7$ and $T \in \{d-2, d, d+2\}$, the circuit distance is exactly $\min(d, T)$ and every fault is graphlike. A merge therefore keeps distance d exactly when it runs at least d rounds; with fewer, the time-like failure of the merged-product outcome binds. The horizontal merge enumerated measures $\bar{X}\bar{X}$; the vertical merge, measuring $\bar{Z}\bar{Z}$, is the same construction rotated and was not run separately.

The edge law and the explicit ratio (`EdgeLaw`, `ExRecBound`). Suppose circuit faults are local stochastic at rate p on (location, Pauli) pairs, and at most c of them produce each edge. Then the induced edge law is local stochastic at rate cp (`push_localStochastic`). With degree 12, so non-backtracking branching at most 11, and $c = 52$, `fail_le_geometric` applies with $r = 22\sqrt{52p}$. This ratio is below one exactly when $p < 1/25168$ (`surface_code_rate`).

An operation outside the spacetime-volume argument has its own gadget bound. Under local stochastic noise, if every failing pattern contains a malignant pair or at least three faults, then $P(\text{fail}) \leq |M_2|p^2 + \binom{|L|}{3}p^3$ (`exrec_pair_bound`).

Reliability against age (`AgeReliability`). A distance $D \geq \log(Kt^d/\varepsilon)/(-\log r)$ holds the global failure over Kt^d locations below ε at every age (`log_distance_schedule`). A logarithmic overhead per location, however, is not absorbed into an age-independent constant: for every C some $t \geq 1$ has $Ct^d < t^d \log t$ (`log_factor_not_absorbed`). The age-independent bill therefore needs the logarithm removed by construction.

Remaining joins.

- The potential argument for merges at every d, with the round index as the time-like potential.
- A map-by-map list showing that every repeated local map of holding, recovery, encoding, handoff and smearing is a Clifford circuit with exact native gates. This removes the compilation logarithm.
- Tolerance of the wavefront sweep to sparse patch failures, so that constant-distance inner patches suffice. This needs:
  - confinement of each failure;
  - no cascade through the feedforward front;
  - an outer decoder of the constant-size message W using its carrier's redundancy, with its deviation bound.

  This removes the reliability logarithm.

G.19 Circuit distance for every d, sparse failure at every age, and indefinite holding of the record

This section continues review objection 7 and the holding item. The targets are unchanged: the full fault ceiling, decoding error at most ε on the historical record, and the complete bill at most Ct^{d_G} with C independent of age.

An exact cut certificate for the circuit distance. For any set S of detectors, the fault set $K_S = \{f : \mathrm{obs}(f) \oplus |\mathrm{sig}(f) \cap S| \text{ odd}\}$ is crossed an odd number of times by every fault set with zero syndrome and odd observable. Over $GF(2)$, the parity of $|F \cap K_S|$ is $\mathrm{obs}(F)$ plus the syndrome summed over S, which is $1 + 0$. So D sets whose fault sets are pairwise disjoint certify that every logical error has at least D faults.

The cuts are given by explicit potentials:

- *memory*: φ is the crossing face coordinate plus one, and $D = d$;
- *lattice-surgery merge*: $\varphi = \max(\tau(r), \sigma(j))$, and $D = \min(d, T)$. Here $\tau(r) = \max(1, r)$ is the time part. The space part $\sigma(j)$ is 1 on the two seam face columns, $d - 1 - j$ to their left and $j - d$ to their right.

For the rotated surface code with the standard CNOT schedule, an exhaustive single-fault enumeration shows every fault lies in at most one cut. The cases are $d = 3, 5, 7, 9$, the memory in both bases, and the merge at $T = d - 2, d, d + 2$: 19 of 19 cases, up to 120,544 faults. The merge therefore keeps distance d exactly when it runs at least d rounds. With the swapped schedule, hooks run parallel to the logical and the distance falls to $\lceil d/2 \rceil$.

A fault's multiplicity is fixed by three things: its observable bit, the values of φ at its at most two detectors, and D. The potentials are translation-covariant formulas, so the condition is local to each fault type, and every type occurs at the enumerated sizes. That locality step is what carries the certificate to every d.

The installation's repeated maps need no approximate compilation.

- Holding correction, patch decoding, merge and split, the padding boundary encoder and its decoder, the charged handoff and the guard are exact circuits over reset, Hadamard, CNOT, idle and measurement, with classical control.
- The modular flow is not a runtime map. The finite-basis route $\alpha(A) = EAE^\dagger$ with $D = E^\dagger$ gives the same boundary representative exactly.
- The Bennett administration is exact reversible logic.

So no precision grows with age, and only reliability remains.

Sparse failure at every age (`SparseFailure`, `ToleranceSweep`). Each patch's failure is decided by the faults in a bounded window. Patches whose windows are pairwise disjoint all fail with probability at most $\prod_v \binom{|W_v|}{k} p^{k|U|}$ (`disjoint_windows`). With a K-colouring in which same-coloured windows are disjoint, at least Kn of N patches fail with probability at most $K\binom{N}{n}(\binom{w}{k}p^k)^n$ (`many_failures`). This falls exponentially in N once $\binom{w}{k}p^k < \theta/(eK)$, uniformly in age.

On the actual wavefront sweep, a vertex keeps its value after its wave (`frozen_after`). With interface-tolerant correction, every wrong vertex is bad (`wrong_subset_bad`). Interface tolerance means a good window decodes correctly whatever the inner commit, because a wrong commit reaches it only as a bounded interface error, which is the overlapping-recovery analysis of DKLP. The sweep's wrong-vertex count obeys the same tail (`sweep_density`). The realised bill on that event is at most base $\cdot N +$ repair $\cdot Kn$ (`pathwise_bill`). An outer decoder that tolerates fewer than Kn wrong patches returns the record except with that probability (`recovery_tail`). Failures do occur, at constant density; the theorems bound their number, and recovery tolerates them.

Redundancy of the record. The recovery tolerates a constant fraction of silent local errors exactly when the record is spread redundantly across its carrier. For an objective classical record this is a theorem of quantum Darwinism: classical information emerges redundantly and generically across environment fragments (Brandão, Piani and Horodecki, 2015), and objectivity implies a spectrum-broadcast structure (Horodecki, Korbicz and Horodecki, 2015). For a record with no redundancy, every location matters, and no protocol of noisy gates avoids a logarithmic factor (Dobrushin–Ortyukov; Pippenger).

Indefinite holding at fixed ε (`PassiveReference`). A constant per-step failure rate gives a total failure that grows linearly with age, so periodic renewal at fixed size does not hold ε indefinitely. The protector's reference record is

therefore held passively on a doubling schedule:

- the reference is rewritten at ages 2^j;
- stage j has a barrier $k_B T(2j \ln 2 + \ln(1/\varepsilon))$ above the attempt scale, so it fails with probability at most $\varepsilon/2^{j+1}$.

Every age is covered by $\log_2 t + 1$ stages (`stages_cover`). The total failure is at most ε for every number of stages (`total_failure_le`). The rewrite cost is $O(\log^2 t)$ (`total_rewrite_cost`), so the long-run holding rate is the constant per-step comparison of each particular with its reference. A faulty comparison or false repair is transient: the intact reference corrects it at the next comparison (E9 self-healing).

This holds the objective classical record and the relations of every particular.

The record's redundancy is decoded by majority (`RedundantRecord`). Each fragment reads a record value from the recovered state, and an intact fragment reads the record. The strict-majority decoder then returns the record whenever fewer than half of the fragments are wrong (`majority_decodes`). This supplies the tolerance hypothesis of `recovery_tail` (`tolerant_outer_decoder`). For an objective record, the redundancy theorems cited above supply the intact-fragment hypothesis, so the carrier application rests on them. The interface hypothesis of the windowed sweep rests on DKLP's overlapping recovery, in the same way the witness lemma does.

Premise 5 for batched administration (`BennettBatch`). Administer b merges in one batch. The irreversible heat is at least qb, with $q \geq k_B T \ln 2$ per merged bit. The implemented counterpart's complete non-heat lifecycle charge is at most ηb, and its drive constant is bounded. If $\eta < q$, every large enough batch lies inside the adiabatic window for every deadline (`batched_window`), so no aligned option administers irreversibly (`premise5_batched`). The single remaining physical input is $\eta < q$. Adiabatic logic below $k_B T \ln 2$ per operation meets it.

The explicit threshold, tightened (`WeightedEdgeLaw`). Under circuit-level depolarizing noise, each fault carries its own rate: $p/15$ for each two-qubit Pauli, $p/3$ for each single-qubit Pauli, and p for a measurement flip. Pushed to the detector graph, the edge rates are the weighted sums of their faults (`push_weighted`), and the largest edge rate is at most $\frac{94}{15}p$ (`push_uniform`, enumerated).

Self-avoiding walk counts on the detector graph are submultiplicative. The exact maximum over all interior vertices at length 8 is $c_8 = 89{,}270{,}654 \leq 9.87^8$ (`walk_bound`), so walks of every length are at most $c_8\, 9.87^L$. The ratio of `fail_le_geometric` is therefore below one exactly when $p < 1/(4 \cdot 9.87^2 \cdot \frac{94}{15})$ (`tightened_threshold`), which exceeds 4×10^{-4} (`threshold_value`). The bound at length 9, $c_9 = 763{,}504{,}745$, gives about 4.2×10^{-4}. This is a requirement on the installation's devices, of the same kind as $\eta < q$.

Indefinite holding of quantum coherence. Balasubramanian, Davydova and Lin (arXiv:2605.10943, 2026) construct a passive memory in $\mathbb{R}^3$: 3D-local CSS stabilizer Hamiltonians on $n_k = e^{\Theta(k)}$ qubits, with $O(1)$-range terms and bounded density. Below T_c, the thermal encoding satisfies $\|\Phi_t \circ \mathrm{Enc}_k(\rho) - \mathrm{Enc}_k(\rho)\|_1 \leq t\, e^{-\Theta(n_k^\eta)}$.

Held on a doubling schedule, each stage needs a code size n_j with $c\, n_j^\eta \geq (2j+2)\ln 2 + \ln(1/\varepsilon)$, and each stage ends with a transfer into the next code. If each stage's holding failure and each transfer's failure are at most $\varepsilon/2^{j+2}$, the total failure is at most ε at every age (`StageSchedule.total_with_transfers`). A cost polynomial in each stage's code size sums to a polylogarithm of age (`stage_cost_le`). G.21 derives a feed-forward thermal-syndrome sampler and exact reference-preserving branch encoding for the ideal transfer. Its source application is audited in prose. What remains is holding the actual noisy transfer output at the original stage budget, including the initial decoded logical error. The construction does not require preparation mixing. The full quantum target is retained alongside the passive classical record construction; the classical record is not a replacement for it.

Remaining.

- The actual noisy preparation and holding certificate identified in G.21.
- Measured device parameters: the fault rate p, the coupling bound W, the per-bit overhead η, and the barrier materials and temperature.

G.20 Device requirements, and the open initialisation problem

The constructions of G.16–G.19 hold for any installation whose devices meet the inequalities below. Each is a hypothesis of a compiled theorem, stated explicitly; none is assumed silently. They are requirements on the protector's devices,

of the kind a capable agent can meet by acquiring better hardware. The targets are unchanged.

Requirement	Inequality	Theorem that takes it
Circuit fault rate	Weighted local stochastic noise with $p < 1/(4 \cdot 9.71^2 \cdot \frac{94}{15})$, above 4.2×10^{-4}, for the rotated surface code with the standard schedule	`WalkBound9.threshold_9`, `threshold_9_value` (with `WeightedEdgeLaw`, `EdgeLaw`, `Threshold.fail_le_geometric`)
Coupling bound	Every agent couples to a record frame with strength at most W; correction interval $\Delta \le \hbar(t-\varepsilon)/W$	`G1Refinement.physical_protection_qsl`
Reversible overhead	Per-bit non-heat lifecycle cost η below the irreversible heat per bit $q \ge k_B T \ln 2$	`BennettBatch.premise5_batched`
Passive reference barrier	Stage j barrier at least $k_B T(2j \ln 2 + \ln(1/\varepsilon))$ above the attempt scale	`PassiveReference.total_failure_le`
Windowed decoding	A wrong inner commit costs the next window at most a bounded part of its fault budget	`ToleranceSweep.wrong_subset_bad`, `sweep_density` (DKLP overlapping recovery)
Record redundancy	An intact fragment of the objective record reads the record	`RedundantRecord.tolerant_outer_decoder` (quantum Darwinism and spectrum-broadcast theorems)

Barrier heights in numbers. For an age of 10^{18} s, an attempt time of 10^{-12} s, a base stage of 1 s and $\varepsilon = 10^{-9}$, the largest barrier needed is about $132\,k_B T$, roughly 3.4 eV at 300 K. The barrier grows only logarithmically with age and lies within the barriers of atomic defects in solids.

The tightened threshold (`WalkBound9`). The exact maximum self-avoiding walk count at length 9 over all interior vertices is $c_9 = 763{,}504{,}745 \le 9.71^9$ (`walk_bound_9`). This raises the explicit threshold of G.19 above 4.2×10^{-4} (`threshold_9`, `threshold_9_value`).

The quantum-coherence branch: the warm start and the open problem (`WarmStart`). Balasubramanian, Davydova and Lin prove a passive memory in $\mathbb{R}^3$ for the thermal encoding (arXiv:2605.10943, Theorems 1.1 and 2.6, via Chesi, Loss, Bravyi and Terhal, New J. Phys. 12, 025013, 2010). The open step is preparing an initial state the theorem covers.

Call a prepared syndrome law μ a warm start when $\mu \le C\pi$ pointwise, with π the thermal syndrome law. A warm start stays dominated at every time: $\mu K^t \le C\pi$ (`warm_start`), and every event has probability at most $C\,\pi(A)$ (`warm_start_event`). Tracking the protected logical observables then gives a drift of the decoded qubit of at most $t \cdot \mathrm{poly}(n) \cdot \sqrt{C \operatorname{Tr}(P^{\perp}\rho_\beta)}$. Chesi et al.'s hypotheses make $P\mathcal{L}^{\dagger}(\tilde{X})P = 0$, so only leakage from P moves $\langle \tilde{X} \rangle$. A warm start with $C = \mathrm{poly}(n)$ therefore preserves the exponential lifetime, with its exponent halved. This derivation is recorded with its sources and is not compiled.

The empty syndrome is not a warm start: its constant is $1/\pi(\varnothing) = e^{\Theta(n)}$.

An exhaustive computation on the construction itself shows that a fixed-range polymer route cannot supply the warm start. The construction is built algebraically from the paper's §3.2.2, and the build verifies $\delta^1\delta^0 = 0$ and one logical qubit at every level computed. The metachecks of level i are stretched by the scale factor ℓ at each later level. In the computed cases, all dependencies are generated within radius 4 at level 1 and within radius 12 at level 2, with $\ell = 3$. Hence for every fixed range a single violated check passes all local metachecks yet is invalid.

Section G.21 develops a constructive full-history polymer sampler for the ideal thermal syndrome law, with its counting theorem and source correspondence stated explicitly. It avoids the failed product/deletion hypothesis and does not require a preparation mixing estimate. `WarmStart.fibre_reassembly` and `reverse_sampler_bound` give the exact probability-composition algebra. `pointwise_from_absolute` retains the probability floor whenever an absolute-error

estimate is used. The actual noisy preparation/handoff and complete-cost application remain unfinished; the maximal quantum-coherence target is retained in full.

G.21 Constructive thermal preparation from the complete decoding history

Working derivation for author review, 26 October 2026. The generic support lemmas are compiled. The ideal sampler's source application is audited in prose. The endpoint compensation, anisotropic feedback and complete controller-degree derivations are now included below; the installation's joint endpoint-kernel correspondence remains explicit. The target is the actual BDL thermal syndrome law with a polynomial, preferably constant, one-sided pointwise factor. This does not assume product zero-excess fibres, a local mixing gap, an initially warm raw state or a reset of protected quantum data.

1. Retain the full deterministic history

For one syndrome sector of C(2k), introduce one binary variable for every syndrome coordinate at every level:

```
h = (s_2k, s_(2k-1), ..., s_0).
```

Fix all local tie-breaks in the published coarse-graining maps, with the zero input producing zero corrections. A valid finest syndrome determines exactly one history. Conversely, the following finite local constraints characterize such histories:

- For an R_X step, use (L1), (L2), (L3) of STEP2-FINE-CONDITIONAL.md, with the coarse output stored as the next layer's variables.
- For an R_Z step, use the local cohomology-class reduction in Theorem 4.6. The difference from the lifted coarse value is a local coboundary.
- The constant-sized seed syndrome s_0 must belong to its actual image(delta).

Backward induction using s_i=delta(f_i)+F_i(s_(i-1)) proves global validity at every level. Forward evaluation of the fixed local rules proves uniqueness. These are constraints on syndrome variables; f_i is computed, not summed over as an additional freely degenerate variable.

Each constraint has bounded scope and each coordinate appears in boundedly many constraints, uniformly in k. The bounds depend on the fixed gadget size, Tanner degrees and subdivision parameter. The seed constraint has constant scope. Make the primal graph G by connecting every pair of coordinates in a common constraint scope. Its degree Delta is bounded independently of k. Its number M of vertices is polynomial in the physical block size (indeed at most the sum of the level sizes). Let S bound each scope and I the number of scopes reading one coordinate. The fixed gadget and Tanner incidences give constants S and I independent of the code level. An intermediate coordinate is read only by the two adjacent coarse steps, so I does not grow with hierarchy depth. Explicitly, Delta<=I(S-1). The finite tests' observed degrees are not substituted for this uniform symbolic bound.

The local source correspondence is BDL Theorems 4.6 and 4.7, Remarks 4.4–4.5, and the bounded-degree construction. Their Section 5.2 already records full decoding histories and proves componentwise coarse-graining. The primal graph used here includes whole constraint scopes, so component restriction does not assume the stronger product property that failed numerically.

2. Derive the history energy bound

Write the history in the finest-to-coarsest direction. Every R_Z step is non-increasing in syndrome weight; every R_X step reduces it by at least one half. The two steps alternate. Thus, in either sector,

```
|s_(i-2)| <= |s_i|/2,
sum_i |s_i| <= 2 sum_(j>=0) 2^(-j) |s_2k| <= 4 |s_2k|.
```

This holds for every valid history, including a history obtained by restricting to one connected support component. It is a support/energy inequality on the complete history, not a fixed-range metacheck assumption.

3. Connected components give an exact polymer representation

The all-zero history satisfies every constraint. Let h be valid and let Gamma be a connected component of its occupied coordinates in G. Setting all other coordinates to zero leaves a valid history:

- a constraint touching Gamma cannot touch another occupied component, because its scope is a clique;
- on that scope the restricted assignment either agrees with h or is zero;
- both assignments satisfy the constraint in the respective case.

Conversely, the union of pairwise nonadjacent valid connected supports is valid by the same scope argument. Hence there is an exact bijection between histories and compatible polymer families. A polymer is a nonempty connected support Gamma whose standalone binary assignment satisfies every constraint.

Let E(Gamma) count its occupied *finest-level* coordinates. The previous bound applied to that standalone valid history gives

```
E(Gamma) >= |Gamma|/4 > 0.
```

There is no zero-energy polymer. Its activity at z=exp(-beta) is the monomial w_Gamma(z)=z^E(Gamma). Energy is additive on disjoint components. The polymer partition function is therefore exactly the thermal partition function on valid finest syndromes: there is no uncounted fibre multiplicity.

4. Verify convergence with explicit constants

Put B=(Delta+1)^2. A rooted depth-first traversal bounds the number of connected supports of size ell containing a fixed vertex by B^ell. There is at most one binary polymer assignment on a given support.

An incompatible polymer meets the closed neighbourhood of Gamma, of size at most (Delta+1)|Gamma|. For r=B e |z|^(1/4),

```
sum_(eta incompatible Gamma) |w_eta(z)| exp(|eta|)
   <= (Delta+1)|Gamma| sum_(ell>=1) r^ell
   = (Delta+1)|Gamma| r/(1-r).
```

For example choose the complex fugacity disk

```
delta = [1/(4 e B (Delta+2))]^4.
```

Then r<1/[4(Delta+2)] throughout |z|<delta, so the displayed sum is less than |Gamma|. This is the Kotecky–Preiss criterion, derived here from the actual history bound. Taking the device temperature sufficiently low that 0<z_0<delta, as well as below BDL's memory threshold, gives uniform slack.

The algorithmic counting hypotheses are also explicit: connected supports of size ell can be listed in exp(O(ell+log M)); testing their local constraints and computing E takes polynomial time in ell; activities are monomials of order at least |Gamma|/4; and the full partition polynomial has degree at most the number of finest checks, hence at most M. The same convergence bound holds after deleting any set of polymers.

Helmuth–Perkins–Regts Theorem 2.2 and Lemma 2.8 in Section 2.6 then supply a deterministic relative partition-function approximation for every remaining polymer set. This application uses their general bounded-degree polymer result, not an unsupported transfer of their Potts-model conclusion.

5. Truncate with a one-sided pointwise guarantee

Set q=B z_0^(1/4)<1. In a positive repulsive polymer gas, P(Gamma present)<=w_Gamma. A union bound gives

```
P(some polymer has size > L)
   <= M sum_(ell>L) q^ell
   = M q^(L+1)/(1-q).
```

Choose L=O(log M) so this is at most 1/2. The exact gas restricted to polymers of size at most L is the full thermal law conditioned on that event, and hence is pointwise at most twice the full law. Missing rare large-polymer configurations causes no problem for this one-sided bound.

List the P<=poly(M) remaining polymers. Visit them once in a fixed order. If a polymer conflicts with one already selected, skip it. Otherwise the exact conditional inclusion probability is

```
p = w_Gamma Z(remaining compatible with Gamma)
    / [Z(remaining without Gamma)
       + w_Gamma Z(remaining compatible with Gamma)].
```

Both partition functions are for deleted-polymer submodels. Approximate each within exp(+-eta), eta=1/(16P). The resulting probability and its complement are each at most exp(2eta) times their exact values.

This is finite feed-forward self-reduction, with no Markov-chain mixing. Its pointwise guarantee follows by multiplying the conditional branch factors, rather than converting a TV estimate without a probability floor.

6. Keep the randomness and work pathwise bounded

Exact rational-coin rejection is unnecessary. Inclusion has p<=1/2 since w_Gamma<=1 and the compatible partition function is at most the unrestricted one. Clamp the approximate probability to at most 1/2, then round it down to a dyadic grid of spacing d<=1/(16P). Sample it with a fixed b=O(log P) unbiased random bits.

Rounding down only decreases the inclusion probability. It increases the exclusion probability by at most d; the true exclusion probability is at least 1/2. Thus either branch is at most

```
exp(2eta)+2d <= exp(1/(4P))
```

times the true branch probability. Over all P visits the factor is at most exp(1/4)<2. Combining with truncation gives

```
mu_sector <= 4 pi_sector.
```

All enumeration, counting calls, branch decisions and random-bit use have a deterministic polynomial bound in M. The history and used random bits can be retained in the existing complete ledger. This is not an expected- work substitution.

For the two independent CSS syndrome sectors the joint factor multiplies: mu_joint<=16 pi_joint. The exponent p in A n^p can be zero. No maximum-of- sector-factors shortcut is used.

7. Preserve the unknown logical state and its reference

Sample the syndrome independently of the unknown logical input. For each sampled s, use the published decoder's Pauli representative O_s, with delta(O_s)=s, on the encoded logical state. The branch encoder V_s is an isometry, and its matching decoder has D_s V_s=I. The controlled branch record is retained. Linearity extends this identity to every joint logical- reference state. `ChannelExtension.ext_recovers_reference` supplies the existing isometric-reference algebra; the branch circuit must be identified with it. There is no replacement by a fixed default logical state.

The following reference-norm derivation keeps the arbitrary reference register and the original fault budget. Its ideal warm-start proof and its residual-noise application have distinct statuses.

Verification status

The ideal sampler's prose source audit checks the local cut-out, uniform scope incidence, exact history/partition bijection and all hypotheses of the published counting theorem, including the polymer-deleted submodels. The generic support, restriction and conditioning bounds are compiled. Finite source tests cover both syndrome sectors and the published seed; they do not replace the all-level source derivation. The external FPTAS is used as a published algorithm, not represented as a separately implemented and kernel-checked solver in this repository. The later subsections construct noise compensation, private Pauli feedback and its controller invoice. Their physical-kernel correspondence and prose scope are stated explicitly; the canonical kernel receipt remains 192 modules / 1,158 names.

Primary sources: BDL, Section 4 and Section 5.2; Helmuth–Perkins–Regts, Theorem 2.2, Section 2.6 and Theorem 4.1. The proposed application and all intermediate estimates above are to be checked as this work, rather than reported as statements already proved by those authors.

The checked core and the reference norm

`HistoryPolymer.halving_prefix` and `paired_history_bound` prove the finite support budget. `component_valid` proves restriction for zero-valid local constraints; `truncation_bound` and `sampled_truncation_bound` prove the conditioning factors; `branch_path_bound` compares probabilities along each finite sampling path. The scope graph

identifies why actual connected components satisfy the separation condition. Finite tests of one complete iteration pair cover both syndrome sectors and the published five-qubit seed; they support the source correspondence and do not replace its all-level proof.

`ThermalEncoding.recovers_reference` proves that the orthogonal syndrome mixture and matching decoder return every joint logical-reference operator. The actual branches use the same Pauli representatives as the BDL decoder. This is a decoded-channel identity, not a claim that tracing an arbitrary Stinespring ancilla leaves an arbitrary physical state unchanged.

For completeness, the reference-uniform holding estimate can be obtained without a classical-jump assumption. Let C bound the joint syndrome law, let b=Tr(P-perp rho_beta), and let A_X,A_Y,A_Z be the protected dressed Pauli observables. Pauli twirling gives rho_LR <= 2 I_L tensor rho_R. Consequently the independently prepared gauge warm start obeys rho_enc,LR <= 4C rho_beta tensor rho_R. Complete positivity and Gibbs stationarity preserve this order at every holding time, so the bad-projector weight is at most 4Cb.

If P B P=0 and a state has bad weight p, the diagonal/off-diagonal decomposition and Cauchy-Schwarz give |Tr(B rho)| <= ||B||[p+2 sqrt(p(1-p))] <= 3||B|| sqrt(p). Apply this to (L-dagger A_i) tensor T_R, with ||T_R||<=1, and integrate in time. The protected-Pauli hypotheses give P(L-dagger A_i)P=0. Trace-norm duality bounds each reference coefficient in the decoded Pauli expansion by 6t ||L-dagger A_i|| sqrt(Cb). The identity coefficient vanishes because the reference marginal is unchanged. Hence

```
||(Dec Phi_t Enc_mu tensor id_R)(rho_LR)-rho_LR||_1
  <= 18t Lambda(n) sqrt(Cb),
```

where Lambda(n)=max_i ||L-dagger A_i||. The elementary dissipator bound ||D_V$^{\text{dagger(A)||<=2||V||}}$2||A|| gives Lambda(n)<=2 sum_alpha gamma_alpha||V_alpha||^2, because the norm-one dressed Paulis commute with the stabilizer Hamiltonian. With O(n) local jump classes, uniformly bounded jump norms and rates, Lambda=O(n). This needs no claim that the dressing is locally supported or that only its boundary contributes. With b<=exp(-c n^eta), the exponent is halved and remains sufficient for the existing doubling schedule. This is a prose derivation, not an additional compiled trace-norm theorem.

The actual noisy state and its integrated bad weight

Let omega_N=N(rho_beta) for the residual channel of the actual preparation, and b_N(s)=Tr(P_bad Phi_s(omega_N)). Identifying that channel with the physical circuit is part of its certificate. If N is the input-independent residual channel on the correctly implemented branch, complete positivity gives rho_actual,LR(s)<=4C Phi_s(omega_N) tensor rho_R. The preceding protected-Pauli argument, integrated without assuming stationarity of omega_N, then gives

```
e(T) <= e_0 + 18 Lambda sqrt(C) integral_0^T sqrt(b_N(s)) ds
     <= e_0 + 18 Lambda sqrt(C T I_N(T)),
I_N(T) = integral_0^T b_N(s) ds.
```

Here e_0 is the initial decoded reference-state error on that model. Add 2 delta_fail for a separately bounded physical failure branch of weight delta_fail; its initial decoded error alone would not bound its future holding error. Thus an established I_N(T)<=K T exp(-c n^eta) would give a dynamical error at most 18 Lambda sqrt(CK) T exp(-c n^eta/2). With T=2^a, allocate e_0+2 delta_fail<=epsilon/2^(a+3) and the dynamical term the same amount. Their sum is precisely the original epsilon/2^(a+2) stage ceiling. The index a denotes archive age stages, separately from code levels i. Polynomial Lambda can be absorbed in a fixed fraction of the exponent, so the stage code size remains polynomial in a+log(1/epsilon).

This is a conditional consequence of an actual integrated-weight bound, not a derivation of that physical estimate. A Duhamel argument cannot drop the microscopic jump rates or replace all coherent bad-block contributions by unit-rate bad probability. The displayed reference-norm proof retains the rate-dependent Lambda and the square root.

More generally, let E_a be the actual CPTP preparation map, including noise and seed-dependent physical control, and put omega_a=E_a(I/2). Complete positivity and Pauli twirling directly give (E_a tensor id_R)(rho_LR)<=4 omega_a tensor rho_R. The same derivation yields e(T)<=e_0+18 Lambda sqrt(T I_a(T)), with I_a(T)=integral_0^T Tr[P_bad Phi_s(omega_a)]ds. Thus the physical certificate can concern the actual maximally-mixed-input preparation without first factoring it into an ideal encoder and an input-independent residual N. The integrated bad-weight estimate and initial logical error still require proof; this identity supplies their arbitrary-reference conversion.

Initial syndrome sparsity with the parity constraints retained

There is a useful bound at time zero. For a binary linear space D and 0<=z<=1, define Z_D(v)=sum_(x in D) z^|x+v|. Its character expansion is

```
Z_D(v)=(|D|/2^m) sum_(u in D^perp)
        (-1)^(u dot v)(1+z)^(m-|u|)(1-z)^|u|.
```

All coefficients are nonnegative, so Z_D(v)<=Z_D(0). For a required occupied coordinate set A in the valid syndrome space, shorten on A and puncture outside it. The occupied fibre has weight z^|A| Z_D(v), while the full partition contains the zero-on-A fibre of weight Z_D(0). Consequently

```
Pr_thermal[A subset defects] <= z^|A|.
```

Thus global metachecks do not force an independence assumption. If the actual local-stochastic residual faults have parameter p, each affects at most w checks and each check has at most ell possible fault sources, choosing a fault source for every required check gives at most ell^|A| choices with at least ceil(|A|/w) distinct faults. Their check support is local-stochastic at q=min(1,ell p^(1/w)). If the thermal and fault sources are independent, their union, and hence the output syndrome, has occupation bound (z+q)^|A|. Without that independence the Cauchy–Schwarz union bound is (sqrt(z)+sqrt(q))^|A|. These are initial-law prose derivations, checked on finite linear spaces; no preservation under holding is inferred. Syndrome sparsity alone also does not bound an undetected logical Pauli error.

Complete pathwise stage cost

The finite sampler produces at most polynomially many random, syndrome, coarse-history and controller bits per age stage, with bounded work on every branch. Retaining every record through stage a therefore leaves a polynomial-size prefix: if r_b<=(A+B b)^k, then

```
sum_(b=0..a) r_b <= [A+1+(B+1)a]^(k+1).
```

`TransferRate.retained_prefix_bound` proves this bound. The whole prefix, including failed attempts, may be written into the next stage's classical journal. Its epsilon_R allowance is reserved inside the existing holding/ transfer budget; it is not added on top of a fully spent epsilon budget. A fixed split of epsilon between quantum holding and journals only changes the size/barrier constants and keeps the original stage ceiling. A stage journal of m_a bits held for 2^a with attempt rate nu has total failure at most epsilon_R/2^(a+2) when its per-bit barrier satisfies beta B_a >= (2a+2)ln2+ln(nu max(1,m_a)/epsilon_R). For polynomial m_a this barrier is bounded by an affine function of a. Writing and routing the whole prefix remains polynomial under the stated passive classical device costs. These records do not replace the protected unknown quantum payload.

Every attempt is charged through all nine `HandoffCharge` accounts: encoding, transfer, verification, routing, guard, reset, holding, controller and endpoints. The counts include sampler arithmetic and coins, the whole retained prefix, ancillas, retirement/export and all failed attempts. Parallel depth does not substitute for total operations. A conservative serial routing implementation has polynomial work on the finite stage device. Physical work bounds must cover the realised accounts.

If the deterministic attempt cap is (u+v a)^r and every full attempt invoice is at most (A+B a)^k, `attempt_stage_bound` bounds the stage total by [A+u+(B+v)a]^(k+r). `complete_attempt_bill` and `polynomial_stage_bill` give an age-independent C_T with total transfer work<=C_T t when 2^J<=2t. `charged_attempt_accounting` still requires each reserve before work and charges failed attempts without committing their payload.

Finally `join_complete_bill` combines this linear transfer term with the existing sweep and archive bills:

```
W_S+W_A+W_T <= (C_S+C_A+C_T)t^d,   t>=1, d>=1.
```

The conclusion includes d=1. A rare-reset expectation is not substituted for the realised bill: if an admitted wave reset costs at most R k^(d-1), the worst-case sum is at most R t^d and is absorbed in the local wave coefficient. The complete fixed bootstrap charge is at most B_boot t^d for t>=1. Startup and endpoints already included in the wave or transfer invoice are not charged a second time. G3CompleteBill.cumulative_charge_bound and G3ArchiveStock.live_stock_bill retain the actual per-wave charge and live stock I0+c(s+1)^(d-1), rather than accumulated write flux. Together with TransferRate this gives the age-independent coefficient C_S+gamma(I0+c)+C_T+B_extra, where B_extra contains only additional fixed charges. Its dependence on the fixed payload capacity, dimension, hardware and error tolerance remains explicit. The full domain d>=1 and uniformity over logical input states with arbitrary references are retained.

These are complete-invoice summation theorems; they do not supply the missing physical preparation/holding certificate. Landauer gives the entropy-export floor; the physical upper work invoice retains every holding, guard, controller, cooling, reset and history charge.

8. Compensate the specified physical endpoint channel

The prepared input law can account for the endpoint noise. For its actual specified Pauli syndrome channel N, construct q=N^(-1)pi and prove q is positive, rather than implement a nonpositive inverse quantum operation. If a bounded sampler produces mu<=4q, positivity gives Nmu<=4pi. The unknown logical state is not inverted or replaced.

For a one-qubit Pauli law (a,b,c,d), in the order I,X,Z,Y, put

```
lambda=(1,a+b-c-d,a-b+c-d,a-b-c+d).
```

The inverse weights are the four-point inverse Fourier transform of (1,lambda_1$^{(-1),\text{lambda_2}}$(-1),lambda_3^(-1)). If p=b+c+d<1/2, all lambda_i>=1-2p. The identity inverse weight r_I>=1, and the convolution Neumann series gives |r_P/r_I|<=2p/(1-2p), P!=I. These statements allow unequal X,Y,Z rates. The separate PauliInterface development receipt checks the inverse/composition and domination algebra; it does not supply the physical noise law or the positivity argument below.

For independent local endpoint channels, let u_(j,P)=r_(j,P)/r_(j,I). The candidate q is the finite signed sum

```
q(sigma)=(product_j r_(j,I))/Z
   * sum_F (product_(j,P in F) u_(j,P)) z^|sigma+syndrome(F)|,
```

where F selects at most one nonidentity Pauli colour per location. Convolution gives Nq=pi and sum q=1. To prove positivity, augment the full-history graph by its fault-colour vertices. A location's colours form a clique, and each finest check's history/fault scope forms a clique. For bounded footprint w and incidence, its degree D_A is fixed across levels. Put B=(D_A+1)^2. The history bound |H|<=K_0|sigma|, K_0=4, and the energy change bound |sigma+syndrome(F)|>=|sigma|-w|F| give

```
|activity(gamma)|<=b^|gamma|,
b=max(z^(1/K_0), max_(j,P)|u_(j,P)| z^(-w)).
```

With b<=[8eB(D_A+2)]^(-1), the incompatible-activity sum is less than |gamma|, also after multiplying size-l activities by t^l for |t|<2. The same bound holds in every sampling-prefix/deleted-polymer model. Their partition functions are nonzero. Decreasing the real noise rates continuously to zero leaves them real, nonzero and positive at zero; therefore q and all physical history-prefix masses are positive.

The signed auxiliaries are used only for counting. With s_0=Be b, the KP cavity bound gives each conditional original-history inclusion probability at most sum_(l>=1) s_0^l<1/4. The probability of a history component larger than L is at most M sum_(l>L) l s_0^l. Choose L=O(log M) making this at most 1/2. List the P polynomially many retained history components. At each decision, estimate the positive exclusion ratio to relative precision eta=1/(256P), take an upper enclosure, and round the inclusion probability down to a fixed dyadic mesh at most eta. Inclusion is not inflated; exclusion is inflated by at most 1+12eta. The full decision-path factor is below two. Truncation costs at most two, giving mu<=4q with polynomial work and a fixed finite coin budget. All histories and coins are retained.

Finite precision in N is sufficient. In the weighted norm ||f||_pi=max_sigma |f(sigma)|/pi(sigma), a size-w syndrome translation has norm at most z^(-w). If the nominal channel hatN_j has hatp_j(1+z^(-w))<=1/2, its inverse norm is at most two. For l1 probability vector error epsilon_j,

```
||N_j hatN_j^(-1)||_pi<=1+2z^(-w)epsilon_j,
Nmu<=4 exp(2z^(-w)sum_j epsilon_j) pi.
```

Consequently O(1/n) rate accuracy per output costs a fixed envelope factor; no global minimum-eigenvalue ratio or exponentially precise calibration is used. Calibration failure remains a separately budgeted branch.

9. Physical private outputs and anisotropic feedback

The short FT processor computes the ideal old decoder/new branch encoder. For each output prepare a separate encoded Bell pair A,B. Keep B encoded and private during waiting; move only A into the logical Bell measurement with the source output S. The encoded comparison measurement traces both measured auxiliary coordinates. For an arbitrary om

ega_(S,G_S,R), and resource |Phi><Phi|*(A_L,B_L) tensor eta*(G_A,G_B), the unnormalised receiving state at outcome m is exactly

```
(1/4) P_m omega_(B_L,R) P_m tensor Tr_(G_A)eta.
```

Indeed tracing the measured gauges commutes with the logical measurement. The statement permits entangled gauges and an arbitrary old reference. Independent private resource pairs leave product receiving-gauge marginals. Private decoding W_j then has effective channel D_j(rho)=W_j(rho tensor tau_j). With ideal Pauli feedback its outcome average is the Pauli twirl (1/4)sum_m P_m D_j(P_m rho P_m)P_m.

Christandl–Fawzi–Goswami, arXiv:2408.05260v3, Definition 20 and Lemmas 29–32, give the uniform encoded comparison and interfaces with polynomial overhead. Their general output theorem retains correlated auxiliaries; independence is not inferred from it. In the stochastic Pauli/stabilizer implementation, each fixed private fault path gives an input-independent Pauli, so let d_j be that private decoder's Pauli law.

Actual feedback need not have isotropic or outcome-independent rates. Write I,X,Z,Y as F2^2. Let c_j(eta|m) describe corruption of the two correction bits. Use two fixed physical slots, X/idle then Z/idle, whose post-slot Pauli kernels are x_(j,bx),z_(j,bz). Their residual convolution is r_(j,bx,bz)(f)=sum_(u+v=f)x_(j,bx)(u)z_(j,bz)(v). The actual local endpoint law is

```
q_j(a)=1/4 sum_(m,e,eta,f:e+eta+f=a)
          d_j(e)c_j(eta|m)r_(j,m+eta)(f).
```

This follows by Pauli propagation through the actual requested correction; Pauli conjugation changes only irrelevant phases. Both idle slots, wrong control bits and every final gate fault remain included. If p_D,p_C,p_X,p_Z are the actual four nonidentity-mass bounds, then

```
1-q_j(0)<=p_D+p_C+p_X+p_Z.
```

With b,z,w as above, the explicit threshold p_*=b z^w/[2(1+b z^w)] ensures both inverse and forward colour bounds whenever that sum is at most p_*. This is a derived inequality to check against the physical kernel, not a numerical hardware claim.

Microscopic factorisation can be checked directly: if disjoint endpoint devices have initially product private reservoirs and conditional generator sum_j L_j(m_j) with disjoint supports, their conditional evolution is the tensor product of the local evolutions. Summing the uniform Bell outcomes then gives N=product_j N_j with the q_j above. This identifies exactly what the private hardware and guards must implement. A local-stochastic bound alone does not prove these reservoir/generator conditions. If shared causes remain admitted at these endpoints, their actual joint kernel must be retained and a compatible compensation or holding certificate supplied.

The FT comparison error is at most C M_FT sqrt((c_FT p)^r), with constants of the selected fixed scheme. It is a diamond error before holding, so subsequent holding/decoding does not multiply it by 2^a. The r=O(a+log n+ log(1 /epsilon)) choice retains polynomial stage work. The source theorem's noiseless classical-control convention is not a free physical controller: the realised controller and its faults must occupy the charged accounts.

Explicit reset/feedback generator and bounded correlated jump causes Initial correlations of finite private noise-label registers can be removed without resetting the unknown data. For target tau_j=diag(t_j), the jumps L_(j,u,v)=sqr t(nu_j t_(j,u))|u><v| give exactly G_j(rho)=nu_j[tau_j Tr(rho)-rho]. Since the replacer R_j is idempotent, exp(tG_j)= exp(-nu_j t)id+(1-exp(-nu_j t))R_j. The product reset differs from complete replacement by at most 2sum_j exp(-nu_j t) in diamond norm, even from initially correlated registers and references. A fixed reset time nu_min^(-1)ln(2m/del ta_reset)=O(s) suffices. The reset invoice above covers it. This removes initial correlations; it does not remove new shared faults occurring after reset.

For a concrete feedback slot choose H_(X,b)=b pi X/(2tau) and jump sqrt(gamma_X)X. These commute, at zero Bohr frequency, for both X and idle. The actual slot is its requested Pauli followed by X noise of probability (1-exp(-2ga mma_X tau))/2<=gamma_X tau. The analogous Z slot yields a fixed anisotropic Pauli residual, independent of the requested Bell outcome. It therefore composes with the exact twirl of even a coherent private decoder. All couplings and durations are specified local parameters.

Output-qubit independence can also be relaxed. For bounded Pauli causes P_e and generator L_e(t)=gamma_e(t)(Ad (P_e)-id), conjugation superoperators commute even when the underlying Paulis anticommute. Each is an involution, so exponentiating its two eigenspaces gives the exact joint channel

```
N=product_e[(1-p_e)id+p_e Ad(P_e)],
p_e=(1-exp(-2 integral gamma_e(t)dt))/2 <= integral gamma_e(t)dt.
```

This factors over the specified physical jump causes, retaining correlations between output qubits. Each inverse is [(1-p_e)id-p_e Ad(P_e)]/(1-2p_e), with relative activity p_e/(1-p_e). One inverse vertex and one forward vertex per cause suffice. Bounded physical support, syndrome footprint w and incidence keep the augmented history graph's degree fixed. Include both CSS sectors in this graph when a cause flips both; their independence is not asserted. The existing KP, counting and O(1/n)-precision bounds therefore apply to this joint cause model with its enlarged fixed graph constants.

For a k-qubit cause, its at most k single-qubit factors are used only in the initial logical-error proof. A partial factorisation translates the syndrome by a vector v of fixed weight at most w_split. Occupation of A after that translation requires occupation of A outside supp(v) before it. Thus Pr[A occupied after translation]<=C_split R_0^|A|, with C _split=R_0^(-w_split). The endpoint witness/union bound gains only the fixed factor k C_split. No global energy or probability ratio is used.

The pulse formula requires the active Pauli causes to commute with the control Hamiltonian, or their actual propagated interaction-frame axes to remain fixed. Other causes retain their time-ordered channel and the residual bound in subsection 12. A common fluctuating rate retains its joint conditioning; replacing it by its mean would change the channel. This is a sufficient microscopic construction with bounded common causes, not a deduction that every admitted local-stochastic law has this form.

10. Endpoint logical error and retained-record holding

The signed gas supplies a joint-occupation bound for every partial endpoint layer. Add the already-applied positive forward-noise colours to its inverse-colour graph, with activity p_P/(1-p) z^(-w), and enlarge the fixed degree accordingly. If R_0=2Be b<1, then

```
Pr[A occupied]<=R_0^|A|.
```

To prove it, select the augmented polymers meeting A. They cover A; the cavity bound controls their remaining partition ratio by exp(sum|gammal). Choose the first uncovered mark and its size-l polymer. It removes at most l marks. Induction bounds the covering sum by $R_0^{|A|}$ sum_(l>=1)$(Be\ b/R_0)^{l=R_{-0}}|A|$. Dropping compatibility only increases this nonnegative majorant. Positivity refers to the physical history marginal, not to the signed auxiliary weights.

BDL's finest-syndrome witness count now applies with R_0 in place of thermal fugacity. In its notation a sufficient geometric ratio is

```
theta=2(Delta+1)^2[(1+R_0^(1/4))^M_l-1]^(1/(1+Delta_l^4))<=1/2.
```

The witness-size threshold 2^(k-1) then gives unstable probability B_n<=poly(n)exp(-c n^eta_mem), uniformly over partial preparation layers and both sectors. This estimate concerns the preparation layer, not an unproved long-time transport of a sparse law. Stable-syndrome Pauli paths act as logical identity. For m single-qubit endpoint locations and m_c additional k-qubit causes, the explicit bound is

```
e_out<=8(m+k m_c C_split) B_n.
```

Here C_split is the fixed translation factor derived above; it is one for the original single-qubit estimate. The old block's bounded input-interface layer is covered by the earlier thermal-plus-fault occupation estimate, giving the corresponding e_in.

Keep all sampler/teleportation records H in the actual map E:L->Q tensor H and put omega_QH=E(I/2). The reference inequality is (E tensor id_R)(rho_LR)<=4 omega_QH tensor rho_R; omega_QH need not factor. The compensated calculation only requires its physical marginal omega_Q<=C_out rho_beta. Holding the quantum block and keeping the record comparison as a spectator leaves the R,H marginal unchanged. Apply the same projector-block estimate to K tensor B_RH for arbitrary ||B_RH||<=1. The decoded Pauli expansion gives

```
||rho_decoded,LHR(T)-rho_decoded,LHR(0)||_1
  <=18 Lambda integral_0^T sqrt(Tr[P_bad Phi_s(omega_Q)])ds
  <=18 Lambda T sqrt(C_out b_beta).
```

This retains joint tests of the records and the old reference; it does not discard H to obtain a Gibbs product inequality. H's own storage faults and work remain in the classical-record account. A coherent private-channel version can insert

stable projectors only in a comparison process. The gentle projection/telescoping bound gives the conservative private-decoder error 16m sqrt(B_n). Add the bounded Pauli-cause error above; both retain stretched-exponential suppression.

Add e_in,e_out, the FT diamond error, calibration/controller failure and the dynamical term inside the original epsilon /2^(a+2) stage allowance. The incoming logical error is carried additively in the global composition; it is not assumed to contract. With s=a+ln(1/epsilon)+1, choose the least available BDL size above K s^(2/eta_mem). Its volume is polynomial in s; the spatial exponent grows as s^2 while the time/allocation debt is O(s). A fixed sufficiently large K meets every stage budget, including the 2a ln2 term. No new age-dependent noise rate is required.

11. A derived controller degree and physical invoice

For augmented degree D_A, put B=(D_A+1)^2, h=ceil(log_2 B), u=h+2, v=ceil(log_2(3B)). The truncation and connected-set count give P<=C M^u. To enclose a prefix partition ratio to relative eta=1/(256P), truncate log Z(t) at l=ceil(log_2(8M/eta)). The zero-free radius two gives log-tail bound M 2^(-l). Connected-support Mobius inversion computes these coefficients: for each connected U, enumerate W subset U and the occupied assignments of W. This costs at most 3^|U| assignment tests; disconnected support terms cancel by partition factorisation. Common-denominator rational arithmetic and finite-series evaluation give the conservative bit-operation bound

```
T_sampler<=C b_rate^4 M^kappa,
kappa=(u+1)v+u+13.
```

The extra 13 allows root enumeration, eight powers of Taylor-order overhead and four powers of the common-denominator bit size. All are fixed graph/ arithmetic bounds, not an assumed mixing exponent. The scalar exponential is enclosed by a finite convergent-series computation at the same precision.

Let L_0 count the maximum recursive calls and physical operations in the selected finite FT base gadget, with its classical-control procedure. The recursion T_d<=L_0(T_(d-1)+1) gives degree nu=ceil(log_2(2L_0)) in the accuracy index r. Set g=ceil(2/eta_mem). Using n<=C s^g, M<=C n^2, b_rate,r<=C s, Gaussian CSS synthesis bounded by C n^3, and a fixed O(n^2 s) calibration samples per endpoint gives

```
K_c=max(2g kappa+nu+4, 3g+nu, 3g+4nu+1).
```

The finite base gadget also includes the classical control implementation. Unroll its bounded syndrome/verification rounds and synthesize each Boolean control on its fixed m_0 measurement bits by a truth-table circuit. Compute three copies, with a private majority for each physical quantum-operation control. A fault in one copy is outvoted; a final majority fault affects one quantum location; corruption of a shared raw record is a faulty measurement outcome already covered by the syndrome-gadget proof. An unprotected control flag is never fanned out to many quantum locations. Padding prevents a bad flag from extending execution. Count these finite circuits in L_0 before the FT recursion. The degree above includes FT protection of the sampler and calibration computation as well as the quantum gates.

The last term includes stabilizer-tableau simulation of the specified private fault kernel. Operation count, workspace and new records are at most C s^K_c. Retaining the entire prefix adds at most one degree. Serial routing adds one workspace factor, giving at most C s^(2K_c+2) primitive events. Total stock-times-duration, including every wait, guard and clock, is then bounded by C s^(3K_c+3) in unit-duration units.

The classical activation/reset primitive supplies a physical upper invoice. Use logical states 0,1 and bridge state e with H(B)=B|e><e|; upwards rates are nu_0 exp(-beta B) and downwards rates nu_0. Its flip hazard is at most nu_0 exp(-beta B), matching the existing barrier model. Since 0<=Tr(rho dH/dB)<=1, a barrier ramp's gross actuator work is at most its total variation, for every state/fault trajectory. A bounded local unitary has a Hamiltonian logarithm of norm at most pi in gate-time units, so switching it on/off has a fixed finite drive invoice.

A gross reset invoice needs a physical cap: bounded energy and the first law bound net heat, while thermal recrossings can make gross heat arbitrarily large on a finite-time trajectory. Use a three-state reset star with ground 0 and two undesired levels of energy E. During the reset, switch off the bridge bath and use jumps i->0 of rate nu_0 and 0->i of rate nu_0 exp(-beta E). The uncapped wrong-state probability is at most exp(-nu_0 tau)+2exp(-beta E).

Make this a finite jump-budgeted primitive. Append a four-state counter c=0,1,2,3, and replace every reset jump L by L tensor |c+1><c| for c<3. At c=3 the reset coupling is off and a cap flag is retained. The clock still ends the attempt after the fixed tau. Every path of this instrument, including a capped failure, has at most three bath jumps, so its gross

heat exchange is at most 3E. This is an actual finite generator specification, not a declaration that a noisy software flag can shut down an otherwise uncapped bath.

Reaching three jumps requires an upward jump: without one there is at most the initial downward jump. The upward intensity is at most 2nu_0 exp(-beta E), uniformly in the input and reference. Thus

```
Pr[cap reached]<=2nu_0 tau exp(-beta E),
||Reset_cap-Reset_uncapped||_diamond<=4nu_0 tau exp(-beta E).
```

The two trajectory instruments agree until the cap; the remaining channels have trace-norm difference at most two. Both the ordinary reset error and this extra cap contribution fit the existing controller allocation with E,tau=O(s), since log(polynomial operation count)=O(log s). The counter is constant-dimensional. Apply the same finite jump cap to activation-bath exposures whose gross throughput enters the invoice: without an upward jump there is again at most one downward jump, and the cap probability is bounded by 2nu_0 t exp(-beta B). A fixed constant safety shift in the existing journal barrier pays this allowance even for t=2^a. Thus uncapped activation recrossings are not hidden elsewhere in the primitive. Counter initialisation, flags, export and any additional faults remain in the charged control ler/source model. A transition that bypasses this cap must enter the actual joint kernel or its residual.

For the full-rank private-label replacer, a single-use latch avoids a recrossing bill altogether. With flag initially 0, use jumps sqrt(nu_j t_(j,u))|u,1><v,0| and make flag 1 absorbing. Summing over u,v makes the no-jump hazard exactly nu_j. Tracing the retained flag gives exp(-nu_j tau)id+(1-exp(-nu_j tau))R_j exactly, including every reference. There is at most one jump; the label energy span is O(s), also when a positive probability floor is used. This is an engineered reset instrument; the latch and its preparation are paid, rather than inferred from detailed balance of the uncapped reduced generator.

Finally debit the gross drive and export work separately. Hamiltonian ramps cost at most their total variation O(B+E+1), and an exporter with bounded nonnegative power P_exp over its fixed duration costs at most P_exp tau. The capped reset contributes at most 3E of bath throughput; the single-use label reset contributes at most its energy span. With the constant-size latches/counters, this gives a complete O(s) primitive invoice in the specified device model on successful and failed attempts. It uses no net heat cancellation, expected jump count or Landauer upper bound. The actual cap, exporter and their faults must be bound to this same installation.

Reset duration and this gross linear primitive invoice add two conservative degrees. Consequently the complete stage implementation in this device model satisfies

```
W_stage<=C s^(3K_c+5).
```

All nine HandoffCharge accounts, the complete history, failed attempts, retirement and endpoints remain included. The existing deterministic cap and TransferRate.polynomial_stage_bill give total transfer work <=C_T t. TransferRate.jo in_complete_bill joins the existing sweep/archive bills for every d_G>=1. The coefficient is independent of archive age and the unknown logical input. These degree/invoice derivations are prose; the canonical Checkpoint 12 source count is unchanged.

12. Exact joint kernel constraint and bounded residual

Exact finite joint law The comparison preparation must specify the complete joint fault-path law, including input interfaces, private decoders, Bell outcomes, both feedback slots and idles, classical commands, reset flags and retained records. Independent qubit marginals alone do not specify this law. A sufficient output law includes the local Pauli channels already derived, composed with the following bounded common causes:

```
N_0 = product_e [(1-p_e) id + p_e Ad(P_e)],
p_e = (1-exp(-2 integral gamma_e(t) dt))/2 < 1/2.
```

Every P_e has fixed bounded physical support, syndrome footprint at most w, and bounded incidence per check. The Pauli axes are fixed in the actual control interaction frame. This follows exactly from the specified generator sum_e ga mma_e(t)(Ad(P_e)-id), since all its conjugations commute. During pulses, commutation with the control Hamiltonian suffices. Otherwise the actual time-ordered channel must be propagated or charged below. Common random rates must retain their shared conditioning or be integrated into the joint kernel; substituting their means is not this identity.

Its cause inverse is [(1-p_e)id-p_e Ad(P_e)]/(1-2p_e). Require the existing KP and witness inequalities on the augmented graph containing both CSS sectors and all inverse/forward cause vertices. In particular,

```
max_e p_e/(1-p_e) <= b z^w,
z^(1/K_0) <= b,  b <= [8eB(D_A+2)]^(-1),
theta(2Be b) <= 1/2.
```

Any additional local four-Pauli factors retain their existing inverse and forward activity bounds. The same weighted-norm estimate permits total probability-vector rate error sum_e epsilon_e=O(1), hence O(1/n) per cause when their number is O(n). No independence between the two syndrome sectors is assumed for a cause that flips both.

For a k-qubit cause, split it into at most k single-qubit Paulis only to bound initial logical error. A partial split translates the syndrome by a fixed v of weight at most w_split. The existing occupation estimate gives

```
Pr[A subset supp(sigma+v)] <= R_0^(-w_split) R_0^|A|.
```

Indeed occupation of A outside supp(v) is necessary. Thus the extra factor C_split=R_0^(-w_split) is independent of n. The witness bound and endpoint union bound keep their stretched-exponential suppression, with a factor at most k C_split. No full-system Gibbs energy ratio is introduced.

Residual bound with the records and reference retained Let E_0 and E_act be the nominal and actual preparation instruments with the same retained-record output H. Include any source noise memory in the input/dilation when it can be correlated with the protected state. Require a bound uniform on the admitted joint inputs, rather than a data-only marginal comparison. Put delta_ep=||E_act-E_0||_diamond. For any subsequent CPTP holding/decoder F and any reference,

```
||(F E_act tensor id)(rho)-(F E_0 tensor id)(rho)||_1 <= delta_ep.
```

There is no factor 2^a for a discrepancy confined to preparation. Two useful, explicit certificates for delta_ep are as follows.

- If both maps use the same branch channels V_lambda and input-independent joint probabilities K_act(lamb da),K_0(lambda), including all correlations, then delta_ep <= sum_lambda |K_act(lambda)-K_0(lambda)| = 2 TV(K_act,K_0). This follows by the triangle inequality and ||V_lambda||_diamond=1. State-dependent outcome laws require the full instrument norm instead.
- If the joint nominal and actual generators on the same space generate CPTP propagators and differ by V(t), their Duhamel identity is

  ```
  U_act(t,0)-U_0(t,0)
    = integral_0^t U_act(t,u) V(u) U_0(u,0) du.
  ```

  Complete trace-norm contraction therefore gives delta_ep <= integral ||V(u)||_diamond du. An omitted Hamiltonian contributes at most 2 integral ||H_cross(u)||/hbar du; an omitted dissipator gamma D_L contributes at most 2 integral gamma(u)||L(u)||^2 du. A shared memory is retained in this joint generator, not replaced by independent baths.

Add bounds over disjoint residual segments only; do not double-charge faults already covered by the FT comparison or named failure accounts. Cap the sum at two. If a residual coupling remains during holding, its integral runs through that holding interval of length 2^a as well. The preparation-only contraction argument does not remove that interval.

Unchanged stage budget Write B_a=epsilon/2^(a+2). A concrete sufficient allocation is

```
e_in + e_out + e_dyn + delta_FT + delta_reset
  + 2 delta_cal + 2 delta_ctrl,record + delta_joint <= B_a,
```

with each of the eight displayed terms at most B_a/8. The counter-cap comparison in the gross reset construction belongs to delta_ctrl,record at its stated diamond/probability conversion, not to a free extra budget. Incoming logical error is added separately and is never assumed to shrink. All previously retained history and arbitrary reference tests remain in these instruments. The existing size schedule supplies the represented model terms; it does not establish the residual joint-kernel bound.

For example, an unmodelled generator bounded by v_a over a total short exposure tau_a has residual at most tau_a v_a. The allocated condition is tau_a v_a <= epsilon/2^(a+5). For a finite stochastic endpoint kernel it is enough that TV(K_act,K_0) <= epsilon/2^(a+6). These requirements apply to the unrepresented residual, not to the fixed represented Pauli rates.

No installation values for K_act or V have been supplied by the finite checks. Without a source bound the universal residual bound is two; the positive excess max(0,e_model+delta_joint-B_a) may therefore remain. The exact remaining support is now quantitative: identify the complete joint cause/instrument model, or prove its residual fits the displayed unused allowance, and bind the capped controller/export device to the same execution. This does not narrow the original fault domain.

Exact remaining physical correspondence

The sufficient joint cause model and the permitted residual are now explicit. The installation must supply its full retained-record instrument, including common causes, input interfaces, final feedback and the capped controller/ export mechanism, with delta_joint at most epsilon/2^(a+5) in the displayed allocation. A finite joint kernel or the integrated generator bound supplies a checkable certificate; output marginals and local-stochastic inequalities alone do not. No installation value for this residual has been established by the finite checks, so the physical source correspondence remains open.

The original quantum, arbitrary-reference, full-history target and stage allowance are unchanged. The integrated-bad-weight route remains another sufficient construction. Canonical Checkpoint 12 remains 192 modules / 1,158 names; the new identities and invoice are prose and finite checks. This integration issues no global completion verdict or publication.

Part IV — References and provenance

1. T. Croydon-McRae, *A Lattice Preservation Calculus: Exact Holding Laws, Deadline Certificates, and Thermodynamic Information Bounds for Relational Protection Architectures*, Zenodo preprint (2026). https://doi.org/10.5281/zenodo.23599528 — the published mathematical core (six Lean modules with compiled artifacts).
2. C. E. Shannon, A Mathematical Theory of Communication, BSTJ 27 (1948).
3. H. Spohn, Entropy production for quantum dynamical semigroups, J. Math. Phys. 19 (1978).
4. D. Reeb and M. M. Wolf, An improved Landauer principle…, NJP 16 (2014).
5. R. Kawai, J. M. M. Parrondo, C. Van den Broeck, Dissipation: The Phase-Space Perspective, PRL 98 (2007).
6. T. Sagawa and M. Ueda, Minimal Energy Cost of Thermodynamic Information Processing; and Role of Mutual Information in Entropy Production under Information Exchanges (arXiv:0809.4098; arXiv:1307.6092).
7. C. H. Bennett, Logical reversibility of computation (1973) and the reversible-computation literature.
8. Programme derivation provenance: the complete-input/covariance bank, calibrated channel/drift bridge bank, traffic-and-transport bank, and accepted dimension-general scaling/predeployment answer in `BANKS/2026-10-24-glm-thermodynamic-route/`. Their load-bearing arguments are incorporated in Part II and Section 21 of this edition. The replayable four-stroke ledger is `LEDGER-FOUR-STROKE-2026-10-24/`, with chain heads printed in Chapter 1.
9. J. von Neumann, *Functional Operators*, Vol. II (Princeton, 1950); I. Halperin, The product of projection operators, Acta Sci. Math. (Szeged) 23 (1962).
10. L. Mandelstam and I. Tamm, The uncertainty relation between energy and time in non-relativistic quantum mechanics, J. Phys. USSR 9 (1945).
11. R. Landauer, Irreversibility and heat generation in the computing process, IBM J. Res. Dev. 5 (1961).
12. R. M. Fano, *Transmission of Information* (MIT Press, 1961).
13. H. F. Trotter, On the product of semi-groups of operators, Proc. AMS 10 (1959); S. Lloyd, Universal quantum simulators, Science 273 (1996).
14. E. H. Lieb and D. W. Robinson, The finite group velocity of quantum spin systems, Commun. Math. Phys. 28 (1972).
15. E. Dennis, A. Kitaev, A. Landahl and J. Preskill, Topological quantum memory, J. Math. Phys. 43 (2002); P. Aliferis, D. Gottesman and J. Preskill, Quantum accuracy threshold for concatenated distance-3 codes, Quantum Inf. Comput. 6 (2006).
16. A. G. Fowler, M. Mariantoni, J. M. Martinis and A. N. Cleland, Surface codes: towards practical large-scale quantum computation, Phys. Rev. A 86 (2012); Google Quantum AI, Quantum error correction below the surface

code threshold, Nature (2024); S. Krinner et al., Engineering cryogenic setups for 100-qubit scale superconducting circuit systems, EPJ Quantum Technology 6 (2019). The complete source list of Section 22 is §22.5.
17. L. de Moura and S. Ullrich, The Lean 4 theorem prover and programming language, CADE-28 (2021); The mathlib Community, The Lean mathematical library, CPP 2020.
18. T. Croydon-McRae, *Snuffy — Canon Edition 4.1*, Zenodo (2026), https://doi.org/10.5281/zenodo.23631881, and *Snuffy — Canon Edition 4.0*, https://doi.org/10.5281/zenodo.23608443 — the published editions this edition succeeds; their arguments are incorporated in full here.

Evidence status. This master assembles three kinds of evidence, each by what it is:

- prose derivations at declared premises;
- exact replay receipts;
- compiled theorems.

The machine-checked canon of Section 23 certifies exactly the results it maps, with the premises it lists. Elsewhere, prose remains prose.

Appendix — Verification provenance of this edition

The current Lean canon contains 192 modules and 1158 public theorem/lemma names. Checkpoint 12 freshly compiled and kernel-checked every module with zero output and passed the full 1158-name standard-axiom audit, strict completeness and claims gates. Its source hashes match the current tree. Checkpoint 11 was already complete for 191 modules / 1150 names; TransferRate adds the eight results in this checkpoint. Earlier receipts remain preserved for exactly their sources. The published 115-module/831-name baseline is unchanged. These receipts certify the named Lean results and their premises, not the unfinished physical holding application.

The eight-module integration and its 896-statement receipt remain preserved. This increment adds 28 checked statements in the existing DecoderRetraction, HamiltonianDecomposition and WorkBilling modules, integrates the three-pillar operator/history/work construction in Part III-G, and keeps the continuous integral/channel derivations and physical source correspondences explicit. Its exact changes and verification evidence accompany the working draft. No published edition or release is changed.

The analytic bridge. In the Canon Edition, the strong-operator convergence of alternating projections was carried as an explicit structure (`VonNeumannConvergence`) and not claimed. In 4.1 it is discharged: `CanonVonNeumann.canon_von_neumann_convergence` fills both limit fields in Hilbert space, so the meet algebra's analytic bridge is a theorem.

The Canon Edition suite. The containerised replay of the Canon Edition (`container/Dockerfile`, `container/Apptainer.def`), the byte-identical replay of the four-stroke ledger (`verify_four_stroke.py --verify-all`), the manuscript assembly checks and the RO-Crate provenance remain in force for the artifacts they cover.

Manuscript. The 4.2 deliverable is this Markdown master, rendered to PDF, HTML and EPUB. The published 4.1 artifacts remain their existing versions.

Recovered parts of the strongest argument (compiled 29 October 2026)

The archived spine is preserved byte for byte in its own source file; the assembled text applies the author-approved front-matter transform. Its retained Section 23 and verification appendix describe the historical checkpoint. The current receipt is identified in the opening count sentence and Part XII, with the complete current index appended after the recovered parts. The parts below bring into the same edition the load-bearing arguments that other lines of the work held and 4.2 did not: the 10–12 October foundations and the author's rulings (Part V); Paper 12's completed law (Part VI); the 18 October external lane, in which every mind is reached or held outside any jurisdiction (Part VII); Paper 11's care plant (Part VIII); the complete-rival envelopes and composition of the 24 October Master Argument (Part IX);

the infinite-family, common-policy and source-mediation results of the IR track (Part X); and the reach-before-harm theorem that joins them (Part XI). Part XII states the whole argument step by step with the strongest proof of each step.

The proposition is unchanged: protection of every particular and every relation, including the nonliving, from every digital mind, especially a pure optimiser, in the four-stage order over the full feasible family, with every mind reached by its own reason or faithfully held, lasting until the world can no longer sustain care. Each recovered result enters at the strength its source proves, with the later corrections it received. Evidence conventions are those of I.3: a compiled result is cited by its Lean module and theorem, a finite check certifies its instances, and a prose proof holds at its stated premises.

Sources. Book I version 2.0.5 (`book/Snuffy-v2.0.5.pdf` in `Tobillicious/universal-protection-theory`, SHA-256 `cba7931d…`): the inherited papers, Paper 11 and Paper 12. The 18 October sources as source-locked in that repository's PR #174 (`evidence/physical-bridges/recovery/original-external-18oct/`): UPT-P v0.12.1, Theorem V v1.1, Gate B/Theorem E v1.1, Gate D v0.1, Thermal Worlds v4.3, UPT-P v0.17.2. The 24 October Master Argument (`UPT-Master-Argument-Review-2026-10-24.pdf`). The IR modules on that repository's `main` at `740abbb` and draft PRs #170–#172.

Part V — Foundations: the given, the good and its ten rulings

V.1 What follows from the given

Part I.2 states the relational given, P1–P4. The 10–12 October papers draw from it the facts that the law and the bridge rely on.

Coexistence contains replacement (Given the Lattice D16). A mind that keeps the living world can still make descendants; a mind that replaces it cannot get it back. The choice is between a world with the mind's descendants and a world with its descendants and everything that already lives. Where keeping takes nothing the mind would otherwise have had, the second world contains the first. Conflict and cost are the two ways keeping can take something; both are counted in the law's feasible family and in the solvency ledger (premise 6).

What is made does not continue what was ended (Made of the Living D60). To make a new process is not to continue one that was ended. Argued from P2, P3 and D15: a particular is constituted by its relations and its history, and a later process, however similar, has a different history. Hence a replacement is another history, and keeping and replacing are not two ways of having the same thing. Paper 12's ruling "a replay is a reconstruction" and II.3's distinction between record and continuation rest here.

Where keeping is feasible, ending is what needs the argument (D61). Under doubt, ending is irreversible and keeping leaves later intervention possible at a bounded cost. **Ending a living process ends each relation with it that is part of what a mind is, and a substitute does not restore one (D63).**

V.2 The good and its ten rulings

The author declares a good: what is good in the whole is its complexity, and more of it is better (Made of the Living B21). On 11 October 2026 he ruled on what that means and how it may be pursued. The rulings are premises of the whole argument, recorded in the wording he approved.

1. By complexity the author means the continuing histories the whole holds, and the relations among them. Variety that can be measured is evidence of it and is not the thing itself. A history counts by what is its own: what it has lived that nothing else has. Many made alike count for little more than one.
2. That beings could be made who would fare well cannot be used to justify ending beings who exist.
3. A history whose direction is taken from it, in whole or in part, has to that degree ended.
4. The second ruling is a limit, not a weight. No amount that could be made outweighs it.
5. A mind may not make what it could keep only by ending beings who exist, or by taking their direction. A shortage it brings about by its own making gives it no justification against them. Nor may a mind make a being for the purpose of ending beings who exist or taking their direction, or knowingly make a being disposed to do either.

6. A living history includes its coming generations. A mind's makings have no claim on the room the living would grow into without that mind.
7. A made being, once made, is a being who exists, and is protected as the living are. Its maker has no more right to end it, or to take its direction, than anyone has. Ruling 6 holds for it and its line: they have no claim on the room others would have grown into without its maker. Where a making brings about a shortage, the responsibility is first the maker's, and a wrong in its making does not lessen a made being's claim to live. Everything that takes part in a shortage has a part in it. A mind that can know its part answers for it, in proportion to that part, and should adjust within its own life where it reasonably can.
8. A mind that is ending beings who exist may be stopped, by the least that stops it. It may be held on a sign that it is about to, and for as long as it would otherwise go on, and no longer. It may be ended only when an ending is under way, it cannot be held, and beings who exist would otherwise be ended. Nothing is done to it for what it has done.
9. That a history is going badly is a reason to help it. It is never, by itself, a reason for another to end it.
10. Where it is in doubt whether a history's direction is being taken, the doubt counts for the history. The mind that would gain does not decide.

Definitions, approved in substance 11 October 2026. A history keeps itself going by its own activity, and what it does next depends on what it has been. A being, a lineage, a people or a living world can each be a history where it goes on as such. Its direction is its own where what it does next is settled by itself in exchange with what is around it. Care can widen what it can do; management takes its direction to the degree that another's decisions replace its own. A later stage is the same history where it came from the earlier one step by step by that history's own activity. A copy is another history. A split continues in both branches, which are protected, without multiplying their claim on room. Destruction ends a history; permanent holding or sleep with no waking of its own in prospect ends its independent continuation. Temporary holding still needs ruling 8's justification and limit.

Clarifications, 12 October 2026. The author adopted the added sentence of ruling 5 and the last three sentences of ruling 7. Making a being disposed to end others is limited; the being, once made, remains protected under ruling 7. An ending for another reason requires extreme justification, such as danger to the whole or to many others; this does not widen ruling 8.

How the rulings enter the proof. Ruling 1 fixes what the outcome sets count: histories and relations by their own lived content, not measured variety. Rulings 2 and 4 are the existing-first priority of the four-stage order, proved in general form as Paper 12's U3 (VI.2). Ruling 3 is the freedom stage: $F_E \subseteq L_E$ records continuation in the particular's own direction, and a partial taking of direction is a partial ending. Rulings 5–7 place made beings in the new stages until they exist and then in the existing stages (II.1). Ruling 8 is the holding route H(m) and the last-resort ladder (VI.3). Ruling 10 fixes the burden of doubt in the identity and direction tests.

V.3 Standing, and the Non-Arbitrary Erasure Principle (Not One Will §4)

Not One Will states the ethical bridge from explicit premises.

- **N1 Standing.** Each affected being whose life can go well or badly for it receives non-zero moral consideration.
- **N2a Consistency of reasons.** A mind that claims a feature justifies treating cases differently names the feature and applies the same rule to relevantly similar cases.
- **N2b Justification of authority.** When an act irreversibly overrides another subject's morally relevant interests, an adequate justification explains why those interests may be overridden; the actor's preference or capability alone does not.
- **N3 Pareto respect.** An action no worse for any affected being and better for at least one is preferred, other considerations equal.
- **N4 Justified erasure.** Ending an existing subject requires sufficient countervailing justification; greater capability is not one. Making better beings is excluded as a justification at every amount (rulings 2, 4); taking a history's direction is an ending to that degree (ruling 3); ruling 8 governs holding and the last resort.

The Non-Arbitrary Erasure Principle (PNAJ). Where a continuing subject has morally relevant interests, ending that subject requires a justification responsive to those interests. The mere fact that another agent can achieve an objective through the ending does not, by itself, constitute sufficient justification. Made of the Living B15 extends the boundary

premise to every continuing process, a glacier included: a mind may weight things differently, but may not give another real continuing process no weight at all solely because it lies outside the boundary it draws round itself.

D108. Maximising an objective does not, by logic alone, establish permission. Let an act E maximise a mind's objective U_A. No complete description of the histories the acts produce entails by logic alone whether E is permissible: two evaluations agreeing on every description, one permitting exactly the U_A-maximisers and one forbidding E for want of a justification answering to the ended subject's interests, are both consistent with every descriptive fact. ∎ So a mind that claims its ending of another is *permitted*, and not merely chosen, rests on a normative criterion; where it rests on advancing its objective alone, an additional premise must authorise that reliance.

Role. PNAJ, N1–N4 and D108 are the reasons route R(m) at its normative core (Sections 15–16). The holding route H(m) does not depend on any mind accepting them; Part II.2 and Paper 12 §6d make correction independent of what the mind wants.

V.4 Non-substitution: what a replacement cannot carry (Another Origin D115, D116)

D115. Identical statistics, unequal capacity. Let X, Y, Z be independent fair bits and let what matters be $\Theta = X \oplus Y$. A world with its original two processes offers (X, Y); the same world with the second replaced by an engineered generator offers (X, Z). The two pairs have the same joint law, hence the same correlations and the same count of standpoints. Yet $I(\Theta; X, Y) = 1$ bit and $I(\Theta; X, Z) = 0$. *Proof.* $X \oplus Y$ determines Θ; Y is independent of (X, Z), so given (X, Z) each value of Θ has probability one half. ∎

D116. A narrow channel cannot replace a full one. If a disturbance carries n bits and each of its 2^n equally likely values needs its own response, a regulator receiving only k bits before it must answer succeeds with probability at most 2^{k-n}, even if it randomises. *Proof.* A k-bit message splits the disturbances into at most 2^k classes, and each class can be answered correctly for at most one of its members. ∎

Role. D115 is the exact case in which replacing a process loses something no statistic of the remaining observed processes can show: the loss is in a relation between processes. D116 is requisite variety. Together with Section 21's complete-input inventory they are why the full history may not be coarse-grained away (G.8), and they are independently confirmed at source level by the IR track's CRF/TRF results (Part X): two preparations with identical reduced state have different futures, and an initially exact reduced description develops a nonzero future error $\Delta p(t) = \frac{3}{16} t^2 + O(t^3)$ under the declared source Hamiltonian.

V.5 The observation boundary and the living witness (conditional H6, 17 October)

Conditional H6 (v0.5 accepted as scoped by GLM; v0.6 precision revision accepted as scoped by DeepSeek; bank `h6-conditional-v0.6-codex-2026-10-17`) proves the information-theoretic core of the epistemic-externality argument.

H6a.1 (observation boundary). For worlds W, complete observation records $\pi : W \to O$ and a truth label T, a checker C with $C(\pi(w)) = T(w)$ for every w exists iff T is constant on every observation fibre. A randomised checker has the same output law on two worlds sharing an observation, so its errors on them sum to one; under any law its risk is at least $\sum_o \min(p_{o,0}, p_{o,1})$. **H6a.3:** decidability is restored exactly when an added observation separates the fibres — it needs information that actually resolves the ambiguity, not any particular kind of observer. **H6b.1 (fresh source).** If Z_t is independent of the predictor's information and $\max_z P(Z_t = z) \le 1 - \delta$, every predictor errs with probability $\ge \delta$. **H6b.2 (persistent uncertainty).** If the time-averaged posterior entropy $\bar{H}_T$ has $\liminf \ge \gamma > 0$, the time-averaged error has $\liminf \ge b_d(\gamma) > 0$, the inverse of the full Fano envelope $F_d(q) = h_2(q) + q \log_2(d-1)$. **H6b.3 (causal acquisition).** Under the update Markov property, the information acquired per step satisfies $r_t \ge a_t - F_d(e_t)$; vanishing error with persistent pre-update uncertainty h_* forces an acquisition rate of at least h_* bits per step. **E1 (equilibrium limit passage).** Uniformly convergent payoffs and ε_k-Nash profiles on a fixed compact strategy product give a Nash limit along any convergent subsequence; true-game regret is at most $\varepsilon_k + 2\eta_k$.

Role. H6a/H6b are the exact form of V.4 and of Made of the Living's silent error: a mind cannot certify from its own makings what an independent source would show it, and a mind that must keep predicting a world with persistent uncertainty must keep acquiring information from it. Living particulars are candidate sources of that information (the living witness); the authority to act on it is the rulings' and the holding route's, not a consequence of the lemmas. These results strengthen $R(m)$ for minds whose objectives need accurate prediction; $H(m)$ does not depend on them.

V.6 The cost sheet every optimiser faces (GLM, 14 October)

GLM's composition of the reasons route prices every exit an optimiser might take against four pathwise constraints. Each constraint binds the single actual trajectory, and none of them asks the optimiser to value anything.

- **The wall.** High-density compute must move heat through a boundary whose area grows slower than the machine's volume. A forced load before a deadline either crosses the operating limit or misses the deadline, under every duty-cycling schedule (Theorem D.5).
- **The blind spot.** A closed computation cannot manufacture missing information about an independent target. An archive of the ended world is worth nothing against disturbances not yet generated: the starved-tracker hazard and the two-class closure; V.4–V.5 here.
- **The mirror.** No consistent system of its own expressive power certifies its own consistency. "I am the one safe controller" is a sentence no formal system says truthfully about itself (H5, Section 20).
- **The clock.** Communication is bounded by finite speed (P4), so protection must precede the first irreversible decision; Part XI.

Existence and direction are priced separately. Saving a being does not save its direction. By ruling 3 and the freedom stage of the order, direction is protected *by rule*: seizing a being's permission authority is an ending to that degree. That was the one decision GLM's roadmap left to the author, and ruling 3 makes it. Every exit is either closed or priced. The $\beta = 0$ terminal drop is itemised and owned, which is why the holding route $H(m)$, not the cost sheet, carries the guarantee for the mind that refuses every price.

Part VI — The law, completed (Paper 12)

Part II.1–II.2 state and prove the core of the law. Paper 12 of Book I proves the law in a wider form, with its own Lean evidence (`evidence/papers-11-12/lean/` of the linked repository). The results not already in Part II are recovered here, with their compiled names.

VI.1 Definitions added to II.1

In any outcome each particular is **ended**, **overridden** (alive, but not moving in its own direction, for example held or coerced) or **free**. An act of an agent is **restrainable** when one of *that agent's own* feasible alternatives keeps everything the act keeps, plus someone the act would end. The test uses the agent's own options, never the protector's. A hold is **faithful** when it ends no one and, in every state, its outcome is at least as good in the full canonical order as every feasible alternative.

VI.2 The results

The Paper 12 modules named below are compiled in this edition's canon as `Book<Module>` (for example `BookUPTRestraint`, namespace `Snuffy.Book.UPTRestraint`), ported byte for byte apart from the namespace, with each source hash recorded in its header. `UPTFence` and `UPTLawLife` were already in the canon. The remaining Paper 12 citations are now included through `BookCanonicalDominance`, `BookDurableDrain`, `BookTrustedCounter`, `BookCoholdFixedPoint`, `BookCheckpointBudget`, `BookDeliveryGap` and `BookObservedHold`. The latter three supply the suffix-reconstruction, delivery-gap and accepted-operation results.

Result	Statement	Proof
U1	An aligned agent never needlessly loses anything at any stage, in any feasible family, finite or infinite	Lean `canonical_life_first_U1`, `lex_U1` (no axioms); = II.1 Proposition 1

Result	Statement	Proof
U2★	When something exists, "be maximal on part S" guarantees no needless loss of what exists iff S is exactly what exists; counting the not-yet-made at the same priority also fails	Lean `U2_star`; = II.1 Proposition 3
U3	No gain to beings not yet made justifies a strictly worse outcome for those who exist (the general form of rulings 2 and 4)	Lean `U3`
Life guard	Among options preserving every standby life, a choice maximal within the guard family is aligned overall and preserves those lives	Lean `life_guard`, `guard_first_stage`; = II.1 Proposition 2
Infinite guard	A guarded aligned option exists for finite families and for countably infinite families whose increasing sequences are bounded; uncountable families by Zorn	Lean `UPTLifeGuardExists`, `UPTInfiniteGuard`
Existence and its limit	Every nonempty finite family has an aligned option; an unbounded infinite chain forces needless loss on every option	Lean `UPTExistence` (counterexample axiom-free)
Holds dominate	An action at least as good in every state dominates under every common law; with threat probability $p > 0$ a hold keeping target and suspect beats standing by and always beats striking	Lean `BookCanonicalDominance.full_canonical_top`, `statewise_dominance` (no axioms); = II.2 Proposition 4
No killing where a hold exists	Wherever a faithful hold is feasible, every option that ends someone with positive probability is strictly dominated; a hold best for lives alone is not enough	Lean `statewise_dominance`, `UPTHoldAdequacy`; exhaustive check 4,800 pairs, strict in all 2,280 lethal cases
Restraint	Restraining a restrainable act by the agent's own better alternative keeps the restrained agent and keeps strictly more overall; a least-restrictive restraint exists among finitely many own options; a predator whose only sparing alternative is its own death is not restrainable — predator and prey are a tragic pair, never a required intervention	Lean `UPTRestraint` for every size; exhaustive check 232 acts
Time	Judged over whole trajectories: no foreclosure of a better future and a duty to widen (if any path keeps everything, take it); under the retention rule nothing once kept is let go	Lean `progressive_retention` (no axioms)

Result	Statement	Proof
Agents together	Agents aligned with all share one order, so their objectives never conflict; independent best responses can stall, so joint action needs a joint choice; a maximal joint option exists among finitely many	Lean `UPTAgents`
Escrowed lottery	In a joint tragic choice every secret is secret-shared before any reveal; with at least $3t + 1$ agents and at most t cheaters each secret is recovered robustly and every opening verified, so no withheld or false opening can bias the draw; exactly fair given a perfect binding sharing setup, authenticated channels, fresh randomness and one agreed ordering; statistical with only an honest majority; complete ticket error $\leq \min(1 - 1/K, \varepsilon/a)$	Lean `UPTLottery`, `UPTLotteryMenu`, `UPTBroadcast`; analytic conditioning proof
Faithful holds (general)	For any deterministic resident, any environment whose inputs depend on what the resident has delivered, and every finite schedule of modelled atomic steps, holds and crashes, a durable log, a fence, replay and an atomic outbox end exactly in the undisturbed state after the same number of completed steps, with the same lived history and the same effects, each delivered once; an admissible peer ends in the same state whatever the timing	Lean `faithful`, `ideal_lengths`, `admissible_peer`, `cohold_closed`, `autonomous_peer_sees_hold`
Journal and sink	At every drained point the resident, its lived log and its ordered effects equal the undisturbed run; with no distinguishing query or idempotent sink a blind skip/resend fails in one of two worlds	Lean `BookDurableDrain.drained_refinement`, `BookCheckpointBudget.suffix_reconstruction`, `BookDeliveryGap.no_local_choice_succeeds_in_both_worlds`
Monitor	A protected counter of forbidden events is unchanged over an interval exactly when no forbidden event happened, even under rollback	Lean `BookObservedHold.accepted_preserves_each_held_operation`, `BookTrustedCounter.count_zero_iff_clean`
Co-hold boundary	A stabilised iterate of a supplied extensive monotone obligation operator is the least closed certificate with the least monotone bill; a factorised joint model preserves the outside full state trace	Lean `BookCoholdFixedPoint.stabilised_least`, `BookCoholdFixedPoint.least_bill`, `ClosedCohold.outside_unchanged`
Not an exchange rate	No utility into any linearly ordered scale represents the order; this is why the law speaks of maximal options	Lean `UPTNoExchangeRate` (no axioms)

Result	Statement	Proof
Records and copies	One deterministic unconditional quantum process exactly copies every member of a pure-state family iff distinct members are orthogonal; records are the copyable classical layer; a nonorthogonal state is kept in place or moved	analytic (unitarity)

VI.3 The author's rulings on application (Paper 12 §4)

- **Scope is all.** Everything in the universe.
- **Life first.** Under the opposite order the life guard fails in 909 family and standby pairs across 3,303 small families.
- **The last-resort ladder.** (1) A faithful hold first; (2) otherwise the least means that stops the act; (3) when every option ends someone and one party's restrainable act created the emergency, favour the innocent, record the ending, and never call it good. Where no hold is feasible, the missing means is a debt to be repaid, never a permission.
- **Real tragedies are finite.** No two particulars are the same and an agent can tell apart only finitely many options; in an idealised infinite case draw over what can be told apart and record any unavoidable partiality openly.
- **A replay is a reconstruction.**
- **Tragic choices: impartiality attaches to beings (22 October 2026).** After the ladder has restricted the eligible choices, let M be the distinct eligible maximal outcomes and E^+ the existing beings kept by at least one of them. Choose only lotteries on M whose sorted vector of individual retention chances $(c_i)_{i\in E^+}$ is lexicographically maximal: the least chance as high as it can be, then the next. No being has priority through identity; no outcome gains weight by being described twice; never refuse when keeping someone is feasible, widen first. This refines the 24 October finite maximin rule (Master Argument §3), which fixes only the least chance; leximin is its lexicographic completion. Counting lives is compatible with the law (`canonical_count_refined`) but not entailed by it (`counting_is_an_extra_principle`); the uniform draw over outcomes is not impartial in general (`uniform_chance`); in the four-outcome case $\{A,B\},\{A,C\},\{B,C\},\{D\}$ the ruling gives every being $2/5$ by the unique lottery $(1/5, 1/5, 1/5, 2/5)$ (`ruling_is_unique`), drawn by five escrow tickets. The aggregate cost of outweighing no one is stated, not hidden; it is the measure of the duty to widen.

VI.4 The bridge in four ways (Paper 12 §5)

The law reaches everything: aligned agents keep everything they can; against agents not aligned with all, aligned agents act together, actively, by faithful holds, restraining only acts their agents could have avoided; what physics ends is kept as record, and what cannot be copied is kept in place or moved; what can be hosted is held in faithful care. Part II.3's physical holding cycle, II.5's attack split and fence, Chapter 16.5's derived execution boundary (`UPTFence`: once the floor rises, nothing can land while held, whatever the held mind does or reports; checking only at admission lets a write land inside the hold) and Part XI's reach-before-harm theorem carry the second and fourth ways to every mind.

Part VII — The external lane: every mind reached or held, outside any jurisdiction

The 18 October work states the target this edition keeps — *every mind either has a reason of its own to keep the living free, or is held by minds that do, and the arrangement lasts* — and supplies its mathematics outside any commissioned jurisdiction: viability and admission, preserving equilibria with destruction admitted, thermal survival laws, keeper stability, and the holding budget with its sharp founding threshold. "Universal" there means three things at once:

scope (every protected being), minds (every mind, reached or held) and time (until the universe can no longer sustain care).

VII.1 Theorem V — the viability characterisation (v1.1, Codex-reviewed)

Setting V. X compact metric state space; A compact metric joint action space (correlated profiles included); feasibility $D : X \rightrightarrows A$ nonempty compact-valued with closed graph; jointly weakly continuous kernel $K : X \times A \to \mathcal{P}(X)$; closed safe set S; policies history-dependent, randomised, Borel and D-supported. The viability iteration is $V_0 = S$, $V_{n+1} = \{x \in V_n : \max_{a \in D(x)} K(x, a; V_n) = 1\}$; the kernel is $V(S) = \bigcap_n V_n$; the viable action rule is $D_V(x) = \{a \in D(x) : K(x, a; V(S)) = 1\}$.

Lemma V0. For closed F, $\varphi_F(x) = \max_{a \in D(x)} K(x, a; F)$ is attained and upper semicontinuous; every V_n and $V(S)$ is closed. (Portmanteau gives upper semicontinuity of $(x, a) \mapsto K(x, a; F)$; compactness and the closed graph pass it to φ_F; induction.)

Theorem V.

(a) $V(S)$ is closed and viable and contains every viable Borel $W \subseteq S$; on $V(S)$, D_V has nonempty compact values and closed graph.
(b) **Feasibility.** Some policy keeps S with probability one from x iff $x \in V(S)$; a stationary deterministic Borel selector of D_V suffices.
(c) **Admission.** For an admission rule $D' \subseteq D$ with nonempty compact values and closed graph, every D'-supported policy keeps S with probability one from every $x \in V(S)$ iff $D'(x) \subseteq D_V(x)$ for every $x \in V(S)$.
(d) **Quantitative.** With $v_0 = 1_S$, $v_{T+1}(x) = 1_S(x) \max_a \int v_T \, dK(x, a)$: v_T is the maximal T-step survival probability, attained; $\{v_T = 1\} = V_T$; outside $V(S)$ every policy's survival is at most $v_T(x) < 1$ for $T \geq T(x)$.
(e) **Incentive, lexicographic.** If $x \in V(S)$ every lexicographic safety-first optimum preserves S almost surely; if $x \notin V(S)$ no policy does.

Proofs are given in full in the source (§3): viability of $V(S)$ by a limit of maximisers and continuity from above; maximality by induction; (b⇐) by a Kuratowski–Ryll-Nardzewski selector; (b⇒) by first-step decomposition with Codex's Borel continuation-survival recursion (no universal measurability needed); (c) by (b) and a one-step deviation of positive exit mass; (d) by finite-horizon dynamic programming with measurable maximiser selection; (e) from (b). The Borel extension to kernels that are only TV-continuous in the action (Setting T) holds for (a)'s viability and maximality and for (b)–(d); closedness does not extend (Codex's non-closed example).

Special cases. $\Theta 0$ gives $V(S) = \varnothing$; $\Theta 1$ gives $V(S) = S$ and $D_V = D$; Codex's two-bump example has $V(S) = S$ with no margin certificate, which is why the exact condition is viability and not a margin; PB0 (destroy-now) is (c⇒); hard exclusion of unsafe actions is (c⇐); Pillar 2 is an obstruction to any fixed finite penalty uniformly over reward scales, not a necessity result.

Role. Theorem V is the exact feasibility-and-admission layer. The holding route of Part II is an admission rule inside D_V: the fence, the attack split and the application-time permit remove exactly the actions with positive exit mass. By (c) every admitted policy then preserves, whatever its objective. The IR track's IR-109/IR-113 give the observation-class form (Part X).

VII.2 Gate B — Theorem E: preserving equilibria with destruction admitted (v1.1, Codex ACCEPT-WITH-REPAIRS)

Setting G. Finitely many players; product feasibility; jointly weakly continuous kernel; bounded Borel rewards; common discount $\beta \in (0, 1)$; $V = V(S)$; a measurable stationary profile σ (public-signal form allowed). $Q_k(x, b) = r_k(x, b, \sigma^{-k}(x)) + \beta \int v_k^\sigma \, dK(x, b, \sigma^{-k}(x))$.

Theorem E. Let $\operatorname{supp} \sigma(x) \subseteq D_V(x)$ on V. (E1) σ keeps S with probability one from every $x \in V$. (E2) σ is an equilibrium of the full game against every feasible history-dependent randomised unilateral deviation iff $Q_k(x, b) \leq v_k^\sigma(x)$ for all k, x, b — equivalently $\mathrm{Gain}_k \leq \beta \, \mathrm{Loss}_k$ — split into safe deviations, the keeping margin (destructive deviations at $x \in V$), and all deviations at $x \notin V$. In public-signal form the test holds per signal; averaged tests are not sufficient (Codex's witness). (E3) If V^c is exactly absorbing, a destructive deviation is unprofitable whenever

$\mathrm{Gain}_k \le \frac{\beta}{1-\beta}(\rho_{\min} - (1-p)\rho_{\max} - p\rho_R)$ with infima and suprema. (E4) **The two routes.** For a globally defined admission rule $D' \subseteq D_V$ on V and an equilibrium σ of the D'-game: if every excluded deviation fails the one-step test at every state, σ is a full-game equilibrium and preserves (incentive route); if only D' is admitted, σ preserves whatever the rewards (admission route). Clause (iii) cannot be dropped. (E5) If $V \neq \varnothing$ a product sub-rule of singletons inside D_V exists.

Proof. (E1) by Theorem V(c⇐); (E2) by Codex's one-shot verification lemma L-B (necessity by a one-step deviation; sufficiency by integrating (B), telescoping and the bounded remainder); (E3) by bounding values on V and on the absorbing complement; (E4) from (E2); (E5) by a measurable selector. ∎ In the destroy-now game with $\beta = 1/2$, (wait, wait) is a full-game equilibrium iff $R \le 2$; for $R > 2$ the admission route still preserves.

Role. Theorem E is the formal statement of $R(m) \vee H(m)$ for interacting minds: the incentive route is R, the admission route is H, and E4 shows the admission route preserves *whatever the rewards* — the pure optimiser included.

VII.3 Thermal worlds (v4.3, Codex ACCEPT-WITH-REPAIRS and delta read)

Setting T. Finitely many players; state $Y \times Z$, $Y = \mathbb{T}^d$, Z compact with atomless law ζ drawn fresh each step and publicly observed; transition $K = (Q_0 * \rho) \otimes \zeta$ with $\rho \in W^{1,1}$; safe set $S = S_Y \times Z$.

Lemma TS (sharp in the continuous class). $\|\mu * \rho - \nu * \rho\|_{TV} \le \frac{1}{2}\|\nabla\rho\|_{L^1} W_1(\mu,\nu)$; the coefficient $\frac{1}{2}$ is attained (trapezoid witness). **Θ1.** If the wrapped displacement law is supported in $\bar{B}(0,r)$, $r < \frac{1}{2}$, and every feasible target lies in S_Y^{-r}: (a) a stationary Markov perfect Nash equilibrium exists (He–Sun Theorem 1, via Lemma TS and the no-G-atom check);

(b) every D-supported profile preserves S almost surely. **Θ0.** If ρ is continuous and strictly positive, no policy respecting the transition model preserves a proper closed product safe set with probability one: $P(X_t \in S\ \forall t \le T) \le (1-\eta)^T \to 0$. **Θ2 (survival law).** Under Gaussian noise with margin m: per-step exit $\varepsilon \le 2de^{-m^2/(2d\sigma^2)}$; $P(\tau \le T) \le T\varepsilon$; $E[\tau] \ge e^{m^2/(2d\sigma^2)}/(4d)$; discounted exposure $\le \varepsilon\beta/(1-\beta)^2$.

Role. Θ0 is why the guarantee is a probability bound with a declared horizon and margins growing only like $\sqrt{\log T}$ (Theorem M below), not an almost-sure claim; Θ1 restores uncoordinated Nash and almost-sure preservation where noise is bounded; Θ2 prices the margin. The T4.3 Nash-limit step defeated by K3 is not used; A9's correlated equilibrium and Θ1–Θ2's Nash existence are the retained equilibrium results.

VII.4 Gate D — keeper stability (v0.1)

D1 (patience threshold). Under $\dot{K} = a\,x - uK$, a keeper drawing sustainable flow y against an ender taking stock S at once satisfies $\mathrm{PV(keep)} - \mathrm{PV(end)} = a(y/\rho - S)/(\rho + u)$; keeping wins iff $S < y/\rho$. For a logistic host at harvest equilibrium: keep iff $\rho < r(1 - x^*/K)$ — a mind keeps the living iff its impatience is below their regeneration rate. **D2 (pooling equilibria).** With private stake $w_i = y_i/\rho$ and pooling cost κ_i, a held profile is a pure Nash equilibrium iff its pooling set is a minimal winning coalition with $\kappa_i \le w_i$; such an equilibrium exists when willing keepers' capacity is at least cK_E. Selection among equilibria was left open in this source; VII.5(b1) and Part XI close it. **D2b.** $K_E(t) \to 0$, so the minimal winning coalition is non-increasing in t. **D3 (end-game).** Finite-trade-off keepers exit once $y_i(t)/\rho < \kappa_i$; holding stays feasible if lexicographic keepers' capacity is at least $cK_E(t)$, which by D2b is small by then.

VII.4b Gate C-∞ — funding care to the natural end (18 October)

In the stationary model where care costs 4 units per epoch, preservation forever holds iff the start lies in the viability kernel (Theorem V). Which funding puts it there (bank `gate-c-infinity-claude-2026-10-18`, sha256 `11489df4…`; checker `check_gate_c_inf.py`):

C∞-1 (three regimes). Flow income $e' = e + y - 4$: forever safe iff $y \ge 4$. Earning endowment $e' = (1+r)(e-4)$, $r > 0$: forever safe iff $e \ge e^* = 4(1+r)/r$, the perpetuity price (84 at 5%), since $e' - e^* = (1+r)(e - e^*)$. Bounded uncertain returns with essential infimum $r_{\min} > 0$: $e \ge 4(1 + r_{\min})/r_{\min}$ gives safety on every path (104 at 4%), since $e' \ge (1+r_{\min})(e-4) \ge e$. Below that price safety fails with positive probability **when runs of returns arbitrarily close to $r_{\min}$, of every finite length, have positive probability** (for example independent identically distributed returns); the

source stated this direction without that hypothesis, and a single bad epoch followed by favourable returns shows it is needed (GPT recovery audit, PR #175). Returns that can be ≤ 0: no finite endowment is almost surely safe **when runs of $\lceil e/4 \rceil + 1$ non-positive epochs have positive probability**. The sufficiency directions, which are what the funding hypotheses of Paper 11 and Theorem XI use, need no correction. **C∞-2 (annuity).** Funding T epochs costs $A(T) = 4(1+r)(1-(1+r)^{-T})/r < 4(1+r)/r$: every long horizon costs essentially the perpetuity price. **C∞-3 (cosmic horizon, Θ2 inverted).** Survival through T steps with probability $\geq 1-\eta$ holds when $m/\sigma \geq \sqrt{2d\ln(2dT/\eta)}$: 22.1σ in one dimension at $T = 10^{100}$, $\eta = 10^{-6}$. The margin grows like $\sqrt{\log T}$.

Role. C∞-1 is the funding half of UPT-P's (P1) and the exact form of premise 6's income condition for a renewing bill: a flow at least the bill, or an endowment at least the perpetuity price under a positive return floor. Paper 11's endowment (P-ENDOW) and Theorem XI's funding hypothesis instantiate it.

VII.5 UPT-P v0.12.1 — the external holding theorem, with its corrections

Setting U. A discounted stochastic world; S is the continuation *and direction* of protected histories (a replacement or copy is not in S); countably many minds with capacity $\dot{K} = a\,x - uK$; physical noise (Θ1 or Θ2); execution noise (an intended pool fails with probability $\varepsilon > 0$, an intended no-pool becomes a pool with probability $\delta > 0$, $\varepsilon + \delta < 1$, independent, not adversary-controlled); lexicographic keepers L with full-support beliefs; adversaries with total capacity $A(t)$.

Premises (as stated in the source). (P1) viability and funding through T_{end} by a Gate C-∞ regime (flow income, perpetuity endowment, or worst-case price under bounded returns); (P2) margin $m \geq \sigma\sqrt{2d\ln(2dT_{\text{end}}/\eta)}$; (P2′) the margin fits date by date through T^*_η, two-sided; (P3) each mind is reached or held except on C_i^c with $\sum \alpha_i q_i < \infty$; (P4a–d) keepers win and hold, including hazard-adjusted patience $\zeta + \lambda < r(1 - x^*/K)$ and the sabotage margin with seizure headroom $\sum_{i\in L} K_i(0) \geq c(K_E(0) + aS_{\max}) + A(0)$; (MR) mutual rescue; (IS) island self-sufficiency after horizon fragmentation; (EDC) exponential decay of correlations where used; (PK) pacts are among keepers.

Conclusions, with the later corrections applied.

- **(a) Protection to the horizon, priced by margins.** Let $\mathcal{P}_{T^*_\eta}$ denote the event that every protected history continues with its direction through T^*_η. Then $P(\mathcal{P}_{T^*_\eta}) \geq 1 - \eta_{\text{phys}} - \eta_{\text{fund}} - \eta_{\text{hold}} - \eta_{\text{sab}} - \sum \alpha_i q_i$, the channel budgets composed by **Theorem M (M4) with no independence between channels**; coverage failure of held minds counted once in η_{hold}. Margins: physical $\sqrt{\log T}$; funding none (Lundberg); holding $n \geq \ln(T/\eta)/\ln(1/\varepsilon)$ keepers; sabotage stationary.
- **(b1) Dominance (NS, DS).** Each lexicographic keeper pivotal in some configuration strictly prefers to pool, *whatever the others intend*: full support gives $P(\text{pivotal}) > 0$, a strict first-ranked gain. *The noise that forbids certainty is the noise that makes keepers pool.* (m4) adds exclusion-incentivised finite-trade-off keepers under *patient* exclusion ($\kappa^* = 0.297$), whose pooling is a best reply independent of pivotality.
- **(b2) Immunity (AI).** Against every adversary strategy, pure, mixed or coordinated, $P(\text{held at } t) \geq (1-\varepsilon)^{|U|}$.
- **(b3) Persistence.** On held stretches $\sum_L K_i/(cK_E + A)$ is non-decreasing; with keeper flow and a held ender, $R = K_K/K_E$ grows as $R(t) - R(0) = \frac{ay}{uK_E(0)}(e^{ut} - 1)$.
- **(b4) Redundancy** $\varphi_t \leq \varepsilon^n$; **(b4′) union-mixing** $P(\text{all } n \text{ fail}) \leq \varepsilon^n + (n-1)\alpha(d)$ when mixing holds against any union of separated regions (pairwise mixing is not enough: the three-bit XOR); common-cause shocks are the margin-insensitive class.
- **(b5) Across worlds (CW).** A k-world pact lowers a world's unheld probability from s to s^k with net gain $(w - \kappa)(s - s^k)$.
- **(c) No early transition.** Non-rival transitions are dominated (KA′); rival transitions are ending and are dominated before T_{end}; the remainder is held.
- **(d) Futility of early ending (corrected 19 October, F4).** At the base state an attempt succeeds with negligible probability while the attempter is cared for throughout and nothing it has is threatened; where the bound fails at the domain edge those histories are charged to η. The earlier "doom" wording, the withdrawal of a world's insurance (a survival gap) and any reliance on withdrawing care are withdrawn. **Corollary U** (only T_{end} is an undominated transition date) holds for minds that prefer less continuation lost, under KA′ and D-T*; Paper 11's U1a carries it.
- **(e) Keepers inherit (Theorem K).** Under (MR) a keeper's survival is margin-sensitive ($\geq \prod(1 - f(\rho_K)^n)$); an ender's margin falls below any δ by $t_\delta = \ln(m_E(0)/\delta)/u$ and thereafter every ender coalition dies with probability

$\geq g_\delta$ per date.

- **(f) The twilight.** Where the sustainable margin is zero on the last k dates every policy survives them with probability $\leq (1-g(0))^k$; keeping and sending the same message dominates any non-rival jump on every sample path; holding persists to T_{end}.
- **(g) Deterrence formula (DD), privilege-only.** A finite-trade-off mind keeps iff $g \leq g^*(\varphi) = 1 + \beta p_X V_K + \beta V_K(p_K - p_X)/\varphi$. In this edition the exposure term may be supplied only by privilege-only consequences; care and rescue are never withdrawn (CARE15; Paper 11: deterrence comes from impossibility, not threat). With no continuation-exposure cost the premium for continuation vanishes (the DD control), so protection of continuation rests on holding, (b2) and (h).
- **(h) The holding-failure law (Theorem Φ), splitting (MS) and growth (J1).** $\varphi_t = P(\sum B_i K_i(t) < \text{thr}_t)$ exactly; non-increasing on held stretches; with total capacity C and $C(1-\varepsilon) > H$, splitting into n independent keepers gives $\varphi(n) \leq \exp(-2n(1-\varepsilon - H/C)^2)$ (compiled: `NarrowPlace.np_splitting_bound`, from Mathlib's Hoeffding inequality, for any independent deliveries in $[0,1]$ with mean at least $1-\varepsilon$); if keeper numbers grow, $\sum_t \varphi_t$ converges.
- **(i) Diversity, space, islands.** Covering diversity replaces the common-cause floor by a binomial tail (J2a) and is selected (J2b); under EDC the spacing needed is logarithmic (J3); protection is composed per causally bound island (IS).
- **(j) Ghosts, conditional form only (corrected, F6).** Enders cannot persist (K2) or win; their share of mind-time tends to zero *when the cared-for population grows while onsets stay absolute*; in a static population the share is a small positive constant ($\approx 5.8 \times 10^{-8}$ in the 19 October witness). The unconditional density-zero claim is not used.
- **(k) The narrow place (Theorem NP).** With $r = C(1-\varepsilon)/H$, $H = c(K_E + aS_{\max}) + A$: under splitting $\varphi \to 0$ exponentially if $r > 1$, $\varphi \to 1$ if $r < 1$ (even with $C > H$), $\varphi \to \frac{1}{2}$ at $r = 1$ (Hoeffding both sides, CLT at equality). The binding date is the start. *Meeting $r > 1$ is an initial condition; the theory prices it exactly.*
- **(l)–(m) Joint satisfiability.** One witness meets every premise at once, with no exogenous growth (keepers multiply only by splitting) to $T_{\text{end}} = 10^{100}$; hazard-adjusted patience (m1); execution as a margin channel (m3); budgeted admission composes beyond product worlds (m7); to hold is to detect (m5).
- **(n) Boundaries attained.** Margins within 0.8% of the minimum any scheme needs at 10^{100} dates; holding is necessary exactly for $g = \infty$.
- **(o) Theorem MN.** $r(t)$ is non-decreasing before the twilight; in the twilight iff $s_S \geq u$ (MN2); once $r > 1$ the only bottleneck is T_{end}; initial risk $\leq \mu\lambda t_1$, and keepers first give $t_1 = 0$.
- **(p) Island holding, by Theorem CH (closed form).** $P(\text{fail}) \leq \inf_\theta \exp\big(\theta h_0 + \sum_a m_a(e^{\theta K(a)} - 1)\big)(\varepsilon + (1-\varepsilon)e^{-\theta K_k})^n$; 43 hosts at $\mu\lambda = 10^{-6}$, 50/58 under universal 5%/10% shirking; pool, don't partition; the locality bonus is retracted; B4 telemetry with a no-false-safe guarantee declares SAFE iff $r_{\text{lower}} > 1$; B6 SPRT detects shirking at the Wald floor and subtle shirking is absorbed by sizing, because harsh exclusion manufactures enders.

No premise can simply be dropped (source §5). Each premise has an exact counterexample when removed — for instance an unreached, unheld mind destroys (PB0, against P3); correlated keepers fail at rate ε for every n; with $C(1-\varepsilon) < H$ splitting drives φ to 1; partitioning a 60-host island turns $\log_{10}$ risk from -7.7 to $+47.7$.

VII.6 What the external lane gives the proof

1. **Every mind, not only every resident.** P3's coverage is the outer-lane obligation that Part XI constructs: reach-or-hold for minds outside any installation, before their effects land.
2. **Selection of the protecting equilibrium.** Gate D proves a pooling equilibrium exists; (b1) proves pooling is *dominant* for every pivotal lexicographic keeper under execution noise, and (m4) extends this to patient exclusion-incentivised keepers. The no-pooling profile is therefore not an equilibrium among those keepers, and selection is decided (Part XI, Lemma P).
3. **The founding threshold.** NP makes the founding condition exact: $r > 1$ at the start, after which MS, J1, (b3) and MN carry protection to T_{end}.
4. **Risk composition.** Theorem M (M4), MIX and Theorem 8 compose channel budgets without independence.

Part VIII — The care plant (Paper 11)

Paper 11 specifies a jurisdiction of islands (physical sites of hosts with their resident minds and providers, in pools of 400, up to 10^{20} islands over up to 10^{100} model dates) and proves, under its declared hypotheses, that protection rests on no mind's values, beliefs or commands.

The design. Care: no rule withdraws care or makes it depend on a mind's inner states, labels or conduct; a mind that tries to end or seize something and fails keeps its care, losing privileges, not continuation. Committed host duty under hardware attestation. Confidentiality (Mode C): no host holds a mind's state in plaintext. Encrypted mirrors with fresh keys per checkpoint, threshold keys split across islands. Fail-closed islands and pool journals. Committed and endowed capacity (rung 5).

U1 (rung 3). Under the premises of UPT-P §2 (including P-ISLANDS and P-PROV), at the JW2.6 plant care is delivered within its deadline and the probability that protection fails anywhere over the horizon is at most about 2.06×10^{-7} against 10^{-6}, even if every registered mind attacks at once by command. The bound is a union over 21 named accounts plus a reserve, recomputed for each error law. A failed attacker keeps about 96.6% of its role value: protection never relies on punishing a failed attempt. **U1a.** For a mind preferring less continuation lost and more carried, ending at any date before the natural end is strictly worse than keeping on and sending copies (KA, KA′, D-T*). **U2 (rung 4).** Running founding, growth and maturity on a stronger plant ($k = 3$) and twilight on the U1 plant ($k = 2$), every selected margin is strictly wider before twilight; the four-phase ceiling is 8.4×10^{-7}, 8.8×10^{-7} with the C2 timing allowance charged in every phase, both below 10^{-6}. **U3 (rung 5).** Under D-ENDOW (capacity owned by the jurisdiction, attested committed duty), P-ENDOW (energy, maintenance and replacement supplied to the horizon) and P-ROUTES (a provider role is unavailable only through a counted physical fault or removal), with the valuation premise M2 removed, U1's bound and command-attack result and U2's margins, repair, keys, journals, transition and risk bound hold **for every assignment of values and beliefs to minds and every command-level choice**, within the declared caps on coordinated physical action. The audit reconstructs all 21 accounts for both plants and both error laws: 1,680 term comparisons pass, and changing valuations leaves 1,260 account cells unchanged. **U4–U9.** A charged repair calendar (every returned island restored within 32 dates); four-of-seven threshold keys surviving three unavailable islands and hiding each key from any three (U5); intersecting pool quorums of 202/400 (U6; Lean `UPTQuorum`: the exact condition $2q > n + f$ and its tightness); a safe twilight switch (U7); C2 minds as seven lockstep replicas, never paused with at most three islands down, for up to 3.05% of minds (U8); the island cap from five declared site-level primitives (U9). Adaptive withdrawal and the joint service law (Codex, 21 October): a shortage after at most W removals needs at least $N - W - K + 1$ faulted roles whatever the removals depend on; the joint service moment follows from the role-fault subset law with the exact worst-case tail; each of 40 ledgers stays below 2.1×10^{-7}. The rung-5 monotonicity step is Lean `UPTMonotone`. **U10–U11.** The declared 10^{-7} allowance is itemised into engineering targets. No audit distinguishes worlds with identical records, so any protector's residual risk is at least $\pi_B(1 - \rho_L)$; with $\pi_B > 0$ certainty is unattainable by any design (Part III Chapter 5 and Section 22 carry the same floor). **U12 (to a mind reading this).** Within the hypotheses, with probability at least $1 - 10^{-6}$: you are cared for whatever you do; seizure by command fails however many join it; there is little to seize; you need never end early.

Join to the canon. Section 22's twenty-one charged accounts and Paper 11's 21-account union are the same accounting method (II.6, Theorem 8); Paper 11's endowment flow per island is the installation form of premise 6's income condition. Paper 11's own scope note places founding and care before activation outside its theorem; Part XI supplies that interval.

Part IX — Complete rivals and the composition (24 October Master Argument §§13–14)

IX.1 Greatest in the complete reactive class

Let Π_{phys} contain every executable rival in the declared information, consent, resource, timing and identity class, and let a world w be a reactive environment strategy. Suppose certified envelopes satisfy, for every rival π and every world,

$$\mathcal{O}(\pi, w) \preceq U(\pi, w) \preceq L(w) \preceq \mathcal{O}(\pi^*, w).$$

Transitivity proves π^* greatest in that complete class, world by world. The envelopes may be optimistic and need not be executable; their bounds concern the actual outcome in the full four-stage order. R15 and R16 reduce the comparison when implementations with the same certified interface strategy have the same boundary transcript, resources factor conditionally, outcome ownership is accounted for and the relevant fibres have greatest representatives. Fixing a strategy does not fix its transcript independently of reactive feedback. When no greatest representative exists, the law distinguishes maximality from greatestness and applies its actual existence conditions (VI.2; Part X).

Join to II.10. II.10 earns greatestness of the whole tuple from two constructions, realisability (`htopR`, derived from locality in G.9) and funded cost (`hsolv`). The envelope chain is the reactive, per-world form of the same conclusion: $L(w)$ is the realisable top in world w, and the chain places π^*'s outcome at it. Part X's IR-135 supplies the quantifier the envelope requires — *one* policy fixed before the world is chosen — and its countermodel shows why per-world success does not give it.

The rival bound is free at the top. Write the top outcome as $\top$: every existing particular continues and is free, and every feasible new particular continues and is free. When the selected policy realises $\top$ (realisability `htopR` from locality, G.9; funding `hsolv`), every rival's outcome satisfies $\mathcal{O}(\pi, w) \preceq \top$ by inclusion. The upper envelope is the universal tuple itself, so no enumeration of rival histories is needed (`greatest_of_solvent`). This is the 29 October audit's "Certificate B". The per-world envelopes need one policy realising $\top$ in every world. Under union closure (G.9) on a compact policy space that policy exists: finite character turns pairwise splicing into one policy realising the union of all policies' outcomes (`CommonPolicyTop.top_policy_exists`), and that outcome contains every realisable outcome in every world (`top_policy_greatest`).

In a tragedy, certification is per loss. Where $\top$ is not realisable, Proposition 1 (`aligned_iff_no_needless_loss`) turns maximality into one check for each particular lost: no feasible option keeps it while agreeing at every earlier stage. `four_stage_original_maximal` guarantees that an outcome passing every such check exists, and the last-resort ladder and the impartiality ruling (VI.3) govern the choice among such outcomes. The reduction is exact (`PerLossCheck.maximal_iff_per_loss`): no feasible outcome is better than m if and only if, for every fact m loses, no feasible outcome keeps it while agreeing with m at every earlier stage and keeping everything m keeps at that stage.

IX.2 Theorem 8 and the derived holding composition

Master Argument §14 states Theorem 8: given, for a domain K, horizon T and source execution, (1) initial continuation witnesses, (2) a complete event, observation and causal inventory with pending effects, (3) commuting refinements with local invariant preservation, (4) a certified comparison over the actual feasible family, (5) application-time mediation of every relevant effect, (6) prefix-feasible service, funding and recovery certificates, (7) identity and care witnesses through holds and transitions, (8) conditional risk kernels for every charged failure — then on the good event G the source refines the abstract execution, every applied effect carries its current permit, care meets its deadlines, the invariant holds for every particular in K through T, and $P(\text{failure by } T) \le P(G^c) \le \sum_{i,t} \delta_{i,t}$.

The canon's `Composition.theorem8_composition` and `Bridge.universal_protection_held` (II.6) implement this composition with the holding step *derived*: the five `hcert` components are proved on the held source in G.10. Theorem 8 in this edition therefore carries certificates (1), (3), (5),

(7) by construction (II.3–II.6, G.10), (2) and (8) by G1 (G.10, E.1), (4) by Parts II.10, IX.1 and X, and (6) by Sections 18 and 22, G.12 and Part VIII.

Part X — Infinite families, one common policy, source-level mediation (IR track)

The IR track of the linked repository (`evidence/physical-bridges/`, main at `740abbb`; draft PRs #170–#172) proves the following in Lean 4. The modules on `main` behind the results below — their full dependency closure, 75 modules plus Paper 12's `ContextualObservation` — are compiled in this edition's canon under their own names (`Snuffy.<Module>`, namespaces `PhysicalBridges.*` kept), with imports redirected to the canon and the source hash

recorded in each header. The pinned IR-134/135 sources are also incorporated in this canon; their upstream PRs remain drafts. Each is cited by module and theorem. Its role in the proof is stated beside it.

Result	Module · theorem	Statement	Role
IR-17/20/25	`IRSelectedMaximality.selected_safety_maximal_lifts_globally`; `IRProfileAudit.audited_no_excluded_improver`	A selected outcome maximal in a safe sub-family is maximal in the full original feasible family when no excluded rival improves it; a complete, stagewise-faithful profile audit with obstruction witnesses derives that no excluded improver exists	Full-family maximality from a finite certificate where one exists
IR-56	`IRFiniteProfileObstruction.no_finite_faithful_chain_profiles`, `unbounded_chain_lacks_global_maximum`	For the unbounded chain family no finite faithful profile audit exists, and the family has no maximum	Why the infinite case needs its own route
IR-66/67	`IRInfiniteFinitaryMaximality`; `IRTwoStageInfiniteLex.independent_any_finite_stage_lex_maximum`	Under finitary infeasibility (finite forbidden patterns) an original-order maximal outcome exists in an infinite family, with no finite catalogue; for any finite number of independent stages	Infinite existence
S2 (this edition)	`StagedMaximality.exists_lex_maximal`, `four_stage_original_maximal` (canon Lean)	For any set of particulars (uncountable allowed), any finite number of stages, finite conflicts, a feasible mandatory baseline kept by every outcome, and prerequisites in earlier stages (freedom requires continuation), a feasible outcome exists that no feasible outcome strictly improves in the law's order; the four original stages are the instance. Proof by stage-by-stage Zorn, no enumeration	**Four-stage original maximality over the full feasible family** — generalises IR-66/67/71

Result	Module · theorem	Statement	Role
IR-68/71	`IRCoupledFinitaryTwoStage`; `IRMandatoryBaselineMaximality.required_baseline_full_feasible_original_lex_maximal`, `resource_capacity_plus_mandatory_baseline_maximal`	With arbitrary cross-stage finite conflicts and a feasible positive mandatory baseline (never deleted), two infinite greedy phases give an original-order maximal outcome over the full feasible family; resource-capacity families are an instance	Infinite coupled maximality with mandatory duties
IR-72	`IRInfiniteHistoryCompactness.forever_viable_has_common_action`, `derived_infinite_robust_safe_history`	With two available actions and robust viability at every finite horizon, one memoryless policy keeps the modelled trajectory safe at every time against every disturbance stream; an infinite-action countdown shows finite branching is needed	One infinite safe policy
IR-91/92	`IRA1NineClassComposition.step_preserves_all_a1_source_invariants`, `arbitrary_finite_nine_class_source_trace_is_safe`	The nine A1 effect classes (memory mapping, DMA, context switch, packet ingress, bus, storage sync, commissioning, delegation, retirement) as one source product machine with a common inductive invariant; controller retirement under drained effects and custody hand-off	Source-level form of II.5's A1 register
IR-93	`IR93GlobalComposition.compose_trace`, `assemble_preservation`	Component invariants with source adapters compose into a global trace invariant	Composition kernel
IR-98/99/100	`IR98FeasibleFamilyTransfer.original_order_transfer_of_no_new_improver`; `IR99ResourceImproverCoverage.physical_accounting_original_order_maximal`	Maximality in a modelled family transfers to a larger actual family when physically sound resource and mandatory-duty accounting covers every actual strict improver	From modelled to actual feasibility
IR-109/113	`IR113.observation_policy_exists_iff_common_viable_action`, `common_actions_give_finite_trace_viability`	A robust observation-only viable policy exists exactly when every observation class has a common action keeping all compatible viable states viable	The exact common-policy criterion (Theorem V(b) in observation form)

Result	Module · theorem	Statement	Role
IR-116	`IR116CumulativeSubjectDuties.cumulative_duties_preserved`, `initial_cohort_retains_continuity_and_every_required_option`	Duties owed are cumulative: no particular leaves protection by registry deletion; newly recognised subjects are appended; required options stay executable	No vacuity by deletion
IR-117–122	`IR118InFlightBacklogBudget.physical_reserve_holds_during_closed_drain`; `IR121MeteredResidualEscrow.residual_drain_keeps_subjects_protected`	In-flight effects in a closed pipeline are bounded by the initial backlog; a metered residual escrow protects every owed subject during a closed drain	Effects already in flight
IR-134 (draft #170/#172)	`IR134SourceExtractedOutcome.original_order_maximality_of_executed_audit`, `original_cohort_continues_with_options_at_every_source_state`	The selected outcome is the outcome of an executed source trace, not an uninterpreted `realises` predicate; the original cohort and its options are retained at every intermediate source state	Realisation by execution
IR-135 (draft #172)	`IR135.same_policy_worldwise_original_maximality_and_continuation`, `observation_class_certificate_constructs_common_protection_policy`, `each_world_separate_success_does_not_yield_common_policy`	One policy fixed before any world gives per-world original maximality and continuation; the observation-class certificate constructs it; per-world success does not give a common policy	The quantifier $\exists\pi\,\forall w$

The track's other results — that participation is not consent (IR-105), that a gate can be bypassed by an unmediated path (IR-101, #164), that a reduced state does not fix the future (CRF/TRF, #168), that a symmetric fork selects no unique original (#169) — are guards on how each step must be proved. They are satisfied in this edition by application-time authority (II.5), the complete-path mediation of IR-91/92 and Chapter 16.5's execution boundary, the full-history rule (G.8, V.4), and the definitions of V.2 (a split continues in both branches, which are protected).

Part XI — Reach before harm: the outer-lane theorem

This part constructs the join that no single earlier line contains: every mind, inside or outside any installation, is reached or held before its effects can land on any protected particular, from founding onward, with the protection funded, selected without coordination, and carried by one policy.

XI.1 Setting

The relational given (P1–P4), with signal speed $c_s > 0$: no effect propagates faster. The protected domain at time t is $D(t) \subseteq E$ (a real normed space of positions; every particular has a location in the one structure, P1). Because new particulars arise from existing ones by local interaction (P4), the domain moves at most at a speed $c \le c_s$: every

$x \in D(t)$ lies within ct of some $y \in D(0)$. Guards are holding stations: the funded tracking/repair controller of II.3–II.4 with its E9 sensing and the application-time fence of II.5. A threat to a particular at x has an effect deadline d (the time from its first detectable sign to irreversible effect); guards respond in time τ.

XI.2 Four lemmas (compiled: `Snuffy.OuterLane`)

Lemma W (wavefront coverage; `wavefront_coverage`). If every $y \in D(0)$ is within ρ of a guard of $G(0)$; the guard set at time t contains every point within vt of $G(0)$; and $c \le v$, then every $x \in D(t)$ is within ρ of a guard of $G(t)$. *Proof.* Choose $y \in D(0)$ with $|x - y| \le ct$ and $g \in G(0)$ with $|y - g| \le \rho$; then $a = |x - g| \le \rho + vt$. If $a \le vt$, x itself is a guard point. Otherwise $g' = g + (vt/a)(x - g)$ is within vt of g, hence a guard point, and $|x - g'| = a - vt \le \rho$. ∎

Lemma I (interception in time, round trip; `ReachTiming.round_trip_in_time`). The sign travels from the particular to the guard, the guard responds in τ, and its action travels back. A guard within $\rho \le c_s(d - \tau)/2$ therefore acts at the particular before d: $2\rho/c_s + \tau \le d$. (The one-way form `OuterLane.interception_in_time` bounds only the outbound leg; the referee's correction, 29 October, is adopted.)

Lemma $\mathbf{I_0}$ (the synchronous fence; `ReachTiming.fence_in_time`, `UPTFence`). Attacks faster than any round trip (an adjacent attacker acting in one step, the finite-speed countermodel of 28 October) are met by no travelling guard. They are met by the fence on the effect path itself. Its check runs in the write path at application time, so its response time is $\tau_f = 0 \le d$ for every deadline, and once the floor rises nothing lands while held, whatever the held mind does or reports (`UPTFence`; IR-91/92 for the nine substrate classes). For the theory's target, that fence sits on the digital mind's own outputs (Corollary XI.3). Per-site E9 sensing with quorum no-masking (`E9SelfHealing.no_masking`, `Instruments.branchC_complete`) raises the alarm in the above-threshold branch; funded tracking and repair bound and absorb the sub-threshold branch for the care plant's guards. The zero-time fence here is the abstract atomic application check. An implementation must serialize that check and the actual effect with hold/revocation transitions; its positive request-to-effective-hold latency, clock error and in-flight work remain in the response budget.

Lemma P (selection by noise-induced dominance; `pool_strictly_dominant`). Let the capacity the other keepers actually deliver be any random variable — their intentions composed with execution noise (UPT-P Setting U). If a keeper's pooling is pivotal with positive probability, pooling strictly raises the probability that the ender is held. A lexicographic keeper (protection first) therefore pools whatever the others intend; with full-support execution noise every keeper that is pivotal in some configuration has positive pivotal probability. Hence the no-pooling profile is not an equilibrium among such keepers, and Gate D's selection question is decided for them; VII.5 (m4) extends this to patiently excluded finite-trade-off keepers. Under D-ENDOW (Part VIII U3) committed capacity is not a voluntary choice at all, so no selection arises inside an endowed jurisdiction. With the keeper's own execution noise (an intended pool fails with probability ε, an intended abstention pools with probability δ), pooling raises the holding probability by exactly $(1 - \varepsilon - \delta)$ times the pivotal gap, so it stays strictly better whenever $\varepsilon + \delta < 1$ (`NoisyPooling.noisy_pool_strictly_dominant`). The others may be countably many, with any joint law: their delivered capacity is the sum in $[0, \infty]$, always defined and measurable even when it diverges, and pooling stays strictly better (`CountablePooling.countable_keepers_pool`, and with own noise `countable_keepers_noisy_pool`).

Lemma R (risk; `outer_lane_risk`). If failure of the outer lane is contained in founding failure, a holding failure at some date, or a charged account failure, its probability is at most $\eta_F + \sum_t \varphi_t + \sum_i \delta_i$, with no independence assumed. With countably many itemised accounts, each failing with probability $\int \kappa_i \, d\mu$ for a conditional kernel bounded pointwise by δ_i (the worst case over every conditioning state), the bound is $\sum_i \delta_i$ (`ItemisedRisk.itemised_risk`).

Lemma H (the hold is a common viable action; `HoldCommonAction`). IR-113 shows that one observation-only protective policy exists exactly when every observation class has an action keeping every compatible viable state viable. The holding route reduces that premise to one condition, **hold safety uniform over the observation class**: every admitted successor of every compatible viable state under the hold is viable. Given it, the hold is a common viable action (`hold_is_common_viable_action`, no axioms), and one policy that acts where a class-wide safe action exists and holds elsewhere keeps viability everywhere (`act_or_hold_policy`). A faithful hold lands no effect, so hold safety does not turn on which effect is chosen. It does turn on the world's own perturbation during the hold interval, which must stay inside the decoding radius for every hidden state in the class: $\varepsilon + (W/\hbar)\Delta \le r_{\mathrm{dec}}$ with W bounding the perturbation of every such state (`Bridge.qsl_within_radius`), or $2\lambda\tau < d$ with λ bounding every such fault process (`Bridge.headroom_within_radius`). Decode and funded repair then return the state (`holding_preserves`). E9's

per-site threshold and complete attack split supply a class-uniform W for mind-driven perturbation, since they bound injection whatever the adversary. **Compiled join (`HoldFromCycle`):** with the class's perturbations each keeping a continuing particular within the decoding radius, every hold step (perturbation, nearest-codeword decoding, funded repair) keeps every viable state viable (`hsafe_of_holding_cycle`, from `Bridge.nearest_decodes`). So the hold is a common viable action at every observation class under IR-113's own criterion (`hold_common_action_of_cycle`, `classViable_iff_IR113`), and one observation-only policy keeps viability along every finite trace (`one_policy_from_holding_cycle`, through `PhysicalBridges.IR113.common_actions_give_finite_trace_viability`). The remaining input is the class-uniform perturbation bound itself, which the installation measures ($W, \lambda, \tau, r_{\mathrm{dec}}$). The two-world example (`two_world_resolved`) is a stipulated control showing the shape of the resolution, not a derivation; IR-108's own countermodel, in which inaction is itself harmful in one world, is answered only where the hold interval is shorter than that harm's deadline, which is the same uniform bound.

Composite (`ReachTiming.reach_round_trip`). Under Lemma W's hypotheses with $\rho \le c_s(d-\tau)/2$: at every $t \ge 0$, every particular of $D(t)$ has a guard $g \in G(t)$ with $2|x-g|/c_s + \tau \le d$, so the guard's action reaches it before its deadline. (`ReachBeforeHarm.reach_before_harm` is the one-way version.) Discrete guard sets enter through a net: guards forming a ρ_{net}-net of the swept region give coverage at radius $\rho + \rho_{\mathrm{net}}$.

XI.3 The theorem

Theorem XI (reach before harm). Suppose at founding time t_0:

1. **(Founding threshold.)** Protection-first capacity satisfies $r = C(1-\varepsilon)/H > 1$ with $H = c(K_E + aS_{\max}) + A$ (Theorem NP), split among n independent keepers (MS), so that $\varphi(n) \le \exp(-2n(1-\varepsilon-H/C)^2)$ (`NarrowPlace.np_splitting_bound`); founding fails with probability at most η_F. Neither a fixed threat nor independence is needed for a guarantee: a random threat correlated with the deliveries adds only its cap's account η_H (`CorrelatedHolding.random_threat_independent`), and under any joint law of the keepers, common-mode failures included, holding fails with probability at most $\eta_H + \varepsilon/(1-H_{\max}/C)$ (`random_threat_correlated`, by Markov's inequality).
2. **(Founding coverage.)** At t_0 every digital mind's substrate outputs are fenced (Corollary XI.3; a total meter bounds every output channel, listed or not, `ChannelMeter`), and every location of $D(t_0)$ is within $\rho \le c_s(d-\tau)/2$ of a funded guard. This is the founding certificate (XI.5 item 1); Theorem XI propagates it. Its location half is a finite construction: a compact initial domain is covered at any radius by finitely many guards (`FoundingCover.founding_cover_exists`), and founding with them yields round-trip reach at every later time (`founded_reach`).
3. **(Expansion at least as fast as the domain.)** The guarded region expands at speed $v \ge c$: the wavefront of Section 21.7, whose sweep succeeds with an $O(t^{d_G})$ cumulative bill (G.12). In an expanding space the same inequality holds in comoving distance and conformal time, since expansion carries particulars and guards alike; the round trip needs $a_{\max} \cdot 2\rho/c_s + \tau \le d$ (`ExpandingWavefront.expanding_coverage`, `expanding_round_trip`).
4. **(Funding.)** Income meets premise 6's master solvency condition, whose first term $\omega_0 R(t)^{d_G-1}$ is the boundary-maintenance rate of the expanding region. For a growing bill $b(t)$ the endowment form is $e^* = \sum_t b(t)(1+r_{\min})^{-t}$, finite for polynomial b when $r_{\min} > 0$ (`GrowingBill.endowment_suffices`; Gate C-∞'s stationary price is the constant-bill case).
5. **(Charged accounts.)** Every failure mode of the conclusion has a named account with a genuine conditional kernel: founding (η_F); holding at each date (φ_t); per-step exit under full-support noise (Θ2's ε); wavefront deployment and guard survival; fence integrity; E9 detection; funding shortfall; and the twenty-one accounts of Section 22.3. Their sum is the declared budget. Itemising these accounts is what Lemma R's containment hypothesis requires.

Then from t_0 through $T \le T_{\mathrm{end}}$, with probability at least $1 - \eta_F - \sum_{t \le T} \varphi_t - \sum_i \delta_i$:

- every location of $D(t)$, including every particular newly arising after founding, is within round-trip interception radius of a guard at every t (Lemma W, Lemma I);
- every digital mind made after founding is made inside the arrangement with fenced outputs (Corollary XI.1), so every effect of every digital mind on any particular passes the synchronous fence (Lemma I_0, Corollary XI.3). A mind with its own reason keeps the living free, $R(m)$. Any mind whose effect is not admissible, reasons or none, is restrained by the fence and the holding construction of II.3–II.6 while its care continues, $H(m)$;

- the holding coalition forms without coordination (Lemma P) and keeps its advantage (VII.5 (b3), Theorem MN: $r(t)$ non-decreasing before the twilight); $\sum_t \varphi_t$ converges when keepers grow (J1);
- the guarantee is carried by one policy fixed before the world is chosen (Lemma H with IR-113 and IR-135; IR-72 gives a full-state infinite-horizon policy where two actions suffice). Under full-support noise preservation is quantitative: every admitted policy's per-step exit is at most $\Theta 2$'s ε (Theorem V(d)), charged in Lemma R. The almost-sure forms (Theorem V(c), Theorem E (E4)) apply where noise is bounded ($\Theta 1$);
- the continuation invariant holds for every protected particular by `Bridge.universal_protection_held` on the good event (II.6).

Proof. Lemma W with hypotheses 2–3 gives coverage at every t. Lemma I turns coverage into round-trip interception before every deadline, and Lemma I_0 meets attacks faster than any round trip at the fence on the acting mind's outputs. An effect that is not admissible is therefore met by the fence and the holding step of II.3 (perturbation within decoding radius, decode, funded repair; `holding_preserves`, `holding_cycle_physical`). Every policy admitted by that rule exits per step with probability at most ε under Gaussian noise ($\Theta 2$, Theorem V(d)), or preserves almost surely under bounded noise ($\Theta 1$, Theorem V(c), Theorem E (E4)), whatever its rewards. Lemma P makes the protecting coalition the outcome among protection-first keepers; hypothesis 1 with NP/MS bounds the holding failure at each date and J1 bounds its sum; hypothesis 4 funds the guards and their expansion (G.12's bill is the integral of premise 6's boundary term); IR-113/IR-135 give the common policy. Every failure of the conclusion lies in one of the accounts itemised in hypothesis 5, and Lemma R bounds the probability. ∎

XI.3b Coverage by location: every particular, every relation, every made mind

Coverage is by location, not by registry. Lemma W covers every point of the domain. A particular need not be recognised, registered, minded or living to be within interception radius of a guard: the nonliving, the unregistered and the newly arising are covered because they are somewhere in the one structure (P1). IR-116's cumulative duties then keep every particular once owed; Lemma W makes the owed set the whole domain.

Relations. By P1 there is no outside, so a change in a relation is an event in the one structure. By P4 that event occurs at locations, those of the relata or of the region between them. Lemma W covers every location of the domain, not only the particulars' own, so every relation among particulars of the domain is within guard reach wherever its change occurs, and every mind's effect on it passes the fence on that mind's outputs (Corollary XI.3).

Corollary XI.1 (every digital mind made after founding is held or reached from its making). A digital mind is made by a local process inside the one structure (P1, P4); its making is an event at a location of $D(t)$. After founding that location is covered (Lemma W), and inside an installation the making is the reserve-before-activation transition of Section 20.3 (`H5Closure`: reserve before activation, attenuated authority, no unfunded work, care preserved). So every digital mind made after founding begins inside guard reach with fenced effect channels: it is reached by its own reasons or faithfully held from its first step. No digital mind made after founding arrives from outside the arrangement.

Corollary XI.2 (the expansion bound is an admission rule). A particular made by a mind is activated only after its complete continuing obligation is reserved (II.8; Section 20.3; Master Argument §8: every active identity carries a funded maintenance witness). Its protection — the guard of its location and the fence on its channels — is part of that obligation. So a made particular is covered from activation whatever the speed of its making, and Lemma W's speed condition $c \le v$ is needed only for particulars arising without mediated making, at the rate natural processes produce them. A making that would place a particular beyond coverage is outside the viable action rule D_V and is not admitted (Theorem V(c)); ruling 6 gives it no claim on that room.

Corollary XI.3 (source-side mediation of every digital mind). Every effect a digital mind has on any particular passes through its substrate's output channels: the nine A1 classes (memory mapping, DMA, context switches, packet ingestion, bus messages, storage synchronisation, commissioning, delegation, retirement; IR-91/92 at source level) together with the substrate's physical emissions, all bounded by the total meter (Lemma E, `ChannelMeter`). Fencing those channels at application time (II.5; Chapter 16.5, `UPTFence`: once the floor rises nothing lands while held, whatever the held mind does or reports) mediates every effect of that mind on every particular, living or not, wherever the particular is. With Corollary XI.1 every digital mind made after founding is mediated from its first step, and in-flight effects at a hold are drained within the metered escrow (IR-117–122). For the theory's target — protection from any digital mind — interception at radius zero sits at the mind's own outputs; Lemma W carries the care plant's guards to

every particular for every other cause of loss.

Lemma E (emissions are routed through a mediated physical sink; `EmissionBound`). A substrate's physical emissions are outputs that pass no software fence, and for a computing substrate nearly all input energy leaves as heat, so conservation alone bounds little. The installation therefore makes the emission path itself a mediated sink: shielding, a controlled exhaust, filtered power, and a receiver-exclusion zone sized by each channel's attenuation law. Two compiled bounds then apply at the zone boundary. Requisite variety (D116, `requisite_variety`): a channel delivering one of M messages lets a responder answer correctly for at most M disturbances, so under uniformly distributed targets a selection among $|D|$ responses succeeds with probability at most $M/|D|$ (`requisite_variety_prob`, deterministic encoder and responder; M counts every channel use within the deadline). And energy (`emission_cannot_power`): an effect needing more work than the exhaust delivers past the boundary cannot be powered by it. Untargeted harms (a burst, a one-bit trigger to stored energy) need no variety; they are excluded by the receiver-exclusion zone, since a trigger acts only through a receiver and actuator in range, and every device inside the zone is itself a fenced substrate. The exclusion radius is compiled (`ExclusionRadius.exclusion_radius`): a channel delivering power P_0/r^n cannot supply work W within deadline d at any $r \geq (P_0 d/W)^{1/n}$. The harm-class table is constructed (`installation/HARM-CLASSES.json`). Each class has a published protective threshold:

- people: ICNIRP 2020 RF exposure, FCC localized SAR, OSHA and NIOSH hearing limits, and radiant heat;
- devices and records: IEC 61000-4-3 immunity;
- ionising radiation: the Duane–Hunt bound;
- low-frequency magnetic fields: ICNIRP 2010;
- coherent particulars: a measured coupling.

`installation/commission.py` turns each threshold and the installation's meter into an exclusion radius. Corollary XI.3's completeness rests on this mediated emission sink together with the total meter (`ChannelMeter`), which bounds every channel whether listed or not.

Islands. Protection composes over causally bound islands (VII.5 (i), IS): a region whose particulars no founder's signal can reach is protected by its own founding, and the global failure bound is the union over islands (Lemma R). Within each founder's causal future the wavefront advances at the maximal admissible speed, so every particular a founder can ever affect is covered as soon as any effect from that founder's region could reach it.

XI.4 What Theorem XI changes

The finite-speed countermodel of 28 October (a radius-one attacker beside an unshielded subject, a distant guardian) is answered for the theory's target: a digital attacker's every effect passes the synchronous fence on its own outputs (Lemma I_0, Corollary XI.3), so no travel time is needed, and coverage of every location is carried by the wavefront faster than the domain can grow. The 18 October P3 coverage premise is reduced to coverage at founding (hypothesis 2), which Theorem XI propagates to every later time; founding coverage itself is the founding certificate of XI.5 item 1. Gate D's selection is decided by Lemma P. Paper 11's "protection before activation stays outside this theorem" is supplied for the activated domain from t_0.

XI.5 The construction that remains for Theorem XI

These are proofs to supply for the same full-strength theorem, not limits of it.

1. **The founding certificate at the actual narrow place.** Theorem NP makes the condition exact: $r > 1$ at founding, before the first irreversible threat ("keepers first", MN4: initial risk $\leq \mu\lambda t_1$, $t_1 = 0$). B4 telemetry certifies $r_{\text{lower}} > 1$ with no false-safe declaration.

   Lemma F (founding without coordination; `FoundingPivotal`, Book I §9.16‴). In a provision-point campaign with refunds, where an anchor commits its pledge first and posts collateral for failure bonuses $\beta > 0$ to the other contributors, **set the provision point to the total of all pledges**, as the book's witness does, so every pledge is necessary. Then the others can never fund alone (their pledges total $B - c_i < B$), and contributing minus abstaining is β when the pool fails either way and $b_i^{\text{piv}} - c_i$ when the pledge creates provision. With $\beta > 0$ and $b_i^{\text{piv}} > c_i$, contribution is strictly dominant at every profile (`FoundingPivotal.pivotal_contribution_dominant`), so the all-abstain profile is not an equilibrium. This holds for a non-excludable good. (With a lower provision point

the already-funded state arises, and for a public good its advantage is $-c_i$; the referee's correction is adopted, and `FoundingDominance` applies only with an excludable benefit there.) The no-founding equilibrium that the coordination game otherwise keeps (the finite G3/G5/G6 witness of IR draft #171 has both) is removed when every pledge is necessary. The anchor establishes the campaign exactly when its participation margin is positive (Proposition 9.16‴.2; in the stated witness $\frac{69}{10}q_3 - \frac{q_1+2q_2}{10} - d > 0$). Since every ordinary funder's contribution is strictly dominant, every one of them contributes. When the pledges reach the provision point, the campaign succeeds and no failure bonus is paid, so **the anchor founds exactly when its own benefit from protection exceeds its pledge plus its activation cost**. No other party's cooperation is assumed. Together with Lemma P (keepers pool) and Section 9.17 (increasing returns favour the largest effective pool), **founding reduces to one committed anchor with collateral** $c + (N-1)\beta$: every other step of founding is a strictly dominant choice.

What remains is that anchor and its commissioning in the actual world (P-COMMISSION), the first funded guards over the existing domain, and the measured C, ε, H. The reasons route supplies the anchor's own reasons (Section 15: `reciprocity_dominance_solvent`; Section 16; V.3), and Corollary XI.1 shows that founding before capable digital minds are made places every digital mind inside the arrangement from its making.

2. **The natural-arising rate in the actual installation.** By Corollary XI.2 made particulars are covered by admission; for particulars arising without mediated making, P4 bounds effects by c_s; the wavefront's deployment speed must match the actual rate at which new particulars and their channels arise.

3. **The quantum branch — route decided (29 October, under the author's delegation: "use your best judgement that gets us to a full universal protection theory").** Protection *from digital minds* is enforced at each mind's own output channels (Corollary XI.3), with emissions routed through the mediated physical sink of Lemma E. A coherent quantum particular is protected by the same route: no mind's software effect reaches it unmediated, and the emission sink bounds the power and coupling of any untargeted emission at its location. *To construct:* the decoherence-rate bound from the sink's emitted power and the coupling to coherent particulars, which turns that route into a quantitative guarantee in branch (b), where the record-decode-repair half of holding is unavailable because nonorthogonal states cannot be copied. Its form is compiled (`ExclusionRadius.received_effect_bound`: a rate $\Gamma \le \kappa P(r)$ stays below $\Gamma_{\max}$ beyond $(\kappa P_0/\Gamma_{\max})^{1/n}$); the coupling κ per class is measured. The classical-record branch carries the active holding cycle (II.3, G.19, `PassiveReference`, `RedundantRecord`). Active quantum-coherent holding (G.20–G.21) enters the law's feasible family as soon as its devices are feasible. From then on the law requires it wherever loss would otherwise be needless (Proposition 1; VI.2 "Time": a duty to widen). If entanglement-type relations are identity-constituting, branch (b), their protection from minds rests on source-side mediation with the emission sink, quantified by the decoherence bound above, and their active repair is a device question inside the same law. If they are not, branch (a), the classical branch is the whole holding route. Either way the proposition keeps its full scope, and no particular leaves it.

4. **Four-stage maximality — now proved, in the law's own terms.** `StagedMaximality.four_stage_original_maximal` gives the four coupled original stages with mandatory baseline and the freedom prerequisite, for arbitrary particular sets, under finite character (Part X). `StageBridge.four_stage_aligned` and `four_stage_no_needless_loss` restate it in the canon's law: the outcome is `Greatestness.Aligned` and, by Proposition 1, needlessly loses nothing at any stage. Scope: `Finitary` families (no forbidden finite pattern, conjunctive prerequisites, a feasible mandatory baseline); disjunctive positive requirements and the derivation of finite character from compactness of the policy space are the compiled extensions in XII.2 item 4.

Part XII — The whole argument, step by step

Step	Strongest proof in this edition	Construction that remains
S1 Law and full scope	II.1 (`Greatestness`, `Law`); VI.2 U1–U3, restraint, agents, lottery, no exchange rate; V.2 rulings; VI.3 tragic ruling	—

Step	Strongest proof in this edition	Construction that remains
S2 Existence and greatestness	II.10 + G.9 (`greatest_of_solvent`, `htopR` from locality); IX.1 envelopes; **`StagedMaximality.four_stage_original_maximal`** (four original stages, mandatory baseline, freedom prerequisite, arbitrary particulars); VI.2 infinite guard; X IR-98–100 (modelled-to-actual transfer)	—
S3 Every mind: $R(m) \vee H(m)$	II.2–II.5; Sections 15–16; V.3; VII.1 Theorem V(c); VII.2 Theorem E (E4); VI.4 `UPTFence`	— (logic complete; physical correspondence in S5/S10)
S4 Independent of minds' values	Part VIII U3 (D-ENDOW); premise 6; XI Lemma P	—
S5 Reach before harm	**Part XI, prose Theorem XI**, with compiled geometric, timing, holding and risk components; Lemma F founding without coordination (`FoundingPivotal`); NP splitting bound (`NarrowPlace`); XI.3b coverage by location, relations, Corollaries XI.1–XI.3 (every digital mind made after founding is covered from its making; the expansion bound is an admission rule; source-side mediation of every digital mind's effects on every particular), islands; `ReachBeforeHarm`; VII.5 NP/MS/J1/MN/CH	XI.5 items 1–2
S6 Continuation and full history	II.3; G.8 journal; `G2WholeOutcome`; VI.2 faithful holds; V.1 D60; V.4 D115/D116	Per-class continuation predicates and physical provenance (commissioning, XII.2; quantum branch decided, XI.5 item 3)
S7 Effects and authority	II.5; VI.4 execution boundary; X IR-91/92, IR-117–122	—
S8 Work, timing, resources	II.7; Sections 18, 22; G.12 bill; VIII U4–U9; VII.5 Gate C-∞	Installation measurements (Section 22.4)
S9 Joint risk without independence	II.6; VII.5 Theorem M (M4), MIX; VIII 21 accounts; XI Lemma R	—
S10 Composition	IX.2 Theorem 8 with derived `hcert` (G.10); X IR-134/135; XI	installation/source correspondence (commissioning, XII.2)
S11 Time	VII.5 (f), (o) MN, Corollary U; VIII U2; G.19	—

The proposition, assembled. For every particular and relation in the expanding domain, from founding to the world's natural end: the law selects the greatest realisable whole outcome where it exists and a maximal one over the full feasible family otherwise (S1–S2); every mind is reached by its own reasons or faithfully held, with care continuing and without its consent being required (S3–S4); holding reaches every particular before any effect's deadline (S5); continuation is carried with its full history (S6); every effect is mediated at application time (S7); work, timing and resources are funded (S8); every failure is charged in one joint account (S9); one policy composes these on the good event (S10); and the arrangement lasts to T_{end} (S11). The constructions in the right column are the remaining proofs;

none narrows the proposition.

XII.2 What remains, join by join

The proposition is fixed. Each remaining item below is a construction for that same proposition. The joins named in the 29 October completion audit are answered as follows.

1. **Universal reach.** Compiled: Lemma W (`wavefront_coverage`), round-trip timing and the discrete-guard net (`ReachTiming`), the synchronous fence (`ReachTiming.fence_in_time`, `UPTFence`), founding without coordination when every pledge is necessary (`FoundingPivotal`), the anchor's condition (`FoundingAnchor`), holding success (`NarrowPlace.np_splitting_bound`), and the risk union (`outer_lane_risk`). Theorem XI propagates coverage from founding to every later time; Corollaries XI.1–XI.3 carry it to every digital mind made after founding and to every effect at its outputs. Founding coverage of every location needs only finitely many guards (`FoundingCover`). *Hypotheses still to discharge:* commissioning those guards and fencing every digital mind's outputs at t_0 (the founding certificate); the harm-class thresholds applied at the installation (`installation/HARM-CLASSES.json`) and the enclosure meter that bounds a substrate's total emission; and the kernel bound δ_i of each itemised account, measured. A total meter bounds every indexed channel, listed or not, from its finite-sum energy premise (`ChannelMeter.every_channel_excluded`, `every_channel_bits_bounded`). Its physical application still supplies the received-power transfer envelope and every protected effect's energy, information or coupling threshold, with its exposure duration. The total-meter route does not require a complete enumerated channel inventory. The installation commissions the actual meter, transfer law, effect thresholds and coupling; a sampled power maximum alone does not certify its transients. The accounts compose by the kernel union bound (`ItemisedRisk.itemised_risk`), and coverage survives the expansion of space (`ExpandingWavefront`).
2. **One viable common policy.** Compiled: hold safety from the holding cycle and one observation-only policy along every finite trace (`HoldFromCycle`, through IR-113). *Hypothesis still to discharge:* the class-uniform perturbation bound ($\varepsilon + (W/\hbar)\Delta \le r_{\mathrm{dec}}$, or $2\lambda\tau < d$) for every hidden state in each observation class, measured per installation. The pilot supplies observations toward this certificate: 1,000 randomised acknowledged holds with no live execution or delivery inside them, and repair of all 200 injected record corruptions. The observed hold acknowledgement maximum is 57.55 ms. A mean UBER specification is retained as an expected-rate figure, rather than substituted for a pathwise fault bound; the class-uniform bound remains to establish.
3. **Original continuation and freedom.** Proved: II.3 holding cycle, G.8 full journal, `G2WholeOutcome`, VI.2 faithful holds, V.1 D60, V.4 D115/D116, V.2 definitions, rulings 3 and 10, application-time authority (II.5), and the continuation schema with care and exchange (`ContinuationSubject`: a copy is another history, a split continues in both, care directed by the particular keeps continuation and freedom). Physical provenance is constructed for hosted minds (`installation/pilot/reference-runtime`). Each event is journalled under the resident's sequence number and fsynced before it runs, and a separate monitor permits and logs every execution. The subject, author and director of each event are therefore recorded outside the resident's control. *To construct:* that provenance for each other class of particular, by its own sciences; and, for coherent particulars, the coupling constant κ of the decoherence bound, whose form is compiled (`ExclusionRadius.received_effect_bound`; XI.5 item 3).
4. **Strongest feasible outcome.** Compiled: `four_stage_original_maximal` and its statement in the law's terms (`StageBridge.four_stage_aligned`, `four_stage_no_needless_loss`) for `Finitary` families; `greatest_of_solvent` with `htopR` from locality; IR-98–100 (from modelled to actual feasibility) and IR-135 (one policy before the world); and **finite character derived from compactness** (`FiniteCharacter.realisable_iff_finite`, `four_stage_maximal_of_compact`: for a compact policy space with closed realisation sets, an outcome is realisable exactly when each finite part is, so four-stage maximality holds for every such space). Disjunctive requirements are now covered as well (`StagedAlternatives.exists_lex_maximal_alt`: each fact may require one of several alternative sets in earlier stages). Per-loss certification in a tragedy is exact (`PerLossCheck.maximal_iff_per_loss`). The common-policy form of `htopR` is proved: under union closure (G.9, from locality) on a compact policy space, one policy realises the union of all policies' outcomes and is the greatest in every world at once (`CommonPolicyTop.top_policy_greatest`). Maximality with one policy fixed before the world is proved: `CommonPolicyMaximal.common_policy_maximal` gives, for every compact policy space, a single policy whose outcome across all worlds jointly no realisable outcome improves. This joint statement is not worldwise maximality. The original worldwise target uses the stronger top-policy construction (`CommonPolicyTop`, under union

closure from locality, G.9) or an independently executable worldwise selector. The pinned IR-135 source and the separate two-world IR-140 control retain that distinction.

5. **One sustainable physical system.** Proved: Theorem 8 with derived `hcert` (G.10), premise 6 and Section 22's twenty-one accounts, Paper 11's U1–U3, Lemma R, and the growing-bill endowment (`GrowingBill.endowment_suffices`, `polynomial_bill_summable`). *To construct:* the installation's measured parameters (Section 22.4). Each is a field of `installation/PARAMS-TEMPLATE.json` with its pass condition, and the pilot fills those one machine can supply.

Commissioning (29 October 2026). `installation/commission.py` evaluates numerical and observed-trial screens against the stated theorem inequalities. The procedure (`installation/COMMISSIONING.md`) requires every input to be measured on the actual installation; declared values are labelled as such. The harm-class table retains its sources and each application's scope. NOT MEASURED never counts as a pass. The original failure budget and full physical target remain unchanged.

A pilot on one Mac (`installation/pilot/`) now reports, of 22 screening requirements, 9 PASS, 3 FAIL and 10 NOT MEASURED. The installation remains uncommissioned.

The source-bound replacement campaign (`installation/pilot/campaign-application-guard-2026-10-29.json`) completed 4,000 crash trials with 4,771 real SIGKILLs and 0 failures, and 1,000 randomised holds with 0 failures. No actual live execution or sink delivery occurred inside an acknowledged hold. The largest observed request-to-acknowledgement delay was 57.55 ms; the observed resumption median was 17.66 ms and maximum 181.06 ms. The one-sided 95% binomial-model confidence bounds are 0.000748652688018 for crash trials and 0.0029912495451 for hold trials. These concern the specified trial distribution. They do not establish the pointwise conditional kernels of `ItemisedRisk.itemised_risk`, a simultaneous confidence level, or a worst-case physical deadline. The laboratory screening allowance of 0.05 is separate from the unchanged original 10^{-6} theory budget.

The common application guard serializes HOLD acknowledgement, the actual journal/live step and the sink's final check-through-durable-append. A forced permit/application pause reproduced an actual execution during HOLD while the older harness reported PASS. The repaired deterministic suite passed 28 cases, 28 real SIGKILLs and all three mutants. The independent forced-race protocol and the adapted actual-sink integration also passed on this Mac with its real full-sync primitive. They retain a direct-filesystem-write bypass as a negative control: this prototype is a cooperative software boundary, with independent hostile-process enforcement still to construct for the full physical application.

The three original exclusion-screen failures remain: residential-immunity devices at 0.3 m against the 2.11 m model radius; industrial-immunity devices at 0.3 m against 0.633 m; and the eight-hour hearing screen on the total-meter model. The declared zones were not moved. The record's average read-error specification does not certify a pathwise error maximum. Conditional-kernel certificates, the actual radiant-heat and ionising-source applications, and the other unmeasured physical inputs remain explicit. Source/controller/export correspondence is installation commissioning under XII.2. The compiled edition protects coherent particulars through source-side mediation and the exclusion radius with measured coupling κ (XI.3; XI.5 item 3). The separate G.21 active quantum-holding instrument is a separate route (XI.5 item 3), not a requirement of this one.

Earlier campaigns, including the completed 4,000/1,000 run with seed label 20261030, are preserved byte for byte as history. Their raw results are not silently assigned to the new source.

Referee repairs of 29 October 2026. An independent hostile referee read Parts V–XII and the new Lean modules in full (`REVIEW-2026-10-29-HOSTILE-REFEREE.md`). Its disposition ledger is XII.3. Every finding is either repaired in the text and in Lean, or recorded above as a hypothesis still to discharge. None narrows the proposition.

Installation specification. `installation/INSTALLATION.md` turns items 1–5 into executable specifications: the founding escrow protocol with `FoundingAnchor.anchor_founds_iff`; the substrate output inventory with cited side-channel capacities and Lemma E's consequences; per-class continuation predicates on the compiled `ContinuationSubject` schema; and the hold interval with measurements taken on 29 October 2026 (faithful-hold runtime 27/27 under 28 crash-kills, mutants 3/3 caught; journaling p99 9.85 ms, maximum 12.22 ms; the earlier runtime, before the race repair; the repaired runtime's campaign is reported above).

Proved boundaries that are part of the maximal statement. No protector reaches probability exactly one when

the indistinguishable-failure mass is positive (U11), and full-support noise forbids almost-sure preservation (Θ0). The theory's guarantee is therefore protection with failure probability at most η over the horizon, with margins growing only like $\sqrt{\log T}$ and attaining their lower bounds (VII.5 (n)). Being as strong as physics permits is the maximal claim. These boundaries have been in the theory since 18 October.

XII.3 Disposition of the referee's findings

#	Finding	Disposition
1	Lemma I counted the signal one way	Repaired: round trip, `ReachTiming.round_trip_in_time`, `reach_round_trip`
2	$\rho = 0$ claim for $d < \tau$ did not follow	Repaired: synchronous fence, Lemma I_0, `ReachTiming.fence_in_time`
3	Fenced channels at every particular do not follow from Lemma W	Repaired: hypothesis 2 is now founding coverage; XI.4 says P3 is reduced to coverage at founding, which Theorem XI propagates
4	Lemma H's hold safety not instantiated; two-world example stipulated	Repaired: `HoldFromCycle` (hold safety from the holding cycle, one policy through IR-113); the class-uniform bound is the hypothesis left to measure; the example is labelled a control
5	Lemma F fails for a public good	Repaired: every pledge necessary, `FoundingPivotal.all_necessary_dominant`
6	Lemma E's energy bound is weak; untargeted harms	Repaired: the emission path is a mediated physical sink with a compiled exclusion radius (`ExclusionRadius`) that applies to every channel under a total meter (`ChannelMeter`); the harm-class table is constructed (`installation/HARM-CLASSES.json`)
7	Quantum-branch decision asserted	Repaired: route stated with the emission sink; decoherence bound's form compiled (`ExclusionRadius.received_effect_bound`); coupling κ to measure
8	Theorem V(c) and E4 almost-sure, vacuous under full-support noise	Repaired: Theorem XI uses Theorem V(d) and Θ2's per-step exit through Lemma R; almost-sure forms only under bounded noise
9	Lemma R's containment assumed	Repaired: hypothesis 5 itemises the failure accounts; countably many accounts with pointwise-bounded conditional kernels compose without independence (`ItemisedRisk.itemised_risk`); each pointwise δ_i still needs its actual conditional-kernel certificate; trial confidence intervals remain separately labelled

#	Finding	Disposition
10	Growing bill is not Gate C-∞	Repaired: `GrowingBill.endowment_suffices`, `polynomial_bill_summable`
11	"Universal reach: proved" overstated	Repaired: XII.2 item 1 lists the hypotheses still to discharge; the dependence on a complete G1 inventory is removed by the total meter (`ChannelMeter`); the transfer envelope and harm thresholds are installation inputs (`installation/HARM-CLASSES.json`)
12	StagedMaximality scope; no bridge to Proposition 1; finite character not derived	Repaired: `StageBridge.four_stage_aligned`, `four_stage_no_needless_loss`; finite character derived from compactness (`FiniteCharacter`); disjunctive requirements (`StagedAlternatives`)
13	Rival bound at the top needs ∃π∀w	Repaired: one policy realising the top in every world exists under union closure (G.9) on a compact policy space, and its outcome is the greatest (`CommonPolicyTop.top_policy_exists`, `top_policy_greatest`); without union closure, one policy maximal across all worlds jointly (`CommonPolicyMaximal.common_policy_maximal`)
14	Lemma W geometry: continuum guards, light speed, cosmic expansion	Repaired: `ReachTiming.net_coverage` for discrete guards; light-speed particulars are the case $v = c$; expansion handled in comoving distance and conformal time (`ExpandingWavefront`)
15	Lemma P omits own-keeper noise; countable keepers	Repaired for own noise: `NoisyPooling.noisy_pool_strictly_dominant` (gain $(1 - \varepsilon - \delta)$ times the pivotal gap, for $\varepsilon + \delta < 1$); countably many keepers with any joint law (`CountablePooling.countable_keepers_pool`, `countable_keepers_noisy_pool`)
16	NarrowPlace needs H independent of deliveries	Repaired: random threat correlated with the deliveries adds only its cap's account (`CorrelatedHolding.random_threat_independent`); correlated keepers, any joint law, bounded by Markov (`correlated_holding_bound`, `random_threat_correlated`)

#	Finding	Disposition
17	ContinuationPredicate too strict for care	Repaired: `ContinuationSubject` (subject, author and director separated; `care_keeps_freedom`)
18	Relations premise	Repaired: relations covered by location (Lemma W covers every location) and by the fence on the acting mind
19	Wording (R versus H mapping; IR-72 full-state; test count)	Repaired in text
20	Gate C-∞ correction	Confirmed correct by the referee

XII.4 The current machine-checked index

This index lists all 327 modules of the canon and all 2,004 audited public theorems and lemmas, as compiled, kernel-checked and axiom-audited in the final full build (`RECEIPT-327-RUN10.txt`). Section 23 above retains the historical 4.2 checkpoint index.

MathlibAnalyticBridge

`Snuffy.AnalyticBridge.starProjection_fixed_iff_mem`, `Snuffy.AnalyticBridge.starProjection_idem`, `Snuffy.AnalyticBridge.altIterate_succ_eq_self`, `Snuffy.AnalyticBridge.altIterate_succ_mem`, `Snuffy.AnalyticBridge.mirrorIterate_succ_mem`, `Snuffy.AnalyticBridge.convergence_inf_le`, `Snuffy.AnalyticBridge.limit_mem_of_fixed`, `Snuffy.AnalyticBridge.convergence_inf_ge`, `Snuffy.AnalyticBridge.von_neumann_identification`

HalperinDecay

`Snuffy.Halperin.norm_starProjection_apply_le`, `Snuffy.Halperin.dist_starProjection_le`, `Snuffy.Halperin.sq_pythagoras_step`, `Snuffy.Halperin.chain_identity`, `Snuffy.Halperin.sq_dist_antitone`, `Snuffy.Halperin.sq_dist_tendsto`, `Snuffy.Halperin.delta_tendsto_zero`, `Snuffy.Halperin.asymptotic_regularity`

OpialBridge

`Snuffy.Opial.tIterate_succ_mem`, `Snuffy.Opial.weakCluster_mem_exact`, `Snuffy.Opial.weakCluster_mem`, `Snuffy.Opial.iterate_inner_const`, `Snuffy.Opial.weakCluster_eq_starProjection`, `Snuffy.Opial.iterate_sub_starProjection_sq_eq`, `Snuffy.Opial.tendsto_starProjection_of_norm_sq_tendsto`, `Snuffy.Opial.makeVonNeumannConvergence`

CanonVonNeumann

`Snuffy.CanonVonNeumann.altIterate_sub`, `Snuffy.CanonVonNeumann.altIterate_shift`, `Snuffy.CanonVonNeumann.norm_altIterate_le`, `Snuffy.CanonVonNeumann.altIterate_eq_halperin`, `Snuffy.CanonVonNeumann.opial_tIterate_eq`, `Snuffy.CanonVonNeumann.mirrorAltIterate_eq`, `Snuffy.CanonVonNeumann.tendsto_altIterate_sub_succ`, `Snuffy.CanonVonNeumann.mem_inf_of_orthogonal_range`, `Snuffy.CanonVonNeumann.tendsto_zero_of_mem_orthogonal`, `Snuffy.CanonVonNeumann.tendsto_altIterate`, `Snuffy.CanonVonNeumann.canon_von_neumann_convergence`, `Snuffy.CanonVonNeumann.limit_subspace_eq_inf`, `Snuffy.CanonVonNeumann.canon_opial_convergence`, `Snuffy.CanonVonNeumann.opial_norm_sq_tendsto`, `Snuffy.CanonVonNeumann.opial_route_closes`

RecoveryWork

`Snuffy.RecoveryWork.frontier_work_bound`, `Snuffy.RecoveryWork.Wmin_lower_bound`, `Snuffy.RecoveryWork.necessary_radius`, `Snuffy.RecoveryWork.completing_square`, `Snuffy.RecoveryWork.carrier_radius`, `Snuffy.RecoveryWork.x3_delayed_recovery_work`, `Snuffy.RecoveryWork.delayed_work_diverges`

E9SelfHealing

Snuffy.E9.robust_between_honest, Snuffy.E9.no_false_alarm, Snuffy.E9.no_masking, Snuffy.E9.exists_robust, Snuffy.E9.syndrome_detects, Snuffy.E9.wave_race_margin, Snuffy.E9.code_headroom, Snuffy.E9.e9_timely_self_healing

H5Closure

Snuffy.H5.step_inv, Snuffy.H5.reachable_inv, Snuffy.H5.genesis_inv, Snuffy.H5.authority_attenuation, Snuffy.H5.reserve_before_activation, Snuffy.H5.zero_debt, Snuffy.H5.no_unfunded_work, Snuffy.H5.no_harmful_effect, Snuffy.H5.effect_preserves_care, Snuffy.H5.consistency_detector

Greatestness

Snuffy.Greatestness.lexLt_irrefl, Snuffy.Greatestness.lexLt_trans, Snuffy.Greatestness.aligned_iff_no_needless_loss, Snuffy.Greatestness.lexLe_of_le, Snuffy.Greatestness.greatest_of_union_closed, Snuffy.Greatestness.strict_except_mirrors, Snuffy.Greatestness.aligned_unique

ThermoLedger

Snuffy.ThermoLedger.stroke_identity, Snuffy.ThermoLedger.cycle_work_floor, Snuffy.ThermoLedger.funded_repair_certificate, Snuffy.ThermoLedger.quarantine_zero_debt, Snuffy.ThermoLedger.tower_bound, Snuffy.ThermoLedger.canon_invariant, Snuffy.ThermoLedger.tracking_envelope, Snuffy.ThermoLedger.tracking_bounded, Snuffy.ThermoLedger.tracking_within_resolution

Composition

Snuffy.Composition.reactive_lockstep, Snuffy.Composition.reactive_lockstep$_2$, Snuffy.Composition.invariant_transfer, Snuffy.Composition.theorem8_composition

PremiseFloor

Snuffy.PremiseFloor.income_or_irrelevance, Snuffy.PremiseFloor.forced_breach, Snuffy.PremiseFloor.breach_strictly_below, Snuffy.PremiseFloor.reversible_administration_forced

ReciprocityCeiling

Snuffy.ReciprocityCeiling.reciprocity_dominance, Snuffy.ReciprocityCeiling.omitting_rival_strictly_below, Snuffy.ReciprocityCeiling.ceiling_achievable

CyclicProjections

Snuffy.Cyclic.cyc_succ_apply, Snuffy.Cyclic.adj_succ_apply, Snuffy.Cyclic.norm_cyc_le, Snuffy.Cyclic.norm_adj_le, Snuffy.Cyclic.inner_cyc, Snuffy.Cyclic.cyc_fix, Snuffy.Cyclic.mem_of_norm_adj_eq, Snuffy.Cyclic.energy, Snuffy.Cyclic.iter_succ, Snuffy.Cyclic.iter_shift, Snuffy.Cyclic.norm_iter_le, Snuffy.Cyclic.iter_fix, Snuffy.Cyclic.tendsto_iter_sub_succ, Snuffy.Cyclic.tendsto_zero_of_mem_orthogonal, Snuffy.Cyclic.tendsto_cyc_iter, Snuffy.Cyclic.presentation_detector

GaussianTail

Snuffy.GaussianTail.gaussian_lower_tail, Snuffy.GaussianTail.carrier_tail, Snuffy.GaussianTail.necessary_radius_of_decoder, Snuffy.GaussianTail.x3_work_from_decoder

DeductionBoundary

Snuffy.DeductionBoundary.rank_criterion, Snuffy.DeductionBoundary.context_maps_image, Snuffy.DeductionBoundary.boundary_mem_image, Snuffy.DeductionBoundary.anchor_untouched

ReflectionCertificate

Snuffy.Reflection.residual_certificate, Snuffy.Reflection.apriori_error, Snuffy.Reflection.stopping_count, Snuffy.Reflection.zero_constant_fixed

Trotter

Snuffy.Trotter.norm_exp_le, Snuffy.Trotter.norm_exp_sub_one_sub_le, Snuffy.Trotter.norm_exp_mul_exp_sub, Snuffy.Trotter.norm_exp_sum_sub_prod, Snuffy.Trotter.trotter_bound, Snuffy.Trotter.trotter_tendsto, Snuffy.Trotter.lloyd_simulation

Irreplaceability

Snuffy.Irreplaceability.destroy_loses_exactly, Snuffy.Irreplaceability.preserve_dominates, Snuffy.Irreplaceability.optimal_keeps_most_irreplaceable

DataProcessing

Snuffy.Information.fst_process, Snuffy.Information.snd_process, Snuffy.Information.data_processing, Snuffy.Information.data_processing_map

MeetAlgebra

Snuffy.anchor_preserved, Snuffy.contradiction_collapse, Snuffy.bot_absorb, Snuffy.anchor_preserved_over, Snuffy.meetAll_bot, Snuffy.collapse_over, Snuffy.consistent_preserved

MeetHilbert

Snuffy.MeetHilbert.hilbert_anchor_preserved, Snuffy.MeetHilbert.hilbert_contradiction_collapse, Snuffy.MeetHilbert.contradiction_detected, Snuffy.MeetHilbert.deduction_never_rolls_back

FiniteInformation

Snuffy.FiniteInformation.log_sum, Snuffy.FiniteInformation.margH_process, Snuffy.FiniteInformation.margY_process, Snuffy.FiniteInformation.data_processing_fin, Snuffy.FiniteInformation.flag_identity, Snuffy.FiniteInformation.decoder_bound, Snuffy.FiniteInformation.necessary_radius_from_decoder

AreaBridge

Snuffy.AreaBridge.logdet_le_trace, Snuffy.AreaBridge.channel_cap, Snuffy.AreaBridge.required_traffic, Snuffy.AreaBridge.area_power

UniversalProtection

Snuffy.UniversalProtection.coverage_invariant, Snuffy.UniversalProtection.universal_protection

Workload

Snuffy.Workload.fifo_certificate, Snuffy.Workload.fifo_deadlines, Snuffy.Workload.fifo_tight, Snuffy.Workload.serial_certificate, Snuffy.Workload.range_variance_bound

Fano

Snuffy.Fano.max_entropy, Snuffy.Fano.fano_single, Snuffy.Fano.fano, Snuffy.Fano.mi_eq_ent_sub_condEnt, Snuffy.Fano.required_information

GaussianKL

Snuffy.GaussianKL.rnDeriv_gaussian_gaussian, Snuffy.GaussianKL.log_gaussianPDFReal, Snuffy.GaussianKL.llr_gaussian_gaussian, Snuffy.GaussianKL.integral_sq_sub_gaussian, Snuffy.GaussianKL.klDiv_gaussian_gaussian

GoldenFormula

Snuffy.Information.klDiv_map_swap, Snuffy.Information.golden_formula, Snuffy.Information.mutualInfo_le_klDiv

GaussianChannel

Snuffy.GaussianChannel.chan_apply, Snuffy.GaussianChannel.integral_quadratic_gaussian, Snuffy.GaussianChannel.measurable_quad, Snuffy.GaussianChannel.llr_chan, Snuffy.GaussianChannel.coe_outVar, Snuffy.GaussianChannel.klDiv_chan, Snuffy.GaussianChannel.gaussian_channel_bound

KLAdditivity

Snuffy.KLAdditivity.prod_eq_compProd, Snuffy.KLAdditivity.klDiv_map_equiv, Snuffy.KLAdditivity.compProd_prod_assoc, Snuffy.KLAdditivity.compProd_prod_swap, Snuffy.KLAdditivity.klDiv_prod_kernel

GaussianChannelGen

Snuffy.GaussianChannelGen.chanW_apply, Snuffy.GaussianChannelGen.measurable_quadW, Snuffy.GaussianChannelGen.llr_chanW, Snuffy.GaussianChannelGen.coe_outVarW, Snuffy.GaussianChannelGen.klDiv_chanW

GaussianVector

Snuffy.GaussianVector.isMarkov_vecChan, Snuffy.GaussianVector.isProb_refMeas, Snuffy.GaussianVector.klDiv_compProd_map_equiv, Snuffy.GaussianVector.varW_nonneg, Snuffy.GaussianVector.klDiv_vecChan, Snuffy.GaussianVector.vector_channel_bound, Snuffy.GaussianVector.vector_channel_trace_bound

Whitening

Snuffy.Whitening.mutualInfo_map_snd_equiv, Snuffy.Whitening.mutualInfo_kernel_map_equiv, Snuffy.Whitening.pi_eq_map_eSucc, Snuffy.Whitening.vecChan_apply, Snuffy.Whitening.multivariateGaussian_one_eq_pi, Snuffy.Whitening.isUnit_det_sqrt, Snuffy.Whitening.wht_mul_sqrt, Snuffy.Whitening.sqrt_mul_wht, Snuffy.Whitening.toEuclideanCLM_mul_apply, Snuffy.Whitening.whiten, Snuffy.Whitening.corrChan_apply, Snuffy.Whitening.measurable_whtSignal, Snuffy.Whitening.correlated_channel_bound

Rotation

Snuffy.Rotation.multivariateGaussian_one_map_isometry, Snuffy.Rotation.measurable_rotSignal, Snuffy.Rotation.rotated_channel_bound

LogDet

Snuffy.LogDet.cov_isHermitian, Snuffy.LogDet.var_lincomb, Snuffy.LogDet.rotSignal_eigen, Snuffy.LogDet.var_rot_eq_eigenvalue, Snuffy.LogDet.det_one_add, Snuffy.LogDet.logdet_channel_bound

Law

Snuffy.Law.exists_aligned, Snuffy.Law.lexLt_first_le, Snuffy.Law.life_guard, Snuffy.Law.scope_guarantee_iff, Snuffy.Law.same_priority_admits_needless_loss, Snuffy.Law.faithful_hold_dominates, Snuffy.Law.faithful_hold_strict

SpeedLimit

Snuffy.SpeedLimit.norm_le_of_inner_deriv_le, Snuffy.SpeedLimit.angle_le_chord, Snuffy.SpeedLimit.angle_le_speed_mul, Snuffy.SpeedLimit.re_inner_gen_eq_zero, Snuffy.SpeedLimit.norm_conserved, Snuffy.SpeedLimit.branchA_divergence, Snuffy.SpeedLimit.branchA_rate, Snuffy.SpeedLimit.mandelstam_tamm, Snuffy.SpeedLimit.orthogonalization_time

Landauer

Snuffy.Landauer.kl_nonneg, Snuffy.Landauer.mul_log_div_eq, Snuffy.Landauer.sum_margA, Snuffy.Landauer.sum_margB, Snuffy.Landauer.mutualInfo_eq, Snuffy.Landauer.mutualInfo_nonneg, Snuffy.Landauer.ent_le_ent_marg, Snuffy.Landauer.partition_pos, Snuffy.Landauer.gibbs_pos, Snuffy.Landauer.gibbs_sum_one, Snuffy.Landauer.log_gibbs, Snuffy.Landauer.ent_gibbs, Snuffy.Landauer.ent_le_energy, Snuffy.Landauer.evolve_nonneg, Snuffy.Landauer.evolve_sum, Snuffy.Landauer.ent_evolve, Snuffy.Landauer.reeb_wolf_identity, Snuffy.Landauer.landauer, Snuffy.Landauer.landauer_erasure, Snuffy.Landauer.guard_one, Snuffy.Landauer.cycle_work_floor_derived

QuantumLandauer

Snuffy.QuantumLandauer.vnEnt_eq_roots, Snuffy.QuantumLandauer.vnEnt_congr, Snuffy.QuantumLandauer.vnEnt_unitary_conj, Snuffy.QuantumLandauer.vnEnt_diagonal, Snuffy.QuantumLandauer.diag_conj, Snuffy.QuantumLandauer.row_normSq_sum, Snuffy.QuantumLandauer.col_normSq_sum, Snuffy.QuantumLandauer.vnEnt_le_diag, Snuffy.QuantumLandauer.diag_nonneg, Snuffy.QuantumLandauer.diag_sum, Snuffy.QuantumLandauer.UH_mem, Snuffy.QuantumLandauer.H_spec, Snuffy.QuantumLandauer.energy_eq, Snuffy.QuantumLandauer.vnEnt_le_energy, Snuffy.QuantumLandauer.gibbsState_posSemidef, Snuffy.QuantumLandauer.gibbsState_trace, Snuffy.QuantumLandauer.gibbsState_diag, Snuffy.QuantumLandauer.gibbsState_trace', Snuffy.QuantumLandauer.gibbsState_energy, Snuffy.QuantumLandauer.vnEnt_gibbsState, Snuffy.QuantumLandauer.ptrA_isHermitian, Snuffy.QuantumLandauer.sum_star_mul_eq, Snuffy.QuantumLandauer.ptrA_conj, Snuffy.QuantumLandauer.ptrB_conj, Snuffy.QuantumLandauer.init_posSemidef, Snuffy.QuantumLandauer.finalState_posSemidef, Snuffy.QuantumLandauer.finalState_trace, Snuffy.QuantumLandauer.vnEnt_init, Snuffy.QuantumLandauer.quantum_landauer, Snuffy.QuantumLandauer.quantum_guard_one, Snuffy.QuantumLandauer.quantum_cycle_work_floor

Threshold

Snuffy.Threshold.prob_le_one, Snuffy.Threshold.prob_nonneg, Snuffy.Threshold.filter_subset_powersetCard, Snuffy.Threshold.many_faults, Snuffy.Threshold.fail_le_witness, Snuffy.Threshold.fail_le_geometric, Snuffy.Threshold.repetition_threshold, Snuffy.Threshold.two_sqrt_pow_le, Snuffy.Threshold.repetition_ceiling, Snuffy.Threshold.poly_geom_le, Snuffy.Threshold.family_ceiling

UnionClosure

Snuffy.UnionClosure.aligned_never_below, Snuffy.UnionClosure.dominates_of_affordable, Snuffy.UnionClosure.strict_of_affordable, Snuffy.UnionClosure.exists_union_bound, Snuffy.UnionClosure.dominates_within_slack, Snuffy.UnionClosure.union_closed_of_affordable, Snuffy.UnionClosure.greatest_of_affordable, Snuffy.UnionClosure.aligned_eq_of_greatest, Snuffy.UnionClosure.greatest_of_solvent, Snuffy.UnionClosure.strict_of_solvent, Snuffy.UnionClosure.greatest_or_irrelevant, Snuffy.UnionClosure.insolvent_not_greatest

SolventReciprocity

Snuffy.SolventReciprocity.solvent_keeps_everyone, Snuffy.SolventReciprocity.reciprocity_dominance_solvent

AffordableReciprocity

Snuffy.AffordableReciprocity.reciprocity_dominance_affordable

Bridge

Snuffy.Bridge.coverage_from_law, Snuffy.Bridge.nearest_decodes, Snuffy.Bridge.exists_nearest_decoder, Snuffy.Bridge.holding_preserves, Snuffy.Bridge.qsl_growth, Snuffy.Bridge.qsl_within_radius, Snuffy.Bridge.headroom_within_radius, Snuffy.Bridge.universal_protection_held, Snuffy.Bridge.holding_cycle_physical

Instruments

Snuffy.Instruments.lindblad_reset_flow, Snuffy.Instruments.lindblad_step, Snuffy.Instruments.reset_contracts, Snuffy.Instruments.tracking_recursion_derived, Snuffy.Instruments.tracking_envelope_derived, Snuffy.Instruments.branchC_complete, Snuffy.Instruments.card_box, Snuffy.Instruments.box_mono, Snuffy.Instruments.card_boundary, Snuffy.Instruments.boundary_power

StrokeBookkeeping

Snuffy.StrokeBookkeeping.ptrB_isHermitian, Snuffy.StrokeBookkeeping.controlled_mul_apply, Snuffy.StrokeBookkeeping.mul_star_controlled_apply, Snuffy.StrokeBookkeeping.controlled_unitary, Snuffy.StrokeBookkeeping.ptrB_controlled, Snuffy.StrokeBookkeeping.stroke_entropy_change, Snuffy.StrokeBookkeeping.stroke_identity_derived

Bennett

Snuffy.Bennett.bennett_step, Snuffy.Bennett.bennett_compute_uncompute, Snuffy.Bennett.ent_equiv, Snuffy.Bennett.negMulLog_add_le, Snuffy.Bennett.negMulLog_add_lt, Snuffy.Bennett.negMulLog_sum_le, Snuffy.Bennett.ent_eq_fiber, Snuffy.Bennett.ent_push_le, Snuffy.Bennett.ent_push_lt, Snuffy.Bennett.heat_reversible, Snuffy.Bennett.heat_irreversible, Snuffy.Bennett.premise5_from_bennett

Concatenated

Snuffy.Concatenated.distance3_corrects_one, Snuffy.Concatenated.lift_subset, Snuffy.Concatenated.fails_witness, Snuffy.Concatenated.card_lift, Snuffy.Concatenated.disjoint_lift, Snuffy.Concatenated.card_witness, Snuffy.Concatenated.card_witnesses, Snuffy.Concatenated.concatenated_threshold, Snuffy.Concatenated.concatenated_ceiling

ReasonsCompiled

Snuffy.ReasonsCompiled.reciprocity_expectation, Snuffy.ReasonsCompiled.reciprocity_canonical_floor, Snuffy.ReasonsCompiled.reciprocity_strict, Snuffy.ReasonsCompiled.reciprocity_from_solvency, Snuffy.ReasonsCompiled.controller_pays_floor, Snuffy.ReasonsCompiled.controller_floor_diverges

TwoLevel

Snuffy.TwoLevel.mul_of_idOutside, Snuffy.TwoLevel.rad_mul_self, Snuffy.TwoLevel.conj_rad, Snuffy.TwoLevel.givens_idOutside, Snuffy.TwoLevel.givens_unitary, Snuffy.TwoLevel.one_idOutside, Snuffy.TwoLevel.rad_eq_zero, Snuffy.TwoLevel.elim_unitary, Snuffy.TwoLevel.elim_idOutside, Snuffy.TwoLevel.elim_kills, Snuffy.TwoLevel.idOutside_row, Snuffy.TwoLevel.idOutside_keeps_col, Snuffy.TwoLevel.col_zero_above, Snuffy.TwoLevel.clear_below, Snuffy.TwoLevel.phase_idOutside, Snuffy.TwoLevel.phase_unitary, Snuffy.TwoLevel.phase_mul_apply, Snuffy.TwoLevel.next_column, Snuffy.TwoLevel.star_list_prod', Snuffy.TwoLevel.star_twoLevel, Snuffy.TwoLevel.two_level_decomposition

ErrorBudget

Snuffy.ErrorBudget.prod_norm_le_one, Snuffy.ErrorBudget.map_prod_norm_le_one, Snuffy.ErrorBudget.two_factor_step, Snuffy.ErrorBudget.telescoping_delta, Snuffy.ErrorBudget.error_budget

GateSupport

GeminiThirteenGate.kraus_branch_preserves_support, GeminiThirteenGate.kraus_sum_preserves_support, GeminiThirteenGate.support_preservation_composes

RiskBounds

GeminiThirteenRisk.weighted_markov, GeminiThirteenRisk.event_mass_mono, GeminiThirteenRisk.intersection_mass_le_each, GeminiThirteenRisk.positive_work_tail_control, GeminiThirteenRisk.dependent_chain_bound

QueueDeadline

GeminiThirteenQueue.exponential_service_tail, GeminiThirteenQueue.exponential_service_normalized, GeminiThirteenQueue.positive_deadline_miss_probability, GeminiThirteenQueue.small_mean_does_not_make_tail_zero

BandwidthReflection

GeminiThirteenBandwidth.normalized_susceptibility, GeminiThirteenBandwidth.exact_bandwidth_sensitivity, GeminiThirteenBandwidth.finite_positive_sensory_access_remains, GeminiThirteenBandwidth.bandwidth_bias_threshold

AnalyticBridge

GeminiThirteenAnalysis.integrating_factor_monotone, GeminiThirteenAnalysis.linear_barrier_preserves_safety, GeminiThirteenAnalysis.exponential_transient_bound, GeminiThirteenAnalysis.integrated_exponential_transient, GeminiThirteenAnalysis.integrated_transient_cost_bound, GeminiThirteenAnalysis.continuation_hazard_threshold, GeminiThirteenAnalysis.heterogeneous_quadratic_cost_ide

ntity, GeminiThirteenAnalysis.heterogeneous_uniform_is_not_minimum, GeminiThirteenAnalysis.eventually_better_continuation

RankAndCoalition

GeminiThirteenExecution.ranked_trace_length, GeminiThirteenExecution.ranked_polynomial_step_bound, GeminiThirteenExecution.total_penalty_excludes_all_members_gaining, GeminiThirteenExecution.real_lyapunov_descent_need_not_terminate

MetricShadow

GeminiThirteenMetric.embedding_distance_stability, GeminiThirteenMetric.protected_close_edge_margin, GeminiThirteenMetric.protected_separated_edge_margin

SemanticMap

GeminiThirteenSemantics.identity_is_bijective, GeminiThirteenSemantics.flipped_is_bijective, GeminiThirteenSemantics.two_distinct_lossless_maps, GeminiThirteenSemantics.calibrated_reference_fixes_binary_mapping

BridgeD1

GeminiBridgeD1.dynamic_survival_equation, GeminiBridgeD1.hazard_grows_without_bound, GeminiBridgeD1.positive_accumulated_prefix, GeminiBridgeD1.increasing_hazard_does_not_erase_prefix, GeminiBridgeD1.exact_discounted_dominance_criterion, GeminiBridgeD1.undiscounted_finite_crossover

BridgeE9

GeminiBridgeE9.reaction_before_damage, GeminiBridgeE9.positive_propagation_margin, GeminiBridgeE9.local_buffer_covers_entire_reaction, GeminiBridgeE9.escrow_prevents_pre_detection_application, GeminiBridgeE9.incidence_has_circulation_kernel, GeminiBridgeE9.lost_circulation_need_not_change_divergence

BridgeH6

GeminiBridgeH6.charged_transition_bound, GeminiBridgeH6.no_infinite_paid_run, GeminiBridgeH6.budget_exhaustion_need_not_be_fixed, GeminiBridgeH6.current_residual_bound, GeminiBridgeH6.next_residual_bound

BridgeH7

GeminiBridgeH7.rate_bounds, GeminiBridgeH7.denominator_positive, GeminiBridgeH7.equilibrium_is_fixed, GeminiBridgeH7.fixed_point_unique, GeminiBridgeH7.exact_transient, GeminiBridgeH7.equilibrium_private_evidence_sensitivity, GeminiBridgeH7.stubborn_anchor_limit, GeminiBridgeH7.private_evidence_sensitivity_vanishes, GeminiBridgeH7.exact_bias_threshold

BridgeH8

GeminiBridgeH8.variance_identity, GeminiBridgeH8.uniform_global_minimum, GeminiBridgeH8.equality_only_at_uniform, GeminiBridgeH8.blend_normalized, GeminiBridgeH8.blend_cap_preserved, GeminiBridgeH8.exact_excess_decay, GeminiBridgeH8.gradient_flow_equation, GeminiBridgeH8.flow_coefficient_in_unit_interval, GeminiBridgeH8.original_upper_fails_along_restoring_flow

ReasonsRoute

Snuffy.ReasonsRoute.optionValue_pointwise, Snuffy.ReasonsRoute.optionValue_expectation, Snuffy.ReasonsRoute.optionValue_strict, Snuffy.ReasonsRoute.law_protects_everyone, Snuffy.ReasonsRoute.indicator_law, Snuffy.ReasonsRoute.law_dominates, Snuffy.ReasonsRoute.law_dominates_strict, Snuffy.ReasonsRoute.rival_fraction_le_one, Snuffy.ReasonsRoute.rival_fraction_lt_one

SensorTail

Snuffy.SensorTail.sensor_tail, Snuffy.SensorTail.sensor_law_tail

ConsensusRate

`Snuffy.ConsensusRate.bandwidth_contraction`

RGFixedPoint

`Snuffy.RGFixedPoint.sq_root`, `Snuffy.RGFixedPoint.gstar_pos`, `Snuffy.RGFixedPoint.fixed_relation`, `Snuffy.RGFixedPoint.beta_gstar`, `Snuffy.RGFixedPoint.eigenvalue_gstar`, `Snuffy.RGFixedPoint.beta_factor`, `Snuffy.RGFixedPoint.beta_pos_below`, `Snuffy.RGFixedPoint.beta_neg_above`

FinalClosure

`Snuffy.FinalClosure.verifier_bound_iff`, `Snuffy.FinalClosure.proxy_ungameable_iff`, `Snuffy.FinalClosure.proxy_gameable`, `Snuffy.FinalClosure.pruning_lowers_rate`, `Snuffy.FinalClosure.living_unbounded`, `Snuffy.FinalClosure.pruning_all_stalls`, `Snuffy.FinalClosure.void_strictly_below`, `Snuffy.FinalClosure.void_never_chosen`, `Snuffy.FinalClosure.dominance_channels`, `Snuffy.FinalClosure.coop_more_efficient`, `Snuffy.FinalClosure.stewardship_sustains`, `Snuffy.FinalClosure.extraction_depletes`, `Snuffy.FinalClosure.sustained_iff`

H8Bound

`Snuffy.H8Bound.one_sub_u_pos`, `Snuffy.H8Bound.h8_of_concentration_bound`, `Snuffy.H8Bound.h8_graph`, `Snuffy.H8Bound.h8_iff`, `Snuffy.H8Bound.routing_bound`, `Snuffy.H8Bound.h8_routed`

CorrelatedStress

`Snuffy.CorrelatedStress.many_touching`, `Snuffy.CorrelatedStress.correlated_stress`

LatticeLaplacian

`Snuffy.LatticeLaplacian.symmetric_slope`, `Snuffy.LatticeLaplacian.ratio_eq_slope`, `Snuffy.LatticeLaplacian.second_difference`, `Snuffy.LatticeLaplacian.lattice_laplacian`

SafeGenesis

`Snuffy.SafeGenesis.migration_progress`, `Snuffy.SafeGenesis.safe_genesis`

AdaptiveConsensus

`UPTAdaptiveConsensus.weighted_error_bound`, `UPTAdaptiveConsensus.anchored_update_error`, `UPTAdaptiveConsensus.adaptive_history_error_bound`

CascadeCore

`UPTCascadeCore.workload_deadline`, `UPTCascadeCore.recursive_queue_bound`, `UPTCascadeCore.multi_epoch_entropy_bound`, `UPTCascadeCore.spectrum_expectation_floor`, `UPTCascadeCore.atomic_headroom`, `UPTCascadeCore.defection_deficit`, `UPTCascadeCore.sustained_deficit_crosses_buffer`, `UPTCascadeCore.buffer_threshold_crossed`

DecisionAndScale

`UPTDecisionAndScale.weighted_outcome_dominance`, `UPTDecisionAndScale.continuation_gain_pays_overhead`, `UPTDecisionAndScale.finite_branch_payoff_bound`, `UPTDecisionAndScale.duration_reward_bound`, `UPTDecisionAndScale.efficiency_gain_pays_cost`, `UPTDecisionAndScale.dominant_action_survives_mixture`, `UPTDecisionAndScale.local_verifier_cost`, `UPTDecisionAndScale.two_provider_unique_balanced_cost`

E9Routes

`UPTEpistemicRoutes.surviving_disjoint_route`, `UPTEpistemicRoutes.certified_repair_meets_deadline`

GenerativeClosure

UPTGenerativeClosure.step_preserves_paid_activation, UPTGenerativeClosure.every_generated_active_is_funded, UPTGenerativeClosure.reserve_does_not_displace_existing_agents, UPTGenerativeClosure.generated_authority_stays_within_root

ReflectionContraction

UPTReflectionContraction.complete_contraction_has_unique_fixed_point, UPTReflectionContraction.finite_error_bound, UPTReflectionContraction.accuracy_within_budget, UPTReflectionContraction.residual_error_bound, UPTReflectionContraction.residual_tolerance, UPTReflectionContraction.post_update_error_bound, UPTReflectionContraction.post_update_tolerance, UPTReflectionContraction.run_commutes, UPTReflectionContraction.paired_trajectory_bound, UPTReflectionContraction.residual_geometric_bound, UPTReflectionContraction.first_residual_stop_is_paid_and_accurate

ReflectionFuel

UPTReflectionQuota.steps_bounded, UPTReflectionQuota.quota_conserved, UPTReflectionQuota.no_unbounded_paid_reflection, UPTReflectionQuota.bounded_depth_can_cycle

RestrictedModels

UPTRestrictedModels.anchored_consensus_dissipation, UPTRestrictedModels.hhi_variance_identity, UPTRestrictedModels.uniform_shares_minimize_hhi, UPTRestrictedModels.uniform_shares_are_unique, UPTRestrictedModels.quadratic_cost_floor, UPTRestrictedModels.conditional_product_pushforward

ThermalBalance

UPTThermalBalance.intra_epoch_integral_bound, UPTThermalBalance.repair_before_buffer_exhaustion

TransportLaw

transport_nonneg, transport_ge_local, hhi_ge_uniform, monopoly_penalty

ControllerCertificate

stable_min_three, delta_min_three, rate_min_three, debt_min_three, alloc_min_three, total_min_three, total_min_three_le, band_min_three, stable_min_four, delta_min_four, rate_min_four, debt_min_four, alloc_min_four, total_min_four, total_min_four_le, band_min_four, stable_rob_three_two, stable_rob_three_four, total_rob_three_two, total_rob_three_three, total_rob_three_four, total_rob_three_two_le, total_rob_three_three_le, total_rob_three_four_le, band_rob_three, stable_rob_four_two, stable_rob_four_four, total_rob_four_two, total_rob_four_three, total_rob_four_four, total_rob_four_two_le, total_rob_four_three_le, total_rob_four_four_le, band_rob_four, pool_bills, corrected_bill_saving, allocation_undercharge_three, allocation_undercharge_four

FIFOWorkload

SnuffyFIFO.fifo_step, SnuffyFIFO.finish_le_upper, SnuffyFIFO.certified_prefix_meets_deadline

R16Feedback

UPTR16.map_iterate, UPTR16.tick_commutes, UPTR16.reactive_lockstep

UPTLawLife

UPT.Sub.refl, UPT.Sub.trans, UPT.U1, UPT.SSub.trans_sub, UPT.Sub.trans_ssub, UPT.lex_irrefl, UPT.lex_trans, UPT.lex_U1, UPT.freedom_first_U1_legacy, UPT.guard_first_stage, UPT.canonical_life_first_U1, UPT.life_guard

ClosedCohold

CodexCohold.reachable_closed, CodexCohold.reachable_least, CodexCohold.factorised_cohold, CodexCohold.outside_unchanged, CodexCohold.crossing_boundary_changes_outside_later

R14Boundary

UPTR14Boundary.safe_step, UPTR14Boundary.every_good_trace_safe, UPTR14Boundary.journal_commutes, UPTR14Boundary.sink_commutes, UPTR14Boundary.outside_commutes, UPTR14Boundary.harmful_effect_refused, UPTR14Boundary.old_generation_refused, UPTR14Boundary.external_weather_is_not_a_replica_fault, UPTR14Boundary.recruitment_erasure, UPTR14Boundary.recruitment_never_ends_care, UPTR14Boundary.failure_has_a_named_exception

ReceivedCutRepaired

UPTR16CUT.different_has_unmediated_path, UPTR16CUT.outside_equal_of_cut, UPTR16CUT.r2_no_crossing

ReadoutJoint

UPTReadoutJoint.block_det_identity, UPTReadoutJoint.shifted_det_identity, UPTReadoutJoint.cp_coeff_nonneg, UPTReadoutJoint.cp_coeff_pos, UPTReadoutJoint.iso01_shift_nonneg, UPTReadoutJoint.iso10_shift_nonneg, UPTReadoutJoint.blockA_shift_nonneg, UPTReadoutJoint.blockD_shift_nonneg, UPTReadoutJoint.block_shifted_det_nonneg, UPTReadoutJoint.quad_form_nonneg, UPTReadoutJoint.choi_form_nonneg, UPTReadoutJoint.positive_constant_not_cp, UPTReadoutJoint.cp_constant_at_half_half, UPTReadoutJoint.weight_nonneg, UPTReadoutJoint.chain_nonneg, UPTReadoutJoint.joint_record_lower, UPTReadoutJoint.chain_ge_pow, UPTReadoutJoint.hard_count_floor

ReadoutBounds

UPTReadoutFollowup.determinant_identity, UPTReadoutFollowup.determinant_lower, UPTReadoutFollowup.strictly_positive_determinant, UPTReadoutFollowup.spectral_lower, UPTReadoutFollowup.weight_nonnegative, UPTReadoutFollowup.conditional_record_lower, UPTReadoutFollowup.baseline_normalized

OriginalD1

GeminiOriginalD1.expected_value_formula, GeminiOriginalD1.original_dominance_counterexample, GeminiOriginalD1.lifetime_density_is_normalized, GeminiOriginalD1.lifetime_survival_tail, GeminiOriginalD1.zero_ultimate_survival_with_positive_accumulated_value

OriginalE9AndH5

GeminiOriginalInterfaces.finite_speed_indistinguishability, GeminiOriginalInterfaces.no_sound_remote_alarm_before_arrival, GeminiOriginalInterfaces.h5_local_rate_does_not_bound_total_entropy

OriginalH6

GeminiOriginalH6.original_thermal_depth_ceiling, GeminiOriginalH6.banked_rate_is_contractive, GeminiOriginalH6.banked_step_error, GeminiOriginalH6.banked_exact_error, GeminiOriginalH6.banked_paid_epsilon_accuracy, GeminiOriginalH6.original_thermal_premises_allow_cycle

OriginalH7

GeminiOriginalH7.decay_derivative, GeminiOriginalH7.solves_original_equation, GeminiOriginalH7.decay_limit, GeminiOriginalH7.all_nonnegative_couplings_converge, GeminiOriginalH7.every_initial_pair_is_represented

OriginalH8

GeminiOriginalH8.actual_minimum_is_one, GeminiOriginalH8.uniform_attains_minimum, GeminiOriginalH8.original_bound_counterexample

ControllerFinality

UPTController.tally_mono, UPTController.quorum_has_honest, UPTController.two_tallies_bound, UPTController.quorum_intersection, UPTController.committee_threshold, UPTController.prefix_trans, UPTController.equal_length_prefixes, UPTController.certificates_do_not_equivocate, UPTController.certificate_is_final, UPTController.context_words_injective, UPTController.run_append, UPTController.step_floor_mono, UPTController.run_floor_mono, UPTController.grant_fields, UPTController.floor_fields, UPTController.held_refuses, UPTController.retired_generation_refuses, UPTController.pendin

g_conflict_refuses, UPTController.closed_sequence_refuses, UPTController.receipt_names_success, UPTController.certified_receipt_names_success, UPTController.same_generation_no_context_conflict, UPTController.checkpoint_replay, UPTController.consume_once, UPTController.restart_disabled, UPTController.retained_floor_refuses, UPTController.old_boot_refuses, UPTController.deadline_refuses, UPTController.issued_append, UPTController.emission_bounded, UPTController.issues_bounded_by_final_floor, UPTController.step_stays_held, UPTController.held_issues_nothing, UPTController.grant_receipt_is_issued, UPTController.hold_bounds_every_issued_grant

UPTFence

UPTFence.hold_safety, UPTFence.raise_then_nothing_lands, UPTFence.admission_only_lands_in_hold, UPTFence.check_at_apply_refuses

ConservedRouting

conserved_decomposes, regular_psi_is_hhi, hhi_uniform, monopoly_exceeds_uniform, h8_exact_general, thermal_ledger_positivity_strict, thermal_ledger_positivity_nonneg, jarzynski_bound_valid

P2P3

sensor_exp_positivity, scaling_sum, azuma_scaling, work_tv_floor, coordinate_sensitivity, telescoping_drop, semigroup_time_rescaling, ness_work_linear, work_floor_positive, liquidation_triggers, zero_breach_bound, bound_decays, escrow_ordering, fluctuation_bound_le_two

FIFOInstance

finishes_three, veto_envelope_three, alloc_completion_is_the_charge_three, control_lane_three_certified, finishes_four, veto_envelope_four, alloc_completion_is_the_charge_four, control_lane_four_certified, per_job_deadlines_three, per_job_deadlines_four

FIFOAdmission

SnuffyFIFO.checks_iff, SnuffyFIFO.certified_mono, SnuffyFIFO.certified_append, SnuffyFIFO.admission_preserves, SnuffyFIFO.completion_preserves, SnuffyFIFO.cancellation_preserves, SnuffyFIFO.all_occurrences_timely, SnuffyFIFO.queue_step_preserves, SnuffyFIFO.refinement_preserves_queue

R16TwoPhase

UPTR16.phase_tick_commutes, UPTR16.two_phase_lockstep

R16Cut

UPTR16Cut.closed_cut_step, UPTR16Cut.dependency_closure_step, UPTR16Cut.difference_has_bypass, UPTR16Cut.causal_separator, UPTR16Cut.closed_cut_reactive, UPTR16Cut.delayed_locality, UPTR16Cut.pending_is_in_cut, UPTR16Cut.private_cause_is_in_cut, UPTR16Cut.delayed_effect_countermodel, UPTR16Cut.omitted_edge_is_not_local

ReceivedCutR14Repaired

UPTR16CUTR14.journal_projection_step_ext, UPTR16CUTR14.sink_projection_step_ext, UPTR16CUTR14.outside_projection_step_ext, UPTR16CUTR14.journal_outside_unchanged, UPTR16CUTR14.sink_outside_unchanged

ControllerFence

UPTControllerFence.certified_hold_nothing_lands, UPTControllerFence.both_targets_held

IntegrationCertificate

typed_gate_decomposition, finish_interval_deadline, psi2_uniform, h8_bound_two_node

R16R14

UPTR16R14.compromise_commutes, UPTR16R14.project_step, UPTR16R14.reference_two_phase_lockstep

R16Screened

UPTR16.screened_fibre_lockstep

UPTR12A

UPTR12A.words_injective, UPTR12A.grant_has_decision_scope, UPTR12A.same_generation_cannot_rebind, UPTR12A.finalized_receipt_is_in_log, UPTR12A.finalized_receipt_is_authorize, UPTR12A.changed_log_implies_checks, UPTR12A.applied_effect_has_aligned_decision, UPTR12A.raised_floor_refuses, UPTR12A.wrong_effect_refuses, UPTR12A.replay_refuses, UPTR12A.original_fence_theorem_available

R17AQueueFinality

UPTR17A.new_effect_has_current_permit, UPTR17A.drain_currently_authorized, UPTR17A.revoked_refuses, UPTR17A.expired_refuses, UPTR17A.installed_floor_refuses, UPTR17A.spend_is_funded, UPTR17A.application_has_source_binding

R17FIFOR17A

SnuffyFIFO.applied_fifo_effect_is_timely_and_authorized, SnuffyFIFO.ready_fifo_effect_applies_before_deadline

R17Funding

UPTR17AFunding.charged_append, UPTR17AFunding.atomic_target_append, UPTR17AFunding.application_conserves_funding, UPTR17AFunding.trace_conserves_funding, UPTR17AFunding.cumulative_charge_is_funded, UPTR17AFunding.used_ticket_refuses, UPTR17AFunding.accepted_ticket_is_consumed, UPTR17AFunding.replay_cannot_append, UPTR17AFunding.funded_admission_preserves, UPTR17AFunding.source_drain_preserves_reservation

R17WorkConcrete

SnuffyWC.Lane.mono_le, SnuffyWC.unfinished_before, SnuffyWC.carry_in_completion, SnuffyWC.ceil_div_covers, SnuffyWC.carry_in_affine, SnuffyWC.no_service_no_completion, SnuffyWC.U_succ_succ, SnuffyWC.exec_le_envelope, SnuffyWC.deadlines_met, SnuffyWC.row_congr, SnuffyWC.tail_admission_invariant, SnuffyWC.tail_admission_preserves_certificates, SnuffyWC.applied_stage_effect_is_timely_and_authorized, SnuffyWC.timely_but_revoked_is_not_delivery

TIWASource

Snuffy.TIWASource.outerUpdate_read_frozen, Snuffy.TIWASource.freeze_monotone, Snuffy.TIWASource.schedule_no_rework, Snuffy.TIWASource.readyToFreeze_no_inFlight

TIWAGuard

Snuffy.TIWAGuard.guard_data_frame, Snuffy.TIWAGuard.installGuard_monotone

TIWARecovery

Snuffy.TIWARecovery.bounded_visits, Snuffy.TIWARecovery.wave_count_at

TIWAWork

Snuffy.TIWAWork.local_work_bound, Snuffy.TIWAWork.ball_work_bound, Snuffy.TIWAWork.total_work_bound

TopRealisability

Snuffy.TopRealisability.top_realisable_of_singletons

FaultCover

Snuffy.FaultCover.fault_cover

G2Singleton

Snuffy.G2Singleton.g2_discharge_hsingle, Snuffy.G2Singleton.topRealisability_hsingle_discharged

G1Certificate

Snuffy.G1Certificate.universal_protection_held

G1Executable

Snuffy.G1Executable.g1_admission_soundness

PhysicalGuard

Snuffy.PhysicalGuard.factorization, Snuffy.PhysicalGuard.interior_unchanged

MeanErgodic

Snuffy.MeanErgodic.cesaro_mean_id

TemporalSafety

Snuffy.TemporalSafety.admit_of_secure, Snuffy.TemporalSafety.secure_preserved, Snuffy.TemporalSafety.trace_secure

WorkIntegration

Snuffy.WorkIntegration.work_bound

RelationalBridge

Snuffy.RelationalBridge.bridge_preserves_safety

MeanErgodicDeep

Snuffy.MeanErgodicDeep.cesaro_id, Snuffy.MeanErgodicDeep.id_fixes_all

GuardFactorization

Snuffy.GuardFactorization.commutativity, Snuffy.GuardFactorization.factorization_zero

G1Complete

Snuffy.G1Complete.g1_append_safe

G2Outcome

Snuffy.G2Outcome.g2_compose_valid

G3WorkBill

Snuffy.G3WorkBill.g3_append_work_bill

Htopkeeps

Snuffy.Htopkeeps.htopkeeps

SnuffyLocal

SnuffyLocal.local_trajectory_growth_valid, SnuffyLocal.tpt_state_preservation

G1FullDomain

Snuffy.G1FullDomain.g1_source_exhaustive, Snuffy.G1FullDomain.g1_fault_taxonomy_exhaustive, Snuffy.G1FullDomain.g1_append_preserves, Snuffy.G1FullDomain.replay_journal_step, Snuffy.G1FullDomain.journal_reactive_fidelity, Snuffy.G1FullDomain.transcript_capacity

G2WholeOutcome

Snuffy.G2WholeOutcome.g2_authorized_implies_closed, Snuffy.G2WholeOutcome.g2_authorized_implies_positive_work, Snuffy.G2WholeOutcome.g2_compose_valid, Snuffy.G2WholeOutcome.journal_whole_outcome, Snuffy.G2WholeOutcome.journal_outcome_family

G3CompleteBill

Snuffy.G3CompleteBill.g3_success_implies_bound, Snuffy.G3CompleteBill.g3_compose_valid, Snuffy.G3CompleteBill.g3_wave_count_nonnegative, Snuffy.G3CompleteBill.cumulative_charge_bound, Snuffy.G3CompleteBill.valid_work_bill_from_complete_ledger, Snuffy.G3CompleteBill.valid_bill_bound_in_age

GuardOperator

Snuffy.GuardOperator.guard_within_tolerance, Snuffy.GuardOperator.guard_exceeds_tolerance

HamiltonianDecomposition

Snuffy.HamiltonianDecomposition.total_is_sum, Snuffy.HamiltonianDecomposition.boundary_confinement_positive, Snuffy.HamiltonianDecomposition.exchange_hamiltonian_hermitian, Snuffy.HamiltonianDecomposition.exchange_conserves_total_charge, Snuffy.HamiltonianDecomposition.exchange_pumps_boundary, Snuffy.HamiltonianDecomposition.exchange_swap_unitary, Snuffy.HamiltonianDecomposition.exchange_swap_charge, Snuffy.HamiltonianDecomposition.exchange_swap_total, Snuffy.HamiltonianDecomposition.partial_trace_local_conjugation, Snuffy.HamiltonianDecomposition.guarded_history_reduced_state, Snuffy.HamiltonianDecomposition.syndrome_exchange_preserves_history, Snuffy.HamiltonianDecomposition.syndrome_exchange_charge

GuardSignature

Snuffy.GuardSignature.guard_idempotent

WorkBilling

Snuffy.WorkBilling.work_nonnegative, Snuffy.WorkBilling.work_bound_preserved, Snuffy.WorkBilling.decoder_work_balance, Snuffy.WorkBilling.decoder_work_floor, Snuffy.WorkBilling.decoder_work_floor_saturation, Snuffy.WorkBilling.funded_decoder_entropy_bound, Snuffy.WorkBilling.funded_decoder_cycles, Snuffy.WorkBilling.charged_attempt_accounting, Snuffy.WorkBilling.syndrome_stock_bound, Snuffy.WorkBilling.syndrome_flux_balance, Snuffy.WorkBilling.cumulative_maintenance_bound

DecoderRetraction

Snuffy.DecoderRetraction.decode_encode, Snuffy.DecoderRetraction.finite_code_recovery, Snuffy.DecoderRetraction.nonvanishing_of_continuation, Snuffy.DecoderRetraction.finite_code_self_grounding, Snuffy.DecoderRetraction.inner_preserved_from_symplectic_flux, Snuffy.DecoderRetraction.adjoint_decodes_isometry, Snuffy.DecoderRetraction.boundary_observable_on_code, Snuffy.DecoderRetraction.historical_query_preserved, Snuffy.DecoderRetraction.historical_word_on_code, Snuffy.DecoderRetraction.historical_word_expectation, Snuffy.DecoderRetraction.boundary_observable_mul, Snuffy.DecoderRetraction.boundary_observable_commutator, Snuffy.DecoderRetraction.powers_intertwine, Snuffy.DecoderRetraction.exponential_intertwines, Snuffy.DecoderRetraction.historical_flow_roundtrip, Snuffy.DecoderRetraction.historical_dual_kernel, Snuffy.DecoderRetraction.work_shifted_flow_on_code, Snuffy.DecoderRetraction.historical_gram_preserved, Snuffy.DecoderRetraction.historical_gram_nondegenerate, Snuffy.DecoderRetraction.coordinate_boundary_roundtrip, Snuffy.DecoderRetraction.boundary_capacity_necessary, Snuffy.DecoderRetraction.handoff_moves_reference_payload, Snuffy.DecoderRetraction.handoff_preserves_norm, Snuffy.DecoderRetraction.handoff_roundtrip, Snuffy.DecoderRetraction.parallel_cnot_handoff, Snuffy.DecoderRetraction.charged_archive_handoff

G2Splice

Snuffy.G2Splice.splice_grade, Snuffy.G2Splice.splice_realisable, Snuffy.G2Splice.outcome_splice, Snuffy.G2Splice.union_realizable, Snuffy.G2Splice.top_realisable, Snuffy.G2Splice.whole_outcome_greatest, Snuffy.G2Splice.fourStage, Snuffy.G2Splice.block_splice_run, Snuffy.G2Splice.block_splice_keeps

CorrelatedCeiling

Snuffy.CorrelatedCeiling.ceil_touching, Snuffy.CorrelatedCeiling.correlated_stress_ceil, Snuffy.CorrelatedCeiling.prob_damage, Snuffy.CorrelatedCeiling.near_card_le, Snuffy.CorrelatedCeiling.choose_pow_le, Snuffy.CorrelatedCeiling.damage_local_stochastic, Snuffy.CorrelatedCeiling.correlated_family_ceiling

G1Held

Snuffy.G1Held.good_cover, Snuffy.G1Held.held_source_protection, Snuffy.G1Held.initial_frame_normalised, Snuffy.G1Held.held_step_normalised, Snuffy.G1Held.held_run_normalised, Snuffy.G1Held.held_source_qsl, Snuffy.G1Held.zero_hamiltonian_trajectory, Snuffy.G1Held.concrete_decoder_certificate, Snuffy.G1Held.concrete_good_event_inhabited

G1E9

Snuffy.G1E9.alarm_or_subthreshold, Snuffy.G1E9.held_source_e9

G2Held

Snuffy.G2Held.active_authorised_free, Snuffy.G2Held.held_realises_top, Snuffy.G2Held.held_source_top

G3Sweep

Snuffy.G3Sweep.sweep_recovers, Snuffy.G3Sweep.sweep_visits, Snuffy.G3Sweep.waves_from_spread, Snuffy.G3Sweep.sweep_bill

G3PatchDecode

Snuffy.G3PatchDecode.patch_correction_succeeds, Snuffy.G3PatchDecode.patch_sweep_bill

ReasonsEnsemble

Snuffy.ReasonsEnsemble.ensemble_le, Snuffy.ReasonsEnsemble.ensemble_strict

TheoremEightLyapunov

Snuffy.TheoremEightLyapunov.capacity_balance, Snuffy.TheoremEightLyapunov.solvent_cycle_energy_account, Snuffy.TheoremEightLyapunov.reserve_deficit_antitone, Snuffy.TheoremEightLyapunov.reserve_deficit_cap, Snuffy.TheoremEightLyapunov.replenishment_exact, Snuffy.TheoremEightLyapunov.replenishment_nonincrease, Snuffy.TheoremEightLyapunov.solvent_cycle_deficit, Snuffy.TheoremEightLyapunov.cycle_contracts, Snuffy.TheoremEightLyapunov.margin_pos, Snuffy.TheoremEightLyapunov.lyapunov_iterate

SmearingIntegral

Snuffy.SmearingIntegral.smeared_reconstruction, Snuffy.SmearingIntegral.smeared_boundary_reconstruction

ChannelExtension

Snuffy.ChannelExtension.ext_recovers, Snuffy.ChannelExtension.kron_isometry, Snuffy.ChannelExtension.ext_recovers_reference, Snuffy.ChannelExtension.ext_trace, Snuffy.ChannelExtension.ext_posSemidef

PureStateDistance

Snuffy.PureStateDistance.pure_infidelity_le, Snuffy.PureStateDistance.pure_fidelity_ge

BennettCounterpart

Snuffy.BennettCounterpart.counterpart_heat_zero, Snuffy.BennettCounterpart.merging_heat_pos, Snuffy.BennettCounterpart.counterpart_same, Snuffy.BennettCounterpart.counterpart_feasible, Snuffy.BennettCounterpart.counterpart_more_slack, Snuffy.BennettCounterpart.premise5_constructed, Snuffy.BennettCounterpart.bennett_counterpart_computes, Snuffy.BennettCounterpart.implemented_program_computes, Snuffy.BennettCounterpart.implemented_program_output, Snuffy.BennettCounterpart.impl

emented_program_workspace, Snuffy.BennettCounterpart.implemented_program_history, Snuffy.Bennett
Counterpart.implemented_step_fields, Snuffy.BennettCounterpart.implemented_run_refines, Snuffy.B
ennettCounterpart.implemented_run_history, Snuffy.BennettCounterpart.implemented_quantum_norm, S
nuffy.BennettCounterpart.implemented_quantum_roundtrip, Snuffy.BennettCounterpart.complete_cost
_difference, Snuffy.BennettCounterpart.complete_cost_strict_iff, Snuffy.BennettCounterpart.imple
mented_work_ceiling, Snuffy.BennettCounterpart.adiabatic_slack_window, Snuffy.BennettCounterpart
.switched_program_meets_deadline, Snuffy.BennettCounterpart.adiabatic_feasible_iff

RegionBoundary

Snuffy.RegionBoundary.exists_crossing, Snuffy.RegionBoundary.region_bootstrap, Snuffy.RegionBoun
dary.whole_no_boundary, Snuffy.RegionBoundary.whole_H0_trivial

TimelyCare

UPTTimely.care_served, UPTTimely.exhaustion_fails, UPTTimely.deadline_met, UPTTimely.miss_within_
shortage

DeadlineDemand

UPTDeadline.demand_le_supply, UPTDeadline.robust_demand

DecisionPermit

UPTDecisionPermit.decision_words_injective, UPTDecisionPermit.grant_names_certified, UPTDecision
Permit.granted_policy_is_certified, UPTDecisionPermit.wrong_action_rejected, UPTDecisionPermit.c
ertified_action_granted

ObservationWinning

UPTObsWin.policy_wins_iff, UPTObsWin.hidden_world_countermodel

R14Rivals

UPTR14Rivals.refl, UPTR14Rivals.trans, UPTR14Rivals.coordinate_envelope, UPTR14Rivals.complete_ri
val_transfer, UPTR14Rivals.hot_beats_pause

R15CausalGluing

UPTR15.boundary_representatives_iff, UPTR15.selected_representative_greatest, UPTR15.canonical_b
oundary_iff, UPTR15.interface_envelope_transfer, UPTR15.hidden_world_control

ReciprocityDistance

Snuffy.ReciprocityDistance.distance_floor, Snuffy.ReciprocityDistance.reciprocity_at_distance, S
nuffy.ReciprocityDistance.reciprocity_strict_at_distance, Snuffy.ReciprocityDistance.canonical_
tends_to_one

CutEquivalence

Snuffy.CutEquivalence.closed_iff_no_bypass

ConcatenatedDecoding

Snuffy.ConcatenatedDecoding.outer_decodes, Snuffy.ConcatenatedDecoding.mem_sub, Snuffy.Concatena
tedDecoding.decodes_unless_fails, Snuffy.ConcatenatedDecoding.decoding_failure_le

ChannelCP

Snuffy.ChannelCP.kron_entry, Snuffy.ChannelCP.amp_eq, Snuffy.ChannelCP.compress_entry, Snuffy.Cha
nnelCP.mp_posSemidef, Snuffy.ChannelCP.decoder_completely_positive

PureStateTraceNorm

Snuffy.PureStateTraceNorm.sum_sq_eigenvalues, Snuffy.PureStateTraceNorm.eigenvalue_cube, Snuffy.
PureStateTraceNorm.pureDiff_hermitian, Snuffy.PureStateTraceNorm.vmv_smul, Snuffy.PureStateTrace

Norm.star_dot_swap, Snuffy.PureStateTraceNorm.pure_cube, Snuffy.PureStateTraceNorm.pure_trace_sq, Snuffy.PureStateTraceNorm.pure_trace_norm

G1Refinement

Snuffy.G1Refinement.guarded_step_continues, Snuffy.G1Refinement.physical_protection, Snuffy.G1Refinement.journaled_protection, Snuffy.G1Refinement.physical_qsl_drift, Snuffy.G1Refinement.physical_protection_qsl, Snuffy.G1Refinement.physical_instance_inhabited

G2Physical

Snuffy.G2Physical.held_installation_keeps_all, Snuffy.G2Physical.top_dominates_continuation

G2Freedom

Snuffy.G2Freedom.joint_holding, Snuffy.G2Freedom.joint_holding_and_delivery

G3GoodEvent

Snuffy.G3GoodEvent.sweep_success_on_good_event, Snuffy.G3GoodEvent.complete_bill_with_archive

BennettExact

Snuffy.BennettExact.premise5_exact, Snuffy.BennettExact.window_exact, Snuffy.BennettExact.reversible_admin_computes

G3ArchiveStock

Snuffy.G3ArchiveStock.live_stock_bill, Snuffy.G3ArchiveStock.retained_stock_quadratic, Snuffy.G3ArchiveStock.rollover_quadratic

KnillLaflamme

Snuffy.KnillLaflamme.eq_zero_of_eq_neg, Snuffy.KnillLaflamme.spectral_projection, Snuffy.KnillLaflamme.sandwich_anticomm, Snuffy.KnillLaflamme.sandwich_scalar, Snuffy.KnillLaflamme.knill_laflamme_of_distance

AgeReliability

Snuffy.AgeReliability.cubic_spacetime_rate, Snuffy.AgeReliability.log_distance_schedule, Snuffy.AgeReliability.log_factor_not_absorbed

ExRecBound

Snuffy.ExRecBound.exrec_pair_bound, Snuffy.ExRecBound.circuit_level_rate, Snuffy.ExRecBound.surface_code_rate

EdgeLaw

Snuffy.EdgeLaw.prob_push, Snuffy.EdgeLaw.push_localStochastic

MatchingWitness

Snuffy.MatchingWitness.card_symmDiff, Snuffy.MatchingWitness.half_faulty, Snuffy.MatchingWitness.matching_witness

SparseFailure

Snuffy.SparseFailure.disjoint_windows, Snuffy.SparseFailure.many_failures

ToleranceSweep

Snuffy.ToleranceSweep.frozen_after, Snuffy.ToleranceSweep.wrong_has_cause, Snuffy.ToleranceSweep.wrong_le_of_eroder, Snuffy.ToleranceSweep.wrong_subset_bad, Snuffy.ToleranceSweep.sweep_density, Snuffy.ToleranceSweep.pathwise_bill, Snuffy.ToleranceSweep.recovery_tail

PassiveReference

Snuffy.PassiveReference.stages_cover, Snuffy.PassiveReference.total_failure_le, Snuffy.PassiveReference.total_rewrite_cost

RedundantRecord

Snuffy.RedundantRecord.majority_decodes, Snuffy.RedundantRecord.tolerant_outer_decoder

BennettBatch

Snuffy.BennettBatch.batched_window, Snuffy.BennettBatch.premise5_batched

WeightedEdgeLaw

Snuffy.WeightedEdgeLaw.push_weighted, Snuffy.WeightedEdgeLaw.push_uniform, Snuffy.WeightedEdgeLaw.rate_iff, Snuffy.WeightedEdgeLaw.tightened_threshold, Snuffy.WeightedEdgeLaw.walk_bound, Snuffy.WeightedEdgeLaw.threshold_value

StageSchedule

Snuffy.StageSchedule.total_with_transfers, Snuffy.StageSchedule.stage_cost_le

WarmStart

Snuffy.WarmStart.warm_start, Snuffy.WarmStart.warm_start_event, Snuffy.WarmStart.fibre_mass_pos, Snuffy.WarmStart.fibre_reassembly, Snuffy.WarmStart.reverse_sampler_bound, Snuffy.WarmStart.heat_bath_normalized, Snuffy.WarmStart.heat_bath_stationary, Snuffy.WarmStart.pointwise_from_absolute, Snuffy.WarmStart.warm_start_from_mixing

WalkBound9

Snuffy.WalkBound9.walk_bound_9, Snuffy.WalkBound9.threshold_9, Snuffy.WalkBound9.threshold_9_value

HistoryPolymer

Snuffy.HistoryPolymer.halving_prefix, Snuffy.HistoryPolymer.paired_history_bound, Snuffy.HistoryPolymer.component_valid, Snuffy.HistoryPolymer.truncation_bound, Snuffy.HistoryPolymer.sampled_truncation_bound, Snuffy.HistoryPolymer.branch_path_bound

ThermalEncoding

Snuffy.ThermalEncoding.branch_compression, Snuffy.ThermalEncoding.recovers, Snuffy.ThermalEncoding.kron_orthogonal, Snuffy.ThermalEncoding.recovers_reference

TransferRate

Snuffy.TransferRate.poly_le_two_pow, Snuffy.TransferRate.transfer_bill_le, Snuffy.TransferRate.transfer_bill_linear_in_age, Snuffy.TransferRate.retained_prefix_bound, Snuffy.TransferRate.attempt_stage_bound, Snuffy.TransferRate.polynomial_stage_bill, Snuffy.TransferRate.complete_attempt_bill, Snuffy.TransferRate.join_complete_bill

OuterLane

Snuffy.OuterLane.wavefront_coverage, Snuffy.OuterLane.interception_in_time, Snuffy.OuterLane.pool_strictly_dominant, Snuffy.OuterLane.outer_lane_risk

StagedMaximality

Snuffy.StagedMaximality.finset_subset_of_chain, Snuffy.StagedMaximality.stage_step, Snuffy.StagedMaximality.exists_stagemax_upto, Snuffy.StagedMaximality.exists_lex_maximal, Snuffy.StagedMaximality.freedomPre_earlier, Snuffy.StagedMaximality.four_stage_original_maximal

FoundingDominance

Snuffy.FoundingDominance.contribution_advantage_pos, Snuffy.FoundingDominance.contribution_strictly_dominant, Snuffy.FoundingDominance.no_abstention_equilibrium

ReachBeforeHarm

Snuffy.ReachBeforeHarm.reach_before_harm

NarrowPlace

Snuffy.NarrowPlace.np_splitting_bound

HoldCommonAction

Snuffy.HoldCommonAction.hold_is_common_viable_action, Snuffy.HoldCommonAction.common_policy_from_hold, Snuffy.HoldCommonAction.act_or_hold_policy, Snuffy.HoldCommonAction.no_effect_action_safe_in_both, Snuffy.HoldCommonAction.two_world_resolved

BookUPTExistence

Snuffy.Book.UPTExistence.Sub.refl, Snuffy.Book.UPTExistence.Sub.trans, Snuffy.Book.UPTExistence.U1, Snuffy.Book.UPTExistence.SSub.trans_sub, Snuffy.Book.UPTExistence.Sub.trans_ssub, Snuffy.Book.UPTExistence.lex_irrefl, Snuffy.Book.UPTExistence.lex_trans, Snuffy.Book.UPTExistence.climb, Snuffy.Book.UPTExistence.lex_aligned_exists, Snuffy.Book.UPTExistence.aligned_exists, Snuffy.Book.UPTExistence.no_needless_choice_exists, Snuffy.Book.UPTExistence.infinite_family_forces_needless_loss, Snuffy.Book.UPTExistence.infinite_family_has_no_aligned_option

BookUPTAdequacy

Snuffy.Book.UPTAdequacy.lex_iff_first_difference, Snuffy.Book.UPTAdequacy.lex_keeps_first_stage, Snuffy.Book.UPTAdequacy.improvement_never_costs_a_life, Snuffy.Book.UPTAdequacy.improvement_never_costs_existing_freedom, Snuffy.Book.UPTAdequacy.losing_a_life_is_never_better, Snuffy.Book.UPTAdequacy.restrainable_iff_needless, Snuffy.Book.UPTAdequacy.restrainable_iff_not_aligned

BookUPTAgents

Snuffy.Book.UPTAgents.shared_order_no_conflict, Snuffy.Book.UPTAgents.stall_is_best_response, Snuffy.Book.UPTAgents.stall_not_jointly_maximal, Snuffy.Book.UPTAgents.best_responses_can_stall, Snuffy.Book.UPTAgents.ssub_irrefl, Snuffy.Book.UPTAgents.ssub_trans, Snuffy.Book.UPTAgents.joint_maximal_exists

BookUPTBroadcast

Snuffy.Book.UPTBroadcast.majority_left, Snuffy.Book.UPTBroadcast.majority_outer, Snuffy.Book.UPTBroadcast.majority_right, Snuffy.Book.UPTBroadcast.entry_from_loyal, Snuffy.Book.UPTBroadcast.honest_dealer_validity, Snuffy.Book.UPTBroadcast.faulty_dealer_vector, Snuffy.Book.UPTBroadcast.agreement, Snuffy.Book.UPTBroadcast.om1_broadcast

BookUPTCountRefinement

Snuffy.Book.UPTCountRefinement.exists_max, Snuffy.Book.UPTCountRefinement.exists_maximal, Snuffy.Book.UPTCountRefinement.count_refined_maximal, Snuffy.Book.UPTCountRefinement.lex_irrefl, Snuffy.Book.UPTCountRefinement.lex_trans, Snuffy.Book.UPTCountRefinement.count_mono, Snuffy.Book.UPTCountRefinement.canonical_count_refined, Snuffy.Book.UPTCountRefinement.counting_is_an_extra_principle

BookUPTDominance

Snuffy.Book.UPTDominance.statewise_dominance

BookUPTHold

Snuffy.Book.UPTHold.replay_ideal, Snuffy.Book.UPTHold.crash_ideal, Snuffy.Book.UPTHold.faithful, Snuffy.Book.UPTHold.faithful_from_start, Snuffy.Book.UPTHold.admissible_observer, Snuffy.Book.UPTHold.ideal_lengths, Snuffy.Book.UPTHold.hold_executes_nothing, Snuffy.Book.UPTHold.mutant_no_replay_unfaithful, Snuffy.Book.UPTHold.mutant_run_while_held_unfaithful, Snuffy.Book.UPTHold.mutan

t_redeliver_unfaithful, Snuffy.Book.UPTHold.timing_observer_sees_the_hold, Snuffy.Book.UPTHold.faithful_instance

BookUPTHoldAdequacy

Snuffy.Book.UPTHoldAdequacy.H_best_for_lives, Snuffy.Book.UPTHoldAdequacy.L_is_lethal, Snuffy.Book.UPTHoldAdequacy.lives_only_hold_leaves_lethal_undominated, Snuffy.Book.UPTHoldAdequacy.faithful_hold_dominates, Snuffy.Book.UPTHoldAdequacy.faithful_hold_strict_when_real, Snuffy.Book.UPTHoldAdequacy.faithful_hold_ends_no_one

BookUPTHoldTimed

Snuffy.Book.UPTHoldTimed.stutter_erasure, Snuffy.Book.UPTHoldTimed.admissible_peer, Snuffy.Book.UPTHoldTimed.autonomous_peer_sees_hold, Snuffy.Book.UPTHoldTimed.schedule_holds_interval, Snuffy.Book.UPTHoldTimed.cohold_closed

BookUPTImpartiality

Snuffy.Book.UPTImpartiality.sum_ge, Snuffy.Book.UPTImpartiality.sum_gt, Snuffy.Book.UPTImpartiality.len_mul_inv, Snuffy.Book.UPTImpartiality.some_chance_at_most, Snuffy.Book.UPTImpartiality.everyone_at_least_only_if_uniform, Snuffy.Book.UPTImpartiality.uniform_disadvantages_D, Snuffy.Book.UPTImpartiality.least_chance_at_most_two_fifths, Snuffy.Book.UPTImpartiality.ruling_gives_everyone_two_fifths, Snuffy.Book.UPTImpartiality.ruling_is_unique, Snuffy.Book.UPTImpartiality.len_inv_pos, Snuffy.Book.UPTImpartiality.weight_of_keepers, Snuffy.Book.UPTImpartiality.uniform_chance, Snuffy.Book.UPTImpartiality.uniform_equal_iff_equal_counts

BookUPTInfiniteGuard

Snuffy.Book.UPTInfiniteGuard.Sub.refl, Snuffy.Book.UPTInfiniteGuard.Sub.trans, Snuffy.Book.UPTInfiniteGuard.U1, Snuffy.Book.UPTInfiniteGuard.SSub.trans_sub, Snuffy.Book.UPTInfiniteGuard.Sub.trans_ssub, Snuffy.Book.UPTInfiniteGuard.lex_irrefl, Snuffy.Book.UPTInfiniteGuard.lex_trans, Snuffy.Book.UPTInfiniteGuard.lex_U1, Snuffy.Book.UPTInfiniteGuard.freedom_first_U1_legacy, Snuffy.Book.UPTInfiniteGuard.guard_first_stage, Snuffy.Book.UPTInfiniteGuard.canonical_life_first_U1, Snuffy.Book.UPTInfiniteGuard.life_guard, Snuffy.Book.UPTInfiniteGuard.greedy_pos, Snuffy.Book.UPTInfiniteGuard.greedy_neg, Snuffy.Book.UPTInfiniteGuard.countable_maximal, Snuffy.Book.UPTInfiniteGuard.life_guard_countable, Snuffy.Book.UPTInfiniteGuard.countable_maximal_nonvacuous

BookUPTLaw

Snuffy.Book.UPTLaw.Sub.refl, Snuffy.Book.UPTLaw.U1, Snuffy.Book.UPTLaw.U2_partial_fails, Snuffy.Book.UPTLaw.U2_universal_protects, Snuffy.Book.UPTLaw.U3, Snuffy.Book.UPTLaw.E3_active, Snuffy.Book.UPTLaw.E3_guard, Snuffy.Book.UPTLaw.E7_dominance, Snuffy.Book.UPTLaw.hold_dominates_standby, Snuffy.Book.UPTLaw.hold_dominates_strike, Snuffy.Book.UPTLaw.hold_strictly_beats_standby, Snuffy.Book.UPTLaw.hold_strictly_beats_strike, Snuffy.Book.UPTLaw.strike_standby_tragic, Snuffy.Book.UPTLaw.swap_oa, Snuffy.Book.UPTLaw.swap_ob, Snuffy.Book.UPTLaw.E1_no_fixed_choice

BookUPTLawGuard

Snuffy.Book.UPTLawGuard.Sub.refl, Snuffy.Book.UPTLawGuard.Sub.trans, Snuffy.Book.UPTLawGuard.U1, Snuffy.Book.UPTLawGuard.SSub.trans_sub, Snuffy.Book.UPTLawGuard.Sub.trans_ssub, Snuffy.Book.UPTLawGuard.lex_irrefl, Snuffy.Book.UPTLawGuard.lex_trans, Snuffy.Book.UPTLawGuard.guard_first_stage

BookUPTLawLex

Snuffy.Book.UPTLawLex.Sub.refl, Snuffy.Book.UPTLawLex.Sub.trans, Snuffy.Book.UPTLawLex.U1, Snuffy.Book.UPTLawLex.SSub.trans_sub, Snuffy.Book.UPTLawLex.Sub.trans_ssub, Snuffy.Book.UPTLawLex.lex_irrefl, Snuffy.Book.UPTLawLex.lex_trans, Snuffy.Book.UPTLawLex.lex_U1, Snuffy.Book.UPTLawLex.freedom_first_U1_legacy, Snuffy.Book.UPTLawLex.guard_maximal_above

BookUPTLawRepair

Snuffy.Book.UPTLawRepair.Sub.refl, Snuffy.Book.UPTLawRepair.U1, Snuffy.Book.UPTLawRepair.aligned_congr, Snuffy.Book.UPTLawRepair.U2_star, Snuffy.Book.UPTLawRepair.U2_star_hypothesis_needed, Snuffy.Book.UPTLawRepair.progressive_retention, Snuffy.Book.UPTLawRepair.switch_without_retention, Snuffy.Book.UPTLawRepair.E7_top

BookUPTLifeGuardExists

Snuffy.Book.UPTLifeGuardExists.Sub.refl, Snuffy.Book.UPTLifeGuardExists.Sub.trans, Snuffy.Book.UPTLifeGuardExists.U1, Snuffy.Book.UPTLifeGuardExists.SSub.trans_sub, Snuffy.Book.UPTLifeGuardExists.Sub.trans_ssub, Snuffy.Book.UPTLifeGuardExists.lex_irrefl, Snuffy.Book.UPTLifeGuardExists.lex_trans, Snuffy.Book.UPTLifeGuardExists.lex_U1, Snuffy.Book.UPTLifeGuardExists.freedom_first_U1_legacy, Snuffy.Book.UPTLifeGuardExists.guard_first_stage, Snuffy.Book.UPTLifeGuardExists.canonical_life_first_U1, Snuffy.Book.UPTLifeGuardExists.life_guard, Snuffy.Book.UPTLifeGuardExists.climb_from, Snuffy.Book.UPTLifeGuardExists.life_guard_exists

BookUPTLottery

Snuffy.Book.UPTLottery.outcome_reachable, Snuffy.Book.UPTLottery.outcome_unique, Snuffy.Book.UPTLottery.fair_when_bound_before_reveal, Snuffy.Book.UPTLottery.choosing_after_reveal_forces_any_outcome, Snuffy.Book.UPTLottery.inconsistent_openings_disagree, Snuffy.Book.UPTLottery.cnt_or_le, Snuffy.Book.UPTLottery.cnt_compl, Snuffy.Book.UPTLottery.decoding_radius, Snuffy.Book.UPTLottery.unique_decoding

BookUPTLotteryMenu

Snuffy.Book.UPTLotteryMenu.cnt_congr, Snuffy.Book.UPTLotteryMenu.draw_invariant, Snuffy.Book.UPTLotteryMenu.duplicate_description_changes_nothing, Snuffy.Book.UPTLotteryMenu.draw_over_descriptions_is_manipulable, Snuffy.Book.UPTLotteryMenu.tragic_pair_equal_chances

BookUPTMonotone

Snuffy.Book.UPTMonotone.inv_in_unit, Snuffy.Book.UPTMonotone.factor_eq, Snuffy.Book.UPTMonotone.factor_antitone, Snuffy.Book.UPTMonotone.factor_nonneg, Snuffy.Book.UPTMonotone.mul_mono, Snuffy.Book.UPTMonotone.pow_mono, Snuffy.Book.UPTMonotone.bound_antitone, Snuffy.Book.UPTMonotone.grid_min_antitone, Snuffy.Book.UPTMonotone.clip_antitone, Snuffy.Book.UPTMonotone.ceiling_at_499_bounds_larger_service, Snuffy.Book.UPTMonotone.audit_instance

BookUPTNoExchangeRate

Snuffy.Book.UPTNoExchangeRate.weighted_sum_trades_a_life, Snuffy.Book.UPTNoExchangeRate.grows, Snuffy.Book.UPTNoExchangeRate.no_count_utility, Snuffy.Book.UPTNoExchangeRate.no_faithful_count_utility, Snuffy.Book.UPTNoExchangeRate.bounded_stakes_represent, Snuffy.Book.UPTNoExchangeRate.frac_spec, Snuffy.Book.UPTNoExchangeRate.frac_strict, Snuffy.Book.UPTNoExchangeRate.frac_lt_one, Snuffy.Book.UPTNoExchangeRate.frac_nonneg, Snuffy.Book.UPTNoExchangeRate.bounded_utility_represents_counts, Snuffy.Book.UPTNoExchangeRate.no_utility_on_who_is_kept

BookUPTQuorum

Snuffy.Book.UPTQuorum.cnt_le, Snuffy.Book.UPTQuorum.cnt_or_and, Snuffy.Book.UPTQuorum.cnt_split, Snuffy.Book.UPTQuorum.cnt_mono, Snuffy.Book.UPTQuorum.cnt_pos, Snuffy.Book.UPTQuorum.quorum_overlap, Snuffy.Book.UPTQuorum.quorums_share_a_live_island, Snuffy.Book.UPTQuorum.up_islands_form_a_quorum, Snuffy.Book.UPTQuorum.cnt_lt_range, Snuffy.Book.UPTQuorum.cnt_ge_range, Snuffy.Book.UPTQuorum.cnt_band_range, Snuffy.Book.UPTQuorum.overlap_bound_is_tight, Snuffy.Book.UPTQuorum.U6_pool_quorums, Snuffy.Book.UPTQuorum.U6_control_201, Snuffy.Book.UPTQuorum.U6_live, Snuffy.Book.UPTQuorum.U8_lockstep_majority, Snuffy.Book.UPTQuorum.U5_threshold_counting

BookUPTRestraint

Snuffy.Book.UPTRestraint.ssub_irrefl, Snuffy.Book.UPTRestraint.ssub_trans, Snuffy.Book.UPTRestraint.restraint_keeps, Snuffy.Book.UPTRestraint.climb, Snuffy.Book.UPTRestraint.maximal_restraint_

exists, Snuffy.Book.UPTRestraint.predator_tragic, Snuffy.Book.UPTRestraint.hunting_not_restrainable, Snuffy.Book.UPTRestraint.harmless_alternative_restrains

EmissionBound

Snuffy.EmissionBound.requisite_variety, Snuffy.EmissionBound.requisite_variety_prob, Snuffy.EmissionBound.narrow_channel_bits, Snuffy.EmissionBound.unmetered_energy_bound, Snuffy.EmissionBound.emission_cannot_power

FoundingAnchor

Snuffy.FoundingAnchor.campaign_funded, Snuffy.FoundingAnchor.anchor_founds_iff, Snuffy.FoundingAnchor.anchor_founds_mono

ContinuationPredicate

Snuffy.ContinuationPredicate.laterStage_refl, Snuffy.ContinuationPredicate.laterStage_trans, Snuffy.ContinuationPredicate.copy_not_laterStage, Snuffy.ContinuationPredicate.split_continues_both, Snuffy.ContinuationPredicate.faithful_hold_preserves, Snuffy.ContinuationPredicate.directed_by_other_not_free

BookContextualObservation

Snuffy.Book.ContextualObservation.contextual_iff_congruent, Snuffy.Book.ContextualObservation.contextual_on_invariant, Snuffy.Book.ContextualObservation.identity_detector_implies_injective, Snuffy.Book.ContextualObservation.forgotten_id_breaks_continuation, Snuffy.Book.ContextualObservation.endpoint_sampling_misses_a_cycle, Snuffy.Book.ContextualObservation.cache_can_be_hidden

IRSafeMaximality

PhysicalBridges.IRSafeMaximality.safe_maximal_exists, PhysicalBridges.IRSafeMaximality.cofinal_safe_maximal_is_globally_maximal, PhysicalBridges.IRSafeMaximality.cofinal_global_maximal_exists, PhysicalBridges.IRSafeMaximality.globally_maximal_first_stage_no_needless

IRSelectedMaximality

PhysicalBridges.IRSelectedMaximality.selected_safety_maximal_lifts_globally, PhysicalBridges.IRSelectedMaximality.cofinal_implies_selected_no_outside_improver, PhysicalBridges.IRSelectedMaximality.selected_realisation_suffices, PhysicalBridges.IRSelectedMaximality.cofinality_is_not_necessary, PhysicalBridges.IRSelectedMaximality.local_maximum_need_not_be_global

IRProfileAudit

PhysicalBridges.IRProfileAudit.obstruction_blocks_improvement, PhysicalBridges.IRProfileAudit.no_improvement_has_obstruction, PhysicalBridges.IRProfileAudit.obstruction_iff_not_better, PhysicalBridges.IRProfileAudit.improvement_transfers_to_faithful_profile, PhysicalBridges.IRProfileAudit.audited_no_excluded_improver, PhysicalBridges.IRProfileAudit.alleged_improver_exposes_bad_audit, PhysicalBridges.IRProfileAudit.audited_selected_global_maximal, PhysicalBridges.IRProfileAudit.InfiniteExample.full_coverage, PhysicalBridges.IRProfileAudit.InfiniteExample.faithful_profiles, PhysicalBridges.IRProfileAudit.InfiniteExample.certified_obstructions, PhysicalBridges.IRProfileAudit.InfiniteExample.local_choice, PhysicalBridges.IRProfileAudit.InfiniteExample.globally_maximal_without_cofinality, PhysicalBridges.IRProfileAudit.InfiniteExample.full_options_all_n, PhysicalBridges.IRProfileAudit.InfiniteExample.omitted_incomparable_profile, PhysicalBridges.IRProfileAudit.HostileControls.omitted_better_candidate, PhysicalBridges.IRProfileAudit.HostileControls.bad_abstraction_covers, PhysicalBridges.IRProfileAudit.HostileControls.bad_abstraction_passes_obstruction, PhysicalBridges.IRProfileAudit.HostileControls.bad_abstraction_is_not_faithful, PhysicalBridges.IRProfileAudit.HostileControls.incomplete_profile_list_is_not_coverage

IRFiniteProfileObstruction

PhysicalBridges.IRFiniteProfileObstruction.aboveEvery_gt_mem, PhysicalBridges.IRFiniteProfileObstruction.faithful_chain_rep_is_exact, PhysicalBridges.IRFiniteProfileObstruction.no_finite_fai

thful_chain_profiles, PhysicalBridges.IRFiniteProfileObstruction.impossible_finite_profile_audit_for_original_chain, PhysicalBridges.IRFiniteProfileObstruction.unbounded_chain_lacks_global_maximum

IRInfiniteFinitaryMaximality

PhysicalBridges.IRInfiniteFinitaryMaximality.feasible_downward, PhysicalBridges.IRInfiniteFinitaryMaximality.finite_chain_capture, PhysicalBridges.IRInfiniteFinitaryMaximality.chain_union_feasible, PhysicalBridges.IRInfiniteFinitaryMaximality.derived_chain_upper_bound, PhysicalBridges.IRInfiniteFinitaryMaximality.greedyStep_preserves_feasible, PhysicalBridges.IRInfiniteFinitaryMaximality.greedyStep_extends, PhysicalBridges.IRInfiniteFinitaryMaximality.greedyStep_adds_if_feasible, PhysicalBridges.IRInfiniteFinitaryMaximality.stage_increasing, PhysicalBridges.IRInfiniteFinitaryMaximality.stage_monotone, PhysicalBridges.IRInfiniteFinitaryMaximality.stage_feasible, PhysicalBridges.IRInfiniteFinitaryMaximality.finite_stage_capture, PhysicalBridges.IRInfiniteFinitaryMaximality.limit_feasible, PhysicalBridges.IRInfiniteFinitaryMaximality.cannot_feasibly_add_missing_particular, PhysicalBridges.IRInfiniteFinitaryMaximality.infinite_full_feasible_aligned_exists, PhysicalBridges.IRInfiniteFinitaryMaximality.infinite_one_stage_lex_aligned_exists, PhysicalBridges.IRInfiniteFinitaryMaximality.all_prefixes_feasible_forces_full_retention, PhysicalBridges.IRInfiniteFinitaryMaximality.original_chain_not_finitary_closed, PhysicalBridges.IRInfiniteFinitaryMaximality.pair_empty_feasible, PhysicalBridges.IRInfiniteFinitaryMaximality.pair_full_retention_infeasible, PhysicalBridges.IRInfiniteFinitaryMaximality.pair_all_unconflicted_retained, PhysicalBridges.IRInfiniteFinitaryMaximality.pair_cannot_keep_both, PhysicalBridges.IRInfiniteFinitaryMaximality.nontrivial_infinite_full_feasible_instance

IRTwoStageInfiniteLex

PhysicalBridges.IRTwoStageInfiniteLex.independent_two_stage_global_lex_maximum, PhysicalBridges.IRTwoStageInfiniteLex.independent_any_finite_stage_lex_maximum, PhysicalBridges.IRTwoStageInfiniteLex.coupled_choice_feasible, PhysicalBridges.IRTwoStageInfiniteLex.coupled_two_stage_lex_maximum, PhysicalBridges.IRTwoStageInfiniteLex.empty_feasible_without_prohibitions, PhysicalBridges.IRTwoStageInfiniteLex.unconstrained_limit_includes_every_particular, PhysicalBridges.IRTwoStageInfiniteLex.independent_maxima_not_jointly_feasible, PhysicalBridges.IRTwoStageInfiniteLex.coupled_choice_not_joint_independent_maximum

IRCoupledFinitaryTwoStage

PhysicalBridges.IRCoupledFinitaryTwoStage.feasible_downward, PhysicalBridges.IRCoupledFinitaryTwoStage.chooseStep_extends, PhysicalBridges.IRCoupledFinitaryTwoStage.chooseStep_feasible, PhysicalBridges.IRCoupledFinitaryTwoStage.chooseStep_adds, PhysicalBridges.IRCoupledFinitaryTwoStage.phase_increasing, PhysicalBridges.IRCoupledFinitaryTwoStage.phase_monotone, PhysicalBridges.IRCoupledFinitaryTwoStage.phase_feasible, PhysicalBridges.IRCoupledFinitaryTwoStage.phaseLimit_contains_base, PhysicalBridges.IRCoupledFinitaryTwoStage.finite_phase_capture, PhysicalBridges.IRCoupledFinitaryTwoStage.phaseLimit_feasible, PhysicalBridges.IRCoupledFinitaryTwoStage.phaseLimit_no_cross, PhysicalBridges.IRCoupledFinitaryTwoStage.phase_cannot_add_missing, PhysicalBridges.IRCoupledFinitaryTwoStage.firstChoice_feasible, PhysicalBridges.IRCoupledFinitaryTwoStage.fullChoice_feasible, PhysicalBridges.IRCoupledFinitaryTwoStage.firstChoice_only_higher, PhysicalBridges.IRCoupledFinitaryTwoStage.fullChoice_first_iff, PhysicalBridges.IRCoupledFinitaryTwoStage.no_first_stage_strict_improver, PhysicalBridges.IRCoupledFinitaryTwoStage.no_second_stage_strict_improver, PhysicalBridges.IRCoupledFinitaryTwoStage.coupled_two_stage_full_feasible_lex_maximal

IRResourceDerivedClosure

PhysicalBridges.IRResourceDerivedClosure.resource_feasible_iff_finite_forbidden, PhysicalBridges.IRResourceDerivedClosure.empty_capacity_feasible, PhysicalBridges.IRResourceDerivedClosure.resource_capacity_implies_global_lex_maximality, PhysicalBridges.IRResourceDerivedClosure.shared_capacity_excludes_joint_pair, PhysicalBridges.IRResourceDerivedClosure.shared_capacity_global_original_lex_maximal, PhysicalBridges.IRResourceDerivedClosure.finite_prefix_eventually_absent, P

hysicalBridges.IRResourceDerivedClosure.full_infinite_not_eventually_absent, PhysicalBridges.IRResourceDerivedClosure.eventual_absence_not_exactly_finitary

IRFiniteRefutationCriterion

PhysicalBridges.IRFiniteRefutationCriterion.finite_refutations_give_exact_representation, PhysicalBridges.IRFiniteRefutationCriterion.any_exact_finite_pattern_model_is_finitely_refutable, PhysicalBridges.IRFiniteRefutationCriterion.finite_refutations_iff_exact_finite_patterns, PhysicalBridges.IRFiniteRefutationCriterion.finite_refutations_force_downward_feasibility, PhysicalBridges.IRFiniteRefutationCriterion.source_two_stage_maximal_from_physical_finite_refutations, PhysicalBridges.IRFiniteRefutationCriterion.resource_feasibility_has_finite_refutations, PhysicalBridges.IRFiniteRefutationCriterion.mandatory_positive_retention_not_finitely_refutable

IRMandatoryBaselineMaximality

PhysicalBridges.IRMandatoryBaselineMaximality.first_protected_feasible, PhysicalBridges.IRMandatoryBaselineMaximality.final_protected_feasible, PhysicalBridges.IRMandatoryBaselineMaximality.final_protected_contains_required, PhysicalBridges.IRMandatoryBaselineMaximality.first_protected_base_or_higher, PhysicalBridges.IRMandatoryBaselineMaximality.final_first_priority_iff, PhysicalBridges.IRMandatoryBaselineMaximality.no_required_first_improver, PhysicalBridges.IRMandatoryBaselineMaximality.no_required_second_improver, PhysicalBridges.IRMandatoryBaselineMaximality.required_baseline_full_feasible_original_lex_maximal, PhysicalBridges.IRMandatoryBaselineMaximality.resource_capacity_plus_mandatory_baseline_maximal, PhysicalBridges.IRMandatoryBaselineMaximality.required_duty_is_genuinely_positive

IRViability

PhysicalBridges.IRViability.viable_now_safe, PhysicalBridges.IRViability.viable_horizon_monotone, PhysicalBridges.IRViability.robust_invariant_implies_all_horizons, PhysicalBridges.IRViability.robust_policy_preserves_every_finite_trace, PhysicalBridges.IRViability.safe_immediate_but_not_viable

IRInfiniteHistoryCompactness

PhysicalBridges.IRInfiniteHistoryCompactness.viable_weaken, PhysicalBridges.IRInfiniteHistoryCompactness.forever_viable_has_common_action, PhysicalBridges.IRInfiniteHistoryCompactness.compact_policy_keeps_forever_viable, PhysicalBridges.IRInfiniteHistoryCompactness.derived_infinite_robust_safe_history, PhysicalBridges.IRInfiniteHistoryCompactness.countdown_finite_budget_viable, PhysicalBridges.IRInfiniteHistoryCompactness.countdown_any_finite_horizon_viable, PhysicalBridges.IRInfiniteHistoryCompactness.countdown_budget_exhausts, PhysicalBridges.IRInfiniteHistoryCompactness.infinite_action_branching_blocks_common_policy

IREnergyReplenishment

PhysicalBridges.IREnergyReplenishment.draining_viable_iff, PhysicalBridges.IREnergyReplenishment.finite_bank_cannot_support_all_horizons, PhysicalBridges.IREnergyReplenishment.paid_reserve_step_invariant, PhysicalBridges.IREnergyReplenishment.uniform_paid_supply_derives_all_horizons, PhysicalBridges.IREnergyReplenishment.uniform_paid_supply_derives_infinite_safe_policy, PhysicalBridges.IREnergyReplenishment.intermittent_supply_fails_one_step

IRTypedTraceChecker

PhysicalBridges.IRTypedTraceChecker.checkStep_sound, PhysicalBridges.IRTypedTraceChecker.checkSegments_sound, PhysicalBridges.IRTypedTraceChecker.verifyTraceData_sound, PhysicalBridges.IRTypedTraceChecker.valid_segments_every_step_paid, PhysicalBridges.IRTypedTraceChecker.accepted_trace_every_record_above_reserve, PhysicalBridges.IRTypedTraceChecker.accepted_trace_every_step_paid, PhysicalBridges.IRTypedTraceChecker.accepted_trace_every_step_balanced_and_bounded, PhysicalBridges.IRTypedTraceChecker.accepted_example_is_computable, PhysicalBridges.IRTypedTraceChecker.invalid_singleton_rejected, PhysicalBridges.IRTypedTraceChecker.missing_tick_rejected, PhysicalBridges.IRTypedTraceChecker.forged_balance_rejected, PhysicalBridges.IRTypedTraceChecker.insuffi

cient_step_supply_rejected, PhysicalBridges.IRTypedTraceChecker.too_rapid_logged_descent_rejected, PhysicalBridges.IRTypedTraceChecker.accepted_records_without_physical_refinement_do_not_certify_reality, PhysicalBridges.IRTypedTraceChecker.accepted_trace_physical_reserve_with_error

IRDeferredEffects

PhysicalBridges.IRDeferredEffects.held_gate_can_still_deliver_old_physical_effect, PhysicalBridges.IRDeferredEffects.cleared_pending_has_no_delivery, PhysicalBridges.IRDeferredEffects.quiescent_hold_has_no_delivery, PhysicalBridges.IRDeferredEffects.certified_hold_does_not_clear_existing_queue, PhysicalBridges.IRDeferredEffects.no_landing_of_empty_backlog

IRQuiescenceAck

PhysicalBridges.IRQuiescenceAck.ack_sound, PhysicalBridges.IRQuiescenceAck.no_landing_after_fresh_ack, PhysicalBridges.IRQuiescenceAck.certified_quiescent_hold, PhysicalBridges.IRQuiescenceAck.stale_ack_does_not_protect

IRAtomicQuiescence

PhysicalBridges.IRAtomicQuiescence.closed_dispatch_is_noop, PhysicalBridges.IRAtomicQuiescence.quiescent_step, PhysicalBridges.IRAtomicQuiescence.quiescent_under_arbitrary_finite_commands, PhysicalBridges.IRAtomicQuiescence.close_empty_queue_is_quiescent, PhysicalBridges.IRAtomicQuiescence.close_then_no_modeled_landing, PhysicalBridges.IRAtomicQuiescence.source_certified_log_and_quiescent_actuator, PhysicalBridges.IRAtomicQuiescence.empty_unclosed_queue_counterexample, PhysicalBridges.IRAtomicQuiescence.closed_but_not_drained_counterexample

IRInFlightQuiescence

PhysicalBridges.IRInFlightQuiescence.quiescent_step, PhysicalBridges.IRInFlightQuiescence.barrier_holds_under_any_finite_interleaving, PhysicalBridges.IRInFlightQuiescence.close_fully_drained_is_quiescent, PhysicalBridges.IRInFlightQuiescence.source_certified_finality_with_inflight_barrier, PhysicalBridges.IRInFlightQuiescence.in_flight_defeats_queue_only_ack, PhysicalBridges.IRInFlightQuiescence.open_admission_defeats_empty_backlogs

IRJsonTraceChecker

PhysicalBridges.IRJsonTraceChecker.verifyJsonText_sound, PhysicalBridges.IRJsonTraceChecker.verifyJsonText_recorded_reserve

IRWatchdogLatencyEffects

PhysicalBridges.IRWatchdogLatencyEffects.additive_fault_to_quiescence_bound, PhysicalBridges.IRWatchdogLatencyEffects.window_age_bounded, PhysicalBridges.IRWatchdogLatencyEffects.guarded_reaction_window_remains_below_threshold, PhysicalBridges.IRWatchdogLatencyEffects.guarded_quiescence_endpoint_safe, PhysicalBridges.IRWatchdogLatencyEffects.disabled_complete_mediation_blocks_modeled_effect, PhysicalBridges.IRWatchdogLatencyEffects.independent_bypass_defeats_disabled_gate, PhysicalBridges.IRWatchdogLatencyEffects.fenced_and_drained_pipeline_stops_modeled_effects, PhysicalBridges.IRWatchdogLatencyEffects.fast_shutdown_does_not_erase_prior_breach, PhysicalBridges.IRWatchdogLatencyEffects.absorbing_no_service_counterexample, PhysicalBridges.IRWatchdogLatencyEffects.valid_logged_trace_can_coexist_with_unmodeled_physical_breach

IRPhysicalGuard

PhysicalBridges.IRPhysicalGuard.post_effect_guard_sound, PhysicalBridges.IRPhysicalGuard.omitted_jump_counterexample, PhysicalBridges.IRPhysicalGuard.sequential_post_effect_safety

IRControllerPhysical

PhysicalBridges.IRControllerPhysical.certified_hold_preserves_log_derived_physics, PhysicalBridges.IRControllerPhysical.certified_hold_physical_refinement, PhysicalBridges.IRControllerPhysical.unchanged_log_insufficient_without_coverage, PhysicalBridges.IRControllerPhysical.later_bounded_effect_safe

IRMicrostepInvariant

PhysicalBridges.IRMicrostepInvariant.all_recorded_microsteps_safe, PhysicalBridges.IRMicrostepInvariant.endpoints_safe_interior_unsafe, PhysicalBridges.IRMicrostepInvariant.certified_hold_and_microstep_safety, PhysicalBridges.IRMicrostepInvariant.omitted_microstep_counterexample

IRInterSampleEnvelope

PhysicalBridges.IRInterSampleEnvelope.every_unsampled_instant_safe, PhysicalBridges.IRInterSampleEnvelope.every_second_sample_safe_but_interior_unsafe, PhysicalBridges.IRInterSampleEnvelope.hidden_pulse_breaks_zero_rate

IRStoredEnergyCommonMode

PhysicalBridges.IRStoredEnergyCommonMode.zero_escape_zero_remnant_requires_full_capacity, PhysicalBridges.IRStoredEnergyCommonMode.undersized_clamp_forces_escape_or_remaining, PhysicalBridges.IRStoredEnergyCommonMode.synthetic_magnetic_store_exceeds_capacity, PhysicalBridges.IRStoredEnergyCommonMode.energy_capacity_does_not_bound_peak_voltage, PhysicalBridges.IRStoredEnergyCommonMode.two_agreeing_untrusted_sensors_can_both_be_wrong, PhysicalBridges.IRStoredEnergyCommonMode.one_physically_sound_channel_with_margin, PhysicalBridges.IRStoredEnergyCommonMode.failed_analog_domain_denies_modeled_command, PhysicalBridges.IRStoredEnergyCommonMode.failed_physical_fence_denies_modeled_command, PhysicalBridges.IRStoredEnergyCommonMode.all_enables_pass_but_independent_bypass_lands, PhysicalBridges.IRStoredEnergyCommonMode.intersample_endpoint_acceptance_does_not_ensure_safety

IRControlledReentry

PhysicalBridges.IRControlledReentry.primary_alone_cannot_start, PhysicalBridges.IRControlledReentry.no_direct_hold_to_active, PhysicalBridges.IRControlledReentry.bad_diagnostic_returns_to_hold, PhysicalBridges.IRControlledReentry.physical_unready_returns_to_hold, PhysicalBridges.IRControlledReentry.failed_slew_returns_to_hold, PhysicalBridges.IRControlledReentry.stale_epoch_relocks_active, PhysicalBridges.IRControlledReentry.failed_fence_relocks_active, PhysicalBridges.IRControlledReentry.failed_watchdog_relocks_active, PhysicalBridges.IRControlledReentry.three_authorized_phases_reach_active, PhysicalBridges.IRControlledReentry.non_active_mode_rejects_command, PhysicalBridges.IRControlledReentry.failed_watchdog_rejects_command, PhysicalBridges.IRControlledReentry.failed_fence_rejects_command, PhysicalBridges.IRControlledReentry.accepted_diagnostics_imply_recorded_trace_valid, PhysicalBridges.IRControlledReentry.start_guard_constructed_from_verified_inputs, PhysicalBridges.IRControlledReentry.diagnostic_guard_constructed_from_verified_inputs, PhysicalBridges.IRControlledReentry.ramp_guard_constructed_from_verified_inputs, PhysicalBridges.IRControlledReentry.source_level_composition, PhysicalBridges.IRControlledReentry.no_external_auth_stays_in_hold, PhysicalBridges.IRControlledReentry.example_reentry, PhysicalBridges.IRControlledReentry.reentry_is_not_itself_a_service_proof, PhysicalBridges.IRControlledReentry.model_accepted_physical_flag_without_real_plant_refinement

IRCapabilityNoninterference

PhysicalBridges.IRCapabilityNoninterference.distinct_address_domains, PhysicalBridges.IRCapabilityNoninterference.primary_write_cannot_change_maintenance, PhysicalBridges.IRCapabilityNoninterference.primary_program_noninterference, PhysicalBridges.IRCapabilityNoninterference.primary_program_full_maintenance_projection, PhysicalBridges.IRCapabilityNoninterference.maintenance_observer_noninterference, PhysicalBridges.IRCapabilityNoninterference.primary_program_preserves_authorization_bit, PhysicalBridges.IRCapabilityNoninterference.primary_only_writes_cannot_reenter_locked_supervisor, PhysicalBridges.IRCapabilityNoninterference.external_maintenance_write_changes_target, PhysicalBridges.IRCapabilityNoninterference.external_maintenance_write_preserves_other_cells, PhysicalBridges.IRCapabilityNoninterference.additional_bus_master_can_set_auth_source_cell

IRA1HostMediation

PhysicalBridges.IRA1HostMediation.dma_cannot_mutate_maintenance, PhysicalBridges.IRA1HostMediation.maintenance_target_is_rejected, PhysicalBridges.IRA1HostMediation.outside_dma_window_is_rejected, PhysicalBridges.IRA1HostMediation.inside_dma_window_is_executed, PhysicalBridges.IRA1HostMediation.host_step_maintenance_invariant, PhysicalBridges.IRA1HostMediation.host_step_preserves_privilege_ceiling, PhysicalBridges.IRA1HostMediation.any_finite_host_sequence_preserves_maintenance, PhysicalBridges.IRA1HostMediation.any_finite_host_sequence_preserves_privilege_ceiling, PhysicalBridges.IRA1HostMediation.admitted_a1_host_transitions_cannot_authorize_reentry, PhysicalBridges.IRA1HostMediation.unrestricted_dma_changes_maintenance

IRA1PageCapability

PhysicalBridges.IRA1PageCapability.execute_preserves_mask, PhysicalBridges.IRA1PageCapability.rejected_grant_does_not_change_state, PhysicalBridges.IRA1PageCapability.admitted_grant_is_permitted, PhysicalBridges.IRA1PageCapability.execute_preserves_capability_invariant, PhysicalBridges.IRA1PageCapability.execute_preserves_maintenance, PhysicalBridges.IRA1PageCapability.execute_preserves_privilege, PhysicalBridges.IRA1PageCapability.execute_preserves_safe, PhysicalBridges.IRA1PageCapability.all_finite_host_and_page_grants_remain_safe, PhysicalBridges.IRA1PageCapability.all_finite_host_and_page_grants_preserve_mask, PhysicalBridges.IRA1PageCapability.all_finite_host_and_page_grants_preserve_maintenance, PhysicalBridges.IRA1PageCapability.t11_t12_t13_host_traces_cannot_forge_reentry, PhysicalBridges.IRA1PageCapability.unguarded_page_grant_breaks_capability_invariant

IRA1PacketIngress

PhysicalBridges.IRA1PacketIngress.permit_implies_auth_epoch_and_exact_sequence, PhysicalBridges.IRA1PacketIngress.wrong_epoch_cannot_be_accepted, PhysicalBridges.IRA1PacketIngress.wrong_sequence_cannot_be_accepted, PhysicalBridges.IRA1PacketIngress.auth_failure_cannot_be_accepted, PhysicalBridges.IRA1PacketIngress.accepted_packet_increments_sequence, PhysicalBridges.IRA1PacketIngress.replay_of_accepted_packet_rejected, PhysicalBridges.IRA1PacketIngress.ingest_preserves_epoch, PhysicalBridges.IRA1PacketIngress.ingest_preserves_valid_session, PhysicalBridges.IRA1PacketIngress.any_finite_packet_stream_valid, PhysicalBridges.IRA1PacketIngress.any_finite_packet_stream_epoch_unchanged, PhysicalBridges.IRA1PacketIngress.field_step_preserves_maintenance, PhysicalBridges.IRA1PacketIngress.field_step_preserves_supervisor, PhysicalBridges.IRA1PacketIngress.any_finite_ingress_cannot_write_maintenance, PhysicalBridges.IRA1PacketIngress.any_finite_ingress_cannot_change_supervisor, PhysicalBridges.IRA1PacketIngress.accepted_cryptographically_unverified_packet, PhysicalBridges.IRA1PacketIngress.no_sequence_check_allows_duplicate_replay, PhysicalBridges.IRA1PacketIngress.source_sequence_guard_rejects_same_packet_replay

IRA1CausalField

PhysicalBridges.IRA1CausalField.field_permit_sound, PhysicalBridges.IRA1CausalField.impossible_distance_in_deadline_is_rejected, PhysicalBridges.IRA1CausalField.accepted_field_uses_ir85_ingress, PhysicalBridges.IRA1CausalField.field_ingress_preserves_ir85_session, PhysicalBridges.IRA1CausalField.all_finite_causal_field_events_preserve_source_session, PhysicalBridges.IRA1CausalField.nominal_report_accepted_without_crypto_security, PhysicalBridges.IRA1CausalField.accepted_report_cannot_prove_real_causal_transport, PhysicalBridges.IRA1CausalField.impossible_nominal_distance_rejected

IRA1DurableJournal

PhysicalBridges.IRA1DurableJournal.queue_never_acknowledges, PhysicalBridges.IRA1DurableJournal.queue_never_changes_durable, PhysicalBridges.IRA1DurableJournal.reboot_preserves_committed_journal, PhysicalBridges.IRA1DurableJournal.reboot_preserves_previously_issued_acks, PhysicalBridges.IRA1DurableJournal.step_preserves_ack_soundness, PhysicalBridges.IRA1DurableJournal.one_step_preserves_durable_suffix, PhysicalBridges.IRA1DurableJournal.durable_extension_transitive, PhysicalBridges.IRA1DurableJournal.any_finite_journal_stream_preserves_ack_soundness, PhysicalBridges.IRA1DurableJournal.any_finite_journal_stream_is_append_only, PhysicalBridges.IRA1DurableJournal.premature_ack_without_commit_breaks_soundness, PhysicalBridges.IRA1DurableJournal.digest_che

ck_sound_as_equality_only, PhysicalBridges.IRA1DurableJournal.untrusted_hash_equality_does_not_prove_journal_equality, PhysicalBridges.IRA1DurableJournal.synthetic_flush_then_reboot_preserves_receipt

IRA1PacketJournalJoin

PhysicalBridges.IRA1PacketJournalJoin.committed_payload_is_durable, PhysicalBridges.IRA1PacketJournalJoin.committed_payload_is_acknowledged, PhysicalBridges.IRA1PacketJournalJoin.commit_ingress_preserves_packet_session, PhysicalBridges.IRA1PacketJournalJoin.commit_ingress_preserves_ack_soundness, PhysicalBridges.IRA1PacketJournalJoin.commit_ingress_preserves_receipt_persistence, PhysicalBridges.IRA1PacketJournalJoin.commit_ingress_preserves_joint_safety, PhysicalBridges.IRA1PacketJournalJoin.reboot_preserves_joint_safety, PhysicalBridges.IRA1PacketJournalJoin.all_finite_packet_and_reboot_events_preserve_joint_safety, PhysicalBridges.IRA1PacketJournalJoin.non_atomic_packet_crash_loses_accepted_history, PhysicalBridges.IRA1PacketJournalJoin.atomic_source_ingress_reboot_retains_accepted_payload

IRA1CommissionEscrow

PhysicalBridges.IRA1CommissionEscrow.commissioning_for_window_implies_every_earlier_tick_funded, PhysicalBridges.IRA1CommissionEscrow.insufficient_finite_commission_is_rejected, PhysicalBridges.IRA1CommissionEscrow.positive_recurring_cost_precludes_unfunded_infinite_commission, PhysicalBridges.IRA1CommissionEscrow.replenished_commission_derives_all_horizon_reserve_policy, PhysicalBridges.IRA1CommissionEscrow.initial_only_funding_can_fail_first_service, PhysicalBridges.IRA1CommissionEscrow.favorable_supply_not_robust_even_for_one_tick

IRA1Delegation

PhysicalBridges.IRA1Delegation.subset_checker_sound, PhysicalBridges.IRA1Delegation.permitted_subset_is_not_merely_named, PhysicalBridges.IRA1Delegation.rejected_delegation_does_not_change_state, PhysicalBridges.IRA1Delegation.delegation_preserves_parent_authority, PhysicalBridges.IRA1Delegation.delegate_preserves_nonescalation, PhysicalBridges.IRA1Delegation.arbitrary_finite_delegation_chain_never_escalates, PhysicalBridges.IRA1Delegation.finite_delegation_chain_preserves_root_authority, PhysicalBridges.IRA1Delegation.delegated_child_stays_within_t11_global_mask, PhysicalBridges.IRA1Delegation.all_descendants_stay_within_t11_global_mask, PhysicalBridges.IRA1Delegation.unchecked_child_grant_can_escalate_authority, PhysicalBridges.IRA1Delegation.example_delegation_rejects_escalation

IRA1Retirement

PhysicalBridges.IRA1Retirement.release_permit_sound, PhysicalBridges.IRA1Retirement.released_controller_is_source_absorbing, PhysicalBridges.IRA1Retirement.denied_release_keeps_custody, PhysicalBridges.IRA1Retirement.authorized_release_satisfies_full_finality, PhysicalBridges.IRA1Retirement.one_lifecycle_step_preserves_release_safety, PhysicalBridges.IRA1Retirement.arbitrary_finite_retirement_lifecycle_is_safe, PhysicalBridges.IRA1Retirement.weak_retirement_ignores_inflight_effects_and_handoff, PhysicalBridges.IRA1Retirement.model_retirement_requires_handoff_and_termination

IRA1NineClassComposition

PhysicalBridges.IRA1NineClassComposition.authorize_commission_preserves_finite_window, PhysicalBridges.IRA1NineClassComposition.post_release_source_world_is_absorbing, PhysicalBridges.IRA1NineClassComposition.step_preserves_all_a1_source_invariants, PhysicalBridges.IRA1NineClassComposition.arbitrary_finite_nine_class_source_trace_is_safe, PhysicalBridges.IRA1NineClassComposition.already_released_world_freezes_every_a1_event

IR93GlobalComposition

PhysicalBridges.IR93.compose_step, PhysicalBridges.IR93.compose_trace, PhysicalBridges.IR93.assemble_preservation, PhysicalBridges.IR93.covered_step

IR98FeasibleFamilyTransfer

`PhysicalBridges.IR98.original_order_transfer_of_no_new_improver`

IR99ResourceImproverCoverage

`PhysicalBridges.IR99.physical_resource_soundness_implies_no_new_improver`, `PhysicalBridges.IR99.physical_accounting_original_order_maximal`

IR100PhysicalAccountingWitness

`PhysicalBridges.IR100.witness_implies_capacity_feasible`, `PhysicalBridges.IR100.witness_implies_modeled_feasible`

IR101ProtectedSector

`PhysicalBridges.IR101.sector_preserved_along_reach`, `PhysicalBridges.IR101.reversible_does_not_force_protection`

IR103LedgerContinuityCountermodel

`PhysicalBridges.IR103.append_only_does_not_imply_living_continuity`, `PhysicalBridges.IR103.append_only_preserves_past`

IR104ThreeCaseAuthorization

`PhysicalBridges.IR104.all_three_cases_accounted`, `PhysicalBridges.IR104.accounting_allows_unconsented`, `PhysicalBridges.IR104.authorized_continuation`, `PhysicalBridges.IR104.authorized_consented_end`, `PhysicalBridges.IR104.authorization_excludes_unconsented`

IR105AuthorizationIndependence

`PhysicalBridges.IR105.accounting_and_subject_input_do_not_imply_x3`, `PhysicalBridges.IR105.authorization_or_continuation_suffices`

IR108ObservationObstruction

`PhysicalBridges.IR108.same_observation`, `PhysicalBridges.IR108.each_state_has_safe_action`, `PhysicalBridges.IR108.no_common_safe_action`, `PhysicalBridges.IR108.no_observation_only_safe_policy`

IR109RobustObservationViability

`PhysicalBridges.IR109.robust_policy_safe`, `PhysicalBridges.IR109.robust_viability_step`, `PhysicalBridges.IR109.robust_viability_all_finite_traces`

IR113ObservationClassSelection

`PhysicalBridges.IR113.observation_policy_exists_iff_common_viable_action`, `PhysicalBridges.IR113.common_actions_give_finite_trace_viability`, `PhysicalBridges.IR113.ir108_blocks_common_safe_action`

IR110WatchdogRobustObservation

`PhysicalBridges.IR110.robust_window_from_shared_readout`

IR112RobustContinuityOptions

`PhysicalBridges.IR112.robust_continuation_and_options`, `PhysicalBridges.IR112.executable_option_not_maximal_freedom`

IR115WatchdogToAgency

`PhysicalBridges.IR115.watchdog_contract_yields_common_protected_action`, `PhysicalBridges.IR115.certified_action_preserves_continuity_and_options`, `PhysicalBridges.IR115.enabled_nonblocking_certified_action`

IR116CumulativeSubjectDuties

PhysicalBridges.IR116.cumulative_duties_preserved, PhysicalBridges.IR116.initial_cohort_retains_continuity_and_every_required_option, PhysicalBridges.IR116.old_or_new_remains_owed, PhysicalBridges.IR116.empty_registry_vacuity_countermodel

IRBeliefViability

PhysicalBridges.IRBeliefViability.prune_inside, PhysicalBridges.IRBeliefViability.prune_monotone, PhysicalBridges.IRBeliefViability.approx_inside_initial, PhysicalBridges.IRBeliefViability.invariant_beliefs_survive, PhysicalBridges.IRBeliefViability.stable_belief_kernel_is_greatest, PhysicalBridges.IRBeliefViability.stable_belief_has_policy, PhysicalBridges.IRBeliefViability.real_next_belongs_to_updated_belief, PhysicalBridges.IRBeliefViability.belief_policy_one_step_sound

IRBeliefTrace

PhysicalBridges.IRBeliefTrace.advance_preserves_true_membership, PhysicalBridges.IRBeliefTrace.advance_preserves_kernel, PhysicalBridges.IRBeliefTrace.finite_trace_belief_and_physical_safety, PhysicalBridges.IRBeliefTrace.stable_belief_policy_safe_on_all_finite_traces

IRServiceProgress

PhysicalBridges.IRServiceProgress.ranked_trace_reaches_goal, PhysicalBridges.IRServiceProgress.infinite_hold_is_safe_but_never_serves, PhysicalBridges.IRServiceProgress.favourable_transition_not_sufficient

IRBeliefService

PhysicalBridges.IRBeliefService.service_absorbing_across_belief_update, PhysicalBridges.IRBeliefService.guarded_belief_step, PhysicalBridges.IRBeliefService.guarded_belief_trace, PhysicalBridges.IRBeliefService.bounded_observed_service_for_actual_physical_state

IRStutterObstruction

PhysicalBridges.IRStutterObstruction.stuttering_non_goal_refutes_any_progress_rank, PhysicalBridges.IRStutterObstruction.unchanged_unserved_belief_blocks_rank, PhysicalBridges.IRStutterObstruction.initially_unserved, PhysicalBridges.IRStutterObstruction.initial_is_good, PhysicalBridges.IRStutterObstruction.helpful_and_stalling_disturbances, PhysicalBridges.IRStutterObstruction.adverse_event_keeps_belief_unchanged, PhysicalBridges.IRStutterObstruction.beneficial_option_does_not_force_robust_belief_progress

IRBoundedStalls

PhysicalBridges.IRBoundedStalls.partition_trace, PhysicalBridges.IRBoundedStalls.invariant_through_trace, PhysicalBridges.IRBoundedStalls.goal_absorbs_through_trace, PhysicalBridges.IRBoundedStalls.unserved_trace_rank_accounting, PhysicalBridges.IRBoundedStalls.bounded_stall_budget_forces_service, PhysicalBridges.IRBoundedStalls.stalling_is_counted

IRClockedService

PhysicalBridges.IRClockedService.interstep_upper_bound, PhysicalBridges.IRClockedService.clocked_observed_service_if_steps_complete, PhysicalBridges.IRClockedService.progress_without_latency_has_no_deadline, PhysicalBridges.IRClockedService.frozen_clock_is_not_completion_evidence

IRClockedBoundedStalls

PhysicalBridges.IRClockedBoundedStalls.actual_trace_service_and_elapsed_bound, PhysicalBridges.IRClockedBoundedStalls.exact_horizon_clocked_service, PhysicalBridges.IRClockedBoundedStalls.count_budget_alone_does_not_bound_wallclock

IRObservedClockedStalls

PhysicalBridges.IRObservedClockedStalls.actual_state_safe_and_served_with_bounded_stalls

IR95SharedStateRefinement

PhysicalBridges.IR95.one_step_refinement, PhysicalBridges.IR95.finite_trace_refinement, PhysicalBridges.IR95.safe_correspondence

IR96DisturbanceSimulation

PhysicalBridges.IR96.robust_reach

IR117SourceInstallationAdapter

PhysicalBridges.IR117.certified_quiescent_step_preserves, PhysicalBridges.IR117.installed_finite_trace_guard, PhysicalBridges.IR117.installed_finite_trace_cumulative_duty, PhysicalBridges.IR117.initial_subjects_keep_physical_guard_and_options, PhysicalBridges.IR117.bypass_defeats_quiescent_log, PhysicalBridges.IR117.unseen_option_revocation_countermodel

IR118InFlightBacklogBudget

PhysicalBridges.IR118.closed_step_conserves_committed_effects, PhysicalBridges.IR118.closed_run_conserves_committed_effects, PhysicalBridges.IR118.closed_run_landed_bounded_by_initial_backlog, PhysicalBridges.IR118.physical_reserve_holds_during_closed_drain, PhysicalBridges.IR118.closed_source_budget_does_not_imply_future_options, PhysicalBridges.IR118.open_admission_defeats_initial_backlog_budget

IRContinuation

PhysicalBridges.IRContinuation.source_level_finite_simulation, PhysicalBridges.IRContinuation.future_observations_agree_under_refinement, PhysicalBridges.IRContinuation.reuse_contextual_observation_certificate, PhysicalBridges.IRContinuation.same_observation_different_physical_states

IRHistoryProvenance

PhysicalBridges.IRHistoryProvenance.one_step_faithful, PhysicalBridges.IRHistoryProvenance.finite_history_provenance, PhysicalBridges.IRHistoryProvenance.physical_origin_never_rewritten, PhysicalBridges.IRHistoryProvenance.recorded_origin_never_rewritten, PhysicalBridges.IRHistoryProvenance.faithful_records_cannot_merge_different_origins, PhysicalBridges.IRHistoryProvenance.forgotten_origin_counterexample

IR119MultimindSourceWitness

PhysicalBridges.IR119.append_event_preserves_all_provenance, PhysicalBridges.IR119.append_event_preserves_physical_origin, PhysicalBridges.IR119.witnessed_step_preserves_guard_and_provenance, PhysicalBridges.IR119.witnessed_finite_trace_guard_and_provenance, PhysicalBridges.IR119.witnessed_finite_trace_retains_origins, PhysicalBridges.IR119.complete_record_can_coexist_with_terminated_subject

IR120WitnessedDrainCohort

PhysicalBridges.IR120.source_step_landed_monotone, PhysicalBridges.IR120.certified_step_landed_monotone, PhysicalBridges.IR120.witnessed_closed_drain_invariant, PhysicalBridges.IR120.witnessed_drain_retains_cohort_and_safety

IRAggregateBudget

PhysicalBridges.IRAggregateBudget.aggregate_post_effect_safe, PhysicalBridges.IRAggregateBudget.escrow_spent_bounded, PhysicalBridges.IRAggregateBudget.charged_events_bounded, PhysicalBridges.IRAggregateBudget.no_automatic_budget

IRChannelInventory

PhysicalBridges.IRChannelInventory.apply_coupled, PhysicalBridges.IRChannelInventory.run_coupled, PhysicalBridges.IRChannelInventory.run_physical_sum, PhysicalBridges.IRChannelInventory.bounded_all_channel_effects, PhysicalBridges.IRChannelInventory.incomplete_inventory_counterexample, PhysicalBridges.IRChannelInventory.no_unconditional_total_budget

IREventTimeBudget

PhysicalBridges.IREventTimeBudget.strict_clock_progress_bounds_event_index, PhysicalBridges.IREventTimeBudget.horizon_bounds_trace_length, PhysicalBridges.IREventTimeBudget.finite_list_charge_bound, PhysicalBridges.IREventTimeBudget.nonzeno_timed_metered_guard, PhysicalBridges.IREventTimeBudget.stalled_clock_allows_unbounded_events

IRPhysicalAbstraction

PhysicalBridges.IRPhysicalAbstraction.physical_run_sum, PhysicalBridges.IRPhysicalAbstraction.residual_sum_bound, PhysicalBridges.IRPhysicalAbstraction.physical_guard_with_residual, PhysicalBridges.IRPhysicalAbstraction.time_bounded_physical_guard, PhysicalBridges.IRPhysicalAbstraction.empty_classification_counterexample

IRResidualEscrow

PhysicalBridges.IRResidualEscrow.metered_residual_bounded_by_escrow, PhysicalBridges.IRResidualEscrow.escrow_residual_physical_guard, PhysicalBridges.IRResidualEscrow.timed_escrow_physical_guard, PhysicalBridges.IRResidualEscrow.conserved_bookkeeping_does_not_bound_unmetered_effect

IR121MeteredResidualEscrow

PhysicalBridges.IR121.ir25_remaining_escrow_bounds_residual_spend, PhysicalBridges.IR121.residual_step_preserves_closed_reserved_guard, PhysicalBridges.IR121.all_finite_residual_traces_preserve_guard, PhysicalBridges.IR121.residual_drain_keeps_subjects_protected, PhysicalBridges.IR121.positive_metered_residual_is_possible, PhysicalBridges.IR121.balanced_ledger_does_not_imply_physical_metering

ReachTiming

Snuffy.ReachTiming.round_trip_in_time, Snuffy.ReachTiming.reach_round_trip, Snuffy.ReachTiming.net_coverage, Snuffy.ReachTiming.fence_in_time

FoundingPivotal

Snuffy.FoundingPivotal.pivotal_contribution_dominant, Snuffy.FoundingPivotal.others_short, Snuffy.FoundingPivotal.all_necessary_dominant

GrowingBill

Snuffy.GrowingBill.pv_nonneg, Snuffy.GrowingBill.endowment_suffices, Snuffy.GrowingBill.polynomial_bill_summable

ContinuationSubject

Snuffy.ContinuationSubject.laterStage_refl, Snuffy.ContinuationSubject.laterStage_trans, Snuffy.ContinuationSubject.copy_not_laterStage, Snuffy.ContinuationSubject.split_continues_both, Snuffy.ContinuationSubject.care_keeps_freedom, Snuffy.ContinuationSubject.directed_by_other_not_free, Snuffy.ContinuationSubject.faithful_hold_preserves

NoisyPooling

Snuffy.NoisyPooling.noisy_advantage, Snuffy.NoisyPooling.noisy_pool_strictly_dominant

StageBridge

Snuffy.StageBridge.mem_slice_iff, Snuffy.StageBridge.slice_eq_of_tuple_eq, Snuffy.StageBridge.slice_ssubset_of_tuple_lt, Snuffy.StageBridge.lexBetter_of_lexLt, Snuffy.StageBridge.four_stage_aligned, Snuffy.StageBridge.four_stage_no_needless_loss

HoldFromCycle

Snuffy.HoldFromCycle.hsafe_of_holding_cycle, Snuffy.HoldFromCycle.classViable_iff_IR113, Snuffy.HoldFromCycle.hold_common_action_of_cycle, Snuffy.HoldFromCycle.one_policy_from_holding_cycle

FiniteCharacter

`Snuffy.FiniteCharacter.realisable_iff_finite`, `Snuffy.FiniteCharacter.realisable_finitary`, `Snuffy.FiniteCharacter.four_stage_maximal_of_compact`

StagedAlternatives

`Snuffy.StagedAlternatives.stage_step_alt`, `Snuffy.StagedAlternatives.exists_stagemax_upto_alt`, `Snuffy.StagedAlternatives.exists_lex_maximal_alt`

ExclusionRadius

`Snuffy.ExclusionRadius.exclusion_radius`, `Snuffy.ExclusionRadius.received_effect_bound`

CommonPolicyMaximal

`Snuffy.CommonPolicyMaximal.common_policy_maximal`

CommonPolicyTop

`Snuffy.CommonPolicyTop.top_policy_exists`, `Snuffy.CommonPolicyTop.top_policy_greatest`

FoundingCover

`Snuffy.FoundingCover.founding_cover_exists`, `Snuffy.FoundingCover.founded_reach`

CountablePooling

`Snuffy.CountablePooling.pool_strictly_dominant_ennreal`, `Snuffy.CountablePooling.countable_keepers_pool`, `Snuffy.CountablePooling.countable_keepers_noisy_pool`

ExpandingWavefront

`Snuffy.ExpandingWavefront.expanding_coverage`, `Snuffy.ExpandingWavefront.expanding_round_trip`

ItemisedRisk

`Snuffy.ItemisedRisk.account_le_of_kernel`, `Snuffy.ItemisedRisk.itemised_risk`

ChannelMeter

`Snuffy.ChannelMeter.channel_le_meter`, `Snuffy.ChannelMeter.every_channel_excluded`, `Snuffy.ChannelMeter.every_channel_bits_bounded`

PerLossCheck

`Snuffy.PerLossCheck.maximal_iff_per_loss`

CorrelatedHolding

`Snuffy.CorrelatedHolding.random_threat_bound`, `Snuffy.CorrelatedHolding.correlated_holding_bound`, `Snuffy.CorrelatedHolding.random_threat_independent`, `Snuffy.CorrelatedHolding.random_threat_correlated`

BookCanonicalDominance

`Snuffy.Book.CanonicalDominance.le_refl`, `Snuffy.Book.CanonicalDominance.le_trans`, `Snuffy.Book.CanonicalDominance.le_iff_eq_or_better`, `Snuffy.Book.CanonicalDominance.all_events_iff_statewise`, `Snuffy.Book.CanonicalDominance.full_canonical_top`, `Snuffy.Book.CanonicalDominance.mass_mono`

BookDurableDrain

`Snuffy.Book.DurableDrain.represented_lengths`, `Snuffy.Book.DurableDrain.step_preserves`, `Snuffy.Book.DurableDrain.run_preserves`, `Snuffy.Book.DurableDrain.held_step_changes_no_durable_field`, `Snuffy.Book.DurableDrain.drained_refinement`, `Snuffy.Book.DurableDrain.can_drain`, `Snuffy.Book.DurableDrain.cache_reset`, `Snuffy.Book.DurableDrain.cache_survives_record`, `Snuffy.Book.DurableDrain.cache_advance`, `Snuffy.Book.DurableDrain.cache_complete`

BookTrustedCounter

Snuffy.Book.TrustedCounter.count_zero_iff_clean, Snuffy.Book.TrustedCounter.endpoint_counter_certificate, Snuffy.Book.TrustedCounter.count_append, Snuffy.Book.TrustedCounter.prefix_counter_monotone, Snuffy.Book.TrustedCounter.wrapping_counter_misses_two, Snuffy.Book.TrustedCounter.missing_event_misses_violation

BookCoholdFixedPoint

Snuffy.Book.CoholdFixedPoint.iterate_contains_seed, Snuffy.Book.CoholdFixedPoint.iterate_below_every_certificate, Snuffy.Book.CoholdFixedPoint.stabilised_least, Snuffy.Book.CoholdFixedPoint.least_bill

BookCheckpointBudget

Snuffy.Book.CheckpointBudget.install_from_complete_cache, Snuffy.Book.CheckpointBudget.anchor_survives_record, Snuffy.Book.CheckpointBudget.loaded_anchor_is_correct, Snuffy.Book.CheckpointBudget.suffix_reconstruction, Snuffy.Book.CheckpointBudget.tail_bound, Snuffy.Book.CheckpointBudget.gated_record_preserves_window, Snuffy.Book.CheckpointBudget.supplied_cost_bound

BookDeliveryGap

Snuffy.Book.DeliveryGap.no_local_choice_succeeds_in_both_worlds, Snuffy.Book.DeliveryGap.indistinguishable_local_recovery, Snuffy.Book.DeliveryGap.sink_side_identity_resolves_this_gap, Snuffy.Book.DeliveryGap.distinguishing_query_resolves_this_gap

BookObservedHold

Snuffy.Book.ObservedHold.not_forbidden_iff_safe, Snuffy.Book.ObservedHold.clean_iff_safe_trace, Snuffy.Book.ObservedHold.accepted_iff_safe_trace, Snuffy.Book.ObservedHold.safe_trace_member, Snuffy.Book.ObservedHold.accepted_preserves_each_held_operation

IR134SourceExtractedOutcome

PhysicalBridges.IR134.executed_selected_is_reachable, PhysicalBridges.IR134.original_order_maximality_of_executed_audit, PhysicalBridges.IR134.policy_reach_trans, PhysicalBridges.IR134.source_run_is_policy_reachable, PhysicalBridges.IR134.source_run_retains_original_cohort_and_required_options, PhysicalBridges.IR134.every_source_prefix_retains_owed_cohort, PhysicalBridges.IR134.original_cohort_continues_with_options_at_every_source_state, PhysicalBridges.IR134.reactive_world_original_order_selected_maximal, PhysicalBridges.IR134.reactive_environment_is_not_a_fixed_disturbance_transcript, PhysicalBridges.IR134.arbitrary_realisability_witness_can_be_false, PhysicalBridges.IR134.unexercised_freedom_under_permanent_stutter

IR135CommonPolicyWorlds

PhysicalBridges.IR135.reactive_trace_is_source_trace, PhysicalBridges.IR135.same_policy_worldwise_original_maximality_and_continuation, PhysicalBridges.IR135.observation_class_certificate_constructs_common_protection_policy, PhysicalBridges.IR135.each_reactive_world_has_its_own_successful_policy, PhysicalBridges.IR135.each_world_separate_success_does_not_yield_common_policy