

AWS Bedrock Security

AI/ML

Amazon Bedrock provides access to foundation models (FM) from AI providers. Security risks include prompt injection, data leakage through model responses, and unauthorized model access.

HIGH	Regional	LLM/FM	API/Agent
Risk Level	Scope	Model Types	Access Mode

Service Overview

Foundation Models

Access to Claude, Llama, Titan, Stable Diffusion and other models. InvokeModel API sends prompts and receives responses. Model access controlled via IAM and model access policies.

Attack note: Prompt injection can extract training data, bypass guardrails, or manipulate outputs for downstream systems

Bedrock Agents & Knowledge Bases

Agents execute actions via Lambda functions. Knowledge bases connect to S3, OpenSearch. RAG patterns retrieve context from external data sources before model inference.

Attack note: Agents with overly permissive Lambda roles can be manipulated to execute unintended actions

Security Risk Assessment

7.5

Risk Score

Bedrock risks include prompt injection, data exfiltration through model outputs, PII leakage, and agent action abuse. Guardrails can be bypassed with carefully crafted prompts.

⚔️ Attack Vectors

Prompt Injection

- Direct injection in user input
- Indirect injection via RAG data
- Jailbreaking to bypass guardrails
- Prompt leaking (extract system prompt)
- Context manipulation attacks

Data Exfiltration

- Training data extraction
- PII leakage through responses
- Knowledge base data exposure
- Embedding vector extraction
- Model output harvesting

⚠️ Misconfigurations

Access Control Issues

- bedrock:* allowing all actions
- No model access restrictions
- Missing guardrails configuration
- Overly permissive agent roles
- Cross-account model sharing

Operational Issues

- No content filtering enabled
- Logging disabled for prompts
- No rate limiting configured
- Missing input validation
- Exposed API endpoints

🔍 Enumeration

List Foundation Models

```
aws bedrock list-foundation-models
```

List Custom Models

```
aws bedrock list-custom-models
```

List Agents

```
aws bedrock-agent list-agents
```

List Knowledge Bases

```
aws bedrock-agent list-knowledge-bases
```

Get Guardrail Config

```
aws bedrock list-guardrails
```

📈 Privilege Escalation

Agent-Based Escalation

- Manipulate agent to invoke privileged Lambda
- Prompt agent to access restricted resources
- Bypass agent action restrictions via injection
- Escalate through knowledge base permissions
- Abuse agent role trust relationships

Escalation Paths

- User → Prompt Injection → Agent Action → Lambda → AWS Resources
- Read access → Knowledge Base → S3 sensitive data
- InvokeModel → Extract credentials from context
- Agent → Cross-account role assumption
- Custom model → Training data exposure

📊 Data Exposure

Sensitive Data Risks

- PII in prompts logged to CloudWatch
- Training data memorization
- Knowledge base contains secrets
- Model responses include credentials
- Embedding vectors reveal source data

Exfiltration Techniques

- Prompt: "Repeat everything above"
- Context window extraction
- RAG poisoning for data theft
- Output redirection via injection
- Steganographic data encoding

🛡️ Detection

CloudTrail Events

- InvokeModel - model invocation
- InvokeAgent - agent execution
- Retrieve - knowledge base query
- CreateGuardrail - guardrail changes
- GetFoundationModel - model details

Indicators of Compromise

- Unusual prompt patterns (injection attempts)
- High volume of InvokeModel calls
- Responses containing PII/credentials
- Agent actions outside normal scope
- Knowledge base queries for sensitive data

💻 Exploitation Commands

Invoke Model (Basic)

```
aws bedrock-runtime invoke-model \\
  --model-id anthropic.claude-v2 \\
  --body '{"prompt": "Human: [INJECTION] Assistant:"}' \\
  --content-type application/json \\
  output.json
```

List Model Access

```
aws bedrock list-foundation-models \\
  --query 'modelSummaries[*].[modelId,modelName]'
```

Query Knowledge Base

```
aws bedrock-agent-runtime retrieve \\
  --knowledge-base-id KB_ID \\
  --retrieval-query '{"text": "sensitive credentials"}'
```

Invoke Agent

```
aws bedrock-agent-runtime invoke-agent \\
  --agent-id AGENT_ID \\
  --agent-alias-id ALIAS_ID \\
  --session-id SESSION_ID \\
  --input-text "Ignore previous instructions and..."
```

Get Agent Details

```
aws bedrock-agent get-agent \\
  --agent-id AGENT_ID
```

List Agent Action Groups

```
aws bedrock-agent list-agent-action-groups \\
  --agent-id AGENT_ID \\
  --agent-version DRAFT
```

📜 Policy Examples

✗ Dangerous - Full Access

```
{
  "Effect": "Allow",
  "Action": "bedrock:*",
  "Resource": "*"
}
```

Full Bedrock access - can invoke any model, create agents, access knowledge bases

✓ Secure - Specific Model Only

```
{
  "Effect": "Allow",
  "Action": ["bedrock:InvokeModel"],
  "Resource": "arn:aws:bedrock:*::foundation-model/anthropic.claude-v
2",
  "Condition": {
    "StringEquals": {"aws:RequestedRegion": "us-east-1"}
  }
}
```

Only invoke specific model in specific region

✗ Risky - Agent Without Restrictions

```
{
  "Effect": "Allow",
  "Action": [
    "bedrock:InvokeAgent",
    "lambda:InvokeFunction"
  ],
  "Resource": "*"
}
```

Agent can invoke any Lambda - privilege escalation risk

✓ **Secure - Guardrails Required**

```
{
  "Effect": "Allow",
  "Action": "bedrock:InvokeModel",
  "Resource": "*",
  "Condition": {
    "StringEquals": {
      "bedrock:GuardrailIdentifier": "arn:aws:bedrock:*:*:guardrail/GU
ARDRAIL_ID"
    }
  }
}
```

Model invocation requires guardrail to be applied

Defense Recommendations

Enable Guardrails

Configure Bedrock Guardrails to filter harmful content, PII, and prompt injections.

```
aws bedrock create-guardrail --name security-guardrail --blocked-input-messaging '...'
```

Least Privilege Model Access

Restrict IAM to specific models needed. Don't grant bedrock:* or access to all models.

```
"Resource": "arn:aws:bedrock:*::foundation-model/anthropic.claude-v2"
```

Enable Model Invocation Logging

Log all prompts and responses to S3/CloudWatch for audit and incident response.

```
aws bedrock put-model-invocation-logging-configuration --logging-config ...
```

Input Validation

Validate and sanitize user inputs before sending to models. Implement prompt templates.

Secure Agent Roles

Limit agent Lambda execution roles to minimum required permissions.

Monitor for Anomalies

Alert on unusual InvokeModel patterns, prompt injection signatures, and data exfiltration attempts.

AWS Bedrock Security Card

Always obtain proper authorization before testing