

1. HTML5 Boilerplate

HTML:

```
<!DOCTYPE html>

<html lang="en">

<head>

  <meta charset="UTF-8">

  <meta http-equiv="X-UA-Compatible" content="IE=edge">

  <meta name="viewport" content="width=device-width, initial-scale=1.0">

  <meta name="description" content="HTML Cheatsheet">

  <meta name="keywords" content="HTML, Cheatsheet, Code">

  <meta name="author" content="Your Name">

  <title>Document Title</title>

  <link rel="stylesheet" href="styles.css">

  <style>

    body { font-family: Arial, sans-serif; }

    @media (max-width: 600px) { body { font-size: 16px; } }

  </style>

</head>

<body>

  <!-- Page Content Goes Here -->

  <script src="script.js"></script>

  <script>console.log("Hello, World!");</script>

</body>

</html>
```

2. Document Structure & Semantics

Tag	Purpose / Description
<!DOCTYPE html>	Defines the document type as HTML5
<html>	Root element of the HTML document
<head>	Container for document metadata
<body>	Container for all visible page content
<header>	Page or section header
<nav>	Navigation links section
<main>	Main content area of the document
<section>	Standalone section of content
<article>	Independent, self-contained content block
<aside>	Sidebar or complementary content
<footer>	Page or section footer
<details> / <summary>	Collapsible content toggle with summary title
<dialog>	Dialog box or modal window

Tag	Purpose / Description
<figure> / <figcaption>	Media/illustration container with caption
<hgroup>	Groups heading elements (<h1>--<h6>)
<noscript>	Content rendered when JavaScript is disabled

3. Headings & Layout Containers

Tag	Description
<h1> to <h6>	Document headings (<h1> largest/most important, <h6> smallest)
<div>	Generic block-level container
	Generic inline container
<p>	Paragraph block
 	Line break
<hr>	Horizontal rule / thematic break
<pre>	Preformatted text (preserves spacing and line breaks)
<blockquote>	Block-level quotation from an external source

Tag	Description
<q>	Short inline quotation

4. Text Formatting & Inline Styling

Tag	Description
 / 	Bold text / Important text (semantic)
<i> / 	Italic text / Emphasized text (semantic)
<u> / <ins>	Underlined text / Inserted text
 / <s>	Deleted text / Strikethrough text
<mark>	Highlighted/marked text
<small>	Small print/disclaimer text
<sub> / <sup>	Subscript / Superscript
<code>	Inline code snippet
<kbd>	Keyboard input representation
<samp>	Sample output from a computer program

Tag	Description
<var>	Mathematical or programming variable
<abbr>	Abbreviation or acronym
<cite>	Title of a cited work
<dfn>	Term definition element
<address>	Contact information for author/owner
<time>	Machine-readable date/time representation
<bdo> / <bdi>	Bi-directional text override / Bi-directional isolation
<ruby> / <rt> / <rp>	Ruby annotations for East Asian typography
<wbr>	Word break opportunity

5. Links & Navigation

Syntax / Tag	Example
Web Link	<code>Visit Site</code>
Email Link	<code>Send Email</code>

Syntax / Tag	Example
Anchor / Jump	<code>Jump to Section</code>
Document Base	<code><base href="https://example.com/" target="_blank"></code>

6. Lists

List Type	Structure Syntax
Unordered	<code> Item A Item B </code>
Ordered	<code> First Second </code>
Definition	<code><dl> <dt>HTML</dt> <dd>HyperText Markup Language</dd> </dl></code>

7. Tables

HTML

```
<table border="1">
```

```
<caption>Sample Table</caption>
```

```
<colgroup>
```

```
<col span="1" style="background-color: #f2f2f2;">
```

```
</colgroup>

<thead>

  <tr>

    <th>Column 1</th>

    <th colspan="2">Column 2</th>

  </tr>

</thead>

<tbody>

  <tr>

    <td rowspan="2">Rowspan Data</td>

    <td>Data A</td>

    <td>Data B</td>

  </tr>

  <tr>

    <td>Data C</td>

    <td>Data D</td>

  </tr>

</tbody>

<tfoot>

  <tr>

    <td>Total</td>

    <td colspan="2">100</td>

  </tr>

</tfoot>

</table>
```

8. Media & Embedded Content

Type	Code Example
Image	<code></code>
Audio	<code><audio controls><source src="audio.mp3" type="audio/mpeg"></audio></code>
Video	<code><video width="480" height="320" controls><source src="video.mp4" type="video/mp4"></video></code>
Iframe	<code><iframe src="https://example.com" width="600" height="400"></iframe></code>
Picture	<code><picture><source media="(min-width:650px)" srcset="large.jpg"></picture></code>
Canvas	<code><canvas id="myCanvas" width="200" height="100"></canvas></code>
SVG	<code><svg width="100" height="100"><circle cx="50" cy="50" r="40" /></svg></code>
Embed/Object	<code><object data="file.pdf" type="application/pdf" width="500" height="300"></object></code>
Map/Area	<code><map name="workmap"><area shape="rect" coords="34,44,270,350" href="link.html"></map></code>

9. Forms & Inputs

HTML

```
<form action="/submit.php" method="post">
```

```
<label for="username">Username:</label>
```

```
<input type="text" id="username" name="username" placeholder="User">
```

```
<label for="pwd">Password:</label>
```

```
<input type="password" id="pwd" name="password">
```

```
<label><input type="checkbox" name="subscribe" value="yes"> Subscribe</label>
```

```
<label><input type="radio" name="gender" value="male"> Male</label>
```

```
<label><input type="radio" name="gender" value="female"> Female</label>
```

```
<select name="country">
```

```
<optgroup label="North America">
```

```
<option value="us">USA</option>
```

```
<option value="ca">Canada</option>
```

```
</optgroup>
```

```
</select>
```

```
<input list="browsers" name="browser">
```

```
<datalist id="browsers">
```

```
<option value="Chrome">
```

```
<option value="Firefox">
```

```
</datalist>
```

```
<textarea name="comments" rows="4" cols="30"></textarea>
```

```
<button type="submit">Submit</button>
```

```
<!-- Input Field Types -->
```

```
<input type="file" name="resume">
```

```
<input type="number" name="age" min="18" max="100">
```

```
<input type="range" name="volume" min="0" max="100">
```

```
<input type="date" name="dob">
```

```
<input type="email" name="email">
```

```
<input type="url" name="website">
```

```
<input type="search" name="query">
```

```
<input type="color" name="favcolor">
```

```
<!-- Gauge & Status Indicators -->
```

```
<progress value="70" max="100"></progress>
```

```
<meter value="0.6">60%</meter>
```

```
<output name="result"></output>
```

```
</form>
```

10. JavaScript Event Handlers

Event	Trigger
onblur	Element loses focus
onchange	Content of a form element changes
onfocus	Element gets focus
onreset	Form is reset
onselect	User selects text inside an element
onsubmit	Form is submitted

11. Special Entities & Symbols

Symbol	Code	Symbol	Code
©	©	™	™
<	<	®	®
>	>	\$	$
&	&	(space)	