Fenwick Tree

(Binary Indexed Tree)

William Fiset

(slightly modified by Sabbir Ahmed, IUT, CSE)

Outline

- **Discussion & Examples**
  - Data structure motivation
  - What is a Fenwick tree?
  - Complexity analysis
- **Implementation details**
  - Range query
  - Point Updates
  - Fenwick tree construction
- **Code Implementation**

Fenwick Tree Motivation

Given an array of integer values compute the range sum between index [i, j].

	0	1	2	3	4	5	6	7	8	9
A =	5	-3	6	1	0	-4	11	6	2	7

Fenwick Tree Motivation

Given an array of integer values compute the range sum between index [i, j].

	0	1	2	3	4	5	6	7	8	9
A =	5	-3	6	1	0	-4	11	6	2	7

Sum of A from [2,6] = 6 + 1 + 0 + -4 + 11 = 14

Fenwick Tree Motivation

Given an array of integer values compute the range sum between index [i, j].

	0	1	2	3	4	5	6	7	8	9
A =	5	-3	6	1	0	-4	11	6	2	7

Sum of A from [2,6] = 6 + 1 + 0 + -4 + 11 = 14

Sum of A from [0,3] = 5 + -3 + 6 + 1 = 9

Fenwick Tree Motivation

Given an array of integer values compute the range sum between index [i, j].

	0	1	2	3	4	5	6	7	8	9
A =	5	-3	6	1	0	-4	11	6	2	7

Sum of A from [2,6] = 6 + 1 + 0 + -4 + 11 = 14

Sum of A from [0,3] = 5 + -3 + 6 + 1 = 9

Sum of A from [7,7] = 6 = 6

Fenwick Tree Motivation

Given an array of integer values compute the range sum between index [i, j].

	0	1	2	3	4	5	6	7	8	9
A =	5	-3	6	1	0	-4	11	6	2	7

P =	Ø	Ø	Ø	Ø	Ø	Ø	Ø	Ø	Ø	Ø	Ø

Let **P** be an array containing all the **prefix sums** of A.

Fenwick Tree Motivation

Given an array of integer values compute the range sum between index [i, j].

	0	1	2	3	4	5	6	7	8	9
A =	5	-3	6	1	0	-4	11	6	2	7

P =	0	∅	∅	∅	∅	∅	∅	∅	∅	∅	∅

Let **P** be an array containing all the **prefix sums** of A.

Fenwick Tree Motivation

Given an array of integer values compute the range sum between index [i, j].

	0	1	2	3	4	5	6	7	8	9
A =	5	-3	6	1	0	-4	11	6	2	7

P =	0	5	∅	∅	∅	∅	∅	∅	∅	∅	∅

Let **P** be an array containing all the **prefix sums** of A.

Fenwick Tree Motivation

Given an array of integer values compute the range sum between index [i, j].

	0	1	2	3	4	5	6	7	8	9
A =	5	-3	6	1	0	-4	11	6	2	7

P =	0	5	2	Ø	Ø	Ø	Ø	Ø	Ø	Ø	Ø

Let **P** be an array containing all the **prefix sums** of A.

Fenwick Tree Motivation

Given an array of integer values compute the range sum between index [i, j].

	0	1	2	3	4	5	6	7	8	9
A =	5	-3	6	1	0	-4	11	6	2	7

P =	0	5	2	8	Ø	Ø	Ø	Ø	Ø	Ø	Ø

Let **P** be an array containing all the **prefix sums** of A.

Fenwick Tree Motivation

Given an array of integer values compute the range sum between index [i, j].

	0	1	2	3	4	5	6	7	8	9
A =	5	-3	6	1	0	-4	11	6	2	7

P =	0	5	2	8	9	Ø	Ø	Ø	Ø	Ø	Ø

Let **P** be an array containing all the **prefix sums** of A.

Fenwick Tree Motivation

Given an array of integer values compute the range sum between index [i, j].

	0	1	2	3	4	5	6	7	8	9
A =	5	-3	6	1	0	-4	11	6	2	7

P =	0	5	2	8	9	9	Ø	Ø	Ø	Ø	Ø

Let **P** be an array containing all the **prefix sums** of A.

Fenwick Tree Motivation

Given an array of integer values compute the range sum between index [i, j].

	0	1	2	3	4	5	6	7	8	9
A =	5	-3	6	1	0	-4	11	6	2	7

P =	0	5	2	8	9	9	5	Ø	Ø	Ø	Ø

Let **P** be an array containing all the **prefix sums** of A.

Fenwick Tree Motivation

Given an array of integer values compute the range sum between index [i, j].

	0	1	2	3	4	5	6	7	8	9
A =	5	-3	6	1	0	-4	11	6	2	7

P =	0	5	2	8	9	9	5	16	Ø	Ø	Ø

Let **P** be an array containing all the **prefix sums** of A.

Fenwick Tree Motivation

Given an array of integer values compute the range sum between index [i, j].

	0	1	2	3	4	5	6	7	8	9
A =	5	-3	6	1	0	-4	11	6	2	7

P =	0	5	2	8	9	9	5	16	22	Ø	Ø

Let **P** be an array containing all the **prefix sums** of A.

Fenwick Tree Motivation

Given an array of integer values compute the range sum between index [i, j].

	0	1	2	3	4	5	6	7	8	9
A =	5	-3	6	1	0	-4	11	6	2	7

P =	0	5	2	8	9	9	5	16	22	24	∅

Let **P** be an array containing all the **prefix sums** of A.

Fenwick Tree Motivation

Given an array of integer values compute the range sum between index [i, j].

	0	1	2	3	4	5	6	7	8	9
A =	5	-3	6	1	0	-4	11	6	2	7

P =	0	5	2	8	9	9	5	16	22	24	31

Let **P** be an array containing all the **prefix sums** of A.

Fenwick Tree Motivation

Given an array of integer values compute the range sum between index [i, j].

	0	1	2	3	4	5	6	7	8	9
A =	5	-3	6	1	0	-4	11	6	2	7

P =	0	5	2	8	9	9	5	16	22	24	31

Sum of A from [2,6] = P[7] - P[2] = 16 - 2 = 14

Fenwick Tree Motivation

Given an array of integer values compute the range sum between index [i, j].

	0	1	2	3	4	5	6	7	8	9
A =	5	-3	6	1	0	-4	11	6	2	7

P =	0	5	2	8	9	9	5	16	22	24	31

Sum of A from [2,6] = P[7] - P[2] = 16 - 2 = 14

Sum of A from [0,3] = P[4] - P[0] = 9 - 0 = 9

Fenwick Tree Motivation

Given an array of integer values compute the range sum between index [i, j].

	0	1	2	3	4	5	6	7	8	9
A =	5	-3	6	1	0	-4	11	6	2	7

P =	0	5	2	8	9	9	5	16	22	24	31

Sum of A from [2,6] = P[7] - P[2] = 16 - 2 = 14

Sum of A from [0,3] = P[4] - P[0] = 9 - 0 = 9

Sum of A from [7,7] = P[8] - P[7] = 22 - 16 = 6

Fenwick Tree Motivation

Question: What about if we want to update our initial array with some new value?

	0	1	2	3	4	5	6	7	8	9
A =	5	-3	6	1	0	-4	11	6	2	7

P =	0	5	2	8	9	9	5	16	22	24	31

Fenwick Tree Motivation

Question: What about if we want to update our initial array with some new value?

	0	1	2	3	4	5	6	7	8	9
A =	5	-3	6	1	3	-4	11	6	2	7

P =	0	5	2	8	9	12	8	19	25	27	34

A[4] = 3

Fenwick Tree Motivation

Question: What about if we want to update our initial array with some new value?

	0	1	2	3	4	5	6	7	8	9
A =	5	-3	6	1	3	-4	11	6	2	7

P =	0	5	2	8	9	12	8	19	25	27	34

A prefix sum array is great for **static arrays**, but takes **O(n)** for updates.

What is a Fenwick Tree?

A **Fenwick Tree** (also called Binary Indexed Tree) is a data structure that supports sum range queries as well as setting values in a static array and getting the value of the prefix sum up some index efficiently.

Complexity

Construction	O(n)
Point Update	O(log(n))
Range Sum	O(log(n))
Adding Index	N/A
Removing Index	N/A

Fenwick Tree Range Queries

16	10000_2
15	01111_2
14	01110_2
13	01101_2
12	01100_2
11	01011_2
10	01010_2
9	01001_2
8	01000_2
7	00111_2
6	00110_2
5	00101_2
4	00100_2
3	00011_2
2	00010_2
1	00001_2

Unlike a regular array, in a Fenwick tree a specific cell is responsible for other cells as well.

16	**10000_2**
15	**01111_2**
14	**01110_2**
13	**01101_2**
12	**01100_2**
11	**01011_2**
10	**01010_2**
9	**01001_2**
8	**01000_2**
7	**00111_2**
6	**00110_2**
5	**00101_2**
4	**00100_2**
3	**00011_2**
2	**00010_2**
1	**00001_2**

Unlike a regular array, in a Fenwick tree a specific cell is responsible for other cells as well.

The position of the **least significant bit (LSB)** determines the range of responsibility that cell has to the cells below itself.

16	**10000_2**
15	**01111_2**
14	**01110_2**
13	**01101_2**
12	**01100_2**
11	**01011_2**
10	**01010_2**
9	**01001_2**
8	**01000_2**
7	**00111_2**
6	**00110_2**
5	**00101_2**
4	**00100_2**
3	**00011_2**
2	**00010_2**
1	**00001_2**

Unlike a regular array, in a Fenwick tree a specific cell is responsible for other cells as well.

The position of the **least significant bit (LSB)** determines the range of responsibility that cell has to the cells below itself.

Index 12 in binary is: 1100_2

LSB is at position 3, so this index is responsible for $2^{3-1} = 4$ cells below itself.

16	**10000_2**
15	**01111_2**
14	**01110_2**
13	**01101_2**
12	**01100_2**
11	**01011_2**
10	**01010_2**
9	**01001_2**
8	**01000_2**
7	**00111_2**
6	**00110_2**
5	**00101_2**
4	**00100_2**
3	**00011_2**
2	**00010_2**
1	**00001_2**

Unlike a regular array, in a Fenwick tree a specific cell is responsible for other cells as well.

The position of the **least significant bit (LSB)** determines the range of responsibility that cell has to the cells below itself.

Index 10 in binary is: 1010_2

LSB is at position 2, so this index is responsible for $2^{2-1} = 2$ cells below itself.

16	**10000_2**
15	**01111_2**
14	**01110_2**
13	**01101_2**
12	**01100_2**
11	**01011_2**
10	**01010_2**
9	**01001_2**
8	**01000_2**
7	**00111_2**
6	**00110_2**
5	**00101_2**
4	**00100_2**
3	**00011_2**
2	**00010_2**
1	**00001_2**

Unlike a regular array, in a Fenwick tree a specific cell is responsible for other cells as well.

The position of the **least significant bit (LSB)** determines the range of responsibility that cell has to the cells below itself.

Index 11 in binary is: 1011_2

LSB is at position 1, so this index is responsible for $2^{1-1} = 1$ cell (itself).

16	10000_2
15	01111_2
14	01110_2
13	01101_2
12	01100_2
11	01011_2
10	01010_2
9	01001_2
8	01000_2
7	00111_2
6	00110_2
5	00101_2
4	00100_2
3	00011_2
2	00010_2
1	00001_2

Blue bars represent the **range of responsibility** for that cell **NOT value**.

All odd numbers have a their first least significant bit set in the ones position, so they are only responsible for themselves.

16	10000_2
15	01111_2
14	01110_2
13	01101_2
12	01100_2
11	01011_2
10	01010_2
9	01001_2
8	01000_2
7	00111_2
6	00110_2
5	00101_2
4	00100_2
3	00011_2
2	00010_2
1	00001_2

Blue bars represent the **range of responsibility** for that cell **NOT value**.

Numbers with their least significant bit in the second position have a range of two.

16	10000_2
15	01111_2
14	01110_2
13	01101_2
12	01100_2
11	01011_2
10	01010_2
9	01001_2
8	01000_2
7	00111_2
6	00110_2
5	00101_2
4	00100_2
3	00011_2
2	00010_2
1	00001_2

Blue bars represent the **range of responsibility** for that cell **NOT value**.

Numbers with their least significant bit in the third position have a range of four.

16	10000_2
15	01111_2
14	01110_2
13	01101_2
12	01100_2
11	01011_2
10	01010_2
9	01001_2
8	01000_2
7	00111_2
6	00110_2
5	00101_2
4	00100_2
3	00011_2
2	00010_2
1	00001_2

Blue bars represent the **range of responsibility** for that cell **NOT value**.

Numbers with their least significant bit in the fourth position have a range of eight.



Blue bars represent the **range of responsibility** for that cell **NOT value**.

Numbers with their least significant bit in the fifth position have a range of sixteen.

16	10000_2	1,16
15	01111_2	15,15
14	01110_2	13,14
13	01101_2	13,13
12	01100_2	9,12
11	01011_2	11,11
10	01010_2	9,10
9	01001_2	9,9
8	01000_2	1,8
7	00111_2	7,7
6	00110_2	5,6
5	00101_2	5,5
4	00100_2	1,4
3	00011_2	3,3
2	00010_2	1,2
1	00001_2	1,1



Index – Range correspondance

16	10000_2	5
15	01111_2	10
14	01110_2	5
13	01101_2	10
12	01100_2	5
11	01011_2	10
10	01010_2	5
9	01001_2	10
8	01000_2	5
7	00111_2	10
6	00110_2	5
5	00101_2	10
4	00100_2	5
3	00011_2	10
2	00010_2	5
1	00001_2	10



Given 16 integers, how will the Fenwick Tree look like?

16	10000_2	5	
15	01111_2	10	10
14	01110_2	5	
13	01101_2	10	10
12	01100_2	5	
11	01011_2	10	10
10	01010_2	5	
9	01001_2	10	10
8	01000_2	5	
7	00111_2	10	10
6	00110_2	5	
5	00101_2	10	10
4	00100_2	5	
3	00011_2	10	10
2	00010_2	5	
1	00001_2	10	10



Given 16 integers, how will the Fenwick Tree look like?

16	10000_2	5	
15	01111_2	10	10
14	01110_2	5	15
13	01101_2	10	10
12	01100_2	5	
11	01011_2	10	10
10	01010_2	5	15
9	01001_2	10	10
8	01000_2	5	
7	00111_2	10	10
6	00110_2	5	15
5	00101_2	10	10
4	00100_2	5	
3	00011_2	10	10
2	00010_2	5	15
1	00001_2	10	10



Given 16 integers, how will the Fenwick Tree look like?

16	10000_2	5	
15	01111_2	10	10
14	01110_2	5	15
13	01101_2	10	10
12	01100_2	5	30
11	01011_2	10	10
10	01010_2	5	15
9	01001_2	10	10
8	01000_2	5	
7	00111_2	10	10
6	00110_2	5	15
5	00101_2	10	10
4	00100_2	5	30
3	00011_2	10	10
2	00010_2	5	15
1	00001_2	10	10



Given 16 integers, how will the Fenwick Tree look like?

16	10000_2	5	
15	01111_2	10	10
14	01110_2	5	15
13	01101_2	10	10
12	01100_2	5	30
11	01011_2	10	10
10	01010_2	5	15
9	01001_2	10	10
8	01000_2	5	60
7	00111_2	10	10
6	00110_2	5	15
5	00101_2	10	10
4	00100_2	5	30
3	00011_2	10	10
2	00010_2	5	15
1	00001_2	10	10



Given 16 integers, how will the Fenwick Tree look like?

16	10000_2	5	120
15	01111_2	10	10
14	01110_2	5	15
13	01101_2	10	10
12	01100_2	5	30
11	01011_2	10	10
10	01010_2	5	15
9	01001_2	10	10
8	01000_2	5	60
7	00111_2	10	10
6	00110_2	5	15
5	00101_2	10	10
4	00100_2	5	30
3	00011_2	10	10
2	00010_2	5	15
1	00001_2	10	10



Given 16 integers, how will the Fenwick Tree look like?

(Note- Values inside the Fenwick Tree will be inserted sequentially, not in the order demonstrated)

Range Queries

In a Fenwick tree we may compute the **prefix sum** up to a certain index, which ultimately lets us perform range sum queries.



Range Queries

In a Fenwick tree we may compute the **prefix sum** up to a certain index, which ultimately lets us perform range sum queries.

Idea: Suppose you want to find the prefix sum of [1, i], then you **start at i and cascade downwards** until you reach zero adding the value at each of the indices you encounter.

Range Queries

In a Fenwick tree we may compute the **prefix sum** up to a certain index, which ultimately lets us perform range sum queries.

Find the prefix sum up to index 7.

Range Queries

In a Fenwick tree we may compute the **prefix sum** up to a certain index, which ultimately lets us perform range sum queries.

Find the prefix sum up to index 7.

sum = A[7]



Range Queries

In a Fenwick tree we may compute the **prefix sum** up to a certain index, which ultimately lets us perform range sum queries.

Find the prefix sum up to index 7.

sum = A[7] + A[6]



Range Queries

In a Fenwick tree we may compute the **prefix sum** up to a certain index, which ultimately lets us perform range sum queries.

Find the prefix sum up to index 7.

sum = A[7] + A[6] + A[4]

Range Queries

In a Fenwick tree we may compute the **prefix sum** up to a certain index, which ultimately lets us perform range sum queries.

Find the prefix sum up to index 11.

Range Queries

In a Fenwick tree we may compute the **prefix sum** up to a certain index, which ultimately lets us perform range sum queries.

Find the prefix sum up to index 11.



sum = A[11]



Range Queries

In a Fenwick tree we may compute the **prefix sum** up to a certain index, which ultimately lets us perform range sum queries.

Find the prefix sum up to index 11.

sum = A[11] + A[10]



Range Queries

In a Fenwick tree we may compute the **prefix sum** up to a certain index, which ultimately lets us perform range sum queries.

Find the prefix sum up to index 11.

sum = A[11] + A[10] + A[8]

Range Queries



Find the prefix sum up to index 11.

sum = A[11] + A[10] + A[8]

How to cascade down: 11 -> 10 -> 8

In each step, subtract the value of LSB

Range Queries



Find the prefix sum up to index 11.

sum = A[11] + A[10] + A[8]

How to cascade down: 11 -> 10 -> 8

In each step, subtract the value of LSB

11 = (1011) LSB = (0001) = 1

11 – 1 = (1011) – (0001) = 10

Range Queries



Find the prefix sum up to index 11.

sum = A[11] + A[10] + A[8]

How to cascade down: 11 -> 10 -> 8

In each step, subtract the value of LSB

11 = (1011) LSB = (0001) = 1

11 – 1 = (1011) – (0001) = 10

10 = (1010) LSB = (0010) = 2

10 – 2 = (1010) – (0010) = 8

Range Queries



Find the prefix sum up to index 11.
sum = A[11] + A[10] + A[8]

How to cascade down: 11 -> 10 -> 8

In each step, subtract the value of LSB

11 = (1011) LSB = (0001) = 1

11 – 1 = (1011) – (0001) = 10

10 = (1010) LSB = (0010) = 2

10 – 2 = (1010) – (0010) = 8

8 = (1000) LSB = (0100) = 8

8 – 8 = (1000) – (1000) = 0

End



Range Queries

How to find the LSB/ rightmost 1 in a binary number?

Like, 11 = (1011) LSB = (0001) = 1

Simply perform: value & (-value)

Range Queries

16	10000_2
15	01111_2
14	01110_2
13	01101_2
12	01100_2
11	01011_2
10	01010_2
9	01001_2
8	01000_2
7	00111_2
6	00110_2
5	00101_2
4	00100_2
3	00011_2
2	00010_2
1	00001_2

How to find the LSB/ rightmost 1 in a binary number?

Like, 11 = (1011) LSB = (0001) = 1

Simply perform: value & (-value)

Let, value = 11 = (1011)

To find (-value):

Perform: **2's complement**

Range Queries



How to find the LSB/ rightmost 1 in a binary number?

Like, 11 = (1011) LSB = (0001) = 1

Simply perform: value & (-value)

Let, value = 11 = (1011)

To find (-value):

Perform: **2's complement**

1011 after 1's complement: 0100

Then add 1: 0100 + 1

(-value) = 0101

Finally, value & (-value) = 1011 & 0101

= **0001**

Range Queries



Let, value = 10 = (1010)

To find (-value):

Perform: **2's complement**

1010 after 1's complement: 0101

Then add 1: 0101 + 1

(-value) = 0110

Finally, value & (-value) = 1010 & 0110

= **0010**

This is how we can easily extract LSB from a number

Range Queries



This is how we can easily extract LSB from a number

To cascade down –
keep subtracting LSB until 0

Range Queries

Let's use prefix sums to compute the interval sum between [i, j].

Compute the interval sum between [11, 15].

Range Queries



Let's use prefix sums to compute the interval sum between [i, j].

Compute the interval sum between [11, 15].

First we compute the prefix sum of [1, 15], then we will compute the prefix sum of [1,11) and get the difference.

Not inclusive! We want the value at position 11.

Range Queries



Compute the interval sum between [11, 15].

First we compute the prefix sum of [1, 15], then we will compute the prefix sum of [1,11) and get the difference.

$$Sum\ of\ [1,15] = A[15]$$

Range Queries



Compute the interval sum between [11, 15].

First we compute the prefix sum of [1, 15], then we will compute the prefix sum of [1,11) and get the difference.

$$Sum\ of\ [1,15] = A[15] + A[14]$$



Range Queries

Compute the interval sum between [11, 15].

First we compute the prefix sum of [1, 15], then we will compute the prefix sum of [1,11) and get the difference.

$$Sum\ of\ [1,15] = A[15] + A[14] + A[12]$$

Range Queries



Compute the interval sum between [11, 15].

First we compute the prefix sum of [1, 15], then we will compute the prefix sum of [1,11) and get the difference.

$$Sum\ of\ [1,15] = A[15] + A[14] + A[12] + A[8]$$

Range Queries



Compute the interval sum between [11, 15].

First we compute the prefix sum of [1, 15], then we will compute the prefix sum of [1,11) and get the difference.

$$Sum\ of\ [1,15] = A[15] + A[14] + A[12] + A[8]$$

$$Sum\ of\ [1,11) = A[10]$$



Range Queries

Compute the interval sum between [11, 15].

First we compute the prefix sum of [1, 15], then we will compute the prefix sum of [1,11) and get the difference.

$$Sum\ of\ [1,15] = A[15] + A[14] + A[12] + A[8]$$

$$Sum\ of\ [1,11) = A[10] + A[8]$$



Range Queries

Compute the interval sum between [11, 15].

First we compute the prefix sum of [1, 15], then we will compute the prefix sum of [1,11) and get the difference.

$$Sum\ of\ [1,15] = A[15] + A[14] + A[12] + A[8]$$

$$Sum\ of\ [1,11) = A[10] + A[8]$$

Range sum:

$$(A[15] + A[14] + A[12] + A[8]) - (A[10] + A[8])$$

Range Queries



Notice that in the worst case the cell we're querying has a binary representation of all ones (numbers of the form $2^n - 1$)

Hence, it's easy to see that in the worst case a range query might make us have to do two queries that **cost** $\log_2(\boldsymbol{n})$ operations.

Range query algorithm

To do a range query from [i,j] both inclusive a Fenwick tree of size N:

```
function prefixSum(i):
    sum := 0
    while i != 0:
        sum = sum + tree[i]
        i = i - LSB(i)
    return sum

function rangeQuery(i, j):
    return prefixSum(j) - prefixSum(i-1)
```

Where **LSB** returns the value of the least significant bit.

Fenwick Tree Point Updates



Point Updates

Instead of querying a range to find the interval sum we want to update a cell in our array.

Point Updates



Instead of querying a range to find the interval sum we want to update a cell in our array.

Recall that with range queries we cascaded down from the current index by **continuously removing the LSB.**

Point Updates



Instead of querying a range to find the interval sum we want to update a cell in our array.

Recall that with range queries we cascaded down from the current index by **continuously removing the LSB.**

$13 = 1101_2$, $1101_2 - 0001_2 = 1100_2$

$\downarrow$

$12 = 1100_2$

Point Updates



Instead of querying a range to find the interval sum we want to update a cell in our array.

Recall that with range queries we cascaded down from the current index by **continuously removing the LSB.**

$13 = 1101_2$, $1101_2 - 0001_2 = 1100_2$

↓

$12 = 1100_2$, $1100_2 - 0100_2 = 1000_2$

↓

$8 = 1000_2$

Point Updates



Instead of querying a range to find the interval sum we want to update a cell in our array.

Recall that with range queries we cascaded down from the current index by **continuously removing the LSB.**

$13 = 1101_2$, $1101_2 - 0001_2 = 1100_2$

↓

$12 = 1100_2$, $1100_2 - 0100_2 = 1000_2$

↓

$8 = 1000_2$, $1000_2 - 1000_2 = 0000_2$

↓

$0 = 0000_2$

Point Updates

Point updates are the opposite of this, we want to **add the LSB** to propagate the value up to the cells responsible for us.

Point Updates

Point updates are the opposite of this, we want to **add the LSB** to propagate the value up to the cells responsible for us.

$9 = 1001_2$, $1001_2 + 0001_2 = 1010_2$

↓

$10 = 1010_2$

Point Updates

Point updates are the opposite of this, we want to **add the LSB** to propagate the value up to the cells responsible for us.

$9 = 1001_2$, $1001_2 + 0001_2 = 1010_2$

↓

$10 = 1010_2$, $1010_2 + 0010_2 = 1100_2$

↓

$12 = 1100_2$

Point Updates

Point updates are the opposite of this, we want to **add the LSB** to propagate the value up to the cells responsible for us.

$9 = 1001_2$, $1001_2 + 0001_2 = 1010_2$

↓

$10 = 1010_2$, $1010_2 + 0010_2 = 1100_2$

↓

$12 = 1100_2$, $1100_2 + 0100_2 = 10000_2$

↓

$16 = 10000_2$

Point Updates



Point updates are the opposite of this, we want to **add the LSB** to propagate the value up to the cells responsible for us.

$9 = 1001_2$, $1001_2 + 0001_2 = 1010_2$

↓

$10 = 1010_2$, $1010_2 + 0010_2 = 1100_2$

↓

$12 = 1100_2$, $1100_2 + 0100_2 = 10000_2$

↓

$16 = 10000_2$

Point Updates



Point updates are the opposite of this, we want to **add the LSB** to propagate the value up to the cells responsible for us.

$9 = 1001_2$, $1001_2 + 0001_2 = 1010_2$

↓

$10 = 1010_2$, $1010_2 + 0010_2 = 1100_2$

↓

$12 = 1100_2$, $1100_2 + 0100_2 = 10000_2$

↓

$16 = 10000_2$

Point Updates

If we add x to position 6 in the Fenwick tree which cells do we also need to modify?

Point Updates



If we add x to position 6 in the Fenwick tree which cells do we also need to modify?

$6 = 0110_2$

Point Updates



If we add x to position 6 in the Fenwick tree which cells do we also need to modify?

$6 = 0110_2$, $0110_2 + 0010_2 = 1000_2$

↓

$8 = 1000_2$

Point Updates



If we add x to position 6 in the Fenwick tree which cells do we also need to modify?

$6 = 0110_2$, $0110_2 + 0010_2 = 1000_2$

↓

$8 = 1000_2$, $1000_2 + 1000_2 = 10000_2$

↓

$16 = 10000_2$

Point Updates



If we add x to position 6 in the Fenwick tree which cells do we also need to modify?

$6 = 0110_2$, $0110_2 + 0010_2 = 1000_2$

↓

$8 = 1000_2$, $1000_2 + 1000_2 = 10000_2$

↓

$16 = 10000_2$

Point Updates



If we add x to position 6 in the Fenwick tree which cells do we also need to modify?

$6 = 0110_2$, $0110_2 + 0010_2 = 1000_2$

↓

$8 = 1000_2$, $1000_2 + 1000_2 = 10000_2$

↓

$16 = 10000_2$

<u>Required Updates:</u>

A[6] = A[6] + x

A[8] = A[8] + x

A[16] = A[16] + x

Point update algorithm

To update the cell at index i in the a Fenwick tree of size N:

```
function add(i, x):
    while i < N:
        tree[i] = tree[i] + x
        i = i + LSB(i)
```

Where **LSB** returns the value of the least significant bit. For example:

LSB(12) = 4 because $12_{10} = 1100_2$ and the least significant bit of 1100_2 is 100_2, or 4 in base ten

Fenwick Tree Construction

William Fiset

Naive Construction

Let A be an array of values. For each element in A at index *i* do a point update on the Fenwick tree with a value of A[i]. There are *n* elements and each point update takes O(log(n)) for a total of $O(nlog(n))$, can we do better?

Linear Construction

12	1100_2	-8
11	1011_2	4
10	1010_2	2
9	1001_2	-9
8	1000_2	-8
7	0111_2	5
6	0110_2	11
5	0101_2	3
4	0100_2	7
3	0011_2	-2
2	0010_2	4
1	0001_2	3



Input values we wish to turn into a legitimate Fenwick tree.

Input Array

3	4	−2	7	3	11	5	−8	−9	2	4	−8

Linear Construction

12	1100_2	-8
11	1011_2	4
10	1010_2	2
9	1001_2	-9
8	1000_2	-8
7	0111_2	5
6	0110_2	11
5	0101_2	3
4	0100_2	7
3	0011_2	-2
2	0010_2	4
1	0001_2	3



Idea: Add the value in the current cell to the **immediate cell** that is responsible for us. This resembles what we did for point updates but **only one cell at a time.**

Input Array

3	4	−2	7	3	11	5	−8	−9	2	4	−8

Linear Construction

12	1100_2	-8
11	1011_2	4
10	1010_2	2
9	1001_2	-9
8	1000_2	-8
7	0111_2	5
6	0110_2	11
5	0101_2	3
4	0100_2	7
3	0011_2	-2
2	0010_2	4
1	0001_2	3



Idea: Add the value in the current cell to the **immediate cell** that is responsible for us. This resembles what we did for point updates but **only one cell at a time.**

This will make the 'cascading' effect in range queries possible by propagating the value in each cell throughout the tree.

Input Array

3	4	−2	7	3	11	5	−8	−9	2	4	−8

Linear Construction

12	1100_2	-8
11	1011_2	4
10	1010_2	2
9	1001_2	-9
8	1000_2	-8
7	0111_2	5
6	0110_2	11
5	0101_2	3
4	0100_2	7
3	0011_2	-2
2	0010_2	4
1	0001_2	3



Let i be the current index

The immediate cell above us is at position j given by:

j := i + LSB(i)

Where LSB is the **Least Significant Bit** of i

Input Array

3	4	−2	7	3	11	5	−8	−9	2	4	−8

Linear Construction

12	1100_2	-8
11	1011_2	4
10	1010_2	2
9	1001_2	-9
8	1000_2	-8
7	0111_2	5
6	0110_2	11
5	0101_2	3
4	0100_2	7
3	0011_2	-2
2	0010_2	4
1	0001_2	3



$i = 1 = 0001_2$

$j = 0001_2 + 0001_2 = 0010_2$
$= 2$

Input Array

3	4	−2	7	3	11	5	−8	−9	2	4	−8

Linear Construction

12	1100_2	-8
11	1011_2	4
10	1010_2	2
9	1001_2	-9
8	1000_2	-8
7	0111_2	5
6	0110_2	11
5	0101_2	3
4	0100_2	7
3	0011_2	-2
2	0010_2	4+3
1	0001_2	3



$i = 1 = 0001_2$

$j = 0001_2 + 0001_2 = 0010_2$
$= 2$

Input Array

3	4	−2	7	3	11	5	−8	−9	2	4	−8

Linear Construction

12	1100_2	-8
11	1011_2	4
10	1010_2	2
9	1001_2	-9
8	1000_2	-8
7	0111_2	5
6	0110_2	11
5	0101_2	3
4	0100_2	7
3	0011_2	-2
2	0010_2	7
1	0001_2	3



$i = 2 = 0010_2$

$j = 0010_2 + 0010_2 = 0100_2$
$= 4$

Input Array

3	4	−2	7	3	11	5	−8	−9	2	4	−8

Linear Construction

12	1100_2	-8
11	1011_2	4
10	1010_2	2
9	1001_2	-9
8	1000_2	-8
7	0111_2	5
6	0110_2	11
5	0101_2	3
4	0100_2	7+7
3	0011_2	-2
2	0010_2	7
1	0001_2	3



$i = 2 = 0010_2$

$j = 0010_2 + 0010_2 = 0100_2$
$= 4$

Input Array

3	4	−2	7	3	11	5	−8	−9	2	4	−8

Linear Construction

12	1100_2	-8
11	1011_2	4
10	1010_2	2
9	1001_2	-9
8	1000_2	-8
7	0111_2	5
6	0110_2	11
5	0101_2	3
4	0100_2	14
3	0011_2	-2
2	0010_2	7
1	0001_2	3



$i = 3 = 0011_2$

$j = 0011_2 + 0001_2 = 0100_2$
$= 4$

Input Array

3	4	−2	7	3	11	5	−8	−9	2	4	−8

Linear Construction

12	1100_2	-8
11	1011_2	4
10	1010_2	2
9	1001_2	-9
8	1000_2	-8
7	0111_2	5
6	0110_2	11
5	0101_2	3
4	0100_2	14+-2
3	0011_2	-2
2	0010_2	7
1	0001_2	3



$i = 3 = 0011_2$

$j = 0011_2 + 0001_2 = 0100_2$
$= 4$

Input Array

3	4	−2	7	3	11	5	−8	−9	2	4	−8

Linear Construction

12	1100_2	-8
11	1011_2	4
10	1010_2	2
9	1001_2	-9
8	1000_2	-8
7	0111_2	5
6	0110_2	11
5	0101_2	3
4	0100_2	12
3	0011_2	-2
2	0010_2	7
1	0001_2	3



$i = 4 = 0100_2$

$j = 0100_2 + 0100_2 = 1000_2$
$= 8$

Input Array

3	4	−2	7	3	11	5	−8	−9	2	4	−8

Linear Construction

12	1100_2	-8
11	1011_2	4
10	1010_2	2
9	1001_2	-9
8	1000_2	-8+12
7	0111_2	5
6	0110_2	11
5	0101_2	3
4	0100_2	12
3	0011_2	-2
2	0010_2	7
1	0001_2	3



$i = 4 = 0100_2$

$j = 0100_2 + 0100_2 = 1000_2$
$= 8$

Input Array

3	4	−2	7	3	11	5	−8	−9	2	4	−8

Linear Construction

12	1100_2	-8
11	1011_2	4
10	1010_2	2
9	1001_2	-9
8	1000_2	4
7	0111_2	5
6	0110_2	11
5	0101_2	3
4	0100_2	12
3	0011_2	-2
2	0010_2	7
1	0001_2	3



$i = 5 = 0101_2$

$j = 0101_2 + 0001_2 = 0110_2$
$= 6$

Input Array

3	4	−2	7	3	11	5	−8	−9	2	4	−8

Linear Construction

12	1100_2	-8
11	1011_2	4
10	1010_2	2
9	1001_2	-9
8	1000_2	4
7	0111_2	5
6	0110_2	11+3
5	0101_2	3
4	0100_2	12
3	0011_2	-2
2	0010_2	7
1	0001_2	3



$i = 5 = 0101_2$

$j = 0101_2 + 0001_2 = 0110_2$
$= 6$

Input Array

3	4	−2	7	3	11	5	−8	−9	2	4	−8

Linear Construction

12	1100_2	-8
11	1011_2	4
10	1010_2	2
9	1001_2	-9
8	1000_2	4
7	0111_2	5
6	0110_2	14
5	0101_2	3
4	0100_2	12
3	0011_2	-2
2	0010_2	7
1	0001_2	3



$i = 6 = 0110_2$

$j = 0110_2 + 0010_2 = 1000_2$
$= 8$

Input Array

3	4	−2	7	3	11	5	−8	−9	2	4	−8

Linear Construction

12	1100_2	-8
11	1011_2	4
10	1010_2	2
9	1001_2	-9
8	1000_2	4+14
7	0111_2	5
6	0110_2	14
5	0101_2	3
4	0100_2	12
3	0011_2	-2
2	0010_2	7
1	0001_2	3



$i = 6 = 0110_2$

$j = 0110_2 + 0010_2 = 1000_2$
$= 8$

Input Array

3	4	−2	7	3	11	5	−8	−9	2	4	−8

Linear Construction

12	1100_2	-8
11	1011_2	4
10	1010_2	2
9	1001_2	-9
8	1000_2	18
7	0111_2	5
6	0110_2	14
5	0101_2	3
4	0100_2	12
3	0011_2	-2
2	0010_2	7
1	0001_2	3



$i = 7 = 0111_2$

$j = 0111_2 + 0001_2 = 1000_2$
$= 8$

Input Array

3	4	−2	7	3	11	5	−8	−9	2	4	−8

Linear Construction

12	1100_2	-8
11	1011_2	4
10	1010_2	2
9	1001_2	-9
8	1000_2	18+5
7	0111_2	5
6	0110_2	14
5	0101_2	3
4	0100_2	12
3	0011_2	-2
2	0010_2	7
1	0001_2	3



$i = 7 = 0111_2$

$j = 0111_2 + 0001_2 = 1000_2$
$= 8$

Input Array

3	4	−2	7	3	11	5	−8	−9	2	4	−8

Linear Construction

12	1100_2	-8
11	1011_2	4
10	1010_2	2
9	1001_2	-9
8	1000_2	23
7	0111_2	5
6	0110_2	14
5	0101_2	3
4	0100_2	12
3	0011_2	-2
2	0010_2	7
1	0001_2	3



$i = 8 = 1000_2$

$j = 1000_2 + 1000_2 = 10000_2$
$= 16$

Ignore updating j if index is out of bounds

Input Array

3	4	−2	7	3	11	5	−8	−9	2	4	−8

Linear Construction

12	1100_2	-8
11	1011_2	4
10	1010_2	2
9	1001_2	-9
8	1000_2	23
7	0111_2	5
6	0110_2	14
5	0101_2	3
4	0100_2	12
3	0011_2	-2
2	0010_2	7
1	0001_2	3



$i = 9 = 1001_2$

$j = 1001_2 + 0001_2 = 1010_2$
$= 10$

Input Array

3	4	−2	7	3	11	5	−8	−9	2	4	−8

Linear Construction

12	1100_2	-8
11	1011_2	4
10	1010_2	2+-9
9	1001_2	-9
8	1000_2	23
7	0111_2	5
6	0110_2	14
5	0101_2	3
4	0100_2	12
3	0011_2	-2
2	0010_2	7
1	0001_2	3



$i = 9 = 1001_2$

$j = 1001_2 + 0001_2 = 1010_2$
$= 10$

Input Array

3	4	−2	7	3	11	5	−8	−9	2	4	−8

Linear Construction

12	1100_2	-8
11	1011_2	4
10	1010_2	-7
9	1001_2	-9
8	1000_2	23
7	0111_2	5
6	0110_2	14
5	0101_2	3
4	0100_2	12
3	0011_2	-2
2	0010_2	7
1	0001_2	3



$i = 10 = 1010_2$

$j = 1010_2 + 0010_2 = 1100_2$
$= 12$

Input Array

3	4	−2	7	3	11	5	−8	−9	2	4	−8

Linear Construction

12	1100_2	-8+-7
11	1011_2	4
10	1010_2	-7
9	1001_2	-9
8	1000_2	23
7	0111_2	5
6	0110_2	14
5	0101_2	3
4	0100_2	12
3	0011_2	-2
2	0010_2	7
1	0001_2	3



$i = 10 = 1010_2$

$j = 1010_2 + 0010_2 = 1100_2$
$= 12$

Input Array

3	4	−2	7	3	11	5	−8	−9	2	4	−8

Linear Construction

12	1100_2	-15
11	1011_2	4
10	1010_2	-7
9	1001_2	-9
8	1000_2	23
7	0111_2	5
6	0110_2	14
5	0101_2	3
4	0100_2	12
3	0011_2	-2
2	0010_2	7
1	0001_2	3



$i = 11 = 1011_2$

$j = 1011_2 + 0001_2 = 1100_2$
$= 12$

Input Array

3	4	−2	7	3	11	5	−8	−9	2	4	−8

Linear Construction

12	1100_2	-15+4
11	1011_2	4
10	1010_2	-7
9	1001_2	-9
8	1000_2	23
7	0111_2	5
6	0110_2	14
5	0101_2	3
4	0100_2	12
3	0011_2	-2
2	0010_2	7
1	0001_2	3



$i = 11 = 1011_2$

$j = 1011_2 + 0001_2 = 1100_2$
$= 12$

Input Array

3	4	−2	7	3	11	5	−8	−9	2	4	−8

Linear Construction

12	1100_2	-11
11	1011_2	4
10	1010_2	-7
9	1001_2	-9
8	1000_2	23
7	0111_2	5
6	0110_2	14
5	0101_2	3
4	0100_2	12
3	0011_2	-2
2	0010_2	7
1	0001_2	3



$i = 12 = 1100_2$

$j = 1100_2 + 0100_2 = 10000_2$
$= 16$

Ignore updating j if index is out of bounds

Input Array

3	4	−2	7	3	11	5	−8	−9	2	4	−8

Linear Construction

12	1100_2	-11
11	1011_2	4
10	1010_2	-7
9	1001_2	-9
8	1000_2	23
7	0111_2	5
6	0110_2	14
5	0101_2	3
4	0100_2	12
3	0011_2	-2
2	0010_2	7
1	0001_2	3



Constructed Fenwick tree! We can now perform point and range query updates as required.

Input Array

3	4	−2	7	3	11	5	−8	−9	2	4	−8

Construction Algorithm

```
# Make sure values is 1-based!
function construct(values):

    N := length(values)

  # Clone the values array since we're
  # doing in place operations
  tree = deepCopy(values)

    for i = 1,2,3, … N:
        j := i + LSB(i)
        if j < N:
            tree[j] = tree[j] + tree[i]

    return tree
```

Source Code Link

Implementation source code and tests can all be found at the following link:

github.com/williamfiset/data-structures

NOTE: Make sure you have understood the previous content sections explaining how a Fenwick Tree works before continuing!

Fenwick Tree Range Update Visualization

16	10000	28
15	01111	6
14	01110	-1
13	01101	2
12	01100	-10
11	01011	9
10	01010	-11
9	01001	-5
8	01000	26
7	00111	11
6	00110	6
5	00101	2
4	00100	9
3	00011	-3
2	00010	5
1	00001	4

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
N/A	4	1	-3	7	2	4	11	0	-5	-6	9	-8	2	-3	6	7



Find the sum in the array between [11,15]

16	10000	28
15	01111	6
14	01110	-1
13	01101	2
12	01100	-10
11	01011	9
10	01010	-11
9	01001	-5
8	01000	26
7	00111	11
6	00110	6
5	00101	2
4	00100	9
3	00011	-3
2	00010	5
1	00001	4

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
N/A	4	1	-3	7	2	4	11	0	-5	-6	9	-8	2	-3	6	7



Find the sum in the array between [11,15]

6

16	10000	28
15	01111	6
14	01110	-1
13	01101	2
12	01100	-10
11	01011	9
10	01010	-11
9	01001	-5
8	01000	26
7	00111	11
6	00110	6
5	00101	2
4	00100	9
3	00011	-3
2	00010	5
1	00001	4

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
N/A	4	1	-3	7	2	4	11	0	-5	-6	9	-8	2	-3	6	7



Find the sum in the array between [11,15]

6 + -1

16	10000	28
15	01111	6
14	01110	-1
13	01101	2
12	01100	-10
11	01011	9
10	01010	-11
9	01001	-5
8	01000	26
7	00111	11
6	00110	6
5	00101	2
4	00100	9
3	00011	-3
2	00010	5
1	00001	4

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
N/A	4	1	-3	7	2	4	11	0	-5	-6	9	-8	2	-3	6	7



Find the sum in the array between [11,15]

6 + -1 + -10

16	10000	28
15	01111	6
14	01110	-1
13	01101	2
12	01100	-10
11	01011	9
10	01010	-11
9	01001	-5
8	01000	26
7	00111	11
6	00110	6
5	00101	2
4	00100	9
3	00011	-3
2	00010	5
1	00001	4

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
N/A	4	1	-3	7	2	4	11	0	-5	-6	9	-8	2	-3	6	7



Find the sum in the array between [11,15]

6 + -1 + -10 + 26

16	10000	28
15	01111	6
14	01110	-1
13	01101	2
12	01100	-10
11	01011	9
10	01010	-11
9	01001	-5
8	01000	26
7	00111	11
6	00110	6
5	00101	2
4	00100	9
3	00011	-3
2	00010	5
1	00001	4

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
N/A	4	1	-3	7	2	4	11	0	-5	-6	9	-8	2	-3	6	7



Find the sum in the array between [11,15]

6 + -1 + -10 + 26

16	10000	28
15	01111	6
14	01110	-1
13	01101	2
12	01100	-10
11	01011	9
10	01010	-11
9	01001	-5
8	01000	26
7	00111	11
6	00110	6
5	00101	2
4	00100	9
3	00011	-3
2	00010	5
1	00001	4

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
N/A	4	1	-3	7	2	4	11	0	-5	-6	9	-8	2	-3	6	7



Find the sum in the array between [11,15]

(6 + -1 + -10 + 26) - (

16	10000	28
15	01111	6
14	01110	-1
13	01101	2
12	01100	-10
11	01011	9
10	01010	-11
9	01001	-5
8	01000	26
7	00111	11
6	00110	6
5	00101	2
4	00100	9
3	00011	-3
2	00010	5
1	00001	4

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
N/A	4	1	-3	7	2	4	11	0	-5	-6	9	-8	2	-3	6	7



Find the sum in the array between [11,15]

(6 + -1 + -10 + 26) - (

16	10000	28
15	01111	6
14	01110	-1
13	01101	2
12	01100	-10
11	01011	9
10	01010	-11
9	01001	-5
8	01000	26
7	00111	11
6	00110	6
5	00101	2
4	00100	9
3	00011	-3
2	00010	5
1	00001	4

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
N/A	4	1	-3	7	2	4	11	0	-5	-6	9	-8	2	-3	6	7



Find the sum in the array between [11,15]

(6 + -1 + -10 + 26) - (-11

16	10000	28
15	01111	6
14	01110	-1
13	01101	2
12	01100	-10
11	01011	9
10	01010	-11
9	01001	-5
8	01000	26
7	00111	11
6	00110	6
5	00101	2
4	00100	9
3	00011	-3
2	00010	5
1	00001	4

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
N/A	4	1	-3	7	2	4	11	0	-5	-6	9	-8	2	-3	6	7



Find the sum in the array between [11,15]

(6 + -1 + -10 + 26) - (-11 + 26)

16	10000	28
15	01111	6
14	01110	-1
13	01101	2
12	01100	-10
11	01011	9
10	01010	-11
9	01001	-5
8	01000	26
7	00111	11
6	00110	6
5	00101	2
4	00100	9
3	00011	-3
2	00010	5
1	00001	4

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
N/A	4	1	-3	7	2	4	11	0	-5	-6	9	-8	2	-3	6	7



Find the sum in the array between [11,15]

(6 + -1 + -10 + 26) - (-11 + 26)

16	10000	28
15	01111	6
14	01110	-1
13	01101	2
12	01100	-10
11	01011	9
10	01010	-11
9	01001	-5
8	01000	26
7	00111	11
6	00110	6
5	00101	2
4	00100	9
3	00011	-3
2	00010	5
1	00001	4

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
N/A	4	1	-3	7	2	4	11	0	-5	-6	9	-8	2	-3	6	7



Find the sum in the array between [11,15]

(6 + -1 + -10 + 26) - (-11 + 26) = 6

16	10000	28
15	01111	6
14	01110	-1
13	01101	2
12	01100	-10
11	01011	9
10	01010	-11
9	01001	-5
8	01000	26
7	00111	11
6	00110	6
5	00101	2
4	00100	9
3	00011	-3
2	00010	5
1	00001	4

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
N/A	4	1	-3	7	2	4	11	0	-5	-6	9	-8	2	-3	6	7



Find the sum in the array between [11,15]

(6 + -1 + -10 + 26) - (-11 + 26) = 6

Least Significant Bit

16	10000
15	01111
14	01110
13	01101
12	01100
11	01011
10	01010
9	01001
8	01000
7	00111
6	00110
5	00101
4	00100
3	00011
2	00010
1	00001

0

Idea: Place an edge between values who only differ by their **Least Significant Bit** (LSB) in binary.

Least Significant Bit

16	10000
15	01111
14	01110
13	01101
12	01100
11	01011
10	01010
9	01001
8	01000
7	00111
6	00110
5	00101
4	00100
3	00011
2	00010
1	00001

Idea: Place an edge between values who only differ by their **Least Significant Bit** (LSB) in binary.

Least significant bits

Least Significant Bit

16	10000
15	01111
14	01110
13	01101
12	01100
11	01011
10	01010
9	01001
8	01000
7	00111
6	00110
5	00101
4	00100
3	00011
2	00010
1	00001

0

Idea: Place an edge between values who only differ by their **Least Significant Bit** (LSB) in binary.

In other words: Place an edge between nodes i and i without its LSB.

Least Significant Bit

16	10000
15	01111
14	01110
13	01101
12	01100
11	01011
10	01010
9	01001
8	01000
7	00111
6	00110
5	00101
4	00100
3	00011
2	00010
1	00001

0

Idea: Place an edge between values who only differ by their **Least Significant Bit** (LSB) in binary.

In other words: Place an edge between nodes i and i without its LSB.

13

1101

Least Significant Bit

16	10000
15	01111
14	01110
13	01101
12	01100
11	01011
10	01010
9	01001
8	01000
7	00111
6	00110
5	00101
4	00100
3	00011
2	00010
1	00001

0

Idea: Place an edge between values who only differ by their **Least Significant Bit** (LSB) in binary.

In other words: Place an edge between nodes i and i without its LSB.

13 -> 12

1101 -> 1100

Least Significant Bit

16	10000
15	01111
14	01110
13	01101
12	01100
11	01011
10	01010
9	01001
8	01000
7	00111
6	00110
5	00101
4	00100
3	00011
2	00010
1	00001

0

Idea: Place an edge between values who only differ by their **Least Significant Bit** (LSB) in binary.

In other words: Place an edge between nodes i and i without its LSB.

13 -> 12 -> 8

1101 -> 1100 -> 1000

Least Significant Bit

16	10000
15	01111
14	01110
13	01101
12	01100
11	01011
10	01010
9	01001
8	01000
7	00111
6	00110
5	00101
4	00100
3	00011
2	00010
1	00001

0

Idea: Place an edge between values who only differ by their **Least Significant Bit** (LSB) in binary.

In other words: Place an edge between nodes i and i without its LSB.

13 -> 12 -> 8 -> 0

1101 -> 1100 -> 1000 -> 0000

Fenwick Tree Visualization

16	10000
15	01111
14	01110
13	01101
12	01100
11	01011
10	01010
9	01001
8	01000
7	00111
6	00110
5	00101
4	00100
3	00011
2	00010
1	00001

Fenwick Tree Visualization

16	10000
15	01111
14	01110
13	01101
12	01100
11	01011
10	01010
9	01001
8	01000
7	00111
6	00110
5	00101
4	00100
3	00011
2	00010
1	00001

16 -> 0

10000 -> 00000

Fenwick Tree Visualization

16	10000
15	01111
14	01110
13	01101
12	01100
11	01011
10	01010
9	01001
8	01000
7	00111
6	00110
5	00101
4	00100
3	00011
2	00010
1	00001

15

1111



Fenwick Tree Visualization

16	10000
15	01111
14	01110
13	01101
12	01100
11	01011
10	01010
9	01001
8	01000
7	00111
6	00110
5	00101
4	00100
3	00011
2	00010
1	00001



15 -> 14

1111 -> 1110

Fenwick Tree Visualization

16	10000
15	01111
14	01110
13	01101
12	01100
11	01011
10	01010
9	01001
8	01000
7	00111
6	00110
5	00101
4	00100
3	00011
2	00010
1	00001



15 -> 14 -> 12

1111 -> 1110 -> 1100

Fenwick Tree Visualization

16	10000
15	01111
14	01110
13	01101
12	01100
11	01011
10	01010
9	01001
8	01000
7	00111
6	00110
5	00101
4	00100
3	00011
2	00010
1	00001



15 -> 14 -> 12 -> 8

1111 -> 1110 -> 1100 -> 1000

Fenwick Tree Visualization

16	10000
15	01111
14	01110
13	01101
12	01100
11	01011
10	01010
9	01001
8	01000
7	00111
6	00110
5	00101
4	00100
3	00011
2	00010
1	00001



15 -> 14 -> 12 -> 8 -> 0

1111 -> 1110 -> 1100 -> 1000 -> 0000

Fenwick Tree Visualization

16	10000
15	01111
14	01110
13	01101
12	01100
11	01011
10	01010
9	01001
8	01000
7	00111
6	00110
5	00101
4	00100
3	00011
2	00010
1	00001



13 -> 12

1101 -> 1100

Fenwick Tree Visualization

16	10000
15	01111
14	01110
13	01101
12	01100
11	01011
10	01010
9	01001
8	01000
7	00111
6	00110
5	00101
4	00100
3	00011
2	00010
1	00001

11

1011



Fenwick Tree Visualization

16	10000
15	01111
14	01110
13	01101
12	01100
11	01011
10	01010
9	01001
8	01000
7	00111
6	00110
5	00101
4	00100
3	00011
2	00010
1	00001



11 -> 10

1011 -> 1010

Fenwick Tree Visualization

16	10000
15	01111
14	01110
13	01101
12	01100
11	01011
10	01010
9	01001
8	01000
7	00111
6	00110
5	00101
4	00100
3	00011
2	00010
1	00001



11 -> 10 -> 8

1011 -> 1010 -> 1000

Fenwick Tree Visualization

16	10000
15	01111
14	01110
13	01101
12	01100
11	01011
10	01010
9	01001
8	01000
7	00111
6	00110
5	00101
4	00100
3	00011
2	00010
1	00001



9 -> 8

1001 -> 1000

Fenwick Tree Visualization

16	10000
15	01111
14	01110
13	01101
12	01100
11	01011
10	01010
9	01001
8	01000
7	00111
6	00110
5	00101
4	00100
3	00011
2	00010
1	00001



7

0111

Fenwick Tree Visualization

16	10000
15	01111
14	01110
13	01101
12	01100
11	01011
10	01010
9	01001
8	01000
7	00111
6	00110
5	00101
4	00100
3	00011
2	00010
1	00001



7 -> 6

0111 -> 0110

Fenwick Tree Visualization

16	10000
15	01111
14	01110
13	01101
12	01100
11	01011
10	01010
9	01001
8	01000
7	00111
6	00110
5	00101
4	00100
3	00011
2	00010
1	00001



7 -> 6 -> 4

0111 -> 0110 -> 0100

Fenwick Tree Visualization

16	10000
15	01111
14	01110
13	01101
12	01100
11	01011
10	01010
9	01001
8	01000
7	00111
6	00110
5	00101
4	00100
3	00011
2	00010
1	00001



7 -> 6 -> 4 -> 0

0111 -> 0110 -> 0100 -> 0000

Fenwick Tree Visualization

16	10000
15	01111
14	01110
13	01101
12	01100
11	01011
10	01010
9	01001
8	01000
7	00111
6	00110
5	00101
4	00100
3	00011
2	00010
1	00001



5 -> 4

0101 -> 0100

Fenwick Tree Visualization

16	10000
15	01111
14	01110
13	01101
12	01100
11	01011
10	01010
9	01001
8	01000
7	00111
6	00110
5	00101
4	00100
3	00011
2	00010
1	00001



3

0011

Fenwick Tree Visualization

16	10000
15	01111
14	01110
13	01101
12	01100
11	01011
10	01010
9	01001
8	01000
7	00111
6	00110
5	00101
4	00100
3	00011
2	00010
1	00001



3 -> 2

0011 -> 0010

Fenwick Tree Visualization

16	10000
15	01111
14	01110
13	01101
12	01100
11	01011
10	01010
9	01001
8	01000
7	00111
6	00110
5	00101
4	00100
3	00011
2	00010
1	00001



3 -> 2 -> 0

0011 -> 0010 -> 0000

Fenwick Tree Visualization

16	10000
15	01111
14	01110
13	01101
12	01100
11	01011
10	01010
9	01001
8	01000
7	00111
6	00110
5	00101
4	00100
3	00011
2	00010
1	00001



1 -> 0

0001 -> 0000

Fenwick Tree Visualization

16	10000
15	01111
14	01110
13	01101
12	01100
11	01011
10	01010
9	01001
8	01000
7	00111
6	00110
5	00101
4	00100
3	00011
2	00010
1	00001



Fenwick Tree Analysis

Although the values contained by different Fenwick trees may differ, the actual structure of the tree does not depend on the values it is holding.

Fenwick Tree Analysis

The furthest node from the root will always be at most $\log_2(n)$ nodes deep. This happens when all the trailing bits are 1's. These numbers are of the form 2^n-1.

2^1-1 = 1 = 0b000001
2^2-1 = 3 = 0b000011
2^3-1 = 7 = 0b000111
2^4-1 = 15 = 0b001111
2^5-1 = 31 = 0b011111
2^6-1 = 63 = 0b111111

Fenwick Tree Analysis

Odd nodes are always leaves in our Fenwick Tree because their LSB is always a 1.



References

1. Fenwick Tree/Binary indexed tree playlist, by William Fiset. Link: https://www.youtube.com/playlist?list=PLDV1Zeh2NRsCvoyP-bztk6uXAYoyZg_U9
2. C++ Implementation : https://gist.github.com/dipta10/8bdc77376027ed3d5b81e90436a8d5bd
3. Binary Indexed Tree/Fenwick Tree (Bangla | বাংলা) Theory + Implementation, Link: https://www.youtube.com/watch?v=aAALKHLeexw&t=1286s&ab_channel=LoveExtendsCode