Experiment 3a:

CODE:

```
  GNU nano 8.7.1
#!/bin/bash

if [ -f "$1" ]
then
echo "$1 is a file"
elif [ -d "$1" ]
then
echo "$1 is a Directory"
elif [ "$#" -lt 1 ]
then
echo "Please Pass the Argument"
else
echo "$1 doesn't exist"
fi
```

OUTPUT:

```
tofiq@Tofiq:~$ nano exp3a.sh
tofiq@Tofiq:~$ bash exp3a.sh MIET
MIET is a Directory
tofiq@Tofiq:~$ bash exp3a.sh title.txt
title.txt doesn't exist
tofiq@Tofiq:~$ bash exp3a.sh name1.txt
name1.txt is a file
tofiq@Tofiq:~$ bash exp3a.sh
Please Pass the Argument
```

Experiment 3b:

CODE:

```
  GNU nano 8.7.1
#!/bin/bash
for file in "$@"
do
    if [ -f "$file" ]
    then
        mv "$file" "$(echo "$file" | tr '[:lower:]' '[:upper:]')"
        echo "$file Changed"
    else
        echo "$file does not exist"
    fi
done
```

OUTPUT:

```
tofiq@Tofiq:~$ bash exp3b.sh name1.txt name2.txt
name1.txt Changed
name2.txt Changed
tofiq@Tofiq:~$ ls
1.sh       10sep.txt  2.sh  Desktop    Downloads  Music      NAME2.TXT
10sep.sh   10sep1.sh  5     Documents  MIET       NAME1.TXT  Pictures
```