



포팅 메뉴얼



Index

1. Stacks

- Issue Management
- SCM(Software Configuration Management)
- Communities
- Development Environment
- Details

2. Env

- application.yml
- 안드로이드 환경변수?

3. Build & Distribute

- Spring Boot
- Android
- Jenkins

4. Deployment Command

- Local
- EC2 - Jenkins Pipeline

5. Nginx default

1. Stacks

- Issue Management : **JIRA**
- SCM(Software Configuration Management) : **GITLAB**
- Communities : **Notion, MatterMost**
- Development Environment
 - **IntelliJ 2023.3**
 - **Android Studio Hedgehog | 2023.1.1**
 - **Java 17**
 - **Kotlin**
 - **Spring Boot 3.2.2**
 - **Ubuntu 20.04.6 LTS (AWS EC2)**
 - **MariaDB (azure)**

2. Env

- application.yml

```
server:
  port: 포트 번호
spring:
  datasource:
    driver-class-name: com.mysql.cj.jdbc.Driver
    url: 사피 DB
    username: 유저네임
    password: 비밀번호
  jpa:
    hibernate:
      ddl-auto: none

  data:
    redis:
      host: 레디스 호스트
      port: 포트 번호
```

```
security:
  oauth2:
    client:
      registration:
        google:
          client-id: 발급 받은 client ID
          client-secret: 발급 받은 Client Secret
          authorization-grant-type: 인증 코드
          redirect-uri: /oauth2/code/registrationId
          scope:
            - email
servlet:
  multipart:
    max-file-size: 100MB
    max-request-size: 100MB

logging:
  level:
    root: info

cloud:
  aws:
    credentials:
      access-key: 액세스 키
      secret-key: 시크릿 키
    s3:
      bucket: 버킷 이름
      region:
        static: 지역 이름
        auto: false
      stack:
        auto: false
decorator:
  datasource:
```

```
p6spy:
  enable-logging: true

jwt:
  secret: jwt 시크릿키
```

3. Build & Distribute

- Git Clone

```
git clone https://lab.ssafy.com/s10-webmobile4-sub2/S10P12A30
```

- Spring Boot

```
# Build
cd togeduck
chmod +x ./gradlew
./gradlew clean build
docker build -t togeduck:latest .
```

- Android

```
// Gradle Scripts - local.properties 에 아래 코드 추가 필요
naver_map_client_secret=네이버 api 인증키
```

- redis

```
docker pull redis:alpine
docker run -d -p 6379:6379 --name=redis redis:alpine
```

4. Deployment Command

Local

- Backend Server

```
docker run -d -p 8082:8082 --name togeduck togeduck:latest
```

- Android

```
build -> Generate Signed Bundle (apk로 추출)
```

EC2 - Jenkins Pipeline

- jenkins 프로젝트구성 - Pipeline - Pipeline Script 선택, 아래 스크립트 복사, 붙여넣기 및 채우기

```
pipeline {
    agent any
    environment {
        repository = {리포지토리}
        DOCKERHUB_CREDENTIALS = credentials('dockerhub')
    }
    stages {
        stage('gitlab clone') {
            steps {
                // Get some code from a GitHub repository
                git branch: 'master', credentialsId: {credentialsId}
            }
        }

        stage('build') {
            steps {
                dir('togeduck') {
                    // some block
                    sh'''
                        echo build start
                        chmod +x ./gradlew
                        ./gradlew clean build
                        ...
                    '''
                }
            }
        }
    }
}
```

```

    }
  }
}
stage('Cleaning up') {
  steps {
    sh "docker rmi $repository:latest" // docker image
  }
}
stage('Building our image') {
  steps {
    script {
      dir('togeduck') {
        // sh "docker build -t $repository:latest ."
        dockerimage = docker.build("$repository:latest")
      }
    }
  }
}
stage('Login'){
  steps{
    sh 'echo $DOCKERHUB_CREDENTIALS_PSW | docker login -u $DOCKERHUB_USERNAME --password-stdin'
  }
}
stage('Deploy our image') {
  steps {
    script {
      docker.withRegistry('https://registry.hub.docker.com', 'DOCKERHUB_USERNAME') {
        // Building new image
        dockerimage.push();
      }
    }
  }
}
stage('Pull image') {
  steps {
    sh "docker pull $repository:latest" // docker image
  }
}

```

```

    }
}
stage('Run Image') {
    steps {
        dir('togeduck') {
            sh'''
                docker stop togeduck
                docker rm togeduck
                docker run -d -p 8082:8082 --name togeduck
            '''
        }
    }
}
}
```

5. Nginx default

```
server {
    listen 80 default_server;
    listen [::]:80 default_server;

    root /var/www/html;

    server_name _;

    location / {
        # First attempt to serve request as file, then
        # as directory, then fall back to displaying a 404
        try_files $uri $uri/ =404;
    }
}
```

```

}

server {

    root /var/www/html;

    # Add index.php to the list if you are using PHP
    index index.html index.htm index.nginx-debian.html;
    server_name i10a301.p.ssafy.io; # managed by Certbot
    client_max_body_size 10M;

    location / {
        proxy_set_header Host $host;
        proxy_set_header X-Real-IP $remote_addr;
        proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
        proxy_set_header X-Forwarded-Proto $scheme;
        proxy_set_header Upgrade $http_upgrade;
        proxy_set_header Connection "upgrade";
        proxy_pass http://localhost:8082;
        proxy_redirect off;
    }

    listen [::]:443 ssl ipv6only=on; # managed by Certbot
    listen 443 ssl; # managed by Certbot
    ssl_certificate /etc/letsencrypt/live/i10a301.p.ssafy.io/fullchain.pem; # managed by Certbot
    ssl_certificate_key /etc/letsencrypt/live/i10a301.p.ssafy.io/private.pem; # managed by Certbot
    include /etc/letsencrypt/options-ssl-nginx.conf; # managed by Certbot
    ssl_dhparam /etc/letsencrypt/ssl-dhparams.pem; # managed by Certbot
}

server {
    if ($host = {host_uri}) {
        return 308 https://$host$request_uri;
    } # managed by Certbot
}

```



```
listen 80 ;  
listen [::]:80 ;  
server_name i10a301.p.ssafy.io;  
return 404; # managed by Certbot  
}
```