

Problem B: The 727 Jumpscare

Time Limit: 1.0s | Memory Limit: 256MB

Description

Ethan is an avid player of the rhythm game *osu!*. Like many players in the community, he has developed a specific neurosis: seeing the number **727** anywhere causes him immense psychological distress.

Ethan has a list of N strings representing data dumps from his recent plays. However, the brainrot has advanced significantly. He no longer just sees the number "727" when the digits are right next to each other. He now sees it hidden inside other numbers!

Ethan sees a "jumpscare" whenever he can find the digits **7**, **2**, and **7** appearing in that order within a string, even if they are separated by other digits.

Formally, for a string S , you need to count the number of triples of indices (i, j, k) such that:

$$1 \leq i < j < k \leq |S|$$

$$S[i] = '7', \quad S[j] = '2', \quad S[k] = '7'$$

Calculate the total number of such "727" subsequences in each string given.

Input

The first line contains a single integer N ($1 \leq N \leq 20$), the number of test strings.

The next N lines each contain a string S consisting of digits ($1 \leq |S| \leq 5000$).

Output

For each string, output a single line containing the number of "727" subsequences.

Examples

Example 1

Input:

```
3
727
7277
7227
```

Output:

1
2
2

Explanation:

- **727**: One occurrence (indices 1, 2, 3).
- **7277**: The first '7' and '2' can combine with either the third '7' or the fourth '7'. Total = 2.
- **7227**: The first '7' and the last '7' can combine with either of the '2's in the middle. Total = 2.

Example 2

Input:

1
12345

Output:

0