


*開關產品未經SWITRONIC同意,請勿拆解,否則無法負品質及安全責任。 Please do not decompose the switch without any permission from SWITRONIC, otherwise the quality and safety responsibility could not be guaranteed.


*本圖面若與目錄之規格尺寸不符,以本圖面規格尺寸為主。 Below is our main specification if different from catalog.








RoHS compliant







JUL. 01, 201

ISSUED

SPECIFICATION

SPECIFICATION
Rating: 0.3A 50V DC.
Timing: Non-shorting.
Contact resistance: $30m\Omega$ Max.(initial)
Insulation resistance: $100M\Omega$ at 500V DC.
Withstand voltage: 500V AC for 1 minute.
Operating force: $200\pm80g$.
Life: 10,000 Cycles Min.
Soldering temperature: $230^{\circ}C$ Max. for 2 ± 0.5 seconds.
Soldering time: 1 time only

Note 1: Unwashable, don't be immerged by epoxy and organic solvent.

Note 2: Please do not scale the drawing comparing to real product and kindly measure the size of real product.

MATERIAL

INIXIEIXE	
Knob: POM, black. —————	
Frame: Steel strip, Ni plated. ——	
Base: Phenolic resin, natural. ——	3
Terminal: Brass strip, Ag plated. —	4
Contact clip: PBS strip, Ag plated.	

STORAGE METHOD

After opening the bag of the switches, please include a desiccant into the bag, then seal it to avoid product oxidation.

打開包裝袋後,請在袋中加入乾燥劑並「密封」,避 免產品氧化。

V2.2	無	改 版	2015.07.01
V2.1	無	改 版	2009.08.26
V2.0	無	新繪製	2004.11.03
版本 VER.	符號 SYMBOL	修 改 內 容 ALTERATION	更新日期 DATE

產品 PRODUCT Slide Switch 型號 MODEL NO. SS12D010	l-G
---	-----

比例 SCALE 5:1 mm 公差 TOLERANCE .X=±0.3mm, .XX=±0.2mm 製圖 DRAWN BY 核圖 CHECKED BY 主管 APPROVED BY Margaret ehuckī poter young Kuo



綺電子企業股份有限公司

總公司:110 含北市信義路四段415號13樓之3 13F-3, NO.415, SEC.4, HSIN YI ROAD, TAIPEI, TAIWAN TEL: 886-2-27290229(Rep.) FAX: 886-2-27582086