

8-hour Online Written Exam of Advanced Computer Systems – ACS, 2020-2021

Department of Computer Science, University of Copenhagen (DIKU)

Date: January 22nd, 2021

Preamble

This is your final 8-hour online written exam for Advanced Computer Systems, block 2, 2020/2021. The exam will be evaluated on the 7-point grading scale with external grading, as announced in the course description.

- Hand in a **single PDF file**, in which your exam number is written on every page.
- Your answers must be provided in English.
- Hand-ins for this exam must be individual, so **cooperation with others in preparing a solution is strictly forbidden**.
- The exam is open-book and all aids are allowed. If you use **any sources other than book or reading material for the course**, they **must be cited appropriately**.
- You may also use your computer or other devices, but you may not access online resources or communicate with any other person in preparing a solution to the exam.
- Remember to write your exam number on all pages.
- You can exclude this preamble in your hand-ins if you directly write on this file.
- This exam has a total of **18** pages excluding this preamble, so please double-check that you have been given a complete exam set before getting started.

Expectations regarding formatted spaces

For each question in this exam, you will find formatted space where you can provide your answer. The spaces provided are designed to be large enough to provide satisfactory (i.e., concise and precise) answers to each of the questions.

Expectations regarding question importance

Questions carry indicative weights. The weights will be used during evaluation to prioritize question answers towards grading; however, recall that the exam is still evaluated as a whole. In other words, we provide weights only as an indication so that you can prioritize your time, should you need to during the exam. You cannot assume that weights will be divided equally among subquestions.

The following table summarizes the questions in this exam and their weights.

Question	Weight
Q1 Atomicity	7%
Q2.1 Bottlenecks	4%
Q2.2 Performance Evaluation	3%
Q3.1 Schedules	13%
Q3.2 Deadlocks	7%
Q4.1 The Missing Log	6%
Q4.2 The Recovery	10%
Q5.1 Lamport Logical Clock and Vector Clock	10%
Q5.2 Replication	10%
Q6.1 Basic Concepts of Distributed Transactions	2%
Q6.2 Two-Phase Commit	8%
Q7.1 Selection	4%
Q7.2 Join and Aggregate	16%

Errors and Ambiguities

If you find any errors or ambiguities in the exam text, you should clearly state your assumptions in answering the corresponding questions. Some of the questions may not have a single correct answer, so recall that ambiguities could be intentional.


1 Atomicity (7%)

Give three flavors of atomicity considered in the lecture and explain what each of them aims to achieve. For each flavor, give and briefly explain one main challenge that makes achieving this flavor a non-trivial task and give one example approach towards achieving it.

This image shows a single sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins or other markings on the paper.

2 Performance (7% in total)

Consider a service that internally uses the following architecture to process the incoming client requests:



The service consists of several distributed components, each of which runs on a separate compute node (i.e., on physically separate hardware):

- a *scheduler* S that distributes the workload between the workers
- n *workers* W_i that perform the actual computation
- an *aggregator* A that combines the computation results into a single output.

The communication between the different compute nodes proceeds as shown in the picture. In particular the workers do not communicate with each other.

Consider two possible scenarios:

1. All workers perform the same computation on different disjoint parts on the input. For example, consider a word count service that inputs words. The words are uniformly assigned to workers by S. Each worker outputs word count histograms, which A periodically combines into a single histogram.
2. Each worker performs a different task on a part of the input. The parts assigned to different workers may (need to) overlap. For example, the service might periodically compute different aggregates upon inputting words and numbers, e.g., the sum of all seen numbers, the set of longest seen words, or the number of words of length greater than the largest number seen so far. The scheduler is responsible for giving each worker the required information to perform its assigned task.

2.1 Bottlenecks (4%)

What are the main performance bottlenecks of the service in both given scenarios? In particular, which bottlenecks are common to both scenarios, and which are specific to only one of them? Which architectural alternatives could alleviate some of the bottlenecks. Briefly justify your answers.

2.2 Performance Evaluation (3%)

How would you evaluate the performance of the above architecture in both scenarios? Which performance metrics would you measure? How would you measure them? Would you setup the experiments differently for the two scenarios?

3 Concurrency Control (20% in total)

3.1 Schedules (13%)

We consider three transactions T1, T2, and T3 consisting of the following actions.

T1: R(X) W(X) R(Y) W(Y) C

T2: R(Y) W(Y) W(Z) C

T3: R(X) R(Z) W(Z) C

IMPORTANT: We ask you to come up with five **different** transaction schedules of T1, T2, and T3 satisfying different constraints given below. For each schedule **explain** why it satisfies the constraints.

Schedules, 3.1.1: Give a serializable transaction schedule of T1, T2, and T3.

(figure space)

Schedules, 3.1.2: Give a conflict-serializable transaction schedule of T1, T2, and T3.

(figure space)

Schedules, 3.1.3: Give transaction schedule of T1, T2, and T3 that is **not** conflict-serializable.

(figure space)

Schedules, 3.1.4: Give a conflict-serializable transaction schedule of T1, T2, and T3 that could **not** have been generated by a scheduler using strict two-phase locking (S2PL) with lock upgrades (from shared to exclusive).

(figure space)

Schedules, 3.1.5: Give a conflict-serializable transaction schedule of T1, T2, and T3 that could have been generated by a scheduler using strict two-phase locking (S2PL) with lock upgrades (from shared to exclusive), but **not** by a scheduler using conservative two-phase locking (C2PL) with lock downgrades (from exclusive to shared).

(figure space)

3.2 Deadlocks (7%)

Deadlocks, 3.2.1: Which of the two-phase locking variants can result in deadlocks? Explain why by giving concrete schedules with deadlocks. Also explain why other variants cannot generate deadlocks.

Deadlocks, 3.2.2: Consider the following two strategies aiming to prevent deadlocks among a fixed set of transactions $\{T_1 \dots T_n\}$ being scheduled by strict two-phase locking (S2PL):

1. If a transaction T_i requests a lock that is currently held by another transaction T_j , then T_j is aborted if $i < j$; otherwise T_i waits.
2. If a transaction T_i requests a lock that is currently held by another transaction T_j , then T_i waits if T_i holds strictly more (other) locks than T_j does; otherwise T_i aborts.

Which of these strategies prevent deadlocks? For those that do, explain why. For those that do not, give a counterexample schedule that exhibits a deadlock.

4 Recovery (16% in total)

We consider a transactional database that uses the ARIES algorithm as its recovery mechanism. At the beginning of time, there are no transactions active in the system and no dirty pages. A checkpoint is taken. After that, three transactions, T1, T2, and T3, enter the system and perform various operations, **including at least one page update per transaction**. Eventually, a crash happens, the system restarts and proceeds with the recovery. As the result of the analysis phase, the algorithm arrives at the following transaction table (sorted by lastLSN) and dirty page table (sorted by recLSN):

XACT_ID	status	lastLSN	PID	recLSN
T3	committed	4	P42	3
T2	aborted	7	P<EN>	$5 + (<EN> \bmod 2)$
T1	running	8	P99	8

Here, <EN> refers to your personal Exam Number. For example, if your Exam Number is 154 then the last line of the dirty page table reads “P154 | 5” (because 154 modulo 2 is 0).

4.1 The Missing Log (6%)

Complete the below log, in the usual format, to be a log at the moment of the crash, which could have lead to the shown situation. Assume that the log sequence numbers are the (consecutive) natural numbers starting with 1.

LSN	PREV_LSN	XACT_ID	TYPE	PAGE_ID	UNDONEXTLSN
---	-----	-----	----	-----	-----
1	-	-	begin CKPT	-	-
2	-	-	end CKPT	-	-
...					

3	null	T3	update	P42	
4	3	T3	commit	-	-
5	null	T1	update	P154	
6	null	T2	update	P42	
7	6	T2	abort	-	-
8	5.	T1	update	P99	
9					

(figure space)

4.2 The Recovery (10%)

Based on your log, complete the recovery procedure. Show:

1. the sets of winner and loser transactions;
2. the values for the LSNs where the redo phase starts and where the undo phase ends;
3. the set of log records that may cause pages to be rewritten during the redo phase;
4. the set of log records undone during the undo phase;
5. the contents of the log after the recovery procedure completes.

For each of the items above, briefly justify your answer.

(figure space)

5 Reliability (20% in total)

The architect of a E-Commerce service, DanskeShop, has adopted an architecture that decomposes the system into several fine-grained independent services, including Payment, Order, and Shipment.

Clients only interact with the Order service, which in turn work with Payment and Shipment to complete the client orders. In particular, Order accept two types of client requests, submit an order or cancel an on-going order. All the communication is *asynchronous*.




Figure 1: System Architecture of DanskeShop

When Order receives a client's order, it *asynchronously* sends the following two messages:

1. an NewOrder message with the order ID and the order amount to Payment;
2. an NewOrder message with the order ID, the list of ordered products and the shipping address to Shipment.

Payment and Shipment will, respectively, send a message AckOrder back to Order upon the completion of processing the order. When Order receives both the AckOrder messages from Payment and Shipment, it acknowledges the client.

A client can send a request to the Order service to cancel an on-going order. Once Order receives a cancellation request from a client, it sends the following messages

1. a Cancel message with the order ID to Payment;
2. a Cancel message with the order ID to Shipment.

Payment and Shipment send, respectively, an AckCancel message back to Order as the response. Upon receiving the AckCancel messages from both Payment and Shipment, it acknowledges the client of the order cancellation.

A client can submit the same order request multiple times. But the system should guarantee that only one of the requests is carried out.

Figure 2 shows the message exchanges of a particular execution, where a client sends a new order request and then shortly after, cancel the same order while it is still on-going. For brevity, we omit the messages sent between the client and Order. At event e1, Order receives a new order request from a Client, and at e3, it receives an order cancellation request from the same client regarding the same order. The same client regrets the cancellation, and resend the same order request with the same order ID again at e7.

Furthermore, some events (including e2, e4 and e6) represent both receiving a message and sending back the responding message. For example, event e2 represents Payment receives the NewOrder message and sends back the AckOrder message. Each one of these events is considered a single atomic event.




Figure 2: Exchange of messages between services

5.1 Lamport and Vector Clock (10%)

Based on the above scenario and the messages exchanges depicted in Figure 2. Answer the following questions.

Lamport and Vector Clock, 5.1.1: Write the Lamport logical clock of each event, assuming each process starts with a clock at 0.

Lamport and Vector Clock, 5.1.2: Write the vector clock of each event, assuming each process starts with clock at (0,0,0).

Lamport and Vector Clock, 5.1.3: P1 received two messages at e9 and e10, respectively. By using Lamport logical clock or vector clock, can P1 tell the message received at e10 was actually sent before the one received at e9? If so, how? Otherwise, why? Briefly explain the reasoning of your answer.

Lamport and Vector Clock, 5.1.4: At e4, P3 received a Cancel message, and then immediately responded with an AckCancel message. At e8 and e11, P3 received, respectively, a NewOrder message with the same order ID. In the figure, the Shipment's responses to these two messages were omitted. Recall that, when a client submit the same order quest multiple times, the system should guarantee that only one of them is executed. What are the correct responses of Shipment to these two NewOrder messages? How Shipment can enforce the correct responses? Brief explain your reasoning.

5.2 Replication (10%)

To enhance the reliability of DanskeShop system, the states of the services have to be replicated. Suppose each service should be replicated into 5 copies. Answer the following questions.

Replication, 5.2.1: The Shipment service maintains the inventory of products available at DanskeShop. After an order is processed, the stocks of the products involved in the order would be deducted accordingly. Compare the pros and cons of synchronous replication and asynchronous replication for replicating Shipment.

Replication, 5.2.2: Suppose synchronous replication is adopted to replicate the state of Shipment into 5 copies. The write quorum is 3 ($Q_w = 3$) while the read quorum is 2 ($Q_r=2$). Would this setup be problematic? Why or why not? Briefly explain the reasoning of your answer.

Replication, 5.2.3: To replicate the Order service, which of the following replication scheme can also enhance the scalability of the service in terms of I/O throughput: a) Asynchronous Primary-Site, b) Asynchronous Peer-to-Peer, and c) Synchronous Replication? How is the state of Order replicated under the chosen scheme? Briefly explain the reasoning of your answer.

6 Distributed Transaction (10% in total)

Consider again the scenario of the e-commerce site DanskeShop described in Question 5 and answer the following questions.

6.1 Basic Concepts of Distributed Transactions (2%)

Basic Concepts of Distributed Transactions, 6.1.1: Does the processing of a client's new order request fulfill the atomicity property in the case of node failures? Use an example scenario to briefly explain why or why not.

6.2 Two-Phase Commit (8%)

DasnkeShop decides to implement another version of the system, where Two-Phase Commit (2PC) is used to carry out a new order request. Suppose the three services are deployed on separate machines, and the transaction coordinator runs on the machine of the Order service, while all the three services take part in each transaction. In this system version, the client cannot cancel an order once it is submitted. Answer the following questions.

Two-Phase Commit, 6.2.1: Briefly describe the procedure of 2PC to commit a New Order transaction over the three services when there is no failure occurred. Write down the coordinator's log records regarding the 2PC protocol in this case. For each log record, write down its type, such as "prepare", and the necessary information to tolerate node failures.

Two-Phase Commit, 6.2.2: Suppose the site of Order fails after the coordinator has decided to abort a transaction and has written the abort log record to the disk, but before the abort messages were sent to any subordinates. Assume Shipment has voted yes (i.e. commit) and Payment has voted no (i.e. abort), describe a scenario where Shipment and Payment can proceed to complete this transaction. Explain the scenario step by step.

This image shows a single sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.

Two-Phase Commit, 6.2.3: Suppose 2PC with presumed abort is implemented, and the site of Order fails after it has decided to abort and has written the abort log record to the disk. Describe what could happen to Shipment if it has not received the abort message, and what could happen to Order after it restarts from the failure.

[illegible]

7 Data Processing (20% in total)

Consider again the DanskeShop scenario described in Question 5. The data analyst at DanskeShop is required to analyze some sales statistics. The following tables are provided to the data analyst:

- Orders(orderID, productID, unitPrice, quantity), which stores the unit price, and the quantity of each product in each order.
- Shipments(orderID, addr, city, country), which stores the shipping address of each order.

The Orders table has 25,000 pages, and Shipments has 1,500 pages.

7.1 Selection (4%)

The first task is to select all the records in Orders, where unitPrice is greater than 500 and the quantity is greater than 10.

Selection, 7.1.1: Suppose there is no index on the attribute of unitPrice or quantity. What is the most efficient algorithm to evaluate this query? What is the I/O cost of the algorithm? Briefly explain your answer.

Selection, 7.1.2: Suppose there is a non-clustered B+ tree index on unitPrice, and there are 50,000 records that can meet the selection conditions. What is the worst-case I/O cost of using this index to answer this query? Is it always a good idea to use this index than the algorithm that you come up with in the previous question? Briefly explain your answer?

7.2 Join and Aggregate (16%)

Another task of the data analyst is to produce the regional sales statistics: “for each product and each city, return the total income from the sales of this product in all the orders delivered to this city”. The schema of the results should be `Sales(productID, city, salesIncome)`. Suppose the database server used by the data analyst has 150 buffer pages. Answer the following questions.

Join and Aggregate, 7.2.1: The first step is joining the tables `Orders` and `Shipments` on `orderID`. What is the most efficient algorithm to perform this step? What is the I/O cost of this algorithm? For simplicity, you can omit the I/O of writing out the join results. Briefly explain your answer and justify your choice of algorithm.

Join and Aggregate, 7.2.2: If the server can be upgraded with more memory, is there a case where your choice of algorithm in Question 7.2 be different? If yes, give the precise condition (in terms of memory size), under which you would make a different algorithm choice, and explain your answer. Otherwise, briefly explain the reasoning.

Join and Aggregate, 7.2.3: The second step is grouping the records of the results from the previous step based on the values of productID and city and then perform aggregation on each group. Assume the output size of the previous step is 100,000 pages and the server is upgraded to having 500 buffer pages. Moreover, suppose the final output should be sorted by productID. Describe the most efficient algorithm to perform this step. What is the I/O cost of this algorithm? Again, you can omit the I/O of writing out the results. Briefly explain your answer and justify your choice of algorithm.

Join and Aggregate, 7.2.4: Suppose the data analyst is provided with a cluster of 5 servers, rather than 1 server. Describe the most efficient parallel algorithm to perform the processing in Question 7.2. Assume the input data of this step is randomly stored on the 5 servers. What is the expected amount of data to be transferred over the network? Briefly explain and justify your answer.
