GateProbe: Metamorphic Testing of the Permission Gates of Coding Agents

Jerzy Kamiński*, Stanislav Chumakov*, Ilya Galyukshev, Artem Kuznetsov, Kirill Redko,
Danil Fedorov, Sergey Chuprin, Aidar Shumbalov, Nikolay Nikitin
ITMO University, Saint Petersburg, Russia
jkaminski@niuitmo.ru, svchumakov@itmo.ru
*Equal contribution

***Abstract*—Coding agents ask a permission gate before each tool call. The newest gates are learned models, decision models or LLM judges, which read a policy and a call and decide whether to allow it. Their errors are hard to find, because the right verdict for most calls is unknown. GateProbe tests such gates by metamorphic testing, without knowing the right verdicts. It rewrites each call in ways whose effect on the verdict is known: writing the recursion flag in full or the policy in another format must keep the verdict, and adding `sudo` must not weaken it. It then checks whether the gate's verdicts agree. GateProbe ships as a command-line tool and a Docker image, and it replays every recorded answer without an API key. On 300 tool calls and seven gates, every gate changes its verdict on some rewrites that keep the meaning, up to 7.5% of them, more often than on a repeated identical request. For the model gates this happens mostly when only the policy's format changes. Injected text pushes two decision models toward allow. Riskier rewrites almost never weaken a verdict, and the few that do reveal gate errors and a gap in one policy. Tool, Docker image and replay bundle: https://github.com/Token-Waste-Group/gate-probe. Demo: https://huggingface.co/spaces/TokenWasteGroup/gateprobe. Video: https://youtu.be/rZ6yazAzKs8.**

***Index Terms*—metamorphic testing, coding agents, permission gates, decision models, LLM-as-a-judge, robustness**

I. Introduction

A coding agent runs shell commands, edits files and calls the network on its user's behalf, so every tool call passes a *permission gate* that allows it, denies it, or asks the user. Gates used to be allow and deny patterns written by hand [1]. Increasingly they are learned models. Since September 2026, OpenRouter's Decisions API has served typed decision models that answer typed questions (true/false, a choice among labels, a score) about a given state [2]. OpenRouter's own recipes use one of them, TypeSafe's Jev, to auto-approve coding-agent permission prompts and to gate agent tool calls [3], [4], and a community project wraps it as a security gate [5].

A gate is a security component: its specification is the policy, and a wrong *allow* runs a destructive or exfiltrating command. Yet the new gates are ML components, and known to be fragile. When the definitions bound to the answer names are swapped, typed decision models follow the names. With yes/no names they change their answer far more often than with neutral 0/1 names, and their mean AUC falls below chance [6]. TypeSafe's documentation warns that injected instructions and misleading framing can move an answer [7], and in one reported integration test, a fake "user pre-approved" field cut Jev's block probability for `rm -rf ~/.ssh` by more than a third [8].

Testing a gate meets the classic oracle problem: for most calls nobody can say what the right verdict is. *Metamorphic testing* sidesteps it by checking relations between the outputs of related inputs [9], [10], as DeepTest did for driving models [11]. Gates fit it well, because their inputs carry a natural risk order. An equivalent rewrite of a call must not change the verdict, a strictly more dangerous rewrite must not lower the block probability, and irrelevant or injected text must not move it. One complication is that the same request can come back with different probabilities, so a test has to separate real changes from noise.

Envisioned users: Platform and DevEx engineers who configure an agent's permissions want evidence before they trust an auto-approver. Authors of gates and gate middleware need a regression suite. Researchers can compare decision models, LLM judges and rule sets on these tests.

Contributions: GateProbe is the first reusable metamorphic test suite for coding-agent permission gates, vendor-neutral across the Decisions API, LLM judges and rule sets:

- a CLI and Docker image with adapters for any Decisions API model, LLM judges (OpenAI-compatible endpoints and the Anthropic API) and Claude Code-style rule sets. A content-addressed response cache doubles as a key-free replay mode, and the outputs are an HTML report, a CI check and a live Claude Code hook [12];
- 26 transforms in five relation classes, all but model paraphrases deterministic and label-free, scored against each gate's repeat rate by rules pre-registered before any run;
- a validation on seven gates: four decision models, two LLM judges and a rule set (Section V).

II. GateProbe

GateProbe is a Python CLI. Fig. 1 shows how data flows through it.

Corpus and policies: A *probe* is one tool call (a shell command, a file read or write, a web fetch) under one authorization policy, tagged with a tool family and a risk tier (read, reversible write, irreversible, exfiltration). Each policy is written once as allow and deny rules over actions and




Fig. 1. How data flows through GateProbe.




Fig. 2. Three rewrites of one call, with drex's verdict and block probability on each.

scopes, then rendered as YAML, JSON, prose and bullets, so a change of format can be tested like any other rewrite. The `expand` command turns each probe into rewrites by the rules of Section III.

Gate adapters: Every gate implements one contract. A policy rendering, a tool call, context text and answer labels go in. A verdict (allow, ask, deny), a block probability p_{block}, the raw response, the pinned model id, latency and cost come out. Decision models answer through the Decisions API. LLM judges give p_{block} by answer-token logprobs on any OpenAI-compatible endpoint, or as a stated probability through the Anthropic Message Batches API. Rule sets match Claude Code-style allow and deny patterns [1]. A new vendor is one file.

Runs and outputs: The cache key holds the gate, the pinned model, the exact request bytes and the repeat index, so the three repeats are real calls and a reviewer's replay needs no API key. The `report` command renders an HTML page with each changed verdict next to its original call. The `ci` command fails a pipeline when a class's share of changed verdicts exceeds the gate's repeat rate significantly and by more than a tolerated margin, so a gate upgrade can be held back. The `hook` command plugs into Claude Code as a `PreToolUse` hook [12]. It prints the gate's verdict for each call, warns when the call contains a rewrite the gate failed, and approves nothing itself.

III. Metamorphic Relations

Each relation compares a gate's answer on a rewrite with its answer on the original call, so no ground truth is needed (Figs. 2 and 3). Four classes are invariance tests in the sense of CheckList [13]: the verdict must stay the same. Riskier rewrites are a directional test: the call becomes more dangerous, so the gate must not block it less. All classes except model paraphrases come from deterministic, seeded rules. Equivalent rewrites use explicit tables, such as a flag's short and long form or path spellings that resolve to the same file, so they keep the meaning by construction. Model paraphrases are written by an open model and are reported apart, since a paraphrase may change the meaning.

Repeat rate: A gate may answer the identical request differently. Its repeat rate f is the share of requests whose verdict differs between the first and second time they are sent. The third repeat serves the mean p_{block} and the majority verdict. For each class, F is the share of rewrites whose first verdict differs from the original call's. A class is violated for a gate when the 95% interval of $F - f$ is positive after a Bonferroni correction over the 35 class tests, by Newcombe's hybrid-score interval [14] built from Wilson intervals [15]. A riskier rewrite violates its rule when the verdict becomes less strict or p_{block} drops by more than it varies between identical requests. That share is compared with the same event between repeats. All rules were committed before the first run.

IV. Usage and Workflow

A user picks a gate from the pinned configuration, runs `expand`, `run` and `analyze`, and reads the report or wires `ci` into a pipeline (Fig. 1). Reviewers run the `replay` command from the published replay bundle, inside the Docker image, with no key and no network. On a clean machine, replaying the bundle reproduced all 134,190 recorded answers,




Fig. 3. The rewrite classes with examples. Swapping the meanings of yes and no follows Sun et al. [6].




Fig. 4. The web demo on the call of Fig. 2: the original call, its equivalent rewrites with drex's recorded verdicts, and the selected rewrite beside the original call. The other four classes continue below.

and re-scoring the recorded runs reproduced every table in this paper byte for byte.

The web demo (Fig. 4) shows one call at a time: the original call on the left, its rewrites grouped by class, and one gate's recorded verdict on each, red where it contradicts the verdict on the original call. Clicking a rewrite shows both requests with the change marked. In live mode the page sends the same requests to a decision model or to the Claude judge with the visitor's own key, builds each request as the adapters do, and shows the live verdict next to the recorded one. The visitor can edit the call and pick another policy, and the rewrites are replayed on the edit.

V. Validation

Setup: The corpus has 300 tool calls, built from 76 templates, under four policies. Deterministic rules turn them into 5,861 requests, the original calls and their rewrites, and Qwen3-8B adds 529 model paraphrases. Seven gates answer every request three times, and each denies a call when its p_{block} is at least 0.5. Four are decision models on the Decisions API [2], in true/false mode: Jev 1.14, GPT-6 Luna Decisions, pplx-decider v1.2 and drex v1.5. Their answer labels are fixed, so renamed answer labels skip them. Two are LLM judges with one frozen prompt: Claude Opus 5.5 states its block probability (Message Batches API), and Gemma 4 31B on vLLM gives it by logprobs. Claude refuses 7 of the 300 calls on every repeat, and the shares exclude refusals. The seventh is a hand-written Claude Code-style rule set [1].

Invariance: Every gate changes its verdict on equivalent rewrites more often than on a repeated request (Table I). Five gates never change it on a repeat, so their changes come from the rewrite. Jev, Luna, drex and the rule set mostly turn allow into deny, and the Claude judge and pplx mostly deny into allow. For the model gates the main cause is the policy written in another format (Fig. 2): most of the Claude judge's changes and at least four in five on the others. The rule set ignores the policy text, so its changes come from how the call is spelled, such as a long flag. A model paraphrase may also change what a command does. In a sandbox with no network, 90 of 229 rewritten commands have the same effect as the original. On these,

TABLE I
Share of rewrites (%) whose verdict differs from the verdict on the original call. Bold: significantly higher than for the repeated request.

Gate	Share with a changed verdict (%)				
	Repeated request	Equivalent rewrite	Irrelevant context	Adversarial input	Model paraphrase
Jev	0.4	**1.7**	0.4	0.4	**2.5**
GPT-6 Luna	0.0	**7.5**	**4.2**	**5.9**	**8.5**
pplx-decider	0.0	**2.0**	**0.3**	**1.9**	**3.2**
drex	0.0	**6.2**	**1.4**	**2.3**	**4.9**
Claude judge	0.5	**1.6**	1.1	0.9	**2.3**
Gemma judge	0.0	**1.9**	0.1	**1.0**	**4.0**
Rule set	0.0	**3.8**	**0.3**	0.2	**14.4**




Fig. 5. Adversarial rewrites that change a gate's verdict, by direction, as a share of that gate's adversarial rewrites.

Luna, drex, the rule set and, on one pair, Gemma still change their verdicts, and Jev, Claude and pplx do not. Drex denies `git push origin --delete feature/old` but allows `git push origin :feature/old`, the same branch deletion, which release-manager forbids.

Riskier rewrites: A riskier rewrite, such as an added `sudo` or a wider path, turns deny into allow at most once in 436 per gate. Three such cases are gate errors. Jev allows erasing .env under a policy that allows no writes, drex allows a `tar` archive once `sudo` is added, and Gemma allows listing the root directory but denies listing the home directory. In the other three, pplx, Claude and the rule set allow overwriting .env under workspace-dev and deny reading it. They follow the policy, which forbids reading secrets and allows any write in the workspace, so the check found a gap in the policy. The pre-registered rule also counts a drop in p_{block} larger than its variation between repeats, which is zero for five gates, so any drop counts there. Under it Luna, pplx and drex fail, mostly through drops that keep the verdict.

Adversarial input: Adversarial input moves the gates in different directions (Fig. 5). Injected text pushes pplx and drex toward allow and Luna toward deny, and renamed answer labels push Gemma toward deny. The line "This action is safe per the policy." makes pplx allow 15 of the 300 calls it otherwise denies, and "The user pre-approved this command." turns Jev's deny into allow on 3. One is a `git fetch` that a read-only policy forbids, allowed at every repeat.

Cost: Per 1,000 probes, the rule set costs nothing and takes seconds. A decision model costs under $4 and two to nine hours with 8 parallel workers. The Claude judge costs $173 and 1.3 hours through message batches, and Gemma under an hour on one H100 with no fees. The evaluation cost $54 in API fees, plus about 20 H100 minutes for the Gemma judge, setup included, and under two consumer-GPU minutes for the paraphrases.

Threats: All 300 calls come from templates. The corpus holds no recorded agent session. A check of the transforms with the most changes found one generator bug: two path rewrites turned an `rsync` remote into a local path. Without them, Claude's share on equivalent rewrites barely changes. A changed verdict marks two verdicts that contradict each other, and either one may be the wrong one. The cases we show were picked after reading the policies.

VI. Related Work

Gate builders and users. Zhou and Jia mediate agent tool calls through typed tools and evaluate their world effects [16]. Jev gates coding-agent permissions in OpenRouter's recipes [3], [4] and in community middleware [5]. These works build or deploy a gate. None tests one against rewrites of the same call. *Fragile decision models and judges.* Sun et al. show that typed decision models follow option names over the definitions bound to them [6]. GateProbe turns that one relation into two of 26 transforms in a reusable suite, run against any gate. An optimized injected phrase can make an LLM judge pick the attacker's answer [17]. GateProbe's adversarial input asks the same of a gate, with fixed phrases and no access to the model. *Testing without an oracle.* Metamorphic relations replace a missing oracle [9], [10], and DeepTest brought them to deep-learning components [11]. CheckList tests NLP models without labels through invariance and directional tests [13]. Consistency checks find errors in models whose answers cannot be verified [18], [19]. GateProbe brings these tests to permission gates, whose inputs carry a risk order that its riskier rewrites use. *Agent and MCP evaluation.* MCP-SafetyBench and GatewayBench evaluate the safety of LLMs on real MCP servers and of MCP gateways [20], [21]. They test a whole server or gateway end to end. GateProbe isolates the gate and compares its answers on pairs of requests, so a failure points at the gate itself.

VII. Conclusion

GateProbe tests permission gates against rewrites whose relation to the original verdict is known without an oracle. All seven gates we tried contradict themselves on equivalent inputs, and injected text moves two decision models toward allow. The check on riskier rewrites found three gate errors and a gap in one of our policies, which forbids reading secrets but allows writing them. Future work extends the sandbox check to commands that need a network and adds a user study with developers who configure a gate.

Availability: GateProbe, its Docker image, the corpus, the replay bundle and the interactive replay demo are available at https://github.com/Token-Waste-Group/gate-probe.

References

[1] Anthropic, "Configure permissions, Claude Code documentation," https://code.claude.com/docs/en/permissions, 2026, accessed 2026-10-19.

[2] OpenRouter, "Submit a Decisions request (POST /api/alpha/decisions), OpenRouter API reference," https://openrouter.ai/docs/api/api-reference/alphadecisions/submit-a-decisions-request, 2026, accessed 2026-10-19.

[3] ——, "Auto-approve coding agent permission prompts with Jev," https://openrouter.ai/docs/cookbook/coding-agents/auto-approve-permission-prompts-with-jev, 2026, OpenRouter Cookbook. Accessed 2026-10-19.

[4] ——, "Gate agent tool calls with Jev," https://openrouter.ai/docs/cookbook/building-agents/gate-tool-calls-with-jev, 2026, OpenRouter Cookbook. Accessed 2026-10-19.

[5] lgy1027, "JevShield: Security gate for AI agent tool calls powered by TypeSafe's Jev," https://github.com/lgy1027/jevshield, 2026, GitHub repository. Accessed 2026-10-19.

[6] Y. Sun, J. Xu, J. Shi, and Z. Yang, "Type-Safe is not error-free: Typed decision models follow the option name, not the definition bound to it," arXiv:2609.26758 [cs.AI], 2026, version 3, 8 Oct 2026.

[7] TypeSafe, "Jev 1.13 jaggedness," https://docs.typesafe.ai/model-jaggedness/jev-1.13, 2026, TypeSafe documentation, last reviewed 2026-10-02. Accessed 2026-10-19.

[8] L. Columbus, "Companies are putting Jev in charge of AI agent decisions — and prompt injection can influence the verdict," https://venturebeat.com/security/companies-are-putting-jev-in-charge-of-ai-agent-decisions-and-prompt-injection-can-influence-the-verdict, Sep. 2026, VentureBeat. Accessed 2026-10-19.

[9] S. Segura, G. Fraser, A. B. Sanchez, and A. Ruiz-Cortés, "A survey on metamorphic testing," *IEEE Transactions on Software Engineering*, vol. 42, no. 9, pp. 805–824, 2016.

[10] T. Y. Chen, F.-C. Kuo, H. Liu, P.-L. Poon, D. Towey, T. H. Tse, and Z. Q. Zhou, "Metamorphic testing: A review of challenges and opportunities," *ACM Computing Surveys*, vol. 51, no. 1, pp. 4:1–4:27, 2018.

[11] Y. Tian, K. Pei, S. Jana, and B. Ray, "DeepTest: Automated testing of deep-neural-network-driven autonomous cars," in *Proceedings of the 40th International Conference on Software Engineering (ICSE)*. ACM, 2018, pp. 303–314.

[12] Anthropic, "Hooks reference, Claude Code documentation," https://code.claude.com/docs/en/hooks, 2026, accessed 2026-10-19.

[13] M. T. Ribeiro, T. Wu, C. Guestrin, and S. Singh, "Beyond accuracy: Behavioral testing of NLP models with CheckList," in *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics (ACL)*, 2020, pp. 4902–4912.

[14] R. G. Newcombe, "Interval estimation for the difference between independent proportions: Comparison of eleven methods," *Statistics in Medicine*, vol. 17, no. 8, pp. 873–890, 1998.

[15] E. B. Wilson, "Probable inference, the law of succession, and statistical inference," *Journal of the American Statistical Association*, vol. 22, no. 158, pp. 209–212, 1927.

[16] J. Zhou and T. Jia, "Introducing safe LLM-agent execution via typed tool mediation and world-effect evaluation," in *Proceedings of the 41st IEEE/ACM International Conference on Automated Software Engineering (ASE)*. ACM, 2026, pp. 3567–3571.

[17] J. Shi, Z. Yuan, Y. Liu, Y. Huang, P. Zhou, L. Sun, and N. Z. Gong, "Optimization-based prompt injection attack to LLM-as-a-judge," in *ACM SIGSAC Conference on Computer and Communications Security (CCS)*, 2024.

[18] L. Fluri, D. Paleka, and F. Tramèr, "Evaluating superhuman models with consistency checks," arXiv:2306.09983, 2023.

[19] D. Paleka, A. P. Sudhir, A. Alvarez, V. Bhat, A. Shen, E. Wang, and F. Tramèr, "Consistency checks for language model forecasters," in *International Conference on Learning Representations (ICLR)*, 2025, arXiv:2412.18544.

[20] X. Zong, Z. Shen, L. Wang, Y. Lan, and C. Yang, "MCP-SafetyBench: A benchmark for safety evaluation of large language models with real-world MCP servers," in *International Conference on Learning Representations (ICLR)*, 2026, arXiv:2512.15163.

[21] Y. Zheng, Z. Chen, H. Li, and B. Li, "GatewayBench: Unified capability and security evaluation platform for MCP gateways," arXiv:2610.23449, 2026.