

Mint/Burn Flow Changelog

Full version history of Mint/Burn Flow methodology decisions, from v1.0 to v6.11.

ump to Version

- Latest
- v6.11
- v6.1
- v6.0
- v5.2
- v5.1
- v5.0
- v4.9
- v4.8
- v4.7
- v4.6
- v4.5
- v4.4

LATEST VERSION

v6.11

May 12, 2026

yBOLD extended transfer coverage

Yearn BOLD (yBOLD) now has extended Ethereum mint/burn tracking through standard ERC-20 zero-address Transfer events.

IMPACT SNAPSHOT

• Adds yBOLD to the extended mint/burn config registry using the shared Ethereum contract metadata

• Tracks yBOLD share issuance and redemption separately from base BOLD's mint/burn flow so wrapper activity does not disappear into the parent asset

• Keeps bridge detection unchanged because the tracked yBOLD deployment is the single Ethereum vault share token

v6.11

May 12, 2026

yBOLD extended transfer coverage

Yearn BOLD (yBOLD) now has extended Ethereum mint/burn tracking through standard ERC-20 zero-address Transfer events.

• Adds yBOLD to the extended mint/burn config registry using the shared Ethereum contract metadata

• Tracks yBOLD share issuance and redemption separately from base BOLD's mint/burn flow so wrapper activity does not disappear into the parent asset

urn:pharos:methodology:mint-burn-flow@v6.11

<https://pharos.watch/methodology/mint-burn-flow-changelog/>

1 / 9

- Keeps bridge detection unchanged because the tracked yBOLD deployment is the single Ethereum vault share token

Hide details

IMPACT NOTES

- Adds yBOLD to the extended mint/burn config registry using the shared Ethereum contract metadata
- Tracks yBOLD share issuance and redemption separately from base BOLD's mint/burn flow so wrapper activity does not disappear into the parent asset
- Keeps bridge detection unchanged because the tracked yBOLD deployment is the single Ethereum vault share token

Commit provenance not recorded

v6.1

May 8, 2026

USG extended transfer coverage

Tangent USD (USG) now has extended Ethereum mint/burn tracking from its reviewed deployment block using standard ERC-20 zero-address Transfer events.

- Adds USG to the extended mint/burn config registry with a reviewed deployment-block start bound
- Captures the initial 40.02M USG zero-address mint history plus future USG supply changes through the standard Transfer decoder
- Keeps bridge and custom-event handling unchanged; no USG bridge classifier is configured because only the Ethereum token contract is currently tracked

Details

v6.0

Apr 17, 2026

Bridge classifier parity, LayerZero endpoint-only signal, canonical-chain gauge weighting

Bridge classification now tags both mint and burn rows for CCIP/CCTP transactions, the LayerZero classifier recognizes endpoint-only fingerprints, and the Bank Run Gauge weights coins by their tracked-

chain circulating supply rather than global supply. Atomic-roundtrip detection now requires mint/burn totals to match within 0.5%, and custom-event counterparty extraction supports unindexed address parameters.

- CCIP and CCTP bridge mints now tag as `flow\_type="bridge\_transfer"` (previously leaked into economic mint flow for USDC, EURC, USDO, USD1, avUSD, ZCHF)
- Bank Run Gauge weights each coin's intensity by its circulating supply on tracked-chain scope only (e.g., USDC weighted by Ethereum supply, not global \$36B+ total)
- LayerZero classifier accepts endpoint-emitter signal alone, catching Executor-only mint patterns previously missed on USDai-Arbitrum
- Atomic-roundtrip detection requires sum(mint) and sum(burn) to match within 0.5% — partial same-tx mix is preserved as economic flow rather than erased

Details

v5.2

Apr 14, 2026

GYD retirement from active mint/burn coverage

GYD was removed from active mint/burn flow tracking after its cross-chain contract incident left the token functionally dead and moved it to the cemetery dataset.

- Mint/burn flow configs no longer scan the Ethereum GYD token after the asset moved out of the active stablecoin registry
- Public flow coverage counts and stablecoin registry totals now exclude GYD from active surfaces
- Historical rows remain in D1 if previously ingested, but current API scope is driven by the active config registry

Details

v5.1

Apr 8, 2026

Canonical-chain mint/burn scope for native issuance tracking

Mint/burn coverage now follows each asset's configured issuance chain instead of assuming Ethereum-only scope, with USDai switched to native Arbitrum issuance/redemption tracking and stale non-canonical rows excluded from public aggregates.

- USDai mint/burn tracking now runs on Arbitrum as the canonical native issuance chain instead of Ethereum bridge-transfer noise
- Aggregate and per-coin APIs now read only configured `(stablecoinId, chainId)` pairs so stale historical rows on non-canonical chains do not contaminate public flow metrics
- Cron metadata, coverage helpers, status reconciliation, daily digest, and DEWS mint/burn inputs now honor chain-aware mint/burn scope
- Admin backfill auto-selection and explicit config replay now work across the configured issuance-chain set instead of Ethereum-only

Details

v5.0

Apr 8, 2026

Bridge-transfer flow exclusion for omnichain tokens

Bridge-aware classification now excludes bridge-transfer mints as well as burns, starting with USDai's LayerZero OFT path, and replay/backfill runs can repair previously inserted rows.

- LayerZero OFT transfers now mark both the mint-side and burn-side event rows as ``flowType='bridge_transfer'`` so they drop out of counted economic-flow aggregates
- Bridge classification now runs after all parsed rows are assembled for the config chunk, so mint-side bridge rows are visible to the classifier
- USDai's Ethereum tracker now recognizes the documented USDai OAdapter / LayerZero packet flow instead of treating equal-sized bridge mints and burns as issuance activity
- Replay and backfill persistence now updates ``flow_type`` on existing rows, allowing post-deploy repair of previously ingested bridge-transfer noise

Details

v4.9

Mar 24, 2026

Deterministic repair loops and adapter provenance disclosures

Mint/burn repair and coverage semantics were tightened through historical-first valuation repair, deterministic cleanup backlogs, aligned FTQ classification, and explicit adapter provenance on public coverage metadata.

- Historical price repair now values events from event-day ``supply_history`` instead of current ``price_cache`` snapshots
- The daily digest now shares the same report-card-cache FTQ classification semantics as ``/api/mint-burn-flows``
- NULL-price healing and atomic-roundtrip sweeping now use deterministic ordered backlog queries
- Per-coin coverage now exposes ``adapterKinds``, ``startBlockSource``, and ``startBlockConfidence`` so blanket start-block defaults are visible in the API

Details

v4.8

Mar 24, 2026

Ethereum coverage wave for long-tail mint/burn tracking

Mint/burn flow coverage expanded materially by restoring and adding long-tail Ethereum ERC-20 configs that can be tracked with the standard zero-address Transfer path.

- Added 40 additional Ethereum transfer-based configs for previously uncovered tracked assets
- Extended flow coverage now includes more long-tail fiat, non-USD, commodity, and yield-bearing

assets where shared metadata already exposes an Ethereum contract

- Coverage scope increased from 84 contract configs / 83 stablecoin IDs to 124 contract configs / 123 stablecoin IDs while preserving the existing critical-lane set

Details

v4.7

Mar 10, 2026

Closed-day baseline, fixed aggregate 24h semantics, and coverage disclosures

Pressure Shift now compares live 24-hour flows against trailing fully closed daily baselines, aggregate API 24h fields are fixed regardless of chart window, and the product now exposes Ethereum-only scope plus coverage/freshness metadata.

- Pressure Shift baseline now excludes the current UTC day and uses the last 30 fully closed daily buckets
- Aggregate `/api/mint-burn-flows?hours=N`` now keeps coin-level 24h fields fixed to the canonical 24h window while only the hourly series respects ``hours``
- Aggregate flow API now exposes ``scope``, ``sync``, ``windowHours``, and per-coin ``coverage`` metadata
- The `/flows`` page now labels the feature as Ethereum-only and visually marks partial-history or lagging coverage states

Details

v4.6

Mar 9, 2026

Safe-frontier ingestion and counted event-history alignment

Mint/burn ingestion now advances only to a shared safe coverage frontier under partial scans, and product event-history surfaces now default to counted economic-flow rows.

- Partial event-definition coverage no longer advances sync state past uncovered log ranges
- Missing block timestamps now cap advancement at the earliest unresolved block instead of silently skipping rows forever
- The event API now exposes ``flowType`` and supports ``scope=counted`` for rows that participate in aggregates
- Detail-page flow history now excludes bridge burns, review-required burns, and atomic roundtrips by default

Details

v4.5

Mar 9, 2026

Data quality: noise filtering, auto-heal, and activity gating

Improves flow data reliability by excluding flash-loan roundtrips from aggregation, auto-healing missing USD prices, and gating pressure shift for low-activity coins.

- Transactions containing both mint and burn for the same token (flash loans, atomic arb) are now flagged as `atomic_roundtrip` and excluded from all flow aggregates
- Coins with less than \$50K absolute 24h flow now return NR instead of a potentially misleading pressure shift score
- Events synced without USD price are now automatically backfilled within 48h by the syncron
- New observability counters in cron metadata: `atomicRoundtripsDetected`, `nullPricesHealed`

Details

v4.4

Mar 7, 2026

Reconstructed

Two-signal flow semantics and baseline-aware interpretation

Per-coin flow UI now separates raw 24h net flow from baseline-relative pressure shift while preserving the underlying formula.

- Per-coin flow UI now separates raw 24h net flow from baseline-relative pressure shift
- Frontend printer and shredder visuals now key off actual net flow direction instead of score sign
- API now exposes canonical ``pressureShiftScore`` and interpretation fields while retaining ``flowIntensity`` as a deprecated alias
- Methodology and product copy now distinguish current direction from pressure-versus-baseline context

Details

v4.3

Mar 4, 2026

Reconstructed

NR gating for no-activity flow windows

Coins with no mint/burn activity in the active 24h window now publish NR flow intensity and are excluded from gauge weighting.

- Removed synthetic neutral intensity fallback for sparse no-activity windows
- Bank Run Gauge now excludes those NR windows from the market-cap-weighted composite
- No-activity windows now return ``flowIntensity = null`` (NR) instead of ``0``
- Frontend flow-intensity UI now displays NR explicitly for null values

Details

v4.2

Mar 4, 2026

Reconstructed

Signed zero-baseline flow-intensity semantics

Flow Intensity Score and Bank Run Gauge moved from midpoint semantics to canonical signed outputs centered at zero baseline.

- Flow Intensity Score now emits signed values via ``clamp(-100, 100, z * 50)``
- Band thresholds were remapped around zero while retaining existing band labels
- Gauge score now uses signed -100 to +100 output with neutral baseline at 0
- Frontend midpoint conversion shim was removed; UI now consumes canonical signed API values directly

[Details](#)

v4.1

Mar 4, 2026

Reconstructed

Reliability remediation and controlled backfill recovery

Ingestion moved to a reliability-first runtime policy with degraded/error health signaling and operator-grade recovery controls.

- Added run-state rotation plus per-chain quotas so coverage remains balanced under budget pressure
- Introduced authenticated chunked backfill endpoint (``/api/backfill-mint-burn``) reusing ingestion parsing and aggregation
- Added degraded/error escalation from sustained low coverage or repeated API failures

[Details](#)

v4.0

Mar 4, 2026

Reconstructed

reUSD deposit amount scale correction

Fixed a scale mismatch in reUSD mint decoding that overstated deposit-side mint volume.

- reUSD ``Deposited`` events now decode with 18 decimals instead of 6
- Added regression test validating a known on-chain ``Deposited`` payload decodes to 10 tokens
- Removed artificial inflation in reUSD mint flow and related aggregates

[Details](#)

v3.2

Mar 3, 2026

Reconstructed

Event-time USD valuation for flow amounts

Flow USD amounts moved from run-time spot pricing to event-time historical price attribution when available.

- Event valuation now prefers daily historical prices from ``supply_history`` at event day
- Price provenance persisted per event (``price_used``, ``price_timestamp``, ``price_source``)
- Row-drop accounting added for malformed/dust logs to improve data quality observability

Details

v3.1

Mar 3, 2026

Reconstructed

Alchemy migration and chain-aware scan controls

Mint/burn ingestion migrated to Alchemy JSON-RPC with chain-specific scan behavior and stronger timestamp resolution guarantees.

- Replaced Etherscan log ingestion with Alchemy ``eth_getLogs``
- Block timestamps now resolved in batch via ``eth_getBlockByNumber``, with retry-on-missing semantics
- Scan ranges and safety margins calibrated per chain (including Optimism support)

Details

v3.0

Mar 2, 2026

Reconstructed

reUSD multi-chain coverage and per-coin dedup correction

Coverage expanded to Re Protocol reUSD across four chains, then corrected aggregate dedup logic to avoid multi-contract over-weighting.

- Added reUSD mint and redemption event tracking on Ethereum, Arbitrum, Base, and Avalanche
- Added nth-data-slot amount decoding for non-standard event payload layouts
- Aggregate flow loop now deduplicates by stablecoin ID to prevent duplicated rows and weighted overcounts

Details

v2.1

Mar 1, 2026

Reconstructed

Grade-aware flight-to-quality classification

Flight-to-quality shifted from static safe-haven lists to report-card score buckets, with fallback only when grade data is stale or missing.

- Safe/risky FTQ buckets now derive from report-card scores (safe ≥ 65 , risky < 50 , neutral ignored)
- Largest-event attribution aligned to requested window semantics in aggregate mode
- Static safe-haven sets are now fallback-only for unavailable or stale report-card cache

Details

v2.0

Mar 1, 2026

Reconstructed

USDT treasury-event capture and partial-data gauge support

Coverage and scoring robustness were upgraded to capture USDT treasury mint/burn events and keep the gauge active during early-history ramp.

- Added `startBlock` per config for near-history initialization instead of scanning from genesis
- USDT now tracks `Issue` and `Redeem` events that do not emit standard `Transfer` mints/burns
- Gauge now computes from available non-null FIS inputs instead of returning null when any coin lacks sufficient history

Details

v1.0

Mar 1, 2026

Reconstructed

Initial Mint/Burn Flow release

Launched baseline mint/burn flow tracking, scoring primitives, and public API surfaces for aggregate and per-coin analysis.

- Introduced phase-1 contract coverage for 10 tracked stablecoins
- Shipped FIS formula, seven-band Bank Run Gauge mapping, and flight-to-quality detection thresholds
- Deployed incremental sync cron with `/api/mint-burn-flows` and `/api/mint-burn-events`

Details

WHITE PAPER [Download Mint/Burn Flow Changelog v6.11 \(PDF\)](#)