




TE/TF series

Single needle, Cylinder bed, Oscillating shuttle hook, Drop feed, Lockstitch machines





Variety



TE-6 Lower feed TE-6B

Lower feed, reverse stitch



TF series (Left side pulley)

TF-6
Lower feed
TF-6B
Lower feed, reverse stitch

Applications

For sewing light to medium heavy weight materials such as leather, vinyl, bags, pouches, various sports equipments and other curved work.

Features

Standard is narrow toe presser foot and roller foot is supplied as accessories. (TE series)

This is a convenient type machine that the left hand of the operator is usable in sewing operation, due to the feature of lefthand cylinder bed. (TF series)

Standard foot is roller foot and narrow toe presser foot is supplied as accessories.

Long beak oscillating shuttle hook

Cam take-up


Cylinder bed

Reverse stitch (TE-6B & TF-6B)

TE/TF series

Suitable for sewing of high-class products, due to the feature of the oscillating hook, which ensures perfect seam tightness.







Long beak oscillating shuttle hook

Cloth plate for flat work available at extra charge (Part no. 8136C)





Specifications (TE- /TF-)

Variety		TE-6	TE-6B	TF-6	TF-6B
Number of needle		Single needle			
Max. sewing speed		1,400(s.p.m.)			
Max. stitch length		15/64" (6 mm)	13/64" (5 mm)	13/64" (5 mm)	5/32" (4 mm)
Clearance under presser foot	by knee	25/64" (10 mm)			
	by hand	9/32" (7mm)			
Needle bar stroke		1-27/64" (36 mm)			
Needle(standard)		DB × 1 (#19)		TF × 2 (#11)	
		16 × 231 (#120)		34LL (#75)	
Thread		#20 (standard)		#40 (standard)	
Hook		Long beak oscillating shuttle hook			
Presser foot	standard	Narrow toe		Roller	
	Accessories	Roller		Narrow toe	
Thread take up lever		Cam type			
Lubrication		Hand type			
Cylinder size		2-27/64" (61.5 mm) dia.		2-1/2" (63.5 mm) dia.	
Working space		11-1/32"x 5-5/16" (280 x 135 mm)		11-1/32"x 5-33/64" (280 x 140 mm)	
Motor		Clutch motor			
Net weight(Head only)		18Kg		21Kg	

NOTE

- (1) Speed depends on threads, materials and type of operation $% \left\{ 1,2,...,n\right\}$
- (2) Specifications subject to change without notice



SEIKO SEWING MACHINE CO., LTD.

2-13-6, Sakaecho, Funabashi-shi Chiba Prefecture, 273-0018, Japan Phone: +81-47-420-3561 (Overseas dept.)

Fax: +81-47-420-3560

E-mail: export@seiko-sewing.co.jp

http://www.seiko-sewing.co.jp/